Learning Sequential Acquisition Policies for Robot-Assisted Feeding

Abstract: A robot providing mealtime assistance must perform specialized maneuvers with various utensils in order to pick up and feed a range of food items. Beyond these dexterous low-level skills, an assistive robot must also plan these strategies in sequence over a long horizon to clear a plate and complete a meal. Previous methods in robot-assisted feeding introduce highly specialized primitives for food handling without a means to compose them together. Meanwhile, existing approaches to long-horizon manipulation lack the flexibility to embed highly specialized primitives into their frameworks. We propose Visual Action Planning OveR Sequences (**VAPORS**), a framework for long-horizon food acquisition. **VAPORS** learns a policy for high-level action selection by leveraging learned latent plate dynamics in simulation. To carry out sequential plans in the real world, **VAPORS** delegates action execution to visually parameterized primitives. We validate our approach on complex real-world acquisition trials involving noodle acquisition and bimanual scooping of jelly beans. Across 38 plates, **VAPORS** acquires much more efficiently than baselines, generalizes across realistic plate variations such as toppings and sauces, and qualitatively appeals to user feeding preferences in a survey conducted across 49 individuals. Code, datasets, videos, and supplementary materials can be found on our website.

Keywords: Deformable Manipulation, Dexterous Manipulation

1 Introduction

Millions of people are impacted logistically, socially, and physically by the inability to eat independently due to upper mobility impairments, age or health-related changes, or simply the toll of meal preparation [1, 2, 3]. Robot-assisted feeding has the potential to greatly improve the quality of life for these individuals while reducing caregiver burden. However, realizing a performant system in practice remains challenging. For instance, humans eat spaghetti noodles as shown in Fig. 1 using nuanced fork-twirling motions. Other dishes, such as ramen, require even more diverse strategies—scooping soup, acquiring noodles, or acquiring meat. Thus, not only must an autonomous feeding system employ various utensils and strategies to handle different foods and quantities, but it must also operate over long horizons to finish a meal.

Prior assistive feeding work has focused on learning individual low-level vision-parameterized primitives for food manipulation. Examples include separate policies for skewering [4, 5, 6], scooping [7], bite transfer [8, 9, 10], cutting [11, 12, 13], and pushing food piles [14]. While highly specialized, these policies cannot reason over an extended horizon or make use of multiple strategies for more effective plate clearance. Humans, on the other hand, interleave *acquisition* and *rearrangement* actions with ease—pushing multiple peas together before scooping instead of painstakingly acquiring each individual pea or gathering noodles closer to each other before twirling with a fork. Replicating this long-horizon foresight in robotic feeding has yet to be demonstrated.

Recent work in skill-based reinforcement learning (RL) provides a natural way to model long-horizon manipulation sequences hierarchically. This entails first learning a high-level policy for

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: **Visual Action Planning OveR Sequences (VAPORS)** employs a high level policy π_H to select amongst discrete manipulation strategies h, such as grouping and twirling, and a low-level vision-parameterized policy π_L to execute these actions a_t for long-horizon dexterous food acquisition.

composing skills [15, 16, 17], and then optionally inferring the parameters of low-level skills separately [18, 19, 20]. These approaches tend to favor learning from simulation to scale data collection [21], but current state-of-the-art simulators lack high-fidelity models for food deformation, visuals, and cutlery interaction. This complicates learning food manipulation policies in simulation and transferring them to the real world [13]. Existing hierarchical approaches also assume that the low-level skills come from a general-purpose library of primitives such as grasping and path planning [19, 22, 18, 15, 23], limiting their applicability to the food domain which requires highly specialized behaviors. Thus, we seek to find an appropriate layer of abstraction for feeding, which can leverage the benefits of (1) hierarchical planning for long-horizon manipulation and (2) vision-based primitives for fine-grained control. Our key insight is that learning from simulated experience only at a *high-level*, which need not capture the intricacies of food dynamics, and incorporating visual planning to instantiate *low-level* specialized primitives, yields a powerful approach to dexterous, multi-step food manipulation.

In this work, we present **VAPORS**: Visual Action Planning OveR Sequences, a unified framework for food manipulation. Our approach is decoupled into a high-level planner, which sequentially composes low-level primitives. We first learn a policy in simulation that models latent dynamics of plates from images. Specifically, we use segmented image observations as a representation space, which captures the distribution of food items and is transferable between simulation and reality for high-level plans. We train the policy using model-based RL with a reward that encourages both acquisition and rearrangement. Separately, we instantiate a library of specialized primitives in the real world from learned food pose estimation and segmentation. Finally, we use the learned high-level planner on segmented real food images to plan sequences of primitives for long-horizon acquisition.

We experimentally validate our approach on two real food manipulation tasks: robotic noodle acquisition and bimanual scooping. Across both real-world trials and a comprehensive user study of 49 users, **VAPORS** achieves the highest efficiency, plate clearance, and qualitative user ratings compared to heuristic and single-primitive baselines, all while generalizing to unseen plates.

2 Related Work

Robot-Assisted Feeding. Recently, a number of devices for mealtime assistance have become available on the market [24, 25], but are limited in functional reach due to reliance on pre-programmed trajectories or teleoperation by users. While *bite transfer* of a food item to a user's mouth is the eventual goal of autonomous feeding [9, 8, 10], we focus on *bite acquisition* as a primary initial step for downstream feeding. Prior work in bite acquisition demonstrates the effectiveness of visual planning for precise manipulation. Feng et al. [6], Gordon et al. [5, 26] and Sundaresan et al. [4] leverage bounding box localization, food pose estimation, and visual servoing to geometrically plan precise fork skewering motions. Similarly, Grannen et al. [7] and Suh and Tedrake [14] plan bimanual scooping and grouping actions, respectively, for segmented food piles. These works focus only on developing a specialized individual primitive for food manipulation. In isolation, this does not capture many long-horizon real-world feeding scenarios with multiple utensils and strategies.

Long-Horizon Planning and Control. Several recent frameworks tackle long-horizon manipulation by separating motion-level decision-making from sequential plans. Traditionally, task-and-motion-

planning (TAMP) approaches tend to assume extensive domain knowledge including after-effects of actions and fixed task plans [27, 28, 29, 30, 31, 28]. In feeding, plate dynamics can be highly uncertain, and state estimation is notoriously challenging, rendering these approaches ineffective. An alternative approach is model-based planning and control, with recent impressive results on complex tasks like dough manipulation [16, 32, 33]. This family of methods leverage learned environment dynamics over visual states like images [34, 35, 36, 37, 33], keypoints [38], or particle-based representations [16, 32] to sample and plan action sequences that maximize predicted rewards. However, these methods do not scale well to high-dimensional continuous action spaces such as that of food acquisition. To address this, hierarchical RL decouples policies into a high-level planner which selects amongst discrete but parameterized low-level primitives [39]. These works have demonstrated promising results on simulated long-horizon tabletop manipulation [18, 19, 15], but have yet to consider (1) real-world deployment beyond carefully controlled experimental setups, or (2) complex manipulation beyond commonplace primitives like pick-place, path-planning, and grasping. In contrast, we consider highly diverse real plates requiring specialized primitives and tools.

Learning and Control for Manipulation in the Real World. A large body of robotics research focuses on learning real-world policies for manipulation either through sim-to-real transfer or exclusively from real interactions. With sufficient domain randomization, sim-to-real transfer has proven effective for tasks involving rigid objects or a limited set of deformable items like cloth, which state-of-the-art simulators support [40, 41, 42]. However, adapting these simulators to modeling food appearance and deformation is highly non-trivial. Meanwhile, learning exclusively from real data has been shown to work well in challenging domains such as semantic grasping [43] or cable untangling [44, 45, 46]. These approaches rely on state representations that are scalable to learn, such as descriptors learned from self-supervised interaction [43] or keypoints learned from a small amount of manually annotated images [47, 48, 49, 50]. In our setting, it is difficult to scale real-world data collection across the range of food shapes, appearances, and properties a robot may encounter. Self-supervised learning is also complicated due to resets and utensil interchange. We instead take a hybrid approach which takes advantage of simulation for modeling high-level plate dynamics from large-scale interactions, but leverages visual planning at the low level for precise real manipulation.

3 Problem Statement

We formalize the long-horizon food acquisition setting by considering an agent interacting in a finite-horizon Partially Observable Markov Decision Process (POMDP). This is defined by the tuple $(\mathcal{S}, \mathcal{O}, \mathcal{A}, \mathcal{T}, \mathcal{R}, T, \rho_0)$. We assume access to plate image observations $o_t \in \mathbb{R}_+^{W \times H \times C} = \mathcal{O}$ of unknown plate states $\mathcal{S}$, with the initial state distribution given by ρ_0. Here, W, H, and C denote the image dimensions. $\mathcal{A}$ denotes the action space, and $\mathcal{T} : \mathcal{S} \times \mathcal{A} \to \mathcal{S}$ represents the unknown transition function mapping states and actions to future states. The time horizon T denotes the discrete budget of actions to clear the plate and $\mathcal{R}(s, a)$ refers to the reward which measures progress towards plate clearance. Our goal is to learn a policy $\pi(a_t|o_t)$ that maximizes expected total return: $\mathbb{E}_{\pi, \rho_0, \mathcal{T}}[\sum_t R(s_t, a_t)]$, with $t \leq T$.

To do so, we decouple π into separate high and low-level sub-policies. We assume access to K discrete manipulation primitives h^k, $k \in \{1, \ldots, K\}$, and learn a high-level policy π_H which selects amongst these primitives. Additionally, we learn a low-level policy π_L which continuously parameterizes a selected primitive according to visual input. The components we aim to learn are summarized below, where h^k denotes a discrete primitive type and a_t denotes its continuous low-level instantiation:

$$\text{High-level policy} : \pi_H(h^k|o_{\leq t}, a_{\leq t-1}) \qquad \text{Low-level policy} : \pi_L(a_t|o_t, h^k)$$

We consider low-level actions a_t, parameterized by the position of the tip of a utensil (x, y, z) and utensil roll and pitch (γ, β). Here, $\beta = 0°$ corresponds to an untilted fork handle, for instance, and $\gamma = 180°$ corresponds to the fork tines being horizontal when viewed top-down (Fig. 2).

3.1 State-Action Representations

In this section, we outline the visual state and action representations which are at the core of our learning approach introduced in Section 4.

Visual State Space. Our approach makes use of RGB-D images and segmented plate observations, $I_t \in \mathbb{R}_+^{W \times H \times 3}$, $D_t \in \mathbb{R}_+^{W \times H}$, $M_t \in \mathbb{R}_+^{W \times H}$ at different levels of abstraction. We leverage binary segmentation masks to capture the spread of food items on a plate, informing high-level planning with π_H, and RGB-D observations as input to π_L which better capture fine geometric details of food.

Action Parameterization. We consider an agent that may either perform *acquisition* or *rearrangement* actions, parameterized below. Acquisition actions attempt to pick up a bite of food, and rearrangement actions consolidate items. For example, as a plate of noodles becomes more empty, the robot may need to employ a rearrangement action by pushing multiple strands together before twirling (acquiring) for a satisfactory bite size.

In *acquisition*, a robot with a utensil-mounted end-effector approaches the position (x_d, y_d, z_d) in the workspace, and executes an acquisition motion parameterized by roll γ and pitch β (i.e. twirling, skewering, scooping, etc.). Here, (x_d, y_d, z_d) denotes the *densest* location of the plate, where food is most closely packed to encourage a high-volume bite. Specifically, $a_{t,\text{acquis}} = (x_d, y_d, z_d, \gamma, \beta)$ (1).

Figure 2: **Action Parameterization:** We parameterize *acquisition* and *rearrangement* actions relative to the densest (x_d, y_d, z_d) and furthest (x_f, y_f, z_f) regions on the plate, as well as the utensil roll γ and pitch β.

The intent of *rearrangement* is to bring food items from the sparsest plate region to the densest by pushing from (x_f, y_f, z_f) ro (x_d, y_d, z_d), while maintaining contact with the plate throughout. As this is a planar push, we simply orient the tool orthogonal to the push direction, such that $\gamma = \arctan\left(\frac{y_f - y_d}{x_f - x_d}\right)$, and is untilted ($\beta = 0°$): $a_{t,\text{rearrange}} = (x_d, y_d, z_d, x_f, y_f, z_f)$ (2).

4 VAPORS: Visual Action Planning OveR Sequences

Within the visual state and action space outlined in Section 3.1, we present our approach **VAPORS** for tackling long-horizon food acquisition. First, **VAPORS** learns a policy π_H, detailed in Section 4.1, to select amongst high-level strategies for long-horizon plate clearance via model-based planning. Finally, **VAPORS** learns a low-level policy π_L, which leverages visually-parameterized primitives to carry out generated sequential plans for real-world food acquisition detailed in Section 4.2.

4.1 Learning High-Level Plans from Simulation

Our goal is to first learn a policy π_H for selecting amongst K discrete acquisition or rearrangement strategies without concern for the low-level action parameters. To do so, we learn a latent dynamics model of the plate from segmented image observations, and instantiate $\pi_H(h^k | M_{\leq t}, a_{\leq t-1})$, $k \in \{1, \dots, K\}$ with model-based planning over this learned dynamics model. In this section, τ denotes the running counter of high-level primitives executed so far, and t denotes the current timestep.

Simulator Overview. We train π_H entirely in simulation, where interactions can be collected at scale as opposed to the real world where manual plate resets and potential food waste are prohibitively expensive. As current simulators lack out-of-the-box support for many feeding scenarios, we develop a custom simulated food manipulation environment, visualized in Figure 3 in Blender 2.92 [40], further detailed in Appendix A.1. The simulator exposes RGB images I_t, binary food segmentation masks M_t, and food item positional states $s_t = \{(x_i, y_i, z_i)\}_{i \in (1, \dots, N)}$. Using this information, we design rewards for food acquisition in terms of ground truth plate state and collect transitions to train π_H.

Figure 3: **Simulation vs. Real:** We visualize the task of bimanual scooping of jelly beans. Due to the sim-to-real gap, we merely leverage simulation to learn high-level food dynamics, and leave low-level action planning to real vision-parameterized primitives.

Reward Design. With access to a simulated testbed for feeding, we train π_H to select amongst strategies via model-based reinforcement learning (RL). Our goal of efficient plate clearance can be specified with a reward that incentivizes either (1) successfully picking up food, or (2) reducing the spread of items on a plate. Optimizing for the first objective alone might lead to plate clearance, but at a slow pace of taking low-volume bites. The second objective encourages rearrangement when the plate is sparse to aid downstream acquisition. Concretely, we express this as a weighted reward with tunable weight $\alpha \in [0,1]$: $r_t = \alpha(\texttt{PICKUP GAIN}) + (1-\alpha)(\texttt{COVERAGE LOSS})$ (3). Here, PICKUP measures the quantity of food items picked up. COVERAGE measures the spread of items on the plate, illustrated in blue in Fig. 2). We provide the details for computing both in Appendix A.2.

Learning Latent Plate Dynamics. With a means of measuring task progress via r_t and access to plate observations M_t, we propose a model-based agent that learns plate dynamics from segmented observations and uses the learned model to plan actions that maximize reward. We achieve this by training a multi-headed latent dynamics model with the following (Fig. 4): (1) An *encoder* $q(z_t|M_{\leq t}, a_{\leq t-1})$ compressing high-dimensional segmented images M_t to compressed latent states z_t, (2) A *transition*

Figure 4: **Latent Plate Dynamics Model:** We learn a latent dynamics model of the plate comprised of an encoder q, transition model $p(z_\tau|z_{\tau-1}, h^k_{\tau-1})$, and a reward model $p(r_t|z_t)$. We use this model to select action sequences that maximize future rewards.

function over the latent states $p(z_\tau|z_{\tau-1}, h^k_{\tau-1})$ with which to imagine rollouts, and (3) A decoded *reward model* given by $p(r_t|z_t)$, such that at test time, we can sample action sequences and determine which maximize predicted rewards. We note that the transition function learns to predict high-level plate state changes between $\tau - 1$ and τ as a result of executing a primitive h^k_τ, rather than between individual timesteps $t - 1$ and t due to a_t.

During training, we collect simulated transitions consisting of the masked image, high-level primitive, low-level action, and reward $\{(M_t, h^k_\tau, a_t, r_r)\}$. We train each head of this network using the objectives detailed in Appendix B.1.

We note that this approach is highly related to [37] with several crucial design choices. First, we learn plate dynamics over *segmented* image observations M_t of food items on a plate, as opposed to raw RGB observations. This allows the dynamics model to attend to food items rather than the whole plate, provides an easily transferable representation between simulation and reality, and eases pressure for latent representations to capture irrelevant details in pixel space. Additionally, we learn a policy within an action space of discrete but continuously parameterized primitives as opposed to a high-dimensional space like joint-motor commands. This encourages actions that induce meaningful and perceptible plate changes likely to be encountered in downstream feeding.

Model-Based Planning. Once trained, we leverage the learned encoder, transition model, and reward model towards instantiating π_H as an MPC-style planner with a receding T-step horizon. At timestep t, we enumerate all K^T future candidate action sequences for the small library of primitives K. Conditioned on a history of observations $M_{1:t}$ and actions $a_{1:t-1}$, we imagine the future latent states $z_{\tau:\tau+T+1}$ under each action sequence $h^k_{\tau:\tau+T}$ via the transition function. Next, we predict decoded rewards according to the reward model $p(r_t|z_t)$ for each candidate sequence: $R = \sum_{i=\tau+1}^{\tau+T+1} \mathbb{E}[p(r_i|z_i)]$. Given the sequence of actions $(\hat{h}^k_\tau, \hat{h}^k_{\tau+1}, \ldots, \hat{h}^k_T)$ which maximizes predicted cumulative reward R, we take $\pi_H(M_{\leq t}, a_{\leq t-1}) = \hat{h}^k_\tau$, the first primitive in the predicted sequence. After executing this action, we replan with π_H, terminating when $\tau = T$. Details of the full planning pipeline, adapted from [37], are provided in Appendix B.2.

4.2 Visual Policies for Low-Level Real Manipulation

Our learned simulated task dynamics model from Section 4.1 relies on segmented images M_t as an observation space and parameterized primitives as an action space. In this section, we describe the visual state estimation pipelines we use to instantiate our state-action representations on real data.

(a) **Spaghetti**   (b) **Jelly Beans**

Figure 5: Across 10 trials for spaghetti (a) and jelly bean (b) acquisition, we visualize the cumulative amount acquired across individual trials (left) and averaged overall (right). Shading denotes the standard error.

Food Segmentation. To define acquisition and rearrangement actions relative to the poses of food, we learn to segment food items on a plate as shown in Fig. 1. We learn a binary segmentation model $f_{\text{seg}} : \mathbb{R}_+^{W \times H \times 3} \to \mathbb{R}_+^{W \times H}$, where for a real image $I_t \in \mathbb{R}_+^{W \times H \times 3}$, $f_{\text{seg}}(I_t)$ yields a binary segmentation mask $\hat{M}_t$ which serves as input to π_H. To train f_{seg}, we require a paired dataset of real plate images and ground truth segmentation masks. However, manually labeling pixel-level segmentation annotations on images is a painstaking and time-consuming process for real plates of food. Instead, we use a self-supervised annotation process which starts by taking an image of an empty plate, gradually adding food items to the plate, and using the absolute frame difference between the empty plate image and current observation to obtain the food segmentation mask. We implement f_{seg} as a fully convolutional FPN (Feature Pyramid Network) and train it according to the procedure detailed in Appendix B.3.

Food Orientation. Although segmentation provides a means to sense global *positional* information about food on the plate, we also care about precisely *orienting* a utensil with respect to the local geometry of a food item. For instance, using a fork to pick up a group of noodles requires orienting the fork tines opposite the grain of the strands. This is crucial to preventing slippage during twirling (Fig. 11), which tends to occur when the tines and strands run parallel. To address this, we also learn a network $f_{\text{ori}} : \mathbb{R}_+^{W' \times H' \times 3} \to \mathbb{R}$ mapping a local RGB crop of a food item of dimensions $W' \times H'$ to the desired roll orientation of the utensil γ. Prior work has shown that acquiring a food item orthogonal to its main principal axis, such as skewering a carrot against its length-wise axis rather than width-wise, can improve acquisition stability [4, 6]. Thus, we implement f_{ori} as a fully convolutional network with a ResNet backbone and train it from a small amount of real food item crops (200), manually annotated with keypoints defining the principal food item axis as in [4].

Action Instantiation. With the visual state estimation pipelines f_{seg} and f_{ori} trained offline, we can instantiate $\pi_L(a_t | o_t, h^k)$ for real-world manipulation. Given an RGBD image observation I_t, D_t, we first infer the segmentation mask $\hat{M}_t = f_{\text{seg}}(I_t)$. Next, we query π_H to obtain a selected primitive $\hat{h}^k = \pi_H(\hat{M}_{\leq t}, \hat{a}_{\leq t-1}^{(H)})$.

If $\hat{h}^k$ is an acquisition primitive, we instantiate the continuous action $a_{t,\text{acquis}}$ according to Eq. (1) by estimating the densest plate region $(\hat{x}_d, \hat{y}_d, \hat{z}_d)$ and utensil orientation $\hat{\gamma}$. To do so, we apply a standard 2D Gaussian kernel over $\hat{M}_t$ yielding $\hat{M}_t^{'}$. This blurs the image such that high-density regions in the original segmentation mask remain saturated but sparse regions have lower intensity. From this, we take the 2D argmax $\hat{u}_d, \hat{v}_d = \arg\max_{(u,v) \in \hat{M}_t^{'}} \hat{M}_t^{'}[u, v]$ to be the densest pixel in the image, deprojected to a 3D location $(\hat{x}_d, \hat{y}_d, \hat{z}_d)$ via D_t and known camera intrinsics. Given a food item crop centered at the densest pixel, $I_t^{'}$ (Fig. 2) we also infer the utensil orientation with $\hat{\gamma} = f_{\text{ori}}(I_t^{'})$. For a rearrangement primitive, we parameterize $a_{t,\text{rearrange}}$ according to Eq. (2). In addition to sensing the densest plate region, we sense the furthest region $(\hat{x}_f, \hat{y}_f, \hat{z}_f)$ by finding the lowest intensity pixel in $\hat{M}'_t$. This yields the following instantiations:

$$\pi_L(o_t, h^{k,\text{acquis}}) = (\hat{x}_d, \hat{y}_d, \hat{z}_d, \hat{\gamma}) \qquad \Big| \qquad \pi_L(o_t, h^{k,\text{rearrange}}) = (\hat{x}_d, \hat{y}_d, \hat{z}_d, \hat{x}_f, \hat{y}_f, \hat{z}_f)$$

Finally, **VAPORS** operates in a perception-action loop using π_H to generate sequential plans and π_L to execute them. The full algorithm can be found in Algorithm 1 of the Appendix.

5 Experiments

We seek to evaluate **VAPORS** ability to clear plates, by effectively leveraging diverse strategies and planning over long horizons. Thus, we compare against a single-strategy baseline with no long-horizon reasoning and a multi-strategy approach that plans long-term actions heuristically rather than via learned plate dynamics. We consider two challenging real-world feeding scenarios to test the capabilities of **VAPORS** compared to other approaches: noodle acquisition and bimanual scooping.

Experimental Setup: In noodle acquisition (Fig. 9), a Franka robot with a wrist-mounted custom motorized fork and RGBD camera must decide amongst *twirling* (acquisition) or *grouping* (rearrangement) to clear a plate of noodles. In bimanual scooping (Fig. 10), two Franka robots operating from overhead RGBD cameras must select amongst *scooping* (acquisition) or *grouping* (rearrangement) to clear a plate of jelly beans. For both tasks, we consider a *half-full* initial plate distribution (50 g. noodles, 15 jelly beans) and a hard count of $\tau = 10$ actions for spaghetti and $\tau = 8$ actions for jelly beans, encouraging the acquisition of multiple items at once to finish a plate. For both tasks, we assume access to hand-eye calibration between the RGB-D camera and robot end-effector. In Appendix C we outline the hardware setup and control stack, low-level action instantiations, and training details for each task.

Baselines: *Acquire-Only* is identical to **VAPORS** in terms of π_L, but does not perform any long-horizon reasoning. Instead, at each timestep, this approach only acquires via twirling or scooping, with no rearrangement in between. *Heuristic* also utilizes π_L in the same manner, but replaces π_H with a naïve group-then-acquire strategy. This method senses the COVERAGE, as defined in Eq. (3), over $\hat{M}_t$ to heuristically determine when acquiring or rearrangement is appropriate. When the area exceeds a pre-defined threshold, the policy defaults to rearrangement and otherwise acquires.

Plate Clearance Results: We evaluate **VAPORS**, Acquire-Only, and Heuristic on clearing plates across 10 trials for each task (Fig. 5). We see that **VAPORS** achieves the most efficient and highest cumulative plate clearance. As expected, Acquire-Only optimizes only for acquisition in the current instant, without exploiting the benefits of grouping for a more substantial pickup of multiple items at once. Scooping one jelly bean at a time or attempting to twirl just a few strands of noodles repeatedly leads to the observed slow rate of overall clearance. Heuristic's greedy group-then-acquire approach plans based on detected coverage thresholds, which we find is brittle in practice especially for any artifacts in segmentation mask predictions. This naive metric also does not encourage acquiring any bite-sized piles that may form intermittently, but rather aims to amass everything into one large pile before acquiring. This delays acquisition gains and wastes the action budget.

Figure 6: **Likert Ratings**: We administer a 7-point Likert survey to users after observing 10 trials per method. **VAPORS** elicits the most positive feedback across all criteria. '*' indicates statistical significance ($p < 0.05$).

User Evaluation: Additionally, we conducted a user study with 49 non-disabled participants (age range 27.0 ± 9.5, 46.9% female and 53.1% male) to gauge user preferences across methods. Of this pool, 77.6% reported prior experience interacting with robots before, 75.5% reported having fed someone before, and 28.6% reported having been fed as an adult. We hypothesized: **H1.** *Compared to baselines, **VAPORS** use of multiple strategies and long horizon foresight will lead to more preferable feeding in terms of quantitative and qualitative metrics.*

We used a within-subjects design where we presented each participant with videos of all 10 plate clearance trials per each of the three methods, for either noodle acquisition or bimanual scooping. For each participant, we randomized the method order, the order of trials per

method, and the food group. In the study, we ask participants to rate efficiency, bite size, similarity to human feeding, practicality, likelihood for reuse, safety, and generalization.

After watching all trials, we provided users with a 7-point Likert survey to assess these criteria (Fig. 6). **VAPORS** incurs the highest qualitative user ratings across criteria, compared to the Acquire-Only and Heuristic baselines, and with statistical significance for certain categories ($p < 0.05$, denoted '*'). Users noted that **VAPORS** "mimicked natural feeding," and "showed a capacity for clustering as the plate got more and more empty, which felt like a great and efficient approach," while Heuristic and Acquire-Only "seem like extreme policies, where [Acquire-Only] never tries to cluster and [Heuristic] focus too much on making big piles." These results align with the hypothesis that **VAPORS'** use of multiple strategies and ability to reason over long horizons benefits a user's mealtime experience. We provide additional user study findings in Appendix C.

Tier 1

Tier 2   Tier 3

Figure 7: **Noodle Acquisition Tiers of Difficulty**: Tier 1 consists of plain noodle varieties: Dan Dan, Udon, and Pappardelle noodles. Tier 2 includes Tier 1 plates along with soy sauce, marinara sauce, and garnishes such as parsley or cilantro. Tier 3 plates include noodle dishes such as pesto pasta and chow mein ordered from DoorDash.

Generalization Testing: Finally, we stress-test **VAPORS'** generalization capabilities by experimenting with noodle dishes prepared with sauces and garnishes as well as ordered from DoorDash (Fig. 7). We conduct 18 additional trials of plate clearance on unseen plates, separated into three tiers of difficulty with 6 trials per tier. We summarize our findings in Table 1.

VAPORS achieves near full plate clearance for Tier 1 noodles, demonstrating generalization to noodle shapes and sizes (Table 1). While **VAPORS** is still able to make decent progress towards

Tier	Description	% Cleared	Failure Categorization				
			A	B	C	D	Failure Rate
1	Plain Noodles	$90\% \pm 6\%$	2	7	2	0	18%
2	Noodles w/ Sauce	$68\% \pm 16\%$	2	8	1	4	25%
3	DoorDash Noodles	$64\% \pm 13\%$	3	5	2	4	23%

Table 1: **OOD Results and Categorization of Failure Modes:** (A) Misperception, (B) Wrong Action, (C) Imprecision, (D) Slip.

plate clearance in Tier 2, we observe the occurrence of more slip failures (D) and misplanned actions (A, B) due to the addition of sauce and distractor food items. Somewhat surprisingly, the performance gap between Tier 2 and Tier 3 is minimal, with **VAPORS** being able to clear well over half the noodles for a fully out-of-distribution plate. The main challenges include misperceiving cabbage for noodles in the chow mein, as well as dropping twirled noodles heavily coated in pesto or soy sauce (D) (Fig. 11). Regardless, **VAPORS** demonstrates promising signs of zero-shot generalization.

6 Discussion

We present **VAPORS**, which to our knowledge is the first framework to address the multi-step food acquisition problem in robot-assisted feeding. Our hybrid approach leverages simulation to learn to model high-level plate dynamics at scale, and uses visual pose estimation in order to perform dexterous maneuvers for complex low-level food pickup. We experimentally validate **VAPORS** on a complex suite of real-world food acquisition tasks such as noodle acquisition and bimanual scooping of beans. **VAPORS** demonstrates the ability to clear plates efficiently over non-learned baselines while appealing to the feeding preferences of real users.

Limitations and Future Work. Although this work highlights promising initial results toward generalization across food variations such as shape, sauces, and toppings, we acknowledge that our library of low-level primitives is currently limited and would benefit from a more diverse repertoire. One actionable future direction is expanding our library with prior work on skewering, cutting, and even toppling unstable items to tackle a more expansive set of plates. Our initial prototypes for dexterous food acquisition, such as the motorized fork, also open up interesting possibilities for future designs of dexterous interchangeable utensils which would enable rapid strategy switching. Currently, the system also executes primitives in an open-loop fashion, but we hope to use reactive control in the future to adapt online to slippage or imprecision.

References

[1] M. W. Brault et al. *Americans with disabilities: 2010*. US Department of Commerce, Economics and Statistics Administration, US . . . , 2012.

[2] S. W. Brose, D. J. Weber, B. A. Salatin, G. G. Grindle, H. Wang, J. J. Vazquez, and R. A. Cooper. The role of assistive robotics in the lives of persons with disability. *American Journal of Physical Medicine & Rehabilitation*, 89(6):509–521, 2010.

[3] V. Maheu, P. S. Archambault, J. Frappier, and F. Routhier. Evaluation of the jaco robotic arm: Clinico-economic study for powered wheelchair users with upper-extremity disabilities. In *2011 IEEE International Conference on Rehabilitation Robotics*, pages 1–5. IEEE, 2011.

[4] P. Sundaresan, S. Belkhale, and D. Sadigh. Learning visuo-haptic skewering strategies for robot-assisted feeding. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=lLq09gVoaTE.

[5] E. K. Gordon, X. Meng, T. Bhattacharjee, M. Barnes, and S. S. Srinivasa. Adaptive robot-assisted feeding: An online learning framework for acquiring previously unseen food items. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 9659–9666. IEEE, 2020.

[6] R. Feng, Y. Kim, G. Lee, E. K. Gordon, M. Schmittle, S. Kumar, T. Bhattacharjee, and S. S. Srinivasa. Robot-assisted feeding: Generalizing skewering strategies across food items on a plate. In *The International Symposium of Robotics Research*, pages 427–442. Springer, 2019.

[7] J. Grannen, Y. Wu, S. Belkhale, and D. Sadigh. Learning bimanual scooping policies for food acquisition. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=qDtbMK67PJG.

[8] L. Shaikewitz, Y. Wu, S. Belkhale, J. Grannen, P. Sundaresan, and D. Sadigh. In-mouth robotic bite transfer with visual and haptic sensing. *arXiv preprint arXiv:2211.12705*, 2022.

[9] S. Belkhale, E. K. Gordon, Y. Chen, S. Srinivasa, T. Bhattacharjee, and D. Sadigh. Balancing efficiency and comfort in robot-assisted bite transfer. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 4757–4763. IEEE, 2022.

[10] D. Gallenberger, T. Bhattacharjee, Y. Kim, and S. S. Srinivasa. Transfer depends on acquisition: Analyzing manipulation strategies for robotic feeding. In *2019 14th ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pages 267–276. IEEE, 2019.

[11] M. Sharma, K. Zhang, and O. Kroemer. Learning semantic embedding spaces for slicing vegetables. *arXiv preprint arXiv:1904.00303*, 2019.

[12] K. Zhang, M. Sharma, M. Veloso, and O. Kroemer. Leveraging multimodal haptic sensory data for robust cutting. In *2019 IEEE-RAS 19th International Conference on Humanoid Robots (Humanoids)*, pages 409–416. IEEE, 2019.

[13] E. Heiden, M. Macklin, Y. Narang, D. Fox, A. Garg, and F. Ramos. Disect: A differentiable simulator for parameter inference and control in robotic cutting. *arXiv preprint arXiv:2203.10263*, 2022.

[14] H. Suh and R. Tedrake. The surprising effectiveness of linear models for visual foresight in object pile manipulation. In *International Workshop on the Algorithmic Foundations of Robotics*, pages 347–363. Springer, 2020.

[15] L. X. Shi, J. J. Lim, and Y. Lee. Skill-based model-based reinforcement learning. *arXiv preprint arXiv:2207.07560*, 2022.

[16] X. Lin, C. Qi, Y. Zhang, Z. Huang, K. Fragkiadaki, Y. Li, C. Gan, and D. Held. Planning with spatial-temporal abstraction from point clouds for deformable object manipulation. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=tyxyBj2w4vw.

[17] Z. Cao, E. Bıyık, W. Z. Wang, A. Raventos, A. Gaidon, G. Rosman, and D. Sadigh. Reinforcement learning based control of imitative policies for near-accident driving. *arXiv preprint arXiv:2007.00178*, 2020.

[18] M. Dalal, D. Pathak, and R. R. Salakhutdinov. Accelerating robotic reinforcement learning via parameterized action primitives. *Advances in Neural Information Processing Systems*, 34:21847–21859, 2021.

[19] S. Nasiriany, H. Liu, and Y. Zhu. Augmenting reinforcement learning with behavior primitives for diverse manipulation tasks. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 7477–7484. IEEE, 2022.

[20] C. Agia, T. Migimatsu, J. Wu, and J. Bohg. Taps: Task-agnostic policy sequencing. *arXiv preprint arXiv:2210.12250*, 2022.

[21] A. Kumar, Z. Fu, D. Pathak, and J. Malik. Rma: Rapid motor adaptation for legged robots. *arXiv preprint arXiv:2107.04034*, 2021.

[22] S. Bahl, A. Gupta, and D. Pathak. Hierarchical neural dynamic policies. *arXiv preprint arXiv:2107.05627*, 2021.

[23] L. Shao, T. Migimatsu, Q. Zhang, K. Yang, and J. Bohg. Concept2robot: Learning manipulation concepts from instructions and human demonstrations. *The International Journal of Robotics Research*, 40(12-14): 1419–1434, 2021.

[24] Meet Obi. https://meetobi.com/. [Online; accessed 6-June-2022].

[25] Meal-Mate - Made2Aid. https://www.made2aid.co.uk/productprofile?productId=8&company=RBF%20Healthcare&product=Meal-Mate. [Online; accessed 6-June-2022].

[26] E. K. Gordon, S. Roychowdhury, T. Bhattacharjee, K. Jamieson, and S. S. Srinivasa. Leveraging post hoc context for faster learning in bandit settings with applications in robot-assisted feeding. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 10528–10535. IEEE, 2021.

[27] L. P. Kaelbling and T. Lozano-Pérez. Hierarchical planning in the now. In *Workshops at the Twenty-Fourth AAAI Conference on Artificial Intelligence*, 2010.

[28] S. Srivastava, E. Fang, L. Riano, R. Chitnis, S. Russell, and P. Abbeel. Combined task and motion planning through an extensible planner-independent interface layer. In *2014 IEEE international conference on robotics and automation (ICRA)*, pages 639–646. IEEE, 2014.

[29] C. R. Garrett, R. Chitnis, R. Holladay, B. Kim, T. Silver, L. P. Kaelbling, and T. Lozano-Pérez. Integrated task and motion planning. *Annual review of control, robotics, and autonomous systems*, 4:265–293, 2021.

[30] R. Chitnis, D. Hadfield-Menell, A. Gupta, S. Srivastava, E. Groshev, C. Lin, and P. Abbeel. Guided search for task and motion plans using learned heuristics. In *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pages 447–454. IEEE, 2016.

[31] C. R. Garrett, T. Lozano-Pérez, and L. P. Kaelbling. Ffrob: An efficient heuristic for task and motion planning. In *Algorithmic Foundations of Robotics XI*, pages 179–195. Springer, 2015.

[32] H. Shi, H. Xu, Z. Huang, Y. Li, and J. Wu. Robocraft: Learning to see, simulate, and shape elasto-plastic objects with graph networks. *arXiv preprint arXiv:2205.02909*, 2022.

[33] X. Lin, Z. Huang, Y. Li, J. B. Tenenbaum, D. Held, and C. Gan. Diffskill: Skill abstraction from differentiable physics for deformable object manipulations with tools. *arXiv preprint arXiv:2203.17275*, 2022.

[34] C. Finn and S. Levine. Deep visual foresight for planning robot motion. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2786–2793. IEEE, 2017.

[35] F. Ebert, C. Finn, S. Dasari, A. Xie, A. Lee, and S. Levine. Visual foresight: Model-based deep reinforcement learning for vision-based robotic control. *arXiv preprint arXiv:1812.00568*, 2018.

[36] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019.

[37] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In *International conference on machine learning*, pages 2555–2565. PMLR, 2019.

[38] Y. Li, A. Torralba, A. Anandkumar, D. Fox, and A. Garg. Causal discovery in physical systems from videos. *Advances in Neural Information Processing Systems*, 33:9180–9192, 2020.

[39] S. Pateria, B. Subagdja, A.-h. Tan, and C. Quek. Hierarchical reinforcement learning: A comprehensive survey. *ACM Computing Surveys (CSUR)*, 54(5):1–35, 2021.

[40] T. Roosendaal. Blender foundation. *The essential Blender: guide to 3D creation with the open source suite Blender*, 2007.

[41] E. Coumans and Y. Bai. 2019. pybullet, a python module for physics simulation for games, robotics and machine learning, 2016.

[42] V. Makoviychuk, L. Wawrzyniak, Y. Guo, M. Lu, K. Storey, M. Macklin, D. Hoeller, N. Rudin, A. Allshire, A. Handa, et al. Isaac gym: High performance gpu-based physics simulation for robot learning. *arXiv preprint arXiv:2108.10470*, 2021.

[43] P. R. Florence, L. Manuelli, and R. Tedrake. Dense object nets: Learning dense visual object descriptors by and for robotic manipulation. *arXiv preprint arXiv:1806.08756*, 2018.

[44] V. Viswanath, K. Shivakumar, J. Kerr, B. Thananjeyan, E. Novoseller, J. Ichnowski, A. Escontrela, M. Laskey, J. E. Gonzalez, and K. Goldberg. Autonomously untangling long cables. *arXiv preprint arXiv:2207.07813*, 2022.

[45] P. Sundaresan, J. Grannen, B. Thananjeyan, A. Balakrishna, J. Ichnowski, E. Novoseller, M. Hwang, M. Laskey, J. E. Gonzalez, and K. Goldberg. Untangling dense non-planar knots by learning manipulation features and recovery policies. *arXiv preprint arXiv:2107.08942*, 2021.

[46] J. Grannen, P. Sundaresan, B. Thananjeyan, J. Ichnowski, A. Balakrishna, M. Hwang, V. Viswanath, M. Laskey, J. E. Gonzalez, and K. Goldberg. Untangling dense knots by learning task-relevant keypoints. *arXiv preprint arXiv:2011.04999*, 2020.

[47] L. Manuelli, Y. Li, P. Florence, and R. Tedrake. Keypoints into the future: Self-supervised correspondence in model-based reinforcement learning. *arXiv preprint arXiv:2009.05085*, 2020.

[48] W. Gao and R. Tedrake. kpam 2.0: Feedback control for category-level robotic manipulation. *IEEE Robotics and Automation Letters*, 6(2):2962–2969, 2021.

[49] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *Conference on Robot Learning*, pages 894–906. PMLR, 2022.

[50] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, et al. Transporter networks: Rearranging the visual world for robotic manipulation. In *Conference on Robot Learning*, pages 726–747. PMLR, 2021.

[51] D. Seita, A. Ganapathi, R. Hoque, M. Hwang, E. Cen, A. K. Tanwani, A. Balakrishna, B. Thananjeyan, J. Ichnowski, N. Jamali, et al. Deep imitation learning of sequential fabric smoothing from an algorithmic supervisor. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 9651–9658. IEEE, 2020.

[52] H. Ha and S. Song. Flingbot: The unreasonable effectiveness of dynamic manipulation for cloth unfolding. In *Conference on Robot Learning*, pages 24–33. PMLR, 2022.