Bayes-Nash Generative Privacy Protection Against Membership Inference Attacks

Abstract

Membership inference attacks (MIAs) expose significant privacy risks by determining whether an individual's data is in a dataset. While differential privacy (DP) mitigates such risks, it struggles to balance the privacy-utility trade-off, requiring intractable sensitivity calculations and limiting flexibility in complex compositions. We propose a game-theoretic framework that models privacy protection as a Bayesian game between a defender and an attacker, solved using a general-sum Generative Adversarial Network (general-sum GAN). The Bayes Generative Privacy (BGP) response, based on cross-entropy loss, defines the attacker's optimal strategy, leading to the Bayes-Nash Generative Privacy (BNGP) strategy, which achieves the optimal privacy-utility trade-off tailored to the defender's preferences. The BNGP strategy avoids sensitivity calculations, supports correlated mechanisms, and is robust to the attacker's heterogeneous preferences over true and false positives. A case study on binary dataset summary statistics demonstrates its superiority over likelihood ratio test (LRT)-based attacks, including the uniformly most powerful LRT. Empirical results confirm BNGP's effectiveness.

1 Introduction

Membership inference attacks (MIAs) exploit vulnerabilities in data analysis and machine learning, enabling adversaries to determine whether an individual's data is included in a dataset, such as medical records or training data. MIAs represent not only a significant privacy threat but also a dominant method for assessing privacy risks. To mitigate the privacy risks, noise perturbation strategies like differential privacy (DP) (Dwork, 2006) introduce randomness to reduce information leakage. DP provides strong theoretical guarantees by ensuring probabilistic near-indistinguishability of an individual's presence in a dataset based on the output of data sharing and processing mechanisms.

However, privacy protection inevitably leads to a tradeoff: adding noise increases uncertainty but reduces data utility, while insufficient noise leaves sensitive information vulnerable to inference attacks. Balancing this privacy-utility trade-off is essential for effective privacy protection across diverse applications. The DP framework quantifies privacy preservation using an (ϵ, δ) scheme, which measures the extent to which individual privacy is protected. However, this scheme does not fully capture the utility of the released aggregate information, because for a given (ϵ, δ) (representing a specific privacy level), different noise perturbation methods—such as varying noise distributions (e.g., Gaussian or Laplace) or magnitudes can yield differing levels of utility (Geng et al., 2020). Identifying optimal privacy parameters and noise mechanisms is therefore crucial to achieving an optimal trade-off for a given objective using any privacy-preserving framework, DP included.

Despite its theoretical appeal, guaranteeing a desired level of DP for a data-processing mechanism is often challenging. For instance, calculating sensitivity—the maximum possible change in the output when a single data point is replaced—is generally NP-hard (Xiao & Tao, 2008). Furthermore, determining the optimal composition of multiple independent DP mechanisms is $\#P$-complete (Murtagh & Vadhan, 2015). Moreover, the tight characterization of aggregate differential privacy risk under the composition of multiple mechanisms with arbitrary correlation remains open. These challenges complicate the design of DP mechanisms that optimally balance privacy and utility, particularly in scenarios involving multiple dataset accesses.

In this paper, we propose a novel game-theoretic framework to address the optimal privacy-utility trade-off by conceptualizing privacy risk as the outcome of strategic interactions between a *defender* and an *attacker*. We model this interaction as a general-sum Bayesian game, where the defender optimizes privacy while preserving utility, and the attacker seeks to perform MIAs. To solve for the Bayes-Nash Equilibrium (BNE), we introduce the general-sum Generative Adversarial Network (general-sum GAN), where the defender's privacy strategy acts as the generator and the attacker's MIA strategy serves as the discriminator. At the core of this approach is the Bayes Generative Privacy (BGP) response, which defines the attacker's best response to the defender's privacy strategy by minimizing a cross-entropy loss that quantifies the discrepancy between the prior distribution of the sensitive information and the attacker's probabilistic inference. The resulting privacy strategy, termed the Bayes-Nash Generative Privacy (BNGP) strategy, achieves the optimal privacy-utility trade-off tailored to the defender's preferences.

The BNGP strategy offers several key advantages. To address the attacker's heterogeneous preferences for true positives and false positives, we extend the membership advantage (MA) (Yeom et al., 2018) to a Bayes-weighted MA (BWMA). The BGP response captures the defender's worst-case privacy risk regardless of the attacker's preferences in terms of BWMA, ensuring no alternative strategy achieves strictly better privacy or utility for a given trade-off objective. Furthermore, the BGP response satisfies post-processing and composition properties, enabling BNGP strategies to optimize privacy for complex compositions involving arbitrary correlations—surpassing the typical independent mechanism assumptions of DP. In addition, we show that each BNGP privacy strategy is also an optimal approximate DP framework for a given trade-off objective. Furthermore, we establish a necessary and sufficient condition for equivalence between BNGP privacy and pure ϵ-DP for a given choice of ϵ. Unlike DP, BNGP avoids intractable sensitivity calculations for privacy guarantees and worst-case proofs for composition, and it can also handle compositions of correlated mechanisms. To demonstrate the effectiveness of our approach, we present a case study on sharing binary dataset summary statistics. Under mild assumptions, we show that a bounded-rational Bayesian attacker with a non-informative prior incurs higher worst-case loss for the defender than the uniformly most powerful likelihood ratio test (LRT) per the Neyman-Pearson lemma (Neyman & Pearson, 1933). Empirical results further confirm the efficacy of the BNGP strategy in achieving superior privacy-preserving sharing of summary statistics and classification models.

Organization Section 2 provides the necessary preliminaries. Section 3 introduces the Bayesian game framework for modeling privacy protection against MIAs. Sections 3.1 and 3.2 formally define the general-sum GAN, BGP response, and BNGP strategy, and explore their properties and relationship with differential privacy. Section 4 presents a case study on sharing summary statistics, comparing the proposed approach to state-of-the-art LRT methods. Section 5 discusses numerical experiments that validate the effectiveness of our framework, and Section 6 concludes the paper.

1.1 RELATED WORK

Quantitative Notions of Privacy Leakage Quantitative notions of privacy leakage have been extensively studied in various contexts which provides mathematically rigorous frameworks for measuring the amount of sensitive information that may be inferred by attackers. Differential privacy (Dwork et al., 2006; Dwork, 2006) and its variants (Bun & Steinke, 2016; Dwork & Rothblum, 2016; Mironov, 2017; Bun et al., 2018) formalize the privacy leakage using various parameterized statistical divergence metrics. For example, Rényi differential privacy (RDP) (Mironov, 2017) generalizes the standard pure DP and quantifies the privacy leakage through the use of Rényi divergence. Information-theoretic measures, such as mutual information (Chatzikokolakis et al., 2010; Cuff & Yu, 2016), f-divergence (Xiao & Devadas, 2023), and Fisher information (Farokhi & Sandberg, 2017; Hannun et al., 2021; Guo et al., 2022), provide alternative ways to quantify and characterize privacy loss. Empirical measurements are also widely studied (Shokri et al., 2017; Yeom et al., 2018; Nasr et al., 2021; Stock et al., 2022) that quantify the actual privacy guarantees or leakage under certain privacy protection methods.

Privacy-Utility Trade-off Balancing the trade-off between privacy and utility is a central challenge in designing privacy-preserving mechanisms. This balance is often modeled as an optimization problem (Lebanon et al., 2009; Sankar et al., 2013; Lopuhaä-Zwakenberg & Goseling, 2024; Ghosh et al., 2009; Gupte & Sundararajan, 2010; Geng et al., 2020; du Pin Calmon & Fawaz, 2012; Alghamdi et al., 2022; Goseling & Lopuhaä-Zwakenberg, 2022). For instance, Ghosh et al. (2009)

formulated a loss-minimizing problem constrained by differential privacy and demonstrated that the geometric mechanism is universally optimal in Bayesian settings. Similarly, optimization problems can be framed with utility constraints Lebanon et al. (2009); Alghamdi et al. (2022). Moreover, Gupte & Sundararajan (2010) modeled the trade-off as a zero-sum game, where the privacy mechanism maximizes privacy while information consumers minimize their worst-case loss using side information.

GAN in Privacy The use of generative adversarial networks (GANs) for privacy protection has gained increasing attention in recent years. Huang et al. (2018) introduced generative adversarial privacy (GAP), which frames privacy protection as a non-cooperative game between a generator (defender) and an adversarial discriminator (attacker). In GAP, the generator creates data that retains target utility while obfuscating sensitive information, while the discriminator attempts to identify the private data. The objective is to train a model that not only achieves high utility but is also resilient to the most powerful inference attacks (i.e., high privacy). Similar efforts have also been proposed in the form of compressive adversarial privacy (CAP), which compresses data before the adversarial training step to enhance privacy (Chen et al., 2018). Nasr et al. (2018) proposed an adversarial regularization method that mitigates this type of attack by adjusting the training process to reduce the information leakage from the model. Similarly, Jordon et al. (2018) presented PATE-GAN, combining the Private Aggregation of Teacher Ensembles (PATE) framework with GANs to generate synthetic data with differential privacy guarantees. Other works in this line includes privacy-preserving adversarial networks (Tripathy et al., 2019), reconstructive adversarial network (Liu et al., 2019b), and federated GAN (Rasouli et al., 2020). Adversarial training has also been applied to defend against MIAs specifically. For example, Li et al. (2021) explored methods where models are trained alongside adversaries attempting MIAs, which enables the models to learn representations that are less susceptible to such attacks. There are also works using GAN to perform attacks, where the generator represents the attacker's strategy (Baluja & Fischer, 2017; Hitaj et al., 2017; Zhao et al., 2018; Liu et al., 2019a; Hayes et al.).

2 PRELIMINARIES: MEMBERSHIP INFERENCE ATTACK

Membership inference attacks (MIA) aim to infer whether a particular data point is a part of the input dataset of a data analysis mechanism, which could output summary statistics (Sankararaman et al., 2009; Dwork et al., 2015), any model learned from the dataset (Abadi et al., 2016; Shokri et al., 2017), or other information or signals such as network traffic when processing the dataset (Chen et al., 2010). Let $U = [K]$ be a population of K individuals, where each individual k has a *data point* d_k (e.g., a feature vector). Let the binary vector $b = (b_1, b_2, \ldots, b_K) \in W \equiv \{0,1\}^K$ denote the *membership vector*, where each $b_k \in \{0,1\}$. The membership vector b indicates whether each data point is included in the dataset $B = \{b, d\}$, where $d = (d_k)_{k \in U}$; specifically, a data point d_k is included in B if and only if $b_k = 1$. Suppose the underlying distribution of the dataset induces a prior distribution of the membership, denoted by $\theta(\cdot) \in \Delta(W)$. Consider a (potentially randomized) mechanism $f(B) \in \mathcal{X}$, which takes the dataset B as input and outputs $x \in \mathcal{X}$, where $\mathcal{X}$ is a set of outputs.

Example: Summary Statistic Sharing Consider a population $U \equiv [K]$ of K individuals, where each individual's data is represented by a binary vector $d_k = (d_{kj})_{j \in Q}$, with $d_{kj} \in \{0, 1\}$ specifies the binary value of the specific attribute at position j. The set Q represents the set of all attributes under consideration, such as genomic positions or other features. The dataset $B = \{b, d\}$ includes a membership vector b and data points $d = \{d_k\}_{k \in U}$, where an individual's data is included only if $b_k = 1$. The data-sharing mechanism $f(B) = x = (x_1, \ldots, x_{|Q|}) \in \mathcal{X} = [0,1]^{|Q|}$ computes the summary statistics x, which is the fraction of individuals with $d_{kj} = 1$ at each attribute j. For example, in genomic data, d_k may represent single-nucleotide variants (SNVs), where each d_{kj} indicates the presence of an alternate allele at SNV j of individual k. The summary statistic in this case, known as the alternate allele frequency (AAF), is computed as $x_j = \frac{1}{\sum_k b_k} \sum_k b_k d_{kj}$, reflecting the fraction of individuals with the alternate allele at each SNV.

An MIA model is a (possibly randomized) mechanism $\mathcal{A}(d_k, x) \in \{0, 1\}$, which predicts the individual's membership information given the target individual k's data point and the output of the mechanism f. The standard *membership advantage* (MA) (Yeom et al., 2018) is a common perfor-

mance measure of the MIA model, defined for each $k \in U$ as:

$$\mathrm{Adv}_k \left(\mathcal{A} \right) \equiv \Pr \left[\mathcal{A}(d_k, x) = 1 | b_k = 1 \right] - \Pr \left[\mathcal{A}(d_k, x) = 1 | b_k = 0 \right]. \tag{1}$$

In other words, $\mathrm{Adv}_k \left(\mathcal{A} \right)$ captures the difference between the model $\mathcal{A}$'s *true positive rate* (TPR) and *false positive rate* (FPR). Other metrics used to assess MIA performance include accuracy (Shokri et al., 2017), area under the curve (AUC) (Chen et al., 2020), mutual membership information leakage (Farokhi & Kaafar, 2020), and privacy-leakage disparity (Zhong et al., 2022). For a comprehensive review, see (Niu et al., 2024).

3 PRIVACY PROTECTION AGAINST MIA AS A BAYESIAN GAME

We define the data curator of the private dataset B as the *defender*, tasked with protecting privacy against MIA, and the entity performing MIA as the *attacker*.

Defender To protect membership privacy, the defender randomizes the mechanism f via *noise perturbation*. Let $g_D : W \mapsto \Delta(\mathcal{D})$ denote the *privacy strategy*, where $g_D(\delta|b)$ specifies the probability distribution over noise $\delta \in \mathcal{D}$. The privacy strategy may also be independent of the membership vector, i.e., $g_D(\cdot) \in \Delta(\mathcal{D})$. The randomized version of f is represented as the mechanism $\mathcal{M}(\cdot; g_D)$, and $\rho_D : W \mapsto \Delta(\mathcal{X})$ is the density function induced by g_D and f. The defender, modeled as a Von Neumann-Morgenstern (vNM) decision-maker, aims to minimize the expected privacy loss.

Noise Perturbation Our noise perturbation aligns with standard randomization paradigms in DP, including input Dwork et al. (2006), objective Chaudhuri et al. (2011), and output Dwork et al. (2006) perturbations. When an output $x = \mathcal{M}(B; g_D)$ is realized with g_D drawing a noise δ, we denote it as $x = \mathrm{r}(\delta)$. In output perturbation, δ is added to the output $\hat{x} = f(B)$, and the publicly released output is $x = \mathrm{r}(\delta) = \mathrm{R}(\hat{x} + \delta)$, where $\mathrm{R}(\cdot)$ ensures the perturbed x remains within the valid range $\mathcal{X}$. For example, as described in Section 2, when $\hat{x}$ represents frequencies, the formulation $x = \mathrm{R}(\hat{x} + \delta) \equiv \mathrm{Clip}_{[0,1]}(\hat{x} + \delta)$ ensures $x \in [0, 1]^{|Q|}$.

Attacker The attacker performs MIA and aims to infer the true membership vector. We consider the attacker as a strategic Bayesian decision-maker, with their external knowledge represented by *subjective prior beliefs* about $b \in W$, denoted by $\sigma(\cdot) \in \Delta(W)$. We refer to this as a σ-*Bayesian attack*. The attacker employs a mixed strategy $h_A : \mathcal{X} \mapsto \Delta(W)$, which assigns a probability distribution over W based on the output of $\mathcal{M}(\cdot; g_D)$. The MIA model is then written as $\mathcal{A}(\cdot; h_A, \sigma) \in \{0, 1\}$.

The attacker may face trade-offs between maximizing privacy extraction and operational costs of post-processing the inferred membership information (e.g., for personalized medicine or marketing). These costs can affect their preference for true positives and true negatives. We extend (1) to the *Bayes-weighted membership advantage* (BWMA) by introducing a coefficient $0 < \gamma \leq 1$ to weight TPR and FPR. That is, BWMA is defined as:

$$\mathrm{Adv}^\gamma \left(h_A, g_D \right) \equiv (1 - \gamma)\mathrm{TPR} \left(h_A, g_D \right) - \gamma \mathrm{FPR} \left(h_A, g_D \right), \tag{2}$$

where $\mathrm{TPR} \left(h_A, g_D \right) \equiv \sum_{k \in U, b_{-k}} \Pr \left[\mathcal{A}(d_k, x; h_A, \sigma) = 1 | b_k = 1; g_D \right] \theta(b_k = 1, b_{-k})$ is the TPR, and $\mathrm{FPR} \left(h_A, g_D \right) \equiv \sum_{k \in U, b_{-k}} \Pr \left[\mathcal{A}(d_k, x; h_A, \sigma) = 1 | b_k = 0; g_D \right] \theta(b_k = 0, b_{-k})$ is the FPR. Decreasing λ indicates a stronger preference for TPR while increasing λ reflects a greater preference for FPR. When $\lambda = 0.5$, the attacker values TPR and FPR equally.

Attacker's Expected Loss Let $s = (s_k)_{k \in U} \in W$ denote the inference output of h_A. Define

$$\ell_A(s, b, \gamma) \equiv -v(s, b) + \gamma c_A(s),$$

where $v(s, b) \equiv \sum_{k \in U} s_k b_k$ captures the sum of true positives, and $c_A(s) \equiv \sum_{k \in U} s_k$ captures the operational costs to post-process positive inference outcomes (i.e., $s_k = 1$, for all $k \in U$). Maximizing $v(s, b)$ reflects maximizing true positives, while minimizing $c_A(s)$ reflects minimizing the operational costs. Given a privacy strategy g_D (and the induced ρ_D), prior σ, and the attacker's strategy h_A, the expected loss is defined as:

$$\mathcal{L}_A^\gamma(g_D, h_A) \equiv \sum_{s,b} \int_x \ell_A(s, b, \gamma) h_A(s|x) \rho_D(x|b) dx \sigma(b). \tag{3}$$

Proposition 1. *Suppose $\sigma = \theta$. Then, for any g_D, h_A, and $0 < \gamma \leq 1$, we have $\mathcal{L}_A^\gamma(g_D, h_A) = -\mathrm{Adv}^\gamma \left(h_A, g_D \right)$.*

Proposition 1 shows that when $\sigma = \theta$ and $0 < \gamma \leq 1$, the attacker's optimal strategy simultaneously minimizes $\mathcal{L}_A^\gamma(g_D, h_A)$ and maximizes $\text{Adv}^\gamma(h_A, g_D)$ for any given g_D. This equivalence simplifies the defender-attacker interaction by modeling it as a Bayesian game, where s represents the attacker's pure strategy.

Given any g_D, define the *maximum MA* as $\text{Adv}_k(g_D) \equiv \max_{h_A} \{\text{TPR}(h_A, g_D) - \text{FPR}(h_A, g_D)\}$.

Proposition 2. *Let g_D and g_D' be two defense strategies, and suppose $\sigma = \theta$. Then, $\text{Adv}_k(g_D) \geq \text{Adv}_k(g_D')$ for all $k \in U$ iff $\max_{h_A} \text{Adv}^{0.5}(h_A, g_D) \geq \max_{h_A} \text{Adv}^{0.5}(h_A, g_D')$.*

Proposition 2 establishes that the ordering of the privacy strength of the defender's strategies, where privacy risk is measured by the standard per-individual membership advantages (MAs), can be fully characterized by the ordering of the Bayes-weighted membership advantage (BWMA). In other words, comparing the BWMA is sufficient to determine which privacy strategy offers stronger protection in terms of per-individual privacy risk.

Defender's Expected Loss The defender aims to optimally balance the privacy-utility trade-off. Given any g_D, h_A, let $\mathcal{L}_D(g_D, h_A)$ represent the *expected loss function*. We consider TPR or standard MA (hence $\text{Adv}^{0.5}$) as the *defender's perceived privacy risk* and impose Assumption 1 on $\mathcal{L}_D$.

Assumption 1. *For a given g_D, the defender's expected loss $\mathcal{L}_D(g_D, h_A)$ increases as either $\text{TPR}(h_A, g_D)$ or $\text{Adv}^{0.5}(h_A, g_D)$ increases.*

Assumption 1 establishes a relationship between the defender's expected loss and privacy risk (dependent on h_A) under a given g_D, indicating that as privacy risk increases, the defender incurs greater loss. The defender aims to minimize privacy risk while maximizing the utility of the mechanism $\mathcal{M}$. A common class of $\mathcal{L}_D(g_D, h_A)$ satisfying Assumption 1 is an additive combination of privacy risk and utility loss, with the utility loss independent of h_A. A useful way to model the utility loss is by the deviation of $x = \mathcal{M}(B; g_D)$ from the unperturbed output $\hat{x} = f(B)$. Specifically, let $\ell_U : \mathbb{R}_+ \mapsto \mathbb{R}_+$ be an increasing, differentiable function, and let $\| \cdot \|_\text{p}$ be a norm on $\mathcal{X}$, for $\text{p} \geq 1$. The *utility loss* is then defined by $\ell_U(\|x - \hat{x}\|_\text{p})$. The defender's *privacy loss* can be either $v(s, b)$ (capturing TPR) or $-\ell_A(s, b, 0.5)$ (capturing MA). For simplicity, we use the membership vector b to represent the dataset $B = \{b, d\}$. If the defender's privacy risk is measured by TPR, the loss function is expressed as

$$\ell_D(b, s) \equiv v(s, b) + \kappa \ell_U(\|\mathcal{M}(b; g_D) - f(b)\|_\text{p}). \tag{4}$$

Given any g_D (and the induced ρ_D) and h_A, the defender's expected loss $\mathcal{L}_D$ is then given by

$$\mathcal{L}_D(g_D, h_A) \equiv \sum_{s,b} \int_x \ell_D(b, s) h_A(s|x) \rho_D(x|b) dx \theta(b). \tag{5}$$

The interaction between the defender and attacker is modeled as a game, with each optimizing their strategy. A σ-*Bayesian Nash Equilibrium* represents the point where neither can unilaterally improve their outcome.

Definition 1 (σ-Bayes Nash Equilibrium). *Let $0 < \gamma \leq 1$. A profile $\langle g_D^*, h_A^* \rangle$ is a σ-Bayesian Nash Equilibrium (σ-BNE) if*

$$g_D^* \in \arg\min_{g_D} \mathcal{L}_D(g_D, h_A^*) \text{ and } h_A^* \in \arg\min_{h_A} \mathcal{L}_A^\gamma(g_D^*, h_A). \tag{6}$$

3.1 BAYES-NASH GENERATIVE PRIVACY MECHANISM

We train the BNE strategies using a GAN-like approach, termed general-sum GAN. The defender's strategy is represented by a neural network *generator* $G_{\lambda_D}(b, \nu)$, parameterized by λ_D, which takes the true membership vector b and an auxiliary vector v as inputs, outputting a noise vector δ. Here, we assume that the auxiliary vector ν of dimension q has entries uniformly distributed in $[0, 1]$, denoted by $\nu \sim \mathcal{U}$. The attacker's strategy is represented by a neural network *discriminator* $H_{\lambda_A}(x)$, parameterized by λ_A, which takes as input $x = \text{r}(G_{\lambda_D}(b, \nu))$ and outputs an inference $s \in W$, where $\text{r}(\cdot)$ represents the relationship between δ and x.

We use G and H to represent the general forms of the models G_{λ_D} and H_{λ_A}, without reference to specific parameterization. Unless otherwise specified, G and H will be used in analysis, where the particular parameterization is not essential. For ease of exposition, we focus on output perturbation,

where $x = \mathtt{r}(\delta) = \mathtt{R}(\hat{x} + \delta)$, with $\hat{x} = f(b)$ as the unperturbed output. Our method applies to the general formulation of the privacy-utility trade-off objective under Assumption 1. Here, we use $\ell_U(\|\delta\|_{\mathtt{p}})$ as the utility loss for simplicity, as minimizing $\ell_U(\|\delta\|_{\mathtt{p}})$ also minimizes $\ell_U(\|\mathtt{R}(\hat{x} + \delta) - \hat{x}\|_{\mathtt{p}})$). Define the defender's and attacker's expected loss functions as:

$$\widetilde{\mathcal{L}}_D(G, H) \equiv \mathbb{E}_{b\sim\theta}^{\nu\sim\mathcal{U}} \left[v\left(H\left(r\left(G(b, \nu)\right)\right), b\right) + \kappa\ell_U\left(\|G(b, \nu)\|\right) \right],$$

$$\widetilde{\mathcal{L}}_A^{\gamma}(G, H) \equiv \mathbb{E}_{b\sim\sigma}^{\nu\sim\mathcal{U}} \left[-v\left(H\left(r\left(G(b, \nu)\right)\right), b\right) + \gamma c_A\left(H\left(r\left(G(b, \nu)\right)\right)\right) \right].$$

Then, the defender and the attacker play the following game:

$$G^* \in \arg\min_G \widetilde{\mathcal{L}}_D(G, H^*), H^* \in \arg\min_H \widetilde{\mathcal{L}}_A^{\gamma}(G^*, H). \tag{7}$$

This equilibrium reformulates the σ-BNE using neural networks. The G and H implicitly define probability distributions that match the mixed strategies g_D and h_A, respectively. With abuse of notation, we denote $\mathtt{TPR}(\cdot)$ and $\mathtt{Adv}^{\gamma}(\cdot)$ by substituting h_A and g_D by H and G. Hence, we have $\widetilde{\mathcal{L}}_D(G, H) = \mathcal{L}_D(g_D, h_A)$ and $\widetilde{\mathcal{L}}_A^{\gamma}(G, H) = \mathcal{L}_A^{\gamma}(g_D, h_A)$. Moreover, if $\mathcal{L}_D(g_D, h_A)$ satisfies Assumption 1, then so does $\widetilde{\mathcal{L}}_D(G, H)$. If G and H are idealized, nonparametric models with infinite capacity that accurately represent the true distributions of g_D and h_A, then Proposition 1 implies $H^* \in \arg\max_H \mathtt{Adv}^{\gamma}(H, G^*)$ if and only if $h_A^* \in \arg\min_{h_A} \mathcal{L}_A^{\gamma}(g_D^*, h_A)$. Here, G^* is the privacy strategy that achieves the optimal privacy-utility trade-off captured by $\widetilde{\mathcal{L}}_D$ under the worst-case privacy loss that can be induced.

Proxies of Loss Functions Since the function $v(s, b)$ requires binary outputs from H, it is inherently discrete. However, using sigmoid activation functions in the neural networks (particularly for H) results in continuous outputs, which makes $v(s, b)$ unsuitable for gradient-based optimization due to non-differentiability. We provide proxies for v and ℓ_A. Let $p = (p_k)_{k\in U}$, where each $p_k \in (0, 1)$, denote the output of H. We substitute $v(s, b)$ with $v(p, b) \equiv \sum_{k\in U} p_k b_k$, and use the *binary cross-entropy loss* for ℓ_A, defined as $\widehat{\ell}_A(p, b) = -\sum_{k\in U}(b_k \log(p_k) + (1 - b_k)\log(1 - p_k))$. Thus, the attacker's *expected cross-entropy loss* (CEL) is given by:

$$\mathcal{L}_{\mathrm{CEL}}(G, H) \equiv \mathbb{E}_{b\sim\sigma}^{\nu\sim\mathcal{U}} \left[\widehat{\ell}_A\left(H\left(r\left(G(b, \nu)\right)\right), b\right) \right]. \tag{8}$$

Definition 2 (Bayes Generative Privacy Response). *Given any G, the* Bayes generative privacy response (BGP response) *to G is defined as $H^* \in \arg\min_H \mathcal{L}_{\mathrm{CEL}}(G, H)$.*

Definition 3 (Bayes-Nash Generative Privacy Strategy). *The model G^* is a* Bayes-Nash generative privacy (BNGP) strategy *for a given objective function $\widetilde{\mathcal{L}}_D(\cdot)$ and subjective prior σ if it is constrained by the BGP response: $G^* \in \arg\min_G \widetilde{\mathcal{L}}_D(G, H^*), H^* \in \arg\min_H \mathcal{L}_{\mathrm{CEL}}(G^*, H)$.*

Theorem 1. *Let G^* be a BNGP strategy for $\widetilde{\mathcal{L}}_D$ and σ, and let H^* be a BGP response to G^*. Suppose that $\widetilde{\mathcal{L}}_D$ satisfies Assumption 1. Then, for any $G' \in \arg\min_G \widetilde{\mathcal{L}}_D(G, H')$ with $H' \in \arg\min_H \widetilde{\mathcal{L}}_A^{\gamma}(G', H)$ where $0 < \gamma \leq 1$, and for any $\widehat{H}$, we have:*

(i) $\mathtt{TPR}(\widehat{H}, G^*) \leq \mathtt{TPR}(H^*, G^*) \leq \mathtt{TPR}(H', G')$.

(ii) $\mathtt{Adv}^{0.5}(\widehat{H}, G^*) \leq \mathtt{Adv}^{0.5}(H^*, G^*) \leq \mathtt{Adv}^{0.5}(H', G')$.

By definition, a BNGP strategy G^* responds to the BGP response H^*, ensuring the optimal privacy-utility trade-off by considering the worst-case privacy loss when the attacker minimizes $\mathcal{L}_{\mathrm{CEL}}$. It is important to note that $\mathtt{TPR}$, $\mathtt{Adv}^{\gamma}$, $\widetilde{\mathcal{L}}_D$ are independent of $\mathcal{L}_{\mathrm{CEL}}$. Theorem 1 establishes that G^* achieves the optimal privacy-utility trade-off given $\widetilde{\mathcal{L}}_D$ by leveraging the worst-case privacy risk under the chosen privacy strategy. Specifically, the first inequalities in (i) and (ii) show that, under G^*, an attacker using H^* achieves the worst-case privacy risk for the defender, and no other attacker can induce a strictly higher privacy loss in terms of $\mathtt{TPR}$ or $\mathtt{Adv}^{0.5}$. The second inequalities in (i) and (ii) further demonstrate that G^* minimizes the defender's perceived privacy risk, ensuring that no alternative privacy strategy G' achieves a strictly lower privacy loss against the worst-case attacker.

3.2 PROPERTIES OF BGP RESPONSE

The BGP risk enjoys the properties of *post-processing* and *composition*. The post-processing property requires that processing a data-sharing mechanism's output cannot increase input data information. Let $\mathrm{Proc} : \mathcal{X} \mapsto \mathcal{Z}$ be a mechanism mapping $\mathcal{M}(b; G) \in \mathcal{X}$ to $\mathcal{Z}$, creating a new mechanism

Proc $\circ \mathcal{M}(b; G) \in \mathcal{Z}$. Proc $\circ G$ denotes the effective randomization device for Proc $\circ \mathcal{M}(\cdot; G)$. Proposition 3 shows that the BGP risk satisfies the post-processing property.

Proposition 3 (Post-Processing). *Suppose that G has BGP risk $H \in \arg\min_H \mathcal{L}_{\text{CEL}}(G, H)$ and $\widehat{\mathcal{L}}_A^\sigma(G, H)$. Suppose in addition that for any* Proc, Proc $\circ G$ *has BGP risk* $H' \in \arg\min_H \mathcal{L}_{\text{CEL}}(\text{Proc} \circ G, H)$. *Then,* $\mathcal{L}_{\text{CEL}}(\text{Proc} \circ G, H') \geq \mathcal{L}_{\text{CEL}}(G, H)$.

Consider a profile $\vec{G} = \{G_1, \ldots, G_n\}$ for $1 \leq n < \infty$, where each G_j corresponds to the density function g_D^j. With a slight abuse of notation, let $\mathcal{M}_j(G_j) : \mathcal{B} \mapsto \mathcal{X}^j$ denote the mechanism $\mathcal{M}_j(g_D^j)$ (i.e., the randomized version of the mechanism f^j) for all $j \in [n]$, where $\mathcal{X}^j$ represents the output space of $\mathcal{M}_j$. Additionally, let $\rho_D^j : \mathcal{B} \mapsto \Delta(\mathcal{X}^j)$ denote the underlying density function of $\mathcal{M}_j(G_j)$.

Define the composition $\mathcal{M}(\vec{G}) : \mathcal{B} \mapsto \prod_{j=1}^n \mathcal{X}^j$ of mechanisms $\mathcal{M}_1(G_1), \ldots, \mathcal{M}_n(G_n)$ as

$$\mathcal{M}(b; \vec{G}) \equiv (\mathcal{M}_1(b; G_1), \ldots, \mathcal{M}_n(b; G_n)).$$

The *joint density function* of $\mathcal{M}(b; \vec{G})$, denoted by $\vec{\rho}_D : \mathcal{B} \mapsto \Delta\left(\prod_{j=1}^n \mathcal{X}^j\right)$, encodes any underlying correlations among the mechanisms. Mechanisms in $\mathcal{M}(\vec{G})$ are independent if $\vec{\rho}_D(x^1, \ldots, x^n | B) = \prod_{j=1}^n \rho_D^j(x^j | B)$; otherwise, they are correlated. For simplicity, let $\vec{\mathbf{r}}(\vec{G}(b)) \equiv (\mathbf{r}_1(G_1(b)), \ldots, \mathbf{r}_n(G_n(b))) = \vec{x} = (x_1, \ldots, x_n)$.

Let $H(\vec{\mathbf{r}}(\vec{G}(b)))$ denote the attacker's discriminator that utilizes all outputs (irrespective of their order), and let $H_j(\mathbf{r}_j(G_j(b)))$ represent the discriminator that takes only $\mathbf{r}_j(G_j(b))$ as input.

Proposition 4 (Composition). *Suppose that $\mathcal{M}(\vec{G})$ is a composition of n mechanisms with arbitrary correlation. Then, we have, for $H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(\vec{G}, H)$, $H_j^* \in \arg\min_{H_j} \mathcal{L}_{\text{CEL}}(G_j, H_j)$ for all $j \in [n]$,*

$$\mathcal{L}_{\text{CEL}}(\vec{G}, \vec{H}^*) = \sum_{j=1}^n \mathcal{L}_{\text{CEL}}(G_j, H_j^*) - \Lambda(\vec{G}, \theta).$$

If mechanisms are independent, *then $\Lambda(\vec{G}, \theta) = -\sum_b \theta(b) \int_{\vec{\mathcal{X}}} \vec{\rho}_D(\vec{x}|b) \cdot \log\left(\sum_{b'} \vec{\rho}_D(\vec{x}|b') \theta(b')\right) d\vec{x}$. If mechanisms are* correlated, *$\Lambda(\vec{G}, \theta) = -\sum_b \theta(b) \int_{\vec{\mathcal{X}}} \vec{\rho}_D(\vec{x}|b) \log\left(\frac{\sum_{b'} \vec{\rho}_D(\vec{x}|b') \theta(b')}{P(\vec{x})}\right) d\vec{x}$, where $P(\vec{x}) = \prod_{j=1}^n \sum_{b'} \int_{\vec{\mathcal{X}}_{-j}} \vec{\rho}_D(x_j, \vec{x}_{-j}|b') \theta(b') d\vec{x}_{-j}$.*

Proposition 4 demonstrates that when privacy risk is quantified in terms of the minimum $\mathcal{L}_{\text{CEL}}$ (induced by the BGP response) for a given $\vec{G}$, the privacy risk adheres to an additive composition property.

3.2.1 RELATIONSHIP TO DIFFERENTIAL PRIVACY

Differential privacy (DP) (Dwork et al., 2006) ensures data analysis outputs remain nearly indistinguishable regardless of an individual's inclusion, hindering membership inference attacks (MIA). For adjacent datasets $B \simeq B'$ differing by one entry, a mechanism $\mathcal{M}(G)$ satisfies (ϵ, ξ)-DP ($\epsilon \geq 0$, $\xi \in [0, 1]$) if for all measurable $\widehat{\mathcal{X}} \subseteq \mathcal{X}$: $\Pr[\mathcal{M}(B; G) \in S] \leq e^\epsilon \Pr[\mathcal{M}(B'; G) \in S] + \xi$.

To align with the standard DP framework, we assume that each individual's membership information is independent of the others. With a slight abuse of notation, we represent $\theta(b)$ as $(\theta^1(b_1), \ldots, \theta^K(b_K))$, a vector of independent priors for each individual's membership.

Proposition 5. *Let $\vec{G}^* = \{G_1^*, \ldots, G_n^*\}$. Let $\mathcal{M}(\vec{G}^*)$ be a composition of $n \geq 1$ mechanisms with arbitrary correlation, where each G_j^* is BNGP strategies for some $\widetilde{\mathcal{L}}_D^j$ satisfying Assumption 1. Then, $\mathcal{M}(\vec{G}^*)$ is (ϵ, ξ)-DP for some $\epsilon \geq 0$ and $\xi \in [0, 1]$.*

Proposition 5 demonstrates that every mechanism employing a BNGP strategy profile is also differentially private. However, it does not specify the corresponding DP parameters. In the following, we outline how to design a BNGP strategy (or profile under composition) when the defender selects a specific value of ϵ.

For any $\epsilon \geq 0$ and any $\vec{G} = (G_1, \ldots, G_n)$, we define the following set:

$$\text{DPH}\left[\vec{G}; \epsilon\right] \equiv \left\{ H \left| \begin{array}{c} \theta(b)e^{-\epsilon} \leq H\left(\vec{\mathbf{r}}\left(\vec{G}(b)\right)\right) \leq \theta(b)e^{\epsilon}, \forall b \in W \\ 1 - (1 - \theta(b))\, e^{\epsilon} \leq H\left(\vec{\mathbf{r}}\left(\vec{G}(b)\right)\right) \leq 1 - (1 - \theta(b))\, e^{-\epsilon}, \forall b \in W \end{array} \right. \right\}. \tag{9}$$

Definition 4 (ϵ-Bayes Generative Bounded Privacy Response). *The ϵ-Bayes Generative Bounded Privacy response (ϵ-BGBP response) for any $\vec{G} = \{G_1, G_2, \ldots, G_n\}$ is defined as $H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(\vec{G}, H) \bigcap \text{DPH}[\vec{G}; \epsilon]$.*

An ϵ-BGBP response satisfies both (i) the conditions of a BGP response and (ii) the linear constraints in $\text{DPH}[\vec{G}; \epsilon]$. However, the attacker optimizing $\mathcal{L}_{\text{CEL}}$ does not consider $\text{DPH}[\vec{G}; \epsilon]$ as a constraint in their optimization. In other words, $\text{DPH}[\vec{G}; \epsilon]$ is not a restriction on the attacker's strategy. Instead, it is the defender's choice of $\vec{G}$ that must ensure the induced attacker's BGP response also satisfies the constraints in $\text{DPH}[\vec{G}; \epsilon]$. That is, $\text{DPH}[\vec{G}; \epsilon]$ constrains the defender's optimization problem.

Proposition 6. *For any $\vec{G} = \{G_1, G_2, \ldots, G_n\}$ and $\epsilon \geq 0$, the composition $\mathcal{M}(\vec{G})$ of $n \geq 1$ mechanisms is ϵ-DP iff all the BGP responses to $\vec{G}$ are ϵ-BGBP responses.*

Proposition 6 establishes the necessity and sufficiency of using the BGBP response to implement a pure ($\xi = 0$) differentially private mechanism. Consequently, for a composition (or a single mechanism) $\mathcal{M}(\vec{G}^*)$ to satisfy ϵ-DP, the defender selects $\vec{G}^*$ based on a given ϵ, ensuring:

$$\vec{G}^* \in \arg\min_{\vec{G}} \widetilde{\mathcal{L}}_D\left(\vec{G}, \text{s.t. } H^*\right), \quad H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(\vec{G}, H) \cap \text{DPH}[\vec{G}; \epsilon].$$

This choice of $\vec{G}^*$ guarantees that $\mathcal{M}(\vec{G})$ is an ϵ-DP mechanism that optimally balances the privacy-utility trade-off for a given privacy risk characterized by ϵ.

4 MIA IN SHARING SUMMARY STATISTICS

In this section, we apply Bayesian game-theoretic privacy protection to the sharing of summary statistics from binary datasets, as outlined in Section 2. Assuming the attributes in each d_k are independent, SNVs can be prefiltered to retain only those in *linkage equilibrium* (Kimura, 1965). An MIA attacker uses the summary statistics x output by $f(B)$ to infer whether specific individuals $k \in U$ belong to the private dataset B. We compare our Bayesian model with state-of-the-art (SOTA) Frequentist attacks, including *fixed(-threshold) LRT* (Sankararaman et al., 2009; Shringarpure & Bustamante, 2015; Venkatesaramani et al., 2021; 2023), *adaptive LRT* (Venkatesaramani et al., 2021; 2023), and the *optimal* LRT. These attacks rely on the log-*likelihood ratio statistic* $\text{lrs}(d_k, x)$, which compares observed summary statistics x to *reference frequencies* $\bar{p}_j$ derived from a population dataset independent of (b, d). Detailed definitions of these models and loss functions are provided in Appendix C.

The fixed LRT attacker determines whether individual k is part of the dataset by rejecting H_0^k (absence) in favor of H_1^k (presence) if $\text{lrs}(d_k, x) \leq \tau$, where the fixed τ balances Type-I (α_τ) and Type-II (β_τ) errors. The adaptive LRT dynamically adjusts $\tau^{(N)}$ using reference population data to refine the hypothesis test. The optimal LRT minimizes Type-II error β_{τ^*} for a given α_{τ^*}, achieving the most powerful test by Neyman-Pearson lemma (Neyman & Pearson, 1933). *Optimal α-LRT attacks* refer to Likelihood Ratio Tests that are Neyman-Pearson optimal at a fixed significance level α. The worst-case privacy loss (WCPL), representing the defender's strategy g_D under each attack, is defined as the expected value of $v(s, b)$. For the optimal, adaptive, and fixed LRT attacks, the WCPL is denoted by $L_{\text{Opt-LRT}}^{\alpha}(g_D)$, $L_{\text{Adp}}^{\alpha}(g_D)$, and $L_{\text{Fixed}}^{\alpha}(g_D)$, respectively (see Appendix C for explicit definitions).

Let $L(g_D, h_A) \equiv \sum_{b,s} \int_r v(s, b) h_A(s|r) \rho_D(r|b) dr \theta(b)$ denote the expected true positive rate. Under σ-Bayesian attacks using the BGP response, the worst-case privacy loss (WCPL) is given by $L_{\text{Bayesian}}^{\sigma}(g_D) \equiv \max_{H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(G,H)} L(g_D, h_A)$, where G and H are neural networks (ideal, non-parameterized) that implicitly define g_D and h_A.

In the absence of parameterized priors over W, we assume a uniform distribution as the non-informative prior, consistent with Laplace's principle (Fienberg, 2006). Our analysis focuses on subjective priors, considering their informativeness relative to the true prior θ. For simplicity, let $\mathcal{BR}^{\sigma}[g_D] \equiv \{h_A^* \mid H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(G, H), H \text{ defines } h_A^*\}$. When $\sigma = \theta$, we denote this set as $\mathcal{BR}^{\theta}[g_D]$.

Definition 5 (Aligned and Misaligned σ). *For a fixed g_D, σ is (weakly) informative if $L(g_D, h_A^{\sigma}) \leq L(g_D, h_A^{\theta})$, where $h_A^{\sigma} \in \mathcal{BR}^{\sigma}[g_D]$ and $h_A^{\theta} \in \mathcal{BR}^{\theta}[g_D]$. It is non-informative if uniformly distributed over W, aligned if either informative or non-informative, and misaligned otherwise. σ is strictly informative if the inequality is strict.*

Theorem 2. *Fix any g_D and α. If $\sigma \in \Delta(W)$ is an* aligned prior, *then:*

$$L^{\sigma}_{\text{Bayesian}}(g_D) \geq L^{\alpha}_{\text{Opt-LRT}}(g_D) \geq L^{\alpha}_{\text{Adp}}(g_D) \geq L^{\alpha}_{\text{Fixed}}(g_D).$$

If σ is strictly aligned, *then $L^{\sigma}_{\text{Bay}}(g_D) > L^{\alpha}_{\text{Opt-LRT}}(g_D)$.*

Theorem 2 establishes a ranking of WCPL from the defender's perspective across four types of attacks: σ-Bayesian, optimal α-LRT, adaptive α-LRT, and fixed α-LRT. Among these, the σ-Bayesian attack produces the highest WCPL. However, this ordering—particularly between $L^{\sigma}_{\text{Bayesian}}(g_D)$ and $L^{\alpha}_{\text{Opt-LRT}}(g_D)$—may not hold if the attacker's prior is misaligned. Appendix D shows an example of how to comparison between σ-Bayesian attack and the α-LRT attack when σ is an arbitrary subjective prior.

5 EXPERIMENTS

(a)   (b)   (c)

(d)   (e)   (f)

(g)   (h)   (i)

Figure 1: (a)-(c): Genomic dataset with 5000 SNVs (attributes) per individual. (d): Adult dataset. (e)-(f): Genomic dataset with 100 SNVs per individual. (g): Genomic dataset with 4000 SNVs per individual. (h): MNIST dataset. (i) Genomic dataset with 1000 SNVs per individual.

Datasets and Baselines: Our experiments use three datasets: the *Adult dataset* (UCI Machine Learning Repository), the *MNIST dataset*, and a *genomic dataset*. Detailed experimental setups and additional results are provided in Appendix P. We compare our Bayesian attacker (inducing the BGP response using $\mathcal{L}_{\text{CEL}}$) with the following baseline attack models: *fixed-threshold* and *adaptive-threshold* attackers (Sankararaman et al., 2009; Shringarpure & Bustamante, 2015; Venkatesaramani et al., 2021; 2023), the *score-based* attacker (Dwork et al., 2015), and *decision-tree* and *support vector machine (SVM)* attackers. The score-based attacker, proposed by Dwork et al. (2015), relaxes the LRT attack from Homer et al. (2008), requiring only that distorted summary statistics approximate the true marginals in ℓ_1-norm. We also evaluate the BNGP strategy against baseline defenses, including *standard DP*, *new pure DP* (Steinke & Ullman, 2016), the *DP mean estimator* (Cai et al., 2021), and two state-of-the-art (SOTA) genomic defense models (Venkatesaramani et al., 2021; 2023). In the experiments for Figures 1a-1e, 1a, and 1g, the mechanism releases summary statistics of the genomic dataset.

For Figure 1f, the mechanism performs mean estimation under DP (Cai et al., 2021). In the experiments for Figure 1h, the mechanism serves as a classifier for the MNIST dataset. For all experiments, we assume a uniform prior θ and set the Bayesian attacker's $\sigma = \theta$. We measure the strength of privacy protection using the attacker's ROC curve and its Area Under the Curve (AUC), which quantifies the attacker's ability to distinguish members from non-members.

Figure 1a presents the defender's performance against Bayesian, fixed-threshold LRT, and adaptive LRT attackers, using the genomic dataset (see Appendix C for details). The results confirm that the Bayesian attacker outperforms both the fixed-threshold and adaptive LRT attackers. That is, the Bayesian attacker poses the greatest threat among the three attack models. **Figure 1b** illustrates the Bayesian attacker's performance across three scenarios, each with the mechanism protected by a different defense model, using the genomic dataset. The Bayesian defender employs the BNGP strategy, while the fixed-threshold LRT and adaptive LRT defenders adopt privacy strategies that best respond to their respective LRT attackers. The results demonstrate that the Bayesian defender using the BNGP strategy is the most robust defense against the Bayesian attacker among the three defense models.

Figure 1c compares the Bayesian attacker's performance under two defenses using the genomic dataset: the Bayesian defender employs the BNGP strategy, while the other uses conventional ϵ-DP. Detailed setup information is in Appendix P.3. The Bayesian defender accounts for heterogeneous privacy-utility trade-offs by assigning weights $\vec{\kappa} = (\kappa_j)_{j \in Q}$ to SNV positions, with $\kappa_j = 0$ for 90% of 5000 SNVs and $\kappa_j = 50$ for the remaining 10%, meaning that the defender only cares about the utility loss for 10% of SNVs. In contrast, the ϵ-DP strategy ignores these preferences but selects ϵ to match the Bayesian defender's expected utility loss. In the experiment, the utility loss for the BNGP strategy is about 0.0001 and the corresponding $\epsilon = 1.25 \times 10^5$ (see Appendix P.3 for explanation). The results show that, despite equal utility loss, the ϵ-DP defense can incur significantly greater privacy loss under the Bayesian attack, with an AUC of 0.53 against the Bayesian defender and 0.91 against the ϵ-DP defender.

Figure 1d presents the performance of four attackers when the mechanism is protected by the Bayesian defense adopting the BNGP strategy, using the Adult dataset. The results show that the Bayesian attacker outperforms the others, with the adaptive LRT slightly surpassing the fixed-threshold LRT, and the score-based attacker performing the weakest. **Figures 1e** and **1f** present the performance of four attackers (Bayesian, fixed-threshold LRT, adaptive LRT, and score-based) when the mechanism is protected by two defense models, using the genomic dataset. In **Figure 1e**, the defender employs the new pure DP defense (Steinke & Ullman, 2016), while in **Figure 1f**, the defender uses DP with peeling (Dwork et al., 2018) to protect the mean estimator (Cai et al., 2021). The results show that the Bayesian attacker consistently achieves the highest performance, followed by the adaptive LRT, which slightly outperforms the fixed-threshold LRT, with the score-based attacker performing the worst.

Figure 1g compares the performance of four attackers (Bayesian, fixed-threshold LRT, adaptive LRT, and score-based) when the mechanism is protected by a defender employing the strategy that best responds to the score-based attacker, using the genomic dataset. The results show that the Bayesian attacker significantly outperforms the others, while the fixed-threshold and adaptive LRT attackers perform similarly but lag behind, with the score-based attacker performing the worst.

Figure 1h presents the results for a classifier trained on the MNIST dataset. The ROC curve compares the performance of the Bayesian, decision-tree, and SVM attackers when the mechanism is protected by the Bayesian defender employing the BNGP strategy. The results indicate that the Bayesian attacker performs the best, followed by the decision-tree attacker, with the SVM attacker performing the worst.

The experiments in **Figure 1i** empirically evaluate the BNGP strategy with the BGP response satisfying the condition in Proposition 6. "Composition" refers to the combination of five mechanisms, while "One Mechanism" represents a single ϵ-DP mechanism. The single ϵ-DP mechanism serves as a reference to assess whether the composition using the BNGP strategy also satisfies ϵ-DP by comparing the Bayesian attacker's performance. If the composition satisfies ϵ-DP, the Bayesian attacker's performance should closely resemble that in the single mechanism case. The results demonstrate that the BNGP strategy using the BGP response satisfying the condition in Proposition 6 ensures that the composition is approximately ϵ-DP.

6 CONCLUSION

This paper introduces a game-theoretic framework for optimal privacy-utility trade-offs, addressing the limitations of differential privacy in balancing privacy and utility. By modeling privacy protection as a Bayesian game between a defender and an attacker, we derive the Bayes-Nash Generative Privacy (BNGP) strategy, which achieves optimal trade-offs tailored to defender preferences. The BNGP strategy avoids intractable sensitivity calculations, supports complex compositions, and remains robust to heterogeneous attacker preferences. Empirical results validate the effectiveness of BNGP in privacy-preserving data sharing and classification, demonstrating its potential as a flexible and practical alternative to existing methods.

REPRODUCIBILITY STATEMENT

We have taken extensive measures to ensure the reproducibility of our work. All theoretical proofs are included in the appendix for transparency. Appendix P provides a comprehensive description of the experiment setups and additional experiments to facilitate replication. Furthermore, the main source code has been submitted as supplementary material

REFERENCES

1000 Genomes Project Consortium et al. A global reference for human genetic variation. *Nature*, 526(7571): 68, 2015.

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pp. 308–318, 2016.

Wael Alghamdi, Shahab Asoodeh, Flavio P Calmon, Oliver Kosut, Lalitha Sankar, and Fei Wei. Cactus mechanisms: Optimal differential privacy mechanisms in the large-composition regime. In *2022 IEEE International Symposium on Information Theory (ISIT)*, pp. 1838–1843. IEEE, 2022.

Shumeet Baluja and Ian Fischer. Adversarial transformation networks: Learning to generate adversarial examples. *arXiv preprint arXiv:1703.09387*, 2017.

David Blackwell. Comparison of experiments. In *Proceedings of the second Berkeley symposium on mathematical statistics and probability*, volume 2, pp. 93–103. University of California Press, 1951.

Mark Bun and Thomas Steinke. Concentrated differential privacy: Simplifications, extensions, and lower bounds. In *Theory of cryptography conference*, pp. 635–658. Springer, 2016.

Mark Bun, Cynthia Dwork, Guy N Rothblum, and Thomas Steinke. Composable and versatile privacy via truncated cdp. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pp. 74–86, 2018.

T Tony Cai, Yichen Wang, and Linjun Zhang. The cost of privacy: Optimal rates of convergence for parameter estimation with differential privacy. *The Annals of Statistics*, 49(5):2825–2850, 2021.

Konstantinos Chatzikokolakis, Tom Chothia, and Apratim Guha. Statistical measurement of information leakage. In *International Conference on Tools and Algorithms for the Construction and Analysis of Systems*, pp. 390–404. Springer, 2010.

Kamalika Chaudhuri, Claire Monteleoni, and Anand D Sarwate. Differentially private empirical risk minimization. *Journal of Machine Learning Research*, 12(3), 2011.

Dingfan Chen, Ning Yu, Yang Zhang, and Mario Fritz. Gan-leaks: A taxonomy of membership inference attacks against generative models. In *Proceedings of the 2020 ACM SIGSAC conference on computer and communications security*, pp. 343–362, 2020.

Shuo Chen, Rui Wang, XiaoFeng Wang, and Kehuan Zhang. Side-channel leaks in web applications: A reality today, a challenge tomorrow. In *2010 IEEE Symposium on Security and Privacy*, pp. 191–206. IEEE, 2010.

Xiao Chen, Peter Kairouz, and Ram Rajagopal. Understanding compressive adversarial privacy. In *2018 IEEE Conference on Decision and Control (CDC)*, pp. 6824–6831. IEEE, 2018.

Paul Cuff and Lanqing Yu. Differential privacy as a mutual information constraint. In *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security*, pp. 43–54, 2016.

Henrique de Oliveira. Blackwell's informativeness theorem using diagrams. *Games and Economic Behavior*, 109:126–131, 2018.

Jinshuo Dong, Aaron Roth, and Weijie Su. Gaussian differential privacy. *Journal of the Royal Statistical Society*, 2021.

Jinshuo Dong, Aaron Roth, and Weijie J Su. Gaussian differential privacy. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 84(1):3–37, 2022.

Flávio du Pin Calmon and Nadia Fawaz. Privacy against statistical inference. In *2012 50th annual Allerton conference on communication, control, and computing (Allerton)*, pp. 1401–1408. IEEE, 2012.

Cynthia Dwork. Differential privacy. In *International colloquium on automata, languages, and programming*, pp. 1–12, 2006.

Cynthia Dwork and Guy N Rothblum. Concentrated differential privacy. *arXiv preprint arXiv:1603.01887*, 2016.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pp. 265–284. Springer, 2006.

Cynthia Dwork, Adam Smith, Thomas Steinke, Jonathan Ullman, and Salil Vadhan. Robust traceability from trace amounts. In *2015 IEEE 56th Annual Symposium on Foundations of Computer Science*, pp. 650–669. IEEE, 2015.

Cynthia Dwork, Weijie J Su, and Li Zhang. Differentially private false discovery rate control. *arXiv preprint arXiv:1807.04209*, 2018.

Farhad Farokhi and Mohamed Ali Kaafar. Modelling and quantifying membership information leakage in machine learning. *arXiv preprint arXiv:2001.10648*, 2020.

Farhad Farokhi and Henrik Sandberg. Fisher information as a measure of privacy: Preserving privacy of households with smart meters using batteries. *IEEE Transactions on Smart Grid*, 9(5):4726–4734, 2017.

Stephen E Fienberg. When did bayesian inference become" bayesian"? 2006.

Quan Geng, Wei Ding, Ruiqi Guo, and Sanjiv Kumar. Tight analysis of privacy and utility tradeoff in approximate differential privacy. In *International Conference on Artificial Intelligence and Statistics*, pp. 89–99. PMLR, 2020.

Arpita Ghosh, Tim Roughgarden, and Mukund Sundararajan. Universally utility-maximizing privacy mechanisms. In *Proceedings of the forty-first annual ACM symposium on Theory of computing*, pp. 351–360, 2009.

Jasper Goseling and Milan Lopuhaä-Zwakenberg. Robust optimization for local differential privacy. In *2022 IEEE International Symposium on Information Theory (ISIT)*, pp. 1629–1634. IEEE, 2022.

Chuan Guo, Brian Karrer, Kamalika Chaudhuri, and Laurens van der Maaten. Bounding training data reconstruction in private (deep) learning. In *International Conference on Machine Learning*, pp. 8056–8071. PMLR, 2022.

Mangesh Gupte and Mukund Sundararajan. Universally optimal privacy mechanisms for minimax agents. In *Proceedings of the twenty-ninth ACM SIGMOD-SIGACT-SIGART symposium on Principles of database systems*, pp. 135–146, 2010.

Awni Hannun, Chuan Guo, and Laurens van der Maaten. Measuring data leakage in machine-learning models with fisher information. In *Uncertainty in Artificial Intelligence*, pp. 760–770. PMLR, 2021.

Jamie Hayes, Luca Melis, George Danezis, and Emiliano De Cristofaro. Logan: Membership inference attacks against generative models. *Proceedings on Privacy Enhancing Technologies*, 2019(1):133–152.

Briland Hitaj, Giuseppe Ateniese, and Fernando Perez-Cruz. Deep models under the gan: information leakage from collaborative deep learning. In *Proceedings of the 2017 ACM SIGSAC conference on computer and communications security*, pp. 603–618, 2017.

Nils Homer, Szabolcs Szelinger, Margot Redman, David Duggan, Waibhav Tembe, Jill Muehling, John V Pearson, Dietrich A Stephan, Stanley F Nelson, and David W Craig. Resolving individuals contributing trace amounts of dna to highly complex mixtures using high-density snp genotyping microarrays. *PLoS genetics*, 4(8):e1000167, 2008.

Chong Huang, Peter Kairouz, Xiao Chen, Lalitha Sankar, and Ram Rajagopal. Generative adversarial privacy. *arXiv preprint arXiv:1807.05306*, 2018.

James Jordon, Jinsung Yoon, and Mihaela Van Der Schaar. Pate-gan: Generating synthetic data with differential privacy guarantees. In *International conference on learning representations*, 2018.

Motoo Kimura. Attainment of quasi linkage equilibrium when gene frequencies are changing by natural selection. *Genetics*, 52(5):875, 1965.

Guy Lebanon, Monica Scannapieco, Mohamed Fouad, and Elisa Bertino. Beyond k-anonymity: A decision theoretic framework for assessing privacy risk. *Transactions on Data Privacy*, 2009.

Jiacheng Li, Ninghui Li, and Bruno Ribeiro. Membership inference attacks and defenses in classification models. In *Proceedings of the Eleventh ACM Conference on Data and Application Security and Privacy*, pp. 5–16, 2021.

Kin Sum Liu, Chaowei Xiao, Bo Li, and Jie Gao. Performing co-membership attacks against deep generative models. In *2019 IEEE International Conference on Data Mining (ICDM)*, pp. 459–467. IEEE, 2019a.

Sicong Liu, Junzhao Du, Anshumali Shrivastava, and Lin Zhong. Privacy adversarial network: representation learning for mobile data privacy. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, 3(4):1–18, 2019b.

Milan Lopuhaä-Zwakenberg and Jasper Goseling. Mechanisms for robust local differential privacy. *Entropy*, 26(3):233, 2024.

Ilya Mironov. Rényi differential privacy. In *2017 IEEE 30th computer security foundations symposium (CSF)*, pp. 263–275. IEEE, 2017.

Jack Murtagh and Salil Vadhan. The complexity of computing the optimal composition of differential privacy. In *Theory of Cryptography Conference*, pp. 157–175. Springer, 2015.

Milad Nasr, Reza Shokri, and Amir Houmansadr. Machine learning with membership privacy using adversarial regularization. In *Proceedings of the 2018 ACM SIGSAC conference on computer and communications security*, pp. 634–646, 2018.

Milad Nasr, Shuang Songi, Abhradeep Thakurta, Nicolas Papernot, and Nicholas Carlin. Adversary instantiation: Lower bounds for differentially private machine learning. In *2021 IEEE Symposium on security and privacy (SP)*, pp. 866–882. IEEE, 2021.

Jerzy Neyman and Egon Sharpe Pearson. Ix. on the problem of the most efficient tests of statistical hypotheses. *Philosophical Transactions of the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character*, 231(694-706):289–337, 1933.

Jun Niu, Peng Liu, Xiaoyan Zhu, Kuo Shen, Yuecong Wang, Haotian Chi, Yulong Shen, Xiaohong Jiang, Jianfeng Ma, and Yuqing Zhang. A survey on membership inference attacks and defenses in machine learning. *Journal of Information and Intelligence*, 2024.

Jean Louis Raisaro, Florian Tramer, Zhanglong Ji, Diyue Bu, Yongan Zhao, Knox Carey, David Lloyd, Heidi Sofia, Dixie Baker, Paul Flicek, et al. Addressing beacon re-identification attacks: quantification and mitigation of privacy risks. *Journal of the American Medical Informatics Association*, 24(4):799–805, 2017.

Mohammad Rasouli, Tao Sun, and Ram Rajagopal. Fedgan: Federated generative adversarial networks for distributed data. *arXiv preprint arXiv:2006.07228*, 2020.

Lalitha Sankar, S Raj Rajagopalan, and H Vincent Poor. Utility-privacy tradeoffs in databases: An information-theoretic approach. *IEEE Transactions on Information Forensics and Security*, 8(6):838–852, 2013.

Sriram Sankararaman, Guillaume Obozinski, Michael I Jordan, and Eran Halperin. Genomic privacy and limits of individual detection in a pool. *Nature genetics*, 41(9):965–967, 2009.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE symposium on security and privacy (SP)*, pp. 3–18. IEEE, 2017.

Suyash S Shringarpure and Carlos D Bustamante. Privacy risks from genomic data-sharing beacons. *The American Journal of Human Genetics*, 97(5):631–646, 2015.

Thomas Steinke and Jonathan Ullman. Between pure and approximate differential privacy. *Journal of Privacy and Confidentiality*, 7(2):3–22, 2016.

Pierre Stock, Igor Shilov, Ilya Mironov, and Alexandre Sablayrolles. Defending against reconstruction attacks with r\'enyi differential privacy. *arXiv preprint arXiv:2202.07623*, 2022.

Haixu Tang, X Wang, Shuang Wang, and Xiaoqian Jiang. Idash privacy and security workshop, 2016.

Ardhendu Tripathy, Ye Wang, and Prakash Ishwar. Privacy-preserving adversarial networks. In *2019 57th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pp. 495–505. IEEE, 2019.

Rajagopal Venkatesaramani, Zhiyu Wan, Bradley A Malin, and Yevgeniy Vorobeychik. Defending against membership inference attacks on beacon services. *arXiv preprint arXiv:2112.13301*, 2021.

Rajagopal Venkatesaramani, Zhiyu Wan, Bradley A Malin, and Yevgeniy Vorobeychik. Enabling trade-offs in privacy and utility in genomic data beacons and summary statistics. *Genome Research*, pp. gr–277674, 2023.

Hanshen Xiao and Srinivas Devadas. Pac privacy: Automatic privacy measurement and control of data processing. In *Annual International Cryptology Conference*, pp. 611–644. Springer, 2023.

Xiaokui Xiao and Yufei Tao. Output perturbation with query relaxation. *Proceedings of the VLDB Endowment*, 1(1):857–869, 2008.

Samuel Yeom, Irene Giacomelli, Matt Fredrikson, and Somesh Jha. Privacy risk in machine learning: Analyzing the connection to overfitting. In *2018 IEEE 31st computer security foundations symposium (CSF)*, pp. 268–282. IEEE, 2018.

Zhengli Zhao, Dheeru Dua, and Sameer Singh. Generating natural adversarial examples. In *International Conference on Learning Representations*, 2018.

Da Zhong, Haipei Sun, Jun Xu, Neil Gong, and Wendy Hui Wang. Understanding disparate effects of membership inference attacks and their countermeasures. In *Proceedings of the 2022 ACM on Asia Conference on Computer and Communications Security*, pp. 959–974, 2022.

APPENDIX

A   NOTATIONS

NOTATIONS FOR SECTION 2

Symbol	Description
$U \in [K]$	population of K individuals
$b \in W$	membership vector; W is the membership vector space
$d = (d_k)_{k \in U}$	d_k : data point of individual k
$B = \{b, d\}$	dataset
θ	true prior distribution of membership vector
$f(\cdot)$	(data processing) mechanism without privacy protection
$x \in \mathcal{X}$	output of f; $\mathcal{X}$ is the output space
$\mathcal{A}(\cdot)$	MIA model
$\texttt{Adv}_k(\mathcal{A})$	standard membership advantage of $\mathcal{A}(\cdot)$

NOTATIONS FOR SECTION 3

Symbol	Description
$g_D(\cdot)$	defender's privacy strategy
$\mathcal{M}(\cdot; g_D)$	randomized version of f by g_D
$\rho_D : W \mapsto \Delta(\mathcal{X})$	density function induced by g_D and f
$\texttt{r}(\cdot)$	$x = \texttt{r}(\delta)$ captures the relationship between an output sample x and a noise sample δ
$\texttt{R}(\cdot)$	clipping processing used in output perturbation to ensure the output is within $\mathcal{X}$
σ	attacker's subjective prior
$h_A(\cdot)$	Bayesian attacker's (inference) strategy
$\mathcal{A}(\cdot; h_A, \sigma)$	MIA model given h_A and σ
$\texttt{Adv}^\gamma(h_A, g_D)$	Bayes-weighted membership advantage (BWMA)
$0 < \gamma \le 1$	coefficient weights the attacker's preferences over TPR and FPR
$\ell_A(\cdot)$	loss function of the attacker
$\mathcal{L}_A(g_D, h_A)$	expected loss function of the attacker given g_D and h_A
$\ell_U(\cdot)$	utility loss function of the defender
$\ell_D(\cdot)$	loss function of the defender
$\mathcal{L}_D(g_D, h_A)$	expected loss function of the defender given g_D and h_A
G	non-parameterized neural network generator that represents g_D
H	non-parameterized neural network discriminator that represents h_A
$G_{\lambda_D}(b, \nu)$	generator parameterized by λ_D, where ν is a uniform random variable
$H_{\lambda_A}(x)$	discriminator parameterized by λ_A
$\widetilde{\mathcal{L}}_D(G, H)$	the defender's expected loss given G and H
$\widetilde{\mathcal{L}}_D^\gamma(G, H)$	the attacker's expected loss given G and H
$\widehat{\ell}_A$	binary cross-entropy loss function of the attacker
$\mathcal{L}_{\text{CEL}}$	expected cross-entropy loss function of the attacker

Note that from Equation (4) onward, the notation of the dataset $B = (b, d)$ is simplified to its membership vector b for clarity.

NOTATIONS FOR SECTION 3.2

Symbol	Description
$\text{Proc} \circ \mathcal{M}(b; G)$	post-processing of mechanism $\mathcal{M}$
$\text{Proc} \circ G$	underlying effective randomization device for $\text{Proc} \circ \mathcal{M}(b; G)$
$\mathcal{M}_j(G_j)$	j-th mechanism, where G_j corresponds to g_D^j
$\vec{G} = \{G_1, \cdots, G_n\}$	a profile of $n \geq 1$ generators, with output $\vec{\delta} = (\delta_1, \ldots, \delta_n)$
$\mathcal{M}(\cdot; \vec{G})$	composition of $\mathcal{M}_1(G_1), \ldots, \mathcal{M}_n(G_n)$
$\vec{\rho}_D$	joint density function of $\mathcal{M}(b; \vec{G})$
$\vec{\mathbf{r}}(\cdot)$	$\vec{x} = \vec{\mathbf{r}}(\vec{\delta})$ captures relationship between $\vec{x}$ and $\vec{\delta}$
$\text{DPH}[\vec{G}; \epsilon]$	a set of linear conditions for the attacker's discriminator H, given by (9)

NOTATIONS FOR SECTION 4

Symbol	Description
$\texttt{lrs}(d_x, x)$	log-likelihood ratio statistic defined in Appendix C
α, α_τ	significance level of a hypothesis testing, with threshold τ
β_τ	Type-II error rates given a threshold τ
$L_{\text{Opt-LRT}}^{\alpha}(g_D)$	worst-case privacy loss (WCPL) under optimal α-LRT attack defined in Appendix C
$L_{\text{Adp}}^{\alpha}(g_D)$	WCPL under adaptive α-LRT attack defined in Appendix C
$L_{\text{Fixed}}^{\alpha}(g_D)$	WCPL under fixed α-LRT attack defined in Appendix C
$L_{\text{Bayesian}}^{\sigma}(g_D)$	WCPL under BGP response attacker

B THEORETICAL INSIGHTS AND SUPPLEMENTARY INTUITIONS

B.1 PROPOSITION 1

(**Proposition 1 Restated**). *Suppose $\sigma = \theta$. Then, for any g_D, h_A, and $0 < \gamma \leq 1$, we have $\mathcal{L}_A^\gamma(g_D, h_A) = -\texttt{Adv}^\gamma(h_A, g_D)$.*

The proof of Proposition 1 is given by Appendix F.

The proof of Proposition 1 begins by reformulating the attacker's loss function $\ell_A(s, b, \gamma)$ to explicitly capture the contributions of true positives ($b_k = 1$) and false positives ($b_k = 0$). The weights $(1 - \gamma)$ and $-\gamma$ highlight the balance between the attacker's trade-offs for these cases, directly linking the loss to the attacker's inference strategy $h_A(s|x)$. The expected loss $\mathcal{L}_A(g_D, h_A; \sigma, \gamma)$ is then expressed as an integral over the attacker's strategy $h_A(s|x)$, the defender's output distribution $\rho_D(x|b)$, and the prior distribution $\sigma(b)$ of the membership vector. This formulation ties the attacker's loss to the probabilistic structure of the problem. A key simplification occurs when $\sigma = \theta$, aligning the prior distribution with the true membership distribution. Under this assumption, the expected loss is simplified into terms weighted by $(1 - \gamma)$ and γ, representing probabilities associated with membership inference. Taking the expectation over the defender's output distribution $\rho_D(x|b)$, the proof shows that:

$$\mathcal{L}_A(g_D, h_A; \sigma, \gamma) = -\texttt{Adv}^\gamma(h_A, g_D).$$

This result establishes that minimizing the attacker's expected loss $\mathcal{L}_A$ is equivalent to maximizing their γ-weighted membership advantage. Thus, the proof connects the attacker's strategy to membership advantage within the Bayesian game-theoretic framework.

B.2 PROPOSITION 2

(**Proposition 2 Restated**). *Let g_D and g'_D be two defense strategies, and suppose $\sigma = \theta$. Then, $\texttt{Adv}_k(g_D) \geq \texttt{Adv}_k(g'_D)$ for all $k \in U$ iff $\max_{h_A} \texttt{Adv}^{0.5}(h_A, g_D) \geq \max_{h_A} \texttt{Adv}^{0.5}(h_A, g'_D)$.*

The proof of Proposition 2 is given by Appendix G.

The proof of Proposition 2 establishes the equivalence between individual membership advantages and the optimal Bayes-weighted membership advantage for two defense strategies, g_D and g'_D.

For the *if* direction, the proof assumes $\texttt{Adv}_k(g_D) \geq \texttt{Adv}_k(g'_D)$ for all $k \in U$. By applying the prior probabilities of $b_k = 0$ and $b_k = 1$ to both sides of the inequality and summing over all individuals, it follows that the total membership advantage of g_D is greater than or equal to that of g'_D, completing the *if* direction.

For the *only if* direction, the proof introduces $\texttt{Adv}^*(g_D)$, the maximum Bayes-weighted membership advantage, and $\mathcal{L}^*_A(g_D)$, the corresponding minimal attacker loss. By Proposition 1, $\texttt{Adv}^*(g_D) \geq \texttt{Adv}^*(g'_D)$ is equivalent to $\mathcal{L}^*_A(g_D) \leq \mathcal{L}^*_A(g'_D)$. Using the Blackwell informativeness ordering, the proof shows that g_D is at least as informative as g'_D, and this ordering is independent of the choice of priors. By considering a uniform prior, the optimal Bayes-weighted membership advantage simplifies to $\texttt{Adv}^\dagger(g_D) = \frac{1}{2} \sum_{k \in U} \texttt{Adv}_k(g_D)$. The informativeness ordering ensures no individual $k_0 \in U$ exists such that $\texttt{Adv}_{k_0}(g_D) > \texttt{Adv}_{k_0}(g'_D)$. This concludes the proof of the equivalence.

B.3 THEOREM 1

(**Theorem 1 Restated**). *Let G^* be a BNGP strategy for $\widetilde{\mathcal{L}}_D$ and σ, and let H^* be a BGP response to G^*. Suppose that $\widetilde{\mathcal{L}}_D$ satisfies Assumption 1. Then, for any $G' \in \arg\min_G \widetilde{\mathcal{L}}_D(G, H')$ with $H' \in \arg\min_H \widetilde{\mathcal{L}}^\gamma_A(G', H)$ where $0 < \gamma \leq 1$, and for any $\widehat{H}$, we have:*
(i) $\texttt{TPR}(\widehat{H}, G^*) \leq \texttt{TPR}(H^*, G^*) \leq \texttt{TPR}(H', G')$; (ii) $\texttt{Adv}^{0.5}(\widehat{H}, G^*) \leq \texttt{Adv}^{0.5}(H^*, G^*) \leq \texttt{Adv}^{0.5}(H', G')$;
(iii) $\widetilde{\mathcal{L}}_D(\widehat{H}, G^*) \leq \widetilde{\mathcal{L}}_D(G^*, H^*) \leq \widetilde{\mathcal{L}}_D(G', H')$.

The proof of Theorem 1 is given by Appendix H.

The proof of Theorem 1 establishes that the Bayes-Nash Generative Privacy (BNGP) strategy G^*, when paired with the Bayes-Generative Privacy (BGP) response H^*, achieves optimal privacy-utility trade-offs under the given assumptions. The proof builds on the definitions of expected loss functions and their relationships with posterior beliefs. The proof uses two key definitions. First, the function $Z(g_D, \sigma; V)$ aggregates the expected value of a general function $V(s, b)$ over the posterior belief μ_σ, which is induced by the defender's strategy g_D and prior σ. Second, the function $L(g_D, h_A; V)$ represents the attacker's expected loss under strategy h_A for the same function $V(s, b)$. When $V(s, b) = \ell_A(s, b; \gamma)$, this loss corresponds to the attacker's expected utility $\mathcal{L}_A(g_D, h_A; \sigma, \gamma)$.

By Proposition 7, the expected value $Z(g_D, \sigma)$ coincides with the attacker's loss $L^\sigma(g_D)$ when h_A corresponds to the posterior belief μ_σ. Furthermore, Proposition 8 ensures that every BGP response H^* matches this posterior belief, guaranteeing that the expected loss $\mathcal{L}_A(G, H^*; \sigma, \gamma)$ is minimized. This implies that the adversary's membership advantage $\texttt{Adv}(H^*, \sigma, \theta, 0.5; G^*)$ is smaller than or equal to that of any other strategy H'. The proof then extends this result to the defender's utility by considering $V(s, b) = v(s, b; \gamma)$. Since the BGP response minimizes the expected loss for this utility function, the corresponding true positive rate (TPR) satisfies $\texttt{TPR}(G^*, H^*) \leq \texttt{TPR}(G', H')$, where G' is any other privacy strategy and H' is its corresponding best response.

These results collectively establish the inequalities in parts (i), (ii), and (iii) of the theorem, confirming that the BNGP strategy G^*, coupled with the BGP response H^*, achieves optimal privacy-utility trade-offs.

B.4 PROPOSITION 3

(**Proposition 3 Restated**). *Suppose that G has BGP risk $H \in \arg\min_H \mathcal{L}_{\text{CEL}}(G, H)$ and $\widehat{\mathcal{L}}^\sigma_A(G, H)$. Suppose in addition that for any Proc, Proc $\circ$ G has BGP risk $H' \in \arg\min_H \mathcal{L}_{\text{CEL}}(\text{Proc} \circ G, H)$. Then, $\mathcal{L}_{\text{CEL}}(\text{Proc} \circ G, H') \geq \mathcal{L}_{\text{CEL}}(G, H)$.*

The proof of Proposition 3 is given by Appendix I.

Proposition 3 establishes that applying a post-processing function Proc to a defender's privacy strategy G cannot decrease the Bayes Generative Privacy (BGP) risk. This property aligns with the principle that post-processing cannot increase the informativeness of a mechanism.

The proof relies on Blackwell's informativeness ordering. By Theorem 2.10 of (Dong et al., 2021) (see also (Blackwell, 1951)), for any fixed significance level, the minimum false positive rates for inferring each individual's membership status are denoted by $T(G)$ and $T(\text{Proc} \circ G)$ when using G and Proc $\circ$ G, respectively. It is shown that $T(\text{Proc} \circ G) \geq T(G)$, meaning that G is at least as informative as Proc $\circ$ G. According to Theorem 1 of (de Oliveira, 2018), Blackwell's informativeness ordering implies that the attacker's minimum expected loss for the post-processed mechanism Proc $\circ$ G satisfies $\widehat{\mathcal{L}}^\sigma_A(\text{Proc} \circ G, H') \geq \widehat{\mathcal{L}}^\sigma_A(G, H)$. Therefore, the post-processing property ensures that applying Proc to G does not reduce the attacker's expected loss, confirming the proposition.

B.5 PROPOSITION 4

(**Proposition 4 Restated**). *Suppose that $\mathcal{M}(\vec{G})$ is a composition of n mechanisms with arbitrary correlation. Then, we have, for $H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(\vec{G}, H)$, $H_j^* \in \arg\min_{H_j} \mathcal{L}_{\text{CEL}}(G_j, H_j)$ for all $j \in [n]$,*

$$\mathcal{L}_{\text{CEL}}(\vec{G}, \vec{H}^*) = \sum_{j=1}^{n} \mathcal{L}_{\text{CEL}}(G_j, H_j^*) - \Lambda(\vec{G}, \theta).$$

If mechanisms are independent, *then* $\Lambda(\vec{G}, \theta) = -\sum_b \theta(b) \int_{\vec{\mathcal{X}}} \vec{\rho}_D(\vec{x}|b) \cdot \log\left(\sum_{b'} \vec{\rho}_D(\vec{x}|b')\theta(b')\right) d\vec{x}$. *If mechanisms are* correlated, $\Lambda(\vec{G}, \theta) = -\sum_b \theta(b) \int_{\vec{\mathcal{X}}} \vec{\rho}_D(\vec{x}|b) \log\left(\frac{\sum_{b'} \vec{\rho}_D(\vec{x}|b')\theta(b')}{P(\vec{x})}\right) d\vec{x}$, *where* $P(\vec{x}) = \prod_{j=1}^{n} \sum_{b'} \int_{\vec{\mathcal{X}}_{-j}} \vec{\rho}_D(x_j, \vec{x}_{-j}|b')\theta(b') d\vec{x}_{-j}$.

The proof of Proposition 4 is given by Appendix J.

For independent mechanisms, the total BGP risk decomposes cleanly into the sum of individual mechanism risks. The interaction term $\Lambda(\vec{G}, \theta)$ reflects the joint contribution to the risk but simplifies due to the independence of outputs. This independence ensures that the attacker's best response to each mechanism depends solely on its marginal posterior distribution, making the overall composition straightforward to analyze. For correlated mechanisms, $\Lambda(\vec{G}, \theta)$ explicitly accounts for dependencies among outputs by incorporating joint densities and marginal probabilities. The joint posterior distribution $\mu_\theta(b|\vec{x})$ aligns the attacker's best response with the interdependent outputs of the mechanisms. This dependency modifies the interaction term and ensures that the total BGP risk reflects both individual risks and the additional information provided by the correlation.

B.6 PROPOSITION 5

(**Proposition 5 Restated**). *Let $\vec{G}^* = \{G_1^*, \ldots, G_n^*\}$. Let $\mathcal{M}(\vec{G}^*)$ be a composition of $n \geq 1$ mechanisms with arbitrary correlation, where each G_j^* is BNGP strategies for some $\widetilde{\mathcal{L}}_D^j$ satisfying Assumption 1. Then, $\mathcal{M}(\vec{G}^*)$ is (ϵ, ξ)-DP for some $\epsilon \geq 0$ and $\xi \in [0, 1]$.*

The proof of Proposition 5 is given by Appendix K.

The proof demonstrates that the composition $\mathcal{M}(\vec{G}^*)$ satisfies (ϵ, ξ)-differential privacy by applying the properties of likelihood-ratio tests and f-DP. The proof uses the properties of likelihood-ratio tests and trade-off functions to establish f-DP guarantees, which are subsequently converted to (ϵ, ξ)-DP guarantees, ensuring that the composition mechanism satisfies differential privacy even under arbitrary correlations.

Using the Neyman-Pearson lemma Neyman & Pearson (1933), the likelihood-ratio test is identified as the Uniformly Most Powerful (UMP) test for distinguishing between the two hypotheses $\mathcal{H}_0^k$ and $\mathcal{H}_1^k$, which correspond to whether an individual's data is included in the dataset. This establishes a fundamental relationship between the test's significance level α^k and the corresponding rejection rule ϕ. The symmetric trade-off function $\mathbf{f}(\alpha^k)$ introduced in Dong et al. (2022) is then used to relate the false positive and false negative rates of this hypothesis test. The function $\mathbf{f}(\alpha^k)$ has key properties, such as convexity, continuity, and monotonicity, which make it suitable for capturing the privacy guarantees of the mechanism. By employing results from the f-DP framework, the privacy guarantees of $\mathcal{M}(\vec{G}^*)$ as f-DP are translated into (ϵ, ξ)-DP guarantees. Specifically, the composition satisfies (ϵ^k, ξ^k)-DP for individual components, where ξ^k is a function of ϵ^k. Aggregating these guarantees across all components ensures that $\mathcal{M}(\vec{G}^*)$ satisfies (ϵ, ξ)-DP for some $\epsilon \geq 0$ and $\xi \in [0, 1]$.

B.7 PROPOSITION 6

(**Proposition 6 Restated**). *For any $\vec{G} = \{G_1, G_2, \ldots, G_n\}$ and $\epsilon \geq 0$, the composition $\mathcal{M}(\vec{G})$ is ϵ-DP iff all the BGP responses $H^* \in \text{DPH}[\vec{G}; \epsilon] \neq \emptyset$.*

The proof of Proposition is given by Appendix L.

This proposition establishes a necessary and sufficient condition for a composition of mechanisms, $\mathcal{M}(\vec{G})$, to satisfy ϵ-differential privacy (DP). The core insight is the equivalence between ϵ-DP of the mechanism and the properties of its best-response discriminators, known as BGP responses. Specifically, $\mathcal{M}(\vec{G})$ is ϵ-DP if and only if all BGP responses satisfy the conditions defined by $\text{DPH}[\vec{G}; \epsilon]$. This bridges the classical notion of ϵ-DP with the Bayesian framework by characterizing privacy guarantees in terms of adversarial inference strategies. This result demonstrates the consistency between classical differential privacy and the Bayesian game-theoretic approach, showing that ϵ-DP can be fully characterized through BGP responses. This provides a powerful perspective on privacy guarantees, uniting two complementary frameworks while maintaining rigorous mathematical consistency.

The proof leverages the posterior distribution $\mu_\theta(b|\vec{x})$ induced by $\vec{G}$ and the prior θ. If $\text{BDP}[\vec{G}; \epsilon] \neq \emptyset$, this posterior distribution satisfies the conditions for ϵ-DP as specified by $\text{DPH}[\vec{G}; \epsilon]$. By the necessary and sufficient conditions established in (Dwork et al., 2006), this implies that $\vec{G}$ is ϵ-DP. Conversely, if $\vec{G}$ is ϵ-DP, the posterior distribution must also meet these conditions, ensuring that all BGP responses belong to $\text{DPH}[\vec{G}; \epsilon]$. The extension of Proposition 8 in Appendix H guarantees that the optimal BGP response aligns with the posterior induced by $\vec{G}$, which completes the equivalence.

B.8 THEOREM 2

(**Theorem 2 Restated**). *Fix any g_D and α. If $\sigma \in \Delta(W)$ is an* aligned prior*, then:*

$$L_{\text{Bayesian}}^\sigma(g_D) \geq L_{\text{Opt-LRT}}^\alpha(g_D) \geq L_{\text{Adp}}^\alpha(g_D) \geq L_{\text{Fixed}}^\alpha(g_D).$$

If σ is strictly aligned*, then $L_{\text{Bay}}^\sigma(g_D) > L_{\text{Opt-LRT}}^\alpha(g_D)$.*

The proof of Theorem 2 is given by Appendix M.

Theorem 2 establishes a hierarchy of worst-case privacy losses incurred by the defender under different attacker models: Bayesian, optimal α-LRT, adaptive α-LRT, and fixed-threshold α-LRT. It asserts that the Bayesian attacker leads to the highest loss when the prior σ is aligned, and the Bayesian loss strictly exceeds the optimal α-LRT loss if σ is strictly aligned.

The proof hinges on several key insights. First, Lemma 4 demonstrates that when σ is aligned, a Bayesian attacker using the posterior belief μ_σ as a best-response strategy minimizes its loss. Lemma 5 further shows that the Bayesian attacker cannot perform worse than the optimal α-LRT under the same defense strategy g_D. This is achieved by leveraging the relationship between the Bayesian attacker's posterior and the likelihood ratio statistic of the α-LRT, ensuring that the Bayesian strategy captures a broader range of risks. For non-informative priors, the proof verifies that the Bayesian attacker still outperforms α-LRTs by demonstrating that any α-LRT strategy can be virtually represented as a special case of the Bayesian framework with uniform prior. The hierarchy of losses for adaptive and fixed-threshold α-LRTs follows directly from the Neyman-Pearson lemma and existing results in the literature (Venkatesaramani et al., 2021; 2023). These results highlight the robustness of the Bayesian approach in capturing privacy risks across various attacker models and priors.

C EXISTENCE FREQUENTIST ATTACK MODELS

Likelihood Ratio Test Attacks MIAs targeting genomic summary data releases are often framed as hypothesis testing problems (Sankararaman et al., 2009; Shringarpure & Bustamante, 2015; Raisaro et al., 2017; Venkatesaramani et al., 2021; 2023), where for each individual $k \in U$, the attacker tests $H_0^k : b_k = 1$ (i.e., the individual k is in the dataset) versus $H_1^k : b_k = 0$ (i.e., the individual k is not). Additionally, $\bar{p}_j$ denotes the frequency of the alternate allele at the j-th SNV in a reference population that is not included in the dataset B.

First, assume $\delta = 0$. The attacker is assumed to have external knowledge of the genomic data for individuals $[K]$, in the form of $\bar{p} = (\bar{p}_j)_{j \in Q}$ and $d = (d_{kj})_{k \in [K], j \in Q}$. The *log-likelihood ratio statistic* (LRS) for each individual k is given by (Sankararaman et al., 2009):

$$\texttt{lrs}(d_k, x) = \sum_{j \in Q} \left(d_{kj} \log \frac{\bar{p}_j}{x_j} + (1 - d_{kj}) \log \frac{1 - \bar{p}_j}{1 - x_j} \right).$$

An *LRT attacker* performs MIA by testing H_0^k against H_1^k using $\texttt{lrs}(d_k, x)$ for each $k \in [K]$. The null hypothesis H_0^k is rejected in favor of H_1^k if $\texttt{lrs}(d_k, x) \leq \tau$ for a threshold τ, and H_0^k is accepted if $\texttt{lrs}(d_k, x) > \tau$.

Let $P_0^k(\cdot) \equiv \Pr(\cdot|H_0^k)$ and $P_1^k(\cdot) \equiv \Pr(\cdot|H_1^k)$ denote the probability distributions under H_0 and H_1, respectively.

Definition 6 ((α_τ, β_τ)-LRT Attack). *An attacker performs $(\alpha_\tau, \beta_\tau)$-LRT Attack if $P_0^k(\texttt{lrs}(d_k, x) \leq \tau) = \alpha_\tau$ and $1 - P_1^k(\texttt{lrs}(d_k, x) \leq \tau) = \beta_\tau$, for all $k \in U$, where α_τ is the* significance level *and $1 - \beta_\tau$ is the* power *of the test with the* threshold τ.

Define the trade-off function (Dong et al., 2021), $T[P_0^k, P_1^k](\alpha) \equiv \inf_\tau \{\beta_\tau : \alpha_\tau \leq \alpha\}$. By Neyman-Pearson lemma (Neyman & Pearson, 1933), the LRT test is the uniformly most powerful (UMP) test for a given significance level. Specifically, for a given α_τ, there exists a threshold τ^* such that no other test with $\alpha_\tau \leq \alpha_{\tau^*}$ can achieve a strictly smaller $\beta_\tau < \beta_{\tau^*}$. Hence, $T[P_0^k, P_1^k](\alpha_{\tau^*}) = \beta_{\tau^*}$, for all $k \in U$. We refer to an α-LRT as a UMP (α, β)-LRT and will interchangeably add or omit the corresponding threshold notation as needed.

From the vNM defender's perspective, the expected privacy losses under an α-LRT attack, without and with defense g_D, respectively, are given by

$$L^o(\tau^o, \alpha) \equiv \mathbb{E}\left[v(\tilde{s}, \tilde{b})\Big|\alpha\right] = \sum_k P_1^k\left[y_k(f(b, z), \tau^o) = 1\right]\theta(b_k = 1) = \sum_k (1 - \beta_{\tau^o})\theta(b_k = 1),$$

$$L(g_D, \tau^o, \alpha) \equiv \mathbb{E}\left[v(\tilde{s}, \tilde{b})\Big|g_D, \tau^o, \alpha\right] = \sum_k P_1^k\left[y_k(r, \tau^o) = 1|g_D\right]\theta(b_k = 1),$$

where $y_k(x, \tau^o) \equiv \mathbf{1}\{\mathtt{lrs}(d_k, x) \geq \tau^o\}$ is the indicator function for the likelihood ratio statistic, and $P_1^k[y_k(r, \tau^o) = 1|g_D] \equiv \int_r \mathbf{1}\{y_k(r, \tau^o) = 1\}\rho_D(r|b)dr$. Here, τ^o is the threshold associated with the α-LRT.

Fixed-Threshold LRT Attack (Sankararaman et al., 2009; Shringarpure & Bustamante, 2015; Venkatesaramani et al., 2021; 2023) A *fixed(-threhsold)* LRT attacker performs MIA without accounting for any privacy defense strategies. Such an attacker selects a fixed threshold τ^o that balances Type-I and Type-II errors, resulting in a UMP α-LRT test in the absence of defense. This approximation can be achieved by simulating Beacons on publicly available datasets or synthesized data using alternate allele frequencies (AAFs) Venkatesaramani et al. (2023).

Given a fixed threshold τ^o, let

$$L_{\text{Fixed}}^\alpha(g_D) \equiv L(g_D, \tau^o, \alpha_{\tau^o})$$

The defender's optimal strategy against the naive α_{τ^o}-LRT attack is given by solving:

$$\min_{g_D} L_{\text{Fixed}}^\alpha(g_D) + \kappa\mathbb{E}\left[\ell_U(\|\delta\|_{\mathbf{p}})\|g_D, \tau^o, \alpha_{\tau^o}\right], \qquad \text{(FixedLRT)}$$

where $\mathbb{E}\left[\ell_U(\|\delta\|_{\mathbf{p}})\|g_D, \tau^o, \alpha_{\tau^o}\right]$ is induced expected utility loss.

Let $\beta^k(\tau, g_D, \alpha) \equiv 1 - P_1^k[y_k(r, \tau) = 1|g_D]$ denote the actual Type-II error under the defense strategy g_D for the naive α-LRT attack. The defender can reduce privacy loss by choosing g_D to increase $\beta^k(\tau, g_D, \alpha)$ for all $k \in U$. For the defense strategy $g_D^\dagger$ that solves (FixedLRT) to be effective in reducing privacy loss, it must be implemented in a *stealthy* manner.

Adaptive-Threshold LRT Attack (Venkatesaramani et al., 2021; 2023) In an *adaptive-threshold LRT* attack, the attacker is aware of the defense strategy and attempts to distinguish individuals in U from those in the reference population $\bar{U}$ (individuals not in U). Let $\bar{U}^{(N)} \subset \bar{U}$ represent the set of N individuals in $\bar{U}$ with the lowest LRS values. The *adaptive threshold* is defined as $\tau^{(N)}(x) = \frac{1}{N}\sum_{i \in \bar{U}^{(N)}}\mathtt{lrs}(d_i, x)$. The null hypothesis H_0 is rejected if $\mathtt{lrs}(d_k, x) \leq \tau^{(N)}(x)$.

The defender's problem is then:

$$\min_{g_D} L_{\text{Adp}}^{\alpha_{\tau^{(N)}(x)}}(g_D) + \mathbb{E}\left[\ell_U(\|\delta\|_{\mathbf{p}})\Big|g_D, \tau^{(N)}(x), \alpha_{\tau^{(N)}(x)}\right], \qquad \text{(AdaptLRT)}$$

where $\alpha_{\tau^{(N)}(x)}$ is the Type-I error associated with the adaptive threshold $\tau^{(N)}(x)$, and

$$L_{\text{Adp}}^{\alpha_{\tau^{(N)}(x)}}(g_D) \equiv L(g_D, \tau^{(N)}(x), \alpha_{\tau^{(N)}(x)}).$$

The WCPL $L_{\text{Adp}}^{\alpha_{\tau^{(N)}(x)}}(g_D)$ in Section 4 has $\mathbb{E}[\alpha_{\tau^{(N)}(\tilde{r})}] = \alpha$.

Optimal LRT Attack Let $P_0^k(g_D) = P_0^k[\cdot|g_D]$ and $P_1^k(g_D) = P_1^k[\cdot|g_D]$ denote the probability distributions under H_0^k and H_1^k, respectively, in the presence of defense g_D. The *worst-case privacy loss* (WCPL) for the defender occurs when the attacker's hypothesis test achieves $\beta^k(\tau^*, g_D, \alpha) = T[P_0^k(g_D), P_1^k(g_D)](\alpha)$ for some threshold τ^*, corresponding to a UMP test under g_D. We refer to these as *optimal α-LRT attacks*.

The defender's optimal strategy against such attacks solves the following problem:

$$\min_{g_D} L_{\text{Opt-LRT}}^\alpha(g_D) + \kappa\mathbb{E}\left[\ell_U(\|\delta\|_{\mathbf{p}})\|g_D, \tau^*, \alpha\right],$$
$$\text{s.t.} \quad \beta^k(\tau^*, g_D, \alpha) = T[P_0^k(g_D), P_1^k(g_D)](\alpha), \qquad \text{(OptLRT)}$$

where

$$L_{\text{Opt-LRT}}^\alpha(g_D) \equiv L(g_D, \tau^*, \alpha).$$

By the Neyman-Pearson lemma, the α-LRT with likelihood ratio statistics $\mathtt{lrs}(d_k, r; g_D) \equiv \sum_{j \in Q} \frac{\rho_D(r|b_k=0, b_{-k})}{\rho_D(r|b_k=1, b_{-k})}$ for all $k \in U$ is optimal, attaining $\beta^k(\tau^*, g_D, \alpha) = T[P_0^k(g_D), P_1^k(g_D)](\alpha)$.

Furthermore, the defense g_D obtained by solving (OptLRT) is robust against adaptive-threshold LRT attacks.

D GAUSSIAN DEFENSE STRATEGIES

In this section, we consider g_D is a Gaussian mechanism and study the comparison between the σ-Bayesian attack and the α-LRT attack when σ is an arbitrary subjective prior.

Define $g_D(\delta|b) = \prod_{j \in Q} g_D^j(\delta_j|b)$, where $g_D^j(\cdot|b)$ is the density function of a Gaussian distribution $\mathcal{N}(\mathtt{M}_b^j, \mathtt{V}^j)$ with mean $\mathtt{M}_b^j$ and variance $\mathtt{V}^j$ for each $b \in U$ and $j \in Q$. Let $y = x + \delta = (x_j + \delta_j)_{j \in Q} \in \mathcal{Y}$, where $y_j = x_j + \delta_j \in \mathcal{Y}_j$. The resulting conditional probability distribution is denoted by $\rho_D(\cdot|b) \in \Delta(\mathcal{Y})$. Let $b_{[0]}^k$ and $b_{[1]}^k$ represent two *adjacent* membership vectors that differ only in individual k's value, where $b_k = 0$ in $b_{[0]}^k$ and $b_k = 1$ in $b_{[1]}^k$. The maximum conditional probability of $s_k = 0$ given $b_k = 1$ is defined as $\mu_{0|1}^\sigma[|Q|] \equiv \max_{k \in U} \sum_{s_{-k}} \int_y \mu_\sigma(s_k = 0|y)\rho_D(y|b_{[1]}^k) \, dy$, where the posterior belief μ_σ is induced by g_D and σ. For a Type-I error rate $\widehat{\alpha}$, let $\widehat{\beta}$ represent the minimum Type-II error rate achievable.

Lemma 1. *Define* $\mathcal{F}(\alpha, \beta) \equiv \frac{(z_\alpha + z_\beta)^2 \overline{\mathtt{V}}}{4\overline{\mathtt{M}}^2}$, *where* z_a *is the* $100(1 - a)$*-th percentile of the standard normal distribution*, $\overline{\mathtt{M}} = \frac{1}{2}\sum_{j \in Q} \widehat{\mathtt{M}}_j^2$, *and* $\overline{\mathtt{V}} = \sum_{j \in Q} \widehat{\mathtt{M}}_j^2$. *Then the following holds:*

(i) $\mathcal{F}(\widehat{\alpha}, \widehat{\beta}) = |Q|$. (ii) *For a fixed* $\widehat{\alpha}$, *as* $|Q|$ *increases (resp. decreases)*, $\widehat{\beta}$ *decreases (resp. increases)*.

Theorem 3. *Let* g_D *be a Gaussian mechanism with each* $g_D^j(\cdot|b) \in \Delta(\mathcal{Y}_j)$ *following* $\mathcal{N}(\mathtt{M}_b^j, \mathtt{V}^j)$ *for any* $b \in W$. *Suppose* $\mathtt{V}^j = \left(\frac{|Q|}{K^\dagger \widehat{\mathtt{M}}_j}\right)^2$ *for all* $j \in Q$, *where* $1 \leq K^\dagger \leq K$ *is the minimum number of individuals involved in B. Additionally, assume* $\max_{b,b'} |\mathtt{M}_b^j - \mathtt{M}_{b'}^j| \leq \frac{|Q|}{K^\dagger}$, *where the maximum is taken over all adjacent membership vectors. Then, for any* Q *with* $|Q| \geq 1$ *and any subjective prior* σ, *if* $\mathcal{F}(\alpha, \mu_{0|1}^\sigma[|Q|]) \geq |Q|$, *it holds that* $L(g_D, \tau^*, \alpha) \leq L^\sigma(g_D)$; *if* $\mathcal{F}(\alpha, \mu_{0|1}^\sigma[|Q|]) \leq |Q|$, *it holds that* $L(g_D, \tau^*, \alpha) \geq L^\sigma(g_D)$.

Theorem 3 provides conditions under which the σ-Bayesian attack outperforms or underperforms the α-LRT attack in Gaussian mechanisms, even when σ is an arbitrary subjective prior independent of the true prior q. For any α, let $1 - \beta_{|Q|}^\alpha$ denote the power of the α-LRT attack, and define $m^\alpha = \mathcal{F}(\alpha, \mu_{0|1}^\sigma[|Q|])$ as the number of SNVs used in the summary statistics such that $1 - \beta_{|Q|}^\alpha = 1 - \mu_{0|1}^\sigma[|Q|]$, i.e., the power of the α-LRT matches the worst-case true positive rate (TPR) of the σ-Bayesian attack. By Lemma 1, as m increases, β^α decreases. When $m^\alpha \geq |Q|$, the actual power $1 - \beta_{|Q|}^\alpha \leq 1 - \mu_{0|1}^\sigma[|Q|]$. Thus, by Proposition 7 in Appendix M, the lowest TPR achievable by the σ-Bayesian attacker exceeds the best power of the α-LRT. Consequently, $L(g_D, \tau^*, \alpha) \leq L^\sigma(g_D)$. Similarly, when $\mathcal{F}(\alpha, \mu_{0|1}^\sigma[|Q|]) \leq |Q|$, the actual $\beta_{|Q|}^\alpha \leq \mu_{0|1}^\sigma[|Q|]$, thus we have $L(g_D, \tau^*, \alpha) \geq L^\sigma(g_D)$.

Based on the sensitivity of f (see the proof at Appendix O for details), Theorem 3 considers the worst-case bound of the powers of the LRT attack when the attacker knows the membership of every individual in the dataset except for a single individual. This bound is evaluated over all possible input membership vectors. Notably, the comparison in Theorem 3 is independent of the true prior distributions $q = (q_k)_{k \in U}$ of the membership vectors and does not rely on specific true membership vectors forming the Beacon dataset.

When $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) < m$, the lowest true positive rate (TPR) of the σ-Bayesian attacker is strictly smaller than the best power of the α-LRT attacker. However, this does not guarantee that every TPR of the σ-Bayesian attacker is smaller than every power of the α-LRT attacker across different Beacon datasets. Therefore, $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) < m$ generally cannot imply that $L(g_D, \tau^*, \alpha) > L^\sigma(g_D)$. Moreover, the condition $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) \geq m$ is not necessary. That is, $L(g_D, \tau^*, \alpha) \leq L^\sigma(g_D)$ does not imply $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) \geq m$ for any arbitrary subjective prior σ. We can also conclude that the sufficient condition in Theorem 3 is not applied only to aligned subjective priors. The following corollary directly follows Theorem 3.

Corollary 1. *Given a Gaussian mechanism* g_D *with* Q, *if the number of SNVs of the Beacon dataset satisfies* $|Q| \leq \mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[|Q|]\right)$, *then the mechanism* g_D *that is optimal to the* σ-Bayesian attacks with any arbitrary σ *is guaranteed to be robust to any optimal* α-LRT attacks.

In this section, we relax Theorem 3 and study the comparison between the Bayesian attacks with arbitrary subjective priors and the optimal LRT attacks without considering the worst-case bound of the powers of the LRT attacks. Suppose in addition that the number of individuals involved in the Beacon dataset is fixed to be $0 < n < K$. For ease of exposition, we consider the noises added to all SNVs to be iid. Consider a Gaussian mechanism $g_D(\delta|b) = \prod_{j \in Q} g_D^j(\delta_j|b)$, where each $g_D^j(\cdot|b)$ is the density function of $\mathcal{N}(\mathtt{M}_b, \mathtt{V})$. Let two adjacent membership vectors $b_0^{[k]}$ and $b_1^{[k]}$ differing in individual k's b_k, where $b_0^{[k]}$ has $b_k = 0$ and $b_1^{[k]}$ has $b_k = 1$. Define two hypotheses: $H_0^{[k]}$: the true membership is $b_0^{[k]}$ vs. $H_1^{[k]}$: the true membership is $b_1^{[k]}$. For any $k \in U$, it is straightforward to see that each $\tilde{y}_j = \tilde{x}_j + \tilde{\delta}_j$ is a Gaussian random variable. That is, $\tilde{y}_j \sim \mathcal{N}(\mathtt{M}_0 + x_j^0, \mathtt{V})$ under $H_0^{[k]}$ and $\tilde{y}_j \sim \mathcal{N}(\mathtt{M}_1 + x_j^1, \mathtt{V})$ under $H_1^{[k]}$, where $\mathtt{M}_i = \mathtt{M}_{b_i^{[k]}}$ and $x_j^i = f(b_i^{[k]}, d_i)$ is the unperturbed summary statistics given $b_i^{[k]}$ with d_i, for $i \in \{0, 1\}$. Then, given any $(b_0^{[k]}, b_1^{[k]})$, the power

of the optimal α-LRT performed upon the observation y_j for all $j \in Q$ can be obtained as

$$T(\mathcal{N}(\mathtt{M}_0 + x_j^0, \mathtt{V}), \mathcal{N}(\mathtt{M}_1 + x_j^1, \mathtt{V}))(\alpha) = \Phi\left(\Phi^{-1}(1-\alpha) - \frac{|\mathtt{M}_1 - \mathtt{M}_0 + x_j^1 - x_j^0|}{\sqrt{\mathtt{V}}}\right),$$

where Φ is the cumulative distribution function (CDF) of the standard normal distribution.

Under the assumption of linkage equilibrium (i.e., each SNV is independent of the others), the power of the optimal α-LRT performed upon $y = (y_j)_j$ can be obtained by the tensor product of $|Q|$ trade-off functions Dong et al. (2021). In particular, the power can be represented by

$$T\left(\times_{j \in Q} \mathcal{N}(\mathtt{M}_0 + x_j^0, \mathtt{V}), \times_{j \in Q} \mathcal{N}(\mathtt{M}_1 + x_j^1, \mathtt{V})\right)(\alpha) = T\left(\mathtt{N}_0^{[k]}, \mathtt{N}_1^{[k]}\right)(\alpha),$$

where $\mathtt{N}_0^{[k]} = \mathcal{N}(\mathtt{M}_0 + x_1^0, \ldots, \mathtt{M}_0 + x_{|Q|}^0, \Sigma(\mathtt{V}))$ and $\mathtt{N}_1^{[k]} = \mathcal{N}(\mathtt{M}_1 + x_1^1, \ldots, \mathtt{M}_0 + x_{|Q|}^1, \Sigma(\mathtt{V}))$, in which $\Sigma(\mathtt{V})$ is a $|Q| \times |Q|$ diagonal matrix where each principal diagonal element is $\mathtt{V}$. The Mahalanobis distance for the joint distributions is

$$d_{\Sigma(V)}\left((\mathtt{M}_0 + x_1^0, \ldots, \mathtt{M}_0 + x_{|Q|}^0), (\mathtt{M}_1 + x_1^1, \ldots, \mathtt{M}_1 + x_{|Q|}^1)\right) = \sqrt{\sum_{j \in Q} \frac{\left(\mathtt{M}_1 - \mathtt{M}_0 + x_j^1 - x_j^0\right)^2}{\mathtt{V}}}.$$

Therefore, we have

$$T\left(\mathtt{N}_0^{[k]}, \mathtt{N}_1^{[k]}\right)(\alpha) = \Phi\left(\Phi^{-1}(1-\alpha) - \sqrt{\sum_{j \in Q} \frac{\left(\mathtt{M}_1 - \mathtt{M}_0 + x_j^1 - x_j^0\right)^2}{\mathtt{V}}}\right)$$

$$= T\left(\mathcal{N}(0,1), \mathcal{N}(\mathtt{M}_{eq}[b_0^{[k]}, b_1^{[k]}], 1)\right)(\alpha),$$

where $\mathtt{M}_{eq}[b_0^{[k]}, b_1^{[k]}] = \sqrt{\sum_{j \in Q} \frac{\left(\mathtt{M}_1 - \mathtt{M}_0 + x_j^1 - x_j^0\right)^2}{\mathtt{V}}}$, in which we show $[b_0^{[k]}, b_1^{[k]}]$ to indicate that the trade-off function is based on $b_0^{[k]}$ and $b_1^{[k]}$.

Let $b_0^{[k]} = (b_k = 0, \hat{b}_{-k})$ and $b_1^{[k]} = (b_k = 1, \hat{b}_{-k})$. Define

$$\beta(\alpha, q) \equiv \sum_{b_k, \hat{b}_{-k}} T\left(\mathcal{N}(0,1), \mathcal{N}(\mathtt{M}_{eq}[b_0^{[k]}, b_1^{[k]}], 1)\right)(\alpha) q_k(b_k) q_{-k}(\hat{b}_{-k}),$$

and

$$\mu_{0|1}(\sigma, q) \equiv \sum_{b_k, \hat{b}_{-k}} \sum_{s_{-k}} \int_y \mu_\sigma(s_k = 0|y) \rho_D(y|b_k = 1, \hat{b}_{-k}) dy \, q_k(b_k) q_{-k}(\hat{b}_{-k}).$$

In addition, define

$$\Delta(\alpha, \sigma, q) \equiv \mu_{0|1}(\sigma, q) - \beta(\alpha, q).$$

The following corollary is straightforward.

Corollary 2. *Let $g_D(\delta|b) = \prod_{j \in Q} g_D^j(\delta_j|b)$ be a Gaussian mechanism, where each $g_D^j(\cdot|b)$ is the density function of $\mathcal{N}(\mathtt{M}_b, \mathtt{V})$. Then, $L(g_D, \tau^*, \alpha) \le L^\sigma(g_D)$ if and only if $\Delta(\alpha, \sigma, q) \ge 0$.*

Corollary 2 represents shows a condition for $L(g_D, \tau^*, \alpha) \le L^\sigma(g_D)$ when the Bayesian attacker's subjective prior σ is arbitrary. Here, $1 - \beta(\alpha, q)$ is the expected power of the α-LRT attacker perceived by the vNM defender, while $1 - \mu_{0|1}$ is the expected posterior beliefs of $\{s_k = 1\}_{k \in U}$. Thus, $\Delta(\alpha, \sigma, q) \ge 0$ implies that the expected accuracy of inferring $\{s_k = 1\}$ using the posterior beliefs is higher than the expected power of the σ-LRT. By Proposition 7, we have that the Bayesian strategy that mirrors the posterior belief leads to the WCPL. Therefore, given any ρ_D and the true prior q, $\Delta(\alpha, \sigma, q) \ge 0$ is equivalent to $L(g_D, \tau^*, \alpha) \le L^\sigma(g_D)$. This condition is independent of the sensitivity of f but depends on g_D and the true prior q.

D.1 LRT vNM DEFENDER

We use $g_\mathtt{N}$, $g_\mathtt{Adp}$, and $g_\mathtt{Opt}$ to denote the typical solutions to (FixedLRT), (AdaptLRT) and (OptLRT), respectively. Suppose that all $g_\mathtt{N}$, $g_\mathtt{Adp}$, and $g_\mathtt{Opt}$ are Gaussian mechanisms. We refer to the defender using $g_\mathtt{N}$, $g_\mathtt{Adp}$, and $g_\mathtt{Opt}$, respectively, as the naive, adaptive, and optimal *LRT vNM defender*. Then, the WCPL is captured by the power of the UMP test given a significant level α. Due to the Neyman-Pearson lemma, the WCPL is the power or the TPR of the optimal α-LRT, $1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$.

Corollary 3. *Fix any g_D and α. Let $\mathtt{TPR}(g_D, \sigma)$ denote the maximum TPR can be obtained by a σ-Bayesian attacker under g_D. Suppose that g_D is chosen such that the WCPL is $1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$. Then, the following hold.*

> *(i) If σ is an informative or non-informative prior, then $\text{TPR}(g_D, \sigma) \geq 1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$.*
>
> *(ii) Suppose that g_D is Gaussian as described in Theorem 3. If $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) \geq m$, then $\text{TPR}(g_D, \sigma) \geq 1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$. If $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) < m$, then $\text{TPR}(g_D, \sigma) < 1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$.*

Part *(i)* of Corollary 3 follows Theorem 2. In particular, from Theorem 2 we have $L^\sigma(g_D) \geq L(g_D, \tau^*, \alpha)$ for aligned subjective priors. Hence, $\text{TPR}(g_D, \sigma) \geq 1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$. Part *(ii)* of Corollary 3 follows Theorem 3. If $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) \geq m$, Theorem 3 implies that $L(g_D, \tau^*, \alpha) \leq L^\sigma(g_D)$, which gives $\text{TPR}(g_D, \sigma) \geq 1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$. If $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[m]\right) < m$, then $L(g_D, \tau^*, \alpha) > L^\sigma(g_D)$, which implies $\text{TPR}(g_D, \sigma) < 1 - T[P_0^k(g_D), P_1^k(g_D)](\alpha)$.

E DIFFERENTIAL PRIVACY

Standard Differential Privacy Differential privacy Dwork et al. (2006); Dwork (2006) is a widely used data privacy preservation technique based on probabilistic distinguishability. Formally, we say a randomized mechanism F is (ϵ, ϱ)-differentially private if for any two adjacent dataset D and D' differing in only one entry if holds that

$$P\left(F((\text{D}')) \in \mathcal{F}\right) \leq e^\epsilon P\left(F(\text{D}') \in \mathcal{F}\right) + \varrho$$

for any possible subset $\mathcal{F}$ of the image of the mechanism F. The parameter ϵ is usually referred to as the *privacy budget*, which is small but non-negligible. $(\epsilon, 0)$-DP or ϵ-DP is known as *pure differential privacy*, while with a non-zero $\varrho > 0$, (ϵ, ϱ)-DP is viewed as *approximate differential privacy*.

Sensitivity Define the *sensitivity* of f by

$$\text{sens}(f) \equiv \max_{b,b'} |f(b, d) - f(b', d')|,$$

where the maximum is over all adjacent datasets (b, d) and (b', d') where b and b' differs only in a single individual with d and d' as the corresponding SNVs, respectively. For a given SNV in a dataset with $B \subseteq U$, d_{kj} is either 0 or 1. Thus, the maximum possible difference between the averages over the columns that differ in one entry is $\frac{1}{|B|}$. Let $1 \leq K^\dagger \leq K$ be the minimum number of individuals involved in the Beacon dataset. Hence, $\text{sens}(f) = \frac{m}{K^\dagger}$. Suppose we choose g_D as a Laplace mechanism. That is, $g_D(\cdot|b)$ is $\texttt{Laplace}(0, \frac{\text{sens}(f)}{\epsilon})$, for all $b \in W$. Then, it satisfies (pure) ϵ-differential privacy if R is the identity function since the Laplace mechanism performs output perturbation Dwork (2006). Due to the post-processing property of the standard differential privacy, it is clear that the Laplace mechanism g_D is also ϵ-differentially private for any non-identity R.

Gaussian Differential Privacy Next, we consider the scenario when g_D is a Gaussian mechanism described in Theorem 3. In particular, given any $b \in W$, $g_D^j(\cdot|b) \in \Delta(\mathcal{Y}_j)$ is the density function of $\mathcal{N}(\text{M}_b^j, \text{V}^j)$ for all $j \in Q$, where $\text{V}^j = \left(\frac{m}{K^\dagger \widehat{\text{M}}_j}\right)^2$ and $\max_{b,b'} |\text{M}_b^j - \text{M}_{b'}^j| \leq \frac{m}{K^\dagger}$, for all $j \in Q$. By Lemma 6, we have

$$T\left[P_b(g_D^j), P_{b'}(g_D^j)\right](\alpha) \geq T\left[\mathcal{N}(0, 1), \mathcal{N}(\widehat{\text{M}}_j, 1)\right],$$

for all adjacent b and b'. Therefore, each g_D^j satisfies $\widehat{\text{M}}_j$-*Gaussian differential privacy* ($\widehat{\text{M}}_j$-GDP) Dong et al. (2021), for all $j \in Q$. By Corollary 2.1 of Dong et al. (2021), this $\widehat{\text{M}}_j$-GDP mechanism g_D^j is also $(\epsilon_j, \varrho_j(\epsilon_j))$-DP for all $\epsilon_j \geq 0$ with

$$\varrho_j(\epsilon_j) = \Phi\left(-\frac{\epsilon_j}{\widehat{\text{M}}_j} + \frac{\widehat{\text{M}}_j}{2}\right) - e^{\epsilon_j}\Phi\left(-\frac{\epsilon_j}{\widehat{\text{M}}_j} - \frac{\widehat{\text{M}}_j}{2}\right),$$

where Φ is the cumulative distribution function (CDF) of the standard normal distribution. Under the assumption of linkage equilibrium and the construct of $g_D(y|b) = \prod_{j \in Q} g_D^j(y_j|b)$, the Gaussian defense strategy g_D is $\overline{\text{M}}$-GDP with $\overline{\text{M}} = \sqrt{\sum_{j \in Q} \widehat{\text{M}}_j^2}$ (Dong et al., 2021) due to the composition property.

F PROOF OF PROPOSITION 1

For any $0 < \gamma \leq 1$, we can rewrite

$$\ell_A(s, b, \gamma) = -\sum_{k \in U}(s_k b_k - \gamma s_k) = -\sum_{k \in U}(b_k - \gamma)s_k$$

$$= -\sum_{k \in U}\left((1 - \gamma)\mathbf{1}_{\{s_k = 1\}}\mathbf{1}_{\{b_k = 1\}} - \gamma\mathbf{1}_{\{s_k = 1\}}\mathbf{1}_{\{b_k = 0\}}\right).$$

Then,

$$\mathcal{L}_A(g_D, h_A; \sigma, \gamma) = \sum_{s,b} \int_x \ell_A(s, b, \gamma) h_A(s|x) \rho_D dr\sigma(b)$$

$$= -\sum_{s,b} \int_x \sum_{k \in U} \left((1-\gamma) \mathbf{1}_{\{s_k=1\}} \mathbf{1}_{\{b_k=1\}} - \gamma \mathbf{1}_{\{s_k=1\}} \mathbf{1}_{\{b_k=0\}} \right) h_A(s|x) \rho_D(x|b) dx\sigma(b).$$

Since $\sigma = \theta$ and

$$\sum_{s_{-k}, b_{-k}} \left((1-\gamma) \mathbf{1}_{\{s_k=1\}} \mathbf{1}_{\{b_k=1\}} - \gamma \mathbf{1}_{\{s_k=1\}} \mathbf{1}_{\{b_k=0\}} \right) h_A(s_k, s_{-k}|x) \theta(b_k, b_{-k})$$

$$= (1-\gamma) \sum_{b_{-k}} \Pr\left[s_k = 1 | b_k = 1, x \right] \theta(b_k, b_{-k}) - \gamma \sum_{b_{-k}} \Pr\left[s_k = 1 | b_k = 1, x \right] \theta(b_k, b_{-k}),$$

taking expectation over x using ρ_D yields $\mathcal{L}_A(g_D, h_A; \sigma, \gamma) = -\texttt{Adv}(h_A, \sigma, \gamma)$.

$\square$

G PROOF OF PROPOSITION 2

We start by showing the *if* part. Suppose that $\texttt{Adv}_k(g_D) \geq \texttt{Adv}_k(g'_D)$ for all $k \in U$. Then, the inequality also holds for all $k \in U$ if we apply both sides by the prior probabilities of $b_k = 0$ and $b_k = 1$. Thus, summing over all individuals yields $\texttt{Adv}_k(g_D) \geq \texttt{Adv}_k(g'_D)$.

Next, we prove the *only if* part. Let $\texttt{Adv}^*(g_D) \equiv \max_{h_A} \texttt{Adv}(h_A, \theta, \theta, 0.5; g_D)$, and let $\mathcal{L}_A^*(g_D) \equiv \min_{h_A} \mathcal{L}_A(g_D, h_A; \theta, 0.5)$. By Proposition 1, $\texttt{Adv}^*(g_D) \geq \texttt{Adv}^*(g'_D)$ is equivalent to $\mathcal{L}_A^*(g_D) \leq \mathcal{L}_A^*(g'_D)$. By Theorem 1 of (de Oliveira, 2018), g_D is more informative than g'_D according to the Blackwell's informativeness ordering. Note that the informativeness ordering of g_D and g'_D is independent of the choice of priors. Thus, when $\mathcal{L}_A^*(g_D) \leq \mathcal{L}_A^*(g'_D)$ also holds when the prior θ is uniform. Let $\texttt{Adv}^\dagger(g_D) \equiv \max_{h_A} \texttt{Adv}(h_A, \theta, \theta, 0.5; g_D)$ when θ is uniform. Thus, given any g_D, the optimal Bayes-weighted membership advantage simplifies to $\texttt{Adv}^\dagger(g_D) = \frac{1}{2} \sum_{k \in U} \texttt{Adv}_k(g_D)$. By definition of each $\texttt{Adv}_{k_0}(g_D)$, the informativeness ordering of g_D and g'_D ensures that there exists no individual $k_0 \in U$ such that $\texttt{Adv}_{k_0}(g_D) > \texttt{Adv}_{k_0}(g'_D)$.

$\square$

H PROOF OF THEOREM 1

In the proof, we use g_D and G interchangeably. For any function $V(s, b) \in \mathbb{R}$, define

$$Z(g_D, \sigma; V) \equiv \sum_{b,s} \int_x V(s, b) \mu_\sigma(s|r) \rho_D(x|b) dx q(b),$$

where μ_σ is the posterior belief induced by g_D and σ, which is independent of the σ-Bayesian attacker's strategy h_A and the test conclusions of α-LRT attacker. In addition, define

$$L(g_D, h_A; V) \equiv \sum_{b,s} \int_x V(s, b) h_A(s|x) \rho_D(x|b) dx \theta(b).$$

Hence, when $V(\cdot) = \ell_A(\cdot; \gamma)$, $L(g_D, h_A; V) = \mathcal{L}_A(g_D, h_A; \sigma, \gamma)$. Let $L^\sigma(g_D; V) \equiv \max_{h_A \in \mathcal{BR}^\sigma[g_D]} L(g_D, h_A; V)$. For simplicity, we write $Z(g_D, \sigma) = Z(g_D, \sigma; V)$ and $L^\sigma(g_D) = L^\sigma(g_D; V)$, unless otherwise stated.

Proposition 7. *For any g_D and σ, $Z(g_D, \sigma) = L^\sigma(g_D)$.*

Proposition 7 shows that a h_A that coincides with the posterior belief induced by g_D and σ leads to the minimum expected loss given any V.

Proposition 8. *Given any G and σ, every $H^* \in \texttt{BN}[G; \sigma]$ coincides with the posterior distribution μ_σ induced by σ and G.*

Proposition 8 implies that every best response in $\texttt{BN}[G; \sigma]$ leads to the probability distribution coincides with the posterior belief given G and σ.

Then, by Proposition 7, every $H^* \in \texttt{BN}[G; \sigma]$ leads to $\mathcal{L}_A(G, H^*; \sigma, \gamma) \leq \mathcal{L}_A(G, H'; \sigma, \gamma)$ (i.e., when $V(\cdot) = \ell_A(\cdot; \gamma)$). Thus, we have $\texttt{Adv}(H^*, \sigma, \theta, 0.5; G^*) \leq \texttt{Adv}(H', \sigma, \theta, 0.5; G')$. In addition, when $V(\cdot) = v(\cdot; \gamma)$, $H^* \in \texttt{BN}[G; \sigma]$ leads to the minimum expected TPR. Therefor, it holds that $TPR(G^*, H^*) \leq TPR(G', H')$.

H.1 Poof of Proposition 7

Given μ_σ (determined by g_D and σ) and any h_A, let $\widehat{U}_A(h_A, b, x) \equiv \sum_s u_A(s, b)h_A(s|x)\mu_\sigma(b|x)$, which depends on the membership vector b sampled by μ_σ but is independent of the samples s drawn by h_A. Define

$$S^*[b, r; g_D] \equiv \left\{ h_A(\cdot|x) \Big| h_A(\cdot|x) \in \arg\min_{h'_A} \widehat{U}_A(h'_A, b, x) \right\},$$

for all $b \in W$ with $\mu_\sigma(b|x) > 0$, any $x \in \mathcal{X}$, where $S^*[b, x; g_D]$ depends on g_D through μ_σ. We first show that there is a $h_A^*(\cdot|x) \in S^*[b, x; g_D]$ that assigns probability 1 to b (with $\mu_\sigma(b|x) > 0$). Suppose in contrast that $0 \leq h_A^*(b|x) < 1$. Then, it holds that $\sum_{s:s\neq b} u_A(s, b)h_A(s|x)\mu_\sigma(b|x) > 0$, which gives

$$\widehat{U}_A(h_A^*, b, x) = \sum_s u_A(s, b)h_A(s|x)\mu_\sigma(b|x)$$

$$= \sum_{s:s\neq b} u_A(s, b)h_A(s|x)\mu_\sigma(b|x) + u_A(b, b)h_A(b|x)\mu_\sigma(b|x) > u_A(b, b)h_A(b|x)\mu_\sigma(b|x).$$

Thus, $\widehat{U}_A(h_A^*, b, x)|_{h_A^*(b|x)\neq 1} > \widehat{U}_A(h'_A, b, x)|_{h'_A(b|x)=1}$, which contradicts to $h_A^*(\cdot|x) \in S^*[b, x; g_D]$. Therefore, we have $u_A(b, b)\mu_\sigma(b|x) \leq \sum_s u_A(s, b)h_A(s|x)\mu_\sigma(b|x)$, for all $h_A(\cdot|x)$, $b \in W$, $x \in \mathcal{X}$, where the equality holds when $h_A(\cdot|x) \in S^*[b, x; g_D]$.

Let $h_A^\mu : \Gamma \mapsto \Delta(W)$ mirror the posterior belief μ_σ; i.e., $h_A^\mu(s|x) = \mu_\sigma(b|x)\mathbf{1}\{s = b\}$, for all $s, b \in W$, $x \in \mathcal{X}$. It is clear that $h_A^\mu(\cdot|x) \in S^*[b, x; g_D]$ for all $b \in W$. Next, we show that if $h_A^\mu(s|x)$ is used by the σ-Bayesian attacker, it induces the WCPL for the vNM defender, which is captured by Proposition 9.

Proposition 9. *Given any g_D and σ, $L(g_D, h_A^\mu, \sigma) \leq L(g_D, h_A^*, \sigma)$, for all $h_A^* \in \mathcal{BR}^\sigma[g_D]$.*

Proof. Define $\pi \equiv h_A \circ \rho_D : W \mapsto \Delta(W)$ by $\pi(s|b) = \sum_r h_A(s|r)\rho_D(r|b)$, for all $s, b \in W$. Define the set
$$\Pi[g_D] \equiv \{\pi = h_A \circ \rho_D | h_A : \Gamma \mapsto \Delta(W)\}.$$
That is, $\Pi[g_D]$ is the set of all feasible probabilistic mappings from a true membership vector b to an inference s, perceived by the defender. We first establish the following lemma regarding the informativeness of g_D in the sense of Blackwell's ordering of informatinveness (Blackwell, 1951; de Oliveira, 2018).

Lemma 2. *Fix any $\sigma \in \Delta(W)$. Given any two g_D, g'_D, $\Pi[g_D] \subseteq \Pi[g'_D]$, if and only if, for any function $\zeta : W \times W \mapsto \mathbb{R}$,*
$$\sum_{b,s} \zeta(s, b)\pi'(s|b)\sigma(b) \leq \sum_{b,s} \zeta(s, b)\pi(s|b)\sigma(b),$$
where $\pi \in \Pi[g_D]$ and $\pi' \in \Pi[g'_D]$.

Proof. We start by showing the *"only if"* part. Let $\Pi^*[g_D] \equiv \{\pi | \pi \in \arg\min_{\pi \in \Pi[g_D]} \sum_{b,s} \zeta(s, b)\pi'(s|b)\sigma(b)\}$. Since $\Pi[g_D] \subseteq \Pi[g'_D]$ and $\Pi^*[g_D] \subseteq \Pi[g_D]$, it must hold that $\Pi^*[g_D] \subseteq \Pi[g'_D]$. Hence,
$$\sum_{b,s} \zeta(s, b)\pi'(s|b)\sigma(b) \leq \sum_{b,s} \zeta(s, b)\pi(s|b)\sigma(b),$$
for all $\pi \in \Pi[g_D]$ and $\pi' \in \Pi[g'_D]$.

Next, we show the *"if"* part. Suppose in contrast that $\Pi[g_D] \not\subseteq \Pi[g'_D]$. Then, there exists a $\pi \in \Pi[g_D]$ such that $\pi \notin \Pi[g'_D]$. Since the set $\Pi[\bar{g}_D]$ for every $\bar{g}_D : W \mapsto \Delta(D)$ is closed under convex combinations of its elements, it is convex. In addition, it is a continuous image of a compact set in the space of probability distributions. Hence, the set $\Pi[\bar{g}_D]$ is also compact. The set $\Pi[\bar{g}_D]$ can be seen as a subset of $\mathbb{R}^{W \times W}$. Therefore, we can also perceive $\pi \in \mathbb{R}^{W \times W} \backslash \Pi[g'_D]$.

Let $\pi^\sigma(s, b) \equiv \pi(s|b)\sigma(b)$ for all $s, b \in W$. With abuse of notation, let $\Pi[g''_D, \sigma] \equiv \{\pi^\sigma | \pi \in \Pi[g''_D]\}$. Then, the set $\Pi[g''_D, \sigma]$ is a subset of $\mathbb{R}^{W \times W}$. Thus, $\pi^\sigma \in \mathbb{R}^{W \times W} \backslash \Pi[g'_D, \sigma]$. Let $\hat{\zeta} \in \mathbb{R}^{W \times W}$ represents the matrix form of the function ζ. Since $|W| = 2^K$ with $K > 1$, there exists a separating hyperplane orthogonal to $\hat{\zeta}$, which separates the set $\Pi[g'_D]$ from the point π, such that
$$\sum_{b,s} \zeta(s, b)\pi'(s|b) > \sum_{b,s} \zeta(s, b)\pi(s|b),$$
for all $\pi' \in \Pi[g'_D]$. Then, the attacker with a non-informative (i.e., uniform prior) σ obtains an ex-ante expected payoff using h_A such that $\pi = h_A \circ g_D$ that is strictly better than any h'_A such that $h'_A \circ \rho_D \in \Pi[g'_D]$. Thus, we obtain a contradiction to $\sum_{b,s} \zeta(s, b)\pi'(s|b)\sigma(b) \leq \sum_{b,s} \zeta(s, b)\pi(s|b)\sigma(b)$ for all $\sigma \in \Delta(W)$. $\square$

Next, we want to show that $\Pi[g_D] \subseteq \Pi[g'_D]$ is equivalent to $g'_D = \eta \circ g_D$ for some garbling $\eta : \Gamma \mapsto \Delta(\Gamma)$, which is another format of Blackwell's ordering of information structures (Blackwell, 1951; de Oliveira, 2018).

Lemma 3. *For any two g_D, g'_D, $\Pi[g'_D] \subseteq \Pi[g_D]$ if and only if $g'_D = \eta \circ g_D$ for some garbling $\eta : \Gamma \mapsto \Delta(\Gamma)$.*

Proof. If $g'_D = \eta \circ g_D$, then there is a garbling $\hat{\eta} : \Gamma \mapsto \Delta(\Gamma)$ such that $\rho'_D = \hat{\eta} \circ \rho_D$. Hence, $\pi' = \hat{\eta} \circ \pi$ for every $\pi' \in \Pi[g'_D]$ and $\pi \in \Pi[g_D]$. Then, from (1) and (2) of Theorem 1 in (de Oliveira, 2018), we obtain $g'_D = \hat{\eta} \circ g_D$ is equivalent to $\Pi[g'_D] \subseteq \Pi[g_D]$. □

For simplicity, let $\mu^r_\sigma = \mu_\sigma(\cdot|r)$. Since $h_A \in \mathcal{BR}^\sigma[g_D]$, there exists a randomized correspondence Y such that $h_A(\cdot|r) = Y(\cdot|\mu^r_\sigma)$ for all $r \in \Gamma$. Then, from Blackwell's theorem (Blackwell, 1951; de Oliveira, 2018), there exists a garbling $y : W \mapsto \Delta(W)$ such that $h_A = y \circ \mu_\sigma$. Let $\hat{\rho}_D \equiv \mu_\sigma \circ \rho_D$ and let $\hat{\rho}'_D \equiv y \circ \hat{\rho}_D$. In addition, let $\hat{g}_D$ and $\hat{g}'_D$, respectively, be corresponding to $\hat{\rho}_D$ and $\hat{\rho}'_D$. Then, from Lemma 3, we have $\Pi[\hat{g}'_D] \subseteq \Pi[\hat{g}_D]$. In addition, Lemma 2 implies that

$$\sum_{b,s} \zeta(s,b)\hat{\pi}(s|b)\sigma(b) \leq \sum_{b,s} \zeta(s,b)\hat{\pi}'(s|b)\sigma(b)$$

for any $\sigma \in \Delta(W)$, any function $\zeta : W \times W \mapsto \mathbb{R}$, where $\hat{\pi} \in \Pi[\hat{g}_D]$ and $\hat{\pi}' \in \Pi[\hat{g}'_D]$. If we take $\zeta(\cdot) = V(\cdot)$ and $\sigma(\cdot) = q(\cdot)$, then we have $L(\hat{g}_D) \geq L(\hat{g}'_D)$. Therefore, $L(g_D, h^\mu_A) \leq L(g_D, h^*_A)$ for all $h^*_A \in \mathcal{BR}^\sigma[g_D]$, which concludes the proof of Proposition 9. □

Next, we show that there is a $h^*_A \in \mathcal{BR}^\sigma[g_D]$ such that $h^*_A(s|r) = h^\mu_A(s|r)$ for all $s \in W$, $r \in \Gamma$. Define $\widehat{U}^\natural(s,r) \equiv \sum_b u_A(s,b)\mu_\sigma(b|r)$, which depends on samples of $s \in W$ and $r \in \Gamma$. Let

$$W^\natural[r] \equiv \left\{ s \in W \Big| s \in \arg\min_{s'} \widehat{U}^\natural(s',r) \right\}.$$

Let $\hat{s} \in W$ such that $\hat{h}_A(\hat{s}|r) = 1$ for $\hat{h}_A \in S^*[b,r;g_D]$. We want to show $\hat{s} \in W^\natural[r]$. Suppose in contrast that $\hat{s} \notin W^\natural[r]$. Then, $\widehat{U}^\natural(s,r) < \widehat{U}^\natural(\hat{s},r)$ for all $s \in W^\natural[r]$. That is, $\sum_b u_A(s,b)\mu_\sigma(b|r) < \sum_b u_A(\hat{s},b)\mu_\sigma(b|r)$. Since $\hat{h}_A \in S^*[b,r;g_D]$, we have $u_A(\hat{s}=b,b) \leq \sum_s \mu_A(s,b)h'_A(s|r)$ for all $h'_A(\cdot|r)$, including $h'_A(s|r) = 1$ for any $s \in W$. Since every $\mu_\sigma(\cdot) \geq 0$, we have $u_A(\hat{s}=b,b)\mu_\sigma(b|r) \leq \mu_A(s,b)\mu_\sigma(b|r)$, for all $s,b \in W$. Then, $\widehat{U}^\natural(\hat{s},r) \leq \widehat{U}^\natural(s,r)$, contradicting to $\hat{s} \notin W^\natural[r]$. Therefore, $\hat{s} \in W^\natural[r]$.

Next, we show that for every $s^* \in W^\natural[r]$, there is a $b \in W$ with $\mu_\sigma(b|r) > 0$ such that $\hat{h}_A(s^*|r) = 1$ for $\hat{h}_A \in S^*[b,r;g_D]$. Suppose in contrast that there exists a $s^* \in W^\natural[r]$ such that $\hat{h}_A(s^*|r) = 0$, for a $\hat{h}_A \in S^*[b,r;g_D]$. Then, there exists $\hat{s}$ with $\hat{h}_A(\hat{s}|r) = 1$ such that, for all $h'_A : \Gamma \mapsto \Delta(W)$,

$$\sum_s u_A(s,b)\hat{h}_A(s|r)\mu_\sigma(b|r)$$
$$= u_A(\hat{s},b)\mu_\sigma(b|r) \leq u_A(s^*,b)h'_A(s^*|r)\mu_\sigma(b|r) + \sum_{s:s\neq s^*} u_A(s,b)h'_A(s|r)\mu_\sigma(b|r),$$

where the equality of the inequality holds when $h'_A = \hat{h}_A$. For all $h'_A \neq \hat{h}_A$, $h'_A(s^*|r) \in [0,1]$, which implies $u_A(\hat{s},b)\mu_\sigma(b|r) < u_A(\hat{s},b)\mu_\sigma(b|r)$ for all $b \in W$ and $r \in \Gamma$ with $\mu_\sigma(b|r) > 0$. Thus, $\sum_b u_A(\hat{s},b)\mu_\sigma(b|r) < \sum_b u_A(s^*,b)\mu_\sigma(b|r)$, which contradicts to $s^* \in W^\natural[r]$. Therefore, $W^\natural[r] = \cup_b\{s \in W | h_A(s|r) = 1, h_A \in S^*[b,r;g_D]\}$. It is not hard to see that every feasible mixed strategy $h_A(\cdot|r)$ that assigns strictly positive probability only to elements of $W^\natural[r]$ is a best response to g_D. Since $h^\mu_A \in S^*[b,r;g_D]$, we can conclude that $h^*_A \in \mathcal{BR}^\sigma[g_D]$ with $h^*_A(s|r) = h^\mu_A(s|r)$, for all $s \in W$, $r \in \Gamma$. In addition, we can rewrite $Z(g_D,\sigma)$ in terms of h^μ_A as $Z(g_D,\sigma) = \sum_{b,s} \int_r v(s,b)h^\mu_A(s|r)\rho_D(r|b)dr q(b)$. Thus, by Proposition 9, we conclude that $L^\sigma(g_D) = Z(g_D,\sigma)$. □

H.2 PROOF OF PROPOSITION 8

For ease of exposition, we directly use the underlying density functions g_D (and ρ_D) and h_A of G and H, respectively, so that $h_A(s_k = 1) = q_k$ and $h_A(s_k = 0) = 1 - q_k$. Thus, we can rewrite

$$\widehat{\mathcal{L}}^\sigma_A(G,H) = \widehat{\mathcal{L}}^\sigma_A(g_D, h_A) = -\sum_b \int_x \sigma(b) \log(h_A(b|x))\rho_D(x|b)dx.$$

Let μ_σ denote the posterior distribution induced by σ and g_D according to Bayes' rule. Then,

$$
\begin{aligned}
&\widehat{\mathcal{L}}_A^\sigma(g_D, h_A) - \widehat{\mathcal{L}}_A^\sigma(g_D, \mu_\sigma) \\
&= -\sum_b \int_x \sigma(b) \log(h_A(b|x)) \rho_D(x|b) dx + \sum_b \int_x \sigma(b) \log(\mu_\sigma(b|x)) \rho_D(x|b) dx \\
&= \sum_b \int_x \sigma(b) \rho_D(x|b) \left(\log(\mu_\sigma(b|x)) - \log(h_A(b|x)) \right) dx \\
&= \sum_b \int_x \sigma(b) \rho_D(x|b) \log(\frac{\mu_\sigma(b|x)}{h_A(b|x)}) dx.
\end{aligned}
$$

By definition of μ_θ using Bayes' rule, we have

$$
\sigma(b) \rho_D(x|b) = \mu_\sigma(b|x) \mathrm{P}^\sigma(x),
$$

where $\mathrm{P}^\sigma(x) \equiv \sum_{b'} \sigma(b) \rho_D(x|b)$. Then, we have

$$
\widehat{\mathcal{L}}_A^\sigma(g_D, h_A) - \widehat{\mathcal{L}}_A^\sigma(g_D, \mu_\sigma) = \sum_b \int_x \mu_\sigma(b|x) \mathrm{P}^\sigma(x) \log \left(\frac{\mu_\sigma(b|x)}{h_A(b|x)} \right) dx \geq 0
$$

which is non-negative because it is the Kullback–Leibler (KL) divergence. In addition, $\widehat{\mathcal{L}}_A^\sigma(g_D, h_A) - \widehat{\mathcal{L}}_A^\sigma(g_D, \mu_\sigma) = 0$ if and only if $h_A(b|x) = \mu_\sigma(b|x)$ for all $b \in W$ and $x \in \mathcal{X}$.

$\square$

I PROOF OF PROPOSITION 3

By by Theorem 2.10. of (Dong et al., 2021) (also see (Blackwell, 1951)), we have that for a fixed significance level, the minimum false positive rates (of inferring each individual k's membership status), denoted by $T(G)$ and $T(\mathrm{Proc} \circ G)$, can be achieved by G and $\mathrm{Proc} \circ G$ satisfy

$$
T(\mathrm{Proc} \circ G) \geq T(G).
$$

Thus, G is more informative than $\mathrm{Proc} \circ G$ according to Blackwell's ordering of informativeness (Blackwell, 1951). By Theorem 1 of (de Oliveira, 2018), we can conclude that $\widehat{\mathcal{L}}_A^\sigma(\mathrm{Proc} \circ G, H') \geq \widehat{\mathcal{L}}_A^\sigma(G, H)$. $\square$

J PROOF OF PROPOSITION 4

For ease of exposition, we focus on the case when there are two mechanisms that are composed. That is, $\vec{G} = (G_1, G_2)$. The proof can be easily extended to general $n \geq 2$.

We start by proving the scenario when the mechanisms are independent. Let $\rho_1(\cdot|b) \in \Delta(\mathcal{X}_1)$ and $\rho_2(\cdot|b) \in \Delta(\mathcal{X}_2)$ be induced density functions by G_1 and G_2, respectively. In addition, we directly use the underlying density function h_A of H, so that $h_A(s_k = 1) = q_k$ and $h_A(s_k = 0) = 1 - q_k$. We can easily generalize Proposition 8 in Appendix H to the case when there are multiple data-sharing mechanisms randomized by $\vec{G}$. That is, every $H \in \mathrm{BN}[\vec{G}; \theta]$ coincides with the posterior distribution $\mu_\theta(b_k, b_{-k}) = \frac{\rho_1(x_1|b) \rho_2(x_2|b) \theta(b)}{\sum_{b'} \rho_1(x_1|b') \rho_2(x_2|b') \theta(b')}$

induced by $\vec{G}$ and the prior θ. Thus, we have

$$\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*) = -\sum_{b \in W} \int_{x_1, x_2} \theta(b) \log(h_A(b|x_1, x_2))\theta(b)\rho_1(x_1|b)\rho_2(x_2|b) dx_1 dx_2$$

$$= -\sum_{b \in W} \int_{x_1, x_2} \theta(b) \log(\mu_\theta(b|x_1, x_2))\theta(b)\rho_1(x_1|b)\rho_2(x_2|b)$$

$$= -\sum_b b\theta(b) \log(\theta(b)) \cdot \int_{x_1, x_2} \rho_1(x_1|b)\rho_2(x_2|b) dx_1 dx_2$$

$$- \sum_b \int_{x_1, x_2} \theta(b) \cdot \rho_1(x_1|b)\rho_2(x_2|b) \cdot \log(\rho_1(x_1|b)\rho_2(x_2|b)) dx_1 dx_2$$

$$+ \sum_b \int_{x_1, x_2} \theta(b) \cdot \rho_1(x_1|b)\rho_2(x_2|b) \cdot \log\left(\sum_{b'} \rho_1(x_1|b')\rho_2(x_2|b')\theta(b')\right) dx_1 dx_2$$

$$= -\sum_b \theta(b) \log(\theta(b)) - \sum_b \int_{x_1, x_2} \theta(b) \cdot \rho_1(x_1|b)\rho_2(x_2|b) \cdot \log(\rho_1(x_1|b)\rho_2(x_2|b)) dx_1 dx_2$$

$$+ \int_{x_1, x_2} \left(\sum_{b'} \rho_1(x_1|b')\rho_2(x_2|b')\theta(b')\right) \cdot \log\left(\sum_{b'} \rho_1(x_1|b')\rho_2(x_2|b')\theta(b')\right).$$

We can following the same steps for each G_j for $j \in \{1, 2\}$ with $H_j \in \text{BN}[G_j; \theta]$:

$$\widehat{\mathcal{L}}(G_j, H_j) = -\sum_b \theta(b) \log(\theta(b)) - \sum_b \int_{x_j} \theta(b) \cdot \rho_j(x_j|b) \cdot \log\left(\rho_j(x_j|b)\right) dx_j$$

$$+ \int_{x_j} \left(\sum_{b'} \rho_j(x_j|b')\theta(b)\right) \log\left(\sum_{b'} \rho_j(x_j|b')\theta(b)\right) dx_j.$$

Summing individual losses yields

$$\sum_{j=1}^2 \widehat{\mathcal{L}}(G_j, H_j) = -2\sum_b \theta(b) \log(\theta(b))$$

$$- \sum_{j=1}^2 \sum_b \int_{x_j} \theta(b) \cdot \rho_j(x_j|b) \cdot \log\left(\rho_j(x_j|b)\right) dx_j$$

$$+ \sum_{j=1}^2 \int_{x_j} \left(\sum_{b'} \rho_j(x_j|b')\theta(b')\right) \log\left(\sum_{b'} \rho_j(x_j|b')\theta(b)\right) dx_j.$$

Let $\mathcal{H} \equiv \sum_b \theta(b) \log(\theta(b))$, $\mathcal{F}_j \equiv \sum_b \int_{x_j} \theta(b) \cdot \rho_j(x_j|b) \cdot \log\left(\rho_j(x_j|b)\right) dx_j$, and $\mathcal{K} \equiv \sum_b \theta(b) \int_{x_1, x_2} \rho_1(x_1|b)\rho_2(x_2|b) \cdot \log\left(\sum_{b'} \rho_1(x_1|b')\rho_2(x_2|b')\theta(b')\right) dx_1 dx_2$.

Since

$$\sum_b \int_{x_1, x_2} \theta(b) \cdot \rho_1(x_1|b)\rho_2(x_2|b) \cdot \log(\rho_1(x_1|b)\rho_2(x_2|b)) dx_1 dx_2$$

$$= \sum_b \int_{x_1, x_2} \theta(b) \cdot \rho_1(x_1|b)\rho_2(x_2|b) \cdot (\log(\rho_1(x_1|b)) + \log(\rho_2(x_2|b))) dx_1 dx_2$$

$$= \sum_{j=1}^2 \sum_b \int_{x_j} \theta(b) \cdot \rho_j(x_j|b) \cdot \log(\rho_j(x_j|b)) dx_j = \sum_{j=1}^2 \mathcal{F}_j,$$

we obtain

$$\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*) = \left(\sum_{j=1}^2 \left(\widehat{\mathcal{L}}(G_j, H_j) - \mathcal{F}_j\right) + 2\mathcal{H}\right) - \mathcal{H} + \mathcal{K}$$

$$= \sum_{j=1}^2 \widehat{\mathcal{L}}(G_j, H_j) + \mathcal{H}(b) - \sum_{j=1}^2 \mathcal{F}_j(\tilde{x}_j) + \mathcal{K}.$$

By combining $\Lambda(\vec{G}, \theta) = - \left(\mathcal{H}(b) - \sum_{j=1}^{2} \mathcal{F}_j(\tilde{x}_j) + \mathcal{K} \right)$, we have

$$\Lambda(\vec{G}, \theta) = - \sum_b \theta(b) \int_{x_1, x_2} \rho_1(x_1|b) \rho_2(x_2|b) \cdot \log \left(\sum_{b'} \rho_1(x_1|b) \rho_2(x_2|b) \theta(b') \right) dx_1 x_2.$$

For general $n \geq 2$, we have $\Lambda(\vec{G}, \theta) = - \sum_b \theta(b) \int_{\vec{x}} \vec{\rho}_D(\vec{x}|b) \cdot \log \left(\sum_{b'} \vec{\rho}_D(\vec{x}|b') \theta(b') \right) d\vec{x}$.

Next, we proceed with the proof when the mechanisms are correlated. Again, for simplicity, we first focus on $n = 2$, i.e., $\vec{G} = (G_1, G_2)$, and generalize to $n \geq 2$ afterward.

By Proposition 8, the posterior distribution $\mu_\theta(b|x_1, x_2)$ is given by:

$$\mu_\theta(b|x_1, x_2) = \frac{\vec{\rho}_D(x_1, x_2|b)\theta(b)}{\sum_{b'} \vec{\rho}_D(x_1, x_2|b')\theta(b')}.$$

The BGP risk $\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*)$ for the composed mechanism becomes:

$$\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*) = - \sum_b \int_{x_1, x_2} \theta(b) \log(\mu_\theta(b|x_1, x_2)) \vec{\rho}_D(x_1, x_2|b) dx_1 dx_2.$$

Substituting $\mu_\theta(b|x_1, x_2)$ into the loss function:

$$\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*) = - \sum_b \int_{x_1, x_2} \theta(b) \vec{\rho}_D(x_1, x_2|b) \log \left(\frac{\vec{\rho}_D(x_1, x_2|b)\theta(b)}{\sum_{b'} \vec{\rho}_D(x_1, x_2|b')\theta(b')} \right) dx_1 dx_2,$$

which can be broken into three terms:

$$\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*) = - \sum_b \theta(b) \log(\theta(b)) \int_{x_1, x_2} \vec{\rho}_D(x_1, x_2|b) dx_1 dx_2$$

$$- \sum_b \int_{x_1, x_2} \theta(b) \vec{\rho}_D(x_1, x_2|b) \log(\vec{\rho}_D(x_1, x_2|b)) dx_1 dx_2$$

$$+ \int_{x_1, x_2} \sum_b \theta(b) \vec{\rho}_D(x_1, x_2|b) \log \left(\sum_{b'} \vec{\rho}_D(x_1, x_2|b')\theta(b') \right) dx_1 dx_2.$$

Define the following terms:

$$\mathcal{H} \equiv - \sum_b \theta(b) \log(\theta(b)), \quad \text{(entropy of the prior)}$$

$$\mathcal{F} \equiv - \sum_b \int_{x_1, x_2} \theta(b) \vec{\rho}_D(x_1, x_2|b) \log(\vec{\rho}_D(x_1, x_2|b)) dx_1 dx_2, \quad \text{(conditional entropy)}$$

$$\mathcal{K} \equiv \int_{x_1, x_2} \sum_b \theta(b) \vec{\rho}_D(x_1, x_2|b) \log \left(\sum_{b'} \vec{\rho}_D(x_1, x_2|b')\theta(b') \right) dx_1 dx_2, \quad \text{(interaction term)}.$$

Thus, the loss can be expressed as:

$$\widehat{\mathcal{L}}_A(\vec{G}, \vec{H}^*) = \mathcal{H} + \mathcal{F} - \mathcal{K}.$$

By combining $\Lambda(\vec{G}, \theta) = - (\mathcal{H} - \mathcal{F} + \mathcal{K})$, we have

$$\Lambda(\vec{G}, \theta) = - \sum_b \theta(b) \int_{x_1, x_2} \vec{\rho}D(x_1, x_2|b) \log \left(\frac{\sum b' \vec{\rho}D(x_1, x_2|b')\theta(b')}{P(x_1, x_2)} \right) dx_1 dx_2,$$

where

$$P(x_1, x_2) = \prod j = 1^2 \sum_{b'} \int_{\mathcal{X}_{-j}} \vec{\rho}D(x_j, x_{-j}|b')\theta(b') dx_{-j}.$$

For $n \geq 2$, this expression naturally generalizes:

$$\Lambda(\vec{G}, \theta) = - \sum_b \theta(b) \int_{\vec{x}} \vec{\rho}D(\vec{x}|b) \log \left(\frac{\sum b' \vec{\rho}_D(\vec{x}|b')\theta(b')}{P(\vec{x})} \right) d\vec{x},$$

where $P(\vec{x}) = \prod_{j=1}^{n} \sum_{b'} \int_{\vec{\mathcal{X}}_{-j}} \vec{\rho}_D(x_j, \vec{x}_{-j}|b')\theta(b') d\vec{x}_{-j}$. $\qquad \square$

K   PROOF OF PROPOSITION 5

Let $\vec{x} = (x_1, \ldots, x_n)$ denote the outputs of the composition $\mathcal{M}(\vec{G}^*)$, and let $\vec{\rho}_D$ is the joint distribution given $\vec{G}$, $\{f_1, \ldots, f_n\}$, and any intrinsic correlations among mechanisms. For simplicity, we consider each individual k has probability $\theta_k = \theta_k(b_k = 1)$ to have $b_k = 1$ and probability $1 - \theta_k$ to have $b_k = 0$. Consider the following binary hypothesis test:

$$\mathcal{H}_0^k: b_k = 0 \text{ with } b_{-k} \text{ vs. } \mathcal{H}_1^k: b_k = 1 \text{ with } b_{-k},$$

where b_{-k} is the same for both $\mathcal{H}_0^k$ and $\mathcal{H}_1^k$. Since $\vec{\rho}_D(\vec{x}|b)$ is well-defined, this binary hypothesis test is a well-defined simple binary hypothesis test. Then, the Neyman-Pearson lemma implies that the likelihood-ratio test is the Uniformly Most Powerful (UMP) test. Then, for any given significance level α^k, there exists a rejection rule ϕ such that

$$\alpha^k = \mathbb{E}\left[\phi \Big| \mathcal{H}_0^k, \vec{G}^*\right] \text{ and } \mathtt{f}(\alpha) = 1 - \mathbb{E}\left[\phi \Big| \mathcal{H}_1^k, \vec{G}^*\right],$$

where $\mathtt{f}(\alpha^k) = \int \left\{t \in [0,1] : \mathtt{f}(t) \leq \alpha^k\right\}$ is the *symmetric trade-off function* introduced by Dong et al. (2022) , which is convex, continuous, non-increasing, and satisfies $\mathtt{f}(\alpha^k) \leq 1 - \alpha^k$ and $\mathtt{f}(\alpha^k) = \inf\left\{t \in [0,1] : \mathtt{f}(t) \leq \alpha^k\right\}$ for $\alpha^k \in [0,1]$. Hence, the composition $\mathcal{M}(\vec{G}^*)$ is $\mathtt{f}$-differentially private ($\mathtt{f}$-DP) (Definition 2.3 of (Dong et al., 2022)). Then, by Proposition 2.4 of Dong et al. (2022), $\mathcal{M}(\vec{G}^*)$ is also $\mathtt{f}^*$-DP, where $\mathtt{f}^*(z) = \sup_{0 \leq \hat{\alpha}^k \leq 1} z\hat{\alpha}^k - f(\hat{\alpha}^k)$. Then, by Proposition 2.12 of Dong et al. (2022), for any $\epsilon^k \geq 0$, the composition $\mathcal{M}(\vec{G}^*)$ is (ϵ^k, ξ^k)-DP, where $\xi^k = \delta(\epsilon^k)$, for any given b_k. Therefore, the composition $\mathcal{M}$ is (ϵ, ξ)-DP for some $\epsilon \geq 0$ and $\xi \in [0,1]$. $\qquad\square$

L   PROOF OF PROPOSITION 6

Proposition 8 in Appendix H can be easily extended to the case when there are multiple data-sharing mechanisms randomized by $\vec{G}$. Thus, if $H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(\vec{G}, H) \bigcap \mathtt{DPH}[\vec{G}; \epsilon]$, the posterior distribution induced by $\vec{G}$ and θ satisfies the conditions specified by $\mathtt{DPH}[\vec{G}; \epsilon]$. By the necessary and sufficient condition given by Claim 3 of (Dwork et al., 2006), $\vec{G}$ is ϵ-DP. Again, by Claim 3 of (Dwork et al., 2006), if $\vec{G}$ is ϵ-DP, the posterior distribution must satisfy the conditions specified by $\mathtt{DPH}[\vec{G}; \epsilon]$. Then, based on the extension of Proposition 8, it must holds that $H^* \in \arg\min_H \mathcal{L}_{\text{CEL}}(\vec{G}, H) \bigcap \mathtt{DPH}[\vec{G}; \epsilon]$. $\qquad\square$

M   PROOF OF THEOREM 2

We start by proving Lemma 4.

Lemma 4. *Fix any g_D. Suppose that σ is aligned. Let $h_A^\mu : \Gamma \mapsto \Delta(W)$ be defined by $h_A^\mu(s|r) = \mu_\sigma(b|r)\mathbf{1}(s = b)$ for all $s, b \in W$, $r \in \Gamma$. Then, $h_A^\mu \in \mathcal{BR}_\Gamma^\sigma[g_D]$.*

Proof. Let $V_A^\ddagger(s, r) \equiv \sum_b u_A(s, b)\mu_\sigma(b|r)$ Define $W^\ddagger[r] \equiv \{s \in W | s \in \arg\min_{s'} V_A^\ddagger(s, r)\}$. Hence, each $h_A : \Gamma \mapsto \Delta(W)$ that only assigns strictly positive probabilities to $s \in W^\ddagger[r]$ satisfies $h_A \in \mathcal{BR}^\sigma[g_D]$. In addition, let $W^\sharp[r] \equiv \{s \in W | \mu_\sigma(s|r) > 0\}$. By definition of c_A and $v_{s,b}$, $\gamma c_A(s) - v_A(s, b)$ (weakly) decreases as $\sum_{k \in U} \mathbf{1}\{s_k = b_k\}$ increases. Thus, $V_A^\ddagger(s^\sharp, r) \leq V_A^\ddagger(s, r)$ for all $s^\sharp \in W^\sharp[r]$ and $s \in W$. Hence, $W^\sharp[r] \subseteq W^\ddagger[r]$ for all r. Hence, $h_A^\mu \in \mathcal{BR}_\Gamma^\sigma[g_D]$ holds. $\qquad\square$

With abuse of notation, we let $q(b)$ and $q(b_k) = \sum_{b_{-k}} q(b_k, b_{-k})$ denote the prior and the marginalized prior, respectively. Next, we show that optimal α-LRT cannot strictly outperform σ-Bayesian under the same g_D.

Lemma 5. *Fix g_D and α. Suppose $\sigma = q$. Then, $Z(g_D, q) \geq L(g_D, \tau^*, \alpha)$.*

Proof. Suppose in contrast that $Z(g_D, q) < L(g_D, \tau^*, \alpha)$. Then,

$$\sum_k P_1^k\left[y_k(r, \tau^*) = 1 | g_D\right] q(b_k = 1) > \sum_{b,s} \int_r v(s, b)\mu_\sigma(s|r)\rho_D(r|b)dr q(b)$$
$$= \sum_k P_\sigma^k\left[s_k = 1 | g_D, b_k = 1\right] q(b_k = 1),$$

where $P_\sigma^k[s_k = 1 | g_D, b_k = 1] = \int_r \mu_\sigma(s_k = 1|r)\rho_D(r|b)dr$. By letting $V(\cdot) = v(\cdot)$, from Proposition 7, we have $L^\sigma(g_D) = Z(g_D, q; v) < L(g_D, \tau^*, \alpha)$. Let $h_A^\dagger(s_k = 1|r) = \mathbf{1}\{y_k(r, \tau^*) = 1\}$ for all $r \in \Gamma$. Since $\sigma = q$, $h_A^\dagger$ is a best response of the Bayesian attacker. Hence, $L(g_D, \tau^*, \alpha) = L(g_D, h_A^\dagger) \leq Z(g_D, q; v)$, which contradicts to $Z(g_D, q; v) < L(g_D, \tau^*, \alpha)$. Therefore, $Z(g_D, q; v) \geq L(g_D, \tau^*, \alpha)$. $\qquad\square$

If σ is informative, we have $L(g_D, h_A^\sigma, \sigma) \leq L(g_D, h_A^q, q)$. Hence, it also holds that $Z(g_D, \sigma; v) \geq Z(g_D, q; v)$. Lemma 5 imples $Z(g_D, \sigma; v) \geq L(g_D, \tau^*, \alpha)$.

Next, we show that when σ is non-informative. Let $h_A^\sigma(s|r) = \mu_\sigma(b|r)\mathbf{1}\{s = b\}$, for all $s, b \in W$, $r \in \Gamma$. By Lemma 4, it holds that $h_A^\sigma \in \mathcal{BR}_\Gamma^\sigma[g_D]$. Suppose in contrast that $L(g_D, \tau^*, \alpha) > Z(g_D, \sigma; v)$. Then, $h_A^\sigma \in \mathcal{BR}_\Gamma^\sigma[g_D]$ implies

$$\sum_k P_1^k \left[y_k(r, \tau^*) = 1 | g_D \right] > \sum_{k,s} \int_r v(s_k = 1, b_k = 1)\mu_\sigma(s_k = 1|r).$$

Let $h_A^\dagger : \Gamma \mapsto \Delta(W)$ such that $h_A^\dagger(s_k = 1|r) = \mathbf{1}\{y_k(r, \tau^*) = 1\}$ for all $r \in \Gamma$. Then, $h_A^\dagger \in \mathcal{BR}^\sigma[g_D]$ when σ is uniform (i.e., non-informative). Proposition 7 implies $Z(g_D, \sigma; v) \geq L(g_D, h_A^\dagger, \sigma)$, which leads to a contradiction. The inequality $L(g_D, \tau^*, \alpha) \geq L(g_D, \tau^{(N)}(\tilde{r}), \alpha_{\tau^{(N)}(\tilde{r})})$ follows the Neyman-Pearson lemma. In addition, by Venkatesaramani et al. (2021; 2023), $L(g_D, \tau^{(N)}(\tilde{r}), \alpha_{\tau^{(N)}(\tilde{r})}) \geq L(g_D, \tau^o, \alpha_{\tau^o})$. Thus, we can conclude the proof of Theorem 2. $\qquad\square$

N   PROOF OF LEMMA 1

First, we show that the test statistics $\mathcal{L}(\tilde{y}) = \sum_{j \in Q} \log\left(\rho_j(\tilde{y}_j|\widehat{H}_0)/\rho_j(\tilde{y}_j|\widehat{H}_1)\right)$ is normally distributed under $\widehat{H}_0$ and $\widehat{H}_1$, respectively, with $\mathcal{N}\left(\overline{M}, \overline{V}\right)$ and $\mathcal{N}\left(-\overline{M}, \overline{V}\right)$, where $\overline{M} = \frac{1}{2}\sum_{j \in Q} \widehat{M}_j^2$ and $\overline{V} = \sum_{j \in Q} \widehat{M}_j^2$. For each y_j, $\tilde{y}_j \sim \mathcal{N}(0,1)$ under $\widehat{H}_0$, and $\tilde{y}_j \sim \mathcal{N}(\widehat{M}_j, 1)$ under $\widehat{H}_1$. Thus, the log-likelihood ratio for each y_j is $\log\left(\frac{\rho_j(y_j|\widehat{H}_0)}{\rho_j(y_j|\widehat{H}_1)}\right)$. Since $\rho_j(\cdot|\widehat{H}_0)$ and $\rho_j(\cdot|\widehat{H}_1)$ are the density functions of normal distribution, the log-likelihood ratio becomes

$$\log\left(\frac{\frac{1}{\sqrt{2\pi}}e^{-\frac{y_j^2}{2}}}{\frac{1}{\sqrt{2\pi}}e^{-\frac{(y_j - \widehat{M}_j)^2}{2}}}\right) = \frac{(y_j - \widehat{M}_j)^2 - y_j^2}{2} = \frac{-2y_j\widehat{M}_j + \widehat{M}_j^2}{2} = -y_j\widehat{M}_j + \frac{\widehat{M}_j^2}{2}.$$

Under $\widehat{H}_0$, the mean is $\mathbb{E}[y_j|\widehat{H}_0] = 0$ and the variance is $\mathrm{Var}[y_j|\widehat{H}_0] = 1$. Hence, the mean of $\mathcal{L}(y)$ under $\widehat{H}_0$ is

$$\mathbb{E}[\mathcal{L}(y)] = \mathbb{E}\left[\sum_{j \in Q}\left(-y_j\widehat{M}_j + \frac{\widehat{M}_j^2}{2}\right)\right] = \sum_{j \in Q}\left(-\mathbb{E}[y_j]\widehat{M}_j + \frac{\widehat{M}_j^2}{2}\right) = \sum_{j \in Q}\frac{\widehat{M}_j^2}{2},$$

and the variance is

$$\mathrm{Var}[\mathcal{L}(y)] = \mathrm{Var}\left[\sum_{j \in Q}\left(-y_j\widehat{M}_j + \frac{\widehat{M}_j^2}{2}\right)\right] = \sum_{j \in Q}\mathrm{Var}[-y_j\widehat{M}_j] = \sum_{j \in Q}\widehat{M}_j^2.$$

Similarly, under $\widehat{H}_1$, the mean of $\mathcal{L}(y)$ is

$$\mathbb{E}[\mathcal{L}(y)] = \mathbb{E}\left[\sum_{j \in Q}\left(-y_j\widehat{M}_j + \frac{\widehat{M}_j^2}{2}\right)\right] = \sum_{j \in Q}\left(-\mathbb{E}[y_j]\widehat{M}_j + \frac{\widehat{M}_j^2}{2}\right) = \sum_{j \in Q}\left(-\widehat{M}_j^2 + \frac{\widehat{M}_j^2}{2}\right) = \sum_{j \in Q}-\frac{\widehat{M}_j^2}{2}.$$

In addition, the variance of $\mathcal{L}(y)$ under $\widehat{H}_1$ is

$$\mathrm{Var}[\mathcal{L}(y)] = \mathrm{Var}\left[\sum_{j \in Q}\left(-y_j\widehat{M}_j + \frac{\widehat{M}_j^2}{2}\right)\right] = \sum_{j \in Q}\mathrm{Var}[-y_j\widehat{M}_j] = \sum_{j \in Q}\widehat{M}_j^2.$$

Since the test statistics $\mathcal{L}(y)$ is normally distributed under $\widehat{H}_0$ and $\widehat{H}_1$, we have

$$Z_0 = \frac{\overline{y} - \overline{M}}{\sqrt{\overline{V}/\sqrt{m}}} \sim \mathcal{N}(0,1) \text{ and } Z_1 = \frac{\overline{y} + \overline{M}}{\sqrt{\overline{V}/\sqrt{m}}} \sim \mathcal{N}\left(\frac{-2\overline{M}}{\sqrt{\overline{V}/\sqrt{m}}}, 1\right),$$

where $\overline{y}$ is the sample mean. For a given significance level $\widehat{\alpha}$, the threshold for Z_0 is set so that $\mathrm{Pr}(Z_0 < z_{\widehat{\alpha}}) = \widehat{\alpha}$, corresponding to the value $\overline{M} + z_{\widehat{\alpha}}\sqrt{\frac{\overline{V}}{m}}$. For a given Type-II error rate $\widehat{\beta}$, the threshold for Z_1 is set so that $\mathrm{Pr}(Z_1 < z_{\widehat{\beta}}) = \widehat{\beta}$, where $z_{\widehat{\beta}}$ aligns with $-\overline{M} - z_{\widehat{\beta}}\sqrt{\frac{\overline{V}}{m}}$. To maintain the consistency of decision-making

between $\widehat{H}_0$ and $\widehat{H}_1$, the threshold at which we switch decisions from failing to reject $\widehat{H}_0$ to rejecting $\widehat{H}_0$ under $\widehat{H}_0$ and $\widehat{H}_1$ are equated. Therefore, we have

$$\sqrt{m\mathtt{M}} + z_{\widehat{\alpha}}\sqrt{\mathtt{V}} = -\sqrt{m\mathtt{M}} - z_{\widehat{\beta}}\sqrt{\mathtt{V}}.$$

Thus, $\mathcal{F}\left(\widehat{\alpha}, \widehat{\beta}\right) = m$ holds.

Next, we show the monotone relationship between $\widehat{\beta}$ and m given $\mathcal{F}\left(\widehat{\alpha}, \widehat{\beta}\right) = m$ while everything else is fixed. Since, $z_{\widehat{\beta}} = \Phi^{-1}(1 - \widehat{\beta})$, where Φ is the cumulative distribution function (CDF) of the standard normal distribution, $z_{\widehat{\beta}}$ decreases as $\widehat{\beta}$ increases as the quantile function Φ^{-1} decreases as the probability increases. As a result, $(z_{\widehat{\alpha}}, z_{\widehat{\beta}})$ decreases when $\widehat{\beta}$ increases. Therefore, $\mathcal{F}\left(\widehat{\alpha}, \widehat{\beta}\right) = m$ implies that m decreases when $\widehat{\beta}$ increases. $\qquad\square$

O   PROOF OF THEOREM 3

We first obtain the following lemma, which extends Theorem 2.7 of Dong et al. (2021).

Lemma 6. *Fix $\alpha \in (0, 1)$. Let g_D be Gaussian defined above with each $g_D^j(\cdot|b) \in \Delta(\mathcal{Y}_j)$ as the density function of $\mathcal{N}(\mathtt{M}_b^j, \mathtt{V}^j)$ given any $b \in W$, where $\mathtt{V}^j = \left(2\mathrm{sens}^j(f)/\widehat{\mathtt{M}}_j\right)^2$. Let $P_b(g_D^j)$ denote the probability distribution associated with $g_D^j(\cdot|b)$. Suppose $\max_{b,b'} |\mathtt{M}_b^j - \mathtt{M}_{b'}^j| \leq \mathrm{sens}^j(f)$. Then, it holds*

$$T\left[P_b(g_D^j), P_{b'}(g_D^j)\right](\alpha) \geq T\left[\mathcal{N}(0, 1), \mathcal{N}(\widehat{\mathtt{M}}_j, 1)\right].$$

Proof. For any two $b, b' \in W$, $y(b) = f_j(b, d) + \delta_j$ and $y(b') = f_j(b', d') + \delta_j'$ are normally distributed with means $f^j(b, d) + \mathtt{M}_b$ and $f^j(b', d') + \mathtt{M}_{b'}$, respectively, and a common variance $\mathtt{V}^j$. Then, we have

$$T\left[P_b(g_D^j), P_{b'}(g_D^j)\right](\alpha) = T\left[\mathcal{N}\left(f^j(b, d) + \mathtt{M}_b, \mathtt{V}\right), \mathcal{N}\left(f^j(b', d') + \mathtt{M}_{b'}, \mathtt{V}\right)\right](\alpha)$$

$$= \Phi\left(\Phi^{-1}(1 - \alpha) - \frac{|f^j(b, d) - f^j(b', d') + \mathtt{M}_b - \mathtt{M}_{b'}|}{\sqrt{\mathtt{V}^j}}\right),$$

where Φ is the cumulative distribution function (CDF) of the standard normal distribution. Since $\mathtt{V}^j = \left(2\mathrm{sens}^j(f)/\widehat{\mathtt{M}}_j\right)^2$ and $\max_{b,b'} |\mathtt{M}_b^j - \mathtt{M}_{b'}^j| \leq \mathrm{sens}^j(f)$, by definition of sensitivity, we obtain

$$T\left[\mathcal{N}\left(f^j(b, d) + \mathtt{M}_b, \mathtt{V}\right), \mathcal{N}\left(f^j(b', d') + \mathtt{M}_{b'}, \mathtt{V}\right)\right](\alpha) \geq \Phi\left(\Phi^{-1}(1 - \alpha) - \widehat{\mathtt{M}}_j\right)$$

$$= T\left[\mathcal{N}(0, 1), \mathcal{N}(\widehat{\mathtt{M}}_j, 1)\right](\alpha).$$

$\qquad\square$

Lemma 6 shows that distinguishing between b and b' is as hard as distinguishing between $\mathcal{N}(0, 1)$ and $\mathcal{N}(\widehat{\mathtt{M}}_j, 1)$. Thus, if the α-LRT attacker only observes y_j for jth SNV, then the maximum power he can obtain is $1 - T\left[\mathcal{N}(0, 1), \mathcal{N}(\widehat{\mathtt{M}}_j, 1)\right](\alpha)$, which leads to the WCPL for the vNM defender among all possible powers when different membership vectors are realized. considered are independent, $1 - T\left[\mathcal{N}(0, 1), \mathcal{N}(\widehat{\mathtt{M}}_j, 1)\right](\alpha)$ serves as the performance bound for every $j \in Q$.

Given any two $b, b' \in W$, define the hypothesis testing problem: H_0 : the membership vector is b versus H_1 : the membership vector is b'. From the assumption of independent SNVs, we can obtain the log-likelihood statistics

$$\mathtt{lrs}(y; g_D, b, b') \equiv \sum_{j \in Q} \log\left(\frac{\rho_D^j(y_j|H_0)}{\rho_D^j(y_j|H_1)}\right).$$

Let $P_i[\cdot|g_D]$ denote the probability distribution associated with H_i for $i \in \{0, 1\}$.

Lemma 7. *Fix $\alpha \in (0, 1)$. Let g_D be Gaussian defined above with each $g_D^j(\cdot|b) \in \Delta(\mathcal{Y}_j)$ as the density function of $\mathcal{N}(\mathtt{M}_b^j, \mathtt{V}^j)$ given any $b \in W$, where $\mathtt{V}^j = \left(2\mathrm{sens}^j(f)/\widehat{\mathtt{M}}_j\right)^2$. Suppose $\max_{b,b'} |\mathtt{M}_b^j - \mathtt{M}_{b'}^j| \leq \mathrm{sens}^j(f)$. Then, it holds for all pair $b, b' \in W$,*

$$\max_{\tau} P_1\left[\mathtt{lrs}(\tilde{y}; g_D, b, b') \geq \tau|g_D\right] \leq 1 - T\left[\mathcal{N}(0, 1), \mathcal{N}\left(\sqrt{\sum_{j \in Q} \widehat{\mathtt{M}}_j^2}, 1\right)\right](\alpha), \tag{10}$$

with $P_0\left[\mathtt{lrs}(\tilde{y}; g_D, b, b') < \tau|g_D\right] = \alpha$.

Proof. Since the SNVs are independent, the joint probability density $P(y|H_i)$ over $\mathcal{Y}$ that is equal to the product $\prod_{j \in Q} \rho_D^j(y_j|H_i)$ for $i \in \{0, 1\}$. It is a $|Q|$-fold composition of $\{\rho_D^j\}_{j \in Q}$, where each ρ_D^j accesses to the same dataset. In addition, $\max_\tau P_1 [\texttt{lrs}(\tilde{y}; g_D, b, b') \geq \tau | g_D]$ is the power of α-LRT given g_D for any $b, b' \in W$. Then, (10) follows Corollary 3.3 of Dong et al. (2021). □

Let $\mathbf{I}_{|Q|}$ denote a $|Q| \times |Q|$ identity matrix. Let $\widehat{\mathbf{M}} \equiv (\widehat{\mathbb{M}}_1, \ldots, \widehat{\mathbb{M}}_{|Q|})$. Consider two multivariate normal distribution $\mathcal{N}(0, \mathbf{I}_{|Q|})$ and $\mathcal{N}(\widehat{\mathbf{M}}, \mathbf{I}_{|Q|})$. Here, $\mathcal{N}(0, \mathbf{I}_{|Q|})$ is rotation invariant, and $\mathcal{N}(\widehat{\mathbf{M}}, \mathbf{I}_{|Q|})$ can be rotated to $\mathcal{N}\left(\sqrt{\sum_{j \in Q} \widehat{\mathbb{M}}_j^2}, 1\right)$. In addition, the rotation here is an invertible transformation. Therefore, $T\left[\mathcal{N}(0, 1), \mathcal{N}\left(\sqrt{\sum_{j \in Q} \widehat{\mathbb{M}}_j^2}, 1\right)\right](\alpha)$ is the same as the $T\left[\mathcal{N}(0, \mathbf{I}_{|Q|}), \mathcal{N}(\widehat{\mathbf{M}}, \mathbf{I}_{|Q|})\right](\alpha)$ for any α because the trade-off function is invariant under invertible transformations Dong et al. (2021). Let $\widehat{\beta} = T\left[\mathcal{N}(0, \mathbf{I}_{|Q|}), \mathcal{N}(\widehat{\mathbf{M}}, \mathbf{I}_{|Q|})\right](\alpha)$. Thus, the α-LRT with the LR statistics formulated by $\mathcal{L}(y)$ has the power $1 - \widehat{\beta}$. Therefore, it holds that $\mathcal{F}(\alpha, \widehat{\beta}) = |Q|$.

Now, let us focus on when the attacker (either Bayesian or LRT) targets a specific individual k. Given any subjective prior σ and Q, let $\mu_{1|0}^\sigma[|Q|] = \int_r \mu_\sigma(s_k = 1|r)\rho_D(r|b_k = 0)$. By Proposition 7, a Bayesian attacker's strategy that mirrors the distribution of the posterior belief leads to the WCPL for the defender. Hence, $\mu_{1|0}^\sigma[|Q|]$ captures the highest Type-II errors of the Bayesian attacker. Then, $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[|Q|]\right)$ captures the number of SNVs (i.e., $|Q|$) so that α-LRT can attain the power $\mu_{0|1}^\sigma[|Q|]$ when the set Q of SNVs of each individual are used in the dataset, leading to $L(g_D, \tau^*, \alpha) = L^\sigma(g_D)$. If $\mathcal{F}\left(\alpha, \mu_{0|1}^\sigma[|Q|]\right) \geq |Q|$, then more SNVs needs to be used to make α-LRT have the power $\mu_{0|1}^\sigma[|Q|]$. This is equivalent to $\widehat{\beta} < \mu_{0|1}^\sigma[|Q|]$, which implies $L(g_D, \tau^*, \alpha) \leq L^\sigma(g_D)$. □

P EXPERIMENT DETAILS

P.1 DATASET

Our experiments use three datasets: *Adult dataset* (UCI Machine Learning Repository), *MNIST dataset*, and *genomic dataset*. The genomic dataset was provided by the 2016 iDASH Workshop on Privacy and Security Tang et al. (2016), derived from the 1000 Genomes Project 1000 Genomes Project Consortium et al. (2015). The genomic dataset used in our experiments was initially provided by the organizers of the 2016 iDash Privacy and Security Workshop Tang et al. (2016) as part of their challenge on Practical Protection of Genomic Data Sharing Through Beacon Services. In this research, we follow Venkatesaramani et al. (2021; 2023) and employ SNVs from chromosome 10 for a subset of 400 individuals to construct the Beacon, with another 400 individuals excluded from the Beacon. We use 800 individuals with different numbers of SNVs of each individual on Chromosome 10. In the experiments, we randomly select 400 individuals from the 800 to constitute a dataset according to the uniform distribution. The experiments were conducted using an NVIDIA A40 48G GPU. PyTorch was used as the deep learning framework.

P.2 NOTES: EXPERIMENT DETAILS FOR LRTS

The output of the defender's neural network G_{λ_D} is a noise term within the range $[-0.5, 0.5]$. We assess the strength of privacy protection using the attacker's ROC curve, converting H_{λ_A}'s output to binary values $s_k \in \{0, 1\}$ by varying thresholds. A lower AUC indicates stronger privacy protection by G_{λ_D}. In addition to the proxies from Section 3.1, we use the sigmoid function to approximate the threshold-based rejection rule of the LRT. Specifically, $\mathbf{1}\{\texttt{lrs}(d_k, x) \leq \tau\}$ is approximated by $1/(1+\exp(-(\tau - \texttt{lrs}(d_k, x))))$, where $\texttt{lrs}(d_k, x)$ is the log-likelihood statistic. Similarly, the sigmoid function approximates $\mathbf{1}\{\texttt{lrs}(d_k, r) \leq \tau^{(N)}(r)\}$. The fixed- and adaptive-threshold LRT defenders optimally select g_D by solving (FixedLRT) and (AdaptLRT), as detailed in Appendix C.

P.3 NOTES: BAYESIAN DEFENDER VS. DIFFERENTIAL PRIVACY

In this experiment (Figure 1c), we illustrate the advantages of the Bayesian defender (i.e., using the BNGP strategy) over standard DP in addressing defender-customized objectives for the privacy-utility trade-off, when the same utility loss is maintained in the trade-off of privacy and utility.

In this experiment, we consider a specific loss function for the defender:

$$\ell_D(\delta, b, s) \equiv v(s, b) + \sum_{j \in Q} \kappa_j |\delta_j|,$$

Figure 2: (a)-(c): Bayesian Defender with $\kappa = 0, 1.5, 50$, respectively. (d): Different attackers under non-strategic DP with $\epsilon = 600$.

where $\kappa_j \geq 0$ represents the defender's preference for balancing the privacy-utility trade-off for the summary statistics of the j-th attribute (e.g., SNV in genomic data). In genomic datasets, each SNP position corresponds to a specific allele at a particular genomic location, and the importance of these positions can vary significantly depending on their association with diseases or traits in medical studies. Consequently, different SNPs may require varying levels of data quality and utility, necessitating less noise for some positions. For SNPs where higher data utility is crucial, we assign larger κ_j values to increase the weight of noise costs in the defender's decision-making process. This position-dependent weighting enables a more customized and refined privacy-utility trade-off.

In the experiment, we define $\vec{\kappa} = (\kappa_j)_{j \in Q}$ for SNV positions, where $\kappa_j = 0$ for 90% of the 5000 SNVs and $\kappa_j = 50$ for the remaining 10%. The BNGP strategy in this setting results in an average utility loss of 0.0001.

The sensitivity of the summary statistics function $f(\cdot)$ is given by sensitivity $= \frac{m}{K^\dagger}$ (see Appendix E), where $m = |Q|$ and $1 \leq K^\dagger \leq K$ is the number of individuals in U included in the dataset. For the experiment, the dataset comprises 400 individuals, each with 5000 SNVs, resulting in a sensitivity of $\frac{m}{K^\dagger} = 12.5$.

The scale parameter of the Laplace distribution in the DP framework is:

$$\frac{\text{sensitivity}}{\epsilon}.$$

To match the utility loss of 0.0001 (measured as the expected absolute value of the noise), the scale parameter must equal 0.0001. This implies:

$$\frac{\text{sensitivity}}{\epsilon} = 0.0001,$$

which gives $\epsilon = 1.25 \times 10^5$.

In general, the number of SNVs (m) is often much larger than the number of individuals (K), i.e., $m \gg K$. Consequently, small ϵ values (e.g., between 1 and 10) result in very large scale parameters for the Laplace distribution. Therefore, relatively large ϵ values are chosen to preserve the utility of genomic datasets. For example, in (Venkatesaramani et al., 2023), the values of ϵ are selected from $\{10,000, 50,000, 100,000, 500,000, 1 \text{ million}, 5 \text{ million}, 10 \text{ million}\}$.

P.4 NOTES: SCORE-BASED ATTACKER:

Figure 1g compares attackers under the defense trained against the score-based attacker. The Bayesian attacker significantly outperforms the others, achieving near-perfect classification, while LRT and adaptive LRT perform similarly but lag behind. As explained in (Dwork et al., 2015), the score-based attacker is assumed to

have less external information and knowledge than the Bayesian, the fixed-threshold LRT, and the adaptive LRT attackers. Theoretically, the score-based attacker uses $\mathcal{O}(n^2 \log(n))$ SNVs, where n is the number of individuals in the dataset. In the experiments for Figure 1g, to guarantee certain accuracy for the score-based attacker, we consider 20 individuals and each time a dataset of 5 individuals with 4000 SNVs being randomly sampled. In this setting, the Bayesian attacker performs very well (with AUC close to 1).

P.5   NOTES: ADULT AND MNIST DATASET

Adult Dataset   In the experiments using the Adult dataset, the original mechanism f (i.e., without privacy protection) releases the summary statistics of the Adult dataset. Specifically, we turn the attributes of the Adult dataset into binary values to simplify the representation of categorical and continuous attributes. For example, categorical attributes like "occupation" or "education level" are one-hot encoded, while continuous attributes like "age" are discretized into binary intervals. This binary transformation allows us to construct a dataset that represents the presence or absence of specific attribute values, making it compatible with our framework for privacy protection and utility optimization. The summary statistics released include the counts or proportions of individuals possessing specific binary attributes. These statistics form the basis for evaluating the membership inference risks and utility trade-offs in our experiments. By using this transformed representation, we ensure the methodology aligns with the assumptions of our privacy-utility trade-off framework.

MNIST Dataset   For the MNIST dataset, the original mechanism is a trained classifier that outputs predicted class probabilities for given input images. Specifically, this classifier is trained on the MNIST training set to perform digit recognition, mapping each image to a probability distribution over the 10-digit classes (0 through 9). In our experiments, we consider the privacy of the test data (or inference dataset) used to query the classifier. The attacker aims to infer whether a specific test image belongs to the inference dataset based on the output probabilities provided by the classifier.

P.6   NOTES: BGBP RESPONSE

The BGBP response acts as a constraint for the *defender* since the defender's choice of G induces H, which (1) represents the attacker's best response, and (2) satisfies the conditions defined by $\texttt{PH}[\vec{G}; \epsilon]$. The attacker, however, simply responds optimally to the defender's choice of G. To incorporate the conditions for H set by $\texttt{PH}[\vec{G}; \epsilon]$, we apply the penalty method to the defender's loss function. In our experiments, we relax the strict pure differential privacy framework and focus on a class of neural networks G that select ϵ for a Gaussian distribution $\mathcal{N}(0, \texttt{Var}(\epsilon))$, where $\texttt{Var}(\epsilon) = \texttt{C}/\epsilon^2$ and $\texttt{C}$ is a fixed constant. For the *composition* of five mechanisms, four are pre-designed with noise perturbation using $\mathcal{N}(0, \texttt{Var}(\epsilon))$. The defender's neural network G_5 selects ϵ for the fifth mechanism, constrained by the BGBP response with $\texttt{BDP}[\vec{G}; 5\epsilon]$. We evaluate whether the target 5ϵ can be approximately achieved if the attacker's performance aligns closely with that of a single 5ϵ-DP mechanism (*One Mechanism*), where the single 5ϵ-DP mechanism is also perturbed by Gaussian noise $\mathcal{N}(0, \texttt{Var}(5\epsilon))$. Our experimental results demonstrate that the BNGP strategy, constrained by BGBP response, successfully implements parameterized privacy in a generative manner.

P.7   ADDITIONAL EXPERIMENT:

As shown in Figure 2, the privacy strength of the defense decreases (resp. increases) as κ increases (resp. decreases), as we would expect, since κ captures the tradeoff between privacy and utility. Figure 2d demonstrates the performances of the Bayesian, fixed-threshold, and adaptive-threshold attackers under ϵ-DP defense where $\epsilon = 600$. The choice of such a large value of ϵ is explained in Appendix E). Similar to the scenarios under the Bayesian defense, the Bayesian attacker outperforms the LRT attackers under the ϵ-DP.

P.8   NETWORK CONFIGURATIONS AND HYPERPARAMETERS

The **Defender** neural network is a generative model designed to process membership vectors and produce beacon modification decisions. The input layer feeds into two fully connected layers with batch normalization and activation functions applied after each layer. The first hidden layer uses ReLU activation, while the second hidden layer uses LeakyReLU activation. The output layer applies a scaled sigmoid activation function. The output of the Defender neural network is a real value between -0.5 and 0.5, which is guaranteed by the scaled sigmoid activation function. All Defender neural networks were trained using the Adam optimizer with a learning rate of 0.001, weight decay of 0.00001, and an ExponentialLR scheduler with a decay rate of 0.988.

The **Attacker** neural network is a generative model designed to process beacons and noise to produce membership vectors. The input layer feeds into two fully connected layers with batch normalization and activation functions. The first hidden layer uses ReLU activation. The output layer applies a sigmoid activation func-

tion. All Attacker models were trained using the Adam optimizer, a learning rate of 0.0001, weight decay of 0.00001, and an ExponentialLR scheduler with a decay rate of 0.988.

The specific configurations for each model are provided in the tables below. Table 1a shows the configurations of the neural network Defender under the Bayesian, the fixed-threshold, and the adaptive-threshold attackers when the trade-off parameter κ is a vector (i.e., each $\kappa_j = \kappa$ for all $j \in Q$). Table 1b shows the configurations of Defender when the trade-off parameter is a vector; i.e., $\vec{\kappa} = (\kappa_j)_{j \in Q}$ where $\kappa_j = 0$ for the 90% of 5000 SNVs and $\kappa_j = 50$ for the remaining 10%. Table 2a lists the configurations of the neural network Attacker under the Bayesian, the fixed-threshold LRT, and the adaptive-threshold LRT defenders. Table 2b lists the configurations of Attacker under the standard ϵ-DP which induces the same $\vec{\kappa}$-weighted expected utility loss for the defender.

Table 1: Bayesian Defender Configurations

(a) Defender with scalar κ

Layer	Input Units	Output Units
Input Layer	830	1500
Hidden Layer 1	1500	1100
Hidden Layer 2	1100	500
Output Layer	500	5000

(b) Defender with vector $\vec{\kappa}$

Layer	Input Units	Output Units
Input Layer	830	1000
Hidden Layer 1	1000	3000
Hidden Layer 2	3000	4600
Output Layer	4600	5000

Table 2: Attacker Configurations

(a) Attacker vs. Defender

Layer	Input Units	Output Units
Input Layer	5000	3400
Hidden Layer 1	3400	2000
Output Layer	2000	800

(b) Bayesian Attacker vs. ϵ-DP

Layer	Input Units	Output Units
Input Layer	5000	3000
Hidden Layer 1	3000	1000
Output Layer	1000	800

P.9 COMPLEXITY ANALYSIS OF THE NEURAL NETWORKS

Here, we use `snp_dim` to denote the number of single-nucleotide variants (SNVs) per data point and `ind_dim` to represent the total number of individuals.

We provide a complexity analysis of the Attacker (D) and Defender (G) neural networks used in our general-sum GAN. This analysis covers the trainable parameters and computational complexity for both networks.

The **Attacker** takes input of dimension `snp_dim` and produces a membership vector of dimension `ind_dim`. Its architecture consists of fully connected layers, batch normalization, and activation functions. Specifically, the first linear layer maps the concatenated input to a hidden layer of dimension `Hidden_Layer_1_dim`, followed by another linear layer reducing the dimensionality to `Hidden_Layer_2_dim`, a batch normalization layer, a ReLU activation function, and a final linear layer mapping to `ind_dim` with a Sigmoid activation function for output.

The total number of trainable parameters in the Attacker is derived as follows. The first linear layer has $(\texttt{snp\_dim}) \cdot \texttt{Hidden\_Layer\_1\_dim}$ weights and `Hidden_Layer_1_dim` biases. The second linear layer includes `Hidden_Layer_1_dim` $\cdot$ `Hidden_Layer_2_dim` weights and `Hidden_Layer_2_dim` biases, while the batch normalization layer adds `Hidden_Layer_2_dim` $\cdot$ 2 scale and shift parameters. The final linear layer contributes `Hidden_Layer_2_dim` $\cdot$ `ind_dim` weights and `ind_dim` biases. Therefore, the total number of trainable parameters in the Attacker is:

$$\texttt{snp\_dim} \cdot \texttt{Hidden\_Layer\_1\_dim} + \texttt{Hidden\_Layer\_1\_dim} \cdot \texttt{Hidden\_Layer\_2\_dim}$$
$$+ \texttt{Hidden\_Layer\_2\_dim} \cdot 2 + \texttt{Hidden\_Layer\_2\_dim} \cdot \texttt{ind\_dim} + \texttt{ind\_dim}.$$

For computational complexity during a forward pass, the dominant operations occur in the linear layers, leading to a total complexity of:

$$\mathcal{O}\big(B \cdot [\texttt{snp\_dim} \cdot \texttt{Hidden\_Layer\_1\_dim} + \texttt{Hidden\_Layer\_1\_dim} \cdot \texttt{Hidden\_Layer\_2\_dim}$$
$$+ \texttt{Hidden\_Layer\_2\_dim} \cdot \texttt{ind\_dim}]\big),$$

where B is the batch size.

The **Defender** network takes input of dimension $\mathtt{ind\_dim} + \mathtt{noise\_dim}$ and produces an output of dimension $\mathtt{snp\_dim}$. Its architecture comprises multiple fully connected layers, batch normalization layers, and activation functions. The first linear layer maps the input to a hidden layer of dimension $\mathtt{Hidden\_Layer\_1\_dim}$, followed by a second linear layer reducing the dimensionality to $\mathtt{Hidden\_Layer\_2\_dim}$. Batch normalization and ReLU activation are applied at this stage. A third linear layer further reduces the dimensionality to $\mathtt{Hidden\_Layer\_3\_dim}$, followed by another batch normalization layer and a LeakyReLU activation. Finally, the output layer maps the representation to $\mathtt{snp\_dim}$ with a ScaledSigmoid activation function for output.

The total number of trainable parameters in the Defender is as follows. The first linear layer contributes $(\mathtt{ind\_dim} + \mathtt{noise\_dim}) \cdot \mathtt{Hidden\_Layer\_1\_dim}$ weights and $\mathtt{Hidden\_Layer\_1\_dim}$ biases. The second linear layer includes $\mathtt{Hidden\_Layer\_1\_dim} \cdot \mathtt{Hidden\_Layer\_2\_dim}$ weights and $\mathtt{Hidden\_Layer\_2\_dim}$ biases, and the batch normalization layer adds $\mathtt{Hidden\_Layer\_2\_dim} \cdot 2$ scale and shift parameters. The third linear layer has $\mathtt{Hidden\_Layer\_2\_dim} \cdot \mathtt{Hidden\_Layer\_3\_dim}$ weights and $\mathtt{Hidden\_Layer\_3\_dim}$ biases, while the second batch normalization layer adds $\mathtt{Hidden\_Layer\_3\_dim} \cdot 2$ scale and shift parameters. The output layer includes $\mathtt{Hidden\_Layer\_3\_dim} \cdot \mathtt{snp\_dim}$ weights and $\mathtt{snp\_dim}$ biases. Thus, the total number of trainable parameters is:

$$(\mathtt{ind\_dim} + \mathtt{noise\_dim}) \cdot \mathtt{Hidden\_Layer\_1\_dim} + \mathtt{Hidden\_Layer\_1\_dim} \cdot \mathtt{Hidden\_Layer\_2\_dim}$$
$$+ \mathtt{Hidden\_Layer\_2\_dim} \cdot 2 + \mathtt{Hidden\_Layer\_2\_dim} \cdot \mathtt{Hidden\_Layer\_3\_dim}$$
$$+ \mathtt{Hidden\_Layer\_3\_dim} \cdot 2 + \mathtt{Hidden\_Layer\_3\_dim} \cdot \mathtt{snp\_dim}$$
$$+ \mathtt{snp\_dim}.$$

The forward-pass computational complexity is dominated by the linear layers, resulting in:

$$\mathcal{O}\big(B \cdot [(\mathtt{ind\_dim} + \mathtt{noise\_dim}) \cdot \mathtt{Hidden\_Layer\_1\_dim}$$
$$+ \mathtt{Hidden\_Layer\_1\_dim} \cdot \mathtt{Hidden\_Layer\_2\_dim} + \mathtt{Hidden\_Layer\_2\_dim} \cdot \mathtt{Hidden\_Layer\_3\_dim}$$
$$+ \mathtt{Hidden\_Layer\_3\_dim} \cdot \mathtt{snp\_dim}]\big).$$

In summary, the Attacker and Defender networks are both computationally efficient and scalable. Their forward-pass complexities scale linearly with the batch size and input dimensions, while the number of trainable parameters remains manageable for modern deep-learning hardware. This ensures that the networks are expressive enough for the task while being feasible for practical implementation.

P.10 AUC Values of ROC Curves with Standard Deviations

Tables 3, 4, and 5 show the AUC values of the ROC curves shown in the plots of the experiments.

Table 3: AUC Values For Different Attackers Under Varying κ

Attacker	Figure 2a ($\kappa = 0$)	Figure 1a and 2b ($\kappa = 1.5$)	Figure 2c ($\kappa = 50$)
Bayesian attacker	0.5205 ± 0.0055	0.7253 ± 0.0069	0.8076 ± 0.0040
Fixed-Threshold LRT attacker	0.5026 ± 0.0062	0.6214 ± 0.0322	0.7284 ± 0.0089
Adaptive-Threshold LRT attacker	0.1552 ± 0.0100	0.1716 ± 0.0144	0.1719 ± 0.0174

Table 4: AUC Values of Attackers For Figures 1b to 1h

Figure	Scenarios	AUC $\pm$ std	Condition
1b	Under Bayesian Defender	0.7237 ± 0.0066	$\kappa = 1.5$
	Under Fixed-threshold LRT Defender	0.9124 ± 0.0026	$\kappa = 1.5$
	Under Adaptive-threshold LRT Defender	0.7487 ± 0.0027	$\kappa = 1.5$
1c	Under Bayesian Defender	0.5318 ± 0.0222	$\vec{\kappa}$
	Under ϵ-DP Defender	0.9153 ± 0.0025	$\vec{\kappa}$
1d	Bayesian Attacker	0.5600 ± 0.0040	$\kappa = 1.5$
	Fix-LRT Attacker	0.5287 ± 0.0052	$\kappa = 1.5$
	Adp-LRT Attacker	0.1431 ± 0.0120	$\kappa = 1.5$
	Score-Based Attacker	0.1267 ± 0.0207	$\kappa = 1.5$
1e	Bayesian Attacker	0.6317 ± 0.0050	
	Fix-LRT Attacker	0.5865 ± 0.0060	
	Adp-LRT Attacker	0.1722 ± 0.0752	
	Score-Based Attacker	0.1223 ± 0.0170	
1f	Bayesian Attacker	0.5868 ± 0.0035	
	Fix-LRT Attacker	0.5615 ± 0.0065	
	Adp-LRT Attacker	0.2076 ± 0.0160	
	Score-Based Attacker	0.1229 ± 0.0028	
1g	Bayesian Attacker	1 ± 0	
	Fix-LRT Attacker	0.8618 ± 0.0019	
	Adp-LRT Attacker	0.2221 ± 0.0106	
	Score-Based Attacker	0.1542 ± 0.0227	
1h	Bayesian Attacker	0.7422 ± 0.0085	$\kappa = 1.5$
	Decision-Tree Attacker	0.6609 ± 0.0110	$\kappa = 1.5$
	SVM Attacker	0.5226 ± 0.0108	$\kappa = 1.5$

Table 5: AUC Values of Figure 1i

Scenarios	AUC $\pm$ std
Composition ($\epsilon = 0.05$)	0.7387 ± 0.0050
One Mechanism ($\epsilon = 0.05$)	0.7427 ± 0.0063
Composition ($\epsilon = 0.1$)	0.8033 ± 0.0057
One Mechanism ($\epsilon = 0.1$)	0.8241 ± 0.0035
Composition ($\epsilon = 0.3$)	0.8921 ± 0.0037
One Mechanism ($\epsilon = 0.3$)	0.9018 ± 0.0033
Composition ($\epsilon = 0.6$)	0.9108 ± 0.0032
One Mechanism ($\epsilon = 0.6$)	0.9201 ± 0.0032
Composition ($\epsilon = 1$)	0.9318 ± 0.0031
One Mechanism ($\epsilon = 1$)	0.9373 ± 0.0030