Thoughts and Lessons on Using Visual Foundation Models for Manipulation

Abstract

Training vision-based robotic systems from scratch is both computationally expensive and memory intensive. To mitigate these challenges, recent approaches forgo end-to-end training in favor of adopting visual representations from visual foundation models – large scale models designed for broad task transferability. Recent years have seen numerous vision foundation models emerge, including several designed specifically for manipulation tasks. However, we still lack clear principles for what makes these models effective for robotics applications. To address this gap, we systematically evaluate vision foundation models to understand what makes them effective for offline robotic learning. We find that across nine diverse vision encoders, a representation's ability to reconstruct edges and predict key points strongly correlates with its performance on manipulation tasks. Extensive correlation analysis across 21 manipulation tasks consistently shows that representations preserving edge and key point information achieve the highest environment success rates. These findings appear to challenge conventional wisdom about reconstruction-based pre-training and offer a new lens for understanding what makes vision representations effective for robotics.

1 Introduction

Figure 1: Visual encoders exhibit substantial variability in their effectiveness when deployed in manipulation tasks with imitation learning. We examine downstream auxiliary tasks that can help explain the variability, providing insight on what is important in visual representations when trying to accomplish manipulation tasks.

Consider the challenge of a robot learning to manipulate its environment directly from raw images. In contrast to image classification systems, robotic vision systems must understand not only what objects are present, but their physical properties, spatial relationships, and how they will respond to interaction.

Training a system from scratch to both understand visual scenes and control actions requires enormous amounts of robot data and computation (Finn et al., 2016). Vision foundation models offer a promising solution to this bottleneck: by leveraging visual representations pretrained on large datasets, robots can start with a strong prior about the visual world. Prior work has shown these pretrained representations can transfer surprisingly well to robotics tasks, even when trained on out-of-domain data (Parisi et al., 2022). Building on this insight, several foundation models have been developed specifically for robotic applications (Radosavovic et al., 2022; Nair et al., 2022; Ma et al., 2022; 2023; Chen et al., 2024).

Despite widespread adoption of pretrained vision representations in robotics, the characteristics that make them effective for control remain largely unclear. While several works have studied different aspects of these representations—from inductive biases (Ze et al., 2023; Yen-Chen et al., 2020) to robustness (Burns et al., 2024) and cross-environment performance (Parisi et al., 2022; Majumdar et al., 2023)—we lack clear principles for selecting and adapting them for manipulation tasks. To address this gap, we conduct a systematic evaluation of nine diverse encoders—ranging from general-purpose to robotics-specific—across 21 manipulation tasks.

Consistent with Majumdar et al. (2023), we find that no single pre-trained representation uniformly outperforms others across all tasks. However, while investigating these encoders, we made a curious discovery: there exist several easy-to-compute diagnostic measures of a visual encoder that are strongly correlated with downstream robotic performance. Specifically, a representation's ability to capture accurate keypoints and reconstruct high-fidelity edges shows remarkably strong correlation with manipulation performance (Pearson $\hat{\rho}_r = 0.92$, Spearman $\hat{\rho}_s = 0.88$). Visual analysis using Sobel filters on reconstructions reveals these measures align with a model's ability to precisely locate objects and their boundaries, capabilities that are crucial for manipulation.

Our contributions are as follows:

1. Through extensive evaluation across 21 manipulation tasks, we identify which vision encoders consistently excel at robotic control. Our results show consistency across both behavior cloning and offline reinforcement learning, providing clear guidance for the robotics community on representation selection.

2. We propose easy-to-compute diagnostic measures that strongly predict a vision encoder's performance on downstream manipulation tasks. In particular, we show that edge reconstruction quality and keypoint prediction accuracy are remarkably good predictors of manipulation success.

3. We demonstrate that representations trained with discriminative pre-training objectives consistently outperform those trained with reconstructive objectives. This finding helps resolve an apparent contradiction in the literature between the effectiveness of supervised versus self-supervised pretraining. Namely, we show that the pre-training objective, rather than the source of supervision, is what matters most for downstream robotic control.

2 Related Works

Pre-trained Representations for Robotic Manipulation In robotic manipulation, visual pre-training learns transferable features for downstream tasks. Parisi et al. (2022) demonstrated that visual representations can perform as well as ground-truth state representations, showing that using learned representations alone can be highly effective. Thus, with the rise of foundation models (Bommasani et al., 2021), researchers have begun leveraging these large-scale representations to tackle initialization challenges (Finn et al., 2016).

This insight has led to the adoption of general-purpose vision models for learning manipulation skills. Additionally, vision encoders such as MVP, R3M, VIP, and VC1 (Radosavovic et al., 2022; Nair et al., 2022; Ma et al., 2022; Majumdar et al., 2023) capture physical dynamics by training on robotics-adjacent datasets (Shan et al., 2020; Goyal et al., 2017; Grauman et al., 2022). Other approaches incorporate inductive biases for grasping and pose estimation (Ze et al., 2023).

Meanwhile, some studies (Hansen et al., 2023; Sharma et al., 2023) suggest that training from scratch or fine-tuning pre-trained models can also yield strong results. In this work, we evaluate off-the-shelf vision encoders, comparing both manipulation-specific and general-purpose models. Our goal is to develop data-driven metrics to assess representation quality in manipulation tasks, helping guide future advancements in designing pre-trained vision models.

Representation Evaluation and Benchmarking in Robotics   Benchmarking foundation vision models for robotic tasks has been extensively studied. Hu et al. (2023) identified behavior cloning and inverse reinforcement learning as key paradigms for analyzing visual representations. Several studies (Burns et al., 2024; Schneider et al., 2023; Sax et al., 2021) evaluate out-of-distribution (OOD) performance of vision encoders, while others (Parisi et al., 2022; Hu et al., 2023) focus on in-distribution performance, which aligns closely with our work.

A key discussion in this space concerns self-supervised versus supervised vision pre-training and their effectiveness for manipulation tasks (Parisi et al., 2022; Burns et al., 2024). Majumdar et al. (2023) found that no single representation consistently outperforms others and introduced the VC-1 encoder, which we include in our evaluation.

Beyond benchmarking, researchers have explored the characteristics of effective representations. Wulfmeier et al. (2021) studied how dimensionality and disentanglement impact multitask performance, while Tomar et al. (2023) analyzed the role of auxiliary training objectives. Both studies, along with Majumdar et al. (2023), suggest that no universal learning algorithm or representation excels across all robotic tasks.

Another line of work highlights the benefits of inductive biases. Burns et al. (2024); Yen-Chen et al. (2020) demonstrated that segmentation-oriented inductive biases improve performance in robotics tasks. To this end, we include SAM (Kirillov et al., 2023) in our evaluation suite. Our work builds on these efforts by identifying key representation qualities that influence manipulation performance.

3   Background

To evaluate vision representations for robotics, we need methods that can effectively learn from offline datasets of expert demonstrations. We focus on two such approaches: behavior cloning, which directly mimics expert actions, and offline reinforcement learning, which learns a value function from demonstrations. In both cases, we maintain a simple architecture (Figure 2) where states and goals are processed through the vision encoder being evaluated.

Behavior Cloning   Behavior cloning seeks to approximate expert behavior by learning a state-conditional action distribution $\pi_\theta^{BC}(a|s)$. We implement this by training a three-layer MLP to regress expert actions onto scene embeddings produced by the vision encoder ϕ. Specifically, for state-action pairs (s_E, a_E) sampled from the expert dataset D_E, we minimize $\min_\theta \mathbb{E}_{a_E, s_E \sim D_E} \|\pi_\theta^{BC}(a|\phi(s_E)) - a_E\|_2^2$. The state space consists of image embeddings augmented with goal image embeddings, excluding proprioception to focus our evaluation on visual representations.

Offline Reinforcement Learning   We also evaluate representations using implicit Q-Learning (IQL) (Kostrikov et al., 2022). To maintain consistency with our behavior cloning experiments and focus purely on evaluating visual representations, we use inverse Q-Learning (Garg et al., 2021) to estimate Q-values directly from expert demonstrations without reward signals, after which implicit Q-learning estimates its V function. This creates a reward-agnostic implicit Q-learning algorithm. Like our behavior cloning experiments, we exclude proprioception data and train only on visual representations. While other offline reinforcement learning methods exist, most require either reward signals (e.g., CQL (Kumar et al., 2020), SAC-n (An et al., 2021)), or environment interaction (e.g., GAIL (Ho & Ermon, 2016)), making them unsuitable for our evaluation framework.

Figure 2: **Imitation algorithms.** We evaluate visual representations using offline imitation methods that learn from expert demonstrations. After training on expert datasets, policies $\pi(a|\phi(s))$ are evaluated in their respective environments.

3.1 Environments

We aim to study the effectiveness of pre-trained visual representations in how they encapsulate information about any given scene, such as the acting agent, the objects in the environment, and the goal of the tasks. To this end, we select environments based on the following criteria: **(a)** they must be renderable into images to be encoded by visual representations; **(b)** solvable using only visual representations without proprioception data ensuring that the agent acts solely on visual representations; **(c)** encompass a diverse range of tasks with varying complexities, such as grasping, nudging, or hand gripping; and **(d)** have variable goal states and starting configurations to promote generality in the analysis.

With these criteria in mind, we arrive at 21 robotic manipulation tasks from the Fetch Suite (Plappert et al., 2018), AdroitHand Suite Rajeswaran et al. (2017), and Metaworld Suite (Yu et al., 2020). We created experts that could solve these three environments with at least 95% success rate. These experts provided offline datasets for our behavior cloning and offline reinforcement learning experiments. Details about the environments and experts are discussed in Appendix A. Examples of environment renderings are shown in Figure 3.

Figure 3: A sample rendering of some of the environments in our evaluation suite.

3.2 Vision Encoders

We evaluate nine off-the-shelf, frozen vision encoders, each encode 224×224 RGB renderings of environment scenes into vector representations. We include both models specifically trained for manipulation tasks and foundation models trained on internet-scale datasets. The selected encoders span diverse pretraining objectives, from prediction and distillation to contrastive and reconstruction approaches. A full list of considered encoders and their pretraining objective can be seen in Table 1.

4 Experimental Investigation of Vision Encoders

In this section, we evaluate the performance different vision encoders across a diverse set of robotic tasks. We focus on understanding how different pre-training strategies, task complexities, and offline learning paradigms impact the success rates of policies for robotic tasks.

4.1 Behavioral Cloning

We evaluated behavior cloning across 21 environments by regressing expert actions onto image embeddings from the vision encoders. For each policy, we pass both the current scene and goal state images through the encoder. The resulting embeddings are concatenated and processed through a three-layer MLP with hidden layers [256, 128, 64] to predict a four-dimensional action vector. We trained policies using 2000 expert trajectories per environment. Additional training details can be found in Appendix B.

In Figure 1, we see that SAM representations do the best on average, even surpassing the average success rates on policies pre-trained with manipulation-based representations. In agreement with Hu et al. (2023), we note that the ResNet50-based representations, (R3M, VIP, MOCOv3) are quite competitive, surpassing the success rates of all ViT representations except for those of SAM representations.

Representations for Manipulation are more Sample Efficient. Data efficiency has always been an area of interest for robotics and in general imitation learning. Particularly for robotics, large-scale high quality data collection is time-consuming, and logistically complex. Thus finding a representation that does well in a small sample regime is useful.

To study sample efficiency, we choose environments where the average success rate was at least 80 percent across all representations in our behavior cloning evaluation. We identified five environments: button press, window open, plate slide, door close, and window close. For almost all representations, these environments can be solved with near perfect accuracy with as little as 40 demonstrations. We examine performance after training using 5, 10 and 40 expert demonstrations.

From Figure 4, we can see that generally, pre-trained representations for manipulation are more sample efficient. MoCov3 is the most sample efficient relative to general pre-trained representations, as it eventually solves the environments with 100 percent success using 40 trajectories. However it is not as sample efficient as R3M, or VIP since these representations can solve the environment at a higher success rate with fewer expert trajectories. In general, representations trained specifically for manipulation tasks are more effective when sample sizes are small, which is aligned with manipulation pre-training literature (Radosavovic et al., 2022; Nair et al., 2022).

4.2 Behavior Cloning versus Offline Reinforcement Learning

In addition to behavioral cloning, we also evaluate the effectiveness of various visual encoders when using offline reinforcement learning. Specifically, we use our reward-agnostic version of implicit Q-learning, training each policy for 10,000 gradient steps on 2,000 expert trajectories. We chose these parameters to make success rates comparable with our behavior cloning results. Training details and the algorithm description can be found in Appendix B and Section 3 respectively.

A surprising pattern emerges when we compare behavior cloning and offline reinforcement learning performance across different types of pretrained representations. While one might expect offline reinforcement

Figure 4: **Sample efficiency of representations.** Behavior cloning trained on 5, 10, and 40 expert demonstrations. Representations trained for manipulation such as R3M, VIP are more sample efficient in general as they achieve higher success rates even with just 5 expert demonstrations. MoCov3 representations are also competitive in the low sample regime. Sample efficiency plots for button-press, window-open, and window-close are shown in Appendix D

Figure 5: **Success rates with offline reinforcement learning with different representations.** In agreement with Figure 1, we see that the representations with reconstruction pre-training objectives perform worse.

learning to consistently improve upon behavior cloning, we find this benefit depends strongly on how the representation was pretrained.

Reconstruction-based representations struggle with offline RL Models pretrained with reconstruction objectives show inconsistent benefits from offline reinforcement learning–for example MAE improves by 12% on Gymnasium tasks but declines by 11% on Metaworld tasks, while MVP, and VC1 both see lower success rates by using offline reinforcement learning. In contrast, representations trained with contrastive objectives (DINO, MOCOv3, CLIP) show consistent improvements under offline reinforcement learning.

Manipulation-specific representations prefer behavior cloning Even more surprisingly, representations specifically pre-trained for manipulation (VC1, VIP, MVP, R3M) perform worse with offline reinforcement learning compared to behavior cloning. This effect is particularly striking for R3M, which excels

at behavior cloning but struggles with offline reinforcement learning, consistent with findings from Hu et al. (2023).

There has been much recent investigation on when one should use behavior cloning and when one should use offline reinforcement learning, and the relative strengths of both methods with respect to the expert occupancy distribution being mode covering or mode seeking (Ke et al., 2021; Ghasemipour et al., 2020). In Appendix F, we carry out a small investigation of settings where offline reinforcement learning and behavior cloning excel and struggle. For the purpose of our main findings, we see that there is no large difference in encoder performances due to occupancy mode behavior, regardless of which training method we select.

Figure 6: **Representations trained for manipulation perform better using behavior cloning.** In fact, aside from VIP which sees no gain, the manipulation representations achieve lower rates of success. Difference plots for Gymnasium and Metaworld are shown side by side in Appendix C

5 What Qualities of Visual Representations Matter for Manipulation?

The goal of this section is to investigate the metrics that can predict how well visual representations can perform in manipulation tasks. We propose two types metrics: performance in key point prediction and performance in image reconstruction.

Key point prediction is a discriminative task where the representations are probed for information on key points such as positions of arm joints, end effectors, objects, or goal locations in the scene. We define key point prediction as modeling $P(\mathbf{v}|\phi(S))$, where $\phi(S)$ represents the encoded scene S from the expert demonstration and $\mathbf{v}$ represents the vector of key points, which can include goals positions, arm and effector positions and velocities, and scene object positions. Representations excelling in key point prediction highlight that the features embed task-relevant information like spatial relationships among key objects and understanding precise manipulation dynamics.

Reconstruction tasks focus on using representations to reconstruct current scenes or scenes k-steps into the future. We define reconstruction tasks to model $P(S|\phi(S))$. That is, we learn to recover the input distribution of scenes that are encoded by the encoder $\phi(S)$. Representations that excel at high-fidelity scene reconstruction suggest that they encode information around scene understanding and model transitions.

To evaluate our hypothesis that both metrics are correlated with imitation learning success, we designed a suite of experiments to assess these predictive and reconstructive capabilities of various vision encoders. These experiments test the ability of encoders to extract task-relevant features and reconstruct high-fidelity image representations of current and future scenes.

5.1 Key Point Prediction is Correlated with Success Rates

Following Hu et al. (2023), we approach key point prediction with the linear probing method. We took the representations of 100 Metaworld trajectories, each rendered with 150 scenes. For each scene, the linear probes learned the positions and rotations of the arm joints, and the positions of objects within the scenes, such as hammers, blocks, walls, and windows. The probe also learned the goal positions for each trajectory. Each linear probe uses a linear head and minimizes square error of the key point position vectors.

Figure 7 shows an overall negative correlation between the log of validation loss and the behavior cloning success rates for each vision representation. The ability to predict the goal position shows a strong negative

correlation between its log of prediction loss and behavior cloning success rate ($\hat{\rho}_s = -0.833$ for Spearman, $\hat{\rho}_r = -0.921$ for Pearson). Meanwhile, predicting the arm's key positions showed a weaker correlation ($\hat{\rho}_s = -0.767$ for Spearman, $\hat{\rho}_r = -0.874$ for Pearson). However, while slightly smaller in magnitude, these relationships were still strongly negative. That the arm positions had the lowest correlation is expected, as successful task completion can be achieved through multiple valid arm configurations—the same task goal can be reached with different joint angles and positions. In contrast, object and goal positions in the scene have a more direct, one-to-one relationship with task success, as they uniquely define the desired end state of a task.

Figure 7: **Correlation between key point prediction validation loss and behavior cloning performance**. Lower validation loss in predicting key points correlates with higher behavior cloning success rates. Reconstruction-based encoders (MAE, VC1, and MVP) show both higher prediction losses and lower success rates. Additional correlations for object position prediction and combined key point positions, along with outlier analysis, are provided in Appendix E.

These correlations suggest that representations that are better at predicting positions in a scene tend to achieve higher success rates in behavior cloning. To verify the robustness of this relationship, we conducted additional analyses to measure the sensitivity of these correlative values. Even when excluding SAM from our analysis, the correlations remain strong ($\hat{\rho}_s = -0.857$ and $\hat{\rho}_r = -0.903$; see Appendix E). Furthermore, a DFBETA analysis (Kleinbaum et al., 1988) confirms that SAM does not unduly influence these correlations. These results strongly support the finding that a representation's position prediction ability, measured by log of validation loss, correlates with its behavior cloning performance.

5.2 Reconstructive Abilities are Correlated with Environment Success Rates

To evaluate the reconstructive abilities of various encoders, we encode 224×224 RGB images from expert trajectories and attempt to reconstruct the current scene as well as scenes 5 and 20 steps into the future. The reconstruction network uses four transposed convolution layers and combines square error loss with VGG-based perceptual loss Johnson et al. (2016). The perceptual loss proved crucial. No representation achieved high-fidelity reconstructions without it.

We evaluate reconstruction quality using two metrics: pixel-wise distance and edge preservation via Sobel edge detection (Kanopoulos et al., 1988), between reconstructions and original scenes. Figure **??** shows that behavior cloning success rates correlate strongly and negatively with pixel differences when reconstructing the current scene (Spearman correlation $\hat{\rho}_s = -0.817$ and Pearson correlation $\hat{\rho}_r = -0.805$). Similar strong

Figure 8: **Scene reconstruction quality correlates with representation performance**. Visualizations show reconstructed scenes, pixel-wise error maps, and Sobel edge detection for SAM (top) and MVP (bottom). SAM, which was the best-performing model, produces accurate reconstructions with clear edges. In contrast, MVP fails to capture critical scene elements.

correlations also hold for 5-step and 20-step future scene reconstructions, with analyses available in Appendix G.

The relationship between reconstruction quality and model performance is visually apparent when comparing our best and worst-performing models, demonstrated in Figure 8. SAM's reconstruction shows sharp edges around the block and end effector, with low pixel-wise errors. In contrast, MVP's reconstruction fails to capture these critical scene elements, showing high pixel-wise errors and poorly defined edges. Surprisingly, despite their reconstruction-based pre-training, MAE, MVP, and VC1 representations perform worse at reconstruction than other pre-trained models, which we discuss further in Section 5.3. Additional reconstruction examples are shown in Appendix G.

Moving to our next experiment, we see reconstruction of edges is also correlated with success rates. To evaluate edge reconstruction quality, following Kirillov et al. (2023) we apply Sobel filters to both original and reconstructed current scenes, comparing their MSE and structural similarity index measure (SSIM) (Wang et al., 2004). We observe strong negative correlations between edge reconstruction loss and behavior cloning success rates in Figure 9 (Pearson $\hat{\rho}_r = -0.88$ and Spearman $\hat{\rho}_s = -0.87$). The edge structural similarity shows similarly strong correlations (Pearson $\hat{\rho}_r = -0.92$, Spearman $\hat{\rho}_s = -0.88$). This suggests that the ability to encode edge information is particularly important for downstream manipulation tasks.

Our analysis of both key point prediction and reconstruction tasks reveals a consistent pattern: representations that can predict key points with lower validation loss and reconstruct scenes with lower errors achieve better manipulation performance. Notably, reconstruction-pre-trained representations struggle with both key point prediction and scene reconstruction fidelity. Meanwhile, representations trained with discriminative objectives excel at both tasks. These results suggest that effective robotics representations should perform well on both discriminative and generative auxiliary tasks.

5.3 Understanding the Impact of Pretraining Objectives on Robotic Performance

There is an apparent contradiction in the vision-based robotics literature. Parisi et al. (2022) showed that the self-supervised MoCo representations outperforms supervised ones like CLIP and ImageNet pre-trained ResNets, in robotic manipulation. Yet, Burns et al. (2024) found supervised representations on ImageNet performed strongest. We propose that this apparent conflict can be resolved by reframing the comparison:

Figure 9: **Edge reconstruction quality correlates with manipulation performance**. Both edge reconstruction error (left) and structural similarity (right) show strong correlations with behavior cloning success rates. Interestingly, reconstruction-pretrained models (MAE, MVP, VC1) consistently show poor edge preservation.

rather than supervised versus self-supervised, the key distinction lies in whether representations are pre-trained with reconstructive or discriminative objectives.

To understand this distinction, we need to examine how these pretraining objectives fundamentally differ. Reconstructive approaches like masked autoencoding focus on rebuilding input images at the pixel level, often after masking patches. While masking creates regularized representations, the resulting representations embeds inherent reconstruction errors that downstream manipulation policies must learn from. In contrast, discriminative approaches optimize representation spaces to capture semantic relationships–either through direct prediction of supervised signals or through contrastive learning between positive and negative pairs (Geiping et al., 2023), facilitating downstream policy learning. Table 1 classifies common vision encoders along these lines.

Encoder	Objective	Type
SAM	Segmentation Prediction	Supervised
MOCOv3	Self Contrastive	Self-Supervised
R3M	Time Language Contrastive	Self-Supervised
VIP	Value function prediction	Supervised
DINOv2	Self-distillation	Self-Supervised
CLIP	Text Image Contrastive	Supervised
MAE	**Masked Image Reconstruction**	Self-Supervised
VC1	**Masked Image Reconstruction**	Self-Supervised
MVP	**Masked Image Reconstruction**	Self-Supervised

Table 1: Pretraining objectives of vision encoders. We provide additional details such as the pre-training data set and architectures used in Appendix B.1

When we analyze our results through this lens of reconstructive versus discriminative pre-training, a clear pattern emerges. Across our experiments, representations trained with discriminative objectives, whether supervised or self-supervised, consistently outperform those trained with reconstructive objectives. Most surprisingly, reconstruction-pretrained models (MAE, MVP, VC1) perform poorly even at reconstruction

tasks. Despite being explicitly trained to reconstruct images, these models struggle to capture fine-grained details and edge information critical for manipulation as seen in Figures **??** and 9

We hypothesize this performance gap likely stems from fundamental differences in how these objectives structure representation spaces. Discriminative approaches naturally emphasize meaningful feature separation and semantic understanding. In contrast, reconstructive approaches focus on pixel-level fidelity, potentially at the cost of semantic abstraction. This distinction helps explain the strong performance of models like SAM and DINOv2, whose pretraining regimes are known to produce features that facilitate segmentation (Kirillov et al., 2023; Oquab et al., 2023). Similarly, data augmentations and contrastive learning in MoCOv3 and DINOv2 help encode localized features (Chen et al., 2021; Oquab et al., 2023), which proves valuable for manipulation tasks.

6 Conclusion

In this work, we conducted a systematic evaluation of pretrained vision representations for robotic manipulation, examining their performance across 21 tasks in three environments. Our analysis reveals that the distinction between reconstructive and discriminative pre-training objectives is more crucial than the supervised versus self-supervised categorization. Representations trained with discriminative objectives consistently outperform those trained with reconstructive objectives across both behavior cloning and offline reinforcement learning tasks.

We identified three diagnostic metrics—keypoint prediction, scene reconstruction, and edge preservation—that strongly correlate with a representation's manipulation performance. Surprisingly, even models pretrained with reconstructive objectives struggled with reconstruction tasks, suggesting these objectives may not effectively capture the fine-grained details needed for manipulation. These findings help explain seemingly contradictory results in prior work comparing supervised and self-supervised representations.

Based on these findings, we hypothesize that future vision encoders for robotics might benefit from combining discriminative objectives with carefully designed reconstruction losses that preserve structural information. For example, incorporating perceptual losses or explicit edge preservation during pretraining might help capture the fine-grained details that prove crucial for manipulation tasks. The landscape of vision encoders is vast, and these insights offer promising directions for further exploration.

References

Rishabh Agarwal, Marlos C Machado, Pablo Samuel Castro, and Marc G Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. In *International Conference on Learning Representations*, 2021.

Gaon An, Seungyong Moon, Jang-Hyun Kim, and Hyun Oh Song. Uncertainty-based offline reinforcement learning with diversified q-ensemble. *Advances in neural information processing systems*, 34:7436–7447, 2021.

Mihael Ankerst, Markus M Breunig, Hans-Peter Kriegel, and Jörg Sander. Optics: Ordering points to identify the clustering structure. *ACM Sigmod record*, 28(2):49–60, 1999.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

Kaylee Burns, Zach Witzel, Jubayer Ibn Hamid, Tianhe Yu, Chelsea Finn, and Karol Hausman. What makes pre-trained visual representations successful for robust manipulation? In *8th Annual Conference on Robot Learning*, 2024.

Ricardo JGB Campello, Davoud Moulavi, and Jörg Sander. Density-based clustering based on hierarchical density estimates. In *Pacific-Asia conference on knowledge discovery and data mining*, pp. 160–172. Springer, 2013.

Shizhe Chen, Ricardo Garcia, Ivan Laptev, and Cordelia Schmid. Sugar: Pre-training 3d visual representations for robotics. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18049–18060, 2024.

Xinlei Chen, Saining Xie, and Kaiming He. An empirical study of training self-supervised vision transformers. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 9640–9649, 2021.

Yen-Chi Chen, Christopher R Genovese, and Larry Wasserman. A comprehensive approach to mode clustering. *Electronic Journal of Statistics*, 10(1), 2016.

Tianhong Dai, Kai Arulkumaran, Tamara Gerbert, Samyakh Tukra, Feryal Behbahani, and Anil Anthony Bharath. Analysing deep reinforcement learning agents trained with domain randomisation. *Neurocomputing*, 493:143–165, 2022.

Chelsea Finn, Sergey Levine, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

Divyansh Garg, Shuvam Chakraborty, Chris Cundy, Jiaming Song, and Stefano Ermon. Iq-learn: Inverse soft-q learning for imitation. In *Thirty-Fifth Conference on Neural Information Processing Systems*, 2021.

Jonas Geiping, Quentin Garrido, Pierre Fernandez, Amir Bar, Hamed Pirsiavash, Yann LeCun, and Micah Goldblum. A cookbook of self-supervised learning. *arXiv preprint arXiv:2304.12210*, 2023.

Seyed Kamyar Seyed Ghasemipour, Richard Zemel, and Shixiang Gu. A divergence minimization perspective on imitation learning methods. In *Conference on robot learning*, pp. 1259–1277. PMLR, 2020.

Raghav Goyal, Samira Ebrahimi Kahou, Vincent Michalski, Joanna Materzynska, Susanne Westphal, Heuna Kim, Valentin Haenel, Ingo Fruend, Peter Yianilos, Moritz Mueller-Freitag, et al. The" something something" video database for learning and evaluating visual common sense. In *Proceedings of the IEEE international conference on computer vision*, pp. 5842–5850, 2017.

Kristen Grauman, Andrew Westbury, Eugene Byrne, Zachary Chavis, Antonino Furnari, Rohit Girdhar, Jackson Hamburger, Hao Jiang, Miao Liu, Xingyu Liu, et al. Ego4d: Around the world in 3,000 hours of egocentric video. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18995–19012, 2022.

Tuomas Haarnoja, Ben Moran, Guy Lever, Sandy H Huang, Dhruva Tirumala, Jan Humplik, Markus Wulfmeier, Saran Tunyasuvunakool, Noah Y Siegel, Roland Hafner, et al. Learning agile soccer skills for a bipedal robot with deep reinforcement learning. *Science Robotics*, 9(89):eadi8022, 2024.

Nicklas Hansen, Zhecheng Yuan, Yanjie Ze, Tongzhou Mu, Aravind Rajeswaran, Hao Su, Huazhe Xu, and Xiaolong Wang. On pre-training for visuo-motor control: revisiting a learning-from-scratch baseline. In *Proceedings of the 40th International Conference on Machine Learning*, pp. 12511–12526, 2023.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

Yingdong Hu, Renhao Wang, Li Erran Li, and Yang Gao. For pre-trained vision models in motor control, not all policy learning methods are created equal. In *International Conference on Machine Learning*, pp. 13628–13651. PMLR, 2023.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11-14, 2016, Proceedings, Part II 14*, pp. 694–711. Springer, 2016.

Nick Kanopoulos, Nagesh Vasanthavada, and Robert L Baker. Design of an image edge detection filter using the sobel operator. *IEEE Journal of solid-state circuits*, 23(2):358–367, 1988.

Liyiming Ke, Sanjiban Choudhury, Matt Barnes, Wen Sun, Gilwoo Lee, and Siddhartha Srinivasa. Imitation learning as f-divergence minimization. In *Algorithmic Foundations of Robotics XIV: Proceedings of the Fourteenth Workshop on the Algorithmic Foundations of Robotics 14*, pp. 313–329. Springer, 2021.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4015–4026, 2023.

David G Kleinbaum, Lawrence L Kupper, Keith E Muller, and Azhar Nizam. *Applied regression analysis and other multivariable methods*, volume 601. Duxbury press Belmont, CA, 1988.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*, 2022.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

Yecheng Jason Ma, Shagun Sodhani, Dinesh Jayaraman, Osbert Bastani, Vikash Kumar, and Amy Zhang. VIP: Towards universal visual reward and representation via value-implicit pre-training. In *Deep Reinforcement Learning Workshop NeurIPS 2022*, 2022.

Yecheng Jason Ma, Vikash Kumar, Amy Zhang, Osbert Bastani, and Dinesh Jayaraman. Liv: language-image representations and rewards for robotic control. In *Proceedings of the 40th International Conference on Machine Learning*, 2023.

Arjun Majumdar, Karmesh Yadav, Sergio Arnaud, Jason Ma, Claire Chen, Sneha Silwal, Aryan Jain, Vincent-Pierre Berges, Tingfan Wu, Jay Vakil, et al. Where are we in the search for an artificial visual cortex for embodied intelligence? *Advances in Neural Information Processing Systems*, 36:655–677, 2023.

Leland McInnes, John Healy, and James Melville. Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

Ashvin Nair, Murtaza Dalal, Abhishek Gupta, and Sergey Levine. Accelerating online reinforcement learning with offline datasets. *CoRR*, abs/2006.09359, 2020.

Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3m: A universal visual representation for robot manipulation. In *6th Annual Conference on Robot Learning*, 2022.

Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. Dinov2: Learning robust visual features without supervision. *arXiv preprint arXiv:2304.07193*, 2023.

Simone Parisi, Aravind Rajeswaran, Senthil Purushwalkam, and Abhinav Gupta. The unsurprising effectiveness of pre-trained vision models for control. In *international conference on machine learning*, pp. 17359–17371. PMLR, 2022.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*, 2018.

Ilija Radosavovic, Tete Xiao, Stephen James, Pieter Abbeel, Jitendra Malik, and Trevor Darrell. Real-world robot learning with masked visual pre-training. *CoRL*, 2022.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. *arXiv preprint arXiv:1709.10087*, 2017.

Alexander Sax, Bryan Chen, Francis Lewis, Iro Armeni, Silvio Savarese, Amir Zamir, Jitendra Malik, and Lerrel Pinto. Robust policies via mid-level visual representations: An experimental study in manipulation and navigation. In *Conference on Robot Learning*, pp. 2328–2346. PMLR, 2021.

Moritz Schneider, Robert Krug, Narunas Vaskevicius, Luigi Palmieri, and Joschka Boedecker. The surprising ineffectiveness of pre-trained visual representations for model-based reinforcement learning. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2023.

Dandan Shan, Jiaqi Geng, Michelle Shu, and David F Fouhey. Understanding human hands in contact at internet scale. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9869–9878, 2020.

Mohit Sharma, Claudio Fantacci, Yuxiang Zhou, Skanda Koppula, Nicolas Heess, Jon Scholz, and Yusuf Aytar. Lossless adaptation of pretrained vision models for robotic manipulation. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023.

Manan Tomar, Utkarsh Aashu Mishra, Amy Zhang, and Matthew E Taylor. Learning representations for pixel-based control: What matters and why? *Transactions on Machine Learning Research*, 2023.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

Markus Wulfmeier, Arunkumar Byravan, Tim Hertweck, Irina Higgins, Ankush Gupta, Tejas Kulkarni, Malcolm Reynolds, Denis Teplyashin, Roland Hafner, Thomas Lampe, et al. Representation matters: Improving perception and exploration for robotics. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6512–6519. IEEE, 2021.

Lin Yen-Chen, Andy Zeng, Shuran Song, Phillip Isola, and Tsung-Yi Lin. Learning to see before learning to act: Visual pre-training for manipulation. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2020.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on robot learning*, pp. 1094–1100. PMLR, 2020.

Yanjie Ze, Yuyao Liu, Ruizhe Shi, Jiaxin Qin, Zhecheng Yuan, Jiashun Wang, and Huazhe Xu. H-index: Visual reinforcement learning with hand-informed representations for dexterous manipulation. *NeurIPS*, 2023.

A Environments and Experts

Metaworld The Metaworld suite contains multiple grasping and nudging tasks, in which an end-effector manipulates objects in the environment to complete the task. Metaworld provides expert policies, from which we created expert trajectories for imitation learning. We used a total of 17 environments from Metaworld. Each task intializes to a random starting position, and a random goal position, making this a good environment for multi-goal tasks.

Fetch Suite From the Fetch suite, we evaluate two environments, FetchPush and FetchPickAndPlace. In both environments, the goal is to move a block to a goal, either by pushing it around the table top, or by grasping the block and moving to a goal location. We trained a SAC policy with hindsight relabeling to create the experts.

AdroitHand From the AdroitHand suite, we evaluated two environments, Hammer and Door. Both environments involve manipulating a 30+ DoF hand to open a door or drive a nail into a board with a hammer. We trained a behavior cloning policy on the Farama expert trajectories to create a larger expert trajectory data set. The Fetch and AdroitHand suite are collectively referred to as the Gymnasium environments due to their use of the Farama gymnasium library.

B Training Parameters

Each epoch in behavior cloning makes 100 gradient steps using 256 scenes for each gradient step, for a total of 10,000 gradient steps. IQL trains with 10,000 gradient steps using 256 scenes for each step. Our IQL algorithm uses 256 samples of the transition tuple (s_t, a, s_{t+1}) (without reward signals), while behavior cloning uses 256 samples in minibatches of (s_t, a_t).

	Behavior Cloning	**IQL**
Batch Size	256	256
Training Size	2000	2000
Epochs	100	-
Minibatches	100	-
Gradient Steps	-	10000
Actor LR	0.0008	0.00015
Q LR	-	0.0003
V LR	-	0.0003
Expectile τ	-	0.7
β	-	3
Polyak τ	-	0.05

Table 2: IQL and Behavior Cloning make the same number of gradient steps on the same size of minibatch.

We do not include any reward signal to perform the offline reinforcement learning. Instead, we use an inverse Q learning method from Garg et al. (2021).

B.1 Model Architectures

Encoder	Objective	Type	Pretraining Data	Architecture
SAM	Segmentation Mask Prediction	Supervised	SA-1.1B	ViT-B
DINOv2	Self-distillation	Self-Supervised	ImageNet	ViT-B
CLIP	Text Image Contrastive	Supervised	WIT	ViT-B
MAE	Masked Image Reconstruction	Self-Supervised	ImageNet	ViT-B
VIP	Value function prediction	Supervised	Ego4D	ResNet50
VC1	Masked Image Reconstruction	Self-Supervised	Ego Suite	ViT-B
R3M	Time Language Contrastive	Supervised	Ego4D	ResNet50
MVP	Masked Image Reconstruction	Self-Supervised	ImageNet, Robotics Adjacent	ViT-B
MOCOv3	Contrastive	Self-Supervised	ImageNet	ResNet50

Table 3: Pretraining Objectives in vision encoders.

C Reinforcement Learning Differences

Figure 10: **Representations trained for manipulation perform better using behavior cloning.** In Gymnasium environments, MAE sees an improvement while in the Metaworld suite, MAE sees a decline in performance. Across the board, manipulation based representations see a decline in performance by using offline reinforcement learning.

D   Sample Efficiency

Figure 11: Sample efficiency of representations for behavior cloning evaluated on 5, 10, and 40 expert demonstrations. Representations trained for manipulation such as R3M, VIP are more sample efficient in general as they achieve higher success rates even with just 5 expert demonstrations.

E Key Position Prediction

For objects and goals, we observe similar correlation patterns. Figure 12 show a strong correlation between key point prediction and behavior cloning success rates.

Figure 12: Correlations between predicting positions and behavior cloning success rates. All three demonstrate strong correlations.

Position	Pearson (*p*-value)	Spearman (*p*-value)
Arm	-0.875 (0.0020)	-0.767 (0.0159)
Goal	-0.921 (0.0004)	-0.833 (0.0053)
Object	-0.886 (0.0015)	-0.833 (0.0053)
Combined	-0.904 (0.0008)	-0.817 (0.0072)

Table 4: Pearson and Spearman rank Correlations for key point prediction are all statistically significant at the $\alpha = 0.05$ level

SAM can be considered as an influential observation and could affect the explanatory nature of our correlation analysis. The correlations without the SAM data points are in Figure 13. Additionally, a DFBETA analysis in Table 6 show that neither of the SAM observations have high influence (Kleinbaum et al., 1988).

The analysis in Tables 4 and 5 shows that removing SAM sees a maximum Pearson correlation increase of 0.05 and a maximum Spearman correlation increase of 0.17. While the Spearman increase of 0.17 is larger than the Pearson increase, Spearman correlation is a non-parameteric method, which inherently has a

Figure 13: Correlations between predicting positions and behavior cloning success rates after removing SAM. Correlations remain strong.

lower statistical power compared to the Pearson correlation, thus its larger increase may not be statistically significant. The differences (Table 6) do not lie in the rejection region of $\Delta = 0.667$ and are not considered influential.

Position	Pearson (p-value)	Spearman (p-value)
Arm	-0.903 (0.0021)	-0.857 (0.0065)
Goal	-0.973 (0.0000)	-1.000 (0.0000)
Object	-0.933 (0.0007)	-1.000 (0.0000)
Combined	-0.937 (0.0006)	-0.976 (0.0000)

Table 5: Without SAM, the Pearson and Spearman rank Correlations for key point prediction are also all statistically significant but are not too different from that in Table 4.

	Arm	Goal	Object	Combined
$DFBETA$	0.007	0.002	0.0003	0.007

Table 6: DFBETA analysis on the correlation coefficients by omitting SAM. All are below the threshold of 0.667, meaning SAM is not an influential point

F Clustering Representations

Interestingly, we find that grasping tasks are harder to solve than nudging tasks in both behavior cloning and reinforcement learning. We define grasping tasks to be tasks where the expert uses end-effectors of the robotic arm to pick up and grip an object in the environment, while a nudging task is one where the expert uses the end-effectors to push or drag an object without moving the effectors. Examples of grasping tasks are hammer, coffee pull, and bin picking. Nudging tasks include plate slide, soccer, and dial turn.

We aim to evaluate which representations benefit from using an offline reinforcement learning regime. To answer this question, we study the modality of the expert action distributions, following Ghasemipour et al. (2020); Ke et al. (2021). We view our expert data set as $(\phi(s), a)$ where the pre-trained image representations $\phi(s)$ define the state space, and a denotes the expert action. The state-action occupancy distribution is denoted by μ_E. The expert policy is represented as $\pi^E(a|\phi(s))$ which is a conditional action distribution. We aim to learn the conditional action distribution using the expert collected trajectories with imitation algorithms. Prior work from Ghasemipour et al. (2020) differentiate between mode-covering and mode-seeking imitation algorithms that recover expert action distributions. Behavior cloning is a mode covering objective, which makes it particularly difficult to recover an expert action distribution that exhibits multiple modes.

We argue that the expert conditional action distributions $\pi^E(a|\phi(s))$ for grasping tasks contain more modes than for nudging tasks. This is clear from the optimization objective in behavior cloning with an L_2 objective, which is equivalent to minimizing a forward KL divergence of a Gaussian policy:

$$\min_\pi D_{KL}(\pi \| \pi^E) = \min_\pi \mathbb{E}_{a \sim \pi^E, s \sim \mu_E} \, \log \pi(a|\phi(s))$$

This formulation corresponds to a mode-covering objective. In contrast, the optimization procedure in implicit Q learning follows an advantage-weighted regression objective, which Nair et al. (2020); Peng et al. (2019) demonstrate is equivalent to a reverse KL divergence:

$$\min_\pi D_{KL}\left(\pi^E \| \pi\right) = \min_\pi \mathbb{E}_{a \sim \pi^E, s \sim \mu_E} \, e^{\beta(Q(\phi(s),a)-V(\phi(s)))} \log \pi(a|\phi(s))$$

Unlike behavior cloning, this objective corresponds to a mode-seeking optimization regime, making it better suited for recovering optimal actions given a multi-modal expert action distribution.

Our expert conditional action distribution are samples drawn from a continuous state action occupancy μ^E, and modes are detected through clustering (Chen et al., 2016). To test our hypothesis that grasping tasks exhibit higher modality in the conditional action distribution, we discretized the representation state space by first applying UMAP (McInnes et al., 2018) dimension reduction on the representations. UMAP preserves local density structure, makes non-linear down projections using intrinsic dimension and algebraic simplexes, and is widely used in dimension reduction and analyzing representations (Agarwal et al., 2021; Haarnoja et al., 2024; Dai et al., 2022). After applying UMAP, we use HDBSCAN (Campello et al., 2013) to cluster the state representations. Upon discretizing the representation space, we cluster actions within each discretized state representation, and count the number of clusters in the conditional action distribution and visualize an example in Figure 15. The details of this algorithm are given in Algorithm 1. We demonstrate that dimension reduction with UMAP is not necessary in Table 8.

For the results in Table 7, we use UMAP with 16 neighbors casting down to 3 dimensions. This produced clusters using HDBSCAN with the largest Silhouette values. We find that the number of negatively scored clusters is minimal with neighbors set at 16. We note that this method is sensitive to hyperparameter tuning.

When we do not reduce the dimensionality, and directly cluster with OPTICS to find approximate conditional action distribution, and then find clusters of actions, we still see that nudging tasks have less modes than grasping tasks in general across representations. The differences correlate with the gains in Figure 14 with Pearson $\hat{\rho}_r = 0.716$ and Spearman $\hat{\rho}_s = 0.7$. However, this method may not be preferred due to the computation time due to clustering in high dimensions.

Figure 14: **IQL is better at solving grasping tasks than BC** The difference in success rates between grasping and nudging tasks vary across encoders, and also by the learning method. Reinforcement learning reduces the gap in success rate between nudging and grasping tasks (blue bar). However the level of improvement varies depending on representation.

Algorithm 1 Determining modality with continuous expert state-actions
---
Require: Expert data $D^E = (\phi(s_t), a_t)_{1:N}$. Tuned clustering algorithm $K(\cdot) : \mathbb{R}^n \mapsto \mathbb{N}$, UMAP algorithm $U(\cdot) : \mathbb{R}^n \mapsto \mathbb{R}^d$

    UMAP reduced embeddings $u \leftarrow U(\phi(s))$

    Number of clusters $K \leftarrow K(u)$ and labels $K_L \in \{1, ..., K\}$

    Append cluster labels to expert data $D^E \leftarrow (\phi(s_t), a_t, K_L)$

    Initialize array L to store number of modes in each cluster

    for $c = 1...K$ **do**

        Subset D^E to get states belonging to cluster c. $D_c \leftarrow (\phi(s_t), a_t, K_L = c)$

        Extract all actions a_t from D_c to get A_c

        Get number of clusters M from conditional actions, $M \leftarrow K(A_c)$ ▷ Optional: Apply $A_c \leftarrow U(A_c)$

        Append $L[c] \leftarrow M$

    end for

    return Mean number of clusters $\bar{L}$

Encoder $\phi(\cdot)$	Average modality for Nudging	Average modality for Grasping	Δ
SAM	3.405	4.083	0.678
DINO	2.987	3.929	0.942
CLIP	2.665	4.556	1.891
MAE	2.776	3.653	0.877
MVP	2.899	4.035	1.136
R3M	3.008	4.887	1.878
VIP	3.350	3.722	0.372
VC1	2.709	4.317	1.608
MOCO3	4.063	5.190	1.127

Table 7: **Average number of clusters in the conditional action distributions.** All conditional expert action distributions exhibit more modes in grasping tasks than for nudging tasks. Each number represents the average mode count from 3000 scenes representations in each of the 17 environments.

Encoder $\phi(\cdot)$	Modes in $\pi^E(a\|\phi(s))$ for nudging	Modes in $\pi^E(a\|\phi(s))$ for grasping	Δ
SAM	3.81	3.88	0.07
DINO	2.75	5.89	3.14
CLIP	3.75	6.44	2.69
MAE	1.62	2.22	0.60
MVP	3.00	3.44	0.44
R3M	2.25	4.11	1.86
VIP	2.25	3.55	1.30
VC1	2.63	3.44	0.81
MOCO3	5.72	8.06	2.34

Table 8: Average number of clusters in the conditional action distributions. SAM representations form a state space that has almost the same number of clusters between nudging and grasping tasks. The clustering is done by the OPTICS (Ankerst et al., 1999) algorithm. This produces moderate to strong correlations

(a) 3D representation of expert actions from a given discretized $\phi(s)$ from coffee-pull (grasping), we can see multi-modal behavior in $\pi^E(a|\phi(s))$ in part due to the end effector movement.

(b) For a given discretized $\phi(s)$ from window-close (nudging), multi-modal behavior is not as prominent in $\pi^E(a|\phi(s))$. There is no end effector movement, and points roughly form a uniform subspace.

Figure 15: **3D representation of the action space.** The (x, y, z) axes parameterize the arm movement, and the colors green and blue respectively parameterize the end effector being open and closed.

Figure 16: Correlations between the mode differences and the percentage improvements gained from using a mode seeking objective. The correlation is moderate and positive, which demonstrates the benefit of using mode seeking algorithms when the differences in expert conditional action distribution modes are larger.

G   Reconstructions

Reconstructions from various environments from Metaworld are shown in Figures 17 and 18 below:

G.1   Reconstructions Correlate with Success Rates

We can also see the p-values in Table 9 and observe the correlations are significant at the $\alpha = 0.05$ level.

Scene	Pearson (p-value)	Spearman (p-value)
Current	-0.805 (0.009)	-0.817 (0.007)
5-step	-0.816 (0.007)	-0.817 (0.007)
20-step	-0.809 (0.008)	-0.817 (0.007)

Table 9: The correlation between image reconstruction is strongly correlated with behavior cloning success and the correlations are statistically significant at the $\alpha = 0.01$ level.

Figure 17: Non-reconstructive pre-trained representations produced these reconstructions. Compared with Figure 18, there appears to be a higher level of fidelity when reconstructing the scene.

Figure 18: Reconstructive pre-trained representations produced these reconstructions. Compared with Figure 17, there appears to be a lower level of fidelity when reconstructing the scene. In particular, the arm is not reconstructed very well, and objects in the scene are poorly reconstructed, if at all.

Figure 19: Pixel differences between reconstructions and the original scene rendering. Across the board, there is a strong negative correlation between reconstructions, future scene reconstructions, and the behavior cloning success rates.