POLARITY IS ALL YOU NEED TO LEARN AND TRANSFER FASTER

ABSTRACT

Natural intelligences (NIs) thrive in a dynamic world – they learn quickly, sometimes with only a few samples. In contrast, Artificial intelligence (AI) has achieved supra (-human) level performance in certain AI settings, typically dependent on a prohibitive amount of training samples and computational power. What design principle difference between NI and AI could contribute to such a discrepancy? Here, we propose a research avenue based on a simple observation from NIs: post-development, neuronal connections in the brain rarely see polarity switch. Why? Our answer is: to learn and transfer more efficiently. We demonstrate with theory and simulations that if weight polarities are adequately set *a priori*, then networks learn with less time and data. We extend such findings onto image classification tasks and demonstrate that polarity, not weight, is a more effective medium for knowledge transfer between networks. We also explicitly illustrate situations in which *a priori* setting the weight polarities is disadvantageous for networks. Our work illustrates the value of weight polarities from the perspective of statistical and computational efficiency for both NI and AI.

1 INTRODUCTION

Natural intelligences (NIs), including animals and humans, thrive in a dynamic world. Often, NIs learn quickly with just a few samples. Artificial intelligences (AIs), specifically deep neural networks (DNNs), can now compete with or even surpass humans in certain tasks, e.g., GO playing (Silver et al., 2017), object recognition (Russakovsky et al., 2015), protein folding analysis (Jumper et al., 2021), etc. However, DNN is only capable of achieving such when a prohibitive amount of data and training resources are available. Such a gap on learning speed and data efficiency between NI and AI has baffled and motivated many AI researchers. A subfield of AI is dedicated to achieving few-shot learning using DNNs (Hoffer & Ailon, 2015; van der Spoel et al., 2015; Vinyals et al., 2016; Snell et al., 2017; Finn et al., 2017). Many research teams have achieved amazing performances on benchmark datasets (Lazarou et al., 2022; Bendou et al., 2022). However, the products of such engineering efforts greatly deviate from the brain. They cannot shed light on what is special about the brain that allows NIs to learn more quickly and with fewer samples than state-of-the-art DNNs. In this paper, we take a different perspective and focus on the design principle difference between NIs and AIs. Based off of a simple discrepancy of these two systems, we propose a new research avenue.

NIs are blessed with hundreds of millions of years of optimization through evolution. Through trial and error, the most survival-advantageous circuit configurations emerge, refine, and slowly come into the form that can thrive in an ever-changing world. Such circuit configurations get embedded into our genetic code, establishing a blueprint to be carried out by development. Among the many configurations, circuit rules, and principles that formed through evolution, one theme stands out, one that neuroscientists celebrate and yet is overlooked by the machine learning community: post-development, neuronal connections in the brain rarely see polarity switch. After development, NIs learn and adapt through synaptic plasticity – a connection between a pair of neurons can change its strength but rarely its excitatory or inhibitory nature; on the contrary, a connection (weight) between a pair of units in a DNN can freely change its sign. In fact, polarity change in the adult brain is hypothesized to be associated with depression, schizophrenia, and other illnesses (Spitzer, 2017). For the rare times such phenomenon have been observed, they never appeared in sensory and motor cortices (Spitzer, 2017) where visual, auditory and motor processing take place. It seems a rather rigid design choice to fix a network's connection polarity. We wonder why the biological networks

settled into such a learning strategy: Is it a mere outcome of an implementation-level constraint? It could be just hard for neurons to switch polarities. Or could it be that some optimality is embedded in the polarity configuration and such a configuration serves as an inductive bias to the brain?

This paper provides some thoughts, proofs, and evidence relevant to these questions. We first investigate why brains pre-set neuronal connection polarities by assessing what we *gain* through setting weight polarity *a priori* (Sec 2-4). We discuss in theory the trade-off between representation capacity and learning speed when weight polarity is fixed for networks. We then propose an SGD-based polarity-fixed learning algorithm: **Freeze-SGD**. We experimentally show that if the weight polarities are adequately set *a priori*, then networks can learn with less time and data. We call such networks **Frozen-Net**. We validate the effectiveness of Frozen-Net in a simulated task (Sec 2) and two image classification tasks (Sec 3). We further find Frozen-Nets are even superior to their liquid counterpart (polarity not constrained, Liquid-Net) initialized with transferred weights (Sec 4). Our results point to an unexplored direction in the machine learning community: polarity, not weight, may be the more effective and compressed medium for transferring knowledge between networks. To complete our discussion, we further discuss what we *lose* when weight polarities are set *a priori* (Sec 5). Frozen-Nets have reduced representation capacity; therefore, a randomly configured network may not even have the capacity to represent a simple problem such as XOR (Def 2.2). We theoretically prove and experimentally show that if the polarities are set randomly, the probability of a single-hidden-layer network learning XOR increases exponentially as a function of its size (i.e., number of hidden units). We also experimentally show that a sufficiently sized network, even when its polarities are randomly picked, can learn with less time and data than an equally sized network without fixed polarities.

By discussing both the advantages and disadvantages of fixing weight polarity, we provide some rationale for why NI widely adopts such a strategy. We also provide some insights on how to make AI more statistically and computationally efficient.

2 WHAT DO WE GAIN BY SETTING WEIGHT POLARITY *a priori*?

Networks need both positive and negative weights to funcion (Wang et al., 2022) - a DNN with all non-negative weights is not a universal approximator. Constraining a network's weight polarity pattern limits its representation capacity: when only half of the range is available to each connection, the reduction in total possible network patterns grows exponentially with more edges in the network. What then makes it so that our brains may have willingly chosen to give up on a vast portion of their representation capacity? Our answer is: to learn more quickly. Below we provide theoretical discussions and experimental evidence.

Definition 2.1 (DNN). *Let $W^{(l)} \in \mathbb{R}^{n_l \times n_{l-1}}$ be the input weights of layer l, n_l be the number of units in layer l, $b^{(l)} \in \mathbb{R}^{n_l}$ be the bias terms of layer l, for $l \in \{1, \ldots, L\}$. $l = 0$ is the input layer, $n_0 = dim(x)$. Let layer l be $\sigma^{(l)}(x) = \sigma(W^{(l)}x + b^{(l)})$.*

$$P(x) = \sigma^{(L)} \circ \sigma^{(L-1)} \circ \ldots \circ \sigma^{(1)}(x), P(x) \in \mathbb{R}^{n_L};$$
$$F(x) = \text{softmax}(P(x))$$

DNN is $F(x)$. For the non-linearity σ, we define it to be ReLU throughout the paper.

$$\sigma(x_j) = \begin{cases} 0 & x_j < 0 \\ x_j & x_j \geqslant 0 \end{cases} \qquad \sigma(x) = (\sigma(x_1), \ldots, \sigma(x_{n_l}))$$

Lemma 2.1 (capacity-speed trade-off). *If the weight polarities are set a priori, such that the function is still representable, then the network can learn faster.*

We prove Lemma 2.1 for single-hidden-layer networks, with the following assumptions:

> Assumption 1: The weights take on discrete values. This is essentially true for all DNNs implemented on silicon chips where all continuous variables are discretized;

> Assumption 2: Exhaustive search as the learning algorithm.

See proof on page 18.

The theory argues for a trade-off between network representation capacity and learning speed. Next, we test with simulation to show that networks learn more quickly when polarities are set *a priori* in such a way that the function is still representable (Figure 1 panel B).

We design our freeze training procedure to be exactly the same as SGD (Adam optimizer) except for one single step: after each batch, all weights are compared to the preset polarity template, and if any of the weight has switched polarity in the last batch, it is reverted back to the desired sign (see algorithm 1). As our goal is to see the pure effect of fixing weight polarity, we did not adopt any bio-plausible learning algorithms as they may introduce confounding factors.

Algorithm 1 Freeze-SGD

---

for $l = 1, 2, \ldots, L$ **do**
    Get weight polarity template $T^{(l)}$ based on the configuration rules. Match $W^{(l)}$ to $T^{(l)}$
end for

for $epoch = 1, 2, \ldots$ **do**
    for $batch = 1, 2, \ldots$ **do**
        SGD updates all weights.
        for $l = 1, 2, \ldots, L$ **do**
            Compare signs of the weights $W^{(l)}$ to the template $T^{(l)}$,
            get $checker = T^{(l)} * \text{sign}(W^{(l)})$.
            for (i, j) where $T^{(l)}(i, j) < 0$ **do**
                Make $W_l(i, j)$ in compliance with $T^{(l)}(i, j)$ by one of the following four ways:
                Case posCon $W^{(l)}(i, j) = T^{(l)}(i, j) * \epsilon$ where $\epsilon > 0$
                Case posRand $W^{(l)}(i, j) = T^{(l)}(i, j) * rand([0, \epsilon])$ where $\epsilon > 0$
                Case zero $W^{(l)}(i, j) = 0$
                Case flip $W^{(l)}(i, j) = -W^{(l)}(i, j)$
            end for
        end for
    end for
end for

We compared three training procedures in our simulation experiment:

1. **Frozen-Net sufficient-Polarity**: Weight polarities were set *a priori*. The polarity pattern was chosen based on a rule that ensures the configuration is adequate for learning the task, i.e., the polarity pattern carries expert knowledge about the data.

2. **Frozen-Net RAND-Polarity**: Weight polarities were set *a priori* randomly $Bernoulli(0.5)$. The polarity pattern does not carry any information about the data.

3. **Fluid-Net**: Weight polarities were free to change throughout the training procedure.

Frozen-Net Sufficient-Polarity is a close simulation of NI. Excitatory and inhibitory connections in the brain are never configured randomly; instead, the range and specificity of neuronal connections follow pre-configured rules (see Sec 6).

We used 5-dimensional XOR (XOR-5D) as our simulation binary classification task; only the first two dimensions are relevant to the task, and the remaining three dimensions are noise following a normal distribution $\mathcal{N}(1, 1)$ (Figure 1 panel A). For Frozen-Net sufficient-Polarity, the polarity template is pre-set in this way: for each hidden unit, the polarity of the output edge is the sign product of the first two dimensions' input weights.

Definition 2.2 (XOR). *Let $x \in \mathbb{R}^2$ and $t_1, t_2 \in \mathbb{R}$,*

$$f(x) = \begin{cases} 0 & [x_1 \geq t_1 \text{ and } x_2 \geq t_2] \quad \text{or} \quad [x_1 < t_1 \text{ and } x_2 < t_2] \\ 1 & [x_1 \geq t_1 \text{ and } x_2 < t_2] \quad \text{or} \quad [x_1 < t_1 \text{ and } x_2 \geq t_2]. \end{cases} \tag{1}$$

To have the best controlled experiments, we fixed the architecture, training samples (n varies, see figure), batch sequence of the training data, and the validation samples (n=1000) across all three procedures. All experiments were run on 2 RTX-8000 GPUs. We first tried four different weight reset methods (details in Algo 1) and found they give us similar results and thus did not matter for our primary questions (supplementary figure A.1). For the rest of this paper, we chose the *posRand* method whereby we set weights to a small random number of the correct sign.

When the polarities are fixed in such a way that it is sufficient to learn the task (red), networks always learn faster than networks without polarity constrains (blue) (Fig 1 panel B). This advantage is true across all data scarcity levels and is particularly valuable when data is scarce. When only 60 or 72 training samples were available, Frozen-Net sufficient-polarity on average take 58% and 48% of the standard Fluid-Net training time respectively to reach the same level of accuracy. When weight polarities are randomly chosen (green), networks learn as fast as their Fluid-Net counterparts (blue), and sometimes faster (e.g., training samples = 80 and 92).

Frozen-Net sufficient-Polarity not only saves time, but also saves data (Fig 1 panel C). At convergence, Frozen-Net sufficient-Polarity (red) takes fewer samples to reach the same level of accuracy when compared to the standard Fluid-Net (blue). Randomly configured Frozen-Net (green) uses similar and oftentimes less data than Fluid-Net (blue) (e.g., to reach 80% accuracy, Frozen-Net RAND-polarity uses less data than Fluid-Net).

Figure 1: **Adequately setting weight polarity *a priori* makes networks learn more quickly (fewer epochs) and with less data (fewer training samples).** Single hidden layer networks with 64 hidden units are trained to learn XOR-5D. In all scenarios, networks were trained for 100 epochs. A) XOR-5D, a binary classification problem where only the first two dimensions are relevant to the task (XOR), and the other three dimensions are noise following a normal distribution $\mathcal{N}(1,1)$. B) Computational efficiency: Setting weight polarity in a data-informed way (red) makes networks learn more quickly – this is true across all data-scarcity levels; when weight polarities are randomly fixed (green), networks learn as fast as their fluid counterparts (blue), and sometimes faster (e.g., training sample sizes = 80 and 92). C) Statistical efficiency: At convergence, adequately configured freeze networks (red) achieve the same level of performance (% error) with less data; randomly configured freeze networks (green) use similar and oftentimes less data than fluid (blue), e.g., to reach 80% accuracy (20% error). For all experiments, n=50 trials. All curves correspond to medians with shaded regions 25[th]-75[th] percentiles.

In both theory and simulations, we showed that setting weight polarity *a priori* makes networks learn in less time, provided the function is still representable. We further showed with simulations another advantage of freezing polarities: the ability to learn with less data. Even randomly configured Frozen-Nets show comparable and sometimes better performance than Fluid-Nets. Such a result is striking from an optimization perspective: Frozen-Net is at a disadvantage by design because the weight resetting step in Freeze-SGD 1 fights against the gradient update - part of the error update information is lost in this process. Regardless of this disadvantage during optimization, our Frozen-Net sufficient-polarity consistently outperforms Fluid-Net; even Frozen-Net RAND-Polarity is never worse than Fluid-Net. Combined, our results argue that NIs learn quickly and with fewer samples because of at least two factors: 1) fixed weight polarities, and 2) well-chosen polarity patterns.

3 EFFECTIVENESS OF FROZEN-NET IN IMAGE CLASSIFICATION TASKS

To prove the effectiveness of our Frozen-Net strategy for more complex tasks, we extended the experiments in Fig 1 to image classification tasks (Fig 2). Such complex learning tasks do not have simple and explicit polarity configuration rules as in XOR-5D. We exploited an alternative strategy by using ImageNet trained polarities (IN-Polarity). A Frozen-Net IN-Polarity has its weight *magnitudes*

initialized randomly, its weight *polarities* initialized and fixed to match the IN-polarity pattern. We trained and tested networks on the Fashion-MNIST (grayscale) and CIFAR-10 (RGB-color) datasets, using AlexNet network architecture (Krizhevsky et al., 2017). For both datasets, we trained for 100 epochs, with lr=0.001. The AlexNet IN-weights were obtained here.

Across the board, Frozen-Nets IN-polarity (red) always learn with fewer samples than Fluid-Net (blue) (Fig 2 first column). When only 100 training images were available (across the 10 classes), Frozen-Net IN-Polarity (red) yields 8% less validation error compared to Fluid-Net (blue) in the Fashion-MNIST task and 9% less error for CIFAR-10. When the polarities are fixed randomly (RAND-polarity, green), networks never perform worse than Fluid-Net (blue).

Across the board, Frozen-Net IN-Polarity always learns with less time than Fluid-Net (Fig 2 third column). Frozen-Net RAND-Polarity takes a comparable number of computational iterations as Fluid-Net. Furthermore, not every network is able to reach the specified accuracy threshold (Fashion-MNIST: 80%, CIFAR-10: 50%; Fig 2 second column). Across the board, Frozen-Net IN-Polarity has a higher chance of passing the specified accuracy threshold than Fluid-Net; Frozen-Net RAND-Polarity has an equal and sometimes higher chance than Fluid-Net (Fashion-MNIST 1000 & 2000 samples; CIFAR-10 10000 & 25000 samples). These observations are true across different validation accuracy thresholds (Supp Fig A.2).

Figure 2: **DNNs with frozen IN-Polarity learn more quickly and with less data in image classification tasks.** A) Experiments on Fashion-MNIST image classification dataset. From left to right: 1) Statistical efficiency: Frozen-Nets with IN-polarity (red) always learn with fewer samples than Fluid-Net (blue); Frozen-Nets RAND-Polarity (green) never perform worse than Fluid-Net (blue). 2) Frozen-Net IN-Polarity always have a higher chance of reaching 80% validation accuracy than Fluid-Net; Frozen-Net RAND-Polarity have comparable and sometimes a higher chance of reaching 80% validation accuracy than Fluid-Net. 3) Computational efficiency: Frozen-Net IN-Polarity always take less time than Fluid-Net to reach 80% validation accuracy; Frozen-Net RAND-Polarity takes a similar number of computational iterations as Fluid-Net. B) Same as A except experiments were on CIFAR-10 dataset and the validation accuracy threshold is at 50%. Gray lines in the first column correspond to the validation accuracy thresholds used to plot the next two columns. For a comprehensive view of performances at different thresholds, see Supp Fig A.2. Both datasets: n=20 trials, 100 epochs, lr=0.001. No data augmentation was performed.

Worth noting, Frozen-Net IN-Polarity in general shows more consistent performance across trials, compared to the Fluid setting. This is especially obvious for the statistical efficiency plots: across the board, Frozen-Net IN-Polarity always shows less variation in its performance on validation error (shaded area marks 25[th]-75[th] percentiles).

In sum, we are able to extend our simulation results in Sec 2 to more complex image classification tasks: Frozen-Net IN-polarity consistently learns with less data and time and does so with a higher probability of success compared to Liquid-Net; Frozen-Net RAND-polarity perform as well as Liquid-Net, sometimes better.

4 POLARITY TRANSFER IS SUPERIOR TO WEIGHT TRANSFER

From a transfer learning perspective, our Frozen-Net strategy essentially transfers weight polarities instead of weights per se. How does polarity transfer compare to the traditional finetune (weight transfer) strategy? This time, instead of randomly initializing the weight magnitudes, we initialized the weight magnitudes based on the ImageNet-trained weights (IN-Weight). We compared them with Frozen-Net IN-Polarity by plotting their differences (Δ={LEGEND} - {Freeze IN-Polarity}) in Fig 3 (the original curves before taking the differences can be found in Supp Fig A.3).

Figure 3: **Across all sample sizes, Frozen-Net with ImageNet-polarities (IN-polarities) learns more quickly than Liquid-Net with ImageNet-weight (IN-weight) initialization.** In first and third columns, curves are the **median difference Δ={LEGEND} - {Freeze IN-Polarity}** (the second term is the red curve in Fig 2). Asterisks (*) indicate statistical significance **{LEGEND} > {Freeze IN-Polarity}** with Mann-Whitney U one-tail test (α=0.05). 1) First column: Polarity transfer is more effective than weight transfer in terms of data efficiency. This is indicated by orange curve above zero across most sample sizes, and it is statistically significant for small sample sizes. Note the zero line here means LEGEND = Freeze IN-Polarity. 2) Second column: Frozen-Net has a higher chance of reaching 80% (Fashion-MNIST) / 50% (CIFAR-10) validation accuracy compared to finetune (orange curve); 3) Third column: Frozen-Net always takes less epochs to reach high validation accuracy than finetune (orange curve). Both datasets: n=20 trials, 100 epochs, lr=0.001. For the right two columns, the validation accuracy thresholds are the same as in Fig 2

The orange curves compare finetune (Liquid-Net IN-Weight) with our polarity transfer strategy (Frozen-Net IN-Polarity). Across almost all data scarcity levels, our polarity transfer strategy achieves higher accuracy than finetune (first column, orange$\geqslant 0$). Such a superiority is statistically significant (Mann-Whitney U one-tail) when training data is limited (Fashion-MNIST: $\leqslant 2000$ samples except 750, CIFAR-10: $\leqslant 1000$ samples except 250). Polarity transfer also allows the networks to learn with higher probability (second column) and fewer epochs (third column, curve$\geqslant 0$). Such faster learning is true regardless of the performance threshold value (Supp Fig A.4). The only instance we observed finetune on average taking less time than Frozen-Net (orange$\leqslant 0$) was to reach 60% accuracy in CIFAR-10 (Supp Fig A.4, bottom right); however, such a difference is not statistically

significant (Mann-Whitey U two-tail test, α=0.05), and finetune has a lower chance of reaching 60% accuracy. In sum, polarity transfer is almost always superior to weight transfer both in terms of statistical efficiency and computational efficiency.

Such an observation suggests polarity configuration is an effective medium, if not superior to weight pattern, for transferring knowledge between networks. This is nicely in line with biological systems: animals never inherit synaptic strengths – they instead inherit development programs that specify the polarity patterns. NIs may have long discovered that polarity pattern is a more effective and compressed form of knowledge transfer.

Surprisingly, when we initialized the Frozen-Net with IN-weight, there is limited gain in performance; in fact, it can sometimes be worse (cyan). When training data is limited (Fashion-MNIST$\leqslant 1000$, CIFAR-10$\leqslant 1000$), Frozen-Net IN-weight gained little performance (cyan$\approx$0) and could be detrimental at times (CIFAR-10 500-1000 samples). When training data is more abundant, there is a more consistent accuracy gain by initializing Frozen-Net with IN-weight (Fashion-MNIST gain 1-2$\%$, CIFAR-10 gain $\sim 3\%$). Such a gain is discounted by longer training iterations (third column), and in general less likelihood of reaching a high level of performance (second column).

Furthermore, similar to Fluid-Net, both finetune (Liquid-Net IN-weight) and Frozen-Net IN-weight have wider performance variations compared to Frozen-Net IN-Polarity (Fig A.3). These could be a result of the stochasticity of sample batching, and our Frozen-Net IN-Polarity strategy is more robust against such stochasticity.

In sum, even though our Frozen-Net strategy only transfers polarity, it is superior to weight transfer (finetune), and such superiority can be observed in a majority of the scenarios that we tested. To a large extent, weight polarity alone, not weight per se, is enough to transfer knowledge between networks. Giving the additional magnitude information to Frozen-Net only gives marginal performance gain provided data is abundant; in all other scenarios (i.e., data-limited or time-limited), initializing Frozen-Net with stereotypical weight magnitudes could be detrimental to the learning performance.

5 WHAT DO WE LOSE BY SETTING WEIGHT POLARITY *a priori*?

Intelligent agents have limited resources in 1) data, 2) time, 3) space (number of hidden units or other network size parameters), and 4) power ($\propto$time$\times$space, number of flops). In Sec 2,3,4, we showed that fixing weight polarity helps to save on two of these resources, time and data, but with a condition – the polarity configuration must be adequately set such that the network can still represent the function. With fixed polarity, certain configurations will result in networks never being able to learn the task. What is the probability of such unfortunate events happening? We investigate this direction with our simulated task XOR-5D.

Assuming unlimited resources (i.e., perfect learning algorithm, unlimited data and time), we deduced the theoretical probability limit for a single-hidden-layer network to be able to represent XOR (and its high-dimensional variants with task-irrelevant higher dimensions) as a function of the number of hidden units (Supp Theorem B.1). The theoretical results are plotted in Fig 4 panel A (top). In theory, it takes at least 3 units for Fluid-Net and Frozen-Net sufficient-Polarity to be able to learn XOR-5D on every single trial. Such a probability will never be 100% for Frozen-Net RAND-Polarity, no matter how large the networks are. Luckily, the probability grows exponentially with the network size: having 15 hidden units is already sufficient for a randomly configured Frozen-Net to learn XOR with $> 99\%$ probability.

This is exactly what we see in our simulation results (Fig 4 panel A bottom). For a generous amount of data (500 training samples) and learning time (100 epochs), the Frozen-Net RAND-Polarity curve nicely matches the theoretical curve - networks with more than 15 hidden units learn XOR-5D with very high probability, even though their polarities are fixed randomly.

Both theory and simulation results show that we will lose all advantages if weight polarities are fixed but not configured adequately; an example of such is a small, randomly configured Frozen-Net (e.g., 10 hidden units, Fig 4 panel B). Notice that for the same network size, if we ensure the configuration is adequately set (red), then the network learns quickly and is data-efficient. By allowing more space (network size), Frozen-Net RAND-Polarity starts to pick up the advantages in time and data efficiency (Fig 4 panel C). In summary, we gain from setting weight polarity *a priori* only if the polarity is

configured adequately (Fig 4 panel D); the adequacy can either be made more probable by having a larger network or can be guaranteed by an explicit configuration rule (e.g., through development for NIs, or explicit rules in our simulations, or transferred polarities from previously trained networks).

Figure 4: **A network has to be sufficiently large for it to learn more quickly, with less data, if its weight polarity is configured randomly.** A) For a randomly configured Frozen-Net to learn XOR-5D, it has to be sufficiently large. In both the theoretical limit and simulation results, it takes at least 15 hidden units for a Frozen-Net RAND-Polarity (green) to have $> 99\%$ chance of learning XOR-5D; it takes three hidden units, in theory, for an adequately configured Frozen-Net (red) and Fluid-Net (blue) to learn XOR-5D. B) When Frozen-Net RAND-Polarity is not large enough, it has a much lower chance of learning XOR-5D, and when it does learn, it uses more time and data. C) When Frozen-Net RAND-Polarity is sufficiently large, it at least shows the same level of performance as standard Fluid-Nets. D) Frozen-Net sufficient-Polarity shows an advantage over Fluid-Net (red + yellow) in almost all training sample sizes (especially when data is limited) and across all network sizes. Randomly configured Frozen-Nets have an advantage over Fluid-Nets (green + yellow), mostly when the network is sufficiently sized (> 15 hidden units). We ran 50 trials for all experiments. All curves represent medians with shaded regions denoting 25th-75th percentiles.

6 DISCUSSION

We showed in this paper that 1) if the weight polarities are adequately set *a priori*, then networks can learn with less data, time, space, and power; 2) polarity may be a more effective and compressed medium of network knowledge transfer; and 3) while we lose all advantages when the polarities are fixed but not set adequately, we can regain these advantages by increasing the size of the networks. Below we discuss the novelty of our work and some future directions.

In the literature of bio-plausible artificial neural networks (ANNs), the most related work is on Dale's principle: a single unit's output weights are exclusively excitatory or inhibitory (Dale, 1935). An exciting attempt of applying such a principle to ANNs achieved performance comparable to multi-layer perceptrons (gray-scale image classification tasks) and VGG16 (CIFAR-10) (Cornford

et al., 2021). Our approach differs in several ways; the most fundamental one is ours does *not* require exclusivity of a unit's weight polarity, we only ask the polarity configuration to stay fixed throughout training. Because we made fewer assumptions on the architecture and network properties, we were able to reveal the true power of weight polarities - polarity-fixed networks can not only perform as well as the traditional approaches when the polarities are set adequately, but they can also learn more quickly with less samples. Additionally, we revealed that polarities, not weights, may be a more effective and compressed form of knowledge transfer mediium. Furthermore, our Freeze-SGD algorithm 1 is easily applicable to any existing network architecture and any learning mode, be it transfer learning or de novo learning, thus enjoy a wider application range.

Our angle is completely novel in the neuroscience literature. The most prominent literature regarding weight polarity is centered around the E/I balance principle (Vreeswijk & Sompolinsky, 1996). Cortical neurons receive balanced excitatory and inhibitory inputs. Disruption of such a balance has been shown to lead to impulsive or indecisive decision making behaviors (Lam et al., 2022) and is hypothesized to be the driving force behind epilepsy (Cohen et al., 2002; Huberfeld et al., 2011; Truccolo et al., 2011). Balanced E/I can also maintain information in working memory (Lim & Goldman, 2013). How to maintain such E/I balance during learning has also been discussed (Landau et al., 2016; Vogels et al., 2011; Sukenik et al., 2021). Such studies, however, cannot answer how magnitudes and weight polarities play different roles in learning. Ours is the first considering this angle. Our work also serves as an interesting bridge between the vast deep learning literature and the E/I balance literature - it would be interesting future work to see how polarity configurations at different E/I balance levels may affect network learning performances.

Our hypothesis is also novel in the machine learning literature. In a statistical learning framework, it is counterintuitive to disassemble a single parameter into magnitude and sign. To the best of our knowledge, we are the first to think in this way and prove that connection polarities themselves serve as an effective form of inductive bias. Previous work that vaguely took on a connectionist's view mostly focused on the existence or range of connections (e.g., adding skip connections (He et al., 2016)), but the polarity of such connections were essentially left out of the discussion. This trend extends in neuroscience as well (Brunel, 2016). Our work broke the stereotypical view and brought weight polarity into the playing field. A lesson we learned from this research is that when designing network architectures, we should not only focus on the range of connections, but also pay attention to the polarities of connections. In the transfer learning literature, to the best of our knowledge, there has been no indication that transferring polarity alone is sufficient for knowledge transfer – ours is the first demonstration of the importance of polarity.

Our work is in sync with the framework of learning theory. Our way of explicitly setting the weight polarities provides a strong prior for the networks. This is in line with the bias-variance trade-off theorem (Geman et al., 1992; Tibshirani & Friedman, 2001). Frozen-Net sufficient-Polarity has a high inductive bias – by trading representation capacity, they gain in time and data efficiency through discounting parameter variances.

Our work is also in sync with the lottery ticket hypothesis (Frankle & Carbin, 2019). Our observations on larger networks enjoying a high probability of learning XOR-5D even when their polarities are randomly configured is a realization of the lottery ticket hypothesis.

We engineered our Freeze-SGD algorithm entirely based on SGD because we are interested in the pure effect of fixing polarity during learning. As discussed in Sec 2, such an approach intrinsically put Frozen-Net in a disadvantageous position. It is an interesting next step to adopt a more polarity-freeze compatible learning algorithm, possibly allowing us to further improve learning performance. One possibility is adapting the primal-dual interior-point method (Vogelstein et al., 2010) or Hebbian learning (Amit, 2019), as well as a host of bio-plausible learning algorithms (Miconi, 2017; Boopathy & Fiete, 2022; Dellaferrera & Kreiman, 2022).

From this work, we have strong experimental evidence (simulation and image classification) and some theoretical discussion suggesting that if the weight polarities are adequately set *a priori*, then networks can learn with less data, time, space, and power. We look forward to applying our Frozen-Net approach to more tasks to see if we can empirically extend our results to more diverse scenarios. We also look forward to extending our results theoretically (e.g., including SGD assumption in our Lemma 2.1).

REFERENCES

Yali Amit. Deep learning with asymmetric connections and hebbian updates. *Frontiers in Computational Neuroscience*, 13:18, 2 2019. ISSN 16625188. doi: 10.3389/FNCOM.2019.00018/BIBTEX.

Yassir Bendou, Yuqing Hu, Raphael Lafargue, Giulia Lioi, Bastien Pasdeloup, Stéphane Pateux, and Vincent Gripon. Easy: Ensemble augmented-shot y-shaped learning: State-of-the-art few-shot classification with simple ingredients. *arXiv*, 1 2022. doi: 10.48550/arxiv.2201.09699. URL `http://arxiv.org/abs/2201.09699`.

Akhilan Boopathy and Ila Fiete. How to train your wide neural network without backprop: An input-weight alignment perspective. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 2178–2205. PMLR, 17–23 Jul 2022. URL `https://proceedings.mlr.press/v162/boopathy22a.html`.

Nicolas Brunel. Is cortical connectivity optimized for storing information? *Nature Neuroscience*, 19: 749–755, 2016. ISSN 15461726. doi: 10.1038/nn.4286.

Ivan Cohen, Vincent Navarro, Stéphane Clemenceau, Michel Baulac, and Richard Miles. On the origin of interictal activity in human temporal lobe epilepsy in vitro. *Science*, 298:1418–1421, 11 2002. ISSN 00368075. doi: 10.1126/science.1076510.

Jonathan Cornford, Damjan Kalajdzievski, Marco Leite, Amélie Lamarquette, Dimitri Michael Kullmann, and Blake Aaron Richards. Learning to live with dale's principle: {ANN}s with separate excitatory and inhibitory units. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=eU776ZYxEpz`.

Henry Dale. Pharmacology and nerve-endings. *Journal of the Royal Society of Medicine*, 28, 1935. ISSN 01410768. doi: 10.1177/003591573502800330.

Giorgia Dellaferrera and Gabriel Kreiman. Error-driven input modulation: Solving the credit assignment problem without a backward pass. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 4937–4955. PMLR, 17–23 Jul 2022. URL `https://proceedings.mlr.press/v162/dellaferrera22a.html`.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1126–1135. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/finn17a.html`.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *7th International Conference on Learning Representations, ICLR 2019*, 2019. URL `https://openreview.net/forum?id=rJl-b3RcF7`.

Stuart Geman, Elie Bienenstock, and René Doursat. Neural networks and the bias/variance dilemma. *Neural Computation*, 4:1–58, 1 1992. ISSN 0899-7667. doi: 10.1162/neco.1992.4.1.1. URL `https://doi.org/10.1162/neco.1992.4.1.1`.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Elad Hoffer and Nir Ailon. Deep metric learning using triplet network. In Aasa Feragen, Marcello Pelillo, and Marco Loog (eds.), *Similarity-Based Pattern Recognition*, pp. 84–92, Cham, 2015. Springer International Publishing. ISBN 978-3-319-24261-3.

Gilles Huberfeld, Liset Menendez De La Prida, Johan Pallud, Ivan Cohen, Michel Le Van Quyen, Claude Adam, Stéphane Clemenceau, Michel Baulac, and Richard Miles. Glutamatergic pre-ictal discharges emerge at the transition to seizure in human epilepsy. *Nature Neuroscience*, 14:627–635, 2011. ISSN 10976256. doi: 10.1038/nn.2790.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, Alex Bridgland, Clemens Meyer, Simon A.A. Kohl, Andrew J. Ballard, Andrew Cowie, Bernardino Romera-Paredes, Stanislav Nikolov, Rishub Jain, Jonas Adler, Trevor Back, Stig Petersen, David Reiman, Ellen Clancy, Michal Zielinski, Martin Steinegger, Michalina Pacholska, Tamas Berghammer, Sebastian Bodenstein, David Silver, Oriol Vinyals, Andrew W. Senior, Koray Kavukcuoglu, Pushmeet Kohli, and Demis Hassabis. Highly accurate protein structure prediction with alphafold. *Nature*, 596:583–589, 2021. ISSN 14764687. doi: 10.1038/s41586-021-03819-2. URL http://dx.doi.org/10.1038/s41586-021-03819-2.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60, 2017. ISSN 15577317. doi: 10.1145/3065386.

Norman H. Lam, Thiago Borduqui, Jaime Hallak, Antonio Roque, Alan Anticevic, John H. Krystal, Xiao Jing Wang, and John D. Murray. Effects of altered excitation-inhibition balance on decision making in a cortical circuit model. *Journal of Neuroscience*, 42, 2022. ISSN 15292401. doi: 10.1523/JNEUROSCI.1371-20.2021.

Itamar D. Landau, Robert Egger, Vincent J. Dercksen, Marcel Oberlaender, and Haim Sompolinsky. The impact of structural heterogeneity on excitation-inhibition balance in cortical networks. *Neuron*, 92:1106–1121, 2016. ISSN 10974199. doi: 10.1016/j.neuron.2016.10.027. URL http://dx.doi.org/10.1016/j.neuron.2016.10.027.

Michalis Lazarou, Tania Stathaki, and Yannis Avrithis. Iterative label cleaning for transductive and semi-supervised few-shot learning. *ICCV*, pp. 8731–8740, 2022. ISSN 15505499. doi: 10.1109/iccv48922.2021.00863.

Sukbin Lim and Mark S. Goldman. Balanced cortical microcircuitry for maintaining information in working memory. *Nature Neuroscience*, 16:1306–1314, 2013. ISSN 10976256. doi: 10.1038/nn.3492.

Thomas Miconi. Biologically plausible learning in recurrent neural networks reproduces neural dynamics observed during cognitive tasks. *eLife*, 6, 2017. ISSN 2050084X. doi: 10.7554/eLife.20899.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115:211–252, 2015. ISSN 15731405. doi: 10.1007/s11263-015-0816-y.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George Van Den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of go without human knowledge. *Nature*, 550:354–359, 2017. ISSN 14764687. doi: 10.1038/nature24270. URL http://dx.doi.org/10.1038/nature24270.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/cb8da6767461f2812ae4290eac7cbc42-Paper.pdf.

Nicholas C. Spitzer. Neurotransmitter switching in the developing and adult brain. *Annual Review of Neuroscience*, 40, 2017. ISSN 15454126. doi: 10.1146/annurev-neuro-072116-031204.

Nirit Sukenik, Oleg Vinogradov, Eyal Weinreb, Menahem Segal, Anna Levina, and Elisha Moses. Neuronal circuits overcome imbalance in excitation and inhibition by adjusting connection numbers. *Proceedings of the National Academy of Sciences of the United States of America*, 118, 2021. ISSN 10916490. doi: 10.1073/pnas.2018459118.

Robert Tibshirani and Jerome H Friedman. *The elements of statistical learning [electronic resource]: data mining, inference, and prediction: with 200 full-color illustrations*. Springer, 2001.

Wilson Truccolo, Jacob A. Donoghue, Leigh R. Hochberg, Emad N. Eskandar, Joseph R. Madsen, William S. Anderson, Emery N. Brown, Eric Halgren, and Sydney S. Cash. Single-neuron dynamics in human focal epilepsy. *Nature Neuroscience*, 14:635–643, 2011. ISSN 10976256. doi: 10.1038/nn.2782.

Evie van der Spoel, Maarten P. Rozing, Jeanine J. Houwing-Duistermaat, P. Eline Slagboom, Marian Beekman, Anton J M de Craen, Rudi G J Westendorp, and Diana van Heemst. Siamese neural networks for one-shot image recognition. *ICML - Deep Learning Workshop*, 7, 2015. ISSN 19454589.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, koray kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/90e1357833654983612fb05e3ec9148c-Paper.pdf.

T. P. Vogels, H. Sprekeler, F. Zenke, C. Clopath, and W. Gerstner. Inhibitory plasticity balances excitation and inhibition in sensory pathways and memory networks. *Science*, 334:1569–1573, 12 2011. ISSN 10959203. doi: 10.1126/science.1211095.

Joshua T. Vogelstein, Adam M. Packer, Timothy A. Machado, Tanya Sippy, Baktash Babadi, Rafael Yuste, and Liam Paninski. Fast nonnegative deconvolution for spike train inference from population calcium imaging. *Journal of Neurophysiology*, 104:3691–3704, 12 2010. ISSN 00223077. doi: 10.1152/JN.01073.2009/ASSET/IMAGES/LARGE/Z9K0081002840010.JPEG. URL https://journals.physiology.org/doi/full/10.1152/jn.01073.2009.

C. Van Vreeswijk and H. Sompolinsky. Chaos in neuronal networks with balanced excitatory and inhibitory activity. *Science*, 274:1724–1726, 1996. ISSN 00368075. doi: 10.1126/science.274.5293.1724.

Qingyang Wang, Michael A. Powell, Ali Geisa, Eric Bridgeford, and Joshua T. Vogelstein. Why do networks need negative weights?, 2022.

A SUPPLEMENTARY FIGURES

Figure A.1: **Different reset methods in the Freeze-SGD algorithm yields similar results.** The meaning of different reset methods is described in algorithm 1. A) Freeze-informed consistently reaches higher validation accuracy after the same amount of training time. This is especially evident when training sample is scarce. B) Same curves as in Fig 4, panels B & C first column, plotted for different reset methods. C) & D) Same curves as in Fig 1, panels B & C, plotted for different reset methods. We run 20 trials for all experiments in this figure. All curves correspond to medians with shaded regions representing the 25th and 75th percentiles.

Figure A.2: **Related to Fig 2. Regardless of validation accuracy threshold, Frozen-Net IN-Polarity always learn more quickly.** Same curves as in Fig 2 right two columns, plotted for different validation accuracy thresholds.

Figure A.3: **Related to Fig 3. All scenarios plotted separately instead of plotting only for the differences.**

Figure A.4: **Related to Fig 3. Regardless of validation accuracy threshold, Frozen-Net IN-Polarity learn quicklier than traditional finetune strategy.** Same curves as in Fig 3 right two columns, plotted for different validation accuracy thresholds.

B XOR THEOREMS RELATED TO SEC 5

Lemma B.1 (minimum XOR solution, 2D). *For any single-hidden-layer network to be able to solve XOR, it is sufficient to have 3 different XOR-compatible hidden units. The weight pattern for each unit can be given by a triplet $(w_{1,j}^{(1)}, w_{2,j}^{(1)}, w_{j,1}^{(2)})$, where j is the unit index, $j \in \{1, \ldots, n\}$, n is the number of hidden units. An XOR compatible hidden unit is one where the weight pattern triplet have their polarities satisfy $sign(w_{j,1}^{(2)}) = sign(w_{1,j}^{(1)}) \times sign(w_{2,j}^{(1)})$.*

See proof on page 18.

Lemma B.2 (can learn XOR probability, 2D). *For a single hidden layer network with n hidden units ($n \in \mathbb{Z}^+$), randomly initialize each weight with its polarity following $P(polarity) \sim Bernoulli(0.5)$, then the probability that this randomly initialized network can learn XOR without changing any of the weight polarity is lower bounded by*

$$\Omega(P(n)) = 1 - \frac{\sum_{k=0}^{2} Q(k, 4, 4, n)}{8^n}, \quad n \in \mathbb{Z}^+$$

$$Q(k, m, M, n) = [(M + k)^n - \sum_{p=0}^{k-1} Q(p, k, M, n)]\binom{m}{k}$$

Q here is a helper function for counting, it is defined in more detail in the proof.

See proof on page 19.

Theorem B.1 (can learn XOR probability, high dimensional). *For a single hidden layer network with n hidden units, randomly initialize each weight with its polarity following $P(polarity) \sim Bernoulli(0.5)$, then the probability that this randomly initialized network can learn high-dimensional XOR (first two dimensions are relevant, the rest $(d-2)$ dimensions are irrelevant) without changing any of the weight polarities is lower bounded by*

$$\Omega(P(n, d)) = 1 - \frac{\sum_{k=0}^{2} Q(k, 2^d, 2^d, n)}{(2^{d+1})^n}, \quad n, d \in \mathbb{Z}^+, d \geq 2$$

$$Q(k, m, M, n) = [(M + k)^n - \sum_{p=0}^{k-1} Q(p, k, M, n)]\binom{m}{k}$$

Q here is a helper function for counting, it is defined in more detail in the proof.

See proof on page 20.

C PROOFS

Lemma 2.1 (capacity-speed trade-off). *If the weight polarities are set a priori, such that the function is still representable, then the network can learn faster.*

Proof of Lemma 2.1. A feedforward DNN can be described by as a graph

$$G = (V, E), w : E \to \mathbb{D}.$$

Nodes of the graph correspond to neurons (units), where each neuron is a function $\sigma_j^{(l)}(x) = \sigma(W_j^{(l)} x + b^{(l)}), j \in [n_l]$. All the weights for the network take on values from the set $\mathbb{D} = \{-d, \dots, 0, \dots, d\}$ for some $d \in \mathbb{N}$. The network is organized in *layers*. That is, the set of nodes can be decomposed into a union of (nonempty) disjoint subsets, $V = \dot{\cup}_{l=0}^{L} V_l$, such that every edge in E connects some node in V_{l-1} to some node in V_l, for some $l \in [L]$. Assume we have fully connected layers. Then the number of incoming edges per node is $|V_{l-1}|$. Let $|V_0|$ be the input space dimensionality. All nodes in V_0 (input layer) and V_L (output layer) are distinct.

Let $|G|$ denote the total number of distinct weight patterns of the graph G. Then for a single hidden layer network where $L = 2$, we have:

$$|G| = |\mathbb{D}|^{|E|} = |\mathbb{D}|^{(|V_0|*|V_1|+|V_1|*|V_2|)} \tag{2}$$

Then

$$\frac{|G|}{|G_{polarityFrozen}|} = \left(\frac{2d+1}{d+1}\right)^{(|V_0|*|V_1|+|V_1|*|V_2|)} \tag{3}$$

Assume a different weight pattern represents a different function (trivially holds in linear + full rank weight case), then for every single representable function, there always exists a set of weight polarity configurations $G_{correct}$ such that $G_{correct} \subseteq G_{polarityFrozen}$, therefore

$$\frac{|G_{correct}|}{|G_{\text{polarityFrozen}}|} \ll \frac{|G_{correct}|}{|G|} \tag{4}$$

This means setting weight polarity *a priori* in an adequate way constraints the combinatorial search space to have much higher proportion of correct solutions, hence easier to learn under exhaustive search algorithm (Lemma 2.1). □

Lemma B.1 (minimum XOR solution, 2D). *For any single-hidden-layer network to be able to solve XOR, it is sufficient to have 3 different XOR-compatible hidden units. The weight pattern for each unit can be given by a triplet $(w_{1,j}^{(1)}, w_{2,j}^{(1)}, w_{j,1}^{(2)})$, where j is the unit index, $j \in \{1, \dots, n\}$, n is the number of hidden units. An XOR compatible hidden unit is one where the weight pattern triplet have their polarities satisfy $sign(w_{j,1}^{(2)}) = sign(w_{1,j}^{(1)}) \times sign(w_{2,j}^{(1)})$.*

Proof of Lemma B.1. For each hidden unit, we can enumerate all of its 8 possible weight polarity configurations, with the index set $A_{Polarities} = \{1, 2, 3, 4, 5, 6, 7, 8\}$:

#	$w_{1,j}^{(1)}$	$w_{2,j}^{(1)}$	$w_{j,1}^{(2)}$
1	+	+	+
2	+	+	-
3	+	-	+
4	+	-	-
5	-	+	+
6	-	+	-
7	-	-	+
8	-	-	-

The set $B_{XOR-Polarities} = \{2, 3, 5, 8\} \subset A_{Polarities}$ contains indexes of polarity patterns that follow XOR. To prove Lemma B.1, we first consider the case of 3 hidden unit single layer network. To prove a network of certain polarity pattern is capable of solving XOR, it suffices to give a working solution. Below, we exhaust all possible 3-unit network that satisfy the statement of Lemma B.1, i.e. having 3 different XOR-compatible units; and list out their corresponding working network solutions.

{}	#	$w_{1,j}^{(1)}$	$w_{2,j}^{(1)}$	$b_j^{(1)}$	$w_{j,1}^{(2)}$	working network $F(x,y)=$
	2	+1	+1	0	-1	
{2,3,5}	3	1	0	0	1	$\text{sigmoid}(-\sigma(x+y) + \sigma(x) + \sigma(y))$
	5	0	1	0	1	
	2	+1	0	0	-1	
{2,3,8}	3	+1	-1	0	+1	$\text{sigmoid}(-\sigma(x) + \sigma(x-y) - \sigma(-y))$
	8	0	-1	0	-1	
	2	0	+1	0	-1	
{2,5,8}	5	-1	+1	0	+1	$\text{sigmoid}(-\sigma(y) + \sigma(y-x) - \sigma(-x))$
	8	-1	0	0	-1	
	3	0	-1	0	+1	
{3,5,8}	5	-1	0	0	+1	$\text{sigmoid}(\sigma(-y) + \sigma(-x) - \sigma(-x-y))$
	8	-1	-1	0	-1	

For the case that single-hidden-layer network has more than 3 hidden units, if it satisfies the rule in Lemma B.1, we can always construct a XOR-solvable network solution by setting all other weights to zero except for 3 different XOR-compatible units, then we arrive at one of the four situations in the above table and we just proved they are XOR solutions.

Therefore, for any single hidden layer network to solve XOR, it is sufficient to have at least 3 of the 4 XOR polarity patterned units. $\qquad\square$

Lemma B.2 (can learn XOR probability, 2D). *For a single hidden layer network with n hidden units ($n \in \mathbb{Z}^+$), randomly initialize each weight with its polarity following $P(polarity) \sim Bernoulli(0.5)$, then the probability that this randomly initialized network can learn XOR without changing any of the weight polarity is lower bounded by*

$$\Omega(P(n)) = 1 - \frac{\sum_{k=0}^{2} Q(k,4,4,n)}{8^n}, \quad n \in \mathbb{Z}^+$$

$$Q(k,m,M,n) = [(M+k)^n - \sum_{p=0}^{k-1} Q(p,k,M,n)]\binom{m}{k}$$

Q here is a helper function for counting, it is defined in more detail in the proof.

Proof of Lemma B.2. For any network randomly initialized, its weight polarity pattern is a set of n draws with replacement from the polarities indexed by the set $A_{Polarities}$, $|A_{Polarities}| = 8$. Define $H = (h_1, \ldots, h_m, \ldots, h_n), h_m \in A_{Polarities}, |H| = n$, to be the tuple of the indices of the observed weight patterns for the hidden layer. h_m is the index of the weight polarity pattern for unit m. For any network to be able to solve XOR, it needs to have at least 3 units whose weight patterns are distinct members of set $B_{XOR-Polarities}$ (Lemma B.1). That is, let $J = \{h_m : h_m \in H, h_m \in B_{XOR-Polarities}\}$. Then we need that $|J| \geq 3$. We can define the probability of having exactly k of the 4 XOR compatible weight patterns present within the hidden layer as following (for brevity, $A = A_{Polarities}, B = B_{XOR-Polarities}$):
None of the members in set B appears is given by:

$$P(|J| = 0) = \frac{|B|^n}{|A|^n} = (\frac{4}{8})^n = (\frac{1}{2})^n$$

Only one of the member in set B appeared in H, and that member can appear more than once in H is given by:

$$P(|J| = 1) = \frac{\binom{|B|}{1}((|B|+1)^n - |B|^n)}{|A|^n} = \frac{\binom{4}{1}(5^n - 4^n)}{8^n}$$

This is explained by choosing one of 4 members of B $\binom{|B|}{1}$, then multiply by the chosen member appears at least once $((|B|+1)^n - |B|^n)$

Only two of the members in set B appeared in H, and both can appear more than once in H:

$$P(|J| = 2) = \frac{\binom{|B|}{2}((|B| + 2)^n - \binom{2}{1}((|B| + 1)^n - |B|^n) - |B|^n)}{|A|^n}$$

$$= \frac{\binom{4}{2}(6^n - \binom{2}{1}(5^n - 4^n) - 4^n)}{8^n}$$

To count two members appear at least once in H, we have $\binom{|B|}{2}$ ways of choosing the 2 members from set B, and there are $(|B| + 2)^n$ ways of choosing with replacement to populate the tuple H, where each hidden unit can choose from in total $(|B| + 2)$ possible patterns, and subtract the situation where only one of the two members appeared $\binom{2}{1}((|B| + 1)^n - |B|^n)$ and the situation where neither appeared $|B|^n$

The above equations can be put into a compact form

$$P(|J| = k) = \frac{Q(k, |B|, |A| - |B|, n)}{|A|^n}$$

where $Q(k, m, M, n) = [(M + k)^n - \sum_{p=0}^{k-1} Q(p, k, M, n)]\binom{m}{k}, k \in \{0, \ldots, m\}, m \in 1, \ldots, |B|, M \in 1, \ldots, |A| - |B|, n \in \mathbb{Z}^+$ is a helper function that gives exactly k of the m different XOR-compatible polarity patterns appeared in n units, and in total $m + M$ options are considered for each unit.

Then, $P(n)$ is counting at least 3 of the 4 set B patterns appear:

$$\Omega(P(n)) = P(|J| \geq 3) = 1 - P(|J| = 0) - P(|J| = 1) - P(|J| = 2)$$

$$= 1 - \frac{\sum_{k=0}^{2} Q(k, 4, 4, n)}{8^n}$$

$$= 1 - (\frac{1}{2})^n - \frac{\binom{4}{1}(5^n - 4^n)}{8^n} - \frac{\binom{4}{2}(6^n - \binom{2}{1}(5^n - 4^n) - 4^n)}{8^n}.$$

$\square$

Theorem B.1 (can learn XOR probability, high dimensional). *For a single hidden layer network with n hidden units, randomly initialize each weight with its polarity following $P(polarity) \sim Bernoulli(0.5)$, then the probability that this randomly initialized network can learn high-dimensional XOR (first two dimensions are relevant, the rest $(d - 2)$ dimensions are irrelevant) without changing any of the weight polarities is lower bounded by*

$$\Omega(P(n, d)) = 1 - \frac{\sum_{k=0}^{2} Q(k, 2^d, 2^d, n)}{(2^{d+1})^n}, \quad n, d \in \mathbb{Z}^+, d \geq 2$$

$$Q(k, m, M, n) = [(M + k)^n - \sum_{p=0}^{k-1} Q(p, k, M, n)]\binom{m}{k}$$

Q here is a helper function for counting, it is defined in more detail in the proof.

Proof of Theorem B.1. We solve Theorem B.1 with the exact same counting algorithm as in Lemma B.2, the only difference is now $|A_{Polarities}| = 2^{d+1}$ and $|B_{XOR-Polarities}| = 2^d$. We prove these two equalities below.

$|A_{Polarities}| = 2^{d+1}$ because we have d input weights and 1 output weight for each unit.

The weight pattern of a single hidden unit in this case is given by a tuple $(w_{1,j}^{(1)}, \ldots, w_{d,j}^{(1)}, w_{j,1}^{(2)}), j \in \{1, \ldots, n\}$ and n is the number of hidden units. Our conclusion in Lemma B.1 trivially extends to the high dimensional case. This is because high-dimensional-XOR-solvable network solutions can be trivially constructed from Lemma B.1 by setting the irrelevant input dimension weights to 0. We can restate Lemma B.1 for high-dimensional XOR as following:

For any single-hidden-layer network to be able to solve high dimensional XOR (only first two dimensions are relevant), it is sufficient to have 3 different XOR-compatible hidden units. A high dimensional XOR compatible unit polarity pattern is ruled by $sign(w_{j,1}^{(2)}) = sign(w_{1,j}^{(1)}) \times sign(w_{2,j}^{(1)})$.

Therefore the irrelevant dimension input weights can be of either polarities and there are 2^{d-2} different combinations of them. Therefore $|B_{XOR-Polarities}| = 4 \times 2^{d-2} = 2^d$.

Follow the steps in Lemma B.2, we have (for brevity, $A = A_{Polarities}, B = B_{XOR-Polarities}$)

$$P(|J| = 0) = \frac{|B|^n}{|A|^n} = (\frac{2^d}{2^{d+1}})^n$$

$$P(|J| = 1) = \frac{\binom{|B|}{1}((|B| + 1)^n - |B|^n)}{|A|^n} = \frac{\binom{2^d}{1}((2^d + 1)^n - (2^d)^n)}{(2^{d+1})^n}$$

$$P(|J| = 2) = \frac{\binom{|B|}{2}((|B| + 2)^n - \binom{2}{1}((|B| + 1)^n - |B|^n) - |B|^n)}{|A|^n}$$

$$= \frac{\binom{2^d}{2}((2^d + 2)^n - \binom{2}{1}((2^d + 1)^n - (2^d)^n) - (2^d)^n)}{(2^{d+1})^n}$$

Therefore, we have

$$\Omega(P(n,d)) = 1 - \frac{\sum_{k=0}^{2} Q(k, 2^d, 2^d, n)}{(2^{d+1})^n}$$

$$= 1 - (\frac{1}{2})^n - \frac{\binom{2^d}{1}((2^d + 1)^n - (2^d)^n)}{(2^{d+1})^n} - \frac{\binom{2^d}{2}((2^d + 2)^n - \binom{2}{1}((2^d + 1)^n - (2^d)^n) - (2^d)^n)}{(2^{d+1})^n},$$

$$n, d \in \mathbb{Z}^+, d \geq 2$$

$\square$