UNIFORM-PRECISION NEURAL NETWORK QUANTIZATION VIA NEURAL CHANNEL EXPANSION

ABSTRACT

Uniform-precision neural network quantization has gained popularity thanks to its simple arithmetic unit densely packed for high computing capability. However, it ignores heterogeneous sensitivity to the impact of quantization across the layers, resulting in sub-optimal inference accuracy. This work proposes a novel approach to adjust the network structure to alleviate the impact of uniform-precision quantization. The proposed neural architecture search selectively expands channels for the quantization sensitive layers while satisfying hardware constraints (e.g., FLOPs). We provide substantial insights and empirical evidence that the proposed search method called *neural channel expansion* can adapt several popular networks' channels to achieve superior 2-bit quantization accuracy on CIFAR10 and ImageNet. In particular, we demonstrate the best-to-date Top-1/Top-5 accuracy for 2-bit ResNet50 with smaller FLOPs and the parameter size.

1 INTRODUCTION

Deep neural networks (DNNs) have reached human-level performance in a wide range of domains including image processing (He et al. (2016); Tan & Le (2019)), object detection (Ren et al. (2015); Liu et al. (2016); Tan et al. (2020)), machine translation (Wu et al. (2016); Devlin et al. (2018)), and speech recognition (Zhang et al. (2016); Nassif et al. (2019)). However, tremendous computation and memory costs of these state-of-the-art DNNs make them challenging to deploy on resource-constrained devices such as mobile phones, edge sensors, and drones. Therefore, several edge hardware accelerators specifically optimized for intensive DNN computation have emerged, including Google's edge TPU(Google (2019)) and NVIDIA's NVDLA (NVIDIA (2019)).

One of the central techniques innovating these edge DNN accelerators is the quantization of deep neural networks (QDNN). QDNN reduces the complexity of DNN computation by quantizing network weights and activations to low-bit precision. Since the area and energy consumption of the multiply-accumulate (MAC) unit can be significantly reduced with the bit-width reduction (Sze et al. (2017)), thousands of them can be packed in a small area. Therefore, the popular edge DNN accelerators are equipped with densely integrated MAC arrays to boost their performance in compute-intensive operations such as matrix multiplication (MatMul) and convolution (Conv).

Early studies of QDNN focused on the quantization of weights and activations of MatMul and Conv to the same bit-width (Hubara et al. (2016); Rastegari et al. (2016); Zhou et al. (2016)). This uniform-precision QDNN gained popularity because it simplifies the dense MAC array design for edge DNN accelerators. However, uniform bit allocation did not account for the properties of individual layers in a network. Sakr & Shanbhag (2018) showed that the optimal bit-precision varies within a neural network from layer to layer. As a result, uniform-precision quantization may lead to sub-optimal inference accuracy for a given network.

Mixed-precision networks address this limitation by optimizing bit-widths at each layer. In this approach, the sensitivity of the layer to the quantization error is either numerically estimated (Zhou et al. (2017); Dong et al. (2019)) or automatically explored under the framework of neural architecture search (NAS, Wang et al. (2019); Elthakeb et al. (2018)) to allocate bit-precision properly. However, mixed-precision representation requires specific variable precision support in hardware, restricting computation units' density and power efficiency (Camus et al. (2019)). Therefore, mixed-precision support imposes a significant barrier for the low-profile edge accelerators with stringent hardware constraints.

In this work, we propose a novel NAS based hardware-friendly DNN quantization method that can address the layer-wise heterogeneous sensitivity under uniform-precision quantization. The proposed method explores network structure in terms of the number of channels. Different from the previous work that only includes pruning of the channels in its search space (Dong & Yang (2019)), we further incorporate the expansion of the channels, thus called *neural channel expansion* (NCE). During a search of NCE, search parameters associated with different numbers of channels are updated based on each layer's sensitivity to the uniform-precision quantization and the hardware constraints; the more sensitive to quantization errors, the larger number of channels preferred in that layer. When the preference to the larger number of channels in a layer exceeds a certain threshold, we expand the channels in that layer's search space so that the more number of channels can be explored. Therefore, NCE allows both pruning and expansion of each layer's channels, finding the sweet-spot for the trade-off between the robustness against the quantization error and the hardware cost. We analytically and empirically demonstrate that NCE can adequately facilitate the search to adapt the target model's structure for better quantization accuracy. The experimental results on CIFAR10 and ImageNet show that the network structures adapted from the popular convolutional neural networks (CNNs) achieve superior accuracy when the challenging 2-bit quantization is uniformly applied to MatMul and Conv layers. In particular, we achieve the best-to-date accuracy of 74.03/91.63% (Top-1/Top-5) for NCE-ResNet50 on ImageNet with slightly lower FLOPs and 30% reduced number of parameters.

Our contributions can be summarized as follows:

- We propose a new NAS-based quantization algorithm called *neural channel expansion* (NCE), which is equipped with a simple yet innovative channel expansion mechanism to balance the number of channels across the layers under uniform-precision quantization.
- We provide an in-depth analysis of NCE, shedding light on understanding the impact of channel expansion for compensation of quantization errors.
- We demonstrate that the proposed method can adapt the structure of target neural networks to significantly improve the quantization accuracy.

2 RELATED WORK

Neural architecture search: The goal of NAS is to find a network architecture that can achieve the best test accuracy. Early studies (Zoph & Le (2016); Zoph et al. (2018)) often employed meta-learners such as reinforcement learning (RL) agents to learn the policy for accurate network architectures. However, RL-based approaches may incur prohibitive search costs (e.g., thousands of GPU hours). As a relaxation, differentiable neural architecture search (DNAS) has been proposed (Liu et al. (2018)), which updates the search parameters and the weights via bi-level optimization. Recent DNAS approaches considered hardware constraints such as latency, the number of parameters, and FLOPs so that the search explored the trade-off between the cross-entropy loss and the hardware constraint loss. This search resulted in the discovery of light-weight models. As an example, Dong & Yang (2019) explored channel pruning that satisfies the target hardware constraints. In this work, we adopt the successful NAS framework in the domain of QDNN, for which we devise a novel channel expansion search to robustify networks against the quantization errors.

Low-precision quantization of deep neural network: QDNN has been actively studied in the literature. Early work on QDNN (Hubara et al. (2016); Rastegari et al. (2016); Zhou et al. (2016)) introduced the concept of a straight-through estimator (STE) for the approximation of gradients of the non-differentiable rounding operation. This approximation enabled uniform-precision (1- or multi-bit) quantization during the model training procedure, which fine-tunes the weight parameters towards lower training loss. QDNN techniques have evolved to adaptively find the quantization step size (Choi et al. (2018); Zhang et al. (2018); Jung et al. (2019); Esser et al. (2020)), which significantly enhanced the accuracy of the uniform-precision quantization. However, this line of research lacks consideration of the heterogeneous quantization sensitivity for individual layers in a network. On the other hand, mixed-precision quantization allows layer-specific bit-precision optimization; the higher bit-precision is assigned to the more quantization sensitive layers. Zhou et al. (2017); Dong et al. (2019) numerically estimated the sensitivity via approximating the impact of quantization errors on model prediction accuracy. Wang et al. (2019); Elthakeb et al. (2018) employed a reinforcement learning framework to learn the bit-allocation policy. Wu et al. (2018); Cai & Vasconcelos (2020) adopted DNAS with the various bit-precision operators in the search space. However, mixed-precision

representation requires specific variable precision support in hardware, restricting computation units' density and power efficiency (Camus et al. (2019)). Therefore, mixed-precision support imposes a significant barrier for the low-profile edge accelerators with stringent hardware constraints. In this work, we exploit NAS to address the layer-wise heterogeneous sensitivity under uniform-precision quantization.

Channel expansion for accurate DNN quantization: Researchers have actively studied channel expansion for accurate DNN quantization. Mishra et al. (2018) (WRPN) demonstrated that an increased number of channels during the training helped regain QDNN accuracy but without an in-depth understanding of it. Zhao et al. (2019) and Park & Choi (2019) further attempted to split the channels with large magnitude weights after the training. The split parameters get reduced dynamic range, and they can be represented with lower bit-precision. Regarding the control over the dynamic range, Meller et al. (2019) also adjusted the scale factors of the weight parameters after training to balance the dynamic range across the layers. However, none of these approaches shed light on understanding the benefit of the increased number of channels when a network is trained for quantization. We provide insights with empirical supports that the structure with the channel expanded layers itself matters, reducing the dynamic range during the quantization-aware training. These exciting insights become a pivotal motivation for us to explore channel expansion in the NAS framework.

3 Neural Channel Expansion

In this section, we explain the detail of our neural channel expansion method. Similar to TAS (Dong & Yang (2019)), we construct the search space over the number of channels $C = \{1 : c_{out}\}$ with the search parameters $\alpha \in \mathbb{R}^{|C|}$. Then the output activation is computed as the weighted sum of sampled activations with a different number of channels aligned via channel-wise interpolation (CWI):

$$\hat{O} = \sum_{j \in I} Softmax(\alpha_j; \{\alpha_k\}_{k \in I}) \times CWI(O_{1:C_j}, max\{c_{out}^k\}_{k \in I}), \tag{1}$$

where output activation $O_{j:1 \leq j \leq c_{out}} = \sum_{k=1}^{c_{in}} Q(X\{k,:,:\}) * Q(W\{j,k,:,:\})$ is computed with input activation X and weight parameters W quantized by the quantizer Q, and I is the sampled subset of C.

During the search, the search parameters are updated via channel selection based on the trade-off between the cross-entropy loss and the hardware constraint loss (e.g., FLOPs). In TAS, the number of channels ($|C|$) is fixed, limiting the exploration scope to the pruning. In NCE, we enable channel expansion of individual layers when the search parameter associated with the maximum number of channels exceeds a certain threshold. The intuition is that if one layer is susceptible to the quantization errors, its search parameters are updated toward the preference for a larger number of channels to decrease the cross-entropy loss. With this simple expansion condition, we can expand channels to those layers affected most by the quantization errors and prune channels of the other layers robust to quantization; therefore, the overall hardware constraints are met.

Algorithm 1 summarizes the overall procedure. NCE consists of three phases: warm-up, search, and train. As advocated by Wu et al. (2018) and Bender et al. (2020), we first perform a warm-up of the entire super-net so that all the super-net weight parameters can be reasonably initialized. The search phase consists of the iterative updates of weights (w) and the search parameters (α) via bi-level optimization. The updated search parameter associated with the maximum number of channels is compared with a threshold (pre-determined as a hyper-parameter) to identify if a layer needs a channel expansion in each layer. When a channel expansion happens (= *Expand*) , the additional weight parameters are added to that layer (and the search parameter is also copied), increasing the number of channels. Once the search is done, the candidate model is derived by the "winner-takes-all" strategy; i.e., for each layer, the number of channels with the largest magnitude search parameter is selected.

4 Analysis

This section explains how NCE finds the network structures that are more robust to the uniform-precision quantization error while maintaining hardware constraints. We first reveal insightful

---

Algorithm 1: Neural Channel Expansion

Input:

    Split the training set into two dis-joint sets: D_{weight} and D_{arch} ($n(D_{weight}) = n(D_{val})$)

    Search Parameter: $\{\alpha_1^l, \alpha_2^l, .., \alpha_n^l\} \in A^l$, $\{A^1, A^2, .., A^L\} \subset \mathbb{A}$, $L =$number of layer

    Expand Threshold: T

1   **For** Warm-up Epoch **do**

2   Sample batch data D_w from D_{weight} and network from $\mathbb{A} \sim U(0, 1)$

3   Calculate $Loss_{weight}$ on D_w to update network weights

4   **End For**

5   **For** Search Epoch **do**

6   Sample batch data D_w from D_{weight} and network from $Softmax(\mathbb{A})$

7   Calculate $Loss_{weight}$ on D_w to update network weights

8   Sample batch data D_a from D_{arch} and network from $Softmax(\mathbb{A})$

9   Calculate $Loss_{arch}$ on D_a to update $\mathbb{A}$

10   **For** layer **do**

11       $j \leftarrow \#A^l$

12   **If** $Softmax(\alpha_j^l; \{\alpha_k^l\}_{k \in j}) \geq T$ **do**

13   *Expand* search space(α_{j+1}^l)

14        $\alpha_{j+1}^l \leftarrow \alpha_j^l$ **# copy search parameter**

15   **End if**

16   **End for**

17   **End for**

18   Derive the searched network from $\mathbb{A}$

19   Randomly initialize the searched network and optimize it on the training set

---

observations that the expanded channel's structure reduces the input activation's dynamic range and suppresses quantization errors. In other words, a network structure adapted by NCE can be trained standalone from scratch and exhibit robustness to the quantization. This finding motivates us to seek a NAS based exploration for channel expansion; we show that NCE can facilitate compensation of the quantization errors by selective channel expansion.

4.1 IMPACT OF CHANNEL EXPANSION ON DYNAMIC RANGE OF ACTIVATION

As discussed in Sec.2, it is well studied that channel-splitting can decrease the dynamic range of the weight parameters. However, it is not clear how much its structure itself affects quantization during neural network training. To understand the impact of expanded channel structure on DNN quantization, we first show that quantization applied to a given network substantially increases the dynamic range of activation, hindering successful QDNN. Fig.1a shows the standard-deviation (STDEV) of input activation for ResNet20 trained from scratch on the CIFAR10 dataset, with and without quantization during training[1]. W{X}A{Y} indicates that weights and activations are quantized into X- and Y-bits, respectively. The substantial increase of STDEV for W2A2 implies that large quantization errors would occur when input activation is quantized. Such an increase of dynamic range could partially explain *why quantization with the fixed model structure often suffers significant accuracy degradation when ultra-low bit-precision is uniformly applied*. This intriguing phenomenon can be observed in all the models we investigated (e.g., VGG16 in Fig.1b).

In addition, Fig. 1a and Fig. 1b show the impact of expanded channel structure on the dynamic range. "2X" models indicate that the number of channels in their layers is doubled. All the hyper-parameter settings are the same. Notice that both 2X ResNet20 and VGG16 models with 2-bit quantization (= W2A2) could reduce the STDEV down to the full-precision 1X models.

One might regard this dynamic range reduction due to weight initialization with 2X channels, based on the idea similar to channel splitting discussed in Sec.2. However, we examined that the initial weight parameters have little impact on the input activation's dynamic range. More specifically, since

---

[1]This quantization-aware training follows the same hyper-parameter settings described in Sec.5.1.

Figure 1: (a) Layer-wise STDEV for ResNet20 with 1X or 2X channels. (The green curve is almost overlapped with the red.) (b) Layer-wise STDEV for VGG16 with 1X or 2X channels. (c) Test accuracy on ResNet20 with 1X or 2X channels.

we used "He" initialization (He et al. (2015))[2], the number of channels determines the dynamic range of the initial weights. As shown in Fig.1a, however, 2X ResNet20 with W2A2 quantization still experiences reduced STDEV even if its weights are initialized in the same way the 1X ResNet model is initialized.

Finally, we confirm that the input activation's reduced dynamic range results in improved test accuracy. As shown in Fig.1c, 1X ResNet20 model suffers large accuracy degradation from quantization (-2.22%) while 2X ResNet20 model experiences relatively small accuracy degradation (-0.84%). Note that this result is consistent with WRPN (Mishra et al. (2018)). However, we argue that such increased robustness against quantization errors is due to the mechanism that the expanded channel structure reduces the activation's dynamic range.

From these experimental results, we conjecture that expanded channel structure plays a crucial role in compensating quantization errors. This finding suggests that if we employ channel expansion in the NAS framework, we can adapt the channels of the layers to find a new network structure that is more robust to uniform-precision quantization when trained from scratch. In the next section, we investigate a proper way of incorporating channel expansion.

4.2 IMPACT OF CHANNEL EXPANSION ON DISTINCT CHANNEL SEARCH

The previous section provides critical reasoning behind the success of channel expansion of QDNN like WRPN. However, it is not practical to expand the channels of all the layers, since it will quadratically increase the computational complexity. The main idea of NCE is to allow channel expansion only when the selection of more number of channels is desirable for compensating quantization errors; otherwise, the channels are pruned to meet the overall hardware constraints. In this section, we show that the channel expansion mechanism of NCE propels such compensation.

We first show that the channel selection preference can be observed by the gradient w.r.t. the search parameters. As explained in Sec. 3, the critical trade-off explored during the search is between the cross-entropy loss and the hardware constraint loss. In particular, a layer that is sensitive to the cross-entropy may select a large number of channels. In other words, the search parameters associated with a large number of channels, like α_7 or α_8, receive large negative gradients.[3] As an example, Fig. 2a shows the gradients of the search parameters during the TAS search of CIFAR10-ResNet20 in full-precision. Note that the search parameter associated with the maximum number of channels (α_8) initially receives the negative gradients. In contrast, the search parameter with the least number of channels (α_1) receives positive gradients. From this trend, we can conjecture that this layer initially prefers a large number of channels, but the preference diminishes over the epochs of search.

---

[2]I.e., the weights are initialized with the normal distribution with standard deviation inversely proportional to the square root of the number of channels.

[3]I.e., $\alpha = \alpha - \eta * grad_\alpha$. Thus the negative gradients increase the magnitude of the search parameter.

Figure 2: Experiments on CIFAR10-ResNet20 that shows gradients of cross-entropy loss w.r.t. search parameters ($\alpha_1 \sim \alpha_8$) of a layer during search: (a) in full-precision, (b) with 2-bit quantization. (c) Kendall rank-correlation score of all layers.

Next, we show that quantization during search excels the preference for a large number of channels. From the same experimental settings, if we apply quantization during the search, the preference to a large number of channels becomes more distinctive, as shown in Fig. 2b. This phenomenon is because the quantization errors affect the cross-entropy loss more. To quantify this channel preference, we calculate the Kendall rank correlation score for the gradients of the search parameters and average over the search epochs; the more consistent preference to a large number of channels, the higher the Kendall score. Fig. 2c shows the layer-wise Kendall score with and without quantization. Note that the Kendall score is increased if the quantization is applied during the architecture search. This increased Kendall score implies that quantization drives the search parameters toward a strong preference to a larger number of channels.

As motivated by this phenomenon, we augment TAS's search space to allow channel expansion. Thanks to this new search space, channel expansion can happen selectively for the layer with a strong preference for many channels. Interestingly, the new search space gains the higher Kendall score, as shown in Fig. 2c, indicating that the search space allows preference to an even larger number of channels. In other words, our simple yet novel search space of selectively expanding the channels can mitigate the limit in choosing a larger number of channels, opening up more significant opportunities for compensating quantization errors.

4.3 DISCUSSION ON NEURAL CHANNEL EXPANSION

So far, we explained how NCE was devised to facilitate the channel expansion for compensating the quantization error. In this section, we further investigate two aspects of NCE to understand its strengths better.

4.3.1 BENEFIT OF QUANTIZATION-AWARE ARCHITECTURE SEARCH

We first show that NCE can reflect quantization during the search to find a better structure for quantization. As we discussed in the previous section, quantization affects the gradients w.r.t. the search parameters, resulting in the difference in the network structures after the search. In Fig.3a, we ran NCE for CIFAR10-ResNet20 with or without W2A2 quantization during the search. Then we took the models after each search and trained them from scratch with or without W2A2 quantization. After the full-precision training, both networks (searched with or without quantization) achieve the same accuracy level. In the case of W2A2, however, the network searched with quantization achieves noticeable gain in average accuracy over the network searched without quantization. Fig. 3b shows the difference in the channel section between the model searched with (=W2A2) and without quantization(=W32A32) where W2A2 prefers more channels in the later layers. This demonstrates that NCE can perform quantization-aware architecture search.

Figure 3: (a) Test accuracy after search with or without quantization. (b) Model structure after search with or without quantization. (c) Accuracy vs. FLOPs for different channel expansion strategies.

4.3.2 BENEFIT OF SELECTIVE CHANNEL EXPANSION

There are two options to search for channel expansion. One option is to start with the enlarged channels as the search space, while the other option is to expand the channel selectively as NCE does. We found that selective expansion always outperforms the static channel expansion. To understand the selective expansion's effectiveness, we constructed an experiment when the model is searched with 1) 1X channels accompanied by eight search parameters for each layer but with NCE, and 2) 2X channels accompanied by 16 search parameters layer. Note that the search space of the 1X-NCE case is strictly a subset of the 2X case. Therefore, if the 1X-NCE finds a suitable network structure, 2X should also find an equally good one. However, it turns out that the search results of the 2X case are inferior to the 2X case. As shown in Fig. 3c, for the same target FLOPs, the network structures found by the 2X case achieve inferior test accuracy than the 1X case. We conjecture that the larger search space might hinder successful optimization.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETTINGS

NCE is evaluated with popular CNNs trained on CIFAR10 and IamgeNet datasets. We employ PACT (Choi et al. (2018)) as the main quantization scheme. NCE is implemented in PyTorch based on the TAS framework[4]. For CIFAR10 experiments, we conducted 200 epochs of warm-up followed by NCE search for 600 epochs. we used threshold (T) of 0.3 and constraint coefficient of 2. For ImageNet experiments, we randomly choose 50 classes from the original 1000 classes to reduce the training time, similar to Wu et al. (2019). We conducted 40 epochs of warm-up followed by search for 110 epochs. we used threshold (T) of 0.19 and constraint coefficient of 1.5. We optimized the weight via SGD and the architecture parameters via Adam. Regularization coefficient of PACT is 0.001. After search, the candidate model is derived by the "winner-takes-all" strategy. Unless noted otherwise, all experiments on CIFAR10 are repeated for three times and the average test accuracy is reported. For fair comparison with prior work (e.g., Choi et al. (2018); Jung et al. (2019)), the first/last and short-cut layers are not considered for 2-bit uniform-precision quantization. More detailed information about the experimental settings can be found in Appendix.

5.2 CIFAR10 RESULTS

To evaluate NCE on CIFAR10, we employ four popular CNNs based on the ResNet structure and the other based on the VGG structure. For each network, we apply 2-bit quantization with and without NCE. As can be shown in Table 1, NCE consistently boosts the accuracy of QDNN w/o NCE by $0.35\% \sim 0.81\%$, demonstrating its benefit. Also, we demonstrate with CIFAR10-ResNet20 that the loss for hardware cost can be either FLOPs or the number of parameters (PARAM); Table 1 shows that ResNet20 could achieve higher accuracy when NCE searches with the PARAM loss. This flexibility in hardware loss can be convenient when targeting hardware platforms with specific needs.

---

[4]https://github.com/D-X-Y/AutoDL-Projects

Network	W32A32	w/o NCE			w/ NCE		
		W2A2	FLOPs	PARAM	W2A2	FLOPs	PARAM
ResNet20	92.88%	90.82%	40.81M	0.27M	91.63%*	39.94M	0.42M
					91.81%**	45.40M	0.27M
ResNet32	93.81%	92.22%	69.12M	0.47M	92.71%	64.26M	0.57M
ResNet56	94.26%	93.08%	125.75M	0.86M	93.43%	123.04M	0.74M
VGG16	94.24%	93.48%	313.2M	14.72M	93.94%	302.96M	5.01M

Table 1: CIFAR10: Comparision on test accuracy and computational complexity for 2-bit QDNN with or without NCE (*: FLOPs loss, **: PARAM loss).

Network	Method	Top-1 Acc	Top-5 Acc	FLOPs	PARAM
ResNet18	*Full precision*	*70.56%*	*89.88%*	1.814G	11.69M
	w/o NCE(Ours)	64.08%	86.47%	1.814G	11.69M
	w/ NCE(Ours)	**66.17%**	**86.75%**	**1.747G**	**12.57M**
	LSQ	67.6%	87.6%		
	QIL	65.7%	-		
	LQ-Nets	64.9%	85.9%	1.814G	11.69M
	PACT	64.4%	85.6%		
	EdMIPS	65.9%	86.5%		
ResNet50	*Full precision*	*76.82%*	*93.33%*	4.089G	25.56M
	w/o NCE(Ours)	72.36%	90.81%	4.089G	25.56M
	w/ NCE(Ours)	**74.03%**	**91.63%**	**3.932G**	**17.66M**
	LSQ	73.7%	91.5%		
	LQ-Nets	71.5%	90.3%	4.089G	25.56M
	PACT	72.2%	90.5%		
	EdMIPS	72.1%	90.6%		

Table 2: ImageNet: Top-1/Top-5 accuracy and computational complexity for 2-bit (W2A2) QDNN with or without NCE compared with the other state-of-the-art uniform (LSQ, QIL, LQ-Nets, PACT) and mixed-precision (EdMIPS) quantization methods.

5.3 IMAGENET RESULTS

We further evaluate NCE with ResNet structures on ImageNet by comparing it with state-of-the-art QDNN methods. We take reported Top-1 and Top-5 accuracy from the state-of-the-art uniform-precision quantization techniques; LSQ(Esser et al. (2020)), QIL(Jung et al. (2019)), LQ-Nets(Zhang et al. (2018)), and PACT(Choi et al. (2018)). We also include recent work on mixed-precision quantization; EdMIPS(Cai & Vasconcelos (2020)). The comparison of accuracy is summarized in Table 2. Note that NCE consistently improves the accuracy of 2-bit quantized models (=w/o NCE) by large margins (1.67% ∼ 2.09%) thanks to the structure's adaptation. Although the PACT quantizer's performance in NCE is inferior to the more recent techniques (e.g., LSQ and QIL), NCE could boost the accuracy to the extremely competitive level. In the case of ResNet50, NCE even surpasses the best-to-date QDNN method, LSQ, in terms of accuracy, FLOPs, and the number of parameters involved in the network. This superior performance indicates that NCE is a promising solution for compensating the accuracy degradation of QDNN.

6 CONCLUSION

In this work, we propose a novel approach that explores the neural network structure to achieve robust inference accuracy while using the simple uni-precision arithmetic units. The key idea is to explore the network structure under the impact of uni-precision quantization. Our novel differentiable neural architecture search employs the search space that can shrink and expand the channels so that the more sensitive layers can be equipped with more channels. At the same time, the overall resource requirements (e.g., FLOPs) are maintained. We provide substantial insights and empirical supports that the proposed method can achieve superior robustness in ultra-low uni-precision quantization for networks in CIFAR10 and ImageNet. In particular, we demonstrate a superior ResNet50 architecture that achieves higher accuracy for 2-bit inference with smaller FLOPs and the parameter size.

REFERENCES

Gabriel Bender, Hanxiao Liu, Bo Chen, Grace Chu, Shuyang Cheng, Pieter-Jan Kindermans, and Quoc V Le. Can weight sharing outperform random architecture search? an investigation with tunas. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14323–14332, 2020.

Zhaowei Cai and Nuno Vasconcelos. Rethinking differentiable search for mixed-precision neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2349–2358, 2020.

Vincent Camus, Linyan Mei, Christian Enz, and Marian Verhelst. Review and benchmarking of precision-scalable multiply-accumulate unit architectures for embedded neural-network processing. *IEEE Journal on Emerging and Selected Topics in Circuits and Systems*, 9(4):697–711, 2019.

Jungwook Choi, Zhuo Wang, Swagath Venkataramani, Pierce I-Jen Chuang, Vijayalakshmi Srinivasan, and Kailash Gopalakrishnan. Pact: Parameterized clipping activation for quantized neural networks. *arXiv preprint arXiv:1805.06085*, 2018.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Xuanyi Dong and Yi Yang. Network pruning via transformable architecture search. In *Advances in Neural Information Processing Systems*, pp. 760–771, 2019.

Zhen Dong, Zhewei Yao, Amir Gholami, Michael W Mahoney, and Kurt Keutzer. Hawq: Hessian aware quantization of neural networks with mixed-precision. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 293–302, 2019.

Ahmed T Elthakeb, Prannoy Pilligundla, FatemehSadat Mireshghallah, Amir Yazdanbakhsh, Sicun Gao, and Hadi Esmaeilzadeh. Releq: an automatic reinforcement learning approach for deep quantization of neural networks. *arXiv preprint arXiv:1811.01704*, 2018.

Steven K Esser, Jeffrey L McKinstry, Deepika Bablani, Rathinakumar Appuswamy, and Dharmendra S Modha. Learned step size quantization. In *International Conference on Learning Representations*, 2020.

Google. Edge tpu - run inference at the edge, 2019. URL https://cloud.google.com/edge-tpu.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Itay Hubara, Matthieu Courbariaux, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks. In *Advances in neural information processing systems*, pp. 4107–4115, 2016.

Sangil Jung, Changyong Son, Seohyung Lee, Jinwoo Son, Jae-Joon Han, Youngjun Kwak, Sung Ju Hwang, and Changkyu Choi. Learning to quantize deep networks by optimizing quantization intervals with task loss. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4350–4359, 2019.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. Darts: Differentiable architecture search. *arXiv preprint arXiv:1806.09055*, 2018.

Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *European conference on computer vision*, pp. 21–37. Springer, 2016.

Eldad Meller, Alexander Finkelstein, Uri Almog, and Mark Grobman. Same, same but different: Recovering neural network quantization error through weight factorization. In *International Conference on Machine Learning*, pp. 4486–4495, 2019.

Asit Mishra, Eriko Nurvitadhi, Jeffrey J Cook, and Debbie Marr. Wrpn: Wide reduced-precision networks. In *International Conference on Learning Representations*, 2018.

Ali Bou Nassif, Ismail Shahin, Imtinan Attili, Mohammad Azzeh, and Khaled Shaalan. Speech recognition using deep neural networks: A systematic review. *IEEE Access*, 7:19143–19165, 2019.

NVIDIA. Nvidia deep learning accelerator, 2019. URL https://nvdla.org.

Hanmin Park and Kiyoung Choi. Cell division: weight bit-width reduction technique for convolutional neural network hardware accelerators. In *Proceedings of the 24th Asia and South Pacific Design Automation Conference*, pp. 286–291, 2019.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *European conference on computer vision*, pp. 525–542. Springer, 2016.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pp. 91–99, 2015.

Charbel Sakr and Naresh Shanbhag. An analytical method to determine minimum per-layer precision of deep neural networks. In *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 1090–1094. IEEE, 2018.

Vivienne Sze, Yu-Hsin Chen, Tien-Ju Yang, and Joel S Emer. Efficient processing of deep neural networks: A tutorial and survey. *Proceedings of the IEEE*, 105(12):2295–2329, 2017.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pp. 6105–6114, 2019.

Mingxing Tan, Ruoming Pang, and Quoc V Le. Efficientdet: Scalable and efficient object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10781–10790, 2020.

Kuan Wang, Zhijian Liu, Yujun Lin, Ji Lin, and Song Han. Haq: Hardware-aware automated quantization with mixed precision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8612–8620, 2019.

Bichen Wu, Yanghan Wang, Peizhao Zhang, Yuandong Tian, Peter Vajda, and Kurt Keutzer. Mixed precision quantization of convnets via differentiable neural architecture search. *arXiv preprint arXiv:1812.00090*, 2018.

Bichen Wu, Xiaoliang Dai, Peizhao Zhang, Yanghan Wang, Fei Sun, Yiming Wu, Yuandong Tian, Peter Vajda, Yangqing Jia, and Kurt Keutzer. Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 10734–10742, 2019.

Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V Le, Mohammad Norouzi, Wolfgang Macherey, Maxim Krikun, Yuan Cao, Qin Gao, Klaus Macherey, et al. Google's neural machine translation system: Bridging the gap between human and machine translation. *arXiv preprint arXiv:1609.08144*, 2016.

Dongqing Zhang, Jiaolong Yang, Dongqiangzi Ye, and Gang Hua. Lq-nets: Learned quantization for highly accurate and compact deep neural networks. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 365–382, 2018.

Ying Zhang, Mohammad Pezeshki, Philémon Brakel, Saizheng Zhang, César Laurent, Yoshua Bengio, and Aaron Courville. Towards end-to-end speech recognition with deep convolutional neural networks. *Interspeech 2016*, pp. 410–414, 2016.

Ritchie Zhao, Yuwei Hu, Jordan Dotzel, Chris De Sa, and Zhiru Zhang. Improving neural network quantization without retraining using outlier channel splitting. In *International Conference on Machine Learning*, pp. 7543–7552, 2019.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv preprint arXiv:1606.06160*, 2016.

Yiren Zhou, Seyed-Mohsen Moosavi-Dezfooli, Ngai-Man Cheung, and Pascal Frossard. Adaptive quantization for deep neural network. *arXiv preprint arXiv:1712.01048*, 2017.

Barret Zoph and Quoc V Le. Neural architecture search with reinforcement learning. *arXiv preprint arXiv:1611.01578*, 2016.

Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8697–8710, 2018.

7 APPENDIX

7.1 EXPERIMENTAL DETAILS

In this section, we summarize the details of our training settings. The CIFAR10 dataset (Krizhevsky Hinton (2010)) is an image classification benchmark containing 32x32 pixel RGB images. It consists of 50K training and 10K test image sets. We used RandomHorizontalFlip and Normalization for preprocessing. We used stochastic gradient descent (SGD) with a momentum of 0.9 and learning rate starting from 0.1 and scheduled by cosine annealing to update network weight. We used Adam optimizer and learning rate of 0.001 to update the search parameter. L2-regularizer with the decay of 0.0004 is applied to weight, and 0.001 is applied to the search parameter. The mini-batch size of 256 is used.

The ImageNet dataset (Russakovsky et al. (2015)) consists of 1000-categories of objects with over 1.2M training and 50K validation images. We used RandomResizedCrop, RandomHorizontalFlip and Normalization for preprocessing. We used stochastic gradient descent (SGD) with a momentum of 0.9 and learning rate starting from 0.1 and scaled by 0.1 at epoch 30, 60, 85, 95 to update network weight. We used Adam and a learning rate of 0.001 to update the search parameter. L2-regularizer with the decay of 0.0001 is applied to weight, and 0.001 is applied to the search parameter. The mini-batch size of 256 is used.