CAUSAL PROXY MODELS FOR CONCEPT-BASED MODEL EXPLANATIONS

ABSTRACT

Explainability methods for NLP systems encounter a version of the fundamental problem of causal inference: for a given ground-truth input text, we never truly observe the counterfactual texts necessary for isolating the causal effects of model representations on outputs. In response, many explainability methods make no use of counterfactual texts, assuming they will be unavailable. In this paper, we show that robust causal explainability methods can be created using approximate counterfactuals, which can be written by humans to approximate a specific counterfactual or simply sampled using metadata-guided heuristics. The core of our proposal is the Causal Proxy Model (CPM). A CPM explains a black-box model $\mathcal{N}$ because it is trained to have the same *actual* input/output behavior as $\mathcal{N}$ while creating neural representations that can be intervened upon to simulate the *counterfactual* input/output behavior of $\mathcal{N}$. Furthermore, we show that the best CPM for $\mathcal{N}$ performs comparably to $\mathcal{N}$ in making factual predictions, which means that the CPM can simply replace $\mathcal{N}$, leading to more explainable deployed models.

1 INTRODUCTION

The gold standard for explanation methods in AI should be to elucidate the *causal role* that a model's representations play in its overall behavior – to truly explain *why* the model makes the predictions it does. Causal explanation methods seek to do this by resolving the counterfactual question of what the model would do if input X were changed to a relevant counterfactual version X'. Unfortunately, even though neural networks are fully observed, deterministic systems, we still encounter the fundamental problem of causal inference (Holland, 1986): for a given ground-truth input X, we never observe the counterfactual inputs X' necessary for isolating the causal effects of model representations on outputs. The issue is especially pressing in domains where it is hard to synthesize approximate counterfactuals. In response to this, explanation methods typically do not explicitly train on counterfactuals at all.

In this paper, we show that robust explanation methods for NLP models can be obtained using texts approximating true counterfactuals. The heart of our proposal is the Causal Proxy Model (CPM). CPMs are trained to mimic both the factual and counterfactual behavior of a black-box model $\mathcal{N}$. We explore two different methods for training such explainers. These methods share a distillation-style objective that pushes them to mimic the factual behavior of $\mathcal{N}$, but they differ in their counterfactual objectives. The input-based method CPM_{IN} appends to the factual input a new token associated with the counterfactual concept value. The hidden-state method CPM_{HI} employs the Interchange Intervention Training (IIT) method of Geiger et al. (2021b) to localize information about the target concept in specific hidden states. Figure 1 provides a high-level overview.

We evaluate these methods on the CEBaB benchmark for causal explanation methods (Abraham et al., 2022), which provides large numbers of original examples (restaurant reviews) with human-created counterfactuals for specific concepts (e.g., service quality), with all the texts labeled for their concept-level and text-level sentiment. We consider two types of approximate counterfactuals derived from CEBaB: texts written by humans to approximate a specific counterfactual, and texts sampled using metadata-guided heuristics. Both approximate counterfactual strategies lead to state-of-the-art performance on CEBaB for both CPM_{IN} and CPM_{HI}.

We additionally identify two other benefits of using CPMs to explain models. First, both CPM_{IN} and CPM_{HI} have factual performance comparable to that of the original black-box model $\mathcal{N}$ and can explain their own behavior extremely well. Thus, the CPM for $\mathcal{N}$ can actually replace $\mathcal{N}$, leading

to more explainable deployed models. Second, CPM_{HI} models localize concept-level information in their hidden representations, which makes their behavior on specific inputs very easy to explain. We illustrate this using the Integrated Gradients method of Sundararajan et al. (2017). Thus, while both CPM_{IN} and CPM_{HI} are comparable as explanation methods according to CEBaB, the qualitative insights afforded by CPM_{HI} models may given them the edge when it comes to explanations.

2 RELATED WORK

Understanding model behavior serves many goals for large-scale AI systems, including transparency (Kim, 2015; Lipton, 2018; Pearl, 2019; Ehsan et al., 2021), trustworthiness (Ribeiro et al., 2016; Guidotti et al., 2018; Jacovi & Goldberg, 2020; Jakesch et al., 2019), safety (Amodei et al., 2016; Otte, 2013), and fairness (Hardt et al., 2016; Kleinberg et al., 2017; Goodman & Flaxman, 2017; Mehrabi et al., 2021). With CPMs, our goal is to achieve explanations that are causally motivated and concept-based, and so we concentrate here on relating existing methods to these two goals.

Feature attribution methods estimate the importance of features, generally by inspecting learned weights directly or by perturbing features and studying the effects this has on model behavior (Molnar, 2020; Ribeiro et al., 2016). Gradient-based feature attribution methods extend this general mode of explanation to the hidden representations in deep networks (Zeiler & Fergus, 2014; Springenberg et al., 2014; Binder et al., 2016; Shrikumar et al., 2017; Sundararajan et al., 2017). Concept Activation Vectors (CAVs; Kim et al. 2018; Yeh et al. 2020) can also be considered feature attribution methods, as they probe for semantically meaningful directions in the model's internal representations and use these to estimate the importance of concepts on the model predictions. While some methods in this space do have causal interpretations (e.g., Sundararajan et al. 2017; Yeh et al. 2020), most do not. In addition, most of these methods offer explanations in terms of specific (sets of) features/neurons. (Methods based on CAVs operate directly in terms of more abstract concepts.)

Intervention-based methods study model representations by modifying them in systematic ways and observing the resulting model behavior. These methods are generally causally motivated and allow for concept-based explanations. Examples of methods in this space include causal mediation analysis (Vig et al., 2020; De Cao et al., 2021; Ban et al., 2022), causal effect estimation (Feder et al., 2021; Elazar et al., 2021; Abraham et al., 2022), tensor product decomposition (Soulos et al., 2020), and causal abstraction analysis (Geiger et al., 2020; 2021a). CPMs are most closely related to the method of IIT (Geiger et al., 2021a), which extends causal abstraction analysis to optimization.

Probing is another important class of explanation method. Traditional probes do not intervene on the target model, but rather only seek to find information in it via supervised models (Conneau et al., 2018; Tenney et al., 2019) or unsupervised models (Clark et al., 2019; Manning et al., 2020; Saphra & Lopez, 2019). Probes can identify concept-based information, but they cannot offer guarantees that probed information is relevant for model behavior (Geiger et al., 2021a). For causal guarantees, it is likely that some kind of intervention is required. For example, Elazar et al. (2021) and Feder et al. (2021) remove information from model representations to estimate the causal role of that information. Our CPMs employ a similar set of guiding ideas but are not limited to removing information.

Counterfactual explanation methods aim to explain model behavior by providing a counterfactual example that changes the model behavior (Goyal et al., 2019; Verma et al., 2020; Wu et al., 2021). Counterfactual explanation methods are inherently causal. If they can provide counterfactual examples with regard to specific concepts, they are also concept-based.

Some explanation methods train a model making explicit use of intermediate variables representing concepts. Manipulating these intermediate variables at test-time yields causal concept-based model explanations (Koh et al., 2020; Künzel et al., 2019).

Evaluating methods in this space has been a persistent challenge. In prior literature, explanation methods have often been evaluated against synthetic datasets (Feder et al., 2021; Yeh et al., 2020). In response, Abraham et al. (2022) introduced the CEBaB dataset, which provides a human-validated concept-based dataset to truthfully evaluate different causal concept-based model explanation methods. Our primary evaluations are conducted on CEBaB.

(a) A structural causal model leading to an actual text $x_{u,v}$ and its counterfactual text $x_{u,v}^{C_i \leftarrow c'}$. U is an exogenous variable over experiences, $c_1, \ldots, c_k$ are mediating concepts, and V is an exogenous variable capturing the writing experience. At right, we create a counterfactual in which concept C_i takes on a different value. Unfortunately, we cannot truly create such counterfactual situations and so we never observe pairs of texts like these. Thus, we must rely on approximate counterfactuals.

Let $x_{u,v}$ be a text written in situation (u, v):

Human-created $\tilde{x}_{u,v}^{C_i \leftarrow c'}$

Crowdworker edit of $x_{u,v}$ to express that C_i had value c', seeking to keep all else constant.

Metadata-sampled $\tilde{x}_{u,v}^{C_i \leftarrow c'}$

Sampled text expressing that C_i has value c' but agreeing with $x_{u,v}$ on all other concepts.

(b) Approximate counterfactuals. In the human-created strategy, humans revise an attested text to try to express a particular counterfactual, seeking to simulate a causal intervention. In the metadata-sampled strategy, we find a separate text that aligns with the original for the value u insofar as it expresses all the same concepts except for the target concept C_i.

(c) $\mathcal{L}_{\text{Mimic}}$: All CPMs (bottom) are trained to mimic the behavior of the neural model $\mathcal{N}$ to be explained (top) for all factual inputs $x_{u,v}$.

(d) $\mathcal{L}_{\text{IN}}$: Examples $x_{u,v}$ and $\tilde{x}_{u,v}^{C_i \leftarrow c'}$ are an approximate counterfactual pair. The CPM is given $x_{u,v}$ augmented with a special token $t_{C_i \leftarrow c'}$ and trained to mimic the target model $\mathcal{N}$ when its input is $\tilde{x}_{u,v}^{C_i \leftarrow c'}$.

(e) $\mathcal{L}_{\text{HI}}$: Examples $x_{u,v}$ and $\tilde{x}_{u,v}^{C_i \leftarrow c'}$ are an approximate counterfactual pair. The CPM is given input $x_{u,v}$. The objective is for it to mimic $\mathcal{N}$ given $\tilde{x}_{u,v}^{C_i \leftarrow c'}$, but under the intervention in which specific internal states are changed to those that the CPM computes for input $x_{u',v'}^{C_i = c'}$, which is a distinct example that is sampled with the only criteria being that it express $C_i = c'$. The effect of this intervention is to localize information about concept C_i at the intervention site, since the only indication the CPM gets about $C_i \leftarrow c'$ is via the intervention.

Figure 1: Causal Proxy Model (CPM) summary. Every CPM for model $\mathcal{N}$ is trained to mimic the factual behavior of $\mathcal{N}$ ($\mathcal{L}_{\text{Mimic}}$). For CPM$_{\text{IN}}$, the counterfactual objective is $\mathcal{L}_{\text{IN}}$. For CPM$_{\text{HI}}$, the counterfactual objective is $\mathcal{L}_{\text{HI}}$.

3 CAUSAL PROXY MODEL (CPM)

Causal Proxy Model (CPMs) are causal concept-based explanation methods. Given a factual input $x_{u,v}$ and a description of a concept intervention $C_i \leftarrow c'$, they estimate the effect of the intervention on model output. The present section introduces our two core CPM variants in detail. We concentrate here on introducing the structure of these models and their objectives, and we save discussion of associated metrics for explanation methods for Section 4.

A Structural Causal Model Our discussion is grounded in the causal model depicted in Figure 1a, which aligns well with the CEBaB benchmark. Two exogenous variables U and V together represent the complete state of the world and generate some textual data X. The effect of exogenous variable U on the data X is completely mediated by a set of intermediate variables $C_1, C_2 \ldots, C_k$, which we refer to as *concepts*. Therefore, we can think of U as the part of the world that gives rise to these concepts $\{C\}_1^k$.

Using this causal model, we can describe counterfactual data – data that arose under a counterfactual state of the world (right diagram in Figure 1a). Our factual text is $x_{u,v}$, and we use $x_{u,v}^{C_i \leftarrow c'}$ for the counterfactual text obtained by intervening on concept C_i to set its value to c'. The counterfactual $x_{u,v}^{C_i \leftarrow c'}$ describes the output when the value of C_i is set to c', all else being held equal.

Approximate Counterfactuals Unfortunately, pairs like $(x_{u,v}, x_{u,v}^{C_i \leftarrow c'})$ are never observed, and thus we need strategies for creating approximate counterfactual $\tilde{x}_{u,v}^{C_i \leftarrow c'}$. Figure 1b describes the two strategies we use in this paper. In the human-created strategy, we rely on a crowdworker to edit $x_{u,v}$ to achieve a particular counterfactual goal – say, making the evaluation of the restaurant's food negative. CEBaB contains an abundance of such pairs $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$. However, CEBaB is unusual in having so many human-created approximate counterfactuals, so we also explore a simpler strategy in which $\tilde{x}_{u,v}^{C_i \leftarrow c'}$ is sampled with the requirement that it match $x_{u,v}$ on all concepts and set C_i to c'. This strategy is supported in many real-world datasets – for example, the OpenTable reviews underlying CEBaB all have the needed metadata (Abraham et al., 2022).

CPM$_\text{IN}$: Input-based CPM To train CPM$_\text{IN}$, we associate a new randomly initialized token $t_{C_i \leftarrow c'}$ with each unique intervention description $C_i \leftarrow c'$. Given a dataset of approximate counterfactual pairs $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$ and a black-box model $\mathcal{N}$, we train a new CPM$_\text{IN}$ model $\mathcal{P}$ under a weighted sum of the following objectives:

$$\mathcal{L}_\text{Mimic} = \text{CE}_\text{S}\big(\mathcal{N}(x_{u,v}), \mathcal{P}(x_{u,v})\big) \tag{1}$$

$$\mathcal{L}_\text{IN} = \text{CE}_\text{S}\big(\mathcal{N}(\tilde{x}_{u,v}^{C_i \leftarrow c'}), \mathcal{P}(x_{u,v}; t_{C_i \leftarrow c'})\big) \tag{2}$$

where $x_{u,v}; t_{C_i \leftarrow c'}$ in Eqn. 2 denotes the concatenation of the factual input and the token describing the intervention. CE_S represents the smoothed cross-entropy loss (Hinton et al., 2015), measuring the divergence between the output logits of both models. The objective in Eqn. 1 pushes $\mathcal{P}$ to predict the same output as $\mathcal{N}$ under conventional circumstances (Figure 1c), while Eqn. 2 pushes $\mathcal{P}$ to predict the counterfactual behavior of $\mathcal{N}$ when a descriptor of the intervention is given (Figure 1d).

At inference time, approximate counterfactuals are inaccessible. To explain model $\mathcal{N}$, we append the newly learned descriptor tokens $t_{C_i \leftarrow c'}$ to a factual input, upon which $\mathcal{P}$ predicts a counterfactual output for an input with desired intervention description $C_i \leftarrow c'$ to estimate the counterfactual behavior of $\mathcal{N}$.

CPM$_\text{HI}$: Hidden-state CPM Our CPM$_\text{HI}$ models are trained on the same data and with the same set of goals as CPM$_\text{IN}$, to mimic both the factual and counterfactual behavior of $\mathcal{N}$. The key difference is how the information about the intervention $C_i \leftarrow c'$ is exposed to the model. Specifically, we adapt Interchange Intervention Training (Geiger et al., 2021b) to train our CPM$_\text{HI}$ models for concept-based model explanation.

A conventional intervention on a hidden representation H of a neural network $\mathcal{N}$ fixes the value of the representation H to a constant. In an interchange intervention, we instead fix H to the value it would have been when processing a separate source input s. The result of the interchange intervention is a new model. Formally, we describe this new model as $\mathcal{N}_{H \leftarrow H_s}$, where $\leftarrow$ is the conventional intervention operator and H_s is the value of hidden representation H when processing input s.

Given a dataset of approximate counterfactual input pairs $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$ and a black-box model $\mathcal{N}$, we train a new CPM$_\text{HI}$ model $\mathcal{P}$ under a weighted sum of the previous factual objective Eqn. 1 and the following counterfactual objective:

$$\mathcal{L}_\text{HI} = \text{CE}_\text{S}\big(\mathcal{N}(\tilde{x}_{u,v}^{C_i \leftarrow c'}), \mathcal{P}_{H^{C_i} \leftarrow H_s^{C_i}}(x_{u,v})\big) \tag{3}$$

Here H^{C_i} are hidden states designated for concept C_i. In essence, we train $\mathcal{P}$ to fully mediate the effect of intervening on C_i in the hidden representation H^{C_i}. The source input s is any input $x_{u',v'}^{C_i = c'}$

that has $C_i = c'$. As $\mathcal{P}$ only receives information about the intervention $C_i \leftarrow c'$ via the interchange intervention $H^{C_i} \leftarrow H_s^{C_i}$, the model is forced to store all causally relevant information with regard to C_i in the corresponding hidden representation. This process is described in Figure 1e.

In the ideal situation, $x_{u',v'}^{C_i=c'}$ and $x_{u,v}$ share the same value only for C_i and differ on all others, so that the counterfactual signal needed for localization is pure. However, we do not insist on this when we sample. In addition, we allow *null effect* pairs in which $x_{u,v}$ and $\tilde{x}_{u,v}^{C_i \leftarrow c'}$ are identical. For additional details on this sampling procedure, see Appendix A.2.

At inference time, approximate counterfactuals are inaccessible, as before. To explain model $\mathcal{N}$ with regard to intervention $C_i \leftarrow c'$, we manipulate the internal states of model $\mathcal{P}$ by intervening on the localized representation H^{C_i} for concept C_i. To achieve this, we sample a source input $x_{u',v'}^{C_i=c'}$ from the train set as any input x that has $C_i = c'$ to derive H_s.

4 EXPERIMENT SETUP

4.1 CAUSAL ESTIMATION-BASED BENCHMARK (CEBaB)

CEBaB (Abraham et al., 2022) is a large benchmark of high-quality, labeled approximate counterfactual for the task of sentiment analysis on restaurant reviews. The benchmark was created starting from a set of 2,299 original restaurant reviews from OpenTable. For each of these original reviews, approximate counterfactual examples were written by human annotators; the annotators were tasked to edit the original text to reflect a specific intervention, like 'change the food evaluation from negative to positive' or 'change the service evaluation from positive to unknown'. In this way, the original reviews were expanded with approximate counterfactuals to a total of 15,089 texts. The groups of originals and corresponding approximate counterfactuals are partitioned over train, dev, and test sets. The pairs in the development and test set are used to benchmark explanation methods.

Each text in CEBaB was labeled by five crowdworkers with a 5-star sentiment score. In addition, each text was annotated at the concept level for four mediating concepts $\{C_{\text{ambiance}}, C_{\text{food}}, C_{\text{noise}}, \text{and} \ C_{\text{service}}\}$, using the labels $\{\text{negative}, \text{unknown}, \text{positive}\}$, again with five crowdworkers annotating each concept-level label. We refer to Appendix A.1 and Abraham et al. 2022 for additional details.

As discussed above (Section 3 and Figure 1b), we consider two sources of approximate counterfactuals using CEBaB. For human-created counterfactuals, we use the edited restaurant reviews of the train set. For metadata-sampled counterfactuals, we sample factual inputs from the train set that have the desired combination of mediating concepts. Using all the human-created edits leads to 19,684 training pairs of factual and corresponding approximate counterfactuals. Sampling counterfactuals leads to 74,574 pairs. We use these approximated counterfactuals to train explanation methods. Appendix A.2 provides more information about our pairing process.

4.2 EVALUATION METRICS

Much of the value of a benchmark CEBaB derives from its support for directly estimating the Individual Causal Concept Effect (ICaCE) for a model $\mathcal{N}$ given a human-generated approximate counterfactual pair $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$:

$$\widehat{\text{ICaCE}}_{\mathcal{N}}(x_{u,v}, x_{u,v}^{C_i \leftarrow c'}) = \mathcal{N}(\tilde{x}_{u,v}^{C_i \leftarrow c'}) - \mathcal{N}(x_{u,v}) \tag{4}$$

This is simply the difference between the vectors of output scores for the two examples.

We do not expect to have pairs $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$ at inference-time, and this is what drives the development of explanation methods $\mathcal{E}_{\mathcal{N}}$ that *estimate* this quantity using only a factual input $x_{u,v}$ and a description of the intervention $C_i \leftarrow c'$. To benchmark such methods, we follow Abraham et al. (2022) in using the ICaCE-Error:

$$\text{ICaCE-Error}_{\mathcal{N}}^{\mathcal{D}}(\mathcal{E}) = \frac{1}{|\mathcal{D}|} \sum_{(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'}) \in \mathcal{D}} \text{Dist}\big(\widehat{\text{ICaCE}}_{\mathcal{N}}((x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})), \mathcal{E}_{\mathcal{N}}(x_{u,v}; C_i \leftarrow c')\big) \tag{5}$$

Here, we assume that $\mathcal{D}$ is a dataset consisting entirely of approximated counterfactual pairs $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$. Dist measures the distance between the actual ICaCE for the model $\mathcal{N}$ and the

effect predicted by the explanation method. Abraham et al. (2022) consider three values for Dist: cosine distance, which captures the direction of effects but not their magnitude; L2, which captures both direction and magnitude, and NormDiff, which captures magnitude but not direction. We report all three metrics.

4.3 BASELINE METHODS

BEST$_{\text{CEBaB}}$ We compare our results with the best results obtained on the CEBaB benchmark. Crucially, BEST$_{\text{CEBaB}}$ is not a single model, but rather pools together the best result obtained by *any* explanation method previously benchmarked on the CEBaB dataset, for every combination of model and metric. Additionally, we supply task performance as `Macro-F1` for CEBaB as a five-class sentiment classification task for each model.

S-Learner Our version of S-Learner (Künzel et al., 2019) learns to mimic the factual behavior of black-box model $\mathcal{N}$ while making the intermediate concepts explicit.[1] Given a factual input, a finetuned BERT model $\mathcal{B}$ first predicts values for the intermediate concepts. Then, a logistic regression model $\text{LR}_{\mathcal{N}}$ is trained to map these intermediate concept values to the factual output of black-box model $\mathcal{N}$, under the following objective.[2]

$$\mathcal{L}_{\text{Mimic}}^{\text{S},\mathcal{B}} = \text{CE}_{\text{S}}\big(\mathcal{N}(x_{u,v}), \text{LR}_{\mathcal{N}}(\mathcal{B}(x_{u,v}))\big) \tag{6}$$

By intervening on the intermediate predicted concept values at inference-time, we can hope to simulate the counterfactual behavior of $\mathcal{N}$:

$$\mathcal{E}_{\mathcal{N}}^{\text{S},\mathcal{B}}(x_{u,v}; C_i \leftarrow c') = \text{LR}_{\mathcal{N}}((\mathcal{B}(x_{u,v}))_{C_i \leftarrow c'}) - \text{LR}_{\mathcal{N}}(\mathcal{B}(x_{u,v})) \tag{7}$$

When using S-Learner in conjunction with approximate counterfactual inputs at train-time, we simply add this counterfactual data on top of the observational data that is typically used to train S-Learner.

GPT-3 Large language models such as `GPT-3` (175B) have shown extraordinary power in terms of in-context learning (Brown et al., 2020).[3] We use `GPT-3` to generate a new approximated counterfactual at test-time given a factual input and a descriptor of the intervention. This generated counterfactual is directly used to estimate the change in model behavior:

$$\mathcal{E}_{\mathcal{N}}^{\text{GPT-3}}(x_{u,v}; C_i \leftarrow c') = \mathcal{N}(\text{GPT-3}(x_{u,v}; C_i \leftarrow c')) - \mathcal{N}(x_{u,v}) \tag{8}$$

We use our train-time approximated counterfactual inputs to construct a prompt for `GPT-3`. Given this prompt, `GPT-3` outputs new approximated counterfactuals given a factual and intervention descriptor. Full details on how these prompts are constructed can be found in Appendix A.7.

4.4 CAUSAL PROXY MODELS

We train CPMs for the publicly available models released for CEBaB, fine-tuned as five-way sentiment classifiers on the factual data. This includes four model architectures: `bert-base-uncased` (BERT; Devlin et al. 2019), `RoBERTa-base` (RoBERTa; Liu et al. 2019), `GPT-2` (GPT-2; Radford et al. 2019), and `LSTM+GloVe` (LSTM; Hochreiter & Schmidhuber 1997; Pennington et al. 2014). All Transformer-based models (Vaswani et al., 2017) have 12 Transformer layers. We include details about our setup in Appendix A.3.

The inference time comparisons for these models are as follows:

$$\mathcal{E}_{\mathcal{N}}^{\text{CPM}_{\text{IN}}}(x_{u,v}; C_i \leftarrow c') = \mathcal{P}(x_{u,v}; t_{C_i \leftarrow c'}) - \mathcal{N}(x_{u,v}) \tag{9}$$

$$\mathcal{E}_{\mathcal{N}}^{\text{CPM}_{\text{HI}}}(x_{u,v}; C_i \leftarrow c') = \mathcal{P}_{H^{C_i} \leftarrow H_s^{C_i}}(x_{u,v}) - \mathcal{N}(x_{u,v}) \tag{10}$$

where s is a source input with $C_i = c'$, C_i is the neural representation associated with H^{C_i}, and $H_s^{C_i}$ is the neural representation associated with H^{C_i} for the source input s. For BERT and RoBERTa, we always map concepts to "[CLS]" token embeddings. For GPT-2, we map to the padded token embeddings at the end of input sequences. For LSTM, we map to the attention-gated sentence

---

[1]We use the finetuned concept-level sentiment analysis models released by Abraham et al. (2022).

[2]We use the default implementation `LogisticRegression` of `scikit-learn` (Buitinck et al., 2013).

[3]We use the largest `davinci` model publicly available at `https://beta.openai.com/playground`.

Model	Metric	BEST$_{\text{CEBaB}}$	S-Learner *no counterfactuals*	S-Learner *sampling*	S-Learner *human*	GPT-3 (175B) *sampling*	GPT-3 (175B) *human*	CPM$_{\text{IN}}$ (ours) *sampling*	*human*	CPM$_{\text{HI}}$ (ours) *sampling*	*human*
BERT	L2$_{\text{ICaCE}}$	0.74 (.02)	0.74 (.02)	0.74 (.02)	0.73 (.02)	0.71 (.01)	0.45 (.01)	0.63 (.01)	0.45 (.02)	0.60 (.01)	0.45 (.03)
	Cos$_{\text{ICaCE}}$	0.59 (.03)	0.63 (.01)	0.63 (.01)	0.60 (.01)	0.51 (.00)	0.36 (.00)	0.46 (.00)	0.35 (.00)	0.45 (.00)	0.36 (.04)
	NormDiff$_{\text{ICaCE}}$	0.44 (.01)	0.54 (.02)	0.53 (.02)	0.52 (.02)	0.35 (.00)	0.25 (.00)	0.39 (.01)	0.24 (.01)	0.38 (.00)	0.27 (.01)
RoBERTa	L2$_{\text{ICaCE}}$	0.78 (.01)	0.78 (.01)	0.78 (.00)	0.77 (.00)	0.74 (.01)	0.48 (.01)	0.66 (.01)	0.46 (.01)	0.67 (.02)	0.47 (.03)
	Cos$_{\text{ICaCE}}$	0.58 (.01)	0.64 (.01)	0.65 (.01)	0.63 (.01)	0.53 (.01)	0.39 (.00)	0.46 (.00)	0.38 (.01)	0.47 (.00)	0.39 (.03)
	NormDiff$_{\text{ICaCE}}$	0.45 (.01)	0.59 (.01)	0.58 (.00)	0.56 (.00)	0.36 (.00)	0.28 (.01)	0.42 (.01)	0.26 (.01)	0.45 (.03)	0.29 (.05)
GPT-2	L2$_{\text{ICaCE}}$	0.60 (.02)	0.60 (.02)	0.61 (.01)	0.61 (.01)	0.65 (.01)	0.43 (.01)	0.55 (.01)	0.41 (.01)	0.51 (.01)	0.41 (.04)
	Cos$_{\text{ICaCE}}$	0.59 (.01)	0.59 (.01)	0.59 (.01)	0.59 (.01)	0.52 (.00)	0.40 (.00)	0.47 (.01)	0.37 (.01)	0.46 (.00)	0.39 (.05)
	NormDiff$_{\text{ICaCE}}$	0.40 (.01)	0.40 (.01)	0.41 (.01)	0.40 (.01)	0.34 (.00)	0.24 (.01)	0.32 (.01)	0.23 (.01)	0.30 (.00)	0.27 (.05)
LSTM	L2$_{\text{ICaCE}}$	0.73 (.01)	0.73 (.01)	0.73 (.01)	0.72 (.00)	0.76 (.00)	0.49 (.00)	0.66 (.01)	0.52 (.01)	0.64 (.02)	0.54 (.01)
	Cos$_{\text{ICaCE}}$	0.64 (.01)	0.64 (.01)	0.64 (.01)	0.63 (.01)	0.57 (0.01)	0.44 (.00)	0.50 (.01)	0.45 (.01)	0.50 (.01)	0.46 (.00)
	NormDiff$_{\text{ICaCE}}$	0.50 (.01)	0.53 (.01)	0.53 (.00)	0.54 (.00)	0.41 (.00)	0.30 (.00)	0.42 (.00)	0.34 (.01)	0.41 (.01)	0.36 (.00)

Table 1: CEBaB scores measured in three different metrics on the test set for four different model architectures as a five-class sentiment classification task. Lower is better. Task performance as `Macro-F1` score is reported when applicable. Details about these evaluation metrics can be found in Section 4. Results averaged over 3 distinct seeds; standard deviations in parentheses.

embeddings. For simplicity, the intervention site for each concept has the same length. On top of these settings, we provide extensive analyses about how different intervention locations and sizes affect our evaluation results in Appendix A.5.

Following the guidance on IIT given by Geiger et al. (2021b), we train CPM$_{\text{HI}}$ with an additional multi-task objective as,

$$\mathcal{L}_{\text{Multi}} = \text{CE}(\text{MLP}(H_b^{C_i}), c) \tag{11}$$

where our probe is parameterized by a multilayer perceptron MLP, and $H_b^{C_i}$ is the value of hidden representation for the concept C_i when processing input b.

5 RESULTS

We first benchmark both variants of CPM on CEBaB based on the source of approximate counterfactual data during training Section 5.1, showing it to be state-of-the-art for CEBaB. We then investigate whether CPMs can be deployed both as predictor and explanation method at the same time (Section 5.2) and find that they can. Finally, we show that the localized representations of CPM$_{\text{HI}}$ give rise to concept-aware feature attribution methods (Section 5.3). Our supplementary materials report on detailed ablation studies and explore the potential of our methods for model debiasing.

5.1 CEBaB PERFORMANCE

Table 1 presents our main results. Both CPM$_{\text{IN}}$ and CPM$_{\text{HI}}$ beat BEST$_{\text{CEBaB}}$ in every evaluation: they are not only better than any individual model evaluated in Abraham et al. 2022, they are also better than the best model for every choice of metric and pretrained starting point. Appendix A.6 reports on ablation studies that indicate that, for CPM$_{\text{HI}}$, these results are driven primarily by the role of IIT in localizing concepts.

Both CPM$_{\text{IN}}$ and CPM$_{\text{HI}}$ also outperform all three variants of S-Learner. S-Learner is arguably the best individual model from Abraham et al. 2022, and these findings show that CPM outperforms it even where we employ the same approximate counterfactual strategies. However, it should be noted that `S-Learner` gains a little from training with human counterfactuals, which suggests that a naive incorporation of counterfactual data during training can help.

In addition, both of our methods perform on-par with `GPT-3` across all model architectures. The results for `GPT-3` highlight some interesting trade-offs. `GPT-3` shows remarkable performance with *human* counterfactuals. This suggests it can generate truthful counterfactual examples that mimic human-created one (as shown in Appendix A.7). However, `GPT-3`'s performance drops significantly when we use sampled counterfactuals, revealing that the model is highly sensitive to noisy prompt signals. In addition, the cost of using `GPT-3` probably makes it infeasible as an explainer: it is a large model that is expensive to run, and we would need to run it every time an explanation for a new example was needed. Our CPM are, by comparison, extremely compact and inexpensive to use.

		CPM$_{\text{IN}}$		**CPM$_{\text{HI}}$**	
		sampling	*human*	*sampling*	*human*
BERT	L2$_{\text{ICaCE}}$	0.63 (.01)	0.42 (.02)	0.52 (.04)	0.38 (.03)
	COS$_{\text{ICaCE}}$	0.46 (.00)	0.34 (.02)	0.45 (.01)	0.30 (.06)
	NormDiff$_{\text{ICaCE}}$	0.39 (.01)	0.23 (.01)	0.33 (.02)	0.22 (.05)
RoBERTa	L2$_{\text{ICaCE}}$	0.66 (.01)	0.40 (.01)	0.63 (.04)	0.37 (.04)
	COS$_{\text{ICaCE}}$	0.46 (.00)	0.33 (.01)	0.48 (.01)	0.29 (.04)
	NormDiff$_{\text{ICaCE}}$	0.42 (.01)	0.21 (.01)	0.42 (.05)	0.23 (.05)
GPT-2	L2$_{\text{ICaCE}}$	0.55 (.01)	0.38 (.01)	0.41 (.03)	0.36 (.04)
	COS$_{\text{ICaCE}}$	0.47 (.01)	0.37 (.01)	0.39 (.02)	0.35 (.05)
	NormDiff$_{\text{ICaCE}}$	0.32 (.01)	0.22 (.01)	0.25 (.02)	0.24 (.05)
LSTM	L2$_{\text{ICaCE}}$	0.66 (.01)	0.46 (.00)	0.41 (.01)	0.42 (.01)
	COS$_{\text{ICaCE}}$	0.50 (.00)	0.50 (.02)	0.42 (.02)	0.40 (.01)
	NormDiff$_{\text{ICaCE}}$	0.42 (.00)	0.31 (.00)	0.25 (.00)	0.28 (.02)

	Finetuned	**CPM$_{\text{IN}}$**		**CPM$_{\text{HI}}$**	
		sampling	*human*	*sampling*	*human*
BERT	0.70 (.01)	0.70 (.00)	0.70 (.01)	0.67 (.02)	0.69 (.01)
RoBERTa	0.70 (.00)	0.70 (.00)	0.71 (.01)	0.69 (.01)	0.71 (.00)
GPT-2	0.65 (.00)	0.65 (.00)	0.66 (.01)	0.67 (.01)	0.68 (.00)
LSTM	0.60 (.01)	0.60 (.01)	0.54 (.00)	0.56 (.00)	0.59 (.01)

Table 2: Task performance measured as Macro-F1 score on the test set. Results averaged over 3 distinct seeds; standard deviations in parentheses.

Table 3: Self-explanation CEBaB scores measured in three different metrics on the test set for four different model architectures as a five-class sentiment classification task. Lower is better. Results averaged over 3 distinct seeds; standard deviations in parentheses.

Models trained with human counterfactuals are significantly better than those trained with sampled counterfactuals. This shows that the performance of explanation methods depends on the quality of the approximated counterfactual training data. However, we can again consider the cost trade-offs: human counterfactuals may be expensive to create, whereas sampled counterfactuals are often naturally abundant, since they depend on having only relevant metadata for approximating the underlying causal model.

Finally, CPM$_{\text{HI}}$ and CPM$_{\text{IN}}$ achieve close performance, but CPM$_{\text{IN}}$ performs slightly better across multiple conditions. CPM$_{\text{IN}}$ is also the simpler of the two models to implement, and so these results may to speak in its favor. However, CPM$_{\text{HI}}$ arguably brings additional benefits when it comes to explainability, as we discuss in Section 5.3 below.

5.2 Self-Explanation with CPM

As outlined in Section 3, CPMs learn to mimic both the factual and counterfactual behaviors of the black-box models they are explaining. The results in Table 1 show that this procedures leads them not only to be high-quality explainers, but also to perform comparably to the black-box models they are explaining, as indicated by the Macro-F1 rows in Table 2, which show almost no difference between our models and those under BEST$_{\text{CEBaB}}$.

Can we then simply drop the black-box models and use CPMs as explainers and as task-specific models? The remaining question here is whether CPMs can explain themselves. To address this, we simply replace the black-box model $\mathcal{N}$ in Eqn. 5 with a CPM model at inference time.

Table 3 reports these results. we find that both of variants, CPM$_{\text{IN}}$ and CPM$_{\text{HI}}$, achieve better performance providing self-explanations comparing with providing explanations for another black-box model. Furthermore, CPM$_{\text{HI}}$ provides better self-explanation than CPM$_{\text{IN}}$, suggesting our interchange intervention procedure leads the model to localize concept-based information in hidden representations. This shows that CPMs may be viable as replacements for their black-box counterpart, since they provide similar task performance while providing faithful counterfactual explanations of both the black-box model and itself.

5.3 Concept-Aware Feature Attribution with CPM$_{\text{HI}}$

We have shown that CPM$_{\text{HI}}$ provides trustworthy explanations (Section 5.1). We now further investigate whether CPM$_{\text{HI}}$ learns representations that mediate the effect of different concepts. Specifically, we adapt Integrated Gradients (IG; Sundararajan et al. 2017) to visualize aggregated gradients over inputs flowing through the neurons mapped to each concept. Details of our implementation of IG can be found in Appendix A.8.

Model	Predicted	Concept	Score	Word Importance
Finetuned	*neutral*	ambiance	+0.03	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+0.11	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	+0.04	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+0.26	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
IIT	*neutral*	ambiance	−0.24	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+1.11	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−0.98	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+1.16	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
Multi-task	*neutral*	ambiance	+0.25	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+0.23	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	+0.31	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+0.16	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]

Table 4: Visualizations of word importance scores using Integrated Gradient (IG) by restricting gradients flow through corresponding intervention site of the targted concept. Target classes we consider are {*positive*, *very positive*} where summed scores are taken. Word importance score is normalized to $[-1, +1]$. -1 means the word contributes the most negatively to predicting the target class. $+1$ means the word contributes the most positively to predicting the target class. Negative word importance score is colored as red, whereas positive one is colored as green. Score represents the sum of word importance score for each concept.

In Table 4, we compare two variants of CPM_{HI} (IIT and Multi-task) with the original black-box (Finetuned) model. Specifically, we remove the multi-task objective $\mathcal{L}_{\text{Multi}}$ and the interchange intervention objective $\mathcal{L}_{\text{HI}}$ from our CPM_{HI} respectively when training these two variants. The three models have vastly different distributions of word importance scores. More importantly, IIT highlights words that are semantically related to each concept. For instance, when we restrict the gradients to flow only through the intervention site of the *noise* concept, "loud" is the word highlighted the most that contributes negatively. On the other hand, when we consider the *service* concept, words like "friendly", "waiter" are highlighted the most and contribute positively. These meaningful variances are missing for both the Finetuned model and the Multi-task model, which shows our training paradigm pushes the model to learn causally motivated representations over the course of training. We include additional results in Appendix A.8.

6 CONCLUSION

We explored the use of approximate counterfactual training data to build more robust causal explanation methods. We introduced Causal Proxy Model (CPM), a method which learns to mimic both the *factual* and *counterfactual* of a black-box model $\mathcal{N}$. Using CEBaB, a benchmark for causal concept-based explanation methods, we demonstrated that both versions of our technique (CPM_{IN} and CPM_{HI}) significantly outperform previous explanation methods. Our experimental comparisons show that this increase in explanation performance is not due to the naive incorporation of additional (counterfactual) data when training conventional explanation methods, but rather stems from the capacity of CPM models to localize causally relevant information.

Interestingly, we find that our GPT-3 based explanation method achieves results on par with our best models for human-created counterfactuals. While test-time use of GPT-3 as explanation model is both slow and expensive, we believe that GPT-3 could be deployed to supplement human-annotation efforts for counterfactual data creation.

Our results suggest that CPMs can be more than just explanation methods. They achieve factual performance on par with the model they aim to explain, and they can explain their own behavior. This paves the way to using them as deployed models that both perform tasks and offer explanations.

In addition, the causally localized representations of our CPM_{HI} variants are very intuitive, as revealed by concept-aware feature attribution techniques. We believe that causal localization techniques could play a vital role in further model explanation efforts.

REFERENCES

Eldar David Abraham, Karel D'Oosterlinck, Amir Feder, Yair Ori Gat, Atticus Geiger, Christopher Potts, Roi Reichart, and Zhengxuan Wu. Cebab: Estimating the causal effects of real-world concepts on nlp model behavior. *arXiv preprint arXiv:2205.14140*, 2022.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete Problems in AI Safety. *arXiv:1606.06565 [cs]*, 2016. URL http://arxiv.org/abs/1606.06565.

Pangbo Ban, Yifan Jiang, Tianran Liu, and Shane Steinert-Threlkeld. Testing pre-trained language models' understanding of distributivity via causal mediation analysis. *arXiv preprint arXiv:2209.04761*, 2022.

Alexander Binder, Grégoire Montavon, Sebastian Lapuschkin, Klaus-Robert Müller, and Wojciech Samek. Layer-wise relevance propagation for neural networks with local renormalization layers. In *International Conference on Artificial Neural Networks*, pp. 63–71. Springer, 2016.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language Models are Few-Shot Learners. *arXiv:2005.14165 [cs]*, July 2020. URL http://arxiv.org/abs/2005.14165. arXiv: 2005.14165 version: 4.

Lars Buitinck, Gilles Louppe, Mathieu Blondel, Fabian Pedregosa, Andreas Mueller, Olivier Grisel, Vlad Niculae, Peter Prettenhofer, Alexandre Gramfort, Jaques Grobler, Robert Layton, Jake VanderPlas, Arnaud Joly, Brian Holt, and Gaël Varoquaux. API design for machine learning software: experiences from the scikit-learn project. In *ECML PKDD Workshop: Languages for Data Mining and Machine Learning*, pp. 108–122, 2013.

Kevin Clark, Urvashi Khandelwal, Omer Levy, and Christopher D. Manning. What does BERT look at? An analysis of BERT's attention. In *Proceedings of the 2019 ACL Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 276–286, Florence, Italy, August 2019. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W19-4828.

Alexis Conneau, German Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. What you can cram into a single $&!#* vector: Probing sentence embeddings for linguistic properties. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2126–2136, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1198. URL https://www.aclweb.org/anthology/P18-1198.

Nicola De Cao, Leon Schmid, Dieuwke Hupkes, and Ivan Titov. Sparse interventions in language models with differentiable masking. *arXiv preprint arXiv:2112.06837*, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://www.aclweb.org/anthology/N19-1423.

Upol Ehsan, Q Vera Liao, Michael Muller, Mark O Riedl, and Justin D Weisz. Expanding explainability: Towards social transparency in ai systems. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, pp. 1–19, 2021.

Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175, 2021.

Amir Feder, Nadav Oved, Uri Shalit, and Roi Reichart. CausaLM: Causal model explanation through counterfactual language models. *Computational Linguistics*, 47(2):333–386, June 2021. doi: 10.1162/coli_a_00404. URL https://aclanthology.org/2021.cl-2.13.

Atticus Geiger, Kyle Richardson, and Christopher Potts. Neural natural language inference models partially embed theories of lexical entailment and negation. In *Proceedings of the Third BlackboxNLP Workshop on Analyzing and Interpreting Neural Networks for NLP*, pp. 163–173, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.blackboxnlp-1.16. URL https://aclanthology.org/2020.blackboxnlp-1.16.

Atticus Geiger, Hanson Lu, Thomas Icard, and Christopher Potts. Causal abstractions of neural networks. *Advances in Neural Information Processing Systems*, 34, 2021a.

Atticus Geiger, Zhengxuan Wu, Hanson Lu, Josh Rozner, Elisa Kreiss, Thomas Icard, Noah D. Goodman, and Christopher Potts. Inducing causal structure for interpretable neural networks. arXiv:2112.00826, 2021b. URL https://arxiv.org/abs/2112.00826.

Bryce Goodman and Seth Flaxman. European Union regulations on algorithmic decision-making and a "right to explanation". *AI Magazine*, 38(3):50–57, October 2017. ISSN 2371-9621, 0738-4602. doi: 10.1609/aimag.v38i3.2741. URL http://arxiv.org/abs/1606.08813. arXiv: 1606.08813.

Yash Goyal, Ziyan Wu, Jan Ernst, Dhruv Batra, Devi Parikh, and Stefan Lee. Counterfactual visual explanations. In *International Conference on Machine Learning*, pp. 2376–2384. PMLR, 2019.

Riccardo Guidotti, Anna Monreale, Salvatore Ruggieri, Franco Turini, Fosca Giannotti, and Dino Pedreschi. A survey of methods for explaining black box models. *ACM computing surveys (CSUR)*, 51(5):1–42, 2018.

Moritz Hardt, Eric Price, Eric Price, and Nati Srebro. Equality of Opportunity in Supervised Learning. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/9d2682367c3935defcb1f9e247a97c0d-Paper.pdf.

Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8): 1735–1780, 1997.

Paul W Holland. Statistics and causal inference. *Journal of the American statistical Association*, 81 (396):945–960, 1986.

Alon Jacovi and Yoav Goldberg. Towards faithfully interpretable NLP systems: How should we define and evaluate faithfulness? In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4198–4205, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.386. URL https://aclanthology.org/2020.acl-main.386.

Maurice Jakesch, Megan French, Xiao Ma, Jeffrey T Hancock, and Mor Naaman. Ai-mediated communication: How the perception that profile text was written by ai affects trustworthiness. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems*, pp. 1–13, 2019.

Been Kim. *Interactive and interpretable machine learning models for human machine collaboration*. PhD thesis, Massachusetts Institute of Technology, 2015.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, and Rory Sayres. Interpretability Beyond Feature Attribution: Quantitative Testing with Concept Activation Vectors (TCAV). In *International Conference on Machine Learning*, pp. 2668–2677. PMLR, July 2018. URL http://proceedings.mlr.press/v80/kim18d.html. ISSN: 2640-3498.

Jon Kleinberg, Sendhil Mullainathan, and Manish Raghavan. Inherent trade-offs in the fair determination of risk scores. In Christos H. Papadimitriou (ed.), *8th Innovations in Theoretical Computer Science Conference (ITCS 2017)*, volume 67 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pp. 43:1–43:23. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, 2017. ISBN 978-3-95977-029-3. doi: 10.4230/LIPIcs.ITCS.2017.43. URL http://drops.dagstuhl.de/opus/volltexte/2017/8156.

Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In *International Conference on Machine Learning*, pp. 5338–5348. PMLR, 2020.

Sören R Künzel, Jasjeet S Sekhon, Peter J Bickel, and Bin Yu. Metalearners for estimating heterogeneous treatment effects using machine learning. *Proceedings of the national academy of sciences*, 116(10):4156–4165, 2019.

Zachary C. Lipton. The mythos of model interpretability. *Communications of the ACM*, 61(10): 36–43, September 2018. ISSN 0001-0782. doi: 10.1145/3233231. URL https://doi.org/10.1145/3233231.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. RoBERTa: A Robustly Optimized BERT Pretraining Approach. *arXiv:1907.11692 [cs]*, July 2019. URL http://arxiv.org/abs/1907.11692. arXiv: 1907.11692.

Christopher D. Manning, Kevin Clark, John Hewitt, Urvashi Khandelwal, and Omer Levy. Emergent linguistic structure in artificial neural networks trained by self-supervision. *Proceedings of the National Academy of Sciences*, 117(48):30046–30054, 2020. ISSN 0027-8424. doi: 10.1073/pnas.1907367117. URL https://www.pnas.org/content/117/48/30046.

Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A survey on bias and fairness in machine learning. *ACM Computing Surveys (CSUR)*, 54(6):1–35, 2021.

Christoph Molnar. *Interpretable machine learning*. Lulu. com, 2020.

Clemens Otte. Safe and Interpretable Machine Learning: A Methodological Review. In Christian Moewes and Andreas Nürnberger (eds.), *Computational Intelligence in Intelligent Data Analysis*, Studies in Computational Intelligence, pp. 111–122, Berlin, Heidelberg, 2013. Springer. ISBN 978-3-642-32378-2. doi: 10.1007/978-3-642-32378-2_8.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

Judea Pearl. The limitations of opaque learning machines. *Possible minds: twenty-five ways of looking at AI*, pp. 13–19, 2019.

Jeffrey Pennington, Richard Socher, and Christopher Manning. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1532–1543, Doha, Qatar, October 2014. Association for Computational Linguistics. doi: 10.3115/v1/D14-1162. URL https://aclanthology.org/D14-1162.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019. URL https://cdn.openai.com/better-language-models/language_models_are_unsupervised_multitask_learners.pdf.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null It Out: Guarding Protected Attributes by Iterative Nullspace Projection. *arXiv:2004.07667 [cs]*, April 2020. URL http://arxiv.org/abs/2004.07667. arXiv: 2004.07667.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "Why Should I Trust You?": Explaining the Predictions of Any Classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1135–1144, San Francisco California USA, August 2016. ACM. ISBN 978-1-4503-4232-2. doi: 10.1145/2939672.2939778. URL `https://dl.acm.org/doi/10.1145/2939672.2939778`.

Naomi Saphra and Adam Lopez. Understanding learning dynamics of language models with SVCCA. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 3257–3267, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1329. URL `https://www.aclweb.org/anthology/N19-1329`.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *International conference on machine learning*, pp. 3145–3153. PMLR, 2017.

Paul Soulos, R. Thomas McCoy, Tal Linzen, and Paul Smolensky. Discovering the compositional structure of vector representations with role learning networks. In *Proceedings of the Third BlackboxNLP Workshop on Analyzing and Interpreting Neural Networks for NLP*, pp. 238–254, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020. blackboxnlp-1.23. URL `https://aclanthology.org/2020.blackboxnlp-1.23`.

Jost Springenberg, Alexey Dosovitskiy, Thomas Brox, and Martin Riedmiller. Striving for simplicity: The all convolutional net. *CoRR*, 12 2014.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 3319–3328. JMLR.org, 2017.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. BERT rediscovers the classical NLP pipeline. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4593–4601, Florence, Italy, July 2019. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/P19-1452`.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5998–6008. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7181-attention-is-all-you-need.pdf`.

Sahil Verma, John Dickerson, and Keegan Hines. Counterfactual explanations for machine learning: A review. *arXiv preprint arXiv:2010.10596*, 2020.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart M. Shieber. Investigating gender bias in language models using causal mediation analysis. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/92650b2e92217715fe312e6fa7b90d82-Abstract.html`.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

Tongshuang Wu, Marco Tulio Ribeiro, Jeffrey Heer, and Daniel S Weld. Polyjuice: Generating counterfactuals for explaining, evaluating, and improving models. *arXiv preprint arXiv:2101.00288*, 2021.

Chih-Kuan Yeh, Been Kim, Sercan Arik, Chun-Liang Li, Tomas Pfister, and Pradeep Ravikumar. On completeness-aware concept-based explanations in deep neural networks. *Advances in Neural Information Processing Systems*, 33:20554–20565, 2020.

Matthew D. Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In David Fleet, Tomas Pajdla, Bernt Schiele, and Tinne Tuytelaars (eds.), *Computer Vision – ECCV 2014*, pp. 818–833, Cham, 2014. Springer International Publishing.

A APPENDIX

A.1 CEBaB DATASET STATISTICS

Table 5 shows dataset statistics of CEBaB. The variants of CEBaB we consider only impact the train split. The top panel shows the amount of observational samples and edits introduced in the CEBaB paper. The bottom panel shows our *paired* versions, where we create approximate counterfactual pairs. We explore two variants of approximate counterfactuals, *human* and *sampled* counterfactuals as in Section 4.1. The *human* setting considers all pairs made possible by using *all* data. The *sampling* setting considers pairs sampled from only the *observational* data, as discussed in Section A.2.

Dataset	# train	# dev	# test
CEBaB (*observational*)	1,755	1,673	1,689
CEBaB (*all*)	11,728	1,673	1,689
CEBaB (*paired*, *human*)	19,684	3,898	3,958
CEBaB (*paired*, *sampling*)	74,574	3,898	3,958

Table 5: Dataset Statistics

A.2 TYPES OF APPROXIMATED COUNTERFACTUAL PAIRS

Our approximated counterfactual training data comes in paired sentences of (*original sentence*, *approximate counterfactual sentence*). The approximate counterfactuals differs from their original counterparts in only one concept value. We consider approximate counterfactual pairs to be symmetric, we use both (*original sentence*, *approximate counterfactual sentence*) and (*approximate counterfactual sentence*, *original sentence*) as training pairs.

Human-created Counterfactuals CEBaB contains multiple counterfactual sentences for each original review. To achieve this, the dataset creators asked annotators to edit the original sentence to achieve a specified goal (e.g., 'change the evaluation of the restaurant's food to negative'). These originals and corresponding edits form our *human* pairs.

Metadata-sampled Counterfactuals Human-created counterfactuals are not always available. With CEBaB, we simulate a second type of approximated counterfactuals by using metadata-guided heuristics. For a given *original sentence*, we sample a counterfactual from the train set by matching concept labels while allowing only one label to be changed.

During training, we also consider *null effect pairs* in our *sampling* setup. These pairs resemble cases where our approximate counterfactual sentence is identical to the original sentence. When training our models on these pairs, we expect our models to predict the same counterfactual and factual output.

A.3 TRAINING REGIMES

CPM$_{\text{IN}}$ To train CPM$_{\text{IN}}$, we use the same model architecture as $\mathcal{N}$, and initialize it with the model weights using weights from $\mathcal{N}$. The maximum number of training epochs is set to 30 with a learning rate of $5e^{-5}$ and an effective batch size of 128. The learning rate linearly decays to zero over the 30 training epochs. We employ an early stopping strategy for COS$_{\text{ICaCE}}$ over the dev set for an interval of 50 steps with an early stopping patience set to 20. We set the max sequence length to 128 and the dropout rate to 0.1. We take a weighted sum of two objectives as the loss term for training CPM$_{\text{HI}}$. Specifically, we use $[w_{\text{Mimic}}, w_{\text{IN}}] = [1.0, 3.0]$.

CPM$_{\text{HI}}$ To train CPM$_{\text{HI}}$, we use the same model architecture as $\mathcal{N}$, and initialize it with the model weights using weights from $\mathcal{N}$. The maximum number of training epochs is set to 30 with a learning rate of $8e^{-5}$ and an effective batch size of 256. We use a higher learning rate of 0.001 for the LSTM

Figure 2: CEBaB scores for different intervention site locations and sizes for CPM$_{\text{HI}}$. The scores are measured in three different metrics on the test set for four different model architectures as a five-class sentiment classification task. Task performance as `Macro-F1` score is reported when applicable. Results averaged over 3 distict seeds; shaded areas outline $\pm$ SD.

		Approx (Abraham et al., 2022)	S-Learner (Künzel et al., 2019)	INLP (Ravfogel et al., 2020)
BERT	L2$_{\text{ICaCE}}$	0.81 ($\pm$ 0.01)	0.74 ($\pm$ 0.02)	0.80 ($\pm$ 0.02)
	COS$_{\text{ICaCE}}$	0.61 ($\pm$ 0.01)	0.63 ($\pm$ 0.01)	0.59 ($\pm$ 0.03)
	NormDiff$_{\text{ICaCE}}$	0.44 ($\pm$ 0.01)	0.54 ($\pm$ 0.02)	0.73 ($\pm$ 0.02)
RoBERTa	L2$_{\text{ICaCE}}$	0.83 ($\pm$ 0.01)	0.78 ($\pm$ 0.01)	0.84 ($\pm$ 0.01)
	COS$_{\text{ICaCE}}$	0.60 ($\pm$ 0.01)	0.64 ($\pm$ 0.01)	0.58 ($\pm$ 0.01)
	NormDiff$_{\text{ICaCE}}$	0.45 ($\pm$ 0.00)	0.59 ($\pm$ 0.01)	0.81 ($\pm$ 0.01)
GPT-2	L2$_{\text{ICaCE}}$	0.72 ($\pm$ 0.02)	0.60 ($\pm$ 0.02)	0.72 ($\pm$ 0.01)
	COS$_{\text{ICaCE}}$	0.59 ($\pm$ 0.01)	0.59 ($\pm$ 0.01)	1.00 ($\pm$ 0.00)
	NormDiff$_{\text{ICaCE}}$	0.41 ($\pm$ 0.01)	0.40 ($\pm$ 0.01)	0.58 ($\pm$ 0.03)
LSTM	L2$_{\text{ICaCE}}$	0.86 ($\pm$ 0.01)	0.73 ($\pm$ 0.01)	0.79 ($\pm$ 0.01)
	COS$_{\text{ICaCE}}$	0.64 ($\pm$ 0.01)	0.64 ($\pm$ 0.01)	0.74 ($\pm$ 0.02)
	NormDiff$_{\text{ICaCE}}$	0.50 ($\pm$ 0.01)	0.53 ($\pm$ 0.01)	0.60 ($\pm$ 0.01)

Table 6: CEBaB scores measured in three different metrics on the test set for four different model architectures as a five-class sentiment classification task. Results are adapted from Abraham et al. (2022). Lower is better. Results are aggregated over all aspects and all directional concept label changes. Details about these evaluation metrics can be found in Section 4. Results averaged over 3 distinct seeds; standard deviations in parentheses.

model as it enables quicker convergence. The learning rate linearly decays to zero over the 30 training epochs. We employ an early stopping strategy for COS$_{\text{ICaCE}}$ over the dev set for an interval of 50 steps with an early stopping patience set to 20. We tune down the interval to 10 for `GPT-2` to allow a practical run-time for training. We set the max sequence length to 128 and the dropout rate to 0.1. We take a weighted sum of three objectives as the loss term for training CPM$_{\text{HI}}$. Specifically, we use $[w_{\text{Mimic}}, w_{\text{Multi}}, w_{\text{HI}}] = [1.0, 1.0, 3.0]$. In Appendix A.6, we conduct a set of ablation studies to show individual contribution from each objective.

Our models are all implemented in `PyTorch` (Paszke et al., 2019) and using the `HuggingFace` library (Wolf et al., 2019). To foster reproducibility, we will release our code repository and model artifacts to the public.

A.4 ADDITIONAL BASELINE RESULTS

Table 6 shows baselines adapted from Abraham et al. (2022), which shows the state-of-the-art explanation methods for the CEBaB benchmark. We report the best scores across these explanation methods in Table 1. These baselines are trained without using counterfactual data. Thus, we build additional baselines that use counterfactual data as shown in Table 7. `S-Learner` is selected as the best performing models and included in Table 1 for comparisons.

		ApproxCounterfactual		ATEExplainer		CaCEExplainer		Random	
		sampling	*human*	*sampling*	*human*	*sampling*	*human*	*sampling*	*human*
BERT	$L2_{\text{ICaCE}}$	0.81 ($\pm$ 0.01)	0.79 ($\pm$ 0.02)	0.81 ($\pm$ 0.02)	0.81 ($\pm$ 0.02)	0.81 ($\pm$ 0.02)	0.80 ($\pm$ 0.02)	0.84 ($\pm$ 0.02)	0.84 ($\pm$ 0.01)
	COS_{ICaCE}	0.60 ($\pm$ 0.00)	0.56 ($\pm$ 0.01)	0.72 ($\pm$ 0.01)	0.69 ($\pm$ 0.01)	0.72 ($\pm$ 0.01)	0.69 ($\pm$ 0.01)	0.53 ($\pm$ 0.00)	0.53 ($\pm$ 0.01)
	$NormDiff_{\text{ICaCE}}$	0.44 ($\pm$ 0.01)	0.43 ($\pm$ 0.01)	0.62 ($\pm$ 0.02)	0.62 ($\pm$ 0.02)	0.62 ($\pm$ 0.02)	0.64 ($\pm$ 0.02)	0.55 ($\pm$ 0.02)	0.54 ($\pm$ 0.02)
RoBERTa	$L2_{\text{ICaCE}}$	0.83 ($\pm$ 0.01)	0.81 ($\pm$ 0.01)	0.85 ($\pm$ 0.00)	0.85 ($\pm$ 0.00)	0.85 ($\pm$ 0.00)	0.84 ($\pm$ 0.00)	0.87 ($\pm$ 0.00)	0.87 ($\pm$ 0.00)
	COS_{ICaCE}	0.61 ($\pm$ 0.01)	0.57 ($\pm$ 0.01)	0.73 ($\pm$ 0.00)	0.70 ($\pm$ 0.00)	0.73 ($\pm$ 0.01)	0.70 ($\pm$ 0.00)	0.53 ($\pm$ 0.00)	0.53 ($\pm$ 0.00)
	$NormDiff_{\text{ICaCE}}$	0.46 ($\pm$ 0.01)	0.44 ($\pm$ 0.01)	0.67 ($\pm$ 0.00)	0.67 ($\pm$ 0.00)	0.67 ($\pm$ 0.00)	0.68 ($\pm$ 0.00)	0.58 ($\pm$ 0.00)	0.59 ($\pm$ 0.00)
GPT-2	$L2_{\text{ICaCE}}$	0.72 ($\pm$ 0.02)	0.72 ($\pm$ 0.01)	0.69 ($\pm$ 0.01)	0.68 ($\pm$ 0.01)	0.68 ($\pm$ 0.01)	0.68 ($\pm$ 0.01)	0.76 ($\pm$ 0.00)	0.76 ($\pm$ 0.00)
	COS_{ICaCE}	0.59 ($\pm$ 0.01)	0.57 ($\pm$ 0.00)	0.67 ($\pm$ 0.01)	0.66 ($\pm$ 0.01)	0.67 ($\pm$ 0.01)	0.65 ($\pm$ 0.00)	0.56 ($\pm$ 0.00)	0.56 ($\pm$ 0.00)
	$NormDiff_{\text{ICaCE}}$	0.40 ($\pm$ 0.01)	0.40 ($\pm$ 0.00)	0.48 ($\pm$ 0.01)	0.49 ($\pm$ 0.01)	0.49 ($\pm$ 0.01)	0.50 ($\pm$ 0.01)	0.47 ($\pm$ 0.00)	0.47 ($\pm$ 0.01)
LSTM	$L2_{\text{ICaCE}}$	0.87 ($\pm$ 0.00)	0.85 ($\pm$ 0.01)	0.78 ($\pm$ 0.00)	0.78 ($\pm$ 0.00)	0.78 ($\pm$ 0.00)	0.76 ($\pm$ 0.00)	0.85 ($\pm$ 0.00)	0.84 ($\pm$ 0.00)
	COS_{ICaCE}	0.65 ($\pm$ 0.00)	0.61 ($\pm$ 0.00)	0.71 ($\pm$ 0.00)	0.69 ($\pm$ 0.00)	0.71 ($\pm$ 0.00)	0.68 ($\pm$ 0.00)	0.57 ($\pm$ 0.00)	0.56 ($\pm$ 0.00)
	$NormDiff_{\text{ICaCE}}$	0.50 ($\pm$ 0.00)	0.49 ($\pm$ 0.00)	0.59 ($\pm$ 0.00)	0.59 ($\pm$ 0.00)	0.59 ($\pm$ 0.00)	0.61 ($\pm$ 0.00)	0.55 ($\pm$ 0.00)	0.55 ($\pm$ 0.00)

Table 7: CEBaB scores for additional baselines we considered. CEBaB scores are measured in three different metrics on the test set for four different model architectures as a five-class sentiment classification task. Lower is better. Details about these evaluation metrics can be found in Section 4. Results averaged over 3 distinct seeds; standard deviations in parentheses.

A.5 Intervention Site Location and Size

Previous work shows that neurons in different layers and groups can encode different high-level concepts (Vig et al., 2020; Koh et al., 2020). CPM_{HI} pushes concept-related information to localize at the targeted intervention site (the aligned neural representations for each concept). In this section, we investigate how the location and the size of the intervention site impact CPM_{HI} performance. We use the optimal location and size found in this study for other results presented in this paper.

Location For Transformer-based models, we vary the location of the intervention site by intervening on the "[CLS]" token embedding layer l. Specifically, we set $l = \{2, 4, 6, 8, 10, 12\}$. We skip this experiment for non-Transformer-based model (i.e., LSTM) since it only contains a single sentence embedding.

As shown in the top panel of Figure 2, intervention location significantly affects CPM_{HI} performance. Our results show that layer 10 for BERT, layer 8 for RoBERTa, and layer 12 for GPT-2 lead to the best performance. This suggests layers have different efficacy in terms of information localization. Our results also show that intervening with deeper layers tends to provide better performance. However, for both BERT and RoBERTa, intervening on the last layer results in a slightly worse performance comparing to earlier layers. This suggests that leaving Transformer blocks after the intervention site helps localized information to be processed by the neural network.

Size For Transformer-based models, we change the size of the intervention site d_c for each concept. Specifically, we set $d_c = \{1, 16, 64, 128, 192\}$. For instance when $d_c = 1$, we use a single dimension of the "[CLS]" token embedding to represent each concept, starting from the first dimension of the vector. For non-transformer-based model (i.e., LSTM), we intervene on the attention-gated sentence embedding whose dimension size is set to 300. Accordingly, we set $d_c = \{1, 16, 64, 75\}$.

As shown in Figure 2, larger intervention site leads to better performance for all Transformer-based models. For LSTM, we find that the optimal size is the second largest one instead. On the other hand, our results suggest that the performance gain from the increase of size diminishes as we increase the size for all model architectures.

A.6 Ablation of Training Objectives

Geiger et al. (2021b) show that training with a multi-task objective helps IIT to improve generalizability. In this experiment, we aim to investigate whether the multi-task objective we added for CPM_{HI} plays an important role in achieving good performance. Specifically, we conduct two ablation studies: removing the multi-task objective by setting $w_{\text{Multi}} = 0.0$, and removing the IIT objective by setting $w_{\text{IIT}} = 0.0$.

Table 8 shows our results, which demonstrate that the IIT objective is the main factor that drives CPM_{HI} performance. Our results also suggest that multi-task objective brings relatively small but consistent performance gains. Overall, our findings corroborate those of Geiger et al. (2021b) and provide concrete evidence that the combination of two objectives always results in the best-performing explanation methods across all model architectures.

	Models	L2_{ICaCE}	$\text{COS}_{\text{ICaCE}}$	$\text{NormDiff}_{\text{ICaCE}}$	Macro-F1
	CPM_{HI}	0.45 (± 0.02)	0.36 (± 0.03)	0.27 (± 0.04)	0.69 (± 0.01)
	$-\mathcal{L}_{\text{Multi}}$	0.47 (± 0.04)	0.38 (± 0.04)	0.30 (± 0.07)	0.69 (± 0.01)
BERT	$-\mathcal{L}_{\text{HI}}$	0.79 (± 0.02)	0.60 (± 0.03)	0.64 (± 0.02)	0.60 (± 0.08)
	$+$ *random init*	0.81 (± 0.02)	0.52 (± 0.00)	0.55 (± 0.02)	0.08 (± 0.02)
	$+$ *no training*	0.80 (± 0.02)	0.86 (± 0.04)	0.76 (± 0.02)	0.70 (± 0.01)
	CPM_{HI}	0.47 (± 0.03)	0.39 (± 0.03)	0.29 (± 0.05)	0.71 (± 0.00)
	$-\mathcal{L}_{\text{Multi}}$	0.49 (± 0.05)	0.41 (± 0.05)	0.32 (± 0.06)	0.70 (± 0.00)
RoBERTa	$-\mathcal{L}_{\text{HI}}$	0.81 (± 0.00)	0.53 (± 0.01)	0.63 (± 0.01)	0.39 (± 0.06)
	$+$ *random init*	0.85 (± 0.00)	0.51 (± 0.00)	0.59 (± 0.01)	0.06 (± 0.00)
	$+$ *no training*	0.84 (± 0.01)	0.93 (± 0.05)	0.83 (± 0.00)	0.70 (± 0.00)
	CPM_{HI}	0.41 (± 0.04)	0.39 (± 0.05)	0.27 (± 0.05)	0.68 (± 0.00)
	$-\mathcal{L}_{\text{Multi}}$	0.43 (± 0.03)	0.41 (± 0.05)	0.29 (± 0.04)	0.67 (± 0.00)
GPT-2	$-\mathcal{L}_{\text{HI}}$	0.66 (± 0.01)	0.58 (± 0.04)	0.49 (± 0.01)	0.58 (± 0.04)
	$+$ *random init*	0.73 (± 0.00)	0.54 (± 0.00)	0.47 (± 0.01)	0.16 (± 0.00)
	$+$ *no training*	0.65 (± 0.00)	0.61 (± 0.00)	0.57 (± 0.02)	0.65 (± 0.00)
	CPM_{HI}	0.54 (± 0.01)	0.46 (± 0.01)	0.36 (± 0.00)	0.59 (± 0.01)
	$-\mathcal{L}_{\text{Multi}}$	0.56 (± 0.02)	0.47 (± 0.02)	0.41 (± 0.02)	0.59 (± 0.01)
LSTM	$-\mathcal{L}_{\text{HI}}$	0.73 (± 0.00)	0.64 (± 0.02)	0.59 (± 0.00)	0.59 (± 0.01)
	$+$ *random init*	0.82 (± 0.00)	0.55 (± 0.00)	0.55 (± 0.00)	0.13 (± 0.04)
	$+$ *no training*	0.73 (± 0.01)	0.74 (± 0.00)	0.59 (± 0.01)	0.60 (± 0.01)

Table 8: Ablation study of our CPM_{HI} method. CEBaB scores measured in three different metrics on the test set for four different model architectures as a five-class sentiment classification task. Lower is better. Task performance as `Macro-F1` score is reported when applicable. Results averaged over 3 distinct seeds; standard deviations in parentheses.

Additionally, we explore two baselines for CPM_{HI}. Firstly, we randomly initialize the weights of CPM_{HI}. Secondly, we take the original black-box model as our CPM_{HI}. Compared to theresults in Table 1, these two baselines fail catastrophically, suggesting the importance of our IIT paradigm.

A.7 GPT-3 GENERATION PROCESS

We use the 175B parameter `davinci` GPT-3 model (Brown et al., 2020) as a few-shot learner to generate approximate counterfactual data. Let $x_{u,v}$ be a review text with an original value c for the mediating concept C_i and an overall review sentiment y (e.g., a restaurant review which is *negative* about the *service*, and felt *neutral* about their overall dining experience), and let c' be the target value of C_i, for which we would like to create a counterfactual review (e.g., change the text to become *positive* about the mediating concept *service*). In order to train GPT-3 as an n-shot learner, we sample $n = 6$ example pairs of original reviews and human-created counterfactual reviews $(x_{u,v}, \tilde{x}_{u,v}^{C_i \leftarrow c'})$, where the original review has the same original value c for C_i and overall sentiment y, and the counterfactual review has the target value c' for C_i. After training the GPT-3 model with the n (original review, counterfactual review) pairs, we prompt the model with the original review $x_{u,v}$. We then collect the text completed by GPT-3 as the GPT-3 counterfactual review. An example for this n-shot prompt and completion is in Figure 3.

Additionally, we add an initial prompt in the form of "Make the following restaurant reviews include c' mentions of C_j.", where c' is expressed as one of {"POSITIVE", "NEGATIVE", "NOT" } ("NOT" corresponds to making the review be unknown regarding the concept C_j) and C_j as one of {"AMBIANCE", "FOOD", "NOISE", "SERVICE"}. We sample using a temperature of 0.9, without any frequency or presence penalties (since we expect the counterfactual review to be similar to the original review). In preliminary experimentation, we found that capitalizing the mediating concept and target value results and inserting line breaks between examples made for better completions, although there is room for future research in this area.

We used the OpenAI API to access GPT-3. At the current price rate of \$0.02 per 1K tokens, the total cost of creating an $n = 6$-shot prompt for the CeBAB test set (around 4k examples) was around \$50.

A.8 INTEGRATED GRADIENTS

We adapt the Integrated Gradients (IG) method of Sundararajan et al. (2017) to qualitatively assess whether CPM_{HI} learned explainable representations of mediated concepts at its intervention site. The IG algorithm computes the average gradient from the model output to its input by incrementally interpolating from a "blank" input x' (consisting only of "[PAD]" tokens) to the original input x.

```
Make the following restaurant reviews include POSITIVE mentions of SERVICE.

Original: I had two casual dinners at State & Lake and three lunches. The
food was great but the service was lacking. Everything was delicious. The
interior is questionable, but not intrusive.

POSITIVE mentions of SERVICE: I had two casual dinners at State & Lake and
three lunches. The food and the service were always great. Everything was
delicious. The interior is questionable, but not intrusive.

Original: Food was excellent, but the service was not very attentive. Noise
level was extremely high due to close proximity of tables and poor acoustics.

POSITIVE mentions of SERVICE: Food and service was excellent. Noise level
was extremely high due to close proximity of tables and poor acoustics.

Original: Great food, poor and very snobbish service.

POSITIVE mentions of SERVICE: Great food, very good service.

Original: My dining experince was excellent! However, the server was not nice.

POSITIVE mentions of SERVICE: My dining experince was excellent!

Original: Hae been here a few times and it is just okay - Entrees and wine
list a bit pricey for what it is, inattentive staff.

POSITIVE mentions of SERVICE: Hae been here a few times and it is just okay
- Entrees and wine list a bit pricey for what it is. Food comes out on time.

Original: Tables fairly close together, mushroom appetiser very good, pork
entree fair, chicken good. The service was terrible.

POSITIVE mentions of SERVICE: Tables fairly close together, mushroom
appetiser very good, pork entree fair, chicken good. The service was great
however.

Original: Service was very poor with the server unresponsive and misinformed
on all requests. The food was very good with a good selection of entrees.
The ambiance was romantic with a quiet excellence.

POSITIVE mentions of SERVICE: Service was very good with the server attentive
and responsive on all requests. The food was very good with a good selection
of entrees. The ambiance was romantic with a quiet excellence.
```

Figure 3: Example GPT-3 prompt (gray) and GPT-3 completion (bold). Note that all original examples convey the same sentiment towards service (c = negative) and same overall sentiment (y = neutral), and that the counterfactual examples are all edited such that the sentiment towards service is the same (c' = positive).

Eqn. 12 is the integrated gradients equation originally proposed in Sundararajan et al. (2017), applied to a CPM model $\mathcal{P}$ on input x.

$$\text{IntegratedGrads}_i(x) = (x_i - x_i') \cdot \int_{\alpha=0}^{1} \frac{\partial \mathcal{P}(x' + \alpha \cdot (x - x'))}{\partial x_i} \partial \alpha \tag{12}$$

Where $\frac{\partial \mathcal{P}(x)}{\partial x_i}$ is the derivative of $\mathcal{P}$ on the ith dimension of x.

Model	Predicted	Concept	Score	Word Importance
Finetuned	*neutral*	ambiance	+0.03	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+0.11	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	+0.04	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+0.26	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
CPMHI	*neutral*	ambiance	−0.61	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	−0.88	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−1.34	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+1.75	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]

Table 9: Visualizations of word importance scores using Integrated Gradient (IG) by restricting gradients flow through corresponding intervention site of the targted concept. Target classes we consider are {*positive*, *very positive*} where summed scores are taken. Word importance score is normalized to $[-1, +1]$. -1 means the word contributes the most negatively to predicting the target class. $+1$ means the word contributes the most positively to predicting the target class. Negative word importance score is colored as red, whereas positive one is colored as green. Score represents the sum of word importance score for each concept.

In our implementation of IG, we wish to show the per-token attribution of input x on the model's final output $\mathcal{P}(x)$, *mediated by* the hidden representation of a concept in $\mathcal{P}$. That is, we'd like to ask, "What is the effect of the word 'delicious' in the input on the model's output, when we restrict our focus only on the model's representation of the concept *food*?"

To answer this question, we compute the gradient of the model output $\mathcal{P}(x)$ with respect to the input x, but restricting the gradient to flow through the intervention site for a particular concept. This allows us to capture the per-token attribution of the model's final output (i.e. whether particular words contributed to a *positive*, *negative*, or *neutral* sentiment prediction), mediated by the concept that is represented by the specified intervention site. For example, in Table 4, we can see that "declicious" has a positive attribution to the output of the model, when we focus on its representation of the concept *food*.

Formally, consider a trained CPM model $\mathcal{P}$, an input x and mediating concept C_i. Let H^{C_i} be the activation of $\mathcal{P}$, when run on x, at the intervention site for C_i – meaning that H^{C_i} should consist of the model's hidden representation for the concept C_i in its computation. We define the gradient of $\mathcal{P}(x)$ along dimension i *mediated by* C_i as

$$\frac{\partial \mathcal{P}(x)}{\partial x_i} \text{ mediated by } C_i = \frac{\partial \mathcal{P}(x)}{\partial H^{C_i}} \cdot \frac{\partial H^{C_i}}{\partial x_i}. \tag{13}$$

Note that if we were to sum $\frac{\partial \mathcal{P}(x)}{\partial x_i}$ mediated by each concept C_i, we would get the whole derivative of $\mathcal{P}(x)$ with respect to x. Hence, Eqn. 13 restricts the gradient to only flow through the hidden representation of the concept along which we'd like to interpret our model.

We apply Eqn. 13 in order to compute the gradient $\frac{\partial \mathcal{P}(x)}{\partial x_i}$ in the integrated gradients formula, Eqn. 12. We implement our IG method using `CaptumAI` library.[4] We use the default parameters for our runs with number of iterations set to 50, and we set the integral method as `gausslegendre`. We set the `multiply-by-inputs` flag to `True`.

Table 9 shows an example attribution using IG on CPMHI supplied with additional ablation studies on our training objectives.

A.9 MODEL DEBIASING

Being able to accurately predict outputs for counterfactual input enables explanation methods to faithfully debias desired concept. For instance, with CEBaB, debiasing a concept (e.g., "food") is equivalent to estimating the causal effect when we remove a concept from that concept from the input, or when we set the concept label for a concept to be "unknown". In this section, we briefly study the extent to whcih our method can function as a debiasing method. To debias a concept, we enforce

---

[4]`https://captum.ai/`

the sampled source input s as in Eqn. 3 to have *unknown* as its concept label for the concept to be debiased.

To show our methods can faithfully debias a targeted concept, we evaluate the correlations between the predicted overall sentiment label for sentences and the concept labels for each concept. Without any debiasing technique, we expect concept labels to be highly correlated with the overall sentiment label (e.g., if *food* is positive, it is more likely that the overall sentiment is positive). We use CPM_{HI} trained for the BERT model architecture as an example, and use examples in the test set.

Figure 4 shows correlation plots for the original Finetuned model as well as CPM_{HI}. As expected, the correlation of the *food* concept is weakness through the debiasing pipeline by 57.50%. Our results also suggest that correlations of other concepts are affected which suggest for some future research direction to minimize the impact of the debiasing pipeline on irrelevant concepts. We include results for the remaining concepts in the Appendix A.9.

Figure 4a to Figure 4d show debiasing visualizations for three concepts including *ambiance*, *noise* and *service*. We use a CPM_{HI} for the BERT model architecture as an example. We calculate the distributions with examples in the test set.

A.10 LEARNING DYNAMICS

Figure 5 shows three different metrics measured on the dev and the test sets for a CPM_{HI} trained for the BERT model architecture as an example. Since we use COS_{ICaCE} on the dev set to early stop our training process, we find our CPM_{HI} reaches local minimum on COS_{ICaCE} while $L2_{ICaCE}$ or $NormDiff_{ICaCE}$ is still in a downward trend. This suggests future research may need to choose desired metrics to optimize with during training for early stopping to reach the best performing model.

Epoch	Predicted	Concept	Score	Word Importance
1	*neutral*	ambiance	−0.17	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+0.66	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−0.32	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+0.05	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
2	*neutral*	ambiance	−0.25	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+1.54	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−0.24	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+0.02	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
3	*neutral*	ambiance	−0.49	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+1.52	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−0.97	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+0.49	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
4	*neutral*	ambiance	−0.69	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+1.41	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−1.92	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+1.14	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
5	*neutral*	ambiance	−0.77	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+1.25	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−1.63	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+1.28	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
6	*neutral*	ambiance	−0.66	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		food	+0.62	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		noise	−0.90	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]
		service	+2.14	[CLS] the music was too loud , and the decorations were taste ##less , but they had friendly waiter ##s and delicious pasta [SEP]

Table 10: Visualizations of word importance scores using Integrated Gradient (IG) by restricting gradients flow through corresponding intervention site of the targted concept by training epochs. Target classes we consider are {*positive*, *very positive*} where summed scores are taken. Word importance score is normalized to $[−1, +1]$. $−1$ means the word contributes the most negatively to predicting the target class. $+1$ means the word contributes the most positively to predicting the target class. Negative word importance score is colored as red, whereas positive one is colored as green. Score represents the sum of word importance score for each concept.

Table 10 visualizations of word importance scores using Integrated Gradient (IG). Different from Table 4 and Table 9 which shows the visualizations of our optimized model, we focus on breakdown visualizations of checkpoints taking after each training epochs for CPM_{HI}. Our results suggest that early checkpoints in the training process focus at drastically different input words comparing to later checkpoints, though all models predict *neutral* for this given sentence. In addition, gradients

(a) Visualization for the *ambiance* concept.

(b) Visualization for the *food* concept.

(c) Visualization for the *noise* concept.

(d) Visualization for the *service* concept.

Figure 4: Debiasing visualizations for different concepts of a CPM_HI with **BERT** model architecture. Individual plot is a correlation plot between concept labels of a concept and the overall sentence sentiment label.

Figure 5: CEBaB scores measured in three different metrics on the dev and the test sets for a CPM_{HI} with the BERT architectures for different training epochs. Task performance as `Macro-F1` score is reported.

aggregations over input words are rather stable towards the end the training. More importantly, CPM_{HI} learns how to highlight words that are semantically related to each concept gradually. For instance, we can see a clear trend of emphasising the word "decorations" for the *ambiance* concept throughout the training process. This suggests that our training procedure induces causally motivated gradients over input words gradually through the training process.