Risk Sensitive and Robust Dead-end Identification in Safety-Critical Offline Reinforcement Learning

Abstract

In safety-critical decision-making scenarios being able to identify worst-case outcomes, or dead-ends is crucial in order to develop safe and reliable policies in practice. These situations are typically rife with uncertainty due to unknown or stochastic characteristics of the environment as well as limited offline training data. As a result, the value of a decision at any time point should be based on the *distribution* of its anticipated effects. We propose a framework to identify worst-case decision points, by explicitly estimating *distributions* of the expected return of a decision. These estimates enable earlier indication of dead-ends in a manner that is tunable based on the risk tolerance of the designed task. We demonstrate the utility of Distributional Dead-end Discovery (DistDeD) in a toy domain as well as when assessing the risk of severely ill patients in the intensive care unit reaching a point where death is unavoidable. We find that DistDeD significantly improves over prior discovery approaches, providing indications of the risk 10 hours earlier on average as well as increasing detection by 20%.

1 Introduction

In complex safety-critical decision-making scenarios, being able to identify signs of rapid deterioration is crucial in order to proactively adjust a course of action, or policy. Consider the challenge of replacing an aging component within high-value manufacturing machinery. The longer one waits to replace this component, the efficiency of the process degrades until catastrophic failure at some unknown future time. However, the cost of temporarily stopping manufacturing to replace the component is non-trivial and the observed state of the system may not transparently signal when failure is imminent. Specifically, being aware of potential "worst-case" outcomes when choosing whether to delay repair is paramount to develop both safe and successful policies. Yet quantifying the worst-case outcomes in these and related circumstances among other safety critical domains–such as healthcare–is usually challenging as a result of unknown stochasticity in the environment, potentially changing dynamics, limited data, and the wide range of possible outcomes that might follow a sequence of decisions. By reliably providing an early indication of system failure to human operators, they would be enabled to intervene and make the necessary repairs in order to avoid system failure.

Reinforcement learning (RL) is a natural paradigm to address sequential decision-making tasks in safety-critical settings, focusing on maximizing the cumulative effects of decisions over time (Sutton & Barto, 2018). RL frameworks have been posed to design safe and responsible machine learning algorithms by regulating undesirable behavior with safety tests (Thomas et al., 2019) or through establishing performance guarantees when learning from limited data (Liu et al., 2020). Unfortunately, these approaches to develop safe RL policies depend on the ability to characterize *a priori* what actions or regions of the state space to avoid. This is not feasible in many real-world tasks as the definition of unsafe or risky behaviors may not be tractable due to unknown interactions between the observed state and selected actions.

A defining feature of RL in high-risk real-world settings is that the learning paradigm is fully *offline* **and** *off-policy* since exploratory data collection is often infeasible due to legal, safety, and ethical implications. However, RL methods are heavily influenced by the data collection policy: data is collected prior to learning,

and frequently contains decisions that rely on confounding information; such as production schedules requiring deviations from normal use of manufacturing machinery or lifestyle information and insurance status in clinical treatment (Dorfman et al., 2021; Gasse et al., 2021). These factors, if unaccounted for, may lead to the overestimation of the anticipated return, biased decisions, and/or overconfident yet erroneous predictions (Thrun & Schwartz, 1993). In addition, rare but dangerous situations can be overlooked if optimizing without accounting for possible "worst case" outcomes, thus failing to guarantee safety.

While RL has been explored within healthcare applications, it has primarily been used as a means for learning *risk-neutral* policies, optimized to provide the action with highest expected return (Raghu et al., 2017; Parbhoo et al., 2017; Prasad et al., 2017; Yu et al., 2021). Without the ability to explore or otherwise test alternative treatment strategies, the learned policies are unreliable (Gottesman et al., 2019; Oberst & Sontag, 2019). An alternative offline RL paradigm was introduced by Fatemi et al. (2021) that prioritizes the avoidance of actions, proportional to their risk of leading to dead-ends (where an agent enters an irrecoverably negative trajectory). In their proposed dead-end discovery (DeD) framework, recorded negative outcomes are leveraged to identify behaviors that should be avoided. Specifically, actions that lead to dead-ends are identified based on thresholded point-estimates of the expected return of that action rather than considering the full distribution. In doing so, risk estimation in DeD is limited and, at worst, too optimistic to determine which actions are safe to be executed. The implications of this are significant: by underestimating the risk associated with a particular action, we are unable to determine whether an action could be potentially dangerous – a necessity in safety-critical settings.

In this paper, we propose a risk-sensitive decision-making framework positioned to serve as an early-warning system for dead-end discovery. Broadly, our framework may be thought of as a tool for thinking about risk-sensitivity in data-limited offline settings. Our contributions are as follows: (i) Unlike former approaches, we incorporate distributional estimates of the return (Bellemare et al., 2022) to determine when an observed state is at risk of becoming a dead-end from the expected worst-case outcomes over available decisions (Chow et al., 2015). (ii) We establish that our risk-estimation procedure serves as a lower-bound to the theoretical results underlying DeD (Fatemi et al., 2021), maintaining important characteristics for assessing when identifying dead-ends. As a result, we are able to detect and provide earlier indication of high-risk scenarios. (iii) By modeling the full distribution of the expected return, we construct a spectrum of risk-sensitivity when assessing dead-ends. We show that this flexibility allows for tunable risk estimation procedures and can be customised according to the task at hand. (iv) Finally, we provide empirical evidence that our proposed framework enables an earlier determination of high-risk areas of the state space on both a simulated environment and a real application within healthcare of treating patients with sepsis.

2 Related Work

Safe and Risk-sensitive RL A shortcoming of most approaches to offline RL is that they are designed to maximise the expected value of the cumulative reward of a policy. This assumes that the training data is sufficient to promote convergence toward an optimal policy. The field of safe-RL instead tries to learn policies that obtain good performance in terms of expected returns while satisfying some safety constraints during learning and/or deployment (García & Fernández, 2015). Several safe RL algorithms (Chow et al., 2015; Achiam et al., 2017; Alshiekh et al., 2018; Berkenkamp et al., 2017) have been developed that either i) transform the standard RL objective to include some form of risk or, ii) leverage external knowledge to satisfy certain safety constraints and quantify performance with a risk metric. However, safe RL assumes *a priori* knowledge of what unsafe regions are, which is not always feasible in real-world safety-critical scenarios. Unlike these, we do not explicitly learn a policy, but learn a value function that conveys the risks inherent in making suboptimal decisions at inopportune times.

Risk-sensitive RL instead focuses on learning to act in a dynamic environment, while accounting for risks that may arise during the learning process (Mihatsch & Neuneier, 2002), where high risk regions do not have to be known a priori. Unlike risk-neutral RL, these methods optimise a *risk measure of the returns* rather than the average or expected return. Among these, Fu et al. (2018) present a survey of policy optimization methods that consider stochastic formulations of the value function to ensure that certain risk constraints may be satisfied when maximising the expected return. Other approaches such as (Chow et al., 2015) propose

replacing the expected long-term reward used by most RL methods, with a *risk-measure* of the total reward such as the Conditional-Value-at-Risk (CVaR) (Stanko & Macek, 2019; Ying et al., 2022; Du et al., 2022) and develop a novel optimization strategy to minimize this risk to ensure safety all-the-time. Ma et al. (2021) adapt distributional RL frameworks (Bellemare et al., 2022) to offline settings and by penalizing the predicted quantiles of the return for out-of-distribution actions. While these methods may be used to learn a distribution of possible outcomes, they have not been used to identify dead-ends as we propose here.

Unlike off-policy evaluation methods, we focus on estimating the *risk* associated with a policy in terms of the expected worst case outcomes. Specifically, we learn a distributional estimate of the future return of a policy using Implicit Quantile Networks (IQN) (Dabney et al., 2018), and integrate a conservative Q-learning (CQL) penalty (Kumar et al., 2020) into the loss to lower bound on the expected value of the policy.

Nonstationary and Uncertainty-Aware RL Several works focus on explicitly modelling *non-stationary dynamics* in MDPs for decision-making that accounts for uncertainty over model dynamics. Among these, methods such as Chandak et al. (2020) focus on safe policy optimization and improvement in non-stationary MDP settings. Here, the authors assume that the non-stationarity in an MDP is governed by an exogenous process, or that past actions do not impact the underlying non-stationarity. Sonabend et al. (2020) use hypothesis testing to assess whether, at each state, a policy from a human expert would improve value estimates over a target policy during training to improve the target policy. More recently, Joshi et al. (2021) presented an approach for learning to defer to human expertise in nonstationary sequential settings based on the likelihood of improving the expected returns on a particular policy. Our work differs from these in that instead of focusing on optimizing a specific policy, we explicitly learn which types of behaviors to avoid using risk-sensitive distributional estimates of the *future return*, as opposed to a point estimate of the expectation of that distribution.

RL in safety critical domains There are several works posed for uncertainty decomposition in applications such as healthcare. Specifically, Depeweg et al. (2018), decompose the uncertainty in bayesian neural networks to obtain an estimate of the aleatoric uncertainty for safety. Similarly, Kahn et al. (2017) use uncertainty-aware RL to guide robots to avoid collisions, while Cao et al. (2021) develop a domain-specific framework called Confidence-Aware RL for self-driving cars to learn when to switch between an RL policy and a baseline policy based on the uncertainty of the RL policy. Unlike these works, we propose a general purpose framework that can be applied to a number of safety-critical applications using risk-sensitive RL to provide an early warning of risk over possible future outcomes.

3 Preliminaries

As outlined above, we frame risk identification for safety critical decision making within a Reinforcement Learning (RL) context. We consider a standard episodic RL setting with an agent determining appropriate actions $a \in \mathcal{A}$ after receiving a state representation $s \in \mathcal{S}$ of their environment, modeled as a Markov Decision Process (MDP) $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, T, R, \gamma\}$, where $T(\cdot|s, a)$ relates to the transition from state s given action a; $R(s, a)$ is a finite reward function and $\gamma \in (0, 1]$ is a scalar discount factor. In offline safety critical settings, we assume that recorded actions a are selected according to an unknown expert policy $\pi(\cdot|s)$, given the observed state s. The objective is to estimate the value of each action as the discounted sum of future rewards (e.g. the return) $Z^\pi(s, a) = \sum_{t=0}^\infty \gamma^t R(s_t, a_t)$ where $s_0 = s$, $a_0 = a$, $s_t \sim T(\cdot|s_{t-1}, a_{t-1})$, and $a_t \sim \pi(\cdot|s_t)$. By characterizing the full probabilistic nature of how $Z^\pi(s, a)$ can be computed, it is used to represent the distribution of future return from the state s, executing action a.

Distributional RL In challenging real-world scenarios, the consequences of a decision carry a measure of unpredictability. Standard approaches to RL seek to maximize the mean of this random return. In reality, complex phenomena in stochastic environment may fail to be accounted for, leading to rare but critical outcomes going ignored. To account for this, Distributional RL (Bellemare et al., 2022) has been introduced to model the full return distribution by treating the observed return from following a policy π and associated states as random variables when forming the Bellman equation:

$$Z^\pi(s, a) \stackrel{D}{=} R(s, a) + \gamma Z^\pi(s', a')$$

The return distribution $Z^\pi(s, a)$ is most commonly represented in RL by the state-action value function $Q^\pi(s, a)$ which represents the expected future return. That is, $Q^\pi(s, a) = \mathbb{E}[Z^\pi(s, a)]$.

As the distribution is an infinite dimensional object, some approximations are needed for tractable estimation. Initially, the support of the distribution was discretized *a priori*, forming a categorical distribution over pre-defined quantiles (Bellemare et al., 2017). More recently this approximation has been relaxed to a distribution of uniformly weighted particles, estimated with neural networks (Dabney et al., 2018), to implicitly represent these quantiles.

Given the flexibility of these implicit quantile networks (IQN), they are well suited to define risk-aware decision criteria over value functions learned from real-world data where the anticipated return structure is unknown. As such, we build our proposed framework from IQN estimates of the state-action value function.

Conservatism in offline RL An important consideration when learning from offline data with RL is avoiding the overestimation of value for actions not present in the data (Fujimoto et al., 2018; 2019). Prior approaches have attempted to choose a lower bound of the Bellman equation approximated value (Fujimoto et al., 2018; Buckman et al., 2020), regularize policy learning by the observed behavior (Fujimoto et al., 2019; Wu et al., 2019; Kumar et al., 2019; Wang et al., 2020) or by directly regularizing the value estimates of the observed actions (Kumar et al., 2020). We utilize this last approach (termed conservative Q-learning; CQL) which resorts to minimizing the estimated values over the observed state-action distribution. This serves to additionally constrain the overestimation of actions not present in the dataset and has been shown to improve risk-averse performance with distributional RL (Ma et al., 2021).

Risk estimation.

We assume the return is bounded (e.g. $\mathbb{E}[|Z|] < \infty$) with cumulative distribution function $\mathcal{F}(z) = \mathbb{P}(Z \leq z)$. When estimating the possible effects of a decision, we want to account for worst-case outcomes that occur with some level of confidence $\alpha \in (0, 1)$. The value-at-risk (VaR) with confidence α represents the α-quantile of the distribution Z: $\text{VaR}_\alpha(Z) = \min\{z \mid \alpha \leq \mathcal{F}(z)\}$. This quantile can then be used to determine the "expected worst-case outcome", or conditional value at risk (CVaR):

$$\text{CVaR}_\alpha(Z) = \frac{1}{\alpha}\mathbb{E}[(Z - \text{VaR}_\alpha(Z))^-] + \text{VaR}_\alpha(Z)$$

Figure 1: Illustration of the determination of conditional value at risk (CVaR_α), with $\alpha = 0.1$

where $(x)^- = \min(x, 0)$ is the negative part of x. We use the dual representation of CVaR (Artzner et al., 1999) which is formulated with a single expectation:

$$\text{CVaR}_\alpha(Z) = \min_{\xi \in \mathcal{U}_{\text{CVaR}}(\alpha, \mathbb{P})} \mathbb{E}_\xi[Z]$$

where $\mathbb{E}_\xi[Z]$ is the ξ-weighted expectation of Z within the α-quantile and $\mathcal{U}_{\text{CVaR}}(\alpha, \mathbb{P})$ is the portion of Z that falls below $\text{VaR}_\alpha(Z)$. This establishes that:

$$\text{CVaR}_\alpha(Z) \leq \mathbb{E}[Z] \tag{1}$$

as $\alpha \to 1$, then $\mathcal{U}_{\text{CVaR}}(\alpha, \mathbb{P})$ encompasses all of Z and $\text{CVaR}_\alpha(Z) \to \mathbb{E}[Z]$. Thus, the CVaR is a lower-bound for value estimates derived through the expectation of the return distribution (e.g. the value function Q^π).

Dead-end Discovery (DeD). As introduced by Fatemi et al. (2021) the DeD framework assures a notion of security when estimating whether an action will lead to a dead-end (see Eqt. 2). DeD constrains the scope of a given policy π if *any* knowledge exists about undesired outcomes. Formally, if at state s, action a transitions to a dead-end at the next state with probability $P_D(s, a)$ or immediate negative termination with probability $F_D(s, a)$ with a level of certainty $\lambda \in [0, 1]$, then π must avoid a at s with the same certainty:

$$P_D(s, a) + F_D(s, a) \geq \lambda \implies \pi(s, a) \leq 1 - \lambda. \tag{2}$$

While P_D, F_D, and λ may not be able to be explicitly calculated, the DeD framework learns an estimate of the likelihood of transitioning to a dead-end as well as the reduction in likelihood of a positive outcome. This is done by constructing two independent MDPs $\mathcal{M}_D$ and $\mathcal{M}_R$ focusing solely on negative and positive outcomes, respectively. DeD learns value approximations of each MDP, $Q_D(s,a)$ for negative outcomes and $Q_R(s,a)$ for positive outcomes ($Q_D \in [-1,0]$ and $Q_R \in [0,1]$ respectively). These value estimates enable the identification and confirmation of dead-ends and actions that lead to them through the relationship:

$$-Q_D(s,a) \geq P_D(s,a) + F_D(s,a) \tag{3}$$

with equality when Q_D is fully converged. Then, the security condition is assured by $\pi(s,a) \leq 1 + Q_D(s,a)$. In practice, the Q_D and Q_R functions are approximated with deep Q-networks (DQN) (called the D- and R- networks, respectively) in concert with empirically determined thresholds δ_D and δ_R to flag when actions or states have the risk of leading to dead-ends and should be avoided.

The DeD framework determines an action a should be avoided when $Q_D(s,a) \leq \delta_D$ **and** $Q_R(s,a) \leq \delta_R$. A state s is said to be a dead-end if the *median* value over all actions falls below these thresholds. That is a dead-end is reached whenever both $\text{median}(Q_D(s,\cdot)) \leq \delta_D$ **and** $\text{median}(Q_R(s,\cdot)) \leq \delta_R$. Our proposed distributional formulation of dead-end discovery follows from these definitions and allows for the identification of **both** high-risk actions and states. However, in this paper we prioritize the identification of dead-end states, demonstrating that our proposed solution provides earlier identification.

4 Risk-sensitive Dead-end Discovery

While the DeD framework is promising for learning in offline safety-critical domains, it has limited risk-sensitivity by neglecting to model the full distribution of possible outcomes. We develop a risk-sensitive framework for dead-end discovery that conservatively models the full distribution of possible returns, driven by irreducible environment stochasticity. Our approach, DistDeD, utilizes distributional dynamic programming (Bellemare et al., 2022) to estimate the full distribution of possible returns while also limiting overestimation due to out-of-distribution actions by incorporating a CQL penalty (Kumar et al., 2020).

Mirroring the construction of DeD, we instantiate two Markov Decision Processes (MDPs) $\mathcal{M}_D$ and $\mathcal{M}_R$ as identical to the original MDP $\mathcal{M}$, $\gamma = 1$, with reward functions: $\mathcal{R}_D$ (returning -1 with any transition to a negative terminal state, zero otherwise) and $\mathcal{R}_R$ (returning $+1$ with any transition to a positive terminal state, zero otherwise). We then approximate the distributional returns Z_D and Z_R of these separate MDPs independently, where the support of Z_D is $[-1,0]$ and the support of Z_R is $[0,1]$.

To robustly quantify the risk of selecting an action a at state s, we consider the expected worst-case outcome—or conditional value at risk (CVaR)—of these return distributions. That is, we infer $\text{CVaR}_\alpha(Z_D(s,a))$ and $\text{CVaR}_\alpha(Z_R(s,a))$ for a chosen $\alpha \in (0,1]$, which we consider to be a hyperparameter along with the choice of thresholds δ_D and δ_R. By using CVaR to determine the risk of approaching a dead-end, we effectively construct a lower-bound on the DeD value estimates (by virtue of Eqt. 1) which allows us to maintain the same theoretical framing. Since DeD is built around the expectation of the return: $Q_D(s,a) = \mathbb{E}[Z_D(s,a)]$. Then, as $\text{CVaR}_\alpha(Z_D(s,a)) \leq \mathbb{E}(Z_D(s,a))$ we are assured that:

$$-\text{CVaR}_\alpha(Z_D(s,a)) \geq -Q_D(s,a) \geq P_D(s,a) + F_D(s,a) \tag{4}$$

Thus, by bounding the estimates of entering a dead-end, we see that using CVaR satisfies the security condition: $\pi(s,a) \leq 1 + \text{CVaR}_\alpha(Z_D(s,a))$. Parallel results for Z_R follow similarly.

With the bounding provided by DistDeD, utilizing CVaR estimates of the inferred return distributions, we enable a more conservative and thereby risk-averse mechanism to determine whether a state s is at risk of being a dead-end. The level of risk-aversion is jointly determined by the confidence level α as well as the thresholds δ_D and δ_R, which can be tuned dependant on acceptable risk tolerances in the task. Choosing a smaller value for α constrains the CVaR evaluation of the estimated distributions to consider lower likelihood (and more adverse, by construction) outcomes, a form of increased conservatism. Smaller values of the thresholds increase the sensitivity of the risk determination of the framework.

Figure 2: **Distributional Dead-end Discovery (DistDeD)** a) Observations are encoded (as needed) into a state representation and then b) passed to independent IQN models to estimate the distribution of returns (Z_D and Z_R) for each possible action. c) The CVaR_α is computed for each distribution and is then evaluated against the thresholds δ_D and δ_R. If both $\mathrm{CVaR}_\alpha(Z_D)$ and $\mathrm{CVaR}_\alpha(Z_R)$ fall below the respective thresholds for any action, then that action is recommended to be avoided. d) If the median over all actions falls below the thresholds for both distributions, then the state is said to be a dead-end.

An illustration of the DistDeD framework is included in Figure 2. *a)* If necessary[1], observations are encoded into a state representation. *b)* The encoded state representations are then passed to independent IQN models to estimate $Z_D(s, \cdot)$ and $Z_R(s, \cdot)$ for each possible action. *c)* The CVaR is computed for each distribution and then evaluated against the thresholds δ_D and δ_R. If both $\mathrm{CVaR}(Z_D)$ and $\mathrm{CVaR}(Z_R)$ fall below the respective thresholds for any action, that action is recommended to be avoided. *d)* Furthermore, if the median over all actions falls below the thresholds for both distributions, then the state is said to be a dead-end.

We choose to represent the distributions Z_D and Z_R for all states s and actions a using implicit Q-networks (IQN) (Dabney et al., 2018). To constrain the distributional estimates from overestimating the return for actions not present in the dataset, thus avoiding overconfidence, we train the IQN architectures with an included conservative Q-learning (CQL) penalty (Kumar et al., 2020). CQL regularizes the distributional Bellman objective by minimizing the value of each action, which serves also to constrain overestimation of actions not present in the observed data. We weight this penalty by the hyperparameter β

5 Illustrative Demonstration of DistDeD

We provide a preliminary empirical demonstration of the advantages seen by using our proposed DistDeD framework using the LifeGate toy domain (Fatemi et al., 2021). Here, the agent is to navigate around a barrier to a goal region while learning to avoid a dead-end zone which pushes the agent to the negative terminal edge after a random number of steps (See Figure 3).

Empirical Comparison We aim to demonstrate the apparent advantages of our proposed DistDeD in comparison to the original DeD framework. For DeD, we model the Q_D and Q_R functions using the DDQN architecture (Hasselt et al., 2016) using two layers of 32-nodes with ReLU activations and a learning rate of $1e^{-3}$. For DistDeD we utilize IQN architectures (Dabney et al., 2018) for both Z_D and Z_R using two layers of 32 nodes, ReLU activations and the same learning rate of $1e^{-3}$. For each IQN model, we sample $N, N' = 8$ particles from the local and target τ distributions while training and also weight the CQL penalty $\beta = 0.1$. When evaluating Z_D and Z_R, we select $K = 1000$ particles and set our confidence level to $\alpha = 0.1$.

All approximate value functions (both expectational and distributional) were trained using 1 million randomly collected transitions from LifeGate. In Figure 3 we show the learned value estimates from the D-Networks for all actions available to the agent in select locations. We suppress the corresponding R-Network estimates for visual simplicity although they reflect qualitatively the same thing. For this demonstration

---

[1]When observations are irregular or partial

Figure 3: Demonstration of inherent value of using $Z_D(s,a)$ estimated with IQN and $\text{CVaR}_{0.1}(Z_D(s,a))$ in comparison to $Q_D(s,a)$ estimated with DDQN on the LifeGate toy domain (Fatemi et al., 2021). **A)** Evaluating returns from an initial state, **B)** evaluating returns from a more favorable location near the goal region. Notably, the CVaR estimate (the mean of the orange "worst-case distribution") is *risk-sensitive* and *provides a lower bound of the expected value of the blue return distribution*, while the value estimate of DeD (black dashed line) is far more optimistic. Here, we set $\delta_D = -0.75$ as a notional threshold (red dashed line).

we plot the full return distribution $Z_D(s,a)$, the α-quantile used to compute $\text{CVaR}_\alpha(Z_D(s,a))$, the value estimate $Q_D(s,a)$ from the DeD, as well as a notional threshold $\delta_D = -0.75$.

We see the inherent value of the distributional estimates used in DistDeD to determine which actions to avoid. Fig. 3(A) presents the returns at an initial state, from which encountering a dead-end is more common. Fig. 3(B) presents the estimated returns from a more favorable location near the goal region. As expected, the CVaR estimate, the mean of the orange "worst-case distribution", is a lower bound on the expected value of the full return distribution (plotted in blue). Notably, the value estimated using DeD (black dashed vertical line) is far more optimistic, since DeD only considers thresholded point-estimates of expected value. This provides evidence of the limitations of DeD, ignoring the full return distribution when estimating the value of available decisions.

In Figure 4(A, B), we evaluate three pre-determined policies in LifeGate using both DeD and DistDeD. Two of the three policies attempt to navigate through the dead-end region of the environment. This construction is purposeful in order to indicate how reliably risk is flagged by each approach. The design of this experiment is to demonstrate the early-warning capability of DistDeD for those sub-optimal trajectories. In Figure 4(C) we evaluated 10,000 trajectories with stochastic execution of the two suboptimal policies and assess how the many steps prior to entering the dead-end region that DistDeD and DeD raise alarm and recommend a change in policy. We assess the overall risk of each state s in a trajectory by averaging the median values of $Q_D(s,\cdot)$ and $Q_R(s,\cdot) - 1$ (for DistDeD $\text{CVaR}_\alpha(Z_D(s,\cdot))$ and $\text{CVaR}_\alpha(Z_R(s,\cdot)) - 1$). If the averaged median value falls below the threshold δ_D, an alarm is raised. We use the previously published value, $\delta_D = -0.15$ for DeD and choose $\delta_D = -0.5$ for DistDeD. These values were chosen empirically by attempting to minimize false-positives among a validation set of the data (see Section A.3.1 for more detail).

DeD (Fig. 4(A)) fails to adequately signal the risk of the two sub-optimal policies before they reach the dead-end region of the environment. In contrast, DistDeD (Fig. 4(B)) appropriately flags the trajectories ahead of the dead-end region, allowing for correction if an overseeing agent is able to intervene. Fig. 4(C) quantifies this advantage, demonstrating that DistDeD provides an indication of risk, on average, 3 steps earlier. This result confirms the utility of modeling the full distribution of expected returns and using a more coherent estimation of risk, focused on expected worst case outcome.

6 Assessing Medical Dead-ends with DistDeD

Data We aim to identify medical dead-ends among a cohort of septic patients derived from the MIMIC-IV (Medical Information Mart for Intensive Care, v2.0) database (Johnson et al., 2020). This cohort comprises the recorded observations of 6,188 patients (5,352 survivors and 836 nonsurvivors), with 42 features, and 25

A) *DeD*   **B)** *DistDeD*   **C)** *Comparison of flags raised by DistDeD and DeD ahead of a suboptimal trajectory's encounter with the Dead-end Region*

Figure 4: DistDeD's advantage when alerting that a trajectory is at risk of encountering a dead-end in the LifeGate domain. Three hand-designed policies (with two purposefully suboptimal) (shown in white) are evaluated using both DeD (A) and DistDeD (B), showing that DistDeD raises alarm earlier than DeD and in a manner that could alert a necessary change in policy before encountering a dead-end. 10000 stochastic executions of these suboptimal policies are then evaluated (C) using both approaches to understand the scope of how much earlier DistDeD raises a flag in comparison to DeD. Dotted lines show how raising alarms earlier leads to actions that could direct a patient's trajectory towards potential recovery (shown in blue).

treatment choices (5 discrete levels for each of IV fluid and vasopressor), over time periods ranging between 12 and 72 hours. We aggregate each feature into hourly bins and fill missing values with zeros, keeping track of which features were actually observed with an appended binary mask. Missing features are implicitly accounted for when constructing state representations of a patient's health through time. Details about the exclusion and inclusion criteria used to define the construction of this patient cohort are contained in Section A.1 in the Appendix.

State Construction As recommended by Killian et al. (2020) and implemented in DeD (Fatemi et al., 2021), we make use of a sequential autoencoder to construct fixed dimension state representations, embedding a history of recorded observation of a patient's health previous to each time step. This allows us to process partial and irregularly occurring observations through time, a characteristic of medical data. To do this, we use an online Neural Controlled Differential Equation (NCDE) (Morrill et al., 2021) for state construction as it naturally handles irregular temporal data. Additional information about the NCDE state construction can be found in Section A.2.1 in the Appendix. We define terminal conditions for each trajectory as whether the patient survives or succumbs to (within 48 hours of the final observation) their infection. There are no intermediate rewards aside from these terminal states. When a patient survives, the trajectory is given a $+1$ reward, where negative outcomes receive -1.

D- and R- Networks The encoded state representations provided by the NCDE are provided as input to the D- and R -Networks to estimate the value (and risk of encountering a dead-end) of each state and all possible treatments. To form the DistDeD framework we use CQL (Kumar et al., 2020) constrained implementations of IQN (Dabney et al., 2018) to train each network, as discussed in Section 4 (details included in Appendix A.2.2).

Training We train the NCDE for state construction as well as the IQN instantiations for the D-, and R-Networks in an offline manner. All models are trained with 75% of the data (4,014 surviving patients, 627 patients who died),validated with 5% (268 survivors, 42 nonsurvivors), and we report all results on the remaining held out 20% (1,070 survivors, 167 nonsurvivors). In order to account for the data imbalance between positive and negative outcomes, we follow a similar training procedure as DeD (Fatemi et al., 2021) where every sampled minibatch is ensured to contain a proportion of terminal transitions from non-surviving patient trajectories. This amplifies the training for conditions that lead to negative outcomes, ensuring that

the D- and R- Networks are able to recognize scenarios that carry risk of encountering dead-ends. Specific details on the training of DistDeD can be found in Appendix A.2.[2]

6.1 Experimental Setup

By design, DistDeD is formulated to provide a more conservative and thereby earlier indication of risk. A secondary benefit of the design of DistDeD is that by adapting the risk tolerance level of the CVaR estimates (by selecting different values for α), we are provided a spectrum of value functions that could be used to assess whether a dead-end has been reached or is eminent. We therefore aim to execute a set of experiments that assess the extent at which these two points of improvement over DeD provide benefit. By establishing more conservative estimators with the IQN D- and R- Networks, we increase the occurrence of what could be identified as false positive indications of risk for patients whose health has not deteriorated to be a legitimate dead-end (e.g. patients who survive). We therefore need to assess the tradeoffs of increased "false-positives" against improved recall for indications of risk for patients who died.

To perform this assessment we execute a set of experiments to quantitatively compare DistDeD to DeD when each approach is applied to the septic patient cohort outlined above. First, this entails measuring how much earlier DistDeD raises flags across a range of CVaR α values (for a fixed set of thresholds $\delta_{D,R}$). Second, we want to identify if DistDeD's variation—due to the choice of CVaR α—introduces settings that perform worse than DeD when considering a full range of possible thresholds $\delta_{D,R}$. Finally, we aim to develop insight into the contributions of both the distributional and CQL additions to the DeD framework by considering ablations to DistDeD where each component is removed.

6.2 Results

As outlined in Section 6.1 we highlight the importance of accounting for risk when thinking about dead-ends and validate the following aspects of DistDeD. First, we assess the performance of DistDeD by demonstrating how DistDeD can provide an earlier indication of risk in comparison to other baselines and notably, outperforms DeD across all settings. Second, we demonstrate the utility of having a tunable assessment of risk that allows for domain experts to easily apply and adapt our method to different contexts, hospital settings and illnesses. Finally, we show that including a CQL penalty in the DistDeD framework further improves performance in comparison to other baselines.

6.2.1 DistDeD Provides Earlier Warning of Patient Risk

We assess the ability of DistDeD to provide an early warning of patient risk in comparison to the original medical dead-ends framework, DeD. Figure 5 shows for non-survivors, the number of hours ahead of death that DistDeD raises a warning flag and how this changes with varying choices of VaR. In comparison to DeD, DistDeD is able to raise flags much earlier warning of up to 25 hours in advance across all values of VaR, thereby enabling timely intervention in safety-critical settings.

To assess DistDeD's ability to raise flags in different contexts, we also compare how its performance varies across both surviving and non-surviving patients. These results are shown in Figure 6. In general we note that for both patient groups, DistDeD is able to detect patient deterioration and provide early warning of up to 20 hours in advance depending on the choice of VaR thresholds in comparison to DeD. The performance across both surviving and non-surviving patients is very similar.

6.2.2 DistDeD Allows for a Tunable Assessment of Risk

Note that because DistDeD explicitly uses the Value at Risk threshold parameter α to provide an assessment of risk, it can easily be adapted and tuned to various scenarios depending on how risk-averse a user would like to be. In addition, the choice of the thresholds δ_D and δ_R can be further adjusted to improve the precision of estimates of the risk of encountering a dead-end. For instance, in an ICU setting where timely

---

[2]All code for data extraction and preprocessing as well as for defining and training the DistDeD models will be released upon publication.

Figure 5: The number of hours before patient death that DistDeD and DeD raise warning.

Figure 6: The number of hours that DistDeD detects patient deterioration and first raises a flag before DeD.

intervention is crucial, a clinician may choose to adopt lower α and higher δ_D & δ_R threshold values to be more conservative such that flags may be raised earlier if necessary.

In our experiments, we evaluate DistDeD and DeD over all possible settings of δ_D and δ_R to assess the sensitivity of those settings when computing the True Positive Rate (TPR) and False Positive Rate (FPR) of determining patient risk. We also continue to evaluate DistDeD over a range of CVaR_α settings. Here, TPR corresponds to the percentage of non-survivor trajectories that are flagged, while FPR corresponds to the percentage of survivor trajectories that are flagged. Figure 7 shows a comparison of ROC curves derived from the DistDeD and DeD frameworks to exhibit how each balance the TPR and FPR tradeoff. For DistDeD we evaluated the TPR and FPR for a range of α values to identify whether there was a particular level of conservatism (or optimism) that would perform worse than DeD. However, we observe that DistDeD robustly outperforms DeD finding a higher TPR while having a low FPR in comparison, across all settings of α, δ_D and δ_R. Overall, having an *tunable* assessment of risk also enables a domain expert like a clinician balance the benefits of early warning with the risk of potential false positive indications of risk, where a patient at low-risk is potentially flagged. Moreover, a higher TPR counteracts an increased FPR when we are more conservative in the DistDeD framework.

6.2.3 CQL Enhances DistDeD Performance

In order to assess the individual contributions of implementing a distributional estimate of the risk of encountering a dead-end *and* constraining the values with CQL, we evaluate separate ablations to DistDeD by computing the area under the ROC curve derived from each approach. Figure 8 shows the performance comparison of DistDeD versus DeD and these two ablations that i) exclude a CQL penalty from the DistDeD framework and ii) incorporate a CQL penalty into the standard DeD framework. Overall, we see that the DistDeD framework outperforms the other baselines in terms of AUC across varying levels of the VaR threshold. Specifically, *both* the use of Distributional RL and the introduction of a CQL penalty are necessary for improving on the performance of DeD. We summarize the findings with the maximum AUC of each approach in Table 1. In total, DistDeD (which combines the IQN and a CQL penalty) provides an average AUC of 0.7912 while DeD results in an AUC of 0.6629, resulting in as much as a 20% improvement in the precision of identifying dead-end states.

Figure 7: ROC curve comparison between CVaR_α settings of DistDeD (green) and DeD (black), demonstrating DistDeD's robust improvement over DeD.

Figure 8: Evaluation of the CQL penalty in terms of area under the ROC curve (AUC), comparing DistDeD, DeD and two ablations to DistDeD.

	Architecture	
	DDQN	IQN
No Penalty	0.6629	0.7744
CQL Penalty	0.7687	**0.7912**

Table 1: Comparison of AUC when considering each improvement to DeD, 1) incorporating the CQL penalty and 2) modeling the full distributions of the expected return. Values represented here for the distributional components represent the mean value over all settings of VaR_α.

7   Discussion

In this paper we have presented our justification, foundational evidence as well as our preliminary findings supporting the development of the DistDeD framework which incorporates a more robust notion of risk when identifying dead-ends in safety-critical scenarios. We do so by leveraging distributional dynamic programming to form estimates of the full return distribution from which we can calculate the expected worst-case outcome for each available action. This form of robust risk-estimation enables a more tangible decision surface for determining which actions to avoid and can be tuned according to the requirements or preferences set forward by human experts that may interact with the trained DistDeD models.

Our DistDeD approach is based around risk-sensitive estimates of the expected worst-case outcome and is thereby contributes a conservative decision support framework. This framework is well suited for complex safety-critical situations where learning is completed in a fully offline manner.

Limitations While DistDeD is a promising framework for decision support in safety-critical domains with limited offline data, there are certain core limitations. The techniques described in this paper have been explored in the context of discrete action spaces only. However in scenarios where, for instance, continuous treatment dosages are important, analyses with the DistDeD framework may have to be adapted to identify potential dead-ends. In addition, the method considers the case where a reward signal is observed on the terminal state only. However, several applications may require us to account for intermediate outcomes as well. Moreover, the framework only explores the medical scenario where dead-ends are derived from a single condition whereas in reality, many concomitant conditions may exist, which contribute to and are associated with different dead-end regions. Finally, we do not make any causal claims about the impact of each action on the outcomes of interest. Future work may explore how to address some of these issues.

Broader Impact

This work serves as a proof of concept for identifying regions of risk in safety-critical settings, learning from offline data. While promising, it has not been thoroughly validated for immediate use in real environments. Despite the demonstrated utility of the DistDeD framework in healthcare problems, it should never be used in isolation to exclude patients from being treated, e.g., not admitting patients or blindly ignore treatments. The risk identification aspect of DistDeD demonstrated in this paper is to signal impending high-risk situations early enough so that the human decision maker has time to correct the course of action. This may help experts make better decisions and avoid circumstances that may lead to irrecoverably negative outcomes. The intention of our approach is to assist domain experts by highlighting possibly unanticipated risks when making decisions and is not to be used as a stand-alone tool nor as a replacement of a human operator. Misuse of this algorithmic solution could carry significant risk to the well-being and survival of critical systems and individuals placed in the care of the expert.

The primary goal of this work is to improve upon the established DeD proof of concept, where high-risk situations can be avoided in context of a system's state. We present a distributional estimate of this risk profile which enables earlier detection of possible dead-ends as well as facilitating a tunable framework for adaptation to each individual task. In acute care scenarios, all decisions come with inherent risk profiles and potential harms. In this spirit, we endeavor to providing a flexible tool for clinical experts to gain an earlier indication when specific decisions or their patient's health state may carry a measure of outstanding risk.

References

Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. In *International conference on machine learning*, pp. 22–31. PMLR, 2017.

Mohammed Alshiekh, Roderick Bloem, Rüdiger Ehlers, Bettina Könighofer, Scott Niekum, and Ufuk Topcu. Safe reinforcement learning via shielding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Philippe Artzner, Freddy Delbaen, Jean-Marc Eber, and David Heath. Coherent measures of risk. *Mathematical finance*, 9(3):203–228, 1999.

Eytan Bakshy, Lili Dworkin, Brian Karrer, Konstantin Kashin, Benjamin Letham, Ashwin Murthy, and Shaun Singh. Ae: A domain-agnostic platform for adaptive experimentation. In *Conference on Neural Information Processing Systems*, pp. 1–8, 2018.

Maximilian Balandat, Brian Karrer, Daniel Jiang, Samuel Daulton, Ben Letham, Andrew G Wilson, and Eytan Bakshy. Botorch: a framework for efficient monte-carlo bayesian optimization. *Advances in neural information processing systems*, 33:21524–21538, 2020.

Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, pp. 449–458. PMLR, 2017.

Marc G. Bellemare, Will Dabney, and Mark Rowland. *Distributional Reinforcement Learning*. MIT Press, 2022. http://www.distributional-rl.org.

Felix Berkenkamp, Matteo Turchetta, Angela Schoellig, and Andreas Krause. Safe model-based reinforcement learning with stability guarantees. *Advances in neural information processing systems*, 30, 2017.

Jacob Buckman, Carles Gelada, and Marc G Bellemare. The importance of pessimism in fixed-dataset policy optimization. In *International Conference on Learning Representations*, 2020.

Zhong Cao, Shaobing Xu, Huei Peng, Diange Yang, and Robert Zidek. Confidence-aware reinforcement learning for self-driving cars. *IEEE Transactions on Intelligent Transportation Systems*, 2021.

Yash Chandak, Scott Jordan, Georgios Theocharous, Martha White, and Philip S Thomas. Towards safe policy improvement for non-stationary mdps. *Advances in Neural Information Processing Systems*, 33: 9156–9168, 2020.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

Yinlam Chow, Aviv Tamar, Shie Mannor, and Marco Pavone. Risk-sensitive and robust decision-making: a cvar optimization approach. *Advances in neural information processing systems*, 28, 2015.

Will Dabney, Georg Ostrovski, David Silver, and Rémi Munos. Implicit quantile networks for distributional reinforcement learning. In *International conference on machine learning*, pp. 1096–1105. PMLR, 2018.

Stefan Depeweg, Jose-Miguel Hernandez-Lobato, Finale Doshi-Velez, and Steffen Udluft. Decomposition of uncertainty in bayesian deep learning for efficient and risk-sensitive learning. In *International Conference on Machine Learning*, pp. 1184–1193. PMLR, 2018.

Ron Dorfman, Idan Shenfeld, and Aviv Tamar. Offline meta reinforcement learning – identifiability challenges and effective data collection strategies. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 4607–4618. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/file/248024541dbda1d3fd75fe49d1a4df4d-Paper.pdf.

Yihan Du, Siwei Wang, and Longbo Huang. Risk-sensitive reinforcement learning: Iterated CVaR and the worst path. *arXiv preprint arXiv:2206.02678*, 2022.

Mehdi Fatemi, Taylor W Killian, Jayakumar Subramanian, and Marzyeh Ghassemi. Medical dead-ends and learning to identify high-risk states and treatments. *Advances in Neural Information Processing Systems*, 34, 2021.

Michael Fu et al. Risk-sensitive reinforcement learning. *arXiv preprint arXiv:1810.09126*, 2018.

Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International conference on machine learning*, pp. 1587–1596. PMLR, 2018.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pp. 2052–2062, 2019.

Javier Garcıa and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16(1):1437–1480, 2015.

Maxime Gasse, Damien Grasset, Guillaume Gaudron, and Pierre-Yves Oudeyer. Causal reinforcement learning using observational and interventional data. *arXiv preprint arXiv:2106.14421*, 2021.

Omer Gottesman, Fredrik Johansson, Matthieu Komorowski, Aldo Faisal, David Sontag, Finale Doshi-Velez, and Leo Anthony Celi. Guidelines for reinforcement learning in healthcare. *Nat Med*, 25(1):16–18, 2019.

Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence*, AAAI'16, pp. 2094–2100. AAAI Press, 2016.

Alistair Johnson, Lucas Bulgarelli, Tom Pollard, Steven Horng, Leo Anthony Celi, and Roger Mark. MIMIC-IV. *PhysioNet. Available online at: https://physionet. org/content/mimiciv/1.0/(accessed August 23, 2021)*, 2020.

Shalmali Joshi, Sonali Parbhoo, and Finale Doshi-Velez. Pre-emptive learning-to-defer for sequential medical decision-making under uncertainty. *arXiv preprint arXiv:2109.06312*, 2021.

Gregory Kahn, Adam Villaflor, Vitchyr Pong, Pieter Abbeel, and Sergey Levine. Uncertainty-aware reinforcement learning for collision avoidance. *arXiv preprint arXiv:1702.01182*, 2017.

Patrick Kidger. On neural differential equations. *arXiv preprint arXiv:2202.02435*, 2022.

Taylor W Killian, Haoran Zhang, Jayakumar Subramanian, Mehdi Fatemi, and Marzyeh Ghassemi. An empirical study of representation learning for reinforcement learning in healthcare. In *Machine Learning for Health*, pp. 139–160. PMLR, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems*, pp. 11784–11794, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative Q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

Yao Liu, Adith Swaminathan, Alekh Agarwal, and Emma Brunskill. Provably good batch off-policy reinforcement learning without great exploration. *Advances in neural information processing systems*, 33: 1264–1274, 2020.

Yecheng Ma, Dinesh Jayaraman, and Osbert Bastani. Conservative offline distributional reinforcement learning. *Advances in Neural Information Processing Systems*, 34:19235–19247, 2021.

Oliver Mihatsch and Ralph Neuneier. Risk-sensitive reinforcement learning. *Machine learning*, 49(2):267–290, 2002.

James Morrill, Patrick Kidger, Lingyi Yang, and Terry Lyons. Neural controlled differential equations for online prediction tasks. *arXiv preprint arXiv:2106.11028*, 2021.

Michael Oberst and David Sontag. Counterfactual off-policy evaluation with gumbel-max structural causal models. In *International Conference on Machine Learning*, pp. 4881–4890, 2019.

Sonali Parbhoo, Jasmina Bogojeska, Maurizio Zazzi, Volker Roth, and Finale Doshi-Velez. Combining kernel and model based learning for hiv therapy selection. *AMIA Summits on Translational Science Proceedings*, 2017:239, 2017.

Niranjani Prasad, Li-Fang Cheng, Corey Chivers, Michael Draugelis, and Barbara E Engelhardt. A reinforcement learning approach to weaning of mechanical ventilation in intensive care units. *arXiv preprint arXiv:1704.06300*, 2017.

Aniruddh Raghu, Matthieu Komorowski, Leo Anthony Celi, Peter Szolovits, and Marzyeh Ghassemi. Continuous state-space models for optimal sepsis treatment: a deep reinforcement learning approach. In *Machine Learning for Healthcare Conference*, pp. 147–163. PMLR, 2017.

Aaron Sonabend, Junwei Lu, Leo Anthony Celi, Tianxi Cai, and Peter Szolovits. Expert-supervised reinforcement learning for offline policy learning and evaluation. *Advances in Neural Information Processing Systems*, 33:18967–18977, 2020.

Silvestr Stanko and Karel Macek. Risk-averse distributional reinforcement learning: A cvar optimization approach. In *IJCCI*, pp. 412–423, 2019.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction.* MIT press, 2018.

Philip S Thomas, Bruno Castro da Silva, Andrew G Barto, Stephen Giguere, Yuriy Brun, and Emma Brunskill. Preventing undesirable behavior of intelligent machines. *Science*, 366(6468):999–1004, 2019.

Sebastian Thrun and Anton Schwartz. Issues in using function approximation for reinforcement learning. In *Proceedings of the 1993 Connectionist Models Summer School Hillsdale, NJ. Lawrence Erlbaum*, volume 6, pp. 1–9, 1993.

Ziyu Wang, Alexander Novikov, Konrad Zolna, Josh S Merel, Jost Tobias Springenberg, Scott E Reed, Bobak Shahriari, Noah Siegel, Caglar Gulcehre, Nicolas Heess, et al. Critic regularized regression. *Advances in Neural Information Processing Systems*, 33, 2020.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

Chengyang Ying, Xinning Zhou, Hang Su, Dong Yan, Ning Chen, and Jun Zhu. Towards safe reinforcement learning via constraining conditional value-at-risk. *arXiv preprint arXiv:2206.04436*, 2022.

Chao Yu, Jiming Liu, Shamim Nemati, and Guosheng Yin. Reinforcement learning in healthcare: A survey. *ACM Computing Surveys (CSUR)*, 55(1):1–36, 2021.

A Appendix

A.1 Sepsis Patient Cohort Details

We use the MIMIC-IV (Medical Information Mart for Intensive Care; v2.0) database, sourced from the Beth Israel Deaconess Medical Center in Boston, Massachusetts Johnson et al. (2020). This database contains deidentified treatment records of patients admitted to critical care units (CCU, CSRU, MICU, SICU, TSICU). The database includes data collected from 76,540 distinct hospital admissions of patients over 16 years of age for a period of 12 years from 2008 to 2019 (inclusive). The MIMIC database has been used in many reinforcement learning for health care projects, including mechanical ventilation and sepsis treatment problems. There are various preprocessing steps that are performed on the MIMIC-IV database in order to obtain the cohort of patients and their relevant observables for sepsis cohort used in this study.

To extract and process the data, we follow the approach used in (Fatemi et al., 2021). This includes all ICU patients over 18 years of age who have some presumed onset of sepsis (following the Sepsis 3 criterion) during their initial encounter in the ICU after admission, with a duration of at least 12 hours. We limited the observation window of each patient encounter from at most 24 hours before to at most 48 hours after presumed sepsis onset. We also constrained collection to include only those patients admitted to the Medical ICU (MICU) on that initial encounter. These criteria provide a cohort of 6,188 patients, among which there is an observed mortality rate of 13.5%, where mortality is determined by patient expiration within 48h of the final observation. Observations are processed and aggregated into hourly windows with treatment decisions (administering fluids, vasopressors, or both) discretized into 5 volumetric categories. All data is normalized to zero-mean and unit variance and missing values are zero-imputed with an binary mask appended to indicate which features were observed at each timestep. We report the 42 features used in the construction of this patient cohort in Table 2 with high-level statistics in Table 3.

Table 2: Patient features used for learning state representations for predicting future observations

Age	Gender	Weight (kg)	Height
Heart Rate	Sys. BP	Dia. BP	Mean BP
Respiratory Rate	Body Temp (C)	Glucose	SO2
PaO2	PaCO2	FiO2	PaO2 / FiO2
Arterial pH	Base Excess	Chloride	Calcium
Potassium	Sodium	Lactate	Hematocrit
Hemoglobin	Platelet	White Blood Cells	Albumin
Anion Gap	Bicarbonate (HCO3)	PT	PTT
Glasgow Coma Scale	SpO2	BUN	Creatinine
INR	Bilirubin	SGOT (AST)	SGPT (ALT)
Urine Output	Mech. Ventilation		

A.2 DistDeD Architecture Details

In this section, we outline the motivation, design, and training of the various architectures used to formulate the DistDeD framework. To account for the irregularity and temporal dependence of the observations made with the medical data, we encode the data using an online Neural Controlled Differential Equation (NCDE).

Table 3: MIMIC-IV Sepsis Cohort Statistics: `Median` (25% - 75% quantiles)

Variable	MIMIC ($n = 6188$)	Variable	MIMIC ($n = 6,188$)
Demographics		**Outcomes**	
Age, years	68.0 (57.0.-80.0)	Deceased	836 (13.51%)
Age range, years		Vasopressors administered	2241 (36.2%)
18-29	171 (2.8%)	Fluids administered	6032 (97.5%)
30-39	269 (4.3%)	Ventilator used	2201 (35.6%)
40-49	414 (6.7%)		
50-59	911 (14.7%)		
60-69	1426 (23%)		
70-79	1332 (21.5%)		
80-89	1207 (19.5%)		
$\geq$90	458 (7.4%)		
Gender			
Male	3251 (52.54%)		
Female	2937 (47.46%)		
Physical exam findings			
Temperature (°C)	36.8 (36.6-37.3)		
Weight (kg)	75.7 (63.1-91.0)		
Height (cm)	168.0 (160.0-177.0)		
Heart rate (beats per minute)	88.0 (76.0-103.0)		
Respiratory rate (breaths per minute)	20.0 (16.0-24.0)		
Systolic blood pressure (mmHg)	112.0 (100.00-127.0)		
Diastolic blood pressure (mmHg)	61.0 (52.0-70.0)		
Mean arterial pressure (mmHg)	75.8 (60.8-90.8)		
Fraction of inspired oxygen (%)	74.0 (66.0-84.0)		
P/F ratio	165.0 (104.2-258.0)		
Glasgow Coma Scale	15.0 (14.0-15.0)		
Laboratory findings			
Hemotology		Coagulation	
White blood cells (thousands/μL)	10.9 (7.0-16.4)	Prothrombin time (sec)	15.1 (13.3-18.5)
Platelets (thousands/μL)	160.0 (97.0-240.0)	Partial thromboplastin time (sec)	33.2 (28.5-41.8)
Hemoglobin (mg/dL)	9.5 (8.2-10.9)	INR	1.4 (1.2-1.7)
Hematocrit (mg/dL)	28.8 (25.2-33.0)		
Base Excess (mmol/L)	-1.0 (-6.0-1.0)		
Chemistry		Blood gas	
Sodium (mmol/L)	136.0 (132.0-140.0)	Arterial pH	7.3 (7.2-7.4)
Potassium (mmol/L)	4.2 (3.7-4.9)	Oxygen saturation (%)	92.0 (74.0-97.0)
Calcium (mg/L)	1.1 (0.9-1.2)	SpO2 (%)	97.0 (95.0-99.0)
Chloride (mmol/L)	106.0 (102.0-111.1)	Partial pressure of O2 (mmHg)	77.0 (48.0-111.0)
Bicarbonate (mmol/L)	22.0 (19.0-25.0)	Partial pressure of CO2 (mmHg)	42.0 (35.0-50.0)
Blood urea nitrogen (mg/dL)	25.0 (15.0-43.0)		
Creatinine (mg/dL)	1.1 (0.7-1.9)		
Albumin (mg/dL)	2.8 (2.4-3.2)		
Anion Gap (mmol/L)	14.0 (12.0-17.0)		
Glucose (mg/dL)	138.0 (106.0-189.0)		
SGOT (units/L)	52.0 (27.0-122.0)		
SGPT (units/L)	39.0 (19.0-102.0)		
Lactate (mg/L)	1.9 (1.3-3.3)		
Total bilirubin (mg/L)	0.9 (0.5-2.5)		

This provides a fixed dimensional state representation at each time step (here, aggregated by hour), to align with the frequency of treatment decisions. The encoded state representations are then used as input into the independent implicit quantile networks (IQN), used to represent the D- and R- Networks to estimate the risk of encountering a dead-end.

Training We train the NCDE for state construction as well as the IQN instantiations for the D-, and R-Networks in an offline manner. All models are trained with 75% of the data (4,014 surviving patients, 627 patients who died),validated with 5% (268 survivors, 42 nonsurvivors), and we report all results on the remaining held out 20% (1,070 survivors, 167 nonsurvivors). In order to account for the data imbalance between positive and negative outcomes, we follow a similar training procedure as DeD (Fatemi et al., 2021) where every sampled minibatch is ensured to contain a proportion of terminal transitions from non-surviving

patient trajectories. This amplifies the training for conditions that lead to negative outcomes, ensuring that the D- and R- Networks are able to recognize scenarios that carry risk of encountering dead-ends.[3]

A.2.1 Neural Controlled Differential Equation

Neural Differential Equations (NDEs; Chen et al. (2018)) have become a popular modeling framework for handling complex temporal data due to their flexibility and the ability to model data in continuous time. In particular, they are well matched for irregularly sampled (e.g. partially observed) data such as is common in healthcare. NDEs learn a continuous latent representation of the dynamics underlying the observed data in a fixed dimension representation; adapting for missingness, various periodic frequencies among features, as well as complex interactions between features (Kidger, 2022). These reasons provide a distinct motivation for using NDEs for processing fixed representations of healthcare data.

In this work we use a variant of NDE, Neural Controlled Differential Equations (NCDE; Morrill et al. (2021)). NCDEs are designed to process irregular time series with a latent process that affects the evolution of the observed features. The particular variant of NCDE we use is designed to operate in online settings, only incorporating historical information to encode representations of the current time step. This is a departure from standard NDE methods that execute a forward-backward time of autoregression when representing the latent dynamics of the time series. By restricting ourselves to online types of processing, we honor the reality with which data is received in a healthcare setting which leads to a more realistic implementation. Otherwise, we may risk biasing the inference over missing data intervals using future observations. For specific algorithmic details of the NCDE, we refer the reader to Morrill et al. (2021).

For our purposes, we train the NCDE as a continuous time autoencoder of the irregular patient observations. This provides a fixed dimension representation of a patient's state at hourly intervals, to match with the frequency of treatment decisions in our extracted data. Following procedures set forth by Morrill et al. (2021), we lightly pre-process the data with rectilinear interpolation (where each patient trajectory is handled independently) so as to signal when and where missing features occur. The NCDE is built around learning representations from an internal projection function (represented by a neural network), optimized using a differential equation solver. We fine-tuned the hyperparameters of this encoding function (most importantly the output embedding dimension) as well as optimization using `Ax` (Bakshy et al., 2018), an adaptive experimentation platform built on top of the `BoTorch` Bayesian Optimization library (Balandat et al., 2020).

When training the NCDE, we found that using a fixed learning rate with the Adam optimizer (Kingma & Ba, 2014) performed best. After 100 Bayesian Optimization trials, we found the following hyperparameter settings to provide the best performing NCDE model. For the encoding neural network, we used 2 layers with 80 hidden units in each with ReLU activations. The output dimension of this encoding network was 55, which provided the state representations then used as input to the Reinforcement Learning models. For optimization, the best learning rate was $5e-4$ over 30 epochs.

A.2.2 DistDeD Value Functions

As outlined in Section 4, we construct two MDPs for estimating the return for negative and positive outcomes independently. With these independent learning objectives, we construct two independent value estimators based on Implicit Q-Networks (Dabney et al., 2018). For specific details on the development and training of these architectures, we refer the reader to the source literature. In summary, quantiles of the approximated distribution of return are approximated with sampled particles from a uniform distribution, which are then transformed with a learned projection function (represented by a neural network) to construct the implicit distribution. When training, a separate copy of the network parameters are kept as a target network to ensure more stable updates (following the double DQN strategy (Hasselt et al., 2016)), a number of samples K are drawn from each distribution (the one we're optimizing and the target distribution), then using a Wasserstein metric the projected particles are brought closer together. To constrain the value estimates of this distribution from overestimation for actions not in the dataset, we include a CQL penalty (Kumar et al.,

---

[3]All code for data extraction and preprocessing as well as for defining and training the DistDeD models will be released upon publication.

Figure 9: The evolution of estimated values using DistDeD over the course of the recorded patient trajectories (72 hours in total prior to termination), represented as histograms. The top row corresponds to the D-Network while the bottom row is derived from the R-Network. Estimated values from non-surviving patients are plotted in blue while those from surviving patients are plotted in green.

2020) following Ma et al. (2021). There is a trade-off between maximizing the fit of the value distributions and the strength of the CQL regularization. We can modulate this by including a multiplicative weight β to the CQL penalty, which we treat as an additional hyperparameter.

As done when training the NCDE state constructor, we optimized the hyperparameters of the IQN models used to represent Z_D and Z_R in DistDeD, the CQL penalty weight, and optimization parameters using the `BoTorch` Bayesian Optimization library Balandat et al. (2020) through the `Ax` API (Bakshy et al., 2018). The best performing hyperparameters used to define the IQN and CQL penalty were chosen after running 100 optimization trials. For the IQN, the projection neural network accepted a 55 dimensional input (from the NCDE), consisted of 2 layers with 16 hidden units in each, using ReLU activations. The number of samples K drawn each optimization step was set to 64. The target network parameters were updated after every 5 optimization steps using an exponentially-weighted moving average with parameter τ set to 0.005. By construction, the discount rate γ is set to 1. For the weighting of the CQL penalty, $\beta = 0.035$. For optimization, we used Adam (Kingma & Ba, 2014) with the best performing learning rate found to be $2e-5$ over 75 epochs of training.

Of special note, the IQN architecture admits a family of risk-sensitive policies by constraining the space from which samples are drawn for the approximating distribution. The way the sampling space is constrained is called a distortion risk measure which influences the underlying value distributions to be more risk seeking or averse. By design, these distortion measures can be selected to influence the estimation of the implicit distributions over expected return. However, we chose not to bias the estimation of these distributions since we are deploying the IQN in an offline setting and cannot recover from a poor modeling choice through the acquisition of new data from the environment (following the optimism under uncertainty principle that guides much of RL). We therefore do not employ any distortion measures, evaluating the CVaR in a post-hoc manner so as to maximize the utility of the underlying distribution to represent the observed data.

Computing the CVaR To compute the CVaR of Z_D and Z_R, we evaluate the fully trained IQN models using held out test data. The full distributions are then sampled using $K_{test} = 1000$. We then sort the resultant estimated values for each particle and select the fraction of smallest values corresponding the the chosen value of α. For example, if $\alpha = 0.35$, we would then take the smallest 350 values of the 1000 samples. The $VaR_{\alpha=0.35}$ would be the maximum value of this subsampled portion of the estimated distribution. Then, the $CVaR_{\alpha=0.35}$ would be the average value of the 350 sample subset. We use this quantity then to compare with the DistDeD thresholds δ_D and δ_R to determine whether or not an action should be avoided or whether the state is a dead-end as outlined in Section 4.

A.3 Additional Experimental Analysis

A.3.1 Preliminary selection of decision thresholds

In Figure 9 we present a visual summary of how the thresholds δ_D and δ_R are empirically determined. Conceptually, we want to select thresholds that minimize the number of "false positives" that occur, meaning we don't want to unnecessarily flag trajectories arising from patients who ultimately survived. We plot the histograms of the assessed values for both non-surviving (blue) and surviving (green) patients for both the

	Non-Surviving Patients		Surviving Patients	
α	DeD	DistDeD	DeD	DistDeD
0.05	59.281	4.790	88.982	20.074
0.1	59.281	8.982	88.982	30.439
0.15	59.281	10.180	88.982	37.721
0.2	59.281	12.574	88.982	44.071
0.25	59.281	13.772	88.982	49.393
0.3	59.281	15.569	88.982	54.435
0.35	59.281	17.964	88.982	57.330
0.4	59.281	19.760	88.982	60.598
0.45	59.281	21.557	88.982	63.772
0.5	59.281	22.754	88.982	66.013
0.55	59.281	23.952	88.982	68.627
0.6	59.281	26.347	88.982	70.588
0.65	59.281	28.144	88.982	72.549
0.7	59.281	30.539	88.982	74.510
0.75	59.281	31.737	88.982	76.657
0.8	59.281	34.131	88.982	78.711
0.85	59.281	35.329	88.982	79.925
0.9	59.281	36.527	88.982	80.486
0.95	59.281	38.323	88.982	81.979
1.0	59.281	41.916	88.982	83.660

Table 4: Percentage of Patient Trajectories Missed. For DistDeD, $\delta_D = -0.5$, $\delta_R = 0.5$

D-Network (top) and R-Network (bottom) using the validation set. To visualize how the estimated values change throughout the recorded trajectory (max 72 hours before termination) we also look at successive time periods when plotting the histograms. Unsurprisingly, as the trajectories near termination, the states from non-surviving patients have lower estimated value (being near to death). The choice of threshold is made to provide as early of an separation of the estimated values between non-surviving and surviving patient as possible.

While this approach carries some precedence, as it follows that done by Fatemi et al. (2021), but it's clear how tedious and in-exact this process is. This is what led to the analysis provided in Section 6.2.2, where we evaluated all possible settings of the thresholds when constructing the ROC curves in Figure 7. By providing the full information of possible precision and anticipated risk of false-positives, we enable the human expert to tune DistDeD according to the characteristics of the task. We suggest that this is a far superior approach to selecting the δ_D and δ_R.

A.3.2 DistDeD recovers risky trajectories overlooked by DeD

While confirming the analysis underlying the results presented in Section 6.2.1, we were surprised to find that a significant number of non-surviving patient trajectories went undetected by DeD. In fact, nearly 60% of this high-risk subpopulation registered no indication from the prior dead-end discovery method. In Table 4 we present the proportion of trajectories (both non-suriving and surviving) where a flag is not raised for their duration, comparing between DeD and DistDeD. We also evaluated a range of α values used to calculate the CVaR of the estimated return distribution. We see that as α decreases, corresponding to a more conservative estimation of risk, that fewer non-surviving patient trajectories are missed at a cost of flagging more surviving patients. In concert with the results presented in Section 6.2.2, this table helps characterize the trade-off with early warning and the number of "false positives" that DistDeD provides. By providing this full range of options as an immediate consequence of the design of DistDeD, we empower the human decision maker to select the best setting of our proposed framework for their use-case.