Image2SSM: Localization-aware Deep Learning Framework for Statistical Shape Modeling Directly from Images

Abstract

Statistical Shape Modelling (SSM) is an effective tool for quantitatively analyzing anatomical populations. SSM has benefitted largely from advances in deep learning where statistical representations of anatomies (e.g., point distribution models or PDMs) are inferred directly from images, alleviating the need for a time-consuming and expensive workflow of anatomy segmentation, shape registration, and model optimization. Nonetheless, to date, existing deep learning methods do not consider the rigid pose transformation of shapes or anatomy of interest. They also require a tight bounding box to be defined over the image of anatomy-of-interest before feeding the image to the deep network for network training and inference. In this paper, we propose a deep learning framework that simultaneously detects and segments the anatomy of interest, estimate the rigid transformation with respect to the population mean (average) using a spatial transformer, and estimates the corresponding statistical representation of that anatomy, all directly from unsegmented 3D image without the need for any additional supervision. Furthermore, we leverage the segmentation task to provide an attention model for the sub-network that estimates shape representation, giving more accurate shape statistics for shape analysis.

Keywords: Statistical Shape Modeling, Deep Learning, Anatomy Segmentation

1. Introduction

Statistical Shape Modeling (SSM) effectively quantifies and characterizes the variations of anatomical shapes. SSM has enabled various biomedical and clinical applications in neuroscience (Gerig et al., 2001), orthopedics (Harris et al., 2013; Atkins et al., 2019), cardiology and biological phenotyping; such as implant design (Kozic et al., 2010) and growth modeling (Datar et al., 2009; Atkins et al., 2017). A popular approach for shape analysis is using landmarks defined by correspondences across the population of shapes. Most recent works (Sarkalkan et al., 2014; Cates et al., 2017; Tóthová et al., 2018) use dense correspondences placed automatically i.e., point distribution models (PDMs) via optimization for shape modeling that can then be turned into low-dimension shape representation by principal component analysis (PCA), thus reducing the need for expert intervention to mark distinct features, which can often be time and cost-consuming.

Conventional SSM methods still require an expert-driven workflow of anatomy segmentation, shape registration, optimization of population-level shape representations, and significant parameter tuning. This has motivated the recent surge of deep learning based methods that estimate statistical representations of shape directly from images (Bhalodia et al., 2018b,a; Adams et al., 2020; Adams and Elhabian, 2022; Tao et al., 2022; Huang et al., 2017; Milletari et al., 2017; Xie et al., 2016; Zheng et al., 2015; Raju et al., 2022),

deep networks can learn to regress shape information directly from images while learning complex functional mappings and incorporating any other prior knowledge required. These methods remove most of the manual overhead needed to estimate an SSM from unsegmented images once a deep network is trained and have shown to perform statistically similarly to traditional SSM methods in downstream tasks (Bhalodia et al., 2018b); nonetheless, these methods still require some pre-processing in the form of indicating the anatomy location, defining a tight bounding box around the anatomy of interest, and aligning the given image to the model's mean. Specifically, images are assumed to be cropped around the anatomy of interest and manually delineating the bounding box of the anatomy is also assumed during model inference. These methods also do not provide the rigid pose information; thus they are only applicable in constrained and limited setups. This is considered as a barrier when deploying these methods as a fully automated alternative to conventional SSM methods.

In this paper, we propose Image2SSM, an end-to-end deep learning framework that simultaneously extracts the tight bounding box over the shape of interest from a complete image, transforms it to match the mean shape, and uses this to extract statistical shape representation. Image2SSM comprises of three subnetworks that are trained end-to-end; a segmentation subnetwork, a registration subnetwork, and a shape regression subnetwork. Specifically, Image2SSM first performs anatomy segmentation using the segmentation subnetwork to localize the anatomy and provide an attention map for the shape regression subnetwork to estimate shape statistics from images. Then a spatial transformer does an affine registration of the cropped region (based on the output of the segmentation subnetwork) to match the mean shape, which is then passed to the shape regression subnetwork that learns the functional mapping from image features to a low-dimensional shape representation. Given a new image, Image2SSM alleviates any manual input required for model inference. In addition, as Image2SSM is a multi-task network, it provides significant accuracy improvements compared to using cropped images for estimating shape descriptors. Moreover, Image2SSM is also orthogonal to existing deep learning methods (Adams et al., 2020; Adams and Elhabian, 2022; Tao et al., 2022; Huang et al., 2017; Xie et al., 2016; Zheng et al., 2015) where it can be integrated in a straighforward manner by replacing the shape regression subnetwork by any of these methods.

2. Methods

Given a dataset of N samples, we denote the unsegmented 3D images $\{\mathbf{I}_n\}_{n=1}^{N}$ where $\mathbf{I}_n \in \mathbb{R}^{H \times W \times D}$. The corresponding segmentations are denoted $\{\mathbf{S}_n\}_{n=1}^{N}$ where $\mathbf{S}_n \in \mathbb{R}^{H \times W \times D}$. The set of corresponding PDMs comprised of M world 3D correspondence points is denoted $\{\mathbf{p}_n\}_{n=1}^{N}$ where $\mathbf{p}_n \in \mathbb{R}^{3M}$, which are essentially coordinates representing the population-level statistical shape information after removing global alignment differences across samples in the given cohort. The proposed network maps the volumetric image $\mathbf{I}_n$ to correspondences $\mathbf{p}_n$ in an end-to-end manner.

First $\hat{\mathbf{S}}_n$ is predicted from $\mathbf{I}_n$ via a segmentation sub-network and the excess background is cropped out, resulting in $\hat{\mathbf{S}}'_n$. Next, a spatial transformer sub-network does an affine registration of the cropped $\hat{\mathbf{S}}'_n$ to match the mean shape. The output of this step is denoted $\hat{\mathbf{S}}''_n$. The cropped, aligned segmentation, $\hat{\mathbf{S}}''_n$, is then passed to a shape regression sub-network

to output predicted correspondences $\hat{\mathbf{p}}_n$. An overview diagram is provided in Figure 1 and the sub-networks are described in the following sections.

Figure 1: *Image2SSM Network Architecture.*

2.1. Segmentation sub-network

The segmentation sub-network utilizes a 3D UNet (Ronneberger et al., 2015; Çiçek et al., 2016) architecture to segment the anatomy of interest from the volumetric image (i.e., predict $\mathbf{S}_n$ from $\mathbf{I}_n$).

$$L_{seg} = -\frac{1}{N} \sum_{i=1}^{N} \mathbf{S}_n \cdot \log \hat{\mathbf{S}}_n + (1 - \mathbf{S}_n) \cdot \log(1 - \hat{\mathbf{S}}_n) \tag{1}$$

The excess background is then cropped from the segmentation, resulting in $\hat{\mathbf{S}}'_n$. This identical cropping is also applied to the input image, resulting in $\mathbf{I}'_n$.

2.2. Registration sub-network

In the registration sub-network a spatial transformer (Jaderberg et al., 2015) is used to transform the segmented shape to enhance the model's geometric invariance. It learns a rigid transformation (parameterized by θ_n) from $\hat{\mathbf{S}}'_n$ to the mean shape, $\overline{\mathbf{S}} = \frac{1}{N} \sum_n \mathbf{S}'_n$.

The rigid spatial transform, θ_n is then applied to the cropped segmentation $\hat{\mathbf{S}}'_n$, resulting in $\hat{\mathbf{S}}''_n$. This transform is additionally applied to the cropped input image $\mathbf{I}'_n$, resulting in $\mathbf{I}''_n$. The registration sub-network optimized MSE loss (L_{reg}) between mean shape, $\overline{\mathbf{S}}$ and transformed cropped anatomy segmentation $\hat{\mathbf{S}}''_n$.

$$L_{reg} = \frac{1}{N} \left(\overline{\mathbf{S}} - \hat{\mathbf{S}}''_n \right)^2 \tag{2}$$

2.3. Attention Map

We apply a Gaussian Filter (kernel size = 5 & $\sigma = 2$) on the transformed cropped anatomy segmentation $(\hat{\mathbf{S}}''_n)$, which acts as an attention map and is added with transformed cropped anatomy image $(\mathbf{I}''_n)$ resulting in $\mathbf{C}_n$.

$$\mathbf{C}_n = \frac{1}{\sqrt{2\pi}\sigma} \exp^{-\frac{(\hat{\mathbf{S}}''_n)^2}{2\sigma^2}} \cdot \max(\mathbf{I}''_n) + \mathbf{I}''_n \tag{3}$$

2.4. Shape sub-network

We based our shape sub-network on DeepSSM (Bhalodia et al., 2018a). It is a set of 2 fully-connected layers that takes the result from the Gaussian Filter $(\mathbf{C}_n)$ and regress to the PCA scores $\mathbf{z}_n$. The PCA score is passed through another linear fully-connected layer with the weights fixed as the eigenvectors and the bias as the mean shape, and hence giving us an estimate of the world correspondences $\mathbf{p}_n$. The shape sub-network optimizes the MSE loss (L_w) between the estimated and the original world correspondences.

$$L_w = \frac{1}{M}(\hat{\mathbf{p}_n} - \mathbf{p}_n)^2 \tag{4}$$

The final loss is given by -

$$L = \lambda_{seg}L_{seg} + \lambda_{reg}L_{reg} + \lambda_w L_w \tag{5}$$

The proposed network is trained in a stepwise manner, initially only training for segmentation ($\lambda_{seg} = 100$, $\lambda_{reg} = \lambda_w = 0$) for first ten epochs. Then the weight corresponding to the registration loss (λ_{reg}) is increased and network is trained for ten more epochs. Finally incrementally increasing λ_w until a certain value. Overall we train the network for 200 epochs; PyTorch is used in constructing and training the network with Adam (Kingma and Ba, 2014) optimizer and a learning rate of 2e-3 for the first ten epochs, then 1e-5 with step learning rate decay. The weights of the network are initialized by He initialization (He et al., 2015).

3. Results

We compare our results with two baseline approaches (Bhalodia et al., 2018a, 2021), DeepSSM$_c$ and DeepSSM$_f$. In DeepSSM$_f$ we use full images (as in our work) for training whereas in DeepSSM$_c$, we crop the image to extract the anatomy as a pre-processing. By comparing these baselines, we showcase that Image2SSM performs better or comparatively to the networks trained separately. For each dataset, we evaluate the performance of each model by comparing the predicted world points to their ground truths and computing the root mean squared error (RMSE) averaged over each dimension. We also reconstruct mesh from the predicted and ground truth points and evaluate the surface-to-surface distance.

3.1. Supershapes

We used a 3D supershapes dataset as a proof of concept. Supershapes can be parametrized by three variables, two define the curvature and the last for the number of lobes. We generate 2000 shapes with random curvature and number of lobes between 4-10 choosen randomly. These shapes are randomly oriented and at a random position in a 128x128x128 size image. Additive Gaussian noise is added, and the images are blurred with a Gaussian filter to mimic diffuse shape boundaries. We form the initial PDM with 32 points from complete data using the Shapeworks software (Cates et al., 2017) and use 6 PCA components to capture 72% of shape variability. We use 1800 examples for training and rest for testing.

The box plots for unseen test data representing the Euclidean distance error per-point

(a) $\qquad\qquad\qquad\qquad$ (b)

Figure 2: Supershapes. **(a) RMSE for world points (mm)**: *Euclidean distance between ground truth points and points obtained from predictions across all test samples.* **(b) Surface-to-surface distance (mm)**: *Computed between reconstructed mesh using ground truth points and points obtained from predictions across all test samples.*

per-shape is shown in Figure 2(a); and the one representing surface-to-surface distance for reconstructed mesh is shown in Figure 2(b). We can see that our method performs comparably or better to the baselines. We have also provided the surface-to-surface distance visualization of reconstructed mesh for best, median and worst cases in the test set in Figure 3.

3.2. Left Atrium

We apply our network on the Left Atrium MRI dataset. The data has a total of 1006 images that vary significantly in intensity and quality, more so due to topological variants pertaining to pulmonary veins arrangements. We divide the data into train and test sets. We form the initial PDM with 1024 points using the Shapeworks software (Cates et al., 2017) from training data (914 examples) and use 300 PCA components to capture 97% of

Figure 3: Supershapes. **Surface to surface distance (mm) visualization**: *Shape reconstruction error interpolated as a heatmap on ground truth reconstructed meshes. Best, Median and Worst case result on Image2SSM.*

shape variability. Note that the test data is kept separate while generating the initial PDM; this is done to ensure that the test data remains completely unseen.

The box plots for unseen test data representing the Euclidean distance error per-point

(a) (b)

Figure 4: Left Atrium. **(a) RMSE for world points (mm)**: *Euclidean distance between ground truth points and points obtained from predictions across all test samples.* **(b) Surface-to-surface distance (mm)**: *Computed between reconstructed mesh using ground truth points and points obtained from predictions across all test samples.*

per-shape is shown in Figure 4(a); and the one representing surface-to-surface distance for reconstructed mesh is shown in Figure 4(b). We can see that our method performs comparably or better to the baselines, primarily as localizing the anatomy provides a strong prior for identifying world points. We have also provided the surface-to-surface distance visualization of reconstructed mesh for best, median and worst cases in the test set in Figure 5.

4. Conclusion

Image2SSM is an end-to-end deep learning framework for extracting the population shape representation in the form of world correspondence. It offers a novel approach for deep learning based shape modeling that simultaneously detects and segments the anatomy of interest, performs rigid transformation with respect to mean shape and predicts the statistical representation of the anatomy. Our work alleviates any manual input required for model inference while also significantly improving the accuracy. We compare our work to the baseline DeepSSM models and find that the qualitative and quantitative performance of the proposed model is better or comparable with the baselines on two different datasets. Additionally, the proposed method can be readily integrated with other deep learning based shape modeling methods by replacing the shape regression sub-network and improve upon the accuracy of those methods.

Figure 5: Left Atrium. **Surface to surface distance (mm) visualization**: *Shape recon-
struction error interpolated as a heatmap on ground truth reconstructed meshes.
Best, Median and Worst case result on Image2SSM.*

Acknowledgments

Acknowledgments withheld.

References

Jadie Adams and Shireen Elhabian. From images to probabilistic anatomical shapes: A deep variational bottleneck approach. *arXiv preprint arXiv:2205.06862*, 2022.

Jadie Adams, Riddhish Bhalodia, and Shireen Elhabian. Uncertain-deepssm: From images to probabilistic shape models. In *International Workshop on Shape in Medical Imaging*, pages 57–72. Springer, 2020.

Penny R Atkins, Shireen Y Elhabian, Praful Agrawal, Michael D Harris, Ross T Whitaker, Jeffrey A Weiss, Christopher L Peters, and Andrew E Anderson. Quantitative comparison of cortical bone thickness using correspondence-based shape modeling in patients with cam femoroacetabular impingement. *Journal of Orthopaedic Research*, 35(8):1743–1753, 2017.

Penny R Atkins, YoungJae Shin, Praful Agrawal, Shireen Y Elhabian, Ross T Whitaker, Jeffrey A Weiss, Stephen K Aoki, Christopher L Peters, and Andrew E Anderson. Which two-dimensional radiographic measurements of cam femoroacetabular impingement best describe the three-dimensional shape of the proximal femur? *Clinical Orthopaedics and Related Research*, 477(1):242, 2019.

Riddhish Bhalodia, Shireen Y Elhabian, Ladislav Kavan, and Ross T Whitaker. Deepssm: a deep learning framework for statistical shape modeling from raw images. In *International Workshop on Shape in Medical Imaging*, pages 244–257. Springer, 2018a.

Riddhish Bhalodia, Anupama Goparaju, Tim Sodergren, Alan Morris, Evgueni Kholmovski, Nassir Marrouche, Joshua Cates, Ross Whitaker, and Shireen Elhabian. Deep learning for end-to-end atrial fibrillation recurrence estimation. In *2018 Computing in Cardiology Conference (CinC)*, volume 45, pages 1–4. IEEE, 2018b.

Riddhish Bhalodia, Shireen Elhabian, Jadie Adams, Wenzheng Tao, Ladislav Kavan, and Ross Whitaker. Deepssm: A blueprint for image-to-shape deep learning models. *arXiv preprint arXiv:2110.07152*, 2021.

Joshua Cates, Shireen Elhabian, and Ross Whitaker. Shapeworks: particle-based shape correspondence and visualization software. In *Statistical Shape and Deformation Analysis*, pages 257–298. Elsevier, 2017.

Özgün Çiçek, Ahmed Abdulkadir, Soeren S Lienkamp, Thomas Brox, and Olaf Ronneberger. 3d u-net: learning dense volumetric segmentation from sparse annotation. In *International conference on medical image computing and computer-assisted intervention*, pages 424–432. Springer, 2016.

Manasi Datar, Joshua Cates, P Thomas Fletcher, Sylvain Gouttard, Guido Gerig, and Ross Whitaker. Particle based shape regression of open surfaces with applications to

developmental neuroimaging. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 167–174. Springer, 2009.

Guido Gerig, Martin Styner, D Jones, Daniel Weinberger, and Jeffrey Lieberman. Shape analysis of brain ventricles using spharm. In *Proceedings IEEE Workshop on Mathematical Methods in Biomedical Image Analysis (MMBIA 2001)*, pages 171–178. IEEE, 2001.

Michael D Harris, Manasi Datar, Ross T Whitaker, Elizabeth R Jurrus, Christopher L Peters, and Andrew E Anderson. Statistical shape modeling of cam femoroacetabular impingement. *Journal of Orthopaedic Research*, 31(10):1620–1626, 2013.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

Weilin Huang, Christopher P Bridge, J Alison Noble, and Andrew Zisserman. Temporal heartnet: towards human-level automatic analysis of fetal cardiac screening video. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 341–349. Springer, 2017.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, et al. Spatial transformer networks. *Advances in neural information processing systems*, 28, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Nina Kozic, Stefan Weber, Philippe Büchler, Christian Lutz, Nils Reimers, Miguel Á González Ballester, and Mauricio Reyes. Optimisation of orthopaedic implant design using statistical shape space analysis based on level sets. *Medical image analysis*, 14 (3):265–275, 2010.

Fausto Milletari, Alex Rothberg, Jimmy Jia, and Michal Sofka. Integrating statistical prior knowledge into convolutional neural networks. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 161–168. Springer, 2017.

Ashwin Raju, Shun Miao, Dakai Jin, Le Lu, Junzhou Huang, and Adam P Harrison. Deep implicit statistical shape models for 3d medical image delineation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 2135–2143, 2022.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

Nazli Sarkalkan, Harrie Weinans, and Amir A Zadpoor. Statistical shape and appearance models of bones. *Bone*, 60:129–140, 2014.

Wenzheng Tao, Riddhish Bhalodia, and Shireen Elhabian. Learning population-level shape statistics and anatomy segmentation from images: A joint deep learning model. *arXiv preprint arXiv:2201.03481*, 2022.

Katarína Tóthová, Sarah Parisot, Matthew CH Lee, Esther Puyol-Antón, Lisa M Koch, Andrew P King, Ender Konukoglu, and Marc Pollefeys. Uncertainty quantification in cnn-based surface prediction using shape priors. In *International Workshop on Shape in Medical Imaging*, pages 300–310. Springer, 2018.

Jin Xie, Guoxian Dai, Fan Zhu, Edward K Wong, and Yi Fang. Deepshape: Deep-learned shape descriptor for 3d shape retrieval. *IEEE transactions on pattern analysis and machine intelligence*, 39(7):1335–1345, 2016.

Yefeng Zheng, David Liu, Bogdan Georgescu, Hien Nguyen, and Dorin Comaniciu. 3d deep learning for efficient and robust landmark detection in volumetric data. In *International conference on medical image computing and computer-assisted intervention*, pages 565–572. Springer, 2015.