Learning More Effective Cell Representations Efficiently

Abstract

Capturing similarity among cells is the core of many tasks in single-cell transcriptomics, such as the identification of cell types and cell states. This problem can be formulated in a paradigm called metric learning. Metric learning aims to learn data embeddings (feature vectors) in a way that reduces the distance between feature vectors corresponding to cells belonging to the same cell type and increases the distance between the feature vectors corresponding to different cell types. Deep metric learning on the other hand uses neural networks to automatically learn discriminative features from the cells and then compute the metric. The (deep) metric learning approaches have been successfully applied to computational biology tasks like similar cell identification and synthesis of heterogeneous single-cell modalities. We identify two computational challenges: precise distance measurement between cells and scalability over a large amount of data in the applications of (deep) metric learning. And then we propose our solutions: optimal transport and coreset optimization. Optimal transport has the potential to measure cell similarity more effectively and coreset optimization is promising to train representation learning models more efficiently. Empirical studies in image retrieval and clustering tasks show the promise of the proposed approaches. We propose to further explore the applicability of our methods to cell representation learning.

1 Introduction

The success of machine learning algorithms largely depends on data representation. Metric learning learns data embeddings and feature vectors in a way that reduces the distance between feature vectors corresponding to objects belonging to the same class and increases the distance between the feature vectors corresponding to different classes. Deep metric learning, on the other hand, uses neural networks to automatically learn discriminative features from the objects and then compute the metric. (Deep) metric learning falls into the broad umbrella of representation learning, whose quest for representation learning is motivating the design of more powerful representation [1, 8].

These representation learning methods have achieved great successes in biology applications [28, 30, 19, 13, 15, 19, 24, 15, 32]. For example, Schema [28] uses a principled metric learning strategy to identify informative features in a modality to synthesize disparate modalities into a single coherent interpretation. It is used to infer cell types by integrating gene expression and chromatin accessibility data. The deep metric learning framework SCimilarity (Invited Talk "Design for Inference in Drug Discovery and Development" by Aviv Regev, ICML 2022), which employs a standard triplet loss design, has achieved impressive performance in identifying similar cells in a massive collection of scRNA-Seq datasets. The results can help answer questions like in which tissues and diseases we find fibrotic macrophage-like cells.

Figure 1: Overview of the Deep Wasserstein Metric Learning Framework

[9] proposes the Deep Wasserstein Metric Learning Framework, as shown in Figure 1, which conducts multiple steps of adjustments over the original metric learning framework and achieves improved performance in image retrieval and clustering tasks. In the rest of the proposal, we introduce the adjustments accordingly and design empirical studies for single-cell applications.

2 Methods

2.1 Representation Learning: Metric Learning and Deep Metric Learning

Representation learning is a class of machine learning approaches that allow a system to discover the representations required for feature detection or classification from raw data [12, 16, 11, 10, 7]. The requirement for manual feature engineering is reduced by allowing a machine to learn the features and apply them to a given activity. Metric learning and deep metric learning, specifically, focus on similarity-based approaches to learning the representations. Thus the similarity measurement becomes very important. Metric learning has only limited capability to capture non-linearity in the data, while deep metric learning captures non-linear features better by learning the non-linear transformation. In the following, we present two adjustments that can improve metric learning's performances, one is optimal transport [6], and one is coreset optimization [20].

2.2 Optimal Transport

The most widely used loss functions for deep metric learning are the contrastive loss and the triplet loss, both use euclidean distance to measure the distance between objects. A more comprehensive illustration of so-called "ranking-based" loss functions are summarized in Figure 2. Optimal transport (OT) is the general problem of moving one distribution of mass to another as efficiently as possible [29, 9, 23, 31]. Optimal transport has been used tremendously in computational biology [27, 26]. For example, [27] uses scRNA-seq data collected across a time course to infer how these probability distributions evolve over time, by using the mathematical approach of optimal transport.

Wasserstein distance provides a mathematical tool to measure distances between functions, histograms, or more general objects in the optimal transport problem. Wasserstein distance is also called Earth Mover's Distance, which is employed to develop PhEMD (Phenotypic Earth Mover's Distance) [4], which is used to embed the space of drug perturbations on the basis of the drugs' effects on cell populations. Wasserstein distance-based loss functions have shown superior performance in learning tasks [14]. Thus a new set of loss functions are proposed to replace the Euclidean distance with Wasserstein distance in original contrastive loss and triplet loss by defining $d_w(x, y) = W_1(x, y)$. The new Wasserstein-contrastive (wcontrastive) loss and Wasserstein-triplet (wtriplet) loss can be formulated as the following [9]:

$$\mathcal{L}_{\text{wcontrastive}} = \frac{1}{b} \sum_{(i,j) \in \mathcal{P}}^{b} \mathbb{I}_{y_i = y_j} d_w(\phi_i, \phi_j) + \mathbb{I}_{y_i \neq y_j} \left[\gamma - d_w(\phi_i, \phi_j) \right]_+, \tag{1}$$

$$\mathcal{L}_{\text{wtriplet}} = \frac{1}{b} \sum_{\substack{(a,p,n) \in \mathcal{T} \\ y_a = y_p \neq y_n}}^{b} \left[d_w(\phi_a, \phi_p) - d_w(\phi_a, \phi_n) + \gamma \right]_+. \tag{2}$$

Figure 2: Illustration of different ranking-based loss functions. Different colors (blue, yellow, green) represent different classes. For simplicity, only 3 classes are shown. The left-most blue square is an anchor (query). In Contrastive loss, the anchor is compared with only one positive example. In Triplet loss, the anchor is compared with only one negative example and one positive example. In Npair, ProxyNCA, and Lifted Struct losses, one positive example and multiple negative classes are incorporated. Npair loss randomly selects one example per negative class. ProxyNCA loss pushes the anchor away from negative proxies instead of negative examples. The proxy is class-level and can represent any instance in the corresponding class. Lifted Struct loss uses all examples from all negative classes [10, 17].

We propose to apply the two new loss functions to similar cell identification and synthesis of heterogeneous modalities applications.

2.3 Coreset Optimization

Coreset optimization is about data-efficient methods to find subsets of massive data that can generalize to the full data when trained on. In other words, a coreset is a subset of the original training set that is representative to train machine learning models [9, 33, 21, 18]. More specifically, Wasserstein measure coreset [5], is an extension of coresets that takes into account continuous data distribution and generalization. Recently coreset has been successfully applied to the purification of single-cell transcriptomics data [22]. It focuses on alleviating potential replicate specific biases within single-cell datasets. The key is to select a "representative" subset (coreset) of cells from areas of the single-cell landscape where multiple replicates are represented. [28] processes data from a Slide-seq replicate (three modalities with 20823 transcriptomes * 17607 genes) in 34 mins. [20] demonstrates a specific coreset optimization algorithm CRAIG can achieve the average speedup of 3x for similar loss residual and error rate. So we expect for the single cell synthesis task in [28], we can reduce data processing time from 34 mins to 11 mins.

3 Experiments Design

The experiments conducted on various datasets have demonstrated that optimal transport and coreset optimization can achieve superior performance on image retrieval and clustering tasks [9, 10]. We plan to follow our setup in [19] to apply the methods on multiple single-cell datasets including sci-CAR cell line [2], SNARE-seq cell line [3], and 10X Multiome T-cell depleted bone marrow [25] to validate the methods' effectiveness and develop new computational and biological insights from the downstream tasks.

References

[1] Y. Bengio, A. Courville, and P. Vincent. Representation learning: A review and new perspectives, 2012.

[2] J. Cao, D. A. Cusanovich, V. Ramani, D. Aghamirzaie, H. A. Pliner, A. J. Hill, R. M. Daza, J. L. McFaline-Figueroa, J. S. Packer, L. Christiansen, F. J. Steemers, A. C. Adey, C. Trapnell, and J. Shendure. Joint profiling of chromatin accessibility and gene expression in thousands of single cells. *Science*, 361(6409):1380–1385, 2018.

[3] S. Chen, B. B. Lake, and K. Zhang. High-throughput sequencing of the transcriptome and chromatin accessibility in the same cell. *Nature Biotechnology*, 37(12):1452–1457.

[4] W. S. Chen, N. Zivanovic, D. van Dijk, G. Wolf, B. Bodenmiller, and S. Krishnaswamy. Embedding the single-cell experimental variable state space to reveal manifold structure of drug perturbation effects in breast cancer. *bioRxiv*, page 455436, 2018.

[5] S. Claici, A. Genevay, and J. Solomon. Wasserstein measure coresets, 2020.

[6] M. Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In *Advances in neural information processing systems*, pages 2292–2300, 2013.

[7] J. X. Dou and R. Bao. Clinical decision system using machine learning and deep learning: a survey.

[8] J. X. Dou, M. Jia, R. Bao, and H. H. Mao. Enhance 'similar'cell identification through optimal transport.

[9] J. X. Dou, L. Luo, and R. M. Yang. An optimal transport approach to deep metric learning (student abstract). In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 12935–12936, 2022.

[10] J. X. Dou, A. Q. Pan, Runxue Bao, H. H. Mao, and L. Luo. Sampling through the lens of sequential decision making. 2022.

[11] J. X. Dou, N. Sun, and X. Zou. "draw my topics": Find desired topics fast from large scale of corpus. *ArXiv*, abs/1602.01428, 2016.

[12] Y. Ektefaie, G. Dasoulas, A. Noori, M. Farhat, and M. Zitnik. Geometric multimodal representation learning, 2022.

[13] M. Flores, Z. Liu, T. Zhang, M. M. Hasib, Y.-C. Chiu, Z. Ye, K. Paniagua, S. Jo, J. Zhang, S.-J. Gao, et al. Deep learning tackles single-cell analysis—a survey of deep learning for scrna-seq analysis. *Briefings in Bioinformatics*, 23(1):bbab531, 2022.

[14] C. Frogner, C. Zhang, H. Mobahi, M. Araya, and T. A. Poggio. Learning with a wasserstein loss. *Advances in neural information processing systems*, 28, 2015.

[15] S. Grebinoski, Q. Zhang, A. R. Cillo, S. Manne, H. Xiao, E. A. Brunazzi, T. Tabib, C. Cardello, C. G. Lian, G. F. Murphy, et al. Autoreactive cd8+ t cells are restrained by an exhaustion-like program that is maintained by lag3. *Nature Immunology*, 23(6):868–877, 2022.

[16] W. L. Hamilton, R. Ying, and J. Leskovec. Representation learning on graphs: Methods and applications. *arXiv preprint arXiv:1709.05584*, 2017.

[17] S. Kim, D. Kim, M. Cho, and S. Kwak. Proxy anchor loss for deep metric learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3238–3247, 2020.

[18] T. Lin, Z. Zheng, E. Y. Chen, M. Cuturi, and M. I. Jordan. On projection robust optimal transport: Sample complexity and model misspecification. *arXiv preprint arXiv:2006.12301*, 2020.

[19] H. Mao, M. Jia, J. X. Dou, H. Zhang, and P. V. Benos. Coem: Cross-modal embedding for metacell identification, 2022.

[20] B. Mirzasoleiman, J. Bilmes, and J. Leskovec. Coresets for data-efficient training of machine learning models. In *International Conference on Machine Learning (ICML)*, July 2020.

[21] B. Mirzasoleiman, K. Cao, and J. Leskovec. Coresets for robust training of deep neural networks against noisy labels. *Advances in Neural Information Processing Systems*, 33, 2020.

[22] R. Pálovics, T. Wyss-Coray, and B. Mirzasoleiman. Purification of single-cell transcriptomics data with coreset selection.

[23] N. Papadakis. *Optimal transport for image processing*. PhD thesis, 2015.

[24] S. Paudel, B. E. Warner, R. Wang, J. Adams-Haduch, A. S. Reznik, J. X. Dou, Y. Huang, Y.-T. Gao, W.-P. Koh, A. Bäckerholm, J.-M. Yuan, and K. H. Y. Shair. Serological profiling using an Epstein-Barr virus mammalian expression library identifies EBNA1 IgA as a pre-diagnostic marker for nasopharyngeal carcinoma. *Clinical Cancer Research*, 09 2022. CCR-22-1600.

[25] S. Persad, Z.-N. Choo, C. Dien, I. Masilionis, R. Chaligné, T. Nawy, C. C. Brown, I. Pe'er, M. Setty, and D. Pe'er. Seacells: Inference of transcriptional and epigenomic cellular states from single-cell genomics data. *bioRxiv*, 2022.

[26] N. Prasad, K. Yang, and C. Uhler. Optimal transport using gans for lineage tracing, 2020.

[27] G. Schiebinger, J. Shu, M. Tabaka, B. Cleary, V. Subramanian, A. Solomon, J. Gould, S. Liu, S. Lin, P. Berube, et al. Optimal-transport analysis of single-cell gene expression identifies developmental trajectories in reprogramming. *Cell*, 176(4):928–943, 2019.

[28] R. Singh, B. L. Hie, A. Narayan, and B. Berger. Schema: metric learning enables interpretable synthesis of heterogeneous single-cell modalities. *Genome biology*, 22(1):1–24, 2021.

[29] R. Singh, J. S. S. Li, S. G. Tattikota, Y. Liu, J. Xu, Y. Hu, N. Perrimon, and B. Berger. Optimal transport analysis of single-cell transcriptomics directs hypotheses prioritization and validation. *bioRxiv*, 2022.

[30] A. Tanay and A. Regev. Scaling single-cell genomics from phenomenology to mechanism. *Nature*, 541(7637):331–338, 2017.

[31] H. Xu, J. Liu, D. Luo, and L. Carin. Representing graphs via gromov-wasserstein factorization. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2022.

[32] Q. Xu, Y. Yang, X. Zhang, and J. J. Cai. Association of pyroptosis and severeness of covid-19 as revealed by integrated single-cell transcriptome data analysis. *ImmunoInformatics*, 6:100013, 2022.

[33] Y. Yang, T. Y. Liu, and B. Mirzasoleiman. Not all poisons are created equal: Robust training against data poisoning. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 25154–25165. PMLR, 17–23 Jul 2022.