Understanding Benign Overfitting in Gradient-based Meta Learning

Abstract

Meta learning has demonstrated tremendous success in few-shot learning with limited supervised data. In those settings, the meta model is usually overparameterized. While the conventional statistical learning theory suggests that overparameterized models tend to overfit, empirical evidence reveals that overparameterized meta learning methods still work well – a phenomenon often called "benign overfitting." In an attempt to understand this phenomenon, we focus on the meta learning settings with a challenging bilevel structure that we term the gradient-based meta learning, and analyze its generalization performance under an overparameterized meta linear regression model. While our analysis uses the relatively tractable linear models, our theory contributes to understanding the delicate interplay among data heterogeneity, model adaptation and benign overfitting in gradient-based meta learning tasks. We corroborate our theoretical claims through numerical simulations.

1 Introduction

Meta learning, also referred to as "learning to learn", usually learns a prior model from multiple tasks so that the learned model is able to quickly adapt to unseen tasks. Meta learning has been successfully applied to few-shot learning and multi-task learning [2, 12, 20, 25, 37]. While there are many exciting meta learning methods today, in this paper, we will study a representative meta learning setting where the goal is to learn a shared initial model that can quickly adapt to task-specific models. This adaptation may take an explicit form such as the output of one gradient descent step, which is referred to as the model agnostic meta learning (MAML) method [20]. Alternatively, the adaptation step may take an implicit form such as the solution of another optimization problem, which is referred to as the implicit MAML (iMAML) method [33]. Since both MAML and iMAML will solve a bilevel optimization problem, we term them the *gradient-based meta learning* thereafter. In many cases, overparameterized models are used as the initial models in meta learning for quick adaptation. For example, ResNets-based MAML models typically have around 6 million parameters, but are trained on 1-3 million meta-training data [11]. Training such initial models is often difficult in meta learning because the number of training data is much smaller than the dimension of the model parameter.

Previous works on meta learning mainly focus on addressing the optimization challenges or analyzing the generalization performance with sufficient data [13, 17, 18]. Different from these works, we are particularly interested in the generalization performance of the sought initial model in practical scenarios where the total number of data from all tasks is *smaller than* the dimension of the initial model, which we term *overparameterized meta learning*. In those overparameterized regimes, the generalization error of meta learning models is not fully understood. Motivated by this, we ask:

Whether overparameterized meta learning models would lead to overfitting, provably?

Table 1: A comparison with closely related prior work on meta learning with linear models. "Reps." and "Gradient" refer to representation based methods and gradient-based methods; "Per-task" refers to the per-task level overparameterization and "Meta" refers to the meta level overparameterization.

Prior work	Type of meta learning		Overparameterization		Methods	Focus of analysis
	Reps.	Gradient	Per-task	Meta		
Bai et al. [3]		✓	✓		iMAML	Train-validation split
Bernacchia [6]		✓		✓	MAML	Optimal step size
Kong [27]	-	-	✓		-	Effect of small data tasks
Saunshi et al. [36]	✓		✓		-	Train-validation split
Sun et al. [39]	✓			✓	-	Optimal representation
Ours		✓		✓	MAML, iMAML	Benign overfitting

Empirical studies have demonstrated that the testing performance of MAML improves as the number of parameters increases [11] – a phenomenon often called "benign overfitting." Complementing this, we take an initial step by answering this theoretical question in the meta linear regression setting.

1.1 Prior art

We review prior art that we group in the following two categories.

Benign overfitting analysis. The empirical success of overparameterized deep neural networks has inspired theoretical studies of overparameterized learning. The most closest line of work is *benign overfitting* in linear regression [5], which provides excess risk that measures the difference between expected population risk of the empirical solution and the optimal population risk. Analysis of overparameterized linear regression model with the minimum-norm solution. It concludes that certain data covariance matrices lead to benign overfitting, explaining why overparameterized models that perfectly fit the noisy training data can work well during testing. The analysis has been extended to ridge regression [40], multi-class classification [43], and adversarial learning with linear models [8]. While previous theoretical efforts on benign overfitting largely focused on linear models, most recently, the analysis of benign overfitting has been extended to two-layer neural networks [7, 21, 28]. However, existing works mainly study benign overfitting for empirical risk minimization problems, rather than bilevel problems such as gradient-based meta learning, which is the focus of this work.

Meta learning. Early works of meta learning build black-box recurrent models that can make predictions based on a few examples from new tasks [2, 12, 25, 37], or learn shared feature representation among multiple tasks [38, 41]. More recently, meta learning approaches aim to find the initialization of model parameters that can quickly adapt to new tasks with a few number of optimization steps such as MAML [20, 32, 35]. The empirical success of meta learning has also stimulated recent interests on building the theoretical foundation of meta learning methods.

Generalization of meta learning. The *excess risk*, as a metric of generalization ability of gradient-based meta learning has been analyzed recently [3, 4, 9, 14, 18, 42]. The generalization of meta learning has been studied in [27] in the context of mixed linear regression, where the focus is on investigating when abundant tasks with small data can compensate for lack of tasks with big data. Generalization performance has also been studied in a relevant but different setting - representation based meta learning [13, 16]. Information theoretical bounds have been proposed in [10, 26], which bound the generalization error in terms of mutual information between the input training data and the output of the meta-learning algorithms. The PAC-Bayes framework has been extended to meta learning to provide a PAC-Bayes meta-population risk bound [1, 15, 19, 34]. These works mostly focus on the case where the meta learning model is underparameterized; that is, the total number of meta training data from all tasks is larger than the dimension of the model parameter. Recently, *overparameterized* meta learning has attracted much attention. Bernacchia [6] suggests that in overparameterized MAML, negative learning rate in the inner loop is optimal during meta training for linear models with Gaussian data. Sun et al. [39] shows that the optimal representation in representation-based meta learning is overparameterized and provides sample complexity for the method of moment estimator.

Compared to the most relevant works, our work is different in the following aspects. Compared to the works that also analyze generalization error or sample complexity in linear meta learning models such as [3, 9, 14], we focus on the overparameterized case when the total number of training data is smaller than the dimension of the model parameter. Compared to the work that focus on *representation-based* meta learning with a bilinear structure [39], we consider initialization-based meta learning methods

78 with a bilevel structure such as MAML and iMAML. Furthermore, we provide tight analysis of the
79 excess risk with explicit consideration of the benign overfitting condition.

80 A summary of key differences compared to prior art is provided in Table 1. We distinguish two differ-
81 ent overparameterization settings: i) the *per-task level overparameterization* where the dimension of
82 model parameter is larger than the number of training data per task, but smaller than the total number
83 of data across all tasks; and, ii) the *meta level overparameterization* where the dimension of model
84 parameter is larger than the total number of training data from all tasks.

1.2   This work

86 This paper provides a unifying analysis of the generalization performance for meta learning problems
87 with overparameterized meta linear models. To our best knowledge, this is the first work that provides
88 the condition for benign overfitting in gradient-based meta learning including MAML and iMAML.

89 **Technical challenges.**   Before we introduce the key result of our paper, we first highlight the
90 challenges of analyzing the generalization of gradient-based meta learning and characterizing its
91 benign overfitting condition, compared to the non-bilevel setting such as in [5, 39, 40].

92 **T1)** Due to the bilevel structure of gradient-based meta learning, the solution to the meta training
93 objective involves high order terms of data covariance. As a result, the dominating term in the excess
94 risk propagated from the label noise contains higher order terms, which is harder to quantify and can
95 potentially lead to orders of magnitude higher excess risk than the linear regression case [5, 39, 40].

96 **T2)** The existing analysis of benign overfitting [5, 40] critically relies on the monotonicity of the
97 eigenvalues of the solution matrix on the eigenvalues of the data matrix. However, due to the structure
98 of gradient-based meta learning and thus the solution matrix, this monotonicity is no longer true.

99 **T3)** Due to the multi-task learning nature of meta learning, the excess risk of MAML depends on the
100 heterogeneity across different tasks in terms of both the task data covariance and the ground truth task
101 parameter. As a result, the data covariance matrices from different tasks have different eigenvectors.
102 This is in contrast to the linear regression case where all the data follow the same distribution.

103 **Contributions.**   In view of challenges, our contributions can be summarized as follows.

C1) Focusing on the relatively tractable linear models, we derive the excess risk for the minimum-
norm solution to overparameterized gradient-based meta learning including MAML and
iMAML. Specifically, the excess risk upper bound adopts the following form

$$\text{Cross-task variance} + \text{Per-task variance} + \text{Bias}$$

where the *cross-task variance* quantifies the error caused by finite task number and the
variation of the ground truth task specific parameter, which is a unique term compared to
single task learning. The *bias* quantifies the bias resulting from the minimum-norm solution.
And the *per-task variance* quantifies the error caused by noise in the training data.

C2) We compare the benign overfitting condition for the overparameterized gradient-based meta
learning models and that for the empirical risk minimization (ERM) which learns a single
shared parameter for all tasks. We show that overfitting is more likely to happen in MAML
and its variants such as implicit MAML than in ERM. In addition, larger data heterogeneity
across tasks will make overfitting more likely to happen.

C3) We discuss the choice of hyperparameter, e.g., the step size in MAML and the weight of
the regularizer in iMAML, such that if the data leads to benign overfitting in ERM, it also
leads to benign overfitting in MAML and iMAML. We show that a negative step size can
preserve benign overfitting in MAML. This is complementary to the recent discovery that
the optimal step size of overparameterized MAML during training is negative [6].

2   Problem Formulation and Methods

122 In this section, we will introduce the problem setup and the considered meta learning methods.

123 **Problem setup.** In the meta-learning setting, assume task m is drawn from a task distribution, i.e.
124 $m \sim \mathcal{M}$. For each task m, we observe N samples with input feature $x_m \in \mathcal{X}_m \subset \mathbb{R}^d$ and target
125 label $y_m \in \mathcal{Y}_m \subset \mathbb{R}$ drawn i.i.d. from a task-specific data distribution $\mathcal{P}_m$. These samples are

collected in the dataset $\mathcal{D}_m = \{(x_{m,n}, y_{m,n})\}_{n=1}^N$, which is divided into the train and validation datasets, denoted as $\mathcal{D}_m^{\mathrm{tr}}$ and $\mathcal{D}_m^{\mathrm{va}}$. And $|\mathcal{D}_m^{\mathrm{tr}}| = N_{\mathrm{tr}}$ and $|\mathcal{D}_m^{\mathrm{va}}| = N_{\mathrm{va}}$ with $N = N_{\mathrm{tr}} + N_{\mathrm{va}}$. We use the empirical loss $\ell_m(\theta_m, \mathcal{D}_m)$ of per-task parameter $\theta_m \in \Theta_m$ as a measure of the performance. In this paper, we consider regression problems, where ℓ_m is defined as the mean squared error.

The goal for gradient-based meta learning methods, such as MAML [20] and iMAML [33], is to learn an initial parameter $\theta_0 \in \Theta_0$, which, with an adaptation method $\mathcal{A} : \Theta_0 \times (\mathcal{X}_m \times \mathcal{Y}_m)^{N_{\mathrm{tr}}} \to \Theta_m$, can generate a per-task parameter θ_m that performs well on the validation data for task m. Given M tasks, our meta-learning objective is computed as the average of the per-task objective, given by

$$\text{Meta training objective} \qquad \mathcal{L}^{\mathcal{A}}(\theta_0, \mathcal{D}) := \frac{1}{M} \sum_{m=1}^M \ell_m(\mathcal{A}(\theta_0, \mathcal{D}_m^{\mathrm{tr}}), \mathcal{D}_m^{\mathrm{va}}). \qquad (1)$$

Obtaining the empirical solution $\hat{\theta}_0^{\mathcal{A}}$ by minimizing (1) under a meta learning method $\mathcal{A}$, in the meta testing stage, we evaluate $\hat{\theta}_0^{\mathcal{A}}$ on the population risk, given by

$$\text{Meta testing objective} \qquad \mathcal{R}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}}) := \mathbb{E}_m \left[\mathbb{E}_{\mathcal{D}_m} \left[\ell_m(\mathcal{A}(\hat{\theta}_0^{\mathcal{A}}, \mathcal{D}_m^{\mathrm{tr}}), \mathcal{D}_m^{\mathrm{va}}) \right] \right]. \qquad (2)$$

Methods. We focus on understanding the generalization of two representative gradient-based meta learning methods MAML [20] and iMAML [33] in the overparameterized regime. MAML obtains the task-specific parameter $\hat{\theta}_m(\theta_0)$ by taking one step gradient descent with step size α of the per-task loss function ℓ_m from the initial parameter θ_0, that is

$$\mathcal{A}(\theta_0, \mathcal{D}_m^{\mathrm{tr}}) = \theta_0 - \alpha \nabla_{\theta_0} \ell_m(\theta_0, \mathcal{D}_m^{\mathrm{tr}}). \qquad (3)$$

On the other hand, iMAML obtains the task-specific parameter $\hat{\theta}_m$ from the initial parameter θ_0 by optimizing the task-specific loss regularized by the distance between $\hat{\theta}_m$ and θ_0, that is

$$\mathcal{A}(\theta_0, \mathcal{D}_m^{\mathrm{tr}}) = \arg\min_{\theta} \ell_m(\theta, \mathcal{D}_m^{\mathrm{tr}}) + \frac{\gamma}{2} \|\theta - \theta_0\|^2 \qquad (4)$$

Figure 1: Two types of meta learning.

where $\gamma > 0$ is the weight of the regularizer. As summarized in Figure 1, MAML has smaller computation complexity than iMAML since iMAML requires solving an inner problem during adaptation, while iMAML may achieve smaller test error since it explicitly minimize the loss.

3 Main Results: Benign Overfitting for Gradient-based Meta Learning

In this section, we introduce the meta linear regression model and some necessary assumptions for the analysis. We present the main results, highlight the key steps of the proof and conduct simulations to verify our results. Due to space limitations, we will defer the proofs to the supplementary document.

3.1 Meta linear regression setting

To make a precise analysis, we will assume the following linear data model. Denoting the ground truth parameter on task m as $\theta_m^{\star} \in \mathbb{R}^d$, and the noise as ϵ_m, we assume the data model for task m is

$$y_m = \theta_m^{\star\top} x_m + \epsilon_m. \qquad (5)$$

Given the linear model (5), the meta training problem (1) with adaptation method (3) or (4) generally have unique solutions when $d \le NM$. However, when the meta model θ_0 and thus the per-task model θ_m are overparameterized, i.e. $d > NM$, the training problem (1) may have multiple solutions. In the subsequent analysis, we will analyze the performance of the *minimum norm* solution because recent advances in training overparameterized models reveal that gradient descent-based methods converge to the minimum norm solution [23, 29]. We provide a formal definition below.

Definition 1 (Minimum norm solution). *Denote $\mathbf{X}_m^{\mathrm{va}} := [x_{m,1}, \ldots, x_{m,N_{\mathrm{va}}}]^\top \in \mathbb{R}^{N_{\mathrm{va}} \times d}$, $\mathbf{y}_m^{\mathrm{va}} := [y_{m,1}, \ldots, y_{m,N_{\mathrm{va}}}]^\top \in \mathbb{R}^{N_{\mathrm{va}}}$. With $\mathcal{A}(\theta, \mathcal{D}_m^{\mathrm{tr}})$ being either (3) or (4), the minimum norm solution to the meta training problem (1) under the linear regression loss is expressed by*

$$\min_{\theta_0} \|\theta_0\|^2 \quad \text{s.t.} \quad \theta_0 \in \arg\min_{\theta} \sum_{m=1}^M \left\| \mathbf{X}_m^{\mathrm{va}} \mathcal{A}(\theta, \mathcal{D}_m^{\mathrm{tr}}) - \mathbf{y}_m^{\mathrm{va}} \right\|^2. \qquad (6)$$

In our analysis, we make the following basic assumptions.

Assumption 1 (Overparameterized model). *The total number of meta training data is smaller than the dimension of the model parameter; i.e. $NM < d$.*

Assumption 2 (Subgaussian data). *The noise ϵ_m is subGaussian with $\mathbb{E}[\epsilon_m] = 0$ and $\mathbb{E}[\epsilon_m^2] = \sigma^2$. For the m-th task, data $x_m = \mathbf{V}_m \mathbf{\Lambda}_m^{\frac{1}{2}} \mathbf{z}_m$, where $\mathbf{z}_m$ has independent, σ_x-subGaussian entries; $\mathbb{E}[\mathbf{z}_m] = \mathbf{0}, \mathbb{E}[\mathbf{z}_m \mathbf{z}_m^\top] = \mathbf{I}_d$, with $\mathbf{I}_d$ being a $d \times d$ identity matrix.*

Assumption 3 (Data matrix). *Define $\mathbf{Q}_m := \mathbb{E}[x_m x_m^\top]$, $\mathbf{Q} := \mathbb{E}_m[\mathbf{Q}_m] = \mathbf{V}\mathbf{\Lambda}\mathbf{V}^\top$ with orthonormal matrices $\mathbf{V}$ and $\mathbf{V}_m$. Denote the i-th eigenvalue of $\mathbf{Q}$ and $\mathbf{Q}_m$ in descending order as λ_i and $\lambda_{m,i}$, respectively. Assume $0 < \underline{\lambda} \le \lambda_{m,i} \le \bar{\lambda}$ with $\underline{\lambda}$ and $\bar{\lambda}$ being the smallest and the largest eigenvalues. Cross-task data heterogeneity $\mathbb{V}(\{\mathbf{Q}_m\}_{m=1}^M) := \max_{i,m} |\lambda_i - \lambda_{m,i}|$ is bounded.*

Assumption 4 (Task parameter). *The ground truth parameter $\theta_m^\star$ is independent of $\mathbf{X}_m$ and satisfies $\mathrm{Cov}[\theta_m^\star] = (R^2/d)\mathbf{I}_d$, where R is a constant, and the entries of θ are i.i.d. $\mathcal{O}(R/\sqrt{d})$-subGaussian.*

Assumption 1 defines the setting that the meta level is overparameterized, which has also been used in [39]. Note that Assumptions 2-4 are common in the analysis of meta learning in [3, 9, 14, 22].

With the linear data model (5), the (minimum norm) solutions to the meta training objective (1) and the meta testing objective (2) can be computed analytically which we will summarize next.

Proposition 1. (Empirical and population level solutions) *Under the meta linear regression model (5), the meta testing objective of method $\mathcal{A}$ in (2) can be equivalently written as*

$$\mathcal{R}^{\mathcal{A}}(\theta_0) = \mathbb{E}_m \left[\|\theta_0 - \theta_m^\star\|_{\mathbf{W}_m^{\mathcal{A}}}^2 \right] \tag{7}$$

where the matrix $\mathbf{W}_m^{\mathcal{A}}$ and its empirical version $\hat{\mathbf{W}}_m^{\mathcal{A}}$ are given in Table 2 with $\hat{\mathbf{Q}}_m^{\mathrm{al}} := \frac{1}{N} \mathbf{X}_m^{\mathrm{al}\top} \mathbf{X}_m^{\mathrm{al}}$. The optimal solutions to the meta-test risk and the minimum-norm solutions to the empirical meta training loss are given below respectively

$$\theta_0^{\mathcal{A}} := \arg\min_{\theta_0} \mathcal{R}^{\mathcal{A}}(\theta_0) = \mathbb{E}_m \left[\mathbf{W}_m^{\mathcal{A}}\right]^{-1} \mathbb{E}_m \left[\mathbf{W}_m^{\mathcal{A}} \theta_m^\star \right] \tag{8a}$$

$$\hat{\theta}_0^{\mathcal{A}} := \arg\min_{\theta_0} \mathcal{L}^{\mathcal{A}}(\theta_0, \mathcal{D}) = \left(\sum\nolimits_{m=1}^M \hat{\mathbf{W}}_m^{\mathcal{A}}\right)^\dagger \left(\sum\nolimits_{m=1}^M \hat{\mathbf{W}}_m^{\mathcal{A}} \theta_m^\star\right) + \Delta_M^{\mathcal{A}} \tag{8b}$$

where † denotes the Moore–Penrose pseudo inverse; $\Delta_M^{\mathcal{A}}$ is a constant that depends on $\mathbf{X}_m, \epsilon_m$ specified in the supplementary document.

To study overfitting in the meta learning model, we quantify its generalization ability via the widely used metric - *excess risk*. The excess risk of method $\mathcal{A}$ (which can be "ma" for MAML and "im" for iMAML), with an empirical solution $\hat{\theta}_0^{\mathcal{A}}$ and population solution $\theta_0^{\mathcal{A}}$, is defined as

$$\mathcal{E}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}}) := \mathcal{R}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}}) - \mathcal{R}^{\mathcal{A}}(\theta_0^{\mathcal{A}}). \quad (9)$$

Table 2: Weight matrices under different method $\mathcal{A}$.

Method	Weight matrices
ERM	$\mathbf{W}_m^{\mathrm{er}} = \mathbf{Q}_m$
	$\hat{\mathbf{W}}_m^{\mathrm{er}} = \hat{\mathbf{Q}}_m$
MAML	$\mathbf{W}_m^{\mathrm{ma}} = (\mathbf{I} - \alpha\mathbf{Q}_m)\mathbf{Q}_m(\mathbf{I} - \alpha\mathbf{Q}_m)$
	$\hat{\mathbf{W}}_m^{\mathrm{ma}} = (\mathbf{I} - \alpha\hat{\mathbf{Q}}_m^{\mathrm{tr}})\hat{\mathbf{Q}}_m^{\mathrm{va}}(\mathbf{I} - \alpha\hat{\mathbf{Q}}_m^{\mathrm{tr}})$
iMAML	$\mathbf{W}_m^{\mathrm{im}} = (\gamma^{-1}\mathbf{Q}_m + \mathbf{I})^{-1}\mathbf{Q}_m(\gamma^{-1}\mathbf{Q}_m + \mathbf{I})^{-1}$
	$\hat{\mathbf{W}}_m^{\mathrm{im}} = (\gamma^{-1}\hat{\mathbf{Q}}_m^{\mathrm{tr}} + \mathbf{I})^{-1}\hat{\mathbf{Q}}_m^{\mathrm{va}}(\gamma^{-1}\hat{\mathbf{Q}}_m^{\mathrm{tr}} + \mathbf{I})^{-1}$

In (9), the excess risk measures the difference between the population risk of the empirical solution, $\hat{\theta}_0$ and the optimal population risk. Given total number of training samples MN, if $d \to \infty$, the classic learning theory implies that the excess risk $\mathcal{E}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}})$ also grows, which leads to overfitting [24]. The larger the excess risk, the further the empirical solution $\hat{\theta}_0^{\mathcal{A}}$ is from the optimal population solution $\theta_0^{\mathcal{A}}$, indicating more severe *overfitting*.

3.2 Main results

With the closed-form solutions given in Proposition 1, we are ready to bound the excess risk of MAML and iMAML in the overparameterized linear regime. For notation brevity, we first introduce some universal constants such as $c_0, c_1, c_2, \ldots$, and only present the dominating terms in the subsequent results. The precise presentation of non-dominant terms are deferred to the supplementary document.

We first decompose the excess risk into three terms in Proposition 2.

Proposition 2. *Denote $\mathbf{W}^{\mathcal{A}} \coloneqq \mathbb{E}_m[\mathbf{W}_m^{\mathcal{A}}]$. There exists a universal constant $c_0 > 0$ that the excess risk of a meta learning method $\mathcal{A}$ can be bounded by*

$$\mathcal{E}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}}) \leq c_0 \left(\mathcal{E}_{\theta_m^{\star}} + \mathcal{E}_{\epsilon_m} + \mathcal{E}_b \right) \tag{10}$$

where the first term $\mathcal{E}_{\theta_m^{\star}}$ is a function of $\theta_m^{\star}, \theta_0^{\mathcal{A}}, \mathbf{W}^{\mathcal{A}}, \hat{\mathbf{W}}_m^{\mathcal{A}}$, which quantifies the weighted variance of the ground truth task specific parameters $\theta_m^{\star}$; the second term $\mathcal{E}_{\epsilon_m}$, as a function of ϵ_m, is the weighted noise variance; and the third term $\mathcal{E}_b$, as a function of $\theta_0^{\mathcal{A}}, \mathbf{W}^{\mathcal{A}}, \hat{\mathbf{W}}_m^{\mathcal{A}}$, is the bias of the minimum-norm solution in overparameterized MAML or iMAML.

Based on this decomposition, as we will show in Section 4, the bound of the excess risk can be derived from the bound of these three terms $\mathcal{E}_{\theta_m^{\star}}, \mathcal{E}_{\epsilon_m^{\star}}, \mathcal{E}_b$, respectively, which gives Theorem 1.

Theorem 1 (Excess risk bound). *Suppose Assumptions 1-4 hold. Let $\mu_1(\cdot) \geq \mu_2(\cdot) \dots$ denote the eigenvalues of a matrix in the descending order. Define $\overline{\mathbf{W}}_M^{\mathcal{A}} \coloneqq \frac{1}{M} \sum_{m=1}^{M} \mathbf{W}_m^{\mathcal{A}}$. For the [meta linear regression]{.underline} problem with the minimum-norm solution (6), for $0 \leq k \leq d$, define the effective ranks as*

$$r_k \left(\overline{\mathbf{W}}_M^{\mathcal{A}} \right) \coloneqq \frac{\sum_{i>k} \mu_i \left(\overline{\mathbf{W}}_M^{\mathcal{A}} \right)}{\mu_{k+1} \left(\overline{\mathbf{W}}_M^{\mathcal{A}} \right)}; \qquad R_k \left(\overline{\mathbf{W}}_M^{\mathcal{A}} \right) \coloneqq \frac{\left(\sum_{i>k} \mu_i (\overline{\mathbf{W}}_M^{\mathcal{A}}) \right)^2}{\sum_{i>k} \mu_i^2 (\mathbf{W}^{\mathcal{A}})}. \tag{11}$$

With the cross-task data heterogeneity $\mathbb{V}$ defined in Assumption 3, if there exist universal constants $c_1, c_2, c_3 > 1$ such that the effective dimension $k^* = \min\{k \geq 0 : r_k(\overline{\mathbf{W}}_M^{\mathcal{A}}) \geq c_1 NM\}$, $c_2 \log(1/\delta) < NM$ and $k^* < NM/c_3$, then with probability at least $1 - \delta$, the excess risk satisfies

$$\mathcal{E}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}}) \leq c_3 \|\mathbb{E}[\theta_m^{\star}]\|^2 \bar{\lambda} \sqrt{\frac{r_0(\mathbf{W}^{\mathcal{A}})}{MN}} + \sigma^2 c_2 \left(\frac{k^*}{MN} + \frac{MN}{R_{k^*}(\overline{\mathbf{W}}_M^{\mathcal{A}})} \right) \left(1 + \mathbb{V}(\{\mathbf{W}_m^{\mathcal{A}}\}_{m=1}^M) \right). \tag{12}$$

Theorem 1 provides the excess risk bound via the effective ranks. In (11), the effective ranks r_k and R_k of a matrix capture the distribution of the eigenvalues of this matrix, and the effective dimension k^* determines the above upper bound by considering the asymmetry of the eigenvalues of the solution matrix. The idea is to choose k^* that makes R_{k^*} large enough and keeps k^* small enough compared to MN so that the variance term of the excess risk is controlled. For example, r_0 is the trace normalized by the largest eigenvalue, which is bounded above by R_0. And both r_0 and R_0 are no larger than the rank of the matrix, and they are equal to the rank only when all non-zero eigenvalues are equal. If the eigenvalues distribute more uniformly, the effective rank will be larger, otherwise smaller.

Remark 1. 1) The definition of effective rank has been also given in [5] but only on the data matrix $\mathbf{Q}$. And our setting reduces to the single task ERM learning, or the linear regression case in [5], when $M = 1, \theta_m^{\star} = \theta_0, \mathbf{W}_m^{\mathcal{A}} = \mathbf{Q}$, which implies that the cross-task variance in (10) as well as the data heterogeneity $\mathbb{V}(\cdot)$ reduces to zero. Accordingly, Theorem 1 reduces to Theorem 4 in [5].

2) Given Theorem 1, in order to control the excess risk of solution $\hat{\theta}_0^{\mathcal{A}}$, we want $r_0(\overline{\mathbf{W}}_M^{\mathcal{A}})$ to be small compared to the total number of training samples MN, but $r_{k^*}(\overline{\mathbf{W}}_M^{\mathcal{A}})$ and $R_{k^*}(\overline{\mathbf{W}}_M^{\mathcal{A}})$ to be large compared to MN. In addition, the cross-task heterogeneity $\mathbb{V}$ should be small. Since for a matrix $\mathbf{W}, r_k(\mathbf{W}) \leq R_k(\mathbf{W}) \leq d$, this suggests the model benefits from overparameterization.

Building upon Theorem 1, we now discuss the conditions for "benign overfitting", which refers to the situation that overparameterization does not "harm" the excess risk, or the excess risk still vanishes when $d > MN$ and N, M, d increase.

Definition 2 (Condition for benign overfitting in meta learning). *The weight matrices $\overline{\mathbf{W}}_M^{\mathcal{A}}$ for method $\mathcal{A}$ satisfy the* benign overfitting condition *in gradient-based meta learning, if and only if*

$$\lim_{NM,d \to \infty} \frac{r_0(\overline{\mathbf{W}}_M^{\mathcal{A}})}{NM} = \lim_{NM,d \to \infty} \frac{k^*}{NM} = \lim_{NM,d \to \infty} \frac{NM}{R_{k^*}(\overline{\mathbf{W}}_M^{\mathcal{A}})} = 0. \tag{13}$$

This guarantees the excess risk (12) goes to zero in overparameterized meta learning models with sufficient training data from all tasks. To provide an intuitive explanation, Figure 2 plots the population

(a) MAML with different α. (b) iMAML with different γ.

Figure 2: Excess risk vs number of samples (N) with different hyperparameters ($M = 10, d = 200$).

(a) MAML (b) iMAML

Figure 3: Excess risks vs number of samples (N) for $\mathbf{Q}_m = \operatorname{diag}(\mathbf{I}_{d_1}, \beta \mathbf{I}_{d-d_1})$ with different β.

risk versus the number of the training data, which demonstrates the "double descent" curve. Namely, as N increases, $\mathcal{E}(\hat{\theta}_0)$ first decreases, then increases and then decreases again, as is discovered in overparameterized neural networks [30]. The trend in Figure 2 is similar to the trend observed in [31]. When $d/(NM) > 1$, the model is overparameterized, which can overfit the training data, leading to larger excess risk as N decreases. However, Figure 2 shows the excess risk does not become too large as N decreases, indicating that overfitting does not severely harm the population risk in this case.

3.3 Examples and discussion

In this section, we discuss how the benign overfitting condition (13) in gradient-based meta learning reduces to that in single task linear regression; e.g., in [5, 40]. We also provide examples to show

Q1) *how certain properties of meta training data affect the excess risk; and,*

Q2) *how to choose the hyperparameters that preserve benign overfitting.*

Data covariance and cross-task heterogeneity. Theorem 1 reveals that the excess risk depends on both the eigenvalues of the data covariance matrix $\mathbf{Q}_m$, and the cross-task data heterogeneity, measured by $\mathbb{V}(\{\mathbf{Q}_m\}_{m=1}^M)$. We give an example below to better demonstrate how these two properties of gradient-based meta training data affect the excess risk.

Example 1 (Data covariance). *Suppose $\mathbf{Q}_m = \operatorname{diag}(\mathbf{I}_{d_1}, \beta \mathbf{I}_{d-d_1})$, $\forall m$. Set $M = 10, d = 200, d_1 = 20, \alpha = 0.1$ for MAML and $\gamma = 10^3$ for iMAML. Then the benign overfitting condition (13) is satisfied by MAML and iMAML. We plot the excess risk under different β in Figure 3.*

From Figure 3 we can observe that given a fixed number of training data N, the population risk increases with β for both MAML and iMAML. This observation verifies our theory since larger β results in a smaller $R_k^{\mathcal{A}}(\overline{\mathbf{W}}_M^{\mathcal{A}})$, leading to a larger upper bound on the variance term in (12).

Example 1 demonstrates how the per-task data matrix $\mathbf{Q}_m$ affects the excess risk. We consider another example that demonstrates how the data heterogeneity across tasks affects the excess risk.

Example 2 (Data heterogeneity). *Suppose $\mathbf{Q}_m = |\omega_m + 1| \operatorname{diag}(\mathbf{I}_{d_1}, \beta \mathbf{I}_{d-d_1})$ with $\omega_m \sim \mathcal{N}(0, \sigma_\omega^2)$ for all m. Set $M = 10, d = 200, d_1 = 20, \beta = 0.3, \alpha = 0.1$ for MAML and $\gamma = 0.1$ for iMAML. Then it satisfies the benign overfitting condition (13) for MAML and iMAML. Figure 4 plots the excess risk with different choices of σ_ω.*

Observing from Figure 4 that the larger σ_ω^2, the higher the excess risk, and the more difficult for the benign overfitting condition to be satisfied for both MAML and iMAML. Therefore, compared to

(a) MAML. (b) iMAML

Figure 4: Excess risks of MAML and iMAML vs number of training samples (N) for $\mathbf{Q}_m = |1 + \omega_m| \operatorname{diag}(\mathbf{I}_{d_1}, \beta \mathbf{I}_{d-d_1}), \omega_m \sim \mathcal{N}(0, \sigma_\omega^2)$ with different σ_ω.

(a) Cross-task variance vs task number (b) Bias vs task number

Figure 5: Cross-task variance and bias versus task number to elaborate Lemma 1 and Lemma 2.

ERM with a single task, the benign overfitting condition for MAML is more restrictive as it imposes constraints for both the expected data covariance $\mathbf{Q}_m$, and the data heterogeneity $\mathbb{V}(\{\mathbf{W}_m^{\mathcal{A}}\}_{m=1}^M)$.

Connection to multi-task ERM. To compare benign overfitting in the gradient-based meta learning with that in the conventional ERM, where $\theta_m = \theta_0$, we can set the step size $\alpha = 0$ in MAML, or $\gamma \to \infty$ in iMAML, and $N_{\text{va}} = N$, which reduces to conventional ERM without adaptation.

Compared to that of MAML and iMAML in (13), the benign overfitting condition is less restrictive for ERM since it does not impose constraints on α or γ. Intuitively, benign overfitting is more likely to happen in MAML or iMAML than in ERM. The hyperparameters α and γ will affect the eigenvalues of $\mathbf{W}_m^{\text{ma}}$, $\mathbf{W}_m^{\text{im}}$, respectively, thus affecting their corresponding excess risk. Here we provide a sufficient condition where the benign overfitting condition in ERM is preserved in MAML or iMAML. We summarize the results in the corollary below.

Corollary 1 (Hyperparameters that preserve benign overfitting). *Recall λ_1 is the largest eigenvalue of $\mathbf{Q}$. For MAML, when $0 < \alpha \le \frac{1}{3\lambda_1}$, and for iMAML, when $\gamma \ge \lambda_1$, then the effective ranks of $\mathbf{W}^{\text{ma}}$ and $\mathbf{W}^{\text{im}}$ are bounded above and below by a positive constant times the effective rank of $\mathbf{Q}$, and therefore the benign overfitting condition holds for MAML and iMAML if it holds for ERM. To summarize, there are constants c_1, c_2, c_3, c such that for $k^* = \min\{k \ge 0 : r_k(\overline{\mathbf{Q}}_M) \ge c_1 NM\}$. For $\delta < 1$, $c_2 \log(1/\delta) < NM$ and $k^* < NM/c_3$, with probability at least $1 - 7e^{-2NM/c}$, it follows*

$$\mathcal{E}^{\mathcal{A}}(\hat{\theta}_0^{\mathcal{A}}) \le c_3 \|\mathbb{E}[\theta_m^\star]\|^2 \bar{\lambda} \sqrt{\frac{r_0(\mathbf{Q})}{MN}} + \sigma^2 c_2 \left(\frac{k^*}{MN} + \frac{MN}{R_{k^*}(\overline{\mathbf{Q}}_M)} \right) \left(1 + \mathbb{V}(\{\mathbf{Q}_m\}_{m=1}^M) \right). \quad (14)$$

Remark 2. For MAML, let the unordered eigenvalues $\tilde{\mu}_i(\mathbf{W}^{\text{ma}}) = \lambda_i(1 - \alpha\lambda_i)^2$. One challenge to control $\tilde{\mu}_i(\mathbf{W}^{\text{ma}})$ is that $\tilde{\mu}_i(\mathbf{W}^{\text{ma}})$ are not necessarily monotonic w.r.t. λ_i; that is, it does not necessarily hold that $\tilde{\mu}_1 \ge \tilde{\mu}_2 \ge \cdots \ge \tilde{\mu}_d$. For any $\lambda_i \ge \lambda_j$, if $\tilde{\mu}_i(\mathbf{W}^{\mathcal{A}}) \ge \tilde{\mu}_j(\mathbf{W}^{\mathcal{A}})$, then we say the order of the eigenvalues is preserved. For this to hold, it requires $\tilde{\mu}_i(\lambda_i)$ to be a monotonically non-decreasing function of λ_i, which yields $\alpha \le \frac{1}{3\lambda_1}$. Similar results can be obtained for iMAML by controlling the value of γ. And the bound on α or γ further ensures that $\tilde{\mu}_i(\mathbf{W}^{\mathcal{A}})$ is bounded above and below by a positive constant times the effective rank of $\mathbf{Q}$.

4 Proof Outline

In this section, we highlight the key steps of the proof for Theorem 1. We achieve so by analyzing the three terms in Proposition 2 respectively.

The first two terms in (10) can be bounded based on the concentration inequalities on subGaussian variables, given in Lemmas 1 and 2.

Lemma 1 (Bound on cross-task variance). *With probability at least $1 - \delta$, it follows*

$$\mathcal{E}_{\theta_m^\star} = \left\| \Big(\sum_{m=1}^M \hat{\mathbf{W}}_m^{\mathcal{A}} \Big)^\dagger \Big(\sum_{m=1}^M \hat{\mathbf{W}}_m^{\mathcal{A}} (\theta_m^\star - \theta_0^{\mathcal{A}}) \Big) \right\|_{\mathbf{W}^{\mathcal{A}}}^2 \le \tilde{\mathcal{O}} \left(\frac{1}{M} \right) \tag{15}$$

where $\widetilde{O}(\cdot)$ hides the log polynomial dependence on N, M, d.

The cross-task variance term analzyed in Lemma 1 is unique in meta learning, which captures the data heterogeneity across different tasks. To elaborate Lemma 1, we plot the cross-task variance versus the task number in Figure 5a with the dimension of model parameter $d = 200$, training validation split parameter $s = N_{\text{tr}}/N = 0.5$, per-task data number $N = 10$. This figure demonstrates that the cross-task variance decreases with number of tasks M with rate $O(\frac{1}{M})$, which is consistent with the theoretical results in Lemma 1. Interestingly, we can observe a double descent phenomenon when M increases so that the model goes from overparameterized setting to underparameterized setting. Note that the "double descent" phenomenon in Figure 5a is different from that in the conventional linear regression case in that increasing the number of tasks M will increase data from different per-task distributions, but they still help reduce the excess risk.

Lemma 2 (Bound on bias). *There is a constant c_3 that depends only on σ_x, such that for any $1 < \log(1/\delta) < MN_{\text{va}}$, with probability at least $1 - \delta$, we have*

$$\mathcal{E}_b \le c_3 \|\theta_0^{\mathcal{A}}\|^2 \|\mathbf{W}^{\mathcal{A}}\| \max \left\{ \sqrt{\frac{r_0(\mathbf{W}^{\mathcal{A}})}{MN_{\text{va}}}}, \frac{r_0(\mathbf{W}^{\mathcal{A}})}{MN_{\text{va}}}, \sqrt{\frac{\log(1/\delta)}{MN_{\text{va}}}} \right\}. \tag{16}$$

This term is similar to the bias term in the linear regression case, but directly depending on the solution matrix $\mathbf{W}$ instead of the data matrix $\mathbf{Q}$. To elaborate Lemma 2, Figure 5b demonstrates that the bias term decays with M until it reaches zero when the model is underparameterized. These two terms in Lemma 1 and Lemma 2 do not go to infinity as N, M, d increase.

Note that, the key step is the bound on $\mathcal{E}_{\epsilon_m}$, which is the dominating term in the decomposition of excess risk (10) in the overparameterized regime. We will bound it below.

Lemma 3 (Bound on per-task variance). *There exist constants c_1, c_2, c_3, c such that for $0 \le k \le 2NM/c_3$, $r_k(\overline{\mathbf{W}}_M^{\mathcal{A}}) \ge c_1 NM$, and $k_0 \le k$, with probability at least $1 - 7e^{-2NM/c}$, it follows*

$$\mathcal{E}_{\epsilon_m} \le c_2 \left(\frac{k_0}{2NM} + \frac{NM}{R_{k_0}(\overline{\mathbf{W}}_M^{\mathcal{A}})} \right) \big(1 + \mathbb{V}(\{\mathbf{W}_m^{\mathcal{A}}\}_{m=1}^M) \big). \tag{17}$$

Note that, in the single task linear regression case, the cross-task data heterogeneity becomes none, i.e., $\mathbb{V} = 0$. This term is unique in the meta learning setting with multiple tasks. Plugging the results of Lemmas 1, 2 and 3 into (10), we will reach Theorem 1.

5   Conclusions and Limitations

This paper studies the generalization performance of the gradient-based meta learning with an overparameterized model. For a precise analysis, we focus on linear models where the total number of data from all tasks is smaller than the dimension of the model parameter. We show that when the data heterogeneity across tasks is relatively small, the per-task data covariance matrices with certain properties lead to benign overfitting for gradient-based meta learning with the minimum-norm solution. This explains why overparameterized meta learning models can generalize well in new data and new tasks. Furthermore, our theory shows that overfitting is more likely to happen in meta learning than in ERM, especially when the data heterogeneity across tasks is relatively high. One limitation of this work is that the analysis focuses on the meta linear regression case. While this analysis can capture practical cases where we reuse the feature extractor from pre-trained models and only meta-train the parameters in the last linear layer, it is also promising to extend our analysis to nonlinear cases via means of random features and neural tangent kernels in the future work.

References

[1] Ron Amit and Ron Meir. Meta-learning by adjusting priors based on extended pac-bayes theory. In *Proc. International Conference on Machine Learning*, pages 205–214, Stockholm, Sweden, 2018.

[2] Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Proc. Advances in Neural Information Processing Systems*, pages 3981–3989, Barcelona, Spain, 2016.

[3] Yu Bai, Minshuo Chen, Pan Zhou, Tuo Zhao, Jason Lee, Sham Kakade, Huan Wang, and Caiming Xiong. How important is the train-validation split in meta-learning? In *Proc. International Conference on Machine Learning*, pages 543–553, virtual, 2021.

[4] Maria-Florina Balcan, Mikhail Khodak, and Ameet Talwalkar. Provable guarantees for gradient-based meta-learning. In *Proc. International Conference on Machine Learning*, pages 424–433, Long Beach, CA, 2019.

[5] Peter L. Bartlett, Philip M. Long, Gábor Lugosi, and Alexander Tsigler. Benign overfitting in linear regression. *Proceedings of the National Academy of Sciences*, 117(48):30063–30070, 2020.

[6] Alberto Bernacchia. Meta-learning with negative learning rates. In *Proc. International Conference on Learning Representations*, virtual, 2020.

[7] Yuan Cao, Zixiang Chen, Mikhail Belkin, and Quanquan Gu. Benign overfitting in two-layer convolutional neural networks. *arXiv preprint arXiv:2202.06526*, 2022.

[8] Jinghui Chen, Yuan Cao, and Quanquan Gu. Benign overfitting in adversarially robust linear classification. *arXiv preprint arXiv:2112.15250*, 2021.

[9] Lisha Chen and Tianyi Chen. Is bayesian model agnostic meta learning better than model agnostic meta learning, provably? In *Proceedings of The 25th International Conference on Artificial Intelligence and Statistics*, 2022.

[10] Qi Chen, Changjian Shui, and Mario Marchand. Generalization bounds for meta-learning: An information-theoretic analysis. In *Proc. Advances in Neural Information Processing Systems*, virtual, 2021.

[11] Wei-Yu Chen, Yen-Cheng Liu, Zsolt Kira, Yu-Chiang Frank Wang, and Jia-Bin Huang. A closer look at few-shot classification. In *Proc. International Conference on Learning Representations*, Vancouver, Canada, 2018.

[12] Yutian Chen, Matthew W Hoffman, Sergio Gómez Colmenarejo, Misha Denil, Timothy P Lillicrap, Matt Botvinick, and Nando Freitas. Learning to learn without gradient descent by gradient descent. In *Proc. International Conference on Machine Learning*, pages 748–756, Sydney, Australia, 2017.

[13] Kurtland Chua, Qi Lei, and Jason D Lee. How fine-tuning allows for effective meta-learning. In *Proc. Advances in Neural Information Processing Systems*, volume 34, 2021.

[14] Giulia Denevi, Carlo Ciliberto, Dimitris Stamos, and Massimiliano Pontil. Learning to learn around a common mean. In *Proc. Advances in Neural Information Processing Systems*, volume 31, Montreal, Canada, 2018.

[15] Nan Ding, Xi Chen, Tomer Levinboim, Sebastian Goodman, and Radu Soricut. Bridging the gap between practice and pac-bayes theory in few-shot meta-learning. In *Proc. Advances in Neural Information Processing Systems*, virtual, 2021.

[16] Simon Shaolei Du, Wei Hu, Sham M Kakade, Jason D Lee, and Qi Lei. Few-shot learning via learning the representation, provably. In *International Conference on Learning Representations*, 2020.

[17] Alireza Fallah, Aryan Mokhtari, and Asuman Ozdaglar. On the convergence theory of gradient-based model-agnostic meta-learning algorithms. In *Proc. International Conference on Artificial Intelligence and Statistics*, pages 1082–1092, virtual, 2020.

[18] Alireza Fallah, Aryan Mokhtari, and Asuman Ozdaglar. Generalization of model-agnostic meta-learning algorithms: Recurring and unseen tasks. In *Proc. Advances in Neural Information Processing Systems*, virtual, 2021.

[19] Alec Farid and Anirudha Majumdar. Generalization bounds for meta-learning via pac-bayes and uniform stability. In *Proc. Advances in Neural Information Processing Systems*, virtual, 2021.

[20] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proc. International Conference on Machine Learning*, page 1126–1135, Sydney, Australia, 2017.

[21] Spencer Frei, Niladri S Chatterji, and Peter L Bartlett. Benign overfitting without linearity: Neural network classifiers trained by gradient descent for noisy linear data. *arXiv preprint arXiv:2202.05928*, 2022.

[22] Katelyn Gao and Ozan Sener. Modeling and optimization trade-off in meta-learning. In *Proc. Advances in Neural Information Processing Systems*, volume 33, virtual, 2020.

[23] Suriya Gunasekar, Jason Lee, Daniel Soudry, and Nathan Srebro. Characterizing implicit bias in terms of optimization geometry. In *Proc. International Conference on Machine Learning*, volume 80, pages 1832–1841, Stockholm, Sweden, 10–15 Jul 2018.

[24] Trevor Hastie, Robert Tibshirani, Jerome H Friedman, and Jerome H Friedman. *The elements of statistical learning: data mining, inference, and prediction*, volume 2. Springer, 2009.

[25] Sepp Hochreiter, A Steven Younger, and Peter R Conwell. Learning to learn using gradient descent. In *Proc. International Conference on Artificial Neural Networks*, pages 87–94, Vienna, Austria, 2001.

[26] Sharu Theresa Jose and Osvaldo Simeone. Information-theoretic generalization bounds for meta-learning and applications. *Entropy*, 23(1):126, 2021.

[27] Weihao Kong, Raghav Somani, Zhao Song, Sham Kakade, and Sewoong Oh. Meta-learning for mixed linear regression. In *Proc. International Conference on Machine Learning*, pages 5394–5404, virtual, 2020.

[28] Zhu Li, Zhi-Hua Zhou, and Arthur Gretton. Towards an understanding of benign overfitting in neural networks. *arXiv preprint arXiv:2106.03212*, 2021.

[29] Vidya Muthukumar, Kailas Vodrahalli, Vignesh Subramanian, and Anant Sahai. Harmless interpolation of noisy data in regression. *IEEE Journal on Selected Areas in Information Theory*, 1(1):67–83, 2020.

[30] Preetum Nakkiran, Gal Kaplun, Yamini Bansal, Tristan Yang, Boaz Barak, and Ilya Sutskever. Deep double descent: Where bigger models and more data hurt. *Journal of Statistical Mechanics: Theory and Experiment*, 2021(12):124003, 2021.

[31] Preetum Nakkiran, Prayaag Venkat, Sham M Kakade, and Tengyu Ma. Optimal regularization can mitigate double descent. In *Proc. International Conference on Learning Representations*, virtual, 2020.

[32] Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *arXiv preprint arXiv:1803.02999*, 2018.

[33] Aravind Rajeswaran, Chelsea Finn, Sham M Kakade, and Sergey Levine. Meta-learning with implicit gradients. In *Proc. Advances in Neural Information Processing Systems*, pages 113–124, Vancouver, Canada, 2019.

[34] Jonas Rothfuss, Vincent Fortuin, Martin Josifoski, and Andreas Krause. PACOH: Bayes-optimal meta-learning with pac-guarantees. In *Proc. International Conference on Machine Learning*, pages 9116–9126, virtual, 2021.

[35] Jonas Rothfuss, Dennis Lee, Ignasi Clavera, Tamim Asfour, and Pieter Abbeel. Promp: Proximal meta-policy search. In *Proc. International Conference on Learning Representations*, Vancouver, Canada, 2018.

[36] Nikunj Saunshi, Arushi Gupta, and Wei Hu. A representation learning perspective on the importance of train-validation splitting in meta-learning. In *International Conference on Machine Learning*, pages 9333–9343, 2021.

[37] J. Schmidhuber. A neural network that embeds its own meta-levels. In *Proc. IEEE International Conference on Neural Networks*, pages 407–412 vol.1, 1993.

[38] Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Proc. Advances in Neural Information Processing Systems*, pages 4080–4090, Long Beach, CA, 2017.

[39] Yue Sun, Adhyyan Narang, Halil Ibrahim Gulluk, Samet Oymak, and Maryam Fazel. Towards sample-efficient overparameterized meta-learning. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Proc. Advances in Neural Information Processing Systems*, virtual, 2021.

[40] Alexander Tsigler and Peter L. Bartlett. Benign overfitting in ridge regression. *arXiv: Statistics Theory*, 2020.

[41] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Proc. Advances in Neural Information Processing Systems*, volume 29, pages 3630–3638, Barcelona, Spain, 2016.

[42] Haoxiang Wang, Ruoyu Sun, and Bo Li. Global convergence and generalization bound of gradient-based meta-learning with deep neural nets. *arXiv preprint arXiv:2006.14606*, 2020.

[43] Ke Wang, Vidya Muthukumar, and Christos Thrampoulidis. Benign overfitting in multiclass classification: All roads lead to interpolation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Proc. Advances in Neural Information Processing Systems*, virtual, 2021.