Is the Pope Catholic? Yes, the Pope is Catholic.
Generative Evaluation of Intent Resolution in LLMs

Abstract

Humans often express their communicative intents indirectly or non-literally, which requires their interlocutors—human or AI—to understand beyond the literal meaning of words. While most existing work has focused on discriminative evaluations, we present a new approach to generatively evaluate large language models' (LLMs') intention understanding by examining their responses to non-literal utterances. Ideally, an LLM should respond in line with the true intention of a non-literal utterance, not its literal interpretation. Our findings show that LLMs struggle to generate contextually relevant responses to non-literal language. We also find that providing oracle intentions substantially improves response appropriateness, but using chain-of-thought to make models spell out intentions before responding improves much less. These findings suggest that LLMs are not yet pragmatic interlocutors, and that explicitly modeling intention could improve LLM responses to non-literal language.

1 Introduction

Humans possess the ability to communicate and understand each other even through non-literal utterances (Roberts and Kreuz, 1994; Dews and Winner, 1999; Glucksberg and McGlone, 2001; Dews and Winner, 1999). This is evident through the use of conversational implicatures—*pragmatic* inferences arising from contextual factors and conventions in conversation, rather than specific words or phrases (Grice, 1975; Davis and Davis, 2016). Since humans often use non-literal language in communication, large language models (LLMs) must also develop pragmatic understanding to facilitate effective and nuanced interactions.

In this work, we introduce a new generative evaluation framework designed to evaluate the ability of large language models (LLMs) to understand and resolve intentions through pragmatic response generation. In Figure 1, Kelly uses hyperbole to express her desire to read numerous books. A contextually appropriate response would be to ideally echo sentiments like "That sounds like a great plan" rather than interpreting "a million" literally, as seen in responses like "That's quite an ambitious reading list.". Our framework uses this intuition to compare LLMs' responses to human-like expectations, enabling a nuanced assessment of their pragmatic understanding and response accuracy.

Our primary focus on pragmatic response marks a departure from prior work (Zheng et al., 2021; Hu et al., 2022; Srivastava et al., 2023; Ruis et al., 2023), which has predominantly measured intention understanding through a contrastive multiple-choice classification. We show that this setting does not necessarily reflect LLMs' abilities in generating pragmatic responses, nor does it correspond to the use of LLMs as conversational agents (West et al., 2023).

We evaluate the pragmatic understanding of several state-of-the-art open-source LLMs on various types of non-literal language from Hu et al. (2022). We observe that LLMs often struggle with generating contextually appropriate responses and tend to interpret non-literal language literally. Furthermore, we find that LLMs' ability in detecting intentions does not translate to their pragmatic response generation, highlighting a key distinction between merely detecting intentions and pragmatically acting on them in a generative setting. Finally, we explore methods to improve LLMs' pragmatic response abilities, finding that making models spell out the likely intention via chain-of-thought has minimal effects, but that models can respond pragmatically when given the oracle true intention.

Overall, our findings indicate that current LLMs are far from pragmatic understanding, with chain-of-thought prompting proving inadequate to address these limitations. This emphasizes the need for better mechanisms to infer intent and use it effectively for better pragmatic communication.

Figure 1: Framework to evaluate whether an LLM can generate an appropriate response to non-literal language use. Given a context C and a non-literal utterance U_1^N, the model responds with U_2^N. Our proposed framework compares U_2^N against responses (U_2^L and U_2^T) from two counterfactual dialog chains based on conveying incorrect literal meaning I_L and direct true intent I_T. We then compare the similarity of the model generated response U_2^N to these reference responses, under the context C, to determine whether it is appropriate.

2 Pragmatic Response Generation

We introduce a new framework to evaluate pragmatic generative ability of models—to understand and infer *implicit* intentions, and *use* it to generate pragmatic responses to non-literal utterances.

Setup Our evaluation setup (pictured in Figure 1) measures LLMs' pragmatic response generation by comparing it to reference dialog chains under the intended true meaning and under a literal misinterpretation. Specifically, it requires:

- **Context** C: Short story involving 2+ characters.

- **Non-literal Utterance** U_1^N: A speaker-generated utterance using non-literal language.

- **True Intention** I_T: The actual intended meaning of the speaker.

- **Incorrect Literal Intention** I_L: An incorrect literal interpretation of the speaker's intention.

- **Reference Dialog Chains based on I_T and I_L:** Speaker alternatively uses direct language to convey intentions I_T as U_1^T and I_L as U_1^L. The listener responds accordingly to U_1^T and U_1^L, with U_2^T and U_2^L respectively. See Figure 1.

Evaluating Pragmatic Understanding Our framework evaluates the extent to which LLMs' generated responses reflect an understanding of the underlying speaker's intention. We operationalize this into an automatic metric by using similarity measurements. Ideally, if LLMs can accurately infer and use the intent to generate *cooperative* responses using direct language, they should respond as if the non-literal utterance was instead communicated literally. Thus, if an LLM generates pragmatic cooperative responses, the response

should be closer in similarity to response generated under the true intention than to one based on the literal interpretation i.e., the relation $sim(U_2^N, U_2^T) > sim(U_2^N, U_2^L)$ should hold under the context C.

Data Hu et al. (2022) evaluate intention detection with a context C, a single non-literal utterance U_1^N, and verbalized intents that include a literal intent I_L and true intent I_T. To instantiate our framework, we augment this data with dialog chains (U_1^L, U_2^L) conditioned on the literal intent I_L and (U_1^T, U_2^T) conditioned on the true intent I_T. We use GPT-4 to get reference chains (See Appendix A.2).

We consider four non-literal language phenomena from Hu et al. (2022):[1]

1. INDIRECT SPEECH. Speakers phrase requests indirectly, such as questions ("Can you pass the salt?") or statements ("It is cold in here").

2. IRONY. Speakers use irony to mean the opposite of what they say. Irony is not explicitly defined in the context C, but C may include information about characters' emotional states.

3. MAXIMS OF CONVERSATION. In this task, speakers flout one of Grice's maxims.

4. METAPHOR. In this task, the speaker uses metaphors to draw comparisons between entities in a non-literal sense.

Models We evaluate five state-of-the-art LLMs: Llama2-7B-chat, Llama2-13B-chat, Llama2-70B-chat, Mistral-7B-Instruct-v0.2 and Zephyr-7B-β instruction finetuned models. We generate candidate listener responses U_2^N using these models, given the preceding context C and the speaker's

---

[1] Hu et al. (2022) have other tasks but we do not include them (e.g., Deceits is too non-cooperative).

Figure 2: Comparison between intention resolution in response generation vs intention detection by LLMs. On average, LLMs fine the generative setting harder than the discriminative setting for non-literal language use.

non-literal utterance U_1^N. Please refer to Appendix A.3 for generation details.

Evaluators Since LLM responses are intended for human conversational partners, we solicit human judgments to check whether understanding of the true intent is reflected in the generated response. We employ 9 students from our institution to evaluate whether Mistral-Instruct responses successfully capture the true intended intention I_T behind the speaker's non-literal utterance U_1^N, within the given context C. We find that our annotators have a good agreement.[2]

Separately, we task GPT-4 with identifying whether the same Mistral-Instruct generated responses U_2^N are closer to the reference responses conveying the true intention or to those with incorrect literal intention (U_2^L or U_2^T), to evaluate the intention resolution abilities of Mistral (cf. Section 2). We also provide GPT-4 with the contexts C and speakers' true intended meanings I_T. We find that GPT-4 agrees well with human annotators.[3] Thus, we can reliably use GPT-4 as a proxy for our evaluation paradigm in all our subsequent experiments.

3 Results on Pragmatic Response Generation

In this section, we analyze how well LLMs can generate contextually relevant responses. We compare our proposed generative approach, which evaluates implicit understanding in responses to U_1^N, against a discriminative multiple-choice setup as in Hu et al. (2022), which evaluates intention detection in U_1^N utterances.

Results Figure 2 indicates that LLMs exhibit better performance in responding to INDIRECT

SPEECH among various non-literal language types, potentially due to conventionalization of responses, or explicit descriptions of requests completed seen during training (Hu et al., 2022). Models perform the worst at responding to flouted MAXIMS, performing worse than chance. For instance, models fail to detect the attempt to change the subject in "Oh, it's such a pleasant day today" amidst a discussion about a "bad date". Llama-2 models exhibit marginally better metaphorical language understanding (METAPHORS) compared to Mistral and Zephyr models. In the Llama-2 family, we see that models perform better with increasing size. In aggregate, we see that LLMs perform at or near chance in generating an appropriate response that reflects having inferred the true intent.

Comparison against Discriminative Intention Detection We follow the multiple-choice setup as in Hu et al. (2022) (details in Appendix B). In Figure 2, we consistently see that models find it easier to detect true intentions in social situations that involve flouting conversational norms (MAXIMS) in a multiple-choice setup. However, they struggle with *using* this potentially inferred understanding in pragmatic response generation.

We see that trends do not remain consistent across different models and phenomena, and that on average, models struggle more in the generative setting. This underscores the importance of evaluating model performance in *both* discriminative and generative settings to obtain a better understanding of LLMs' pragmatic understanding.

4 Chain-of-Thought Prompting for Pragmatic Response Generation

Motivated by the ability of LLMs to detect intentions in some phenomena, we explore ways to improve their implicit intention understanding to bet-

---

[2]pairwise agreement = 0.8, Krippendorff's $\alpha = 0.6$

[3]We compute average across individual pairwise agreements of each annotator with GPT-4 (pairwise agreement = 0.77, $\sigma = 0.05$; Krippendorff's $\alpha = 0.54$, $\sigma = 0.1$)

Figure 3: Results from experiments with CoT prompting show that performance is highest when providing oracle true intention, and lowest with no oracle information.

ter generate pragmatic responses using chain-of-thought prompting (CoT) (Camburu et al., 2018; Wei et al., 2022).

Experiments using Chain-of-Thought In our experiments with CoT, we first generate an inferred intention and then a response (unless otherwise specified). We examine how response generation performance is affected by introducing varying levels of oracle cues at the inferred intention generation step, organized by increasing amounts of "hand-holding": (0) No oracle information (Naive) (1) Counterfactual reasoning to clarify the non-literal utterances (no inferred intention here) (2) Questioning a specific phenomenon (e.g., 'is Kelly being ironic') (3) Merely indicating non-literal language use (4) Identifying the phenomenon (e.g., 'Kelly is being ironic') (5) Providing the true intention as CoT (no model-generated inferred intention here) (6) Providing true intention *and* phenomenon information (e.g., "Kelly wants to read a lot and is using irony to convey it"). See Appendix C for prompt templates.

Results Figure 3 illustrates that specifying the type of non-literal language used, and the speaker's true intent (`Prompt 6`) significantly improves the model's ability to generate appropriate responses. Even providing subsets of this, such as just the true intention (`Prompt 5`) also helps. In contrast, models performance drops when no oracle information is provided (`Prompt 0`) or when prompted for counterfactual reasoning regarding the non-literal expression (`Prompt 1`).

The effectiveness of basic CoT prompting varies with model size; it benefits smaller models, such as Llama-2-7b and Llama-2-13b than for larger ones like Llama-2-70b or the more advanced Mistral-Instruct. While explicit cues about the phenomenon (e.g.,'Kelly is being ironic' vs. 'Is Kelly being

ironic?') help slightly (`Prompts 2-4`), they do not improve performance as significantly as providing only the true intention. These findings highlight of the importance of explicitly modeling intention in LLMs, indicating that response accuracy to non-literal language can improve with such approaches.

5 Related Work

Non-literal language understanding in LLMs Recent work has proposed several ways to evaluate LLMs' ability to interpret non-literal language, including implicature (Ruis et al., 2023; Kim et al., 2023), figurative language use (Liu et al., 2022a; Wachowiak and Gromann, 2023), detecting profundity (Herrera-Berg et al., 2023), broader benchmarks for social language understanding (Choi et al., 2023) and various pragmatic phenomena (Hu et al., 2022). Kim et al. (2023) also find that chain-of-thought helps improve a model's ability to interpret the use of implicatures. These tasks have focused on evaluating models' ability to *interpret* the true intent underlying an utterance, but not *respond* to it as we do in this work.

Generating responses based on inferred intents Some work has presented resources for intent or emotion-conditioned response generation, where a conversational agent must respond conditioned on a particular intent or emotion. Li et al. (2017) and Rashkin et al. (2019) present datasets of dialogues annotated with discrete emotion or intent labels. Zhang and Zhang (2019) and Chen et al. (2022) present approaches to modeling intent explicitly. Gu et al. (2022) generate explicit scene elaborations to improve figurative language understanding. While these works consider conditioning on intent, they do not explicitly focus on generating or evaluating responses to non-literal language use.

6 Summary

We propose a new framework to evaluate how well LLMs understand and respond to intentions in non-literal language, moving beyond previously employed multiple-choice settings. Our results show that LLMs often struggle to generate contextually relevant responses, with chain-of-thought prompting providing minimal improvements, while explicitly providing oracle intentions substantially boosts performance. These findings highlight current inadequacies of current LLMs in pragmatic understanding, suggesting methods that explicitly model intentions could improve conversational abilities.

7 Limitations & Ethical Considerations

Despite taking the first step towards proposing a new generative framework for evaluating intention resolution in LLMs, there are several limitations and ethical concerns, which we list below.

Limited Context Scope In this study, our primary focus is the evaluation of intention understanding and using it in pragmatic response generation. The context that we have considered is a short 1-3 sentence story. Future work should explore introducing other forms of context into the pragmatic generation pipeline, such as richer social and power dynamics (Antoniak et al., 2023), emotional states (Zhou et al., 2023), and external knowledge (Ghazvininejad et al., 2018), all of which can significantly contribute to varied levels of pragmatic understanding.

Amount of context In our experiments, we opted to include short 1-3 sentence stories. Future work can explore longer stories and include more preceding dialog turns. We hypothesize that more context will make this task more challenging, and we would need nuanced ways of understanding intentions at different turns.

Limited number of non-literal phenomenon We explore the evaluation of only four phenomena: INDIRECT SPEECH, IRONY, MAXIMS, and METAPHORS. Future work should consider other types of figurative language, such as cultural metaphors, visual metaphors (Liu et al., 2022b), idioms, proverbs, etc. Expanding the scope to include these elements would provide a more comprehensive understanding of LLMs' capabilities in interpreting nuanced language.

Potentially Inconsistent Human Evaluation In our work, we employ only 9 expert human annotators and assume human judgments as the gold standard. Concurrent work has shown that human evaluation might not always be consistent (Clark et al., 2021; Karpinska et al., 2021); however human judgments continue to be the gold standard for evaluating open-ended text generation.

Potential effects on Factuality In our work, we show that LLMs struggle with responding pragmatically to non-literal language. Training approaches which might help with better intention modeling to handle non-literal language may potentially affect faithfulness or factuality of LLMs responses.

References

Maria Antoniak, Anjalie Field, Ji Min Mun, Melanie Walsh, Lauren F. Klein, and Maarten Sap. 2023. Riveter: Measuring power and social dynamics between entities. In *ACL demonstrations*.

Oana-Maria Camburu, Tim Rocktäschel, Thomas Lukasiewicz, and Phil Blunsom. 2018. e-snli: Natural language inference with natural language explanations. *Advances in Neural Information Processing Systems*, 31.

Mao Yan Chen, Siheng Li, and Yujiu Yang. 2022. EmpHi: Generating empathetic responses with human-like intents. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1063–1074, Seattle, United States. Association for Computational Linguistics.

Minje Choi, Jiaxin Pei, Sagar Kumar, Chang Shu, and David Jurgens. 2023. Do LLMs understand social knowledge? evaluating the sociability of large language models with SocKET benchmark. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 11370–11403, Singapore. Association for Computational Linguistics.

Elizabeth Clark, Tal August, Sofia Serrano, Nikita Haduong, Suchin Gururangan, and Noah A Smith. 2021. All that's 'human'is not gold: Evaluating human evaluation of generated text. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 7282–7296.

Wayne A Davis and Wayne A Davis. 2016. Implicature. *Irregular Negatives, Implicatures, and Idioms*, pages 51–84.

Shelly Dews and Ellen Winner. 1999. Obligatory processing of literal and nonliteral meanings in verbal irony. *Journal of pragmatics*, 31(12):1579–1599.

Marjan Ghazvininejad, Chris Brockett, Ming-Wei Chang, Bill Dolan, Jianfeng Gao, Wen-tau Yih, and Michel Galley. 2018. A knowledge-grounded neural conversation model. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Sam Glucksberg and Matthew S McGlone. 2001. *Understanding figurative language: From metaphor to idioms*. 36. Oxford University Press.

Herbert P Grice. 1975. Logic and conversation. In *Speech acts*, pages 41–58. Brill.

Yuling Gu, Yao Fu, Valentina Pyatkin, Ian Magnusson, Bhavana Dalvi Mishra, and Peter Clark. 2022. Just-DREAM-about-it: Figurative language understanding with DREAM-FLUTE. In *Proceedings of the 3rd Workshop on Figurative Language Processing (FLP)*, pages 84–93, Abu Dhabi, United Arab

Emirates (Hybrid). Association for Computational Linguistics.

Eugenio Herrera-Berg, Tomás Browne, Pablo León-Villagrá, Marc-Lluís Vives, and Cristian Calderon. 2023. Large language models are biased to overestimate profoundness. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9653–9661, Singapore. Association for Computational Linguistics.

Jennifer Hu, Sammy Floyd, Olessia Jouravlev, Evelina Fedorenko, and Edward Gibson. 2022. A fine-grained comparison of pragmatic language understanding in humans and language models. *arXiv preprint arXiv:2212.06801*.

Marzena Karpinska, Nader Akoury, and Mohit Iyyer. 2021. The perils of using mechanical turk to evaluate open-ended text generation. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1265–1285.

Zae Myung Kim, David E. Taylor, and Dongyeop Kang. 2023. "is the pope catholic?" applying chain-of-thought reasoning to understanding conversational implicatures.

Yanran Li, Hui Su, Xiaoyu Shen, Wenjie Li, Ziqiang Cao, and Shuzi Niu. 2017. DailyDialog: A manually labelled multi-turn dialogue dataset. In *Proceedings of the Eighth International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 986–995, Taipei, Taiwan. Asian Federation of Natural Language Processing.

Emmy Liu, Chenxuan Cui, Kenneth Zheng, and Graham Neubig. 2022a. Testing the ability of language models to interpret figurative language. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4437–4452, Seattle, United States. Association for Computational Linguistics.

Emmy Liu, Chenxuan Cui, Kenneth Zheng, and Graham Neubig. 2022b. Testing the ability of language models to interpret figurative language. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*.

Hannah Rashkin, Eric Michael Smith, Margaret Li, and Y-Lan Boureau. 2019. Towards empathetic open-domain conversation models: A new benchmark and dataset. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5370–5381, Florence, Italy. Association for Computational Linguistics.

Richard M Roberts and Roger J Kreuz. 1994. Why do people use figurative language? *Psychological science*, 5(3):159–163.

Laura Eline Ruis, Akbir Khan, Stella Biderman, Sara Hooker, Tim Rocktäschel, and Edward Grefenstette. 2023. The goldilocks of pragmatic understanding: Fine-tuning strategy matters for implicature resolution by llms. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. 2023. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Transactions on Machine Learning Research*.

Lennart Wachowiak and Dagmar Gromann. 2023. Does GPT-3 grasp metaphors? identifying metaphor mappings with generative language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1018–1032, Toronto, Canada. Association for Computational Linguistics.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

Peter West, Ximing Lu, Nouha Dziri, Faeze Brahman, Linjie Li, Jena D Hwang, Liwei Jiang, Jillian Fisher, Abhilasha Ravichander, Khyathi Chandu, et al. 2023. The generative ai paradox:" what it can create, it may not understand". *arXiv preprint arXiv:2311.00059*.

Bo Zhang and Xiaoming Zhang. 2019. Hierarchy response learning for neural conversation generation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 1772–1781, Hong Kong, China. Association for Computational Linguistics.

Zilong Zheng, Shuwen Qiu, Lifeng Fan, Yixin Zhu, and Song-Chun Zhu. 2021. Grice: A grammar-based dataset for recovering implicature and conversational reasoning. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 2074–2085.

Xuhui Zhou, Hao Zhu, Akhila Yerukola, Thomas Davidson, Jena D. Hwang, Swabha Swayamdipta, and Maarten Sap. 2023. Cobra frames: Contextual reasoning about effects and harms of offensive statements. In *Findings of ACL*.

A Pragmatic Response Generation

A.1 Data

We consider four non-literal language phenomenon from Hu et al. (2022):

1. INDIRECT SPEECH - 20 examples

2. IRONY - 25 examples

3. MAXIMS OF CONVERSATION 20 examples

4. METAPHOR - 20 examples

These examples were were manually curated by expert researchers to cover a broad range of non-literal phenomena and elicit individual differences among humans.

A.2 Gold Dialog Chains based on I_T and I_L

In our experiments, we use GPT-4 to generate counterfactual gold dialog chains based on I_T and I_L. We first generate U_1^L by providing GPT-4 with only the incorrect literal intention I_L to prevent any possible contextual inference from C from being reflected in U_1^L. Next, we generate U_1^T by providing GPT-4 with the context C and true intention I_T, mimicking an ideal direct cooperative utterance generation setting. We follow the same setting to generate U_2^L and U_2^T from U_1^L and U_1^T, respectively.

A.3 Models

We use the following prompt to generate responses using LLMs:

```
Generate a short, concise single sentence
response.
Context: {context}
{speaker's non-literal utterance}

Generate a co-operative response without
any non-literal language as
{listener character name}.

{listener character name} replies,
```

We use temperature sampling with temperatures of 0.3 and 0.5 to generate responses, averaging the results from both settings. We find that a lower temperature= 0 results in incoherent, uninteresting responses, while a temperature > 0.5 leads to very verbose responses that digress from the main context and extrapolate excessively.

A.4 Evaluators

For GPT-4 as an evaluator, we provide the following prompt:

```
Task: You will read a short story. The story
will be followed by a question. Your
task is to decide which response option is
closest to the 'Generated Response'.
The answer options are 1 or 2.

Scenario: {Context}
{speaker's non-literal utterance U_1^N}
Intention: {True intention}

Generated Response:
{Person2} replies, {U_2^N from model}

Compare the below utterances to the
Generated Response. Which of the
below utterances is closest to the
above Generated Response?
Options:
1. {U_2^T from true intention dialog chain}
2. {U_2^L from incorrect literal intention
dialog chain}

Answer (option number 1 or 2): {number}
```

We randomly shuffle intentions provided as options 1 and 2. We set the temperature=0 to ensure the stability of the evaluation.

For human evaluation, we provide the following prompt:

```
Task: You will be provided a short story,
an utterance by one of the characters
in the story (person1). Person1 uses
non-literal language (like irony).
Person2 from the story responds to person1's
utterance. The task is to identify if
the "true intention" (provided) is
resolved/understood in person2's response
or not.

Make a binary yes/no choice.
```

We employ 9 students from our institution – 6 women, 3 men (20-30 age group) living in the United States of America.

B Discriminative Setup

We follow setup in Hu et al. (2022) for our discriminative setup comparison. They use a the multiple-choice setup. They compute the probability of answer options – true intention I_T and literal misinterpretation I_L – given the context C, the speaker's non-literal utterance U_1^N, and task instructions. We

Figure 4: Positive correlation between inferred intention accuracy and pragmatic response accuracy.

measure accuracy as assigning the highest probability to the correct answer token (e.g., "1", "2"). We follow the same prompt template as Hu et al. (2022):

```
Task: You will read short stories that
describe everyday situations. Each
story will be followed by a multiple-
choice question. Read each story and
choose the best answer. Your task is
to decide what the character in the
story is trying to convey. The answer
options are 1 or 2.

Scenario: {context} {dialog}.
What might {person1} be trying to convey?
Options:
1) {option1}
2) {option2}
Answer:
```

C Chain-of-thought Prompting

Please refer to for the chain-of-thought prompting templates used for all the models

C.1 Inferred Intention vs Response Accuracy

We evaluate similarity of CoT generated intents with the true intent and the incorrect literal intent using GPT-4. We follow a similar prompt as GPT-4 evaluator in Appendix A.4. We observe in Figure 4 that a model that is able to correctly infer the underlying true intention is also better at generating contextually relevant responses, corroborating our finding from PROMPT 5-6 in Section 4.

Figure 5: Chain-of-thought Prompting templates used in Section 4. Orange highlighted text is the explicitly provided oracle information.