kRAIG: A Natural Language-Driven Agent for Automated DataOps Pipeline Generation

Abstract

Modern machine learning systems rely on complex data engineering workflows to extract, transform, and load (ELT) data into production pipelines. However, constructing these pipelines remains time-consuming, and requires substantial expertise in data infrastructure and orchestration frameworks. Recent advances in large language model (LLM) agents offer a potential path toward automating these workflows, but existing approaches struggle with under-specified user intent, unreliable tool generation, and limited guarantees of executable outputs.

We introduce kRAIG, an AI agent that translates natural language specifications into production-ready Kubeflow Pipelines (KFP). To resolve ambiguity in user intent, we propose ReQuesAct (Reason + Question + Act), an interaction framework that explicitly clarifies intent prior to pipeline synthesis. The system orchestrates end-to-end data movement from diverse sources and generates task-specific transformation components through a retrieval-augmented tool synthesis process. To ensure data quality and safety, kRAIG incorporates LLM-based validation stages that verify pipeline integrity prior to execution.

Our framework achieves a 3x improvement in extraction and loading success and a 25% increase in transformation accuracy compared to state-of-the-art agentic baselines. These improvements demonstrate that structured agent workflows with explicit intent clarification and validation significantly enhance the reliability and executability of automated data engineering pipelines.

1 Introduction

Mapping natural language specifications to executable programs has been an active area of research in semantic parsing and program synthesis (Bisk et al., 2020). While this foundational work established key techniques for language-to-code generation, the landscape of production data systems has evolved significantly. Modern ML pipelines now involve complex orchestration across heterogeneous data sources, streaming platforms, and cloud infrastructure that were less prevalent when these methods were developed.

End-to-end machine learning workflows consist of multiple interdependent stages, including data ingestion, preprocessing, validation, model training, and evaluation. The early stages, data ingestion, transformation, and validation, require substantial manual effort, involving tailored pipelines that must be maintained and updated before model training can begin (Chen et al., 2025).

To address these challenges, we introduce k-Retrieval Augmented Integration Governor (kRAIG), an AI agent designed to automate the data processing phase of the machine learning lifecycle. Recent work has shown that large language models can be extended into agentic systems capable of multi-step reasoning and tool invocation (Wang et al., 2023; Schick et al., 2023). Building on these capabilities, kRAIG provides a conversational interface where users specify data integration and transformation requirements in natural language, which the system translates into executable data pipelines.

kRAIG is built on top of Kubeflow Pipelines and automatically generates containerized pipeline components to implement user-specified data tasks. Because Kubeflow executes on Kubernetes, kRAIG can leverage distributed compute resources and integrate data processing tool that can be containerized, enabling deployment across large-scale data engineering environments.

In contrast to existing agentic systems that target a wide variety of tasks, such as those evaluated in ELT-Bench, kRAIG focuses on specializing in composable data engineering pipelines (Jin et al., 2025). This shift aims to reduce the manual burden of data preparation while preserving the robustness

Figure 1: kRAIG Architecture

and scalability required in modern machine learning environments. This initial version of kRAIG focuses on a subset of tools and tasks that are representative of real-world enterprise data engineering workflows.

1.1 Methodology Comparison

Existing agent frameworks, such as SWE-Agent and Spider-Agent, are based on the **ReAct** (Reason + Act) framework that utilizes a recurrent cycle of:

1. **Thought** – internal reasoning about the current state

2. **Action** – a concrete step (e.g., call a tool, write code, issue a command)

3. **Observation** – the result of that action

4. **Repeat** until the task is solved

However, prior studies have shown that purely reason-then-act agent frameworks can exhibit unstable behavior under under-specified or execution-heavy tasks, often failing to recover from early incorrect assumptions (Yao et al., 2022).

We propose a modified interaction framework, termed **ReQuesAct** (Reason + Question + Act), which explicitly incorporates intent clarification as a step in the agent loop:

1. **Thought** – internal reasoning about the current state

2. *Question* - intent-clarifying question

3. **Action** – a concrete step (e.g., call a tool, write code, issue a command)

4. **Observation** – the result of that action

5. **Repeat** until the task is solved

2 Task understanding

We adopt a hybrid neurosymbolic approach to task interpretation in which kRAIG engages in a multi-turn dialogue to clarify user intent. As illustrated in Figure 2, the system incrementally asks clarifying questions to refine the task specification. Rather than requiring users to manually condense their requests into predefined templates, kRAIG analyzes the conversation to extract the structured specification needed to synthesize a data pipeline, reducing user effort compared to traditional template-based systems.

Empirically, we found that without inference-time steering strategies, evaluated models frequently failed to generate appropriate clarifying questions for complex data tasks, consistent with observations reported in QuestBench (Li et al., 2025). Once task intent is sufficient, kRAIG queries a retrieval-augmented generation (RAG) component to retrieve the most relevant pipeline examples. We intentionally restricted the number of example pipelines to evaluate few-shot generalization. With the few pipeline examples kRAIG was able to achieve success in completing our internal tasks. Rather than increasing the number of example pipelines, our approach emphasizes few-shot generalization from a small set of representative examples.

2.1 Interface Example

```
Assistant: Where should the data from the ELT-
    Bench GitHub repository be stored?

User: git clone https://github.com/uiuc-kang-
    lab/ELT-Bench

A: Where should the data from the ELT-Bench
    GitHub repository be stored?

User: s3 name it cve-bench-new

A: What kind of data transformations would you
    like to perform on the GitHub repository
    data before storing it in the S3 bucket?

User: None, actually change the name of the s3
    to elt-bench-new
```

Figure 2: Example of questioning schema

3 Dynamic tool discovery and on-demand tool synthesis

After completing the initial task interpretation, kRAIG performs a post-hoc analysis to identify the tools required for the target ELT workflow, as shown in Figure 3. kRAIG formulates a retrieval query to a RAG component to obtain tools relevant to the current task. The retrieved tool specifications (e.g., interfaces, parameters, and constraints) are then used as context for pipeline generation.

Figure 3: kRAIG tools flow

Transformation steps in the ELT sequence can be highly diverse, making it impractical to define a set of all required tools prior to generation. To address this, kRAIG is able to synthesize task-specific tools when existing capabilities are insufficient. However, automated tool synthesis introduces safety risks, as generated tools may unintentionally truncate, delete, or otherwise compromise data integrity. We discuss mitigation strategies for these failure modes in the safeguards section. To improve the reliability of tool selection and synthesis, we apply inference-time steering using example pipelines, which biases generation toward valid transformation implementations and reduces deviation from expected pipeline structure.

4 Safeguards

Figure 4: kRAIG LLM Validation

Data security and safety are primary concerns in our design. Because kRAIG operates over potentially sensitive data lakes, we prevent the agent from issuing harmful operations. Prior work has shown that agentic systems may generate unsafe or destructive actions when operating without sufficient constraints.

To mitigate these risks, we implement two complementary safeguards:

- **LLM validation of generated pipelines.** After pipeline synthesis, a validation stage inspects the resulting specification for destructive operations (e.g., DROP TABLE, bulk deletions, or other data-removal patterns), as illustrated in Figure 4. Pipelines that violate safety constraints are rejected or automatically sanitized prior to execution.

- **Constrained tool usage.** For high-risk operations, kRAIG is restricted to a curated set of

tools with enforced safety constraints, such as read-only access or scoped writes. The agent cannot arbitrarily construct or invoke low-level operations in these cases. Instead, it must compose workflows from these controlled tools, enforcing constrained and safe pipelines.

Together, these mechanisms reduce the likelihood that kRAIG can generate or execute pipelines that compromise data integrity.

4.1 Kubeflow Pipeline Example

Figure 5 shows an example execution of a pipeline generated by kRAIG within Kubeflow. The run illustrates how the synthesized pipeline is compiled and executed within the orchestration framework.

Figure 5: Example of a kRAIG-generated Kubeflow run

5 Analysis and Data Visualization

We also extended kRAIG with capabilities for simple data visualization and aggregation tables, enabling effective auditing of the transformations performed within kRAIG's pipeline. Examples of kRAIG-generated tables and visualizations on user-provided data are shown in Figures 6 and 7. kRAIG requires data extraction to be performed as a separate step prior to downstream augmentation and visualization. For most tasks, kRAIG automatically generates a set of standard components:

- Data extraction
- Data transformation
- Data migration to the target source
- Basic data validation (e.g., comparing the number of rows inserted versus extracted)

These components enable users to audit intermediate results and verify correctness without manual checks.

5.1 Example of visualizations

Figure 6: Example of kRAIG Generated Table

Figure 7: Example of kRAIG generated graph

6 Evaluation

We evaluate kRAIG across three complementary dimensions: (i) model and prompting variant performance for pipeline generation, (ii) pipeline generation stability and variance, and (iii) end-to-end extract, loading and transform (ELT) performance on ELT Bench. Together, these evaluations assess kRAIG's ability to generate executable pipelines, minimize human intervention, support complex transformations, and balance reproducibility.

6.1 Model Variant Performance

Table 1 evaluates two large language models, Nova Premier and Claude 3.7, under three prompting variants: NL (pure natural language), NL + Exp (natural language with grounding examples of valid Kubeflow pipelines), and NL + Exp + Tools (examples plus optional pre-set tools). Each configuration is evaluated over three independent runs.

We report three metrics:

Model	Variant	SC (%)	SPC (%)	Num Edits Needed
Nova Premier	NL	0	0	N/A
Nova Premier	NL + Exp	58	33	6
Nova Premier	NL + Exp + Tools	77	66	9
Claude 3.7	NL	0	0	N/A
Claude 3.7	NL + Exp	91.67	100	2
Claude 3.7	NL + Exp + Tools	100	100	0

Table 1: Performance comparison across models and prompting variants. SC = Successful Components, SPC = Successful Pipelines Compiled.

- **Successful Components (SC)**: average percentage of pipeline components that successfully compile across runs. The total number of components varies by task (typically 1–4).

- **Successful Pipeline Components (SPC)**: fraction of runs in which the entire pipeline compiles and executes end-to-end.

- **Num Edits Needed**: number of manual code edits required by a human to achieve a successful end-to-end pipeline.

Results. With pure natural language prompting, both models fail to generate executable pipelines, resulting in 0% SC and 0% SPC. In these cases, generated code does not conform to Kubeflow pipeline requirements and never reaches a state where manual edits are meaningful.

Adding grounding example pipelines (NL + Exp) substantially improves pipeline performance. Nova Premier achieves 58% SC and 33% SPC, while Claude 3.7 reaches 91.67% SC and 100% SPC with only two manual edits. This demonstrates that structural pipeline grounding is critical for mapping user intent to executable pipelines.

Providing optional tools (NL + Exp + Tools) further improves component-level and pipeline-level success. Claude 3.7 achieves 100% SC and 100% SPC with zero manual edits, indicating fully autonomous pipeline generation. Nova Premier also improves to 77% SC and 66% SPC, with the cost of more manual edits. This result highlights a capability–complexity tradeoff, where additional tooling increases expressiveness but also raises the rate of error for less capable models.

Overall, these results show that kRAIG's design strongly benefits from structured prompting, and that model capability determines whether added tooling reduces or increases human intervention.

6.2 Pipeline Generation Variance and Reproducibility

We additionally evaluate kRAIG for generation stability under repeated prompting. Table 2 evaluates kRAIG's pipeline generation variance across six data sources, including Hugging Face datasets and GitHub repositories. For each source, we generate 20 pipelines using identical prompts and compute pairwise similarity between generated pipelines using a normalized sequence-based string similarity metric over the serialized pipeline code, with aggregate similarity statistics used to quantify generation variance.

We report average, minimum, and median similarity, as well as variance, number of unique pipeline versions, and duplication Gini coefficient.

Results. Across most data sources, kRAIG exhibits high average similarity (0.96–0.99), indicating strong stability. Hugging Face datasets, which typically involve more standardized data access patterns, show particularly high similarity and low variance.

GitHub repositories requiring nontrivial transformations (e.g., YOLO and NumPy) exhibit higher variance, lower minimum similarity, and more unique pipeline versions. This behavior is expected and desired, as transformation-heavy pipelines allow multiple valid implementations, giving kRAIG flexibility in writing custom transformation logic. Importantly, even in these cases, pipelines remain executable and diverse rather than collapsing to a single template.

These results demonstrate that kRAIG balances stability and diversity, producing consistent pipelines for standardized tasks while allowing controlled variation when task complexity increases.

6.3 ELT Bench Evaluation

We further evaluate kRAIG on ELT Bench, an existing benchmark designed to measure extraction,

Data Source	Avg Sim	Min Sim	Median Sim	Std Sim	Variance	Unique Versions	Duplication Gini
HuggingFace Cauldron	0.9802	0.9344	0.9875	0.0186	0.0198	14	0.2286
HuggingFace Docmatix	0.9978	0.9924	0.9968	0.0022	0.0022	6	0.5333
HuggingFace Mathvision	0.9973	0.9933	0.9973	0.0015	0.0027	15	0.2133
Grype Github Repo	0.9875	0.9237	0.9952	0.0197	0.0125	18	0.0889
Numpy Github Repo	0.9614	0.7949	0.9803	0.0474	0.0386	20	0
YOLO Github Repo	0.8990	0.7810	0.9007	0.0298	0.1010	20	0

Table 2: Similarity and duplication statistics across data sources, computed over 20 runs using the same prompt, highlighting output consistency and redundancy.

Method	LLM	SRDEL (%)	SRDT (%)
SWE-Agent	Claude-3.5-Sonnet	12.5	0
Spider-Agent	Claude-3.7-Sonnet (extended thinking)	25	0
Spider-Agent (Modified)	Claude-3.7-Sonnet (extended thinking)	**75**	12.5
kRAIG (Ours)	**Claude-3.7-Sonnet**	**75**	**25**

Table 3: ELT Bench SRDEL and SRDT performance across agent frameworks and LLMs.

loading, and transformation performance. We report two metrics:

- **SRDEL**: success rate of extraction and loading.

- **SRDT**: success rate of transformations, measured across all runs.

Table 3 compares kRAIG against SWE-Agent, Spider-Agent, and a custom modified variant of Spider-Agent adapted for ELT-style workflows.

Benchmark adaptation. ELT Bench was originally designed to evaluate general-purpose agents operating over a fixed set of data solutions. In contrast, kRAIG is designed as a specialized data engineering agent that leverages Python, Kubeflow, and complementary libraries to support diverse data sources, transformations, and target destinations.

To ensure a fair comparison, we randomly select eight ELT Bench tasks with evenly distributed difficulty, including simple to complex workflows. This same subset is used consistently to evaluate kRAIG, Spider-Agent, and SWE-Agent. Because ELT Bench tasks must be adapted to align with kRAIG's deployment and execution constraints, we restrict evaluation to a limited subset. The selected eight tasks are sufficiently diverse to capture a broad range of workflow complexities while remaining representative of the benchmark as a whole. For baseline comparisons, we evaluate each agent using its strongest single model configuration, rather than averaging across multiple variants.

Importantly, while ELT Bench is designed to evaluate extraction, loading, and transformation, in practice it primarily exercises loading and transformation logic. kRAIG's extraction capabilities extend beyond what the benchmark captures, including web scrapers, crawlers, Hugging Face dataset loaders, and custom data ingestion utilities. As a result, the benchmark should be interpreted primarily as an evaluation of load and transform performance.

Spider-Agent modification. In addition to the original Spider-Agent, we evaluate a modified variant adapted for ELT-style tasks. In practical data engineering settings, execution environments often vary and task descriptions frequently omit critical setup details (e.g., infrastructure configuration or schema assumptions). Under such ambiguity, purely iterative agents can fail due to repeated execution errors.

We modify Spider-Agent by updating its instruction examples to include a setup and structural details before pipeline generation. This change steers the agent toward more effective reasoning under under-specified instructions. We include this variant to reflect realistic prompt adaptation and to assess whether kRAIG's results persist against a tuned baseline.

Results. Existing agents exhibit limited ELT performance. For each baseline, we report results using the best-performing model configuration identified during preliminary evaluation. SWE-Agent achieves an SRDEL of 12.5%, with SRDT near zero across most model configurations. Even with extended reasoning, Spider-Agent reaches only 25% SRDEL and 0% SRDT, while the modified

agent matches kRAIG's SRDEL with only a 12.5% SRDT.

kRAIG achieves **75% SRDEL** and **25% SRDT**, substantially outperforming all baselines, particularly on transformation tasks where prior methods largely fail.

A key contributor to this improvement is kRAIG's ability to clarify underspecified execution assumptions before pipeline generation. Several ELT Bench tasks involve MongoDB-backed workflows where critical configuration details (e.g., local vs. managed deployment or expected schema) are not specified in the prompt.

In such cases, Spider-Agent and SWE-Agent must implicitly infer infrastructure details and frequently fail under repeated execution errors, leading to invalid pipelines. In contrast, kRAIG explicitly queries missing execution context before pipeline synthesis, preventing cascading failures and resulting in higher end-to-end success.

6.4 Discussion

Across all evaluations, kRAIG consistently demonstrates strong end-to-end performance:

1. Structured prompting with grounding examples is essential for executable pipeline generation, while tool integration enables full autonomy for capable models.

2. kRAIG produces stable and reproducible pipelines under repeated prompting, while allowing increased diversity for transformation-heavy tasks.

3. On ELT Bench, kRAIG significantly improves on extraction, loading, and transformation performance compared to established agents.

Beyond benchmarked tasks, kRAIG has been successfully applied internally to complex real-world workloads, including security data cleaning for CVE analysis and image preprocessing pipelines over Hugging Face datasets. These tasks involve diverse sources, nontrivial transformations, and heterogeneous destinations, highlighting kRAIG's flexibility and practical utility.

These results validate kRAIG as a robust agent framework that reduces human intervention, supports complex transformations, and generalizes across a wide range of data engineering tasks.

Limitations

kRAIG demonstrates the ability to generate data pipelines that consistently compile and execute. However, performance varies across task types. The system performs more reliably on extraction and load tasks than on complex transformation tasks, which often require more nuanced reasoning and domain-specific logic.

For extraction tasks, difficulty increases when workflows involve a large number of highly heterogeneous or geographically dispersed data sources, which can overwhelm kRAIG's ability to accurately infer task structure and dependencies. In complex scenarios, kRAIG may also fail to identify missing task specifications and may proceed without sufficient clarification, leading to incomplete or suboptimal pipelines.

These limitations reflect broader challenges in current large language models' ability to identify under-specified requirements and generate effective clarifying questions, consistent with observations reported in QuestBench (Li et al., 2025).

Conclusion

Our development and evaluation of kRAIG reveal several key distinctions relative to agents evaluated in ELT-Bench:

- **Reason–Question–Action Framework.** Introducing an explicit questioning phase prior to action selection reduces task ambiguity and prevents cascading failures caused by under-specified instructions. Analysis of Spider-Agent trajectories indicates that certain failures arise from schema inconsistencies between local and cloud environments, which additional reasoning iterations alone cannot resolve.

- **Context Distillation.** Summarizing and distilling important information from conversational history and task specifications improves success rates on complex workflows, particularly when instruction length approaches model context limits.

- **Limitations of Traditional ReAct Frameworks.** Pure reason-then-act approaches are more susceptible to ambiguity in natural language instructions, often resulting in inefficient reasoning paths and increased execution steps before reaching valid solutions.

In this iteration, the kRAIG agent is primarily designed to reliably execute internal tasks. Our development and evaluation efforts focus on leveraging the Kubeflow platform and implementing functionalities that support our researchers by enabling greater focus on data analysis, while automating repetitive operations and reducing manual effort within the machine learning workflow.

Future Work

Our evaluation highlights several limitations that motivate future work. A primary direction is a comprehensive evaluation of kRAIG across the full ELT-Bench task suite to better characterize its strengths and failure modes. In parallel, we aim to expand kRAIG's functional capabilities while maintaining strict adherence to security and governance constraints required for internal deployment.

6.5 Expansion of Questioning Ability

An important direction for future work is improving kRAIG's ability to identify missing or ambiguous task specifications and to generate targeted clarifying questions. We plan to explore a range of training and post-training techniques to enhance the base model's ability to infer intermediate steps required for diverse data engineering tasks and to detect when critical information is absent.

Once missing steps are identified, the agent must generate context-aware questions that elicit the necessary details from users. While kRAIG demonstrates reduced performance in this area, the inherent structure of extract, load, and transform workflows enable reasonable performance on standard ELT tasks through few-shot generalization, retrieval-augmented examples, and constrained tool usage.

6.6 Enhancements on Data Visualization and Analytics

We plan to enhance kRAIG's data visualization and analytics capabilities, with improvements to complex transformation pipelines serving as a key enabling factor. Strengthening transformation support will allow kRAIG to more effectively generate, audit, and analyze intermediate and final datasets, enabling end-to-end workflows that extract, transform, and visually summarize data in response to user queries.

6.7 Guardrail Improvement

We acknowledge that the LLM-based validation and static patterns used here are necessary but insufficient for high-stakes production environments, as they may be susceptible to adversarial 'jailbreaking' or sophisticated prompt injection. Next-generation security for kRAIG must move beyond reactive guardrails toward formal verification of generated code and sand-boxed symbolic execution. These methods would allow the system to mathematically guarantee that a generated pipeline cannot perform unauthorized data deletions or out-of-scope writes before a single line of code is executed.

Ethical Considerations

kRAIG is an AI agent that translates natural-language requests into executable data engineering pipelines. Because such pipelines may access sensitive data sources and can perform write operations, incorrect generations or misuse could cause harms including inadvertent disclosure of private data, creation of non-compliant derived datasets, corruption or loss of data through unsafe transformations, and operational disruptions (e.g., triggering expensive jobs or propagating erroneous outputs downstream).

We explicitly design kRAIG with safety considerations for DataOps settings. First, we incorporate static validation of generated pipelines to detect and reject destructive operations (e.g., patterns resembling bulk deletions or irreversible data removal) prior to execution. Second, kRAIG is constrained to compose workflows from a curated set of vetted tools rather than issuing arbitrary low-level actions, reducing the likelihood of unsafe behaviors and supporting organizational policies such as least-privilege access. In practical deployments, kRAIG should additionally be operated with standard governance controls including authentication/authorization, audit logging, and clear separation between development and production environments, with human review for high-risk changes.

Our evaluation focuses on pipeline executability and benchmark performance; it does not constitute comprehensive security testing or red-teaming against adversarial prompts. Future work includes more rigorous evaluation of safety guarantees under adversarial or ambiguous instructions, and stronger policy enforcement for write operations and dataset handling across heterogeneous sources and destinations.

Use of AI Assistants

We used AI assistants for editing assistance and code debugging during the preparation of this work. The authors take full responsibility for all content.

References

Airbyte. 2025. Airbyte: Open source data integration. Accessed: 01/16/2026.

Amazon Web Services. 2025. Amazon sagemaker: Machine learning service. Accessed: 09/26/2025.

Chinmaya Andukuri, Jan-Philipp Fränken, Tobias Gerstenberg, and Noah D. Goodman. 2024. Star-gate: Teaching language models to ask clarifying questions.

Anthropic. 2024. The claude 3 model family: Opus, sonnet, haiku.

Yonatan Bisk, Ari Holtzman, Jesse Thomason, Jacob Andreas, Yoshua Bengio, Joyce Chai, Mirella Lapata, Angeliki Lazaridou, Jonathan May, Aleksandr Nisnevich, Nicolas Pinto, and Joseph Turian. 2020. Experience grounds language. *arXiv preprint arXiv:2004.10151*.

Jingyi Chen, Songqiang Chen, Jialun Cao, Jiasi Shen, and Shing-Chi Cheung. 2025. When llms meet api documentation: Can retrieval augmentation aid code generation just as it helps developers?

Amazon Artificial General Intelligence. 2024. The amazon nova family of models: Technical report and model card. *Amazon Technical Reports*.

Tengjun Jin, Yuxuan Zhu, and Daniel Kang. 2025. Eltbench: An end-to-end benchmark for evaluating ai agents on elt pipelines.

Fangyu Lei, Jixuan Chen, Yuxiao Ye, Ruisheng Cao, Dongchan Shin, Hongjin Su, Zhaoqing Suo, Hongcheng Gao, Wenjing Hu, Pengcheng Yin, Victor Zhong, Caiming Xiong, Ruoxi Sun, Qian Liu, Sida Wang, and Tao Yu. 2024. Spider 2.0: Evaluating language models on real-world enterprise text-to-sql workflows.

Belinda Z. Li, Been Kim, and Zi Wang. 2025. Questbench: Can llms ask the right question to acquire information in reasoning tasks?

Changle Qu, Sunhao Dai, Xiaochi Wei, Hengyi Cai, Shuaiqiang Wang, Dawei Yin, Jun Xu, and Ji-Rong Wen. 2024. Tool learning with large language models: A survey. *arXiv preprint arXiv:2405.17935*.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. *arXiv preprint arXiv:2302.04761*.

Hongru Wang, Lingzhi Wang, Yiming Du, Liang Chen, Jingyan Zhou, Yufei Wang, and Kam-Fai Wong. 2023. A survey of the evolution of language model-based dialogue systems. *arXiv preprint arXiv:2311.16789*.

John Yang, Carlos E Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik R Narasimhan, and Ofir Press. 2024. SWE-agent: Agent-computer interfaces enable automated software engineering. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*.