Analytic Insights into Structure and Rank of Neural Network Hessian Maps

Abstract

The Hessian of a neural network captures parameter interactions through second-order derivatives of the loss. It is a fundamental object of study, closely tied to various problems in deep learning, including model design, optimization, and generalization. Most prior work has been empirical, typically focusing on low-rank approximations and heuristics that are blind to the network structure. In contrast, we develop theoretical tools to analyze the range of the Hessian map, providing us with a precise understanding of its rank deficiency as well as the structural reasons behind it. This yields exact formulas and tight upper bounds for the Hessian rank of deep linear networks, allowing for an elegant interpretation in terms of rank deficiency. Moreover, we demonstrate that our bounds remain faithful as an estimate of the numerical Hessian rank, for a larger class of models such as rectified and hyperbolic tangent networks. Further, we also investigate the implications of model architecture (e.g. width, depth, bias) on the rank deficiency. Overall, our work provides novel insights into the source and extent of redundancy in overparameterized networks.

1 Introduction

Since the very infancy of neural networks, the Hessian matrix has been a central object of study. This is because the Hessian captures pairwise interactions of parameters via second-order derivatives of the loss function. As a result, the Hessian was productively employed, for instance, in (quasi-Newton) optimization methods [1, 2], model design and pruning [3–5], generalization [6], network calibration [7], automatically tuning hyper-parameters [8]. But, from the outset the main practical challenge has been its size, scaling quadratically with the model dimensionality. This makes the problem severe for today's DNNs which have millions or even billions of parameters [9, 10].

Consequently, most prior work has focused on designing scalable Hessian approximations, which either take the route of Hessian-vector products (R-operator) [11–13] or employ positive definite approximations by appealing to the Fisher information matrix. Additional approximations — without exception — are needed on top, such as diagonal approximations [3, 14] in the former or K-FAC [15–17] restricted to layerwise or arbitrary blocks on the diagonal [18–20], in the latter.

The goal of this paper is to advance the analytical understanding of the Hessian map of a neural network. We pursue the fundamental question of how the model architecture induces structural properties of the Hessian. In particular, we analyze the dimension of its range (i.e., the rank) and identify the sources of rank deficiency. Understanding the range of the Hessian map, in turn, delivers insights into the important aspect of how gradients change between iterations.

A reason why such an important direction currently remains sidelined is that non-linearities in a neural network result in an increased dependence on the data distribution, making a suitable theoretical analysis seem intractable. Following Saxe et al. [21], Kawaguchi [22], who delivered

useful general insights on neural networks by looking at the linear case, we take a step back and rigorously characterize the range of the Hessian map and determine the resultant rank deficiency for deep linear networks. *The key result of our paper is an exact formula along with tight upper bound on the rank of the Hessian — which effectively depend on the sum of hidden-layer widths.* This stands opposed to the total number of parameters which are proportional to the sum of squared layer widths, thus implying a significant redundancy in the parameterization of neural networks (see Figure 1).

The exact quantification of the Hessian rank gives a precise yet interpretable ballpark on the inherent complexity of neural networks since rank naturally measures the effective number of parameters. This relationship is further reinforced by connection to the classical complexity measure of Gull [23], MacKay [24], which is equivalent to rank for a sufficiently small constant controlling the prior. Therefore, this sheds a novel perspective on the nature and degree of overparameterization in neural networks, and opens up interesting avenues for future investigation.

Contributions. (i) Section 3: We characterize the structure in the Hessian range by exhibiting it in the form of matrix derivatives. (ii) Section 4: We prove tight upper bounds and provide exact formulas on the Hessian rank that are neatly interpretable. *To the best of our knowledge, this is the very first time that such formulas and bounds are made available for neural networks.* (iii) Section 5.2: In the non-linear case, we show that our (linear) rank formulae faithfully capture the numerical rank. (iv) Section 6: We demonstrate via experiments and theory that such rank bounds also hold during the course of training. (v) Section 7.1: In the non-linear case, we also provide a pessimistic yet non-trivial bound, which provably establishes degeneracy of the Hessian at the minimum. (vi) Section 7.2, 5.1: We extend our rank results to the case

Figure 1: Hessian spectrum of linear and ReLU networks at initialization. Dashed lines indicate our rank predictions. Results have been averaged over 3 runs.

of bias and investigate the effects of architectural components (such as width, depth, bias) on rank. (vii) Appendix S9: As a by-product, our analysis also reveals interesting properties of the Hessian spectrum, and we prove the presence of additional redundancies due to repeated eigenvalue plateaus.

Related work. The study of the Hessian, in recent times, has been re-invigorated by the empirical observations of Sagun et al. [25, 26] who noted a high degree of degeneracy experimentally, and characterized the spectrum as being composed of a bulk around zero and few outlier eigenvalues. Since then, works such as [27, 28] have scaled the empirical analysis to bigger networks via efficient spectral density calculations and better explained the observations in [26]. However, a drawback is that due to their empirical nature, it remains hard to uncover the exact level of degeneracy via these methods [29], and neither are the exact factors that affect the rank deficiency discerned. Another approach has been to fit models from random matrix theory to match the observed Hessian spectrum in neural networks [29, 30], however, such methods do not properly capture the sharp peak at zero observed in empirical spectra [31]. Yet others have investigated the properties of the spectrum in the asymptotic regime [32, 33], but the bounds, if any, are quite coarse (see Fig. 4). Moreover, a common issue underlying most of these approaches is that they are blind to the layerwise compositional structure of neural networks, and are often motivated by reference to a black-box decomposition of the Hessian.

In regards to indicating the parameter redundancy in neural networks, we are far from being the first work. Prior empirical studies have long reported similar observations, like in the form of, post-training pruning [3, 4, 19, 20, 34] or inherently contained sub-networks (Lottery Ticket Hypothesis [35]). Recently, [36] have experimentally argued for the effective dimensionality from [23, 24] to be a good predictor of double descent [37]. Nevertheless, determining the precise extent of redundancy and the structural reasons behind it, have remained illusory in such approaches.

2 Setup and Formalism

General notation. We use the shorthand, $\mathbf{W}^{k:l}$, to refer to the matrix product chain $\mathbf{W}^k \cdots \mathbf{W}^l$, when $k > l$. When $k < l$, $\mathbf{W}^{k:l}$ will stand for the transposed product chain $\mathbf{W}^{k\top} \cdots \mathbf{W}^{l\top}$. Besides,

$\otimes$ denotes the Kronecker product of two matrices, vec_r indicates the row-wise vectorization of matrices, rk refers to the rank of a matrix, and $\mathbf{I}_k$ is the identity matrix of size $k \times k$.

Deep Neural Networks (DNNs). A feedforward DNN is a composition of maps, i.e., $F = F^L \circ \cdots \circ F^1$, where the l-th layer map $F^l : \mathbb{R}^{M_{l-1}} \to \mathbb{R}^{M_l}$, with input dimension $d := M_0$, output dimension $K := M_L$, total number of hidden neurons $M := \sum_{l=1}^{L-1} M_l$. Each layer map is parameterized by a weight matrix $\mathbf{W}^l$ and applies an elementwise activation function σ^l. So we have,

$$F^l = \sigma^l \circ \mathbf{W}^l \text{ with } \mathbf{W}^l \in \mathbb{R}^{M_l \times M_{l-1}} \text{ and } \sigma^l : \mathbb{R} \to \mathbb{R}.$$

For the sake of tractability, we will often investigate linear DNNs where $\sigma^l = \mathrm{id}$, and so $F(\mathbf{x}) = \mathbf{W}^{L:1}\mathbf{x}$. For compactness, we also represent the entire set of parameters by $\boldsymbol{\theta} := \{\mathbf{W}^1, \cdots, \mathbf{W}^L\}$, and where emphasis requires, we will subscript the DNN map F with it and write $F_{\boldsymbol{\theta}}$.

Next, assume that we are given a dataset $S = \{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1}^N$ of N input-output pairs, drawn i.i.d from an underlying distribution $p_{\mathbf{x},\mathbf{y}}$. Our focus will be on the squared loss (MSE), $\ell_{\mathbf{x},\mathbf{y}}(\boldsymbol{\theta}) = \frac{1}{2}\|\mathbf{y} - \hat{\mathbf{y}}\|^2$ and its residual $\boldsymbol{\delta}_{\mathbf{x},\mathbf{y}} := \hat{\mathbf{y}} - \mathbf{y} = \frac{\partial \ell_{\mathbf{x},\mathbf{y}}}{\partial \hat{\mathbf{y}}}$, where $\hat{\mathbf{y}} = F_{\boldsymbol{\theta}}(\mathbf{x})$ is the DNN prediction. The population loss, $\mathcal{L}$ is: $\mathcal{L}(\boldsymbol{\theta}) = \mathbf{E}_{p_{\mathbf{x},\mathbf{y}}}[\ell_{\mathbf{x},\mathbf{y}}(\boldsymbol{\theta})]$. Finally, we will analyze the Hessian matrix $\mathbf{H}_{\mathcal{L}} = \frac{\partial^2 \mathcal{L}}{\partial \boldsymbol{\theta} \partial \boldsymbol{\theta}}$.

Backpropagation in matrix derivatives. As all parameters are collected into matrices, we often work with matrix-matrix derivatives by vectorizing *row-wise* in the numerator (Jacobian) layout, i.e., $\frac{\partial \mathbf{Y}}{\partial \mathbf{X}} := \frac{\partial \mathrm{vec}_r(\mathbf{Y})}{\partial \mathrm{vec}_r(\mathbf{X})^\top}$, see [38] and Appendix S3.5. Alongside this, we use the following rule:

$$\frac{\partial \mathbf{AWB}}{\partial \mathbf{W}} = \mathbf{A} \otimes \mathbf{B}^\top, \quad \text{e.g.} \quad \frac{\partial F}{\partial \mathbf{W}^k} = \mathbf{W}^{L:k+1} \otimes \mathbf{x}^\top \mathbf{W}^{1:k-1} \in \mathbb{R}^{K \times M_k M_{k-1}}. \tag{1}$$

By the usual chain rule (backpropagation) one has for a linear DNN, at a sample $(\mathbf{x}, \mathbf{y})$:

$$\frac{\partial \ell_{\mathbf{x},\mathbf{y}}}{\partial \mathbf{W}^k} = \underbrace{\left[\mathbf{W}^{k+1:L}\boldsymbol{\delta}_{\mathbf{x},\mathbf{y}}\right]}_{\text{backward} \in \mathbb{R}^{M_k}} \cdot \underbrace{\left[\mathbf{W}^{k-1:1}\mathbf{x}\right]^\top}_{\text{forward} \in \mathbb{R}^{M_{k-1}}} = \mathbf{W}^{k+1:L}\left[\mathbf{W}^{L:1}\mathbf{x}\mathbf{x}^\top - \mathbf{y}\mathbf{x}^\top\right]\mathbf{W}^{1:k-1}. \tag{2}$$

The above gradient with respect to $\mathbf{W}^k$ is of first order in $\mathbf{W}^k$ itself and second order in the other weight matrices. Lastly, let us setup the following shorthand, $\boldsymbol{\Omega} := \mathbf{E}[\boldsymbol{\delta}_{\mathbf{x},\mathbf{y}}\mathbf{x}^\top] = \mathbf{E}[\mathbf{W}^{L:1}\mathbf{x}\mathbf{x}^\top - \mathbf{y}\mathbf{x}^\top]$, $\boldsymbol{\Sigma}_{\mathbf{xx}} := \mathbf{E}[\mathbf{x}\mathbf{x}^\top]$, and $\boldsymbol{\Sigma}_{\mathbf{yx}} := \mathbf{E}[\mathbf{y}\mathbf{x}^\top]$, which we will use throughout the paper.

3 Hessian Maps of Linear DNNs

3.1 Hessian structure

The Hessian map has a natural block structure defined by the layers and their dimensionality. In order to leverage this structure, we directly take the derivative of the loss gradient in a matrix-by-matrix fashion. First, consider the k-th diagonal block of the Hessian, which is independent of $\mathbf{y}$ and is given by,

$$\mathbf{H}_{\mathcal{L}}^{kk} := \frac{\partial^2 \mathcal{L}}{\partial \mathbf{W}^k \partial \mathbf{W}^k} = \mathbf{W}^{k+1:L}\mathbf{W}^{L:k+1} \otimes \mathbf{W}^{k-1:1}\boldsymbol{\Sigma}_{\mathbf{xx}}\mathbf{W}^{1:k-1}.$$

This follows from the matrix-derivative rule in Eq. (1) along with the Eq. (2) and taking expectation. The calculation of the off-diagonal Hessian blocks (kl-th block of size $M_k M_{k-1} \times M_l M_{l-1}$) involves the product rule. Note that the two occurrences of a weight matrix $\mathbf{W}^l$, in Eq. (2), are once non-transposed (in $\mathbf{W}^{L:1}\mathbf{x}\mathbf{x}^\top$) and once transposed (in $\mathbf{W}^{k+1:L}$ or $\mathbf{W}^{1:k-1}$ respectively for $k < l$ or $k > l$). For simplicity, let us express these parts without adding them and directly write the other Hessian contribution with respect to the *transposed matrix*, giving:

$$\forall k \neq l, \quad \widetilde{\mathbf{H}}_{\mathcal{L}}^{kl} := \frac{\partial^2 \mathcal{L}}{\partial \mathbf{W}^l \partial \mathbf{W}^k} = \mathbf{W}^{k+1:L}\mathbf{W}^{L:l+1} \otimes \mathbf{W}^{k-1:1}\boldsymbol{\Sigma}_{\mathbf{xx}}\mathbf{W}^{1:l-1}. \tag{3}$$

$$\forall k < l \quad \widehat{\mathbf{H}}_{\mathcal{L}}^{kl} := \frac{\partial^2 \mathcal{L}}{\partial \mathbf{W}^{l\top} \partial \mathbf{W}^k} = \mathbf{W}^{k+1:l-1} \otimes \mathbf{W}^{k-1:1}\boldsymbol{\Omega}^\top \mathbf{W}^{L:l+1}. \tag{4}$$

$$\forall k > l \quad \widehat{\mathbf{H}}_{\mathcal{L}}^{kl} := \frac{\partial^2 \mathcal{L}}{\partial \mathbf{W}^{l\top} \partial \mathbf{W}^k} = \mathbf{W}^{k+1:L}\boldsymbol{\Omega}\mathbf{W}^{1:l-1} \otimes \mathbf{W}^{k-1:l+1}. \tag{5}$$

122 **Equivalence to Gauss-Newton Decomposition.** A common approach is to look at the Hessian
123 map from the perspective of the Hessian chain rule, where we have that, $\mathbf{H}_{\mathcal{L}} = \mathbf{H}_o + \mathbf{H}_f$, with

$$\mathbf{H}_o = \mathbf{E}_{p_{\mathbf{x},\mathbf{y}}} \left[\nabla_{\boldsymbol{\theta}} F(\mathbf{x})^\top \left[\partial^2 \ell_{\mathbf{x},\mathbf{y}} \right] \nabla_{\boldsymbol{\theta}} F(\mathbf{x}) \right] , \quad \text{and} \quad \mathbf{H}_f = \mathbf{E}_{p_{\mathbf{x},\mathbf{y}}} \left[\sum_{c=1}^{K} [\partial \ell_{\mathbf{x},\mathbf{y}}]_c \, \nabla_{\boldsymbol{\theta}}^2 F_c(\mathbf{x}) \right] .$$

124 For the MSE loss, the Gauss-Newton decomposition is in fact equivalent to what we discussed before
125 (see details in Appendix S1), where $\mathbf{H}_o$ contains the blocks $\mathbf{H}_{\mathcal{L}}^{kk}$ and $\widetilde{\mathbf{H}}_{\mathcal{L}}^{kl}$, while $\mathbf{H}_f$ consists of
126 $\widehat{\mathbf{H}}_{\mathcal{L}}^{kl}$ (although with the non-transposed matrix). Henceforth, we will refer to the first term $\mathbf{H}_o$ as the
127 *outer-product Hessian*, while we coin the second-term $\mathbf{H}_f$ as the *functional Hessian*.

3.2 Range of the Hessian map

129 Assuming a local Taylor-series approximation of the loss' gradient, we have that for $\|\Delta\boldsymbol{\theta}\| < \epsilon$,
130 $\nabla_{\boldsymbol{\theta}+\Delta\boldsymbol{\theta}} \mathcal{L} \approx \nabla_{\boldsymbol{\theta}} \mathcal{L} + \mathbf{H}_{\mathcal{L}} \Delta\boldsymbol{\theta}$. This indicates how the gradients will change over any local perturbation
131 $\Delta\boldsymbol{\theta}$. As a result, this also holds over successive iterations of an optimization algorithm such as gradient
132 descent, and serves to show the significance of the Hessian range. Let us multiply the two parts of the
133 Hessian with a vector $\Delta\boldsymbol{\theta}$, which we decompose as $\Delta\boldsymbol{\theta} = \left[\text{vec}_r(\Delta\mathbf{W}^1)^\top \ \ldots \ \text{vec}_r(\Delta\mathbf{W}^L)^\top \right]^\top$ to
134 best reflect the layerwise structure (the details of the following characterization are in Appendix S2).

135 **Range of the outer-product $\mathbf{H}_o$** The product of the k-th row-block $\mathbf{H}_o^{k\bullet}$, corresponding to the k^{th}
136 layer, with $\Delta\boldsymbol{\theta}$ can be written succinctly as, $\mathbf{H}_o^{k\bullet} \cdot \Delta\boldsymbol{\theta} = \text{vec}_r\left(\mathbf{W}^{k+1:L} \cdot \bar{\Delta} \cdot \mathbf{W}^{1:k-1} \right)$, $\bar{\Delta} :=$
137 $\sum_{l=1}^{L} \mathbf{W}^{L:l+1} \Delta\mathbf{W}^l \mathbf{W}^{l-1:1} \Sigma_{\mathbf{xx}}$, with $\bar{\Delta} \in \mathbb{R}^{K \times d}$. This already hints that there is a significant
138 intrinsic structure in the Hessian that constrains its range, and the dependence manifests itself only
139 through $\bar{\Delta}$ of dimension Kd.

140 **Range of the functional Hessian $\mathbf{H}_f$** Here we multiply with $\widehat{\Delta\boldsymbol{\theta}}$, which is similar to
141 $\Delta\boldsymbol{\theta}$ except that we consider $\Delta\mathbf{W}^{l\top}$ instead of $\Delta\mathbf{W}^l$. Then the product corresponding to
142 k^{th} layer is, $\mathbf{H}_f^{k\bullet} \cdot \widehat{\Delta\boldsymbol{\theta}} = \text{vec}_r\left(\mathbf{W}^{k+1:L} \Omega [\Delta^{<k}]^\top + [\Delta^{>k}]^\top \Omega \mathbf{W}^{1:k-1} \right)$, where $\Delta^{<k} :=$
143 $\sum_{l=1}^{k-1} \mathbf{W}^{k-1:l+1} \Delta\mathbf{W}^l \mathbf{W}^{l-1:1}$ and $\Delta^{>k} := \sum_{l=k+1}^{L} \mathbf{W}^{L:l+1} \Delta\mathbf{W}^l \mathbf{W}^{l-1:k+1}$. Notice that the
144 range of $\mathbf{H}_f$ is also inherently constrained, albeit in a more intricate manner as compared to the case of
145 $\mathbf{H}_o$. But as we will see ahead, this neatly gives rise to a dependence on the sum of hidden-layer widths.

4 Main result: Analysis of the Hessian rank

147 **Preliminaries.** Let us denote the rank of the uncentered covariance $\Sigma_{\mathbf{xx}} = \mathbf{E}\left[\mathbf{xx}^\top\right]$ by r. If
148 $r < d$, then without loss of generality, consider $\Sigma_{\mathbf{xx}} := (\Sigma_{\mathbf{xx}})_{r \times r}$, which is always possible by pre-
149 processing the input. Thus, $\Sigma_{\mathbf{xx}} \succ 0$, always. Also, in such a case, we take $\mathbf{W}^1 \in \mathbb{R}^{M_1 \times r}$. Further,
150 the only assumption we make in our analysis is A1, which is in fact guaranteed at typical initialization
151 with high probability (c.f. Appendix S3.6). In Section 6, we see what happens while training.

152 **Assumption A1.** *Maximal Rank:* $\forall l \in [L]$, $\mathbf{W}^l \in \mathbb{R}^{M_l \times M_{l-1}}$ *has rank equal to* $\min(M_l, M_{l-1})$.

153 Lastly, the omitted proofs in the coming subsections are located in Appendices S3, S4, S5 respectively.

4.1 Analytical tool

155 The key idea of our analysis technique is to reduce the rank of involved matrices to the rank of a
156 certain special kind of matrix (or its variant), $\mathbf{Z}$, as shown below:

$$\mathbf{Z} = \begin{pmatrix} \mathbf{I}_q \otimes \mathbf{C} \\ \mathbf{D} \otimes \mathbf{I}_n \end{pmatrix} , \quad \text{with } \mathbf{C} \in \mathbb{R}^{m \times n}, \ \mathbf{D} \in \mathbb{R}^{p \times q} . \tag{6}$$

157 This row-partitioned matrix has a characteristic structure, where an identity matrix alternates between
158 the two sides of the Kronecker product. Such matrices are in fact omnipresent in the Hessian structure,
159 and importantly for our purpose, they possess additional properties on their rank. Inherent to these
160 properties and our analysis, is the use of generalized inverse [39] and oblique (non-orthogonal)
161 projector matrices. The following Lemma 1 from [40] details such a result:
162 **Lemma 1.** *Let $\mathbf{Z}$ be a matrix as in Eq. (6). Then,* $\text{rk}(\mathbf{Z}) = q \, \text{rk}(\mathbf{C}) + n \, \text{rk}(\mathbf{D}) - \text{rk}(\mathbf{C}) \, \text{rk}(\mathbf{D})$.

4.2 Rank of the outer-product Hessian

Consider the following decomposition of $\mathbf{H}_o$, which reveals its 'outer-product' nature:

Proposition 2. *For a deep linear network,* $\mathbf{H}_o = \mathbf{A}_o \mathbf{B}_o \mathbf{A}_o^{\top}$, *where* $\mathbf{B}_o = \mathbf{I}_K \otimes \boldsymbol{\Sigma}_{\mathbf{xx}} \in \mathbb{R}^{Kd \times Kd}$,

$$\text{and } \mathbf{A}_o^{\top} = \begin{pmatrix} \mathbf{W}^{L:2} \otimes \mathbf{I}_d & \cdots & \mathbf{W}^{L:l+1} \otimes \mathbf{W}^{1:l-1} & \cdots & \mathbf{I}_K \otimes \mathbf{W}^{1:L-1} \end{pmatrix} \in \mathbb{R}^{Kd \times p},$$

where p is the number of parameters. A straightforward consequence is that if there is no bottleneck in between, i.e., no hidden-layer with width $M_i < \min(K, d)$, then the matrix $\mathbf{B}_o$ will control the rank of $\mathbf{H}_o$. Hence, as a first upper bound we get, $\text{rk}(\mathbf{H}_o) \leq \min(\text{rk}(\mathbf{A}_o), \text{rk}(\mathbf{B}_o)) = \text{rk}(\mathbf{B}_o) = \text{rk}(\mathbf{I}_K)\,\text{rk}(\boldsymbol{\Sigma}_{\mathbf{xx}}) = Kr$.

Such a decomposition is however not new (see [41]), but this only forms an initial step of our analysis and the current bound can be loose in the bottleneck case (e.g., an auto-encoder). Let us define the minimum dimension to be $q := \min(r, M_1, \cdots, M_{L-1}, K)$. Our main theorem can then be stated as:

Theorem 3. *Consider the matrix* $\mathbf{A}_o$ *mentioned in Proposition 2. Under the assumption A1,*
$\text{rk}(\mathbf{A}_o) = r\,\text{rk}(\mathbf{W}^{2:L}) + K\,\text{rk}(\mathbf{W}^{L-1:1}) - \text{rk}(\mathbf{W}^{2:L})\,\text{rk}(\mathbf{W}^{L-1:1}) = q\,(r + K - q)$.

Now, from Theorem 3, it is evident that we can simply upper bound the rank of $\mathbf{H}_o$, by the rank of $\mathbf{A}_o$. But actually, it is possible to show an equality (using Lemma 18), as described below:

Corollary 4. *Under the setup of Theorem 3, the rank of* $\mathbf{H}_o$ *is given by* $\text{rk}(\mathbf{H}_o) = q\,(r + K - q)$.

Remark. It should be emphasized that this analysis not only delivers the rank of the outer-product Hessian but also of Neural Tangent Kernel [42] (see Appendix S10.5), Fisher information matrix, network Jacobian, due to their underlying intimate relationship, unaltered through the lens of rank.

4.3 Rank of the functional Hessian

For analyzing the rank of the functional Hessian $\mathbf{H}_f$, we will continue operating by having one of the derivatives with respect to a transposed weight matrix (here, $\mathbf{W}^{l\top}$), since rank does not change with column or row permutations. We denote this modification of the functional Hessian by $\widehat{\mathbf{H}}_f$. Then from Eqs. (4, 5), we can observe that there is a common structure within the blocks contained in the column l. Namely, all the weight matrix-chains have either $l-1$ or $l+1$ as their right indices. So our approach will be to bound the rank of the individual column blocks, as formalized below:

Theorem 5. *For a deep linear network, the rank of* l-*th column-block,* $\widehat{\mathbf{H}}_f^{\bullet l}$, *of the matrix* $\widehat{\mathbf{H}}_f$, *under the assumption A1 is given as* $\text{rk}(\widehat{\mathbf{H}}_f^{\bullet l}) = q\,M_{l-1} + q\,M_l - q^2$, *for* $l \in [2, \cdots, L-1]$. *When* $l \in \{1, L\}$, *we have* $\text{rk}(\widehat{\mathbf{H}}_f^{\bullet l}) = q\,M_l + q\,s - q^2$. *Here,* $q := \min(r, M_1, \cdots, M_{L-1}, K, s)$ *and* $s := \text{rk}(\boldsymbol{\Omega}) = \text{rk}(\mathbf{E}\,[\boldsymbol{\delta}_{\mathbf{x,y}}\,\mathbf{x}^{\top}])$.

The upper bound on the rank of $\mathbf{H}_f$ follows by combining the above result over all the columns:

Corollary 6. *Under the setup of Theorem 5, the rank of* $\mathbf{H}_f$ *can be upper bounded as,*
$\text{rk}(\mathbf{H}_f) \leq 2\,q\,M + 2\,q\,s - L\,q^2$, *where* $M = \sum_{i=1}^{L-1} M_i$.

Although the above corollary states an upper bound, empirically we find that this is precisely the formula at initialization, and thus we have the *tightest upper bound on the rank of the functional Hessian*. Also, we find that usually at initialization $s = \min(r, K)$, although this is not needed for the proof.

Block-column independence. A surprising element of the above analysis is that just adding the ranks of the block-columns, corresponding to the respective layers, gives the rank of the entire $\mathbf{H}_f$ which is tight. This phenomenon is quite straightforward to see in a 2-layer network and there Corollary 6 is an equality. However, the more interesting observation is that this holds even for arbitrary depth and also extends to networks *with non-linearities* such as ReLU and Tanh. This implies that the column spaces associated with the layerwise block-columns do not overlap. Thus, $\mathbf{H}_f$ *is similar to a block diagonal matrix*, and it should be possible to uncover the similarity transformation. But this is beyond the current scope, and we leave it as an open question.

4.4 Overall bound on the Hessian Rank

Finally, in order to get an upper bound on the rank of the entire Hessian, we simply use $\text{rk}(\mathbf{A} + \mathbf{B}) \leq \text{rk}(\mathbf{A}) + \text{rk}(\mathbf{B})$, along with the Corollary 4 and Corollary 6, to obtain:
$$\text{rk}(\mathbf{H}_{\mathcal{L}}) \leq \text{rk}(\mathbf{H}_o) + \text{rk}(\mathbf{H}_f) \leq 2\,q\,M - L\,q^2 + 2\,q\,s + q\,(r + K - q).$$

Fact 7. *The following equality holds empirically:* $\boxed{\mathrm{rk}(\mathbf{H}_{\mathcal{L}}) = 2q\,M - L\,q^2 + q(r + K)}$.

This implies that our upper bound is off by just a constant additive factor of $2\,q\,s - q^2$, which is another startling finding. Thus, revealing that the *intersection of the* $\mathbf{H}_o$, $\mathbf{H}_f$ *column spaces has a rather small dimension*. E.g., take the typical case of no bottlenecks, $q = s$, then our upper bound exceeds the true rank by a small constant q^2, i.e., minimum dimension squared. This suggests that the direct sum of their column spaces is not too far-fetched as an approximation to the column space of $\mathbf{H}_{\mathcal{L}}$. Previously, [30] empirically noted a similar observation for 1-hidden layer networks and [33] showed a high degree of mutual orthogonality in the asymptotic regime. Our result shows a similar consequence in the finite case.

Alternative interpretation. Besides the above result, that the rank of the Hessian is proportional to the sum of widths, there is an alternate way of viewing this. Let us calculate the rank deficiency in the network when (uncentered) input-covariance has rank, i.e., $r = d$. Using Fact. (7) this comes out to rank-deficiency$(\mathbf{H}_{\mathcal{L}}) = \sum_{i=0}^{L-1}(M_i - q)(M_{i+1} - q)$, whereas the number of parameters is equal to $p = \sum_{i=0}^{L-1} M_i M_{i+1}$. Hence this lends an elegant interpretation to our formula, whereby the amount of rank deficiency is equal to the number of parameters of a hypothetical network whose all layer-widths have been subtracted by the minimum layer-width of the original network.

5 Empirical Results

5.1 Verification of Rank formulas and their behaviour

(a) Rank vs # samples N **(b)** Rank vs minimal width M_* **(c)** $\frac{\mathrm{rank}}{\#\,\mathrm{params}}$ vs minimal width M_*

Figure 2: Behaviour of rank and rank/#params on CIFAR10 using MSE, with hidden layers: $50, 20, 20, 20$ (Fig. 2a) and M_*, M_* (Fig. 2b, 2c). The lines indicate the true value and circles denote our formula predictions.

Setup. We test our results on a *variety of datasets*: MNIST [43], FashionMNIST [44], CIFAR10 [45]; for *various loss types*: MSE, cross-entropy, cosh; across *several initialization schemes*: Glorot [46], uniform, orthogonal [21]. Our theory extends to all these settings. However, due to space constraints we only show a subset of experiments here, but the rest can be found in the Appendix S10.

Procedure. To verify the prediction of our theoretical results, we perform an exact calculation of the rank by computing the full Hessian and the corresponding singular value decomposition (SVD). The available iterative schemes for rank approximation (c.f. [47]), although more memory-efficient, are only effective for well-separated spectra and thus cannot provide useful approximations in the case of neural network Hessians. Besides the exact Hessian computation, we also utilize FLOAT-64 precision to ensure 'true' rank calculation, resulting in increased memory costs. Hence, we downscale the image resolution to $d = 64$ to test on more realistic networks.

Results. We study how the rank varies as a function of the sample size N and the network architecture (for varying widths). Fig. 2 shows this for a linear network on CIFAR10 with MSE loss. First, in Fig 2a, we observe that our predictions match the true rank exactly across all sample sizes as the dependence on N is only exhibited in the rank of the empirical covariance $\widehat{\boldsymbol{\Sigma}}_{\mathbf{xx}}$, confirming that rank is largely a distribution-independent quantity. So, for the rest of our experiments, we sufficiently subsample to ensure that the empirical and true covariance have the same rank. Next, in Fig. 2b, we see that *our rank formulas hold for arbitrary-sized network architectures*. To contextualize the growth of rank with increasing width, in Fig. 2c, we normalize it by # params p. We notice that rank/# params, which intuitively captures the fraction of effective parameters, saturates down to a small level — *signalling the extent of redundancy present in the network parameterization* (similar plots across depth and simulation of rank/# params on larger settings can be found in S10.1, S10.2).

5.2 The case of non-linearities

Although the linear nature of the neural network was crucial to our analysis, in this section we show experimentally that our results also extend to the non-linear setting — as numerical rank [48].

Figure 3: Spectrum of the loss Hessian $\mathbf{H}_{\mathcal{L}}$ (left), functional Hessian $\mathbf{H}_f$ (middle) and outer product $\mathbf{H}_o$ (right), for **linear** and **non-linear** networks. Black dashed lines are the predictions of the bulk size via our rank formulas. We use 2 hidden layers of size $30, 20$ with Tanh activation on MNIST.

Visual comparison of the Hessian spectra. Let us first understand how non-linearities affect the Hessian spectrum relative to the spectrum of linear networks. Fig. 3 compares the spectra of $\mathbf{H}_{\mathcal{L}}$, $\mathbf{H}_f$, $\mathbf{H}_o$ in these two scenarios (linear vs Tanh), with a zoomed-in inset near the cut-off obtained from rank formulas corresponding to the linear case. We can observe the presence of numerous tiny, but not exactly zero, eigenvalues in the non-linear case. So, if we were to measure the rank with a threshold up to machine precision — as we did in the linear case — this would result in an inflation of the rank measurement for the non-linear scenario. From a practical point of view, tiny but non-zero eigenvalues hold little significance, so a more relevant quantity is the numerical rank [48] that uses a reasonable threshold to weed out such extraneous eigenvalues. The numerical rank, or alternatively the size of bulk around zero, for the non-linear case, indeed seems to be captured by our (linear) rank formulas to high fidelity, as evident from Fig. 3. Similar results for other non-linearities, loss functions, datasets can be found in the Appendix S10.4.

Quantitative measure of the fidelity of Rank formulas. To complement the visual grounds presented above, we now quantitatively measure the (in)significance of such spuriously tiny eigenvalues, in terms of the reconstruction error incurred by excluding them. Hence, we perform a low-rank approximation via the SVD and measure the (relative) reconstruction error at the value of rank from our formulas of the linear case. Fig. 4 displays the reconstruction error as a function of the # of top eigenvectors employed, for a ReLU network. As a reference, we consider the empirical rank measurement obtained at machine precision in this case. *We find that using the linear rank value provides an excellent reconstruction (*0.002%* error), hence demonstrating the fidelity of our rank formulas to serve as a measure of numerical rank in the non-linear case.* The same observation extends to other non-linearities and losses, which we highlight in the Appendix S10.3. Consequently, iterative Hessian estimation procedures, e.g. in second-order optimization methods [16], could

Figure 4: Hessian reconstruction error for a **ReLU** network of hidden layer sizes $30, 20$, as the rank of the approximation is increased. The dashed vertical lines indicate the cut-off at various values of the rank: **first line** at the prediction based on the linear model, **second line** at the empirical measurement of rank, and **third line** based on upper bounds from [33], which become too coarse to be of any use (actually even > # parameters).

benefit from the linear rank as a guiding criterion for their design of Hessian approximation. Besides, these experiments also indicate that previous bounds, such as those by Jacot et al. [33], on the rank of outer-product Hessian and functional Hessian are quite coarse to be of much use. This is because these bounds have a linear dependence on the product of: # of samples N and # of classes K.

6 Evolution of Rank during training

The upper bounds on the Hessian rank detailed before inherently depend on the rank of the weight matrices. While initialization guarantees them to be of maximal rank, the rank of weight matrices might possibly decrease during training, thus bringing about a decrease in the Hessian rank. Under some additional assumptions, Lemma 8 shows that this does not happen and the rank remains constant.

Lemma 8. *For a deep linear network, consider the gradient flow dynamics $\dot{\mathbf{W}}_t^l = -\eta \nabla_{\mathbf{W}^l} \mathcal{L}_S(\boldsymbol{\theta})\big|_{\boldsymbol{\theta}=\boldsymbol{\theta}_t}$. Assume: (a) Centered classes: $\frac{1}{N}\sum_{i:y_{ic}=1}^N \mathbf{x}_i = \mathbf{0}$, $\forall c \in [1,\ldots,K]$. (b) Balancedness at initialization: $\mathbf{W}_0^{k+1\top}\mathbf{W}_0^{k+1} = \mathbf{W}_0^k \mathbf{W}_0^{k\top}$. (c) Square weight-matrices: $\mathbf{W}^l \in \mathbb{R}^{M \times M}$, $\forall l$ and $K = d = M$. Then for all layers l, $\mathrm{rk}(\mathbf{W}_t^l) = \mathrm{rk}(\mathbf{W}_0^l)$, $\forall t < \infty$.*

Balancedness is a common assumption that has been used in many previous works, like Arora et al. [49]. Centered classes can easily be enforced via a pre-processing step, however empirically this is not required. While the proof (see Appendix S6) holds for square case, empirically we also find this to be true for non-square matrices and non-linearities as shown in Fig. 5 (and more in Appendix S6).

Figure 5: Rank dynamics for a ReLU network with hidden layer sizes $25, 20, 15$, trained on a subset of MNIST. We show the evolution of the rank of the weights (left) with usual Glorot initialization (guaranteeing maximal rank) and the rank of the Hessians as a function of training time (right).

Consequence. An implication of this result is that *our upper bounds on the Hessian rank remain valid throughout the training.* Even if the rank of the weight matrices were to decrease, say in the rectangular case, the Hessian rank would only decrease and our bounds would still be valid. The other avenue for a decrease in rank is learning-driven, and as $\boldsymbol{\Omega} = \mathbf{E}\left[\boldsymbol{\delta}_{\mathbf{x},\mathbf{y}}\mathbf{x}^\top\right] \to 0$, the functional Hessian $\mathbf{H}_f \to \mathbf{0}$ (as it has an explicit dependence on the residual $\boldsymbol{\delta}_{\mathbf{x},\mathbf{y}}$). So, if the learning architecture is powerful enough, the rank of $\mathbf{H}_f$ will approach 0, as well as leading to a decrease in the rank of $\mathbf{H}_\mathcal{L}$, and so $\mathrm{rk}(\mathbf{H}_\mathcal{L}) \to \mathrm{rk}(\mathbf{H}_o)$. In other words, the loss Hessian is completely captured through the outer product Hessian at convergence. These observations also extend to the non-linear case, as shown in Fig. 5.

7 Further results

7.1 Provable Hessian degeneracy with non-linearities

From Section 5.2, it is clear that our upper bounds faithfully estimate the numerical rank in the non-linear case, despite the numerous tiny eigenvalues which cause inflated rank measurements. This might raise the question if it is possible to establish, in this non-linear case, that the Hessian has provable degeneracy and not just approximate? The challenge is that here the data distribution manifests additionally via the activations at each layer, thus a theoretical analysis seems intractable without imposing strong assumptions. For a 1-hidden layer network, $F(\mathbf{x}) = \mathbf{W}^2\sigma(\mathbf{W}^1\mathbf{x})$, we show it is still possible to get a pessimistic yet non-trivial upper bound with the following (mild) assumption:

Assumption A2. *For each active hidden neuron i, the weighted input covariance has the same rank as the overall input covariance, i.e., $\mathrm{rk}(\mathbf{E}\left[\alpha_{\mathbf{x}}\mathbf{x}\mathbf{x}^\top\right]) = \mathrm{rk}(\boldsymbol{\Sigma}_{\mathbf{xx}}) = r$, with $\alpha_{\mathbf{x}} = \sigma'(\mathbf{x}^\top \mathbf{W}_{i\bullet}^1)^2$.*

Theorem 9. *Consider a 1-hidden layer network with non-linearity σ such that $\sigma(z) = \sigma'(z)z$ and let $\widetilde{M}$ be the # of active hidden neurons (i.e., probability of activation > 0). Then, under assumption A1 and A2, rank of $\mathbf{H}_o$ is given as, $\mathrm{rk}(\mathbf{H}_o) \leq r\widetilde{M} + \widetilde{M}K - \widetilde{M}$.*

Assumption A2 is rather mild, i.e., in the finite-sample case, it holds as soon as the # of samples $N > 2d$, for typical initialization of parameter weights. Besides, the class of non-linearities which satisfy the above-mentioned condition includes e.g., *ReLU, Leaky-ReLU*. Further, this result extends to $\mathbf{H}_\mathcal{L}$:

Corollary 10. *At convergence to the minimum, the rank of the loss Hessian $\mathbf{H}_\mathcal{L}$, for the same setup as Theorem 9, is upper bounded by: $\mathrm{rk}(\mathbf{H}_\mathcal{L}) \leq r\widetilde{M} + \widetilde{M}K - \widetilde{M}$.*

Contrast this with the view from [50], who claim the spectrum to be generically non-degenerate. Or, unlike [51], we establish this without any assumptions on a particular kind of overparameterization.

Fact 11. *For multiple hidden-layers, the following generalization of Theorem 9 holds empirically, $\mathrm{rk}(\mathbf{H}_o) \leq p - M_1(d-r) - \sum_{i=1}^{L-1} M_i$, where p is the # of parameters and assuming no dead neurons.*

While these bounds are likely to be quite loose as noticeable from Section 5.2, *but more importantly they help establish provable degeneracy of the Hessian at the minimum, with the number of 'absolutely-flat' directions (i.e., those in the Hessian null space) in proportion to the sum of hidden-layer sizes.*

7.2 Effect of bias on the rank of Hessian

Now, we see how the Hessian rank changes when bias is enabled throughout a deep linear network. We make the following simplifying assumption, which is actually a standard convention in practice.

Assumption A3. *The input data has zero mean, i.e.,* $\mathbf{x} \sim p_{\mathbf{x}}$ *is such that* $\mathbf{E}\left[\mathbf{x}\right] = 0$.

> **Theorem 12.** *Under the assumption A1 and A3, for a deep linear network with bias, the rank of* $\mathbf{H}_o$ *is upper bounded as,* $\mathrm{rk}(\mathbf{H}_o) \leq q(r + K - q) + K$, *where* $q := \min(r, M_1, \cdots, M_{L-1}, K)$.

The proof can be found in the Appendix S8. Empirically, we do not require the input to be mean zero and our upper bound actually holds with equality. Also, we list rank formulas for functional Hessian and the overall Hessian in Appendix S8, in the non-bottleneck case. E.g.,

Fact 13. $\mathrm{rk}\left(\mathbf{H}_{\mathcal{L}}\right) = 2q'M + q'(r+K) - Lq'^2 + Lq'$, *where* $q' := \min(r+1, M_1, \cdots, M_{L-1}, K)$.

Here as well, rank deficiency has a cleaner interpretation of being equal to the # of parameters in a hypothetical network with bias enabled, albeit with the minimum dimension q' (that reflects the homogeneous coordinate at input) subtracted: rank-deficiency$(\mathbf{H}_{\mathcal{L}}) = \sum_{i=0}^{L-1}(M_i+1-q')(M_{i+1}-q')$.

8 Conclusion

Summary.   Our paper provides a precise understanding of how the neural network structure constrains the Hessian range and the resulting rank deficiency. In contrast to the number of parameters which are proportional to layer-widths squared, we obtain that rank is proportional to layer-width. The proof strategy relies on bounding the rank of the two parts of the Hessian separately, i.e., the outer-product Hessian $\mathbf{H}_o$ and the functional Hessian $\mathbf{H}_f$, both of which are replete with the special $\mathbf{Z}$-like structure. The analysis also reveals several striking properties of the Hessian, such as surprisingly small overlap in the column spaces of $\mathbf{H}_o$ and $\mathbf{H}_f$, and independence of the layer-wise column blocks in $\mathbf{H}_f$. While our results were derived assuming linear activations, we demonstrate that, even with non-linearities, our formulas faithfully capture the numerical rank. All in all, our work delivers important insights into the nature and degree of parameterization contained in a neural network as a result of its compositional structure.

Discussion.   Our results merit discussion on some of the fundamental aspects of deep learning:

(i) Overparameterization: Modern DNNs, with billions of parameters, are in stark contrast to the traditional statistical viewpoint of having # of parameters approximately equal to the # of samples. While several works have argued for measuring model complexity instead through weight norms [52], margins [53], compressibility [54], yet it remains hard to get an interpretable ballpark on the model complexity of neural networks. Since rank intuitively captures the notion of effective parameters, it could be a *possible alternative to benchmark overparameterization*, e.g. for double descent [37].

(ii) Flatness: A growing number of works [55–57] correlate the choice of regularizers, optimizers, or hyperparameters, with the additional flatness brought about by them at the minimum. However, the significant rank degeneracy of the Hessian, which we have provably established, also points to *another source of flatness* — that exists as a virtue of the compositional model structure —from the initialization itself. Thus, a prospective avenue of future work would be to compare different architectures based on this inherent kind of flatness.

(iii) Generalization: An interesting observation available from our work is that factors such as width, depth, enabling bias — commonly observed to improve generalization — *also result in decreasing the rank/# parameters ratio*, see Appendix S10.2. In a similar vein, recent work of [58] has provided a lower bound to the generalization error of statistical estimators in terms of the rank of the Fisher (which is intimately related to the Hessian) divided by # of parameters. Practically, one could use a further relaxation of rank as nuclear norm normalized by the spectral norm, in scenarios with spurious rank inflation. Overall, this suggests the relevance of studying the link between rank and generalization.

Besides the above aspects, there are many other interesting questions that naturally arise. These include, to list a few: (a) finding the Hessian rank for convolutional networks, (b) using the rank formulae to build informed models of the Hessian spectrum [29, 30], (c) obtaining an equality on the bounds — which is what we observe empirically at initialization, (d) better understanding the interaction between $\mathbf{H}_o$ and $\mathbf{H}_f$. To conclude, by providing fundamental insights into the range of the Hessian map, our work paves the way to exciting avenues for future research.

References

[1] Ciyou Zhu, Richard H Byrd, Peihuang Lu, and Jorge Nocedal. Algorithm 778: L-bfgs-b: Fortran subroutines for large-scale bound-constrained optimization. *ACM Transactions on Mathematical Software (TOMS)*, 23(4):550–560, 1997.

[2] Rudy Setiono and Lucas Chi Kwong Hui. Use of a quasi-newton method in a feedforward neural network construction algorithm. *IEEE Transactions on Neural Networks*, 6(1):273–277, 1995.

[3] Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pages 598–605, 1990.

[4] Babak Hassibi and David G. Stork. Second order derivatives for network pruning: Optimal brain surgeon. In *NIPS*, pages 164–171, 1992. URL http://papers.nips.cc/paper/647-second-order-derivatives-for-network-pruning-optimal-brain-surgeon.

[5] Sepp Hochreiter and Jürgen Schmidhuber. Simplifying neural nets by discovering flat minima. In *Advances in neural information processing systems*, pages 529–536, 1995.

[6] David J. C. MacKay. A Practical Bayesian Framework for Backpropagation Networks. *Neural Computation*, 4(3):448–472, 05 1992. ISSN 0899-7667. doi: 10.1162/neco.1992.4.3.448. URL https://doi.org/10.1162/neco.1992.4.3.448.

[7] John S. Denker and Yann LeCun. Transforming neural-net output levels to probability distributions. In *Proceedings of the 3rd International Conference on Neural Information Processing Systems*, NIPS'90, page 853–859, San Francisco, CA, USA, 1990. Morgan Kaufmann Publishers Inc. ISBN 1558601848.

[8] Y. LeCun, P. Simard, and Barak A. Pearlmutter. Automatic learning rate maximization by on-line estimation of the hessian's eigenvectors. In *NIPS 1992*, 1992.

[9] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

[10] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *Proceedings of NAACL-HLT*, 2019.

[11] Barak A Pearlmutter. Fast exact multiplication by the hessian. *Neural computation*, 6(1):147–160, 1994.

[12] James Martens and Ilya Sutskever. Learning recurrent neural networks with hessian-free optimization. In *ICML*, 2011.

[13] Frédéric Bastien, Pascal Lamblin, Razvan Pascanu, James Bergstra, Ian Goodfellow, Arnaud Bergeron, Nicolas Bouchard, David Warde-Farley, and Yoshua Bengio. Theano: new features and speed improvements. *arXiv preprint arXiv:1211.5590*, 2012.

[14] Tom Schaul, Sixin Zhang, and Yann LeCun. No more pesky learning rates, 2013.

[15] James Martens and Roger Grosse. Optimizing neural networks with kronecker-factored approximate curvature, 2020.

[16] Aleksandar Botev, Hippolyt Ritter, and David Barber. Practical gauss-newton optimisation for deep learning. In *International Conference on Machine Learning*, pages 557–565. PMLR, 2017.

[17] Donald Goldfarb, Yi Ren, and Achraf Bahamou. Practical quasi-newton methods for training deep neural networks. *arXiv preprint arXiv:2006.08877*, 2020.

[18] César Laurent, Thomas George, Xavier Bouthillier, Nicolas Ballas, and Pascal Vincent. An evaluation of fisher approximations beyond kronecker factorization, 2018. URL https://openreview.net/forum?id=ryVC6tkwG.

[19] Xin Dong, Shangyu Chen, and Sinno Jialin Pan. Learning to prune deep neural networks via layer-wise optimal brain surgeon, 2017.

[20] Sidak Pal Singh and Dan Alistarh. Woodfisher: Efficient second-order approximation for neural network compression, 2020.

[21] Andrew M. Saxe, James L. McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks, 2014.

[22] Kenji Kawaguchi. Deep learning without poor local minima, 2016.

[23] Stephen F. Gull. *Developments in Maximum Entropy Data Analysis*, pages 53–71. Springer Netherlands, Dordrecht, 1989. ISBN 978-94-015-7860-8. doi: 10.1007/978-94-015-7860-8_4. URL https://doi.org/10.1007/978-94-015-7860-8_4.

[24] David MacKay. Bayesian model comparison and backprop nets. In J. Moody, S. Hanson, and R. P. Lippmann, editors, *Advances in Neural Information Processing Systems*, volume 4. Morgan-Kaufmann, 1992. URL https://proceedings.neurips.cc/paper/1991/file/c3c59e5f8b3e9753913f4d435b53c308-Paper.pdf.

[25] Levent Sagun, Leon Bottou, and Yann LeCun. Eigenvalues of the hessian in deep learning: Singularity and beyond. *arXiv preprint arXiv:1611.07476*, 2016.

[26] Levent Sagun, Utku Evci, V Ugur Guney, Yann Dauphin, and Leon Bottou. Empirical analysis of the hessian of over-parametrized neural networks. *arXiv preprint arXiv:1706.04454*, 2017.

[27] Behrooz Ghorbani, Shankar Krishnan, and Ying Xiao. An investigation into neural net optimization via hessian eigenvalue density. In *International Conference on Machine Learning*, pages 2232–2241. PMLR, 2019.

[28] Vardan Papyan. Measurements of three-level hierarchical structure in the outliers in the spectrum of deepnet hessians. *arXiv preprint arXiv:1901.08244*, 2019.

[29] Diego Granziol, Timur Garipov, Dmitry Vetrov, Stefan Zohren, Stephen Roberts, and Andrew Gordon Wilson. Towards understanding the true loss surface of deep neural networks using random matrix theory and iterative spectral methods, 2020. URL https://openreview.net/forum?id=H1gza2NtwH.

[30] Jeffrey Pennington and Yasaman Bahri. Geometry of neural network loss surfaces via random matrix theory. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2798–2806. PMLR, 06–11 Aug 2017. URL http://proceedings.mlr.press/v70/pennington17a.html.

[31] Diego Granziol. Beyond random matrix theory for deep networks. *ArXiv*, abs/2006.07721, 2020.

[32] Ryo Karakida, Shotaro Akaho, and Shun ichi Amari. Universal statistics of fisher information in deep neural networks: Mean field approach, 2019.

[33] Arthur Jacot, Franck Gabriel, and Clément Hongler. The asymptotic spectrum of the hessian of dnn throughout training. *arXiv preprint arXiv:1910.02875*, 2019.

[34] Song Han, Huizi Mao, and William J. Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding, 2016.

[35] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv: Learning*, 2019.

[36] Wesley J. Maddox, Gregory Benton, and Andrew Gordon Wilson. Rethinking parameter counting: Effective dimensionality revisted. *arXiv preprint arXiv:2003.02139*, 2020.

[37] Mikhail Belkin, Daniel J. Hsu, Siyuan Ma, and Soumik Mandal. Reconciling modern machine-learning practice and the classical bias–variance trade-off. *Proceedings of the National Academy of Sciences*, 116: 15849 – 15854, 2019.

[38] Jan R Magnus and Heinz Neudecker. *Matrix differential calculus with applications in statistics and econometrics*. John Wiley & Sons, 2019.

[39] C Radhakrishna Rao. Generalized inverse of a matrix and its applications. In *Vol. 1 Theory of Statistics*, pages 601–620. University of California Press, 1972.

[40] Jianjun Chuai and Yongge Tian. Rank equalities and inequalities for kronecker products of matrices with applications. *Applied Mathematics and Computation*, 150(1):129–137, 2004. ISSN 0096-3003. doi: https://doi.org/10.1016/S0096-3003(03)00203-0. URL https://www.sciencedirect.com/science/article/pii/S0096300303002030.

[41] Alberto Bernacchia, Mate Lengyel, and Guillaume Hennequin. Exact natural gradient in deep linear networks and its application to the nonlinear case. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/7f018eb7b301a66658931cb8a93fd6e8-Paper.pdf.

[42] Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *arXiv preprint arXiv:1806.07572*, 2018.

[43] Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010.

[44] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

[45] Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009.

[46] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In Yee Whye Teh and Mike Titterington, editors, *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pages 249–256, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR. URL http://proceedings.mlr.press/v9/glorot10a.html.

[47] Shashanka Ubaru and Yousef Saad. Fast methods for estimating the numerical rank of large matrices. page 468–477, 2016.

[48] Gene H. Golub, Virginia C. Klema, and Gilbert W. Stewart. Rank degeneracy and least squares problems. Technical report, Stanford, CA, USA, 1976.

[49] Sanjeev Arora, Nadav Cohen, Noah Golowich, and Wei Hu. A convergence analysis of gradient descent for deep linear neural networks, 2019.

[50] Jeffrey Pennington and Pratik Worah. The spectrum of the fisher information matrix of a single-hidden-layer neural network. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/18bb68e2b38e4a8ce7cf4f6b2625768c-Paper.pdf.

[51] Tomaso Poggio, Kenji Kawaguchi, Qianli Liao, Brando Miranda, Lorenzo Rosasco, Xavier Boix, Jack Hidary, and Hrushikesh Mhaskar. Theory of deep learning iii: explaining the non-overfitting puzzle, 2018.

[52] Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In Peter Grünwald, Elad Hazan, and Satyen Kale, editors, *Proceedings of The 28th Conference on Learning Theory*, volume 40 of *Proceedings of Machine Learning Research*, pages 1376–1401, Paris, France, 03–06 Jul 2015. PMLR. URL http://proceedings.mlr.press/v40/Neyshabur15.html.

[53] Peter Bartlett, Dylan J. Foster, and Matus Telgarsky. Spectrally-normalized margin bounds for neural networks, 2017.

[54] Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach, 2018.

[55] Nitish Shirish Keskar, Dheevatsa Mudigere, Jorge Nocedal, Mikhail Smelyanskiy, and Ping Tak Peter Tang. On large-batch training for deep learning: Generalization gap and sharp minima. *arXiv preprint arXiv:1609.04836*, 2016.

[56] Stanisław Jastrzębski, Zachary Kenton, Devansh Arpit, Nicolas Ballas, Asja Fischer, Yoshua Bengio, and Amos Storkey. Finding flatter minima with sgd, 2018. URL https://openreview.net/forum?id=r1VF9dCUG.

[57] Carlo Baldassi, Fabrizio Pittorino, and Riccardo Zecchina. Shaping the learning landscape in neural networks around wide flat minima. *Proceedings of the National Academy of Sciences*, 117(1):161–170, 2020.

[58] Inbar Seroussi and Ofer Zeitouni. Lower bounds on the generalization error of nonlinear learning models. *arXiv preprint arXiv:2103.14723*, 2021.

[59] George Matsaglia and George P. H. Styan. Equalities and inequalities for ranks of matrices. *Linear and Multilinear Algebra*, 2(3):269–292, 1974. doi: 10.1080/03081087408817070. URL https://doi.org/10.1080/03081087408817070.