Multilayer Dense Connections for Hierarchical Concept Prediction

Abstract

Classification is a pivotal function for many computer vision tasks such as image recognition, object detection, scene segmentation. Multinomial logistic regression with a single final layer of dense connections has become the ubiquitous technique for CNN-based classification. While these classifiers learn a mapping between the input and a set of output category classes, they do not typically learn a comprehensive knowledge about the category. In particular, when a CNN based image classifier correctly identifies the image of a Chimpanzee, it does not know that it is a member of Primate, Mammal, Chordate families and a living thing. We propose a multilayer dense connectivity for a CNN to simultaneously predict the category *and* its conceptual superclasses in hierarchical order. We experimentally demonstrate that our proposed dense connections, in conjunction with popular convolutional feature layers, can learn to predict the conceptual classes with minimal increase in network size while maintaining the categorical classification accuracy.

1 Introduction

Classification is a core concept for numerous computer vision tasks. Given the convolutional features, different architectures classify either the image itself (He et al., 2015; Szegedy et al., 2016), the region/bounding boxes for object detection (He et al., 2017; Liu et al., 2015), or, at the granular level, pixels for scene segmentation (Chen et al., 2018). Although early image recognition works employed multilayer classification layers (Krizhevsky et al., 2012; Simonyan & Zisserman, 2015), the more recent models have all been using single layer dense connection (He et al., 2016; Szegedy et al., 2016) or convolutions (Lin et al., 2017).

The vision community has invented a multitude of techniques to enhance the capacity of feature computation layers (Xie et al., 2017; Huang et al., 2017; Hu et al., 2018; Dai et al., 2017; Chollet, 2016; Tan & Le, 2019). But, the classification layer has mostly retained the form of a multinomial/softmax logistic regression performing a mapping from a set of inputs (images) to a set of categories/labels. As such, the networks themselves do not acquire a comprehensive knowledge about the input entity. In particular, when an existing CNN correctly identifies an image of an English Setter, the network itself does not learn that it is an instance of a dog, or more precisely, a hunting dog which is also a domestic animal and above all, a living thing. Acquiring such knowledge is perhaps essential for cognitive empowerment of CNNs; it can be argued that encoding exhaustive information about object categories, and building upon it, is crucial for automation of intelligent systems.

Extensive information about most categories are freely available in repositories such as WordNet (Fellbaum, 1998). WordNet provides the hierarchical organization of category classes (e.g., English Setter) and their conceptual superclasses (e.g., Hunting dog, Domestic animal, Living thing). However, a surprisingly limited number of CNNs utilize the concept hierarchy. The primary goal of almost all existing studies is to improve the category-wise classification performance by exploiting the conceptual relations, often via a separate tool.

Deng et al. (2014) and Ding et al. (2015) apply graphical models to capture the interdependence among concept labels to improve category classification accuracy. Other works either do not clarify the semantic meaning of the ancestor concepts (Yan et al., 2015) or do not explain how the hierarchy was generated (Guo et al., 2017). We have not found an existing (deep learning) model that attempts to predict both the finer categories and the chain of ancestor concepts for an input image by a single

network. The classical hedging method (Deng et al., 2012) computes either the finer labels or one of its superclasses *exclusively*, but not both simultaneously.

In this paper, we introduce a CNN to classify the category *and* the concept superclasses simultaneously. As illustrated in Figure 1, in order to classify any category class (e.g., English Setter), our model is constrained to also predict the ancestor superclasses (e.g., Hunting dog, Domestic animal, Living thing) in the same order as defined in a given ontology. We propose a configuration of multilayer dense connections to predict the category & concept superclasses as well as model their interrelations based on the ontology. We also propose a simple method to prune and rearrange the label hierarchy for efficient connectivity.

Existing methods: English Setter

Proposed prediction: Living thing → Domestic → Hunting Dog → English Setter.

Figure 1: The goal of the proposed algorithm. In contrast to the existing methods, our proposed CNN architecture predicts the chain of superclass concepts as well as the finer category.

Capturing the hierarchical relationship within the CNN architecture itself enables us to train the model end-to-end (as opposed to attaching a separate tool) by applying existing optimization strategies for training deep networks. We experimentally demonstrate that one can train the proposed architecture using standard optimization protocols to predict the concept classes with two popular CNN backbones: ResNet and InceptionV4, while maintaining their category-wise accuracy. The proposed model also equips us to learn the multilayer dense configurations capturing the label relationships from data using architecture learning techniques (Zoph et al., 2017; Pham et al., 2018).

Predicting coarser superclasses in addition to finer level categories improves interpretability of the classifier performance. Even if an eagle is misclassified as a parrot, the capability of inferring that it is a bird, and not an artifact (e.g., drone), may be beneficial in some applications (e.g., surveillance). More importantly, an object detector can enhance its capability on unseen categories by adopting the proposed classification scheme (as demonstrated in Section 5.3). For example, a movie/TV violence recognition/detection tool can recognize an equipment as a 'weapon' concept class even if that particular weapon category was not in the training set. In visual question answering (VQA), encoding concept classes would expand the scope of query terms by allowing broader description ('how many vehicles are present' in addition to 'how many buses', 'how many trucks' etc.; see Cao et al. (2018); Wang et al. (2016)). In Appendix G, we point out how our architecture can be extended to object detectors to compute the concept classes. In addition, we allude to the potential applications of our model to capture label structures different from concept graph, e.g., spatial or compositional dependence.

2 RELEVANT WORKS

Use of hierarchical classifiers can be traced back to the early works of Torralba et al. (2004); Wu et al. (2004); Fergus et al. (2010) that shared features for improved classification. Some studies claimed a hierarchical organization of categories resembles how human cognitive system stores knowledge (Zhao et al., 2011) while others experimentally showed a correspondence between structure of semantic hierarchy and visual confusion between categories (Deng et al., 2010). Bengio et al. (2010); Deng et al. (2011) learn a label tree for efficient inference with low theoretical complexity and also suggest a label hierarchy is beneficial for datasets with tens of thousands of categories.

Deng et al. (2012) aim to predict either a coarse level concept or a fine level category (but not both at the same time) given an initial classical classifier. Provided an initial classifier output, this method determines category or the coarse concept node (exclusively) with max reward based on aggregated probabilities in a label hierarchy. The reported results suggest the prediction of superclasses comes at the expense of the fine level category classification failure. For CNN based classification, Deng et al. (2014) modeled the relationships such as subsumption, overlap and exclusion among the categories via a CRF. Although the CRF parameter can be trained via gradient descent, the inference required a separate computation of message passing. The work of Ding et al. (2015) extended this model by utilizing probabilistic label relationships.

Figure 2: Partial view of the original (left) and condensed (right) label hierarchies. Concepts are enclosed in rectangular boxes, with number of all descendants in parentheses.

The HDCNN framework (Yan et al., 2015) groups the finer classes into coarse concept using the category labels. The framework comprises two modules for coarse and fine categories where the coarse prediction modulates the layers for finer classification. However, this work does not describe the coarser concept classes in order to analyze whether they, or their descendent categories, have any semantic meaning (see Appendix H). Furthermore, the overlap among concept class descendants precludes a mechanism to predict the conceptual superclasses. Guo et al. (2017) attempted to classify the coarse labels or the conceptual superclasses of categories by augmenting an RNN to CNN output. In addition to increased complexity imposed by the RNN, it is not clear how the hierarchy among labels was generated and how the hierarchy would scale up with increasing number of categories.

There are a few other studies that proposed to incorporate structural prediction techniques in their design (Hu et al., 2016; Liang, 2019); we provide their description in Appendix A due to space limitation. Unlike us, the primary objective of almost all the aforementioned papers is to improve the category prediction performance by utilizing the superclass hierarchy as an auxiliary source of information or as intermediate result. With the exception of classical Deng et al. (2012), none of these studies were designed for, and demonstrate their effectiveness in, concept prediction. The algorithms of Deng et al. (2014); Guo et al. (2017) require substantial modifications to be able to classify the concept classes. Furthermore, in contrast to ours, most of these studies use a separate technique/tool for modeling the conceptual relations that need to be trained or applied separately with different mechanisms.

3 PROPOSED METHOD

Given an input image, the goal of our proposed method is to determine its category *and* a list of its concept superclasses. As an example, for an image of a Chimpanzee, the proposed algorithm produces predictions for 1) the category Chimpanzee, and 2) an ordered list of ancestor concepts: Living thing → Chordate → Mammal → Primate → Chimpanzee. We illustrate (and experiment with) the proposed model for image classification in this paper.

Our CNN architecture is designed to encompass the chain of relationships among the category and the predecessor concepts in the dense layers. We utilize an existing label hierarchy/ontology to guide the design of the dense layers, but do not use the hierarchy in prediction. In order to maximize the information within an ontology and to reduce the number of variables in the dense layers, we condense the original label hierarchy as explained in Section 3.1.

In our design of multilayer dense connections, each concept is associated with a set of hidden nodes. These hidden nodes are in turn connected to those of its children (both category and concept) and the output prediction nodes. Section 3.2 elaborates these connections and the loss functions to train the network.

3.1 CONDENSED CONCEPT HIERARCHY

In general, a concept class decomposes to multiple sub-concepts in an ontology, e.g., ImageNet12 (Deng et al., 2009) subset of WordNet (Fellbaum, 1998). However, the lineage of a parent

to a single child (e.g., Entity → Physical Entity → Abstraction) is redundant and does not provide much information. Similarly, parent concepts with highly imbalanced distribution of descendants are not informative as well. Modeling the redundant and uninformative concepts will increase the network size with no information gain.

We reorganize the given ontology to reduce such redundancy. We assume the hierarchy to be a directed acyclic graph (DAG) and perform a depth first search (DFS) traversal on it. During the traversal, we first prune the label hierarchy based on the distribution of descendants of a concept node. Let η_γ denote the number of all descendants of a concept indexed by γ. Any child node $\gamma_{\text{ch}} \in \text{Children}(\gamma)$ with $\frac{\eta_{\gamma_{\text{ch}}}}{\eta_\gamma} \geq \tau$, i.e., the overlap between descendants γ and γ_{ch} is more than τ, is absorbed by the parent γ. This process is applied recursively to yield a balanced distribution of descendants of any concept in the resulting hierarchy. In addition, we remove any concept γ in the structure with a descendant count $\eta_\gamma < \delta$ and append the children set $\text{Children}(\gamma)$ to those of its parent γ_{pa}. Conceptually, it is not worth modeling a concept node with only a few descendants.

We depict the differences between the original and modified ontologies in Figure 2. The distributions of the descendants for children concepts are more balanced in the compressed version (right) than that in the original version (left). As the network connections are dependent on the concept hierarchy, this reduction of nodes and relationships in the ontologies are crucial for our method. It is worth noting that the proposed modification added direct concept-category relations in the middle layers of the hierarchy.

Executing a DFS on a DAG ontology may lead to a few ambiguous grouping of few concepts and categories as Deng et al. (2014) pointed out. We adopted DFS for simplicity to compute the compressed graph, which can be replaced by an unambiguous one whenever it is available; one can also apply the methods proposed in Deng et al. (2011); Bengio et al. (2010) to generate the ontology graph.

3.2 Network Architecture

Our proposed algorithm aims to model the abridged label hierarchy with dense connections. As Figure 2 suggests, there are multiple kinds of dense connectivities in our proposed classification layer. Each concept in the hierarchy corresponds to one set of hidden nodes which are connected to the hidden nodes representing its children, if any. For example, if Mammal, Bird and Reptile are the descendant concept of Chordate, there will be all to all connections from the hidden nodes representing Chordate to those accounting for Mammal, Bird and Reptile. The hidden nodes of a concept is also connected to the output prediction node for the concept itself and those for each of its children category nodes. An additional type of connectivity constrains the concept and category predictions to follow the hierarchical organization of the ontology. We illustrate each of these connections below.

Modeling Concepts and Categories: Let us denote by z^γ and $\mathbf{h}^\gamma$ the output prediction variable and the set of hidden nodes associated with the concept γ. The terms node and variables are used interchangeably in the description of our model. Let concept γ_{ch} and category j both be children of concept γ in the hierarchy and $\mathbf{h}^{\gamma_{\text{ch}}}$ and x_j denote the hidden and the output prediction variables for them respectively. The proposed model computes the output prediction z^γ and initial values $\tilde{\mathbf{h}}^{\gamma_{\text{ch}}}$, $\tilde{x}_j$ for quantities of the children concept and categories using the following dense connections.

$$z^\gamma = \phi\Big(\sum_i u_i^\gamma h_i^\gamma + b_z^\gamma \Big); \;\; \tilde{x}_j = \psi\Big(\sum_i v_{i,j}^\gamma \, h_i^\gamma + b_j^\gamma \Big); \;\; \tilde{h}_{i'}^{\gamma_{\text{ch}}} = \omega\Big(\sum_i w_{i,i'}^\gamma \, h_i^\gamma + b_{i'}^\gamma \Big) \tag{1}$$

In these equations, u, v, w and b are the weights/biases of the dense connectivity and h_i corresponds to the i-th value of $\mathbf{h}$. The activation functions ϕ, ψ, ω utilized for these different quantities are $\phi = \text{Sigmoid}, \; \psi = \text{Linear}, \; \omega = \text{ReLU}$. In our design, the number $d^\gamma = |\mathbf{h}^\gamma|$ of nodes representing a concept $\gamma > 0$ is directly proportional to the total number of descendants η_γ of γ. We have used $d^\gamma = \mu\eta_\gamma$ for this study with $\mu = 2$. The flattened output of the final feature layer of an existing network architecture (e.g., ResNet-50 or InceptionV4 etc.) is utilized to populate $\mathbf{h}^0$ and its size depends on the particular architecture used. We do not predict the root concept z^0 of the hierarchy (e.g., Entity for ImageNet12) since all categories descend from it.

Concept Category Label Constraints: The values for category prediction x_j and hidden nodes for child concept $\mathbf{h}^{\gamma_{\text{ch}}}$ are calculated by multiplying initial values of these quantities with the concept

prediction z^γ.

$$x_j = \tilde{x}_j * z^\gamma; \quad h_{i'}^{\gamma_{\text{ch}}} = \tilde{h}_{i'}^{\gamma_{\text{ch}}} * z^\gamma \qquad (2)$$

Note that, the Sigmoid activation constrains the value of z^γ to be $z^\gamma \in [0, 1]$. In effect, the node z^γ plays an excitatory or inhibitory role based on the predicted value of the concept γ. This constraint enforces that the nodes representing any child of concept γ, whether it is a category (x_j) or another downstream sub-concept ($\mathbf{h}^{\gamma_{\text{ch}}}$), be activated only if the concept itself is correctly predicted.

The category predictions for an input image are computed by applying Softmax activation over all category nodes $\{x_1, x_2, \ldots, x_N\}$, where N is the total number of categories. The predictions for M concepts are given by the collection of the variables $\{z^1, z^2, \ldots, z^M\}$. The hierarchical relationship among the variables $\{z^1, z^2, \ldots, z^M\}$ are enforced by construction. Observe that, while an image can be classified to only one (e.g., Chimpanzee) of the N categories, multiple concepts (e.g., Primate, Mammal, Chordate) at different levels of the hierarchy can be set to 1.

Figure 3 clarifies the proposed dense arrangement between the hidden nodes $\mathbf{h}^\gamma$ and its children concept nodes as well as the prediction outputs. The hidden nodes $\mathbf{h}^\gamma$ (shown in empty circles) are connected to those of its Q children concepts and B category output variables (solid circles) to compute the initial quantities $\{\tilde{\mathbf{h}}^{\gamma_{\text{ch}1}}, \ldots, \tilde{\mathbf{h}}^{\gamma_{\text{ch}Q}}\}$ and $\{\tilde{x}_{j_1}, \ldots, \tilde{x}_{j_B}\}$ respectively. The concept prediction z^γ (solid square) is computed by another dense connections which modulates the final values of $\{\mathbf{h}^{\gamma_{\text{ch}1}}, \ldots, \mathbf{h}^{\gamma_{\text{ch}Q}}\}$ and $\{x_{j_1}, \ldots, x_{j_B}\}$ for the concept and category variables respectively via multiplication.

Figure 3: Schematic view of proposed dense connections. The solid square and circle nodes correspond to the concept and category prediction node respectively, whereas the empty circles depicts the hidden nodes. We assume the concept γ has Q concepts and B categories as children.

Number of Variables: The total number of weights in proposed multilayer dense connection with α-way decomposition is $\leq \mu d^0 \left(N + \rho + \frac{1}{(1-\alpha)}\right)$ where ρ is the height of the hierarchy and μ is the fixed multiplier used to set the number of hidden nodes for concept γ (see Appendix B). In comparison, conventional single layer CNN classifiers consist of $d^0 N$ variables.

Loss Functions: The proposed method minimizes two different losses for the two types of output nodes. For the category predictions, we minimize a cross-entropy loss $L_{CE}(x)$ computed over the N category labels and the network outputs x_j, $j = 1, \ldots, N$. However, as more than one concepts may be detected for any input, a cross-entropy loss is not suitable for z variables. We introduce a binary indicator quantity χ^γ, $\gamma = 1, \ldots, M$ for an input image such that $\chi^\gamma = 1$ if γ is an ancestor concept for the category and $\chi^\gamma = 0$ otherwise. With this indicator variable, the concept classification loss is defined as the MSE between χ^γ and z^γ : $L_{CON}(z) = \frac{1}{M} \sum_\gamma (z^\gamma - \chi^\gamma)^2$ where $\gamma = 1, \ldots, M$.

The proposed method minimizes the combined loss $L_{CE} + \lambda L_{CON}$ with the balancing weight λ fixed to $\lambda = 5$ in all our experiments. Note that, while the error for any category is backpropagated through its predecessor concepts due to the dependence imposed by construction, one needs to ensure that other concepts – that are not related to the category – to remain 0 in the $\mathbf{z}$. This is exactly the constraint enforced by $L_{CON}(z)$.

4   EXPERIMENTAL SETUP

We utilize the ontology provided by the ImageNet12 dataset Deng et al. (2009) to design our dense layers. All the labels of ImageNet12 between $[1, 1000]$ correspond to the $N = 1000$ category classes and labels > 1000 are assigned to the 860 concept superclasses. In all our experiments, we fixed the two quantities for compressing the concept hierarchy (Section 3.1) to be $\tau = 90\%$, $\delta = 20$. After compressing the label hierarchy using the methods described in Section 3.1, there are 40 concept labels left in the hierarchy which has a height of $\rho = 7$.

Table 1: Accuracy comparison on ImageNet12 val set (single crop top-1). The proposed models achieve significantly higher Acc_{CON}, Acc_{COMB} than the baselines.

Method	Acc_{CAT}	Acc_{CON}	Acc_{COMB}	mhP	mhR
HG-RN Deng et al. (2012)	68.97	82.9	66.15	93.28	94.57
BL-RN	76.26	62.66	53.01	92.36	89.48
BL-RN-FT	76.0	69.04	58.89	93.91	91.06
MD-RN(ours)	75.94	80.25	69.05	94.22	93.68
MD-RN-FT(ours)	75.82	81.67	**70.06**	94.0	94.13
HG-IC Deng et al. (2012)	71.49	84.28	68.87	93.75	95.07
BL-IC	80.11	72.68	63.56	95.03	91.51
MD-IC(ours)	80.02	88.18	**77.76**	95.46	96.1

The proposed architecture has been trained on the ImageNet12 training dataset and tested on multiple datasets as described in next sections. We used two popular CNN architectures for feature computation layers: ResNet-50 (He et al., 2015; 2016) and Inception V4 (Szegedy et al., 2015; 2016)[1]. Adding the proposed multilayer dense connections increased the total number of variables of the ResNet-50 model by a factor of 1.182 ($\frac{30.29}{25.61}$M). For the InceptionV4 model, the increase is 1.059 ($\frac{46.89}{44.24}$M). This suggests that the increase induced by our proposed model is far lower than the analytical estimate (Section 3.2) in practice and is tolerable with respect to overall network size.

Inference: During inference of the proposed network, we select the category with largest softmax probability for category classification as usual. The parent concepts are classified by thresholding **z** values. We also set any $z^\gamma = 0$ if the variable for its parent $z^{\gamma_{pa}} = 0$ (i.e., lower than a confidence threshold). If more than one child of any concept is detected, we select the one with the highest confidence among them to compute the concept chain.

Evaluation measures: We report the single crop top-1 accuracy results Acc_{CAT} for categories when they are available. For concept inference, we report two measures based on hierarchical precision and recall (Costa et al., 2007), which computes the precision an recall between the predicted and true chain of concepts : 1) the mean hierarchical precision (mhP) and recall (mhR) over all images of test set, and, 2) percentage of images Acc_{CON} that were predicted with 100% hP and hR. The combined accuracy, Acc_{COMB}, denotes the percentage of images with both $Acc_{CAT} = Acc_{CON} = 1$.

Baselines: As the first baseline, we build a CNN classifier for $N + M$ classes with a single flat dense layer for each feature computation architecture. These baselines are trained with the same loss functions of the their multilayer counterparts.

We utilize a modified version of the hedging method of Deng et al. (2012) as the second baseline. Our modified version uses ReasNet-50 and Inception V4 based classifiers instead of classical versions. We observed the optimal strategy to compute category and concept chain from the output of the hedge model (which is either category or max reward concept) is to use the category prediction as is and use the concept with maximum reward, along with all its ancestors, as the predicted concept chain. The hedge model utilizes the same underlying hierarchy as ours and we read off the prediction for concepts that overlap with our condensed hierarchy.

5 RESULTS

5.1 IMAGENET12 DATASET

We first demonstrate the performance of two varaints of the proposed method that were trained on ImageNet12 training set and tested on its validation set. For one variant of our proposed CNN models, **MD-RN** with ResNet-50 and **MD-IC** with Inception V4 backbones, only the weights of the multilayer dense connections were trained; the weights of the feature layers were kept at their original pretrained values. The other variant **MD-RN-FT** performs finetuning, i.e., it initiates the weights in the feature layer from the pretrained ResNet-50 and trains all variables in the network. The corresponding flat dense connection baselines are referred to as BL-RN, BL-IC, BL-RN-FT respectively. The hedging model of Deng et al. (2012) is dubbed HG-RN and HG-IC that utilizes a ResNet-50 and Inception V4 initial classifiers respectively.

Training: We trained MD-RN, MD-RN-FT and MD-IC following standard training procedures of Szegedy et al. (2016); Chollet (2016). The details of training parameters and techniques are described in Appendix C for space limitation. The initial classifiers for HG-RN and HG-IC were

---

[1]pretrained versions downloaded from `https://github.com/tensorflow/models/tree/master/research/slim`.

Table 2: Accuracy comparison on naturally adversarial images (single crop top -1). The proposed models achieve significantly higher Acc_{CON}, Acc_{COMB} than the baselines.

Method	Acc_{CAT}	Acc_{CON}	Acc_{COMB}	mhP	mhR
HG-RN Deng et al. (2012)	0.37	14.36	0.3	57.08	55.99
BL-RN-FT	0.86	11.52	0.26	59.12	54.33
MD-RN-FT (ours)	1.05	**15.92**	0.66	61.74	57.2
HG-IC Deng et al. (2012)	3.18	19.76	2.8	59.73	58.77
BL-IC	7.54	16.62	3.56	61.78	58.07
MD-IC (ours)	7.1	**23.5**	6.1	63.79	61.46

trained from scratch on 93% of training examples for each class in ImageNet 2012 training set (achieving 74% and 76% category accuracy on validation set respectively). The remaining 7% examples were used to estimate the dual variable maximizing the reward for multiple accuracy guarantees. The results reported here correspond to the dual variable, accuracy guarantee with best overall Acc_{COMB}.

Evaluation: Table 1 reports the accuracies for all the aforementioned models. Table 1 demonstrates that the MD-RN, MD-RN-FT and MD-IC networks with proposed multilayer dense connections achieved a comparable category accuracy ACC_{CAT} of the flat baselines BL-RN, BL-RN-FT and BL-IC (which are similar to the published results). The category accuracy of HG-RN, HG-IC are significantly lower than the aforementioned models – a phenomenon also observed by Deng et al. (2012). This is due to the inherent design of the hedge model to only predict concept classes (and not the leaf categories) for some examples.

Table 1 also suggests that an unconstrained flat dense connection is insufficient for learning the superclass sequence. The proposed models attains $> 10\%$ higher Acc_{CON} and even larger combined Acc_{COMB} than the flat baselines BL-RN, BL-RN-FT, BL-IC. The baseline methods can either learn to classify the finer categories or the concept chain correctly but the proposed CNN architecture can attain the ability to do both simultaneously with high accuracy. The proposed models MD-RN, MD-RN-FT and MD-IC achieves a significantly higher overall accuracy Acc_{COMB} than the hedging models HG-RN and HG-IC. The inception based model MD-IC is also more accurate than HG-IC for concept prediction – indeed, MD-IC leads to the best overall accuracy Acc_{COMB} among all models.

The comparison implies that the proposed top-down hierarchical constraints on category classification to preserve the ancestor concept chain is superior to the hedging technique of concept prediction distilled from the aggregated probabilities accumulated bottom-up from category confidence. As we will show in next section, a top-down constrained prediction is more robust to the challenging examples because it does not rely primarily on the category classificaiton probabilties.

Analysis: We provide an in-depth analysis of the failure cases of concept prediction, compared the distribution of category classifications and training times of different variants of the proposed models and baslines in Appendix D. Appendix E discusses the ablation studies with the network structure and λ values in loss function.

We also trained a ResNet-50 model MD-RN-SC from scratch on ImageNet 2012 (details provided in Appendix C). Although ACC_{COMB} of MD-RN-SC is better than its flat dense layer baseline BL-RN-SC, it is lower than those of other variants. Therefore, we exclude the performance of MD-RN-SC in this paper.

5.2 NATURALLY ADVERSARIAL EXAMPLES

Our next experiment demonstrates the robustness of the proposed network on challenging images. For this experiment, we collected the naturally adversarial images (Hendrycks et al., 2019) that the popular CNN architectures (e.g. ResNet) trained on standard datasets fail to classify correctly. The ResNet-50 model we downloaded from the tensorflow website (pretrained on full ImageNet 2012) could classify only 0.73% of the images. There are 7500 images in this dataset that belong to 200 categories. Since these 200 categories are a subset of the $N = 1000$ categories of ImageNet 2012 dataset, one can use the same concept structure for hierarchical classification.

In Table 2 the proposed MD-RN-FT and MD-IC model accuracies are compared with those of their flat dense layer counterparts BL-RN-FT and BL-IC as well as those of the hedging model (Deng et al., 2012) with corresponding initial classifiers. The proposed models MD-RN-FT and MD-IC were able to correctly classify the superclass sequences of more images than the baseline models. With the exception of BL-IC, their categorical accuracies ACC_{CAT} are also higher than the baselines.

Figure 4: Qualitative comparison between the proposed and the pretrained ResNet50 models on naturally adversarial images (Hendrycks et al., 2019).

We provide a qualitative comparison in Figure 4 between the proposed MD-RN-FT method and the pretrained ResNet-50 output. One can observe that, without the constraints on predicting the concept chain correctly, the ResNet-50 can classify the images to semantically very different categories. Aggregating these category-wise confidences will consequently lower the ACC_{CON} of the hedging model compared to those of the proposed model. The proposed MD-RN-FT, on the other hand, determines the ancestor classes correctly even when the leaf level category is misclassified.

5.3 PASCAL VOC 12 DATASET

In this section, we test the generalization of the knowledge learned by the proposed architecture. Ideally, the proposed network should be able to extrapolate its understanding of the concept super-classes learned from one category set to previously unseen categories. That is, after learning that a zebra is a mammal, it should be able to identify a horse (of any color) as a mammal too. To test generalization capability, we test classifiers learned from the ImageNet12 dataset on the trainval split of PASCAL VOC dataset (Everingham et al., 2010). Note that, there is no one to one correspondence between the categories of ImageNet and VOC[2]. Each of the VOC 12 categories were assigned to one of the concepts in the condensed label hierarchy of ImageNet dataset.

Table 3: Average concept accuracy comparison on testing on PASCAL VOC 12 trainval subset. The proposed method achieves significantly higher Acc_{CON} than the baseline for both architectures.

	PrAggRN	BL-RN-FT	MD-RN-FT(ours)	PrAggIC	BL-IC	MD-IC(ours)
Acc_{CON}	46.2	38.06	**48.79**	48.32	40.3	**50.38**

In Table 3, we show the average concept prediction accuracies of the different variants of the proposed model the corresponding flat dense layer baselines over 16 VOC categories. Since there are no categories to predict, the second baseline predicts the concept classes by thresholding the aggregated probabilities as computed in Deng et al. (2012). These are referred to as PrAggRN and PrAggIC when computed from the initial ResNet-50 and Inception V4 classifiers respectively. As the table shows, the proposed variants MD-RN-FT, MD-RN-SC and MD-IC achieved a higher average concept prediction accuracy over all classes than those of the baselines. Appendix F details the performances for all classes and analyzes the results on this dataset.

6 DISCUSSION

In this paper, we have demonstrated the advantages of multilayer dense connections for classifying both the category and the ordered chain of ancestor concept classes with two popular architectures in different settings. The experimental results show that the proposed dense layers can equip the existing CNN classifiers with additional capability of learning the coarse concepts without sacrificing the category-wise accuracy. Attaining this capability of determining the ancestor concept classes is relatively easy – one can only modify the final classification layers and train using the same optimization technique, for some cases without training the full network.

Our experiments demonstrate the advantage of the proposed architecture over a) an unconstrained technique for predicting the superclasses, and b) methods estimating them from probabilities accumulated in a bottom up fashion given an offline hierarchy (Deng et al., 2012). Our top-down constraints enforces the category classification to conform to the semantically meaningful lineage of ancestor classes rather than the converse strategy of bottom up approaches. The proposed method also removes the necessity of a separate training/optimization tool and enables to learn end-to-end. This property in turn leaves open the possibility to learning the concept hierarchy itself using the network search methods (Zoph et al., 2017; Pham et al., 2018).

---

[2]See `http://image-net.org/challenges/LSVRC/2012/analysis`.

REFERENCES

Samy Bengio, Jason Weston, and David Grangier. Label embedding trees for large multi-class tasks. In *NIPS*. 2010.

Clemens-Alexander Brust and Joachim Denzler. Integrating domain knowledge: using hierarchies to improve deep classifiers. *CoRR*, abs/1811.07125, 2018.

Qingxing Cao, Xiaodan Liang, Bailing Li, Guanbin Li, and Liang Lin. Visual question reasoning on general dependency tree. *CoRR*, abs/1804.00105, 2018.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *CoRR*, abs/1706.05587, 2017.

Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. *CoRR*, abs/1802.02611, 2018.

François Chollet. Xception: Deep learning with depthwise separable convolutions. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1800–1807, 2016.

Eduardo P. Costa, A. Lorena, A. Carvalho, and A. Freitas. A review of performance evaluation measures for hierarchical classifiers. In *AAAI*, 2007.

J. Dai, H. Qi, Y. Xiong, Y. Li, G. Zhang, H. Hu, and Y. Wei. Deformable convolutional networks. In *2017 IEEE International Conference on Computer Vision (ICCV)*, 2017.

J. Deng, W. Dong, R. Socher, L. Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

Jia Deng, Alexander C. Berg, Kai Li, and Li Fei-Fei. What does classifying more than 10,000 image categories tell us? In *ECCV*, 2010.

Jia Deng, Sanjeev Satheesh, Alexander C. Berg, and Fei Li. Fast and balanced: Efficient label tree learning for large scale object recognition. In *NIPS*, 2011.

Jia Deng, Jonathan Krause, Alex Berg, and Li Fei-Fei. Hedging your bets: Optimizing accuracy-specificity trade-offs in large scale visual recognition. In *CVPR*, 2012.

Jia Deng, Nan Ding, Yangqing Jia, Andrea Frome, Kevin Murphy, Samy Bengio, Yuan Li, Hartmut Neven, and Hartwig Adam. Large-scale object classification using label relation graphs. In *ECCV*, 2014.

Nan Ding, Jia Deng, Kevin Murphy, and Hartmut Neven. Probabilistic label relation graphs with ising models. In *ICCV*, 2015.

M. Everingham, L. Van Gool, C. K. I. Williams, J. Winn, and A. Zisserman. The Pascal visual object classes (VOC) challenge. *International Journal of Computer Vision*, 88(2):303–338, June 2010.

Christiane Fellbaum (ed.). *WordNet: An Electronic Lexical Database*. Language, Speech, and Communication. MIT Press, Cambridge, MA, 1998.

Rob Fergus, Hector Bernal, Yair Weiss, and Antonio Torralba. Semantic label sharing for learning with many categories. In *ECCV*, 2010.

Yanming Guo, Yu Liu, Erwin M. Bakker, Yuanhao Guo, and Michael S. Lew. Cnn-rnn: a large-scale hierarchical image classification framework. *Multimedia Tools and Applications*, 77:10251–10271, 2017.

K. He, G. Gkioxari, P. Dollár, and R. Girshick. Mask r-cnn. In *ICCV*, pp. 2980–2988, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *CoRR*, abs/1512.03385, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. *CoRR*, abs/1603.05027, 2016.

Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. *CoRR*, abs/1907.07174, 2019.

H. Hu, G. Zhou, Z. Deng, Z. Liao, and G. Mori. Learning structured inference neural networks with label relations. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Hexiang Hu, Guang-Tong Zhou, Zhiwei Deng, Zicheng Liao, and Greg Mori. Learning structured inference neural networks with label relations. *CoRR*, abs/1511.05616, 2015.

J. Hu, L. Shen, and G. Sun. Squeeze-and-excitation networks. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2018.

G. Huang, Z. Liu, L. v. d. Maaten, and K. Q. Weinberger. Densely connected convolutional networks. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems 25*. 2012.

Xiaodan Liang. Learning personalized modular network guided by structured knowledge. In *CVPR*, June 2019.

T. Lin, P. Dollár, R. Girshick, K. He, B. Hariharan, and S. Belongie. Feature pyramid networks for object detection. In *CVPR*, 2017.

Tsung-Yi Lin, Priya Goyal, Ross B. Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *ICCV*, 2017.

Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott E. Reed, Cheng-Yang Fu, and Alexander C. Berg. SSD: single shot multibox detector. *CoRR*, abs/1512.02325, 2015.

Hieu Pham, Melody Guan, Barret Zoph, Quoc Le, and Jeff Dean. Efficient neural architecture search via parameters sharing. In *ICML*, 2018.

K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. In *ICLR*, 2015.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. *CoRR*, abs/1512.00567, 2015.

Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alex A. Alemi. Inception-v4, inception-resnet and the impact of residual connections on learning. In *ICLR 2016 Workshop*, 2016. URL `https://arxiv.org/abs/1602.07261`.

Mingxing Tan and Quoc Le. EfficientNet: Rethinking model scaling for convolutional neural networks. In *ICML*, 2019.

A. Torralba, K. P. Murphy, and W. T. Freeman. Sharing features: efficient boosting procedures for multiclass object detection. In *CVPR*, 2004.

Zhuowen Tu, Xiangrong Chen, Alan L. Yuille, and Song-Chun Zhu. Image parsing: Unifying segmentation, detection, and recognition. *Int. J. Comput. Vision*, 63(2):113–140, July 2005.

Peng Wang, Qi Wu, Chunhua Shen, Anton van den Hengel, and Anthony R. Dick. FVQA: fact-based visual question answering. *CoRR*, abs/1606.05433, 2016.

Jianxin Wu, James M Rehg, and Matthew D. Mullin. Learning a rare event detection cascade by direct feature selection. In *NIPS*. 2004.

S. Xie, R. Girshick, P. Dollár, Z. Tu, and K. He. Aggregated residual transformations for deep neural networks. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Zhicheng Yan, Hao Zhang, Robinson Piramuthu, Vignesh Jagadeesh, Dennis DeCoste, Wei Di, and Yizhou Yu. HD-CNN: Hierarchical deep convolutional neural networks for large scale visual recognition. In *ICCV*, pp. 2740–2748, 2015.

Bin Zhao, Fei Li, and Eric P. Xing. Large-scale category structure aware image categorization. In *NIPS*. 2011.

Hengshuang Zhao, Jianping Shi, Xiaojuan Qi, Xiaogang Wang, and Jiaya Jia. Pyramid scene parsing network. *CoRR*, abs/1612.01105, 2016.

Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V. Le. Learning transferable architectures for scalable image recognition. *CoRR*, abs/1707.07012, 2017.

A   APPENDIX: OTHER RELEVANT WORKS

Hu et al. (2016) discuss a hierarchical representation of coarse to fine scene context. In their structured inference model, the concepts representing scene attributes are predicted as indicator vectors of different length and a bidirectional message passing, inspired by the bidirectional recurrent networks, establishes the relations among different levels of concepts. The model leads to a large number of inter and intra-layer label interactions some which needed to be manually hard-coded to 0. In a similar line of thought, Liang (2019) employed graph based reinforcement learning to learn features of a set of modules, each of which corresponds to a concept. Once the network search is completed, the activated module outputs are passed through prediction layers for generating final output. The algorithm demonstrated promising performance for classifying scene contexts for semantic segmentation.

Commercial vision solutions such as Amazon Rekognition (https://aws.amazon.com/blogs/aws/amazon-rekognition-image-detection-and-recognition-powered-by-deep-learning/) or Google Vision (https://cloud.google.com/vision) seem to produce outputs that resemble concept classes. Due to the proprietary nature of these solutions, it is not possible for us to confirm whether or not they indeed predict concept classes and their relationships. However, based on the description provided in (https://aws.amazon.com/blogs/aws/amazon-rekognition-image-detection-and-recognition-powered-by-deep-learning/) and scrutiny of results, we speculate that Amazon rekognition does not use any hierarchy and probably uses a look-up from hard-coded (undisclosed) relations strategy.

B   APPENDIX: NUMBER OF VARIABLES IN MULTILAYER DENSE CONNECTIONS

This section quantifies the increase in the number of weights in the dense layers induced by our multilayer computations. The CNN classifiers typically consists of $d^0 N$ connections in dense layer, where d^0 and N are the size of the last feature layer and number of category classes respectively. In proposed multilayer dense connections with a balanced α-way decomposition of the concepts, the total number of weights is $\leq \mu d^0 \left(N + \rho + \frac{1}{(1-\alpha)} \right)$ where ρ is the height of the hierarchy and μ is the fixed multiplier used to set the number of hidden nodes for concept γ (see Section 3.2).

In a balanced decomposition, the number of hidden nodes for concepts reduces by a constant factor α. With the size of smallest set of hidden nodes as δ, the max layer of the dense connections is $\rho = \log_\alpha(\frac{d^0}{\delta})$. For any concept prediction z^γ, we need $d^\gamma = \frac{\mu d^0}{\alpha^l}$ weights at layer l i.e., max number of weights for concept class prediction is $\mu d^0 \rho = \mu d^0 \log_\alpha(\frac{d^0}{\delta})$. The number of concept-concept connections can be calculated as $d^0(\frac{\mu}{\alpha} + \frac{\mu}{\alpha^2} + \cdots + \frac{\mu}{\alpha^\rho}) = \mu d^0 \frac{(1-\alpha^\rho)}{(1-\alpha)} \leq \mu d^0 \frac{1}{(1-\alpha)}$.

In order to predict a category variable $x_j \in$ Children(γ), d^γ weights are necessary. Since any $\mu d^0 \geq d^\gamma = \mu \frac{d^0}{\alpha^l}$ at any level l in a balanced decomposition, the total number of weights for category class prediction must be $\leq \mu d^0 N$.

C   APPENDIX: TRAINING DETAILS

For MD-RN, MD-RN-FT and MD-IC training, we used the RMSProp optimizer with momentum in our multi-GPU distributed training scheme similar to Szegedy et al. (2016); Chollet (2016). The

initial learning rate for this experiment was 0.1 and was multiplied by 0.94 every 2 epochs. The epoch size is the same as the training set size with batch size 256, momentum value 0.9, and weight decay 0.0001. The training data were augmented by random crop and horizontal flips. For proposed network learning, the weights corresponding to the concept outputs and the concept interconnections were learned for first 2 epochs before optimizing those for the category variables. We did not use label smoothing for training the Inception v4 model. The training was continued until the CNN achieved the same or close accuracy for category classification as reported in the original paper/repository.

We have also trained a ResNet-50 with proposed multilayer dense connections MD-RN-SC and baseline flat dense connection BL-RN-SC from scatch on ImageNet 2012 training set. In our training from scratch, we applied stochastic gradient descent (SGD) optimizer with momentum value 0.9 and initial learning rate 0.2. The learning rate was decreased every 30 epochs by a factor of 10 (similar to Simonyan & Zisserman (2015); He et al. (2015) training). All other values of the hyperparameters remain the same as those of MD-RN training. Table 4 reports the accuracies of MD-RN-SC and BL-RN-SC.

Table 4: Accuracy comparison for learning full network from scratch. All accuracies are computed for the single crop top-1 setting. The proposed method achieves significantly higher Acc_{CON}, Acc_{COMB} than the baseline.

Method	Acc_{CAT}	Acc_{CON}	Acc_{COMB}
BL-RN-SC	75.24	69.87	59.7
MD-RN-SC	73.5	78.14	**65.74**

D APPENDIX: PERFORMANCE ANALYSIS OF MD-RN AND MD-IC ON IMAGENET

Figure 5(a) shows some example categories where the proposed MD-IC model generated different concept orders than those in the condensed ontology. Monitor and Space bar are children of Equipment and Implement concepts respectively in the condensed ontology. But, they contain many images of Desktop computer and Computer keyboards – both of which are children of the Device concept. As a result, 68% and 88% of Monitor and Space bar images respectively were classified as Artifact$\rightarrow$ Instrumentality$\rightarrow$ Device. Similarly, although it is grouped to Matter$\rightarrow$ Solid concepts, 75% of the Mushroom images were predicted as Living thing which consists of Earthstar, Stinkhorn categories that are visually very similar to Mushroom images. Motor scooter was placed in Wheeled vehicle in our compressed hierarchy; but at test time, 94% of the time its images was predicted as Self propelled vehicle. In general, predictions from our proposed model concur more

(a) Concept misclassification examples   (b) Acc_{CAT} distribution   (c) Acc_{CAT} progress

Figure 5: (a): Categories where the proposed method predicted a concept order different from the condensed hierarchy. (b) : Category-wise classification accuracy of the proposed method vs the baseline architecture (w/ ResNet50). (c): Progession of validation accuracy of the proposed CNN (blue) and baseline (red).

with the concept chains for descendants of Living thing than it does for those of Artifact concept.

Since different category classes are predicted at different layers of the proposed dense structure, it is rational to verify whether or not the category classification capability is impaired by the depth of layer. To test this, we have plotted in Figure 5(b) the category prediction accuracies for each of the $N = 1000$ classes of the baseline against those of the proposed CNN with ResNet50 backbone. The plot implies no clear effect of the prediction depths on the classification performances on different categories as they remain same or very close to those of the original architecture.

Due to the increased number of dense layers and additional sigmoid activations, it is perhaps natural to expect the proposed architecture to require more iteration to converge. As Figure 5(c) demonstrates, our model indeed takes more epochs(x-axis) to attain a category classification performance (y axis) similar to that of baseline built upon ResNet50.

E   APPENDIX: ABLATION STUDIES

We have conducted ablation studies with model MD-RN. In our first ablation study, we model the dense layers based on the original uncompressed hierarchy instead of the condensed hierarchy. Adopting the original ontology in ResNet-50 increased the number of z variables to 806, depth of dense layers to 17 and model size to 43M (compare with 40, 7, 30M resp. of compressed). Our attempts with different hyperparameters (λ, lr etc) achieved at most $\{Acc_{\text{CAT}}, Acc_{\text{CON}}, Acc_{\text{COMB}},$ mhP, mhR$\}$=$\{44.02, 1.12, 1.03, 60.05, 47.6\}$ at 30 epoch (compare Acc_{CAT} with ours Fig 5(c). The training is perhaps smothered by 1) increased depth with many redundant single parent-child connections, and 2) imbalance in descendent distribution where smaller concept classes are underrepresented.

The second analysis is performed with varying the values of the balancing term λ in the combined loss function (Section 3.2). As can be inferred from the network architecture for multiple dense connections and the loss functions, with $\lambda = 0$ the category-wise loss drive concept z variables of only the ancestor concepts to 1. However, with $\lambda = 0$, the optimization will not force z variables of the other non-ancestor concepts to 0. Consequently, concept and combined accuracy of a model trained with $\lambda = 0$ will be very low.

As Table 5 shows, we observe a very low $Acc_{\text{CON}}, Acc_{\text{COMB}}$ for MD-RN-λ0 while achieving close Acc_{CAT} to the published results. It is also apparent that a small λ (= 2) favors improving Acc_{CAT} while a relatively large λ (=8) favors improving Acc_{CON} compared to those of the MD-RN model reported on Table 1. This is expected behavior with the loss function we are optimizing.

Table 5: Performance of MD-RN with different λ values. All accuracies are computed for the single crop top-1 setting.

λ	Acc_{CAT}	Acc_{CON}	Acc_{COMB}	mhP	mhR
0	76.04	1.86	1.57	33.35	45.41
2	76.04	78.57	66.66	91.78	93.81
8	75.42	81.74	70.08	94.13	94.08

F   APPENDIX: PERFORMANCE ANALYSIS ON PASCAL VOC DATASET

We have excluded the classes {Person, Pottedplant} since these categories were underrepresented in the ImageNet12 dataset. For example, Person is represented by three rare subclasses Scuba diver, Ballplayer, Groom. On the other hand, the {Dog, Bird} categories were over represented in ImageNet12 and their subcategories were assigned to multiple concepts in our hierarchy. These classes could lead to inconsistency and therefore also excluded in evaluation. After removing the images that overlaps with multiple categories, we are left with 6941 images from 16 categories. For these images, we report the Acc_{CON} in Table 6 (Acc_{CAT} and Acc_{COMB} cannot be computed as there is no one to one correspondence between categories of the two datasets).

The accuracy values for concept classification on VOC 2012 clearly indicate the superiority of the proposed architecture to generalize the knowledge it learned from ImageNet12 hierarchy of ancestor superclasses. All the CNN models resulted in weak performances of categories {Train, Car, Diningtable}. Such a performance can be attributed to equivocal ancestry within the condensed ontology. For the category Train, the proposed model with InceptionV4 architecture predicted Entity$\rightarrow$ Artifact$\rightarrow$ Instrumentality$\rightarrow$ Container$\rightarrow$ Wheeled vehicle $\rightarrow$ Self propelled vehicle for 56% of images whereas the compressed ontology assigns it the concept order : Entity$\rightarrow$ Artifact$\rightarrow$ Instrumentality$\rightarrow$ Conveyance. It is important to note though that for the ambiguous categories, both the baseline and the proposed models performed poorly – i.e., the proposed method is not drawing any inequitable advantage due to the label ambiguity.

Table 6: Concept accuracy comparison on testing on PASCAL VOC 2012 trainval subset. The proposed method achieves significantly higher Acc_{CON} than the baseline for both architectures.

Method	cat	cow	horse	sheep	plane	boat	bike	mbike	bus	train	car	botl	chair	dtable	sofa	montr	avg
PrAggRN	71.2	73.1	51.4	72.1	75.1	55.3	73.4	34.1	61.7	4.4	2.4	36	29.3	8.5	30.8	37.8	46.2
BL-RN-FT	57.2	53.9	43	53.8	72.5	50.2	65.7	35.3	56.8	1.5	1.6	21.6	17.9	1	13.1	30.7	38.06
MD-RN-FT	72.4	79.0	58.4	75.3	84.4	69.5	75.66	4.9	49.8	3.6	2.4	40.8	36.6	15.9	42.1	51.1	**48.79**
PrAggIC	69.8	80.7	59.8	80.7	80.3	59.7	75.4	30.1	64.6	4	2	38.9	31.8	9.5	36.4	33.3	48.32
BL-IC	64.9	63.2	47.2	60.5	80.3	45.9	45	2.9	71	1.9	2.1	25.3	19.3	3.1	24	32.3	40.3
MD-IC	74.6	84.1	60.9	80.7	86	63.1	77.5	8.1	65.8	3.8	1.7	46.4	39.4	15.9	40.9	43.3	**50.38**

G APPENDIX: POSSIBLE APPLICATIONS AND EXTENSIONS

Our dense connectivity can also be extended to two-stage object detection algorithms (He et al., 2017; Lin et al., 2017) by replacing the final detection head with proposed mulitlayer connections. For SSD-type architectures (Liu et al., 2015; Lin et al., 2017), the dense computations can be carried out by 1×1 convolutions (or extended to 3×3) and added to the classification branches at each scale. The convolutional form should conceptually enable the semantic segmentation techniques (Chen et al., 2017; 2018; Zhao et al., 2016) to adopt our model as well.

Furthermore, rather than capturing the conceptual class lineage, the dense layers can be modeled after a different contextual relationship such as spatial or compositional consistency (via can-coexist-with (Hu et al., 2015) or is-part-of (Brust & Denzler, 2018; Wang et al., 2016) relations. These relationship graph, e.g., parsing graph (Tu et al., 2005), can be either precomputed or learned for the particular task at hand.

H APPENDIX: GROUPING CATEGORIES USING HDCNN TECHNIQUE

We also attempted to group the ImageNet 2012 categories following the strategy suggested by the HDCNN paper, Section 4 of (Yan et al., 2015). For this purpose we exploited the ResNet-50 classifier trained on 93% training examples of ImageNet 2012 (i.e., the initial classifier for HG-RN). The remaining 7% of the training set was used to compute 100 disjoint clusters of categories. While some of the animal and vegetable/fruit categories were correctly grouped into the same clusters, many of the clusters comprises semantically very different classes. We are listing a few of these clusters below. Yan et al. (2015) further created some overlapping groups for their algorithm. It is not clear how to assign concept class labels to these undersegmented clusters of categories and how they can be predicted using a classifier. That is why we cannot compare our method with HDCNN.

```
Cluster 1 : {n02509815 lesser-panda, n02346627 porcupine,
n01872401 echidna, n02172182 dung-beetle, n02319095 sea-urchin,
n03717622 manhole-cover, n04033901 quill, n03733281 maze}.

Cluster 2 : {n04086273 revolver, n02804414 bassinet, n03954731
plane, n03995372 power-drill, n03483316 hand-blower, n03868863
oxygen-mask, n03759954 microphone, n02841315 binoculars, n02749479
assault-rifle, n04090263 rifle, n03602883 joystick, n04485082
tripod, n04517823 vacuum, n04554684 washer, n03724870 mask,
n04069434 reflex-camera, n03424325 gasmask}.

Cluster 3: {n02389026 sorrel, n02403003 ox, n02437312
Arabian-camel, n03538406 horse-cart, n03868242 oxcart, n04417672
thatch}.

Cluster 4: {n03447447 gondola, n02951358 canoe, n04204347
shopping-cart, n03933933 pier, n04311004 steel-arch-bridge,
n04366367 suspension-bridge, n04532670 viaduct, n03160309 dam,
n03873416 paddle}.
```