Dissimilar Nodes Improve Graph Active Learning

Abstract

Training labels for graph embedding algorithms could be costly to obtain in many practical scenarios. Information score-based active learning (AL) algorithms are frameworks that could obtain the most useful labels for training while keeping the total label queries under a certain budget. The existing Active Graph Embedding framework has been shown to be capable of bringing some improvement to the node classification tasks of Graph Convolutional Networks, however, when evaluating the importance of unlabeled nodes, they fail to consider the influence of existing labeled nodes on the value of unlabeled nodes. With the aim of addressing this limitation, in this work, we introduce 3 dissimilarity-based information scores for active learning: feature dissimilarity score (FDS), structure dissimilarity score (SDS), and embedding dissimilarity score (EDS). According to experiments, our newly proposed scores boost the classification accuracy by 2.1% on average and are capable of generalizing to different Graph Neural Network architectures.

1 Introduction

Graph is a common data structure in the field of computer science. Nowadays, Graph Neural Networks (GNNs) have been drawing increasing research attention because of its great success in various applications [5] [3] [14] [11][18] [19]. However, in many real world scenarios, such as chemistry and health care, it could be very expensive to collect sufficient amount of labeled data to facilitate the training of GNNs, which limits the performance of GNNs. Active learning is a framework to resolve this challenge, which allows to dynamically query new node labels from unlabeled node sets given a limited budget.

Existing graph active learning query functions only use properties of the unlabeled nodes to determine the next label to be queried [1]. In many real world data sets, however, we often do not have control on the distribution of the available labeled set of nodes. The available labeled node set could be biased (e.g. most of them belong to a single class) or isolated (e.g. all of them are in a single isolated sub-graph). If we need to query a new label, the label which is not as valuable given an unbiased labeled set could turn to be very valuable given a biased labeled set. Hence, design label query functions that consider the influence of the current labeled set on the value of candidates for label queries will be promising in selecting the most valuable labels.

In this work, inspired by the idea in [9] that a more diverse training set improves the performance of active learning, we proposed three novel active learning scores for graphs based on node dissimilarity: feature dissimilarity score (FDS), structure dissimilarity score (SDS), and embedding dissimilarity score (EDS). Those scores directly evaluate how dissimilar a candidate node for label queries is with respective to existing labeled nodes. We conduct extensive experiments to demonstrate that those scores improve the performance of node classification tasks of GCN by about 2.1% when added to the other conventionally-used active learning scores. Meanwhile, we also conduct some ablation studies where we replace GCN backbone with other well-known graph neural network variants such as GAT [14] and SGC [16]. Results show that our methods are generalizable to those GNN variants.

2 Background and Related Works

2.1 Graph Neural Network

GNN is a family of graph embedding models that achieves the state-of-the-art performance in graph-related tasks. It learns node representations by iteratively aggregating neighborhood information using a convolution operator. GCN [5] takes the first step to formally propose the graph convolutional operation, GAT [14] improves the model architecture with the attention mechanism. There are many other GNN architectures such as GraphSAGE [3], SGC [16], and GIN [18], that make improvement on generalizability, scalability, and effectiveness. Details about different GNN variants could be found in appendix C.

2.2 Active Learning Methods

Active learning (AL) is a framework aiming for maximizing the downstream supervised task training by selecting the most valuable nodes to query their labels under the given budget. AL algorithm generally consists of two main components: a query system and an oracle. The query system selects the most valuable instances from the unlabeled dataset, and the oracle then annotate labels for the selected instances. Most of the query systems can be categorized into four types [9]: (1) uncertainty-based query systems which select samples which the current model is the most uncertain about; (2) diversity-based query systems that select samples that shares the most diverse attributes; (3) performance-based query systems which measure the expected effect of selected samples on the model training; (4) representativeness-based query systems which select samples that could represent the true data distribution the most.

In recent years, as GNNs become increasingly popular, graph active learning gets more research attentions. The work of [1] proposes a strong graph active learning baseline which combines uncertainty-based query systems and representativeness-based query systems. [17] and [6] focus on develop robust representativeness-based query systems. [4] propose a reinforcement learning algorithm to evaluate the query systems based on the performance. Details about existing graph AL algorithms could be found in Appendix A.

In our work, since representativeness-based metrics might fail to address the nodes which have low centrality; performance based metrics need pre-computation to evaluate the value of a new label, causing significant computational burden; uncertainty-based needs to be combined with other metrics to select the most valuable nodes at early training stage since the model could not provide sufficient probability information at early training stage; we decide to explore diversity-based query systems.

3 Method

3.1 Workflow of Active Graph Embedding System

Our work focus on the node classification task. Given an attributed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ with node set $\mathcal{V}$ and edge set $\mathcal{E}$, $\mathcal{V}$ would be the union set of the labeled node set $\mathcal{L}_0$ and unlabeled node set $\mathcal{U}_0$ at epoch 0, and let node attribute matrix be X, the class vector for $\mathcal{V}$ be Y, the labelling budget for AL be B, and total training epoch be T.

We follow the training process of the standard active learning framework. At every training epoch t, if the labeling budget B is not reached, the AL query strategy module selects the best candidate in the unlabeled nodes set at current epoch (denoted as $\mathcal{U}_t$) with the query strategy, queries its label with the oracle, and adds it into the labeled nodes set at current epoch (denoted as $\mathcal{L}_t$), i.e. we will have $\mathcal{U}_{t+1} = \mathcal{U}_t \setminus v^*$ and $\mathcal{L}_{t+1} = \mathcal{L}_t \cup v^*$ for epoch $t+1$ where v^* is the node being selected at epoch t. If the labeling budget B is reached, i.e., $|\mathcal{L}_t| = B$, we stop the selecting and querying process. The training is carried normally until GNN converges. Let l be the loss of the GNN model training, the optimization objective of graph active learning problem could be formally formulated as:

$$\underset{\mathcal{L}_T, \mathcal{U}_T}{\text{argmin}} \ \mathbb{E}\left[\ell(\text{GNN}(\mathcal{G}, X), Y)\right], \text{ such that } |\mathcal{L}_T| = B \tag{1}$$

3.2 Dissimilarity Scores

In the aforementioned AL system, the most important part is the query strategy, which evaluates the importance of each unlabeled node. Inspired by the well-recognized idea in active learning that a more diverse training set can benefit the performance [9], we propose three node dissimilarity-based metrics to augment the query strategy and improve the active graph embedding system.

Feature dissimilarity score (FDS): To evaluate how dissimilar a candidate node is compared to the nodes that have already been labeled in terms of their node feature, we propose FDS, which apply the commonly used cosine similarity for feature distance measurement:

$$\phi_{\text{FDS}}(v_i) = \frac{1}{\max\limits_{l \in \mathcal{L}_t} \cos(v_i, l)} \tag{2}$$

Structural dissimilarity score (SDS): In the context of graph data sets, the similarity of two nodes is not only dependent on how similar their features are, but also dependent on their graph-level structures as well. To evaluate the structural dissimilarity, we consider the second-order similarity [13], whose underlying idea is, two nodes are similar if their neighbors are similar. Given the adjacency matrix A, the element $(A^2)_{i,j}$ gives the number of paths of length 2 from node i to node j, i.e. number of shared neighbors between node i and node j. Therefore, we could design our score ϕ_{SDS} to be:

$$\phi_{\text{SDS}}(v_i) = \frac{1}{\max\limits_{l \in \mathcal{L}_t} (A^2)_{i,\text{index}(l)}} \tag{3}$$

where $\text{index}(l)$ is the index of the labeled node l. We can interpret this idea as: if we already have a labeled node to propagate the feature information to its neighbors, the value of another node label connected to the same group of neighbors might be low in the setting of GNNs.

Embedding dissimilarity score (EDS): EDS is designed to measure node dissimilarities based on their embeddings. It utilizes the node representations obtained with the GNN backbone model, and is capable of capturing both structure and feature information. Similar to FDS, we use the cosine similarity as a distance measurement.

$$\phi_{\text{EDS}}(v_i) = \frac{1}{\max\limits_{l \in \mathcal{L}_t} \cos(\text{EMB}(v_i), \text{EMB}(l))} \tag{4}$$

where $\text{EMB}(l)$ is the embedding of node l after the convolution.

The main difference between our dissimilarity-based metrics and previous graph active learning metrics is that by directly comparing between $\mathcal{L}_t$ and $\mathcal{U}_t$, we are able to take the influence of the labeled set on the value of unlabeled candidates into consideration.

3.3 Query Module

With our newly proposed dissimilarity scores and the conventional metrics proposed in the standard active graph embedding system [1], our AL query module can be described as follows:

$$v^* = \underset{i}{\operatorname{argmax}} \left(\alpha \phi_{\text{AGE}}(v_i) + \beta \phi_{\text{dissimilarity}}(v_i) \right)$$

where $\phi_{\text{AGE}}(v_i)$ is the traditional graph active learning query metrics (details could be found at Appendix A) and $\phi_{\text{dissimilarity}}(v_i)$ is the combination of the three newly proposed dissimilarity scores. The hyper-parameter α and β are time sensitive. Details on the selection and tuning of those hyper-parameters could be found in Appendix B.

4 Experiments and Discussion

Experimental Setting. We evaluate the performance of our proposed scores on three commonly used datasets: Cora [7], Citeseer [2], and Pubmed [12]. We select GCN [5] as our GNN model, and adopt the AGE [1] system to show that our proposed scores can improve this promising system. Details about the data set and our training settings are in Appendix B.

Main Results. We present our main results in Table 1. According to our experiments, all three scores (FDS, SDS, and EDS) have shown improvement on the classification accuracy on all benchmark datasets. We can find that, the combination of FDS and SDS yields the best performance, because our method can utilize both the feature level information of the unlabeled nodes and the structural level information of the unlabeled nodes by combining FDS and SDS.

Although the EDS also combines both the structural and feature-level information of unlabeled nodes, it does not give as much performance gain as the other two scores. In Pubmed, we observed a performance drop when using EDS as our additional score. Moreover, we obserbed that combining all the three dissimilarity scores are shown to be less powerful than combining FDS and SDS. One possible explanation is that the embedding dissimilarity score is dependent on the quality of our GCN parameters. At the early stage of the training process, the GCN backbone might not be well trained, hence hard to provide an accurate embedding to aggregate the feature-level information and the structural information.

Ablation Studies. We examine whether our method can be applied to GNN backbones other than GCN. As shown in Table 2, we replace the GCN backbone with graph attention network (GAT) [14] and simplifying graph convolutional network (SGC) [16]. We provide the results on Cora dataset in Table 2. We observe that our three dissimilarity metrics could still improve the accuracy of node classification tasks when the network model is changed to GAT and SGC. This further assures the generalizability of our dissimilarity metrics among different GNN architectures. Due to space limitation, we put the results on Citeseer in Appendix E.

In addition, we examine whether our method can be applied to other benchmark datasets, such as heterophilic graphs whose connected nodes are less likely to belong to the same class [20], and find that all the current scores will results in a degenerated performance, as their key intuition is dissimilar nodes would be able to cover a more diverse training set (and can cover different classes), which is not true for heterogeneous graphs.

Datasets \Metric	GCN	AGE	AGE+FDS	AGE+SDS	AGE+EDS	AGE+FDS+SDS
Cora \MacroF1 (%)	79.13	80.22	**81.54**	81.00	80.85	81.43
Citeseer \MacroF1 (%)	66.96	66.70	66.93	**67.86**	66.94	67.43
Pubmed \MacroF1 (%)	77.30	78.85	79.37	79.43	76.87	**79.53**
Cora \MicroF1 (%)	79.95	81.36	82.55	82.18	81.84	**82.59**
Citeseer \MicroF1 (%)	70.83	71.92	72.77	72.69	72.42	**73.06**
Pubmed \MicroF1 (%)	77.91	79.43	80.00	79.93	77.90	**80.23**

Table 1: F1 Scores of Different Active Learning Score Combination for GCN Backbone

Backbone	Metrics	Non-AL	AGE	AGE+FDS	AGE+SDS	AGE+EDS	AGE+FDS+SDS
GAT	**MacroF1** (%)	77.61	78.95	80.08	80.45	79.37	**80.89**
GAT	**MicroF1** (%)	78.28	80.39	80.93	81.76	80.46	**82.32**
SGC	**MacroF1** (%)	78.17	78.53	**80.58**	79.98	80.46	80.11
SGC	**MicroF1** (%)	79.18	80.10	**81.87**	81.38	81.65	81.57

Table 2: F1 Scores of Different Active Learning Score Combination for Other Backbones for Cora

5 Conclusion and Future Directions

In this work, with the aim of improving active learning on graphs, we propose 3 dissimilarity-based metrics to select the valuable nodes to query their labels. As shown by our experiments, all these scores are capable of bringing performance gain. In addition, our ablation study shows the proposed metrics can work with different GNN backbones, which shows they have good generalizability. Though our proposed scores achieve a promising result, there are some limitations that we can work as a future direction to further improve this work. First, since the EDS relies on the embedding learned by the backbone GNN model, it's power might be weakened as the model may not be able to provide high-quality embeddings. Second, we mainly evaluate our method on homogeneous graphs now, and it is worth exploring to examine the method on more heterogeneous graphs.

References

[1] Hongyun Cai, Vincent Wenchen Zheng, and Kevin Chen-Chuan Chang. 2017. Active Learning for Graph Embedding. *CoRR* abs/1705.05085 (2017). arXiv:1705.05085

[2] C Lee Giles, Kurt D Bollacker, and Steve Lawrence. 1998. CiteSeer: An automatic citation indexing system. In *Proceedings of the third ACM conference on Digital libraries*. 89–98.

[3] William L. Hamilton, Rex Ying, and Jure Leskovec. 2017. Inductive Representation Learning on Large Graphs. In *Proceedings of the 31st International Conference on Neural Information Processing Systems* (Long Beach, California, USA) *(NIPS'17)*. Curran Associates Inc., Red Hook, NY, USA, 1025–1035.

[4] Shengding Hu, Zheng Xiong, Meng Qu, Xingdi Yuan, Marc-Alexandre Côté, Zhiyuan Liu, and Jian Tang. 2020. Graph Policy Network for Transferable Active Learning on Graphs. In *Proceedings of the 34th International Conference on Neural Information Processing Systems* (Vancouver, BC, Canada) *(NIPS'20)*. Curran Associates Inc., Red Hook, NY, USA, Article 853, 12 pages.

[5] Thomas N. Kipf and Max Welling. 2017. Semi-Supervised Classification with Graph Convolutional Networks. In *International Conference on Learning Representations (ICLR)*.

[6] Jiaqi Ma, Ziqiao Ma, Joyce Chai, and Qiaozhu Mei. 2022. Partition-Based Active Learning for Graph Neural Networks. In *Proceedings of the 8th International Workshop on Deep Learning on Graphs (DLG-KDD)*.

[7] Andrew Kachites McCallum, Kamal Nigam, Jason Rennie, and Kristie Seymore. 2000. Automating the construction of internet portals with machine learning. *Information Retrieval* 3, 2 (2000), 127–163.

[8] Lawrence Page, Sergey Brin, Rajeev Motwani, and Terry Winograd. 1999. *The PageRank Citation Ranking: Bringing Order to the Web*. Technical Report 1999-66. Stanford InfoLab. Previous number = SIDL-WP-1999-0120.

[9] Pengzhen Ren, Yun Xiao, Xiaojun Chang, Po-Yao Huang, Zhihui Li, Brij B. Gupta, Xiaojiang Chen, and Xin Wang. 2021. A Survey of Deep Active Learning. *ACM Comput. Surv.* 54, 9, Article 180 (oct 2021), 40 pages. https://doi.org/10.1145/3472291

[10] Benedek Rozemberczki, Carl Allen, and Rik Sarkar. 2021. Multi-Scale Attributed Node Embedding. *Journal of Complex Networks* 9, 2 (2021).

[11] Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. 2018. Modeling relational data with graph convolutional networks. In *European semantic web conference*. Springer, 593–607.

[12] Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. 2008. Collective Classification in Network Data. *AI Magazine* 29, 3 (Sep. 2008), 93. https://doi.org/10.1609/aimag.v29i3.2157

[13] Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. 2015. Line: Large-scale information network embedding. In *Proceedings of the 24th international conference on world wide web*. 1067–1077.

[14] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. 2018. Graph Attention Networks. *International Conference on Learning Representations* (2018). accepted as poster.

[15] Boris Weisfeiler and Andrei Leman. 1968. The reduction of a graph to canonical form and the algebra which appears therein. *NTI, Series* 2, 9 (1968), 12–16.

[16] Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. 2019. Simplifying Graph Convolutional Networks. In *Proceedings of the 36th International Conference on Machine Learning*. PMLR, 6861–6871.

[17] Yuexin Wu, Yichong Xu, Aarti Singh, Yiming Yang, and Artur Dubrawski. 2019. Active Learning for Graph Neural Networks via Node Feature Propagation. *CoRR* abs/1910.07567 (2019). arXiv:1910.07567

[18] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. 2019. How Powerful are Graph Neural Networks?. In *International Conference on Learning Representations*.

[19] Rex Ying, Jiaxuan You, Christopher Morris, Xiang Ren, William L. Hamilton, and Jure Leskovec. 2018. Hierarchical Graph Representation Learning with Differentiable Pooling. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems* (Montréal, Canada) *(NIPS'18)*. Curran Associates Inc., Red Hook, NY, USA, 4805–4815.

[20] Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. 2020. Beyond homophily in graph neural networks: Current limitations and effective designs. *Advances in Neural Information Processing Systems* 33 (2020), 7793–7804.

A Common Active Learning Algorithms on Graphs

A.1 AGE

Active Graph Embedding (AGE) is a framework proposed by [1]. AGE use ϕ_{AGE} as query function to select the best querying candidates. ϕ_{AGE} has three components.

The first and the second component of ϕ_{AGE} are two representativeness-based metrics: graph centrality and information density. Graph centrality measures how important an candidate node v_i is in the perspective of information flow on the entire graph by adopting the PageRank centrality [8]. Information density measures how representative an candidate node v_i is by using KMeans clustering, the closer a node is to the cluster center, the more representative it is. Their equations are as following:

$$\phi_{\text{centrality}}\left(v_i\right) = \rho \sum_j A_{ij} \frac{\phi_{\text{centrality}}\left(v_j\right)}{\sum_k A_{jk}} + \frac{1 - \rho}{N} \tag{5}$$

$$\phi_{\text{density}}\left(v_i\right) = \frac{1}{1 + \text{ED}\left(\text{EMB}(v_i), \text{CC}(v_i)\right)} \tag{6}$$

where ED is the euclidean distance function, $\text{EMB}(v_i)$ is the embedding of the node v_i, $\text{CC}(v_i)$ is the center of cluster which v_i belongs to, and ρ is the damping parameter.

The third one is an uncertainty-based metric which uses the entropy information of each node during the learning process. It is calculated according to the following equation:

$$\phi_{\text{entropy}}\left(v_i\right) = -\sum_{c=1}^{C} \mathbf{P}\left(Y_{ic} = 1 \mid \mathcal{G}, \mathcal{L}, X\right) \log \mathbf{P}\left(Y_{ic} = 1 \mid \mathcal{G}, \mathcal{L}, X\right), \tag{7}$$

where the component $\mathbf{P}\left(Y_{ic} = 1 \mid \mathcal{G}, \mathcal{L}, X\right)$ denotes the probability that node v_i belongs to class c.

$$\phi_{\text{AGE}}\left(v_i\right) = \alpha_1 \phi_{\text{centrality}}\left(v_i\right) + \alpha_2 \phi_{\text{density}}\left(v_i\right) + \alpha_3 \phi_{\text{entropy}}\left(v_i\right) \tag{8}$$

where α_1, α_2 and α_3 are the coefficients of $\phi_{\text{centrality}}$, ϕ_{density} and ϕ_{entropy} in the AGE model,

A.2 Other Notable Active Learning Model for Graphs

There are some other active learning frameworks for GNN-based graph mining models. Hu et. al. [4] propose a performance-based active learning framework based on reinforcement learning. Wu et. al. [17] improve on the KMeans clustering method and yield better accuracy among representativeness-based metrics. Recently, Ma et. al. [6] propose a partition algorithm to enhance the representativeness of the selected nodes. Although Hu et. al.'s work thoroughly exploits the strength of performance-based metrics, the reinforcement learning framework itself could be a significant computational burden. Both Wu et. al.'s work and Ma et. al.'s work focus on improving representativeness-based metrics only, which might neglect certain under-represented nodes.

B Experimental Setting

Our $\phi_{\text{dissimilarity}}$ is formulated in this way:

$$\phi_{\text{dissimilarity}}\left(v_i\right) = \beta_1 \phi_{\text{FDS}}\left(v_i\right) + \beta_2 \phi_{\text{SDS}}\left(v_i\right) + \beta_3 \phi_{\text{EDS}}\left(v_i\right) \tag{9}$$

Here, β_1, β_2 and β_3 are the coefficients of our proposed FDS, SDS, and EDS.

Inspired by [1], We learn our hyper-parameters with the following constraints:

$$\alpha + \beta = 1 \tag{10}$$

$$\alpha_1 + \alpha_2 + \alpha_3 = 1 \tag{11}$$

$$\beta_1 + \beta_2 + \beta_3 = 1 \tag{12}$$

$$\alpha_1 \sim \mathbf{Beta}(1,\ 1.005 - Ct) \tag{13}$$

$$\alpha_2 = \alpha_3 = \beta_1 = \beta_2 = \beta_3 = \frac{1 - \alpha_1}{5} \tag{14}$$

t is the epoch number, **Beta** is the beta distribution where we sample α_1 from, C is a constant and a hyper-parameter to be chosen. On high level, the time-sensitive hyper-parameter set increases the weight of $\phi_{\text{centrality}}(v_i)$ at the early training stage because we want to collect more representitive nodes from the graph, and decrease the weight of $\phi_{\text{centrality}}(v_i)$ at the later training stage since we want to include more dissimilar nodes to our existing labelled set. When running experiments on one of our dissimilarity scores (e.g. FDS), we let coefficients of other dissimilarity scores (e.g. β_2 and β_3 in the case of FDS) to be 0.

For the Cora dataset, it consists of 2708 scientific publications that are classified into seven classes. And its graph has 5429 links. As for Citeseer, it has 3312 scientific publications classified into six classes. And its graph has 4732 links. On the other hand, we also have a larger dataset Pubmed which consists of 19717 publications that are classified into 3 categories. And it has 44338 links. For all the baselines, we re-run their experiments to make sure we get reliable results.

We use Macro F1 and Micro F1 to evaluate our node classification performance.

We choose 4 labels for each class to be our original labels. Then, we incrementally add 1 additional label after each epoch based on our new proposed scores. We use the same total label budget B, which is 20 times the number of class to better compare with our baseline. After the budget is reached, we no long add more labels and continue training until converges.

Since the performance of active learning is often unstable, we run our experiments on 10 different validation sets using 10 different random seeds to reduce the variance of our results. We then take the average Macro F1 and Micro F1 over these 10 runs. For Pubmed, since the dataset is large, we only average over 3 runs due to time limit.

Here are some details of our hyper-parameter setting: We use the original implementation of GCN which has 2 graph convolution layers. We use a learning rate of 0.01 and a maximum number of epoches of 300. The hidden embedding dimension after layer 1 is 16. We choose our weight tuning hyper-parameter C to be 0.9 for Citeseer, 0.99 for Cora and 0.995 for Pubmed. The hyper-parameter C is chosen based on empirical results. One high level explanation of our choice of C is that Pubmed is denser than Cora, and Cora is denser than Citeseer. When the graphs are denser, we should put more weight on the centrality score, since the nodes with high centrality are more likely to be the most representation nodes in those graphs.

C   GNN Variants

- **GAT** [14]: Graph Attention Network (GAT) is an architecture that operates on graph-structured data, leveraging masked self-attentional layers to address the shortcomings of prior graph convolution methods.
- **SGC** [16]: Simplifying Graph Convolutional Networks (SGC) is a compact model which reduces excess complexity of GCN through successively removing nonlinearities and collapsing weight matrices between consecutive layers.
- **GraphSAGE** [3]: A GNN model that generates inductive node embedding by local neighborhood sampling strategies, which allows better generalizability to unseen node data.
- **GIN** [18]: Graph Isomorphism Network (GIN) is a model that generalizes Weisfeiler-Lehman (WL) graph isomorphism test [15]. It could reach the maximum discriminative power among GNN variants on graph classification tasks.

D   A Closer Study on Heterophily

In recent years, the study of heterophilic graph mining has gain some research attention. Homophily ratio stands for the fraction of graph edges where the two nodes they connect are of the same class. Zhu et. el. [20] have shown that algorithms perform well in homophilic graphs (e.g., Cora, Citeseer, Pubmed) might not perform as well in heterophilic datasets. Hence, it is worth checking the assumption of homophily in our active learning framework. In this way we could better study on the the generalizability of current AL framework in the setting of heterophilic graphs.

- **Centrality Score**: The effectiveness of centrality score will somehow be affected by changing the assumption of homophily. While centrality usually implies representativeness

on homophilic graphs, this might not be true on heterophilic graphs. In heterophilic graphs, all nodes with high centrality might belongs to a single class. For example, in a university enrolment network with professors and students, all high centrality nodes are professors.

- **Entropy Score**: The effectiveness of entropy score will not be affected by changing the assumption of homophily. The reason is that the entropy score is generated using the model output, and it aims for evaluating how uncertain the model is when regarding to a particular nodes. Changing the graph from homophilic to heterophilic will not affect the pipeline which chooses the most uncertain nodes.

- **Density Score and Embedding Dissimilarity Score**: The effectiveness of density score will not be affected if we change the assumption of homophily. This is because most density scores are generated using clustering algorithms in-taking model embedding outputs as raw inputs. If the model itself is well trained, the quality of the node embedding will be good enough to provide guidance for valuable node selection. The same arguments also applies for EDS.

- **Feature Dissimilarity Score**: The effectiveness of FDS will be severely affected by changing the assumption of homophily, since FDS is a score that completely neglects the structural information of a graph. While this is not a significant problem in homophilic graphs where nodes in different sub-graph clusters usually have different features, in heterophilic graphs, neglecting the structural information might lead to node selection within a single sub-graph cluster. This will severely affect the representativeness of nodes being selected.

- **Structural Dissimilarity Score**: The effectiveness of SDS will also be severely affected by changing the assumption of homophily, since the assumption "two nodes are similar if they share the same neighbors" will break under heterophilic setting.

To verify our hypothesises above, we conduct experiments on a heterophilic dataset, Chameleon, which contains 2277 nodes in 5 categories and 31421 edges. The data is collected by Rozemberczki et. al. [10] from the English Wikipedia which represent page-page networks on chameleons. Its homophily ratio is 0.23, which makes Chameleon a highly heterophilic dataset. For comparison, the homophily ratio is 0.81 in Cora, 0.74 in Citeseer and 0.80 in Pubmed. We use the same experimental settings as what we have for the other experiments. For fair comparison, we add only one score at a time when running on Chameleon dataset. We use GCN-Cheby (GCC) to be our baseline, which is one of the SOTA models for node classification on heterophilic graphs [20].

Score	GCC	GCC+Centrality	GCC+Entropy
MacroF1 (%)	47.68	33.05	38.84
MicroF1 (%)	48.15	33.70	40.33

Score	GCC+FDS	GCC+SDS	GCC+EDS
MacroF1 (%)	25.10	32.28	39.99
MicroF1 (%)	30.99	32.58	40.41

Table 3: F1 Scores of Different Dissimilarity Scoring Functions on Chameleon dataset

The experimental results align with our hypothesis that FDS and SDS are the most severely affected scores when changed to heterophilic setting. Those two scores have the most performance drop compared to GCC. The performance drop of Centrality Score is also significant, but slightly better than FDS and SDS. In contrast, EDS and Entropy Score experience a relatively small performance drop compared to GCC, which means those two scores are more robust under heterophilic setting. It is also notable that none of those scores performs better that GCC, which means that there is still a significant room for performance improvement by finding specifically targeted types of active learning score functions for heterophilic graphs.

E   Results for GAT and SGC on Citeseer Dataset

Datasets	GAT	GAT+AGE	GAT+AGE+FDS	GAT+AGE+SDS	GAT+AGE+EDS	GAT+AGE+FDS+SDS
Citeseer \MacroF1 (%)	62.05	61.96	61.90	63.22	61.95	**63.10**
Citeseer \MacroF1 (%)	65.76	67.65	68.12	68.50	67.92	**69.36**
Datasets	SGC	SGC+AGE	SGC+AGE+FDS	SGC+AGE+SDS	SGC+AGE+EDS	SGC+AGE+FDS+SDS
Citeseer \MacroF1 (%)	64.61	65.94	66.01	**67.25**	66.94	66.14
Citeseer \MacroF1 (%)	68.25	70.65	70.24	**71.72**	71.12	70.63

Table 4: F1 Scores of Different Active Learning Score Combination for other backbones