Temporal Alignment Prediction for Supervised Representation Learning and Few-Shot Sequence Classification

Abstract

Explainable distances for sequence data depend on temporal alignment to tackle sequences with different lengths and local variances. Most sequence alignment methods infer the optimal alignment by solving an optimization problem under pre-defined feasible alignment constraints, which not only is time-consuming, but also makes end-to-end sequence learning intractable. In this paper, we propose a learnable sequence distance called Temporal Alignment Prediction (TAP). TAP employs a lightweight convolutional neural network to directly predict the optimal alignment between two sequences, so that only straightforward calculations are required and no optimization is involved in inference. TAP can be applied in different distance-based machine learning tasks. For supervised sequence representation learning, we show that TAP trained with various metric learning losses achieves completive performances with much faster inference speed. For few-shot action classification, we apply TAP as the distance measure in the metric learning-based episode-training paradigm. This simple strategy achieves comparable results with state-of-the-art few-shot action recognition methods.

1 Introduction

Distance between sequences plays a crucial role in sequence classification (Sakoe & Chiba, 1978), retrieval (Su et al., 2019), clustering (García-García et al., 2008), etc. Measuring distance between sequences is difficult, since different sequences may have different sampling rates, execution speeds, local distortions, initial states, and elastic warpage. To tackle such temporal variances, existing sequence distances either encode each sequence into a feature vector invariant to temporal variances (Abid & Zou, 2018; Lohit et al., 2019) or employ alignment for temporal correspondence calibration (Sakoe & Chiba, 1978; Su & Hua, 2019). Typical feature-based methods use recurrent neural networks (RNNs) (Ramachandran et al., 2017) to encode sequences and measure the Euclidean distance between corresponding features. The feature of a sequence is fixed when compared with any other sequence. Although such methods are naturally learnable and only perform forward calculations in inference, they require large amounts of sequences to train complex RNNs and have weak interpretability, since how the learned features handle temporal variances and what kinds of variances can be handled are not clear.

Alignment-based methods determine different optimal alignments for different sequence pairs. This is more intuitive and flexible because temporal variances may be different when comparing different sequences. Such methods have good interpretability since alignments clearly indicate how and where the two sequences differ in temporal steps. Most alignment methods solve an optimization problem under pre-defined feasible constraints to infer the optimal alignment. E.g., DTW (Sakoe & Chiba, 1978) requires dynamic programming and OPW (Su & Hua, 2019) employs fixed-point iterations. Such optimizations are often time-consuming, cannot fully utilize GPU, and do not scale well to long sequences.

Moreover, since inferring the alignment is itself an optimization problem and has its own objective, sequence distance-based end-to-end learning using other objectives becomes intractable. For instance, learning discriminative temporal representations for elements in sequences often adopt the objective that sequences of different classes are better separated w.r.t. a sequence distance (Mei et al.,

2014; Su & Wu, 2020b). Gradients of this overall objective are difficult to pass through alignments since they are latent variables determined by another optimization problem.

In this paper, we propose a learnable alignment-based sequence distance, namely *Temporal Alignment Prediction (TAP)*. TAP simulates the optimization-based inference from the input sequence pair to the optimal alignment as a function. The function is modeled by a lightweight convolutional neural network to directly predict the optimal alignment. TAP can be applied in different distance-based machine learning tasks under different settings. As instances, we show the applications of TAP in supervised representation learning and few-shot learning for sequence data. For supervised learning, we employ metric learning losses by using TAP as the distance measure to learn the frame-wise temporal representations of sequence data. For few-shot learning, we adopt TAP as the distance measure in the metric learning based paradigm to compare the query and support sequence samples. In both cases, owing to the straightforward structure of TAP, the alignment prediction network and the feature extraction or transformation network can be jointly trained in an end-to-end manner, resulting in principled yet straightforward temporal supervised learning and few-shot learning solutions for sequence data. We further show the application of TAP in self-supervised alignment learning in the appendix.

The main contributions of this paper are three-fold. 1. We propose TAP, a learnable and fast sequence distance that only requires straightforward calculations in inference and has good interpretability. 2. We show that TAP conveniently enables end-to-end supervised sequence representation learning with different losses. 3. We adopt TAP to dynamically align the support and query sequences for few-shot action recognition, so that alignments and temporal representations can be jointly learned with the episode-training strategy. Experiments on six datasets demonstrate the effectiveness of TAP for both supervised learning and few-shot learning.

2 RELATED WORK

Alignment-based sequence distance. Various variations of DTW have been proposed to speed up the inference (Salvador & Chan, 2007; Al-Naymat et al., 2009), or adapt to additional or modified constraints (Ratanamahatana & Keogh, 2004), or tackle sequences from different modalities (Zhou & Torre, 2009; Zhou & De la Torre, 2016; Trigeorgis et al., 2016; 2017; Cohen et al., 2021). They rely on non-differential dynamic programming for inference. Soft-DTW (Cuturi & Blondel, 2017) optimizes a differentiable loss by using the soft-minimum cost of all feasible alignments as the objective. TCOT (Su et al., 2019) and OPW (Su & Hua, 2019) view the alignment problem as the optimal transport problem with temporal regularizations. These methods solve an optimization problem to infer the optimal alignment. In contrast, our method directly predicts the alignment using a neural network, does not have its own objective, and only involves differentiable calculations.

Data-driven alignment methods. In Abid & Zou (2018), Autowarp finds the warping distance that best mimics the distance between the features encoded by LSTM, which is difficult to be integrated into an end-to-end framework because the autoencoder needs to be pre-trained and a betaCV-based optimization is required. It is shown in Tallec & Ollivier (2018) that RNN can learn to warp sequences. In Lohit et al. (2019); Weber et al. (2019), a fixed warping function is predicted for a given sequence when comparing with different sequences. This may be viewed as warping all sequences w.r.t. a fixed timing scale, which may bias to the training sequences. In contrast, since the relative local variations and correspondences between different sequences are different, our method predicts different alignments for different sequence pairs.

Supervised representation learning for sequences. Generally, since alignment-based distances need to solve their own optimization problems to infer alignments in the latent space, the gradients of the supervised metric learning loss cannot be directly propagated. Existing methods exploit either an approximate proxy loss (Su et al., 2018; Lajugie et al., 2014), or a time-consuming optimization method to iteratively infer alignments (Mei et al., 2014), or both (Su & Wu, 2020a;b). In this paper, we show that existing deep metric learning methods can be readily applied to the proposed TAP distance in an end-to-end manner.

Few-shot action recognition. Most existing few-shot action recognition methods follow the metric learning based paradigm. In Ben-Ari et al. (2021) and Tan & Yang (2019), TAEN and FAN encode each action into a representation with a fixed dimension and apply vector-wise metrics. Recent

Figure 1: (a) The TAP framework. (b) The alignment prediction network.

works identify the importance of temporal alignment for tackling non-linear temporal variations. Various alignment-based distances are proposed to compare sequence pairs, such as the temporal attentive relation network (TARN) (Bishay et al., 2019), a variant of DTW used in OTAM (Cao et al., 2020), the permutation-invariant spatial and temporal attention reweighted distance in ARN (Zhang et al., 2020), the temporal CrossTransformer for comparing all possible subsequences in TRX (Perrett et al., 2021), and the two-stage temporal alignment network (TTAN) (Li et al., 2021). Following this spirit, we apply the proposed TAP to perform temporal alignment and measure the distance between support and query sequences without any complicated attention mechanism, yielding a simple yet effective few-shot sequence learning solution.

3 METHODOLOGY

3.1 TEMPORAL ALIGNMENT PREDICTION

We first revisit the unified formulation of sequence distance in Su & Wu (2019). Let $\boldsymbol{X} = [\boldsymbol{x}_1, \cdots, \boldsymbol{x}_{L_X}] \in \mathbb{R}^{d \times L_X}$ and $\boldsymbol{Y} = [\boldsymbol{y}_1, \cdots, \boldsymbol{y}_{L_Y}] \in \mathbb{R}^{d \times L_Y}$ be two sequences with lengths of L_X and L_Y, respectively. The elements $\boldsymbol{x}_i, i = 1, \cdots, L_X$ of $\boldsymbol{X}$ and $\boldsymbol{y}_j, j = 1, \cdots, L_Y$ of $\boldsymbol{Y}$ lie in a d-dimensional feature space $\mathbb{R}^d$. Many alignment-based distances between $\boldsymbol{X}$ and $\boldsymbol{Y}$ can be unified as follows:

$$d(\boldsymbol{X}, \boldsymbol{Y}) = \langle \boldsymbol{T}^*, \boldsymbol{D} \rangle, \tag{1}$$

$$\boldsymbol{T}^* = \arg\min_{\boldsymbol{T} \in \boldsymbol{\Phi}} \langle \boldsymbol{T}, \boldsymbol{D} \rangle + \mathscr{R}(\boldsymbol{T}), \tag{2}$$

where $\langle \boldsymbol{T}, \boldsymbol{D} \rangle = tr(\boldsymbol{T}^T \boldsymbol{D})$ is the Frobenius dot product. $\boldsymbol{D} := [e(\boldsymbol{x}_i, \boldsymbol{y}_j)]_{ij} \in \mathbb{R}^{L_X \times L_Y}$ is the matrix of pairwise distances between elements in $\boldsymbol{X}$ and $\boldsymbol{Y}$, $e(\boldsymbol{x}_i, \boldsymbol{y}_j)$ is a vector-wise distance between two elements $\boldsymbol{x}_i$ and $\boldsymbol{y}_j$, which we use Euclidean distance in this paper. $\boldsymbol{T}$ is an alignment matrix whose element $\boldsymbol{T}_{ij}$ indicates whether or how likely $\boldsymbol{x}_i$ and $\boldsymbol{y}_j$ are aligned. $\boldsymbol{\Phi}$ is the set of all feasible $\boldsymbol{T}$ with some constraints, which is a subset of $\mathbb{R}^{L_X \times L_Y}$. $\mathscr{R}(\boldsymbol{T})$ is a regularization term on $\boldsymbol{T}$. $\boldsymbol{T}^*$ is the optimal alignment which is the solution of the optimization problem in Eq. (2).

Different sequence distances impose different constraints on the feasible set, have different regularization terms, and use different optimization methods for inference. For instance, DTW optimizes Eq. (2) with $\mathscr{R}(\boldsymbol{T}) = 0$ and the boundary, continuity, and monotonicity constraints via dynamic programming, while OPW optimizes Eq. (2) with two temporal regularization terms and the coupling constraints via the Sinkhorn's matrix scaling algorithm. Solving $\boldsymbol{T}^*$ by the optimization Eq. (2) not only requires a long inference time, but also makes it difficult to apply a loss on the sequence distance Eq. (1) for learning element representations, because $\boldsymbol{T}^*$ is a latent variable that needs to be inferred and its gradient cannot be calculated.

To avoid solving the optimization problem, we propose a feedforward framework for measuring the distances between sequences, namely *Temporal Alignment Prediction (TAP)*. Fig. 1(a) illustrates the TAP framework. For two sequences $\boldsymbol{X} = [\boldsymbol{x}_1, \cdots, \boldsymbol{x}_{L_X}]$ and $\boldsymbol{Y} = [\boldsymbol{y}_1, \cdots, \boldsymbol{y}_{L_Y}]$, their TAP distance also has the form of Eq. (1), i.e., the Frobenius dot product of $\boldsymbol{D}$ and $\boldsymbol{T}^*$. Different from other sequence distances which infer the alignment with predefined objectives and constraints, TAP uses an alignment prediction neural network f to directly predict the optimal $\boldsymbol{T}^* = f(\boldsymbol{X}, \boldsymbol{Y})$ by taking the two sequences as inputs and learns f from data.

The alignment prediction network f can be instantiated by different architectures. In this paper, we propose a lightweight convolutional neural network architecture for its simplicity, fast inference speed, and good interpretability. Specifically, we reuse the spatial ground matrix $\boldsymbol{D}$ to measure all pairwise distances between elements in $\boldsymbol{X}$ and $\boldsymbol{Y}$. The relative positions of $\hat{\boldsymbol{x}}_i$ and $\hat{\boldsymbol{y}}_j$ are i/L_X and j/L_Y, respectively. To incorporate the temporal dissimilarities, TAP further calculates all pairwise Euclidean distances between the relative positions between $\boldsymbol{x}_i$ and $\boldsymbol{y}_j$ into a matrix $\boldsymbol{D}_t := [e(i/L_X, j/L_Y)]_{ij} \in \mathbb{R}^{L_x \times L_Y}$.

Then, we concatenate $\boldsymbol{D}$ and $\boldsymbol{D}_t$ along the channel dimension to form $\boldsymbol{D}_s$ with a size of $L_x \times L_y \times 2$. We use a CNN g to predict the final alignment matrix from $\boldsymbol{D}_s$. The CNN uses three convolutional layers each followed by ReLu. The kernel size in the three layers is 5, 5, and 3, respectively, the stride is fixed to 1, and the padding is set to 2, 2, and 1, respectively, to keep the spatial size. The numbers of kernels in the three layers are set to 30, 30, and 1, respectively. The learned kernels are expected to capture the local alignment patterns. The output of f is augmented by a residual connection with $\boldsymbol{D}$, resulting in the similarity matrix $\boldsymbol{S} := -(\boldsymbol{D} + g(\boldsymbol{D}_s)) \in \mathbb{R}^{L_X \times L_Y}$.

The attentions of elements in $\boldsymbol{Y}$ on $\boldsymbol{x}_i$ are obtained by performing Softmax on the i-th row of $\boldsymbol{S}$. The attentions on all elements in $\boldsymbol{X}$ form an attention matrix $\boldsymbol{A}$, which can be obtained by performing Softmax along the 2nd dimension of $\boldsymbol{S}$:

$$\boldsymbol{A} = [\frac{exp(\boldsymbol{S}_{ij})}{\sum_{k=1}^{L_Y} exp(\boldsymbol{S}_{ik})}]_{ij} \in \mathbb{R}^{L_X \times L_Y}. \tag{3}$$

To generate the predicted alignment $\boldsymbol{T}^*$, TAP finally performs a global L_1 normalization on $\boldsymbol{A}$:

$$\boldsymbol{T}^* = [\frac{\boldsymbol{A}_{ij}}{\sum_{i=1}^{L_X} \sum_{j=1}^{L_Y} \boldsymbol{A}_{ij}}]_{ij} \in \mathbb{R}^{L_X \times L_Y}. \tag{4}$$

$\boldsymbol{T}_{ij}^*$ indicates the probability of aligning $\boldsymbol{x}_i$ and $\boldsymbol{y}_j$. The TAP distance between $\boldsymbol{X}$ and $\boldsymbol{Y}$ is calculated as in Eq. (1). The prediction network f of TAP is lightweight since it only contains a few convolutional kernels of g as parameters.

Limitations. 1. The family of alignments for TAP is $\Phi := \{\boldsymbol{T} \in \mathbb{R}_+^{L_x \times L_y} | \boldsymbol{T}\boldsymbol{1}_{L_y} = \boldsymbol{1}_{L_x}/L_x\}$, where $\boldsymbol{1}_L$ is a L-dimensional vector with all 1 elements. Since strict order-preserving is not guaranteed in Φ, the performance of TAP may be limited when data are strictly ordered. 2. $\boldsymbol{T}^T\boldsymbol{1}_{L_x} = \boldsymbol{1}_{L_y}/L_y$ does not necessarily hold, hence TAP is asymmetric and is not a real metric. These limitations make TAP more flexible in turn. 1. Without strict order-preserving constraint, TAP can tackle local temporal reorders and generalize to non-sequential (e.g. spatial, cross-modal, etc) correspondences. 2. Asymmetric alignment distinguishes the source sequence $\boldsymbol{X}$ and the target sequence $\boldsymbol{Y}$, where all elements in $\boldsymbol{X}$ must be transported with the same mass when aligning to different target sequences. To perform classification or retrieval, we can always set the test or query sequence as the source, which serves as a standard template to be aligned. The symmetric distance can be obtained by averaging $d(\boldsymbol{X}, \boldsymbol{Y})$ and $d(\boldsymbol{Y}, \boldsymbol{X})$.

3.2 SUPERVISED REPRESENTATION LEARNING WITH TAP

The performance of conventional alignment-based distances and TAP highly depends on $\boldsymbol{D}$, where $\boldsymbol{D}$ depends on the representation space or the ground metric for elements in sequences. Therefore, learning more discriminative representations or ground metrics is of great interest. We transform element-wise features $\boldsymbol{x}_i$ of $\boldsymbol{X}$ into a new space by a transformation network h. We denote the sequence of transformed features $h(\boldsymbol{x}_i)$ by $h(\boldsymbol{X})$. When labeled training sequences are available, the objective is often to make the sequence distance better separate sequences from different classes. However, such objectives are difficult to optimize for conventional alignment-based distances because they solve another optimization problem to obtain the alignments. For example, if we apply the triplet loss to the OPW distance, the objective becomes:

$$\min_{h} \sum_{n=1}^{B} \Big(\sum_{n':y^{n'}=y^n} \max(\big\langle \boldsymbol{T}_{nn'}^*, \boldsymbol{D}(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'})) \big\rangle - d_s^n + m, 0)$$
$$+ \sum_{n':y^{n'}\neq y^n} \max(d_l^n + m - \big\langle \boldsymbol{T}_{nn'}^*, \boldsymbol{D}(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'})) \big\rangle, 0)) \quad . \tag{5}$$
$$s.t. \ \boldsymbol{T}_{nn'}^* = \arg\min_{\boldsymbol{T}\in\Phi} \big\langle \boldsymbol{T}, \boldsymbol{D}(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'})) \big\rangle + \mathcal{R}(\boldsymbol{T})$$

The gradients of this objective with respect to the parameters of h rely on $\boldsymbol{T}_{nn'}^*$, which is determined by another optimization problem with additional constraints on $\boldsymbol{T}$ and this optimization problem depends on h in turn. Therefore, the gradients cannot be explicitly formulated and directly obtained. The overall optimization problem thus cannot be optimized via back propagation in an end-to-end manner. An alternative solution is to alternatively update $\boldsymbol{T}^*$ and h by fixing the other in an iterative way, which is time-consuming and there is no theoretical guarantee of convergence. Existing methods (Mei et al., 2014; Su & Wu, 2020b) optimize a proxy or approximate objective through complex iterative solutions.

In contrast, TAP enables supervised learning of temporal representations without seeking surrogates objectives. Given a batch of B training sequences $\boldsymbol{X}^n, n = 1, \cdots, B$ with corresponding labels $y^n, n = 1, \cdots, B$, for each sequence $\boldsymbol{X}^n$, we generate its augmentation $\tilde{\boldsymbol{X}}^n$, whose class label is the same as $\boldsymbol{X}^n$, and calculate its TAP distances to all other B sequences including $\tilde{\boldsymbol{X}}^n$ after transformation by h. We obtain its largest TAP distance to $h(\boldsymbol{X}^{n'})$ of the same class as $d_l^n = \max_{n':y^{n'}=y^n} d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f)$ and its smallest TAP distance to $h(\boldsymbol{X}^{n'})$ of different classes as $d_s^n = \min_{n':y^{n'}\neq y^n} d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f)$.

Any metric learning losses can be used to train TAP. We employ three metric learning losses to learn h and f jointly, including the triplet loss with hard-mining (HM) (Hermans et al., 2017), the lifted structure (Lifted) loss (Song et al., 2016), and binomial deviance loss (Binomial) (Yi et al., 2014). For the triplet loss, we minimize the TAP distances to sequences of the same class that are larger than $d_s^n - m$, and maximize those to different classes that are smaller than $d_l^n + m$, where m is a margin and set to 0.1. The objective to be minimized over f and h is formulated as follows:

$$\min_{f,h} \sum_{n=1}^{B} \Big(\sum_{n':y^{n'}=y^n} \max(d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f) - d_s^n + m, 0)$$
$$+ \sum_{n':y^{n'}\neq y^n} \max(d_l^n + m - d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f), 0)) \quad . \tag{6}$$

For the lifted structure loss, we minimize the following objective to utilize the TAP distances among all the positive and negative pairs:

$$\min_{f,h} \sum_{n=1}^{B} \Big(\frac{2}{\beta} \log\Big(\sum_{n':y^{n'}=y^n} e^{\beta d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f)} \Big) + \frac{2}{\alpha} \log\Big(\sum_{n':y^{n'}\neq y^n} e^{-\alpha d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f)} \Big) \Big) \quad . \tag{7}$$

For the binomial deviance loss, for the n-th sequence, we first perform hard mining to select its hard positive and negative samples within the batch:

$$\mathscr{P}^n = \{n'|y^{n'}=y^n; d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f) > d_s^n - m\}$$
$$\mathscr{N}^n = \{n'|y^{n'}\neq y^n; d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f) < d_l^n + m\} \quad . \tag{8}$$

We then minimize the following objective:

$$\min_{f,h} \sum_{n=1}^{B} \Big(\frac{2}{\beta|\mathscr{P}^n|} \sum_{n'\in\mathscr{P}^n} \log(1 + e^{\beta(d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f) - 0.5)})$$
$$+ \frac{2}{\alpha|\mathscr{N}^n|} \sum_{n'\in\mathscr{N}^n} \log(1 + e^{-\alpha(d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f) - 0.5)})) \quad . \tag{9}$$

where $|\mathscr{P}^n|$ and $|\mathscr{N}^n|$ denote the number of mined positive and negative sequences, respectively. In all losses, α and β are hyper-parameters controlling the weights of positive and negative pairs, respectively. For all the losses, we also incorporate the self-supervised loss of minimizing the TAP

distance between each sequence and its augmentation, as presented in the appendix, where the augmentation is obtained by random blurring and random merge. For any supervised loss, the feature transformation network h and the alignment prediction network f in TAP are learned jointly by back-propagation in an end-to-end manner.

3.3 FEW-SHOT ACTION RECOGNITION WITH TAP

In this subsection, we demonstrate the application of TAP in few-shot action recognition. Given a training set, where the training classes have sufficient labeled videos, the goal is to train a model that can generalize to classify new classes in novel few-shot classification tasks. For a N-way K-shot classification task, there are N action classes and each class has K support videos. The task aims to classify each query video into one of the N classes. We follow the episode training and evaluation. The video dataset is divided into a training set, a validation set, and a test set. Classes in the three sets are disjoint. In the training phase, we randomly construct one N-way K-shot task in each episode to train the model. The best model is selected according to the performance on tasks constructed from the validation set and evaluated on tasks constructed from the test set.

We adopt the metric learning strategy with the TAP distance. For each N-way K-shot classification task, the support videos are denoted by $V_k^n, n = 1, \cdots, N; k = 1, \cdots, K$ and the query videos are denoted by $V_q, q = 1, \cdots, Q$, where Q is the number of query videos. For each video, we follow Cao et al. (2020); Li et al. (2021) to sample a fixed number L of frames per video. We use a feature embedding backbone h to represent each frame v_i by a d-dimensional feature vector $x_i = h(v_i)$, thus each video V is represented by a feature sequence $X = h(V) = [x_1, \cdots, x_L] \in \mathbb{R}^{d \times L}$.

To classify a query video V_q, we calculate the TAP distances between X_q and all the support sequences. Since TAP is non-symmetric, we add $d(X_q, X_k^n; f)$ and $d(X_k^n, X_q; f)$ as the dissimilarity between X_q and the k-th support sequence of the n-th class X_k^n. The similarity between V_q and the n-th class is then obtained as:

$$s_q^n = \sum_{k=1}^{K} -d(h(V_q), h(V_k^n); f) - d(h(V_k^n), h(V_q); f) \qquad (10)$$

X_q is classified to the class with the largest similarity.

In the training phase, we jointly learn the backbone h and the prediction network f of TAP with the cross-entropy loss. The loss over a single episode is formulated as follows:

$$\mathcal{L} = -\sum_{q=1}^{Q} \log \frac{exp(s_q^{y_q})}{\sum_{n=1}^{N} exp(s_q^n)}. \qquad (11)$$

where y_q is the ground-truth class label of the query video V_q.

4 EXPERIMENTS

4.1 DATASETS

For supervised representation learning, we evaluate TAP on four sequence datasets. **MSR Action3D** (Li et al., 2010; Wang et al., 2012) contains 557 skeleton sequences from 20 action classes. We follow the splitting of the dataset in Wang et al. (2012); Wang & Wu (2013). We use the 192-dimensional element-wise features in Wang et al. (2012); Wang & Wu (2013). **MSR Daily Activity3D** (Wang et al., 2012) contains 320 skeleton sequences from 16 activity classes. We also follow the splitting of the dataset in Wang et al. (2012); Wang & Wu (2013) and use the 390-dimensional element-wise features in Wang et al. (2012); Wang & Wu (2013). The **"Spoken Arabic Digits (SAD)" dataset** from the UCI Machine Learning Repository (Bache & Lichman, 2013) contains 8,800 sequences of 13-dimensional mel-frequency cepstrum coefficients from 10 classes. The dataset has 6,600 training sequences and 2,200 testing sequences. **ChaLearn** (Escalera et al., 2013b;a) contains 955 Italian gesture sequences from 20 classes. The dataset is split into training, validation, and test sets. Following Fernando et al. (2015), we conduct experiments on the segmented sequences where each sequence contains one gesture. We use the 100-dimensional element-wise features in Fernando et al. (2015). On all datasets, the lengths of different sequences are different.

For few-shot action recognition, we evaluate TAP on two video datasets. **UCF101** (Soomro et al., 2012) contains 13,320 videos of 101 classes. We follow the protocol used in Zhang et al. (2020) to split the dataset, where the training, validation, and test sets contain 70, 10, and 21 classes with 9154, 1421, and 2745 videos, respectively. **HMDB51** (Kuehne et al., 2011) consists of 6,840 videos from 51 classes. We also follow the protocol used in Zhang et al. (2020) to split the dataest, where the training, validation, and test sets contain 31, 10, and 10 classes with 4280, 1194, and 1292 videos, respectively.

4.2 IMPLEMENTATION DETAILS

The structure and hyper-parameters of the alignment prediction network are fixed in TAP, as introduced in Section 3.1. To evaluate TAP in comparison with other distances and methods on supervised representation learning, we perform two tasks on each dataset: sequence classification and sequence retrieval. For classification, we use the nearest neighbor (1-NN) classifier. For each test sequence, we calculate the distances to all training sequences w.r.t. the evaluated distance and its label is determined by the training sequence with the smallest distance. We use accuracy as the performance measure. For retrieval, we use each test sequence as a query and rank all training sequences according to their distances to the query in ascending order. We use mean average precision (MAP) as the performance measure.

Following Su & Wu (2020b), we use a three-layer perceptron as the transformation network h, where the two hidden layers have 1024 nodes followed by ReLU activations and the output has the same dimension with the input element-wise features. For learning the TAP distance, we use the Adam optimizer with a momentum of 0.9 and a weight decay of $1e^{-4}$ and train a maximum of 100 epochs. The learning rate is fixed to 0.0001 on all datasets. The batch size is set to 64 except for the MSR Activity3D dataset, where it is reduced to 16 due to memory limitation. We fix the hyper-parameters α and β in the lifted structure loss and the binomial deviance loss to 40 and 2, respectively.

To evaluate TAP on few-shot action recognition, we perform 5-way 1-shot and 5-way 5-shot classification tasks. Following Cao et al. (2020); Zhang et al. (2020); Li et al. (2021), we uniformly sample $L = 8$ frames per video, resize each frame to 256×256, augment the frames with random horizontal flipping, perform 224×224 random crops for training and center crops for testing, and use the pretrained ResNet-50 as the backbone. We jointly tune the backbone and train TAP by the SGD optimizer with a learning rate of 0.001. Each episode contains 1 task due to the memory constraint. We adapt the toolbox [1] and all other hyper-parameters remain the same. We train a maximum of 35000 iterations and select the best iteration every 5000 iterations according to the performance on the validation set. The selected model is then evaluated on the test set. Specifically, we randomly sample 10,000 tasks from the test set and report the average accuracy.

4.3 COMPARISON WITH SUPERVISED REPRESENTATION LEARNING METHODS

TAP can be used to learn temporal representations in a supervised manner as presented in Section 3.2. Comparisons with other supervised sequence representation learning methods on the four datasets are shown in Table 1, where we follow the setting and compare with the results reported in Su & Wu (2020b). LDMLT (Mei et al., 2014), SWMD (Huang et al., 2016), and RVSML (Su & Wu, 2019) learn linear transformations for elements in sequences, while deep metric learning methods with binomial deviance loss (Binomial) (Yi et al., 2014), lifted structured loss (Lifted) (Song et al., 2016), triplet loss with hard-mining (HM) (Hermans et al., 2017), and multi-similarity loss (MS) (Wang et al., 2019) learn non-linear temporal representations by treating elements in each sequence as independent samples of the same class. DeepRVSML (D-R) (Su & Wu, 2020b) is the deep extension of RVSML. All methods use the same transformation network. TAP generally outperforms these methods on all datasets. Especially, TAP achieves much higher MAP, which reflects that the TAP distances between sequences from the same class are generally smaller than those from different classes. This shows the effectiveness of the end-to-end joint training of the feature transformation network and the alignment prediction network of TAP.

SoftDTW is differentiable and can also be combined with different losses to train h. This can be achieved by replacing the TAP distance $d(h(\boldsymbol{X}^n), h(\boldsymbol{X}^{n'}); f)$ with the SoftDTW distance in Eq. (6),

---

[1]https://github.com/tobyperrett/few-shot-action-recognition

Table 1: Comparison of supervised representation learning methods.

Method	Action3D		Activity3D		SAD		ChaLearn	
	MAP	1-NN	MAP	1-NN	MAP	1-NN	MAP	1-NN
LDMLT+DTW (Mei et al., 2014)	0.643	84.98	0.366	55.00	0.595	96.50	0.213	84.37
LDMLT+OPW (Mei et al., 2014)	0.536	80.59	0.348	54.37	0.611	96.73	0.216	82.74
SWMD+DTW (Huang et al., 2016)	0.597	80.95	0.378	61.25	0.524	93.95	0.144	64.45
SWMD+OPW (Huang et al., 2016)	0.432	66.67	0.356	55.00	0.580	95.41	0.154	60.31
RVSML+DTW (Su & Wu, 2019)	0.593	82.78	0.422	62.50	0.602	96.23	0.338	**87.38**
RVSML+OPW (Su & Wu, 2019)	0.475	76.56	0.366	57.50	0.656	97.09	0.331	83.82
Binomial+DTW (Yi et al., 2014)	0.481	60.81	0.568	62.50	0.482	91.73	0.182	69.72
Binomial+DTW (Yi et al., 2014)	0.500	62.64	0.616	60.62	0.602	95.77	0.199	69.17
Lifted+DTW (Song et al., 2016)	0.440	67.40	0.484	62.50	0.464	89.64	0.130	66.85
Lifted+OPW (Song et al., 2016)	0.504	65.20	0.596	65.62	0.548	94.86	0.146	67.66
HM+DTW (Hermans et al., 2017)	0.432	57.51	0.589	65.62	0.656	92.68	0.237	67.28
HM+OPW (Hermans et al., 2017)	0.438	55.31	0.613	63.12	0.738	95.95	0.256	68.41
MS+DTW (Wang et al., 2019)	0.344	45.42	0.479	51.25	0.580	85.64	0.181	65.95
MS+OPW (Wang et al., 2019)	0.342	40.66	0.480	50.00	0.631	92.27	0.197	63.67
D-R+DTW (Su & Wu, 2020b)	0.617	79.49	0.531	61.88	0.782	97.32	0.440	81.15
D-R+OPW (Su & Wu, 2020b)	0.691	74.36	0.689	65.62	0.831	98.91	0.463	79.91
HM+SoftDTW	0.818	87.91	0.585	69.38	0.959	**99.55**	0.578	87.12
Lifted+SoftDTW	0.074	4.03	0.108	6.25	0.123	10.00	0.560	80.66
Binomial+SoftDTW	0.806	**89.74**	0.108	6.25	0.123	10.00	0.524	81.38
HM+TAP (Ours)	0.798	87.18	0.701	**74.38**	**0.961**	98.82	**0.614**	85.06
Lifted+TAP (Ours)	0.772	82.05	**0.728**	73.75	0.936	98.14	0.469	74.64
Binomial+TAP (Ours)	**0.826**	87.91	0.678	73.13	0.952	98.64	**0.614**	87.17

Eq. (7), and Eq. (9), respectively. Comparisons between TAP and SoftDTW for supervised representation learning are also presented in Tab. 1. We employ the PyTorch implementation[2] of SoftDTW. The triplet loss is relatively straightforward, since the sequence distance does not undergo a nonlinear function. SoftDTW outperforms TAP when the HM loss is used on some datasets. In the other two losses, exponential and logarithmic transformations are applied to the sequence distance, so the backpropagation through the alignment variable is more complicated. For SoftDTW, using a large α will lead to infinite initial losses, so we reduce α and β to 2 and 1, respectively. When using the lifted structure loss and binomial deviance loss to optimize the transformation network h, the results of SoftDTW are inferior to those of TAP on most datasets. In addition, it is easy to fall into a trivial solution when incorporating SoftDTW into complex losses on some datasets. This may be because that gradients backpropagated through SoftDTW cannot be automatically calculated and such manually derived backward processes with respect to complex losses may be more unstable. On all datasets, TAP outperforms all other methods by a significant margin on MAP. In cases where the accuracy of TAP is not the best, it is also comparable with the best result. These results show that TAP can be better learned with different losses, the training of TAP is easier and more consistent, and TAP has better potential to be applied to more complex tasks. In addition, TAP can be generalized to tackle non-sequential data, e.g., determining the spatial or set-to-set correspondences; while SoftDTW is more restricted to strictly order-preserving sequence data.

4.4 COMPARISON OF COMPUTATIONAL TIMES AND VISUALIZATIONS

Table 2 compares the average running times for computing the distances between one test sequence and all training sequences with different distance measures including DTW, optimal transport (OT), OPW, SoftDTW, and TAP. l indicates the average length of sequences in the corresponding dataset. The proposed OAP runs faster than OT, DTW, and OPW by at least an order of magnitude. The larger the dataset, the more significant the advantage. This is because TAP avoids complex optimizations required by other distances, only involves feedforward calculations, and can be accelerated conveniently by GPU. When both running on GPU, TAP is faster than SoftDTW. As presented in the appendix, the advantage increases as l increases.

---

[2]https://github.com/Sleepwalking/pytorch-softdtw. In Fig. 2, we use the implementation (https://github.com/mblondel/soft-dtw) for calculating the SoftDTW alignment.

Table 2: Comparison of the running time.

Dataset	Action3D	SAD	ChaLearn
l	39.64	39.81	39.72
DTW	0.9212	29.568	28.9270
OT	279.6414	794.9984	2614.677
OPW	0.8029	25.309	32.7774
SoftDTW	0.217	4.922	4.959
TAP	**0.138**	**3.009**	**3.033**

Figure 2: TAP (left) alignment and Soft-DTW (right) alignment.

Table 3: Comparison of few-shot action recognition methods.

Method	UCF101		HMDB51	
	1-shot	5-shot	1-shot	5-shot
ARN (Zhang et al., 2020)	66.3±0.99	83.1±0.70	45.5±0.96	60.6±0.86
OTAM (Cao et al., 2020)	79.9	88.9	54.5	66.1
TRX($\Omega = 1$) (Perrett et al., 2021)	79.0	95.9	52.1	**76.1**
TRX($\Omega = 2, 3$) (Perrett et al., 2021)	78.2	**96.1**	53.1	75.6
TTAN (Li et al., 2021)	80.9	93.2	**57.1**	74.0
SoftDTW	51.4±0.4	62.1±0.4	36.0±0.4	46.0+/-0.4
TAP	**83.5**±0.3	94.5±0.2	54.0±0.4	72.5±0.4

Fig.2 shows visualizations on the MSR Action3D dataset. For the test sequence of "draw tick", the nearest training sequence by TAP comes from the same class, but the one by Soft-DTW comes from another class "horizontal arm wave". Actions contain different movement cycles and similar poses. Each alignment path of Soft-DTW is strictly order-preserving, causing some meaningless alignments. The alignments of TAP show periodicity while preserving the general orders.

4.5 EVALUATION ON FEW-SHOT ACTION RECOGNITION

TAP can be used as the distance measure in metric-based few-shot action recognition as presented in Section 3.3. Comparisons with state-of-the-art few shot action recognition methods on UCF101 and HMDB51 for 5-way 1-shot and 5-way 5-shot tasks are shown in Table 3, where the results of ARN are reported in Zhang et al. (2020), the results of OTAM (Cao et al., 2020), TRX (Perrett et al., 2021), and TTAN (Li et al., 2021) are reported in (Li et al., 2021). OTAM employs a modified DTW as the distance measure. Again, SoftDTW can also be adopted as the distance measure. TAP generally outperforms OTAM and SoftDTW significantly. TRX and TTAN use the transformer to enhance the representations, which may be combined with TAP for further improvement. When only 1 support sample per class is available, TAP also achieves better results than TRX. TAP with much fewer parameters outperforms TTAN consisting of two stages on the UCF101 dataset. TAP has tighter 95% confidence intervals and is more stable than SoftDTW and ARN. These results further validate the effectiveness of our TAP model on few-shot action recognition.

5 CONCLUSION

In this paper, we present TAP, which is a learnable distance for sequences. TAP calculates the optimal alignment from the input sequences using a prediction network. We demonstrate the application of TAP in supervised representation learning for sequence data and few-shot action recognition. For supervised learning, TAP can be learned with various metric learning-based losses. Experimental results on four real-world datasets show that TAP achieves competitive performances with much faster inference speed. For few-shot learning, simply applying TAP in the metric-based strategy achieves comparable results with some state-of-the-art few-shot action recognition methods.

ETHICS STATEMENT

This paper proposes a learnable sequence distance that employs a lightweight neural network to predict the optimal alignment between two sequences and its applications in supervised learning, few-shot learning, and self-supervised learning (in the appendix) for sequence data. The proposed distance can be applied to any sequence data to speed up the inference of optimal alignment and improve the discrimination ability. Because this work presents such a general distance measure and its learning methods under different conditions, we did not see any particular foreseeable negative ethics impacts.

REPRODUCIBILITY STATEMENT

The architecture and hyper-parameters of the alignment prediction network in TAP are fixed and specified in Section 3.1. We specify all the training details on hyper-parameters and experimental settings in Section 4.2. Code will be made publicly available.

REFERENCES

Abubakar Abid and James Zou. Autowarp: learning a warping distance from unlabeled time series using sequence autoencoders. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 10568–10578, 2018.

Ghazi Al-Naymat, Sanjay Chawla, and Javid Taheri. Sparsedtw: a novel approach to speed up dynamic time warping. In *Proceedings of the Eighth Australasian Data Mining Conference-Volume 101*, pp. 117–127. Australian Computer Society, Inc., 2009.

K. Bache and M. Lichman. *UCI Machine Learning Repository*. http://archive.ics.uci.edu/ml, University of California, Irvine, School of Information and Computer Sciences, 2013.

Rami Ben-Ari, Mor Shpigel Nacson, Ophir Azulai, Udi Barzelay, and Daniel Rotman. Taen: Temporal aware embedding network for few-shot action recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2786–2794, 2021.

Mina Bishay, Georgios Zoumpourlis, and Ioannis Patras. Tarn: Temporal attentive relation network for few-shot and zero-shot action recognition. *arXiv preprint arXiv:1907.09021*, 2019.

Kaidi Cao, Jingwei Ji, Zhangjie Cao, Chien-Yi Chang, and Juan Carlos Niebles. Few-shot video classification via temporal alignment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10618–10627, 2020.

Samuel Cohen, Giulia Luise, Alexander Terenin, Brandon Amos, and Marc Deisenroth. Aligning time series on incomparable spaces. In *International Conference on Artificial Intelligence and Statistics*, pp. 1036–1044. PMLR, 2021.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In *Advances in neural information processing systems*, pp. 2292–2300, 2013.

Marco Cuturi and Mathieu Blondel. Soft-dtw: a differentiable loss function for time-series. In *International Conference on Machine Learning*, pp. 894–903, 2017.

Sergio Escalera, Jordi Gonzàlez, Xavier Baró, Miguel Reyes, Isabelle Guyon, Vassilis Athitsos, Hugo Escalante, Leonid Sigal, Antonis Argyros, Cristian Sminchisescu, et al. Chalearn multi-modal gesture recognition 2013: grand challenge and workshop summary. In *Proceedings of the 15th ACM on International conference on multimodal interaction*, pp. 365–368. ACM, 2013a.

Sergio Escalera, Jordi Gonzàlez, Xavier Baró, Miguel Reyes, Oscar Lopes, Isabelle Guyon, Vassilis Athitsos, and Hugo Escalante. Multi-modal gesture recognition challenge 2013: Dataset and results. In *Proceedings of the 15th ACM on International conference on multimodal interaction*, pp. 445–452. ACM, 2013b.

Basura Fernando, Efstratios Gavves, José Oramas M., Amir Ghodrati, and Tinne Tuytelaars. Modeling video evolution for action recognition. In *Proc. IEEE Int'l Conf. Computer Vision and Pattern Recognition*, 2015.

Darío García-García, Emilio Parrado Hernández, and Fernando Díaz-de María. A new distance measure for model-based sequence clustering. *IEEE transactions on pattern analysis and machine intelligence*, 31(7):1325–1331, 2008.

Alexander Hermans, Lucas Beyer, and Bastian Leibe. In defense of the triplet loss for person re-identification. *arXiv preprint arXiv:1703.07737*, 2017.

Gao Huang, Chuan Guo, Matt J Kusner, Yu Sun, Fei Sha, and Kilian Q Weinberger. Supervised word mover's distance. In *Advances in Neural Information Processing Systems*, pp. 4862–4870, 2016.

Soheil Kolouri, Se Rim Park, Matthew Thorpe, Dejan Slepcev, and Gustavo K Rohde. Optimal mass transport: Signal processing and machine-learning applications. *IEEE Signal Processing Magazine*, 34(4):43–59, 2017.

Hildegard Kuehne, Hueihan Jhuang, Estíbaliz Garrote, Tomaso Poggio, and Thomas Serre. Hmdb: a large video database for human motion recognition. In *2011 International conference on computer vision*, pp. 2556–2563. IEEE, 2011.

Rémi Lajugie, Damien Garreau, Francis Bach, and Sylvain Arlot. Metric learning for temporal sequence alignment. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 1817–1825, 2014.

Shuyuan Li, Huabin Liu, Rui Qian, Yuxi Li, John See, Mengjuan Fei, Xiaoyuan Yu, and Weiyao Lin. Ttan: Two-stage temporal alignment network for few-shot action recognition. *arXiv preprint arXiv:2107.04782*, 2021.

Wanqing Li, Zhengyou Zhang, and Zicheng Liu. Action recognition based on a bag of 3d points. In *IEEE Int'l Workshop on CVPR for Human Communicative Behavior Analysis*, 2010.

Suhas Lohit, Qiao Wang, and Pavan Turaga. Temporal transformer networks: Joint learning of invariant and discriminative time warping. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 12426–12435, 2019.

Jiangyuan Mei, Meizhu Liu, Hamid Reza Karimi, and Huijun Gao. Logdet divergence-based metric learning with triplet constraints and its applications. *IEEE Transactions on Image Processing*, 23 (11):4920–4931, 2014.

Toby Perrett, Alessandro Masullo, Tilo Burghardt, Majid Mirmehdi, and Dima Damen. Temporal-relational crosstransformers for few-shot action recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 475–484, 2021.

Prajit Ramachandran, Peter J Liu, and Quoc Le. Unsupervised pretraining for sequence to sequence learning. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 383–391, 2017.

Chotirat Ann Ratanamahatana and Eamonn Keogh. Making time-series classification more accurate using learned constraints. In *Proc. SIAM Int. Conf. Data Mining*, pp. 11–22. Lake Buena Vista, Florida, 2004.

H. Sakoe and S. Chiba. Dynamic Programming Algorithm Optimization for Spoken Word Recognition. *IEEE Trans. Acoustics, Speech and Signal Processing*, 26(1):43–49, 1978.

Stan Salvador and Philip Chan. Toward accurate dynamic time warping in linear time and space. *Intelligent Data Analysis*, 11(5):561–580, 2007.

Hyun Oh Song, Yu Xiang, Stefanie Jegelka, and Silvio Savarese. Deep metric learning via lifted structured feature embedding. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4004–4012, 2016.

Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. Ucf101: A dataset of 101 human actions classes from videos in the wild. *arXiv preprint arXiv:1212.0402*, 2012.

Bing Su and Gang Hua. Order-preserving optimal transport for distances between sequences. *IEEE transactions on pattern analysis and machine intelligence*, 41(12):2961–2974, 2019.

Bing Su and Ying Wu. Learning distance for sequences by learning a ground metric. In *International Conference on Machine Learning*, pp. 6015–6025, 2019.

Bing Su and Ying Wu. Learning low-dimensional temporal representations with latent alignments. *IEEE transactions on pattern analysis and machine intelligence*, 42(11):2842–2857, 2020a.

Bing Su and Ying Wu. Learning meta-distance for sequences by learning a ground metric via virtual sequence regression. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020b.

Bing Su, Xiaoqing Ding, Hao Wang, and Ying Wu. Discriminative dimensionality reduction for multi-dimensional sequences. *IEEE Trans. Pattern Anal. Mach. Intell.*, 40(1):77–91, 2018.

Bing Su, Jiahuan Zhou, and Ying Wu. Order-preserving wasserstein discriminant analysis. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 9885–9894, 2019.

Corentin Tallec and Yann Ollivier. Can recurrent neural networks warp time? In *International Conference on Learning Representation 2018*, 2018.

Shaoqing Tan and Ruoyu Yang. Learning similarity: Feature-aligning network for few-shot action recognition. In *2019 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–7. IEEE, 2019.

George Trigeorgis, Mihalis A Nicolaou, Stefanos Zafeiriou, and Bjorn W Schuller. Deep canonical time warping. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5110–5118, 2016.

George Trigeorgis, Mihalis A Nicolaou, Björn W Schuller, and Stefanos Zafeiriou. Deep canonical time warping for simultaneous alignment and representation learning of sequences. *IEEE transactions on pattern analysis and machine intelligence*, 40(5):1128–1138, 2017.

Jiang Wang and Ying Wu. Learning maximum margin temporal warping for action recognition. In *Proc. IEEE Int'l Conf. Computer Vision*, 2013.

Jiang Wang, Zicheng Liu, and Ying Wu. Mining actionlet ensemble for action recognition with depth cameras. In *Proc. IEEE Int'l Conf. Computer Vision and Pattern Recognition*, 2012.

Xun Wang, Xintong Han, Weilin Huang, Dengke Dong, and Matthew R Scott. Multi-similarity loss with general pair weighting for deep metric learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5022–5030, 2019.

Ron Shapira Weber, Matan Eyal, Nicki Skafte Detlefsen, Oren Shriki, and Oren Freifeld. Diffeomorphic temporal alignment nets. In *NeurIPS*, pp. 6570–6581, 2019.

Dong Yi, Zhen Lei, Shengcai Liao, and S. Z Li. Deep metric learning for person re-identification. In *International Conference on Pattern Recognition*, pp. 34–39, 2014.

Hongguang Zhang, Li Zhang, Xiaojuan Qi, Hongdong Li, Philip HS Torr, and Piotr Koniusz. Fewshot action recognition with permutation-invariant attention. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part V 16*, pp. 525–542. Springer, 2020.

Feng Zhou and Fernando De la Torre. Generalized canonical time warping. *IEEE transactions on pattern analysis and machine intelligence*, 38(2):279–294, 2016.

Feng Zhou and Fernando Torre. Canonical time warping for alignment of human behavior. In *Proc. Advances in Neural Information Processing Systems*, pp. 2286–2294, 2009.

A APPENDIX

A.1 SELF-SUPERVISED LOSS FOR TAP

We show that the proposed TAP distance can also be learned in a self-supervised manner with unlabeled sequence samples. We learn the prediction network of TAP by minimizing the TAP distances between sequences and their corresponding augmentations. Data of specific modalities such as images and videos can be augmented through low-level transformations, where self-supervised learning methods learn the feature embedding network by encouraging consistent features extracted from original data and their augmentations. Differently, we focus on learning the distance between sequences, where the element-wise features are already given no matter where and how the features are extracted, so low-level transformations are not applicable. To this end, we propose two augmentation methods for sequences: random blur and random merge.

Random blur. Random blur constructs a blur kernel K with a randomly selected size. The values in the kernel are also randomly selected from the range of $[0, 1]$ so that values in the kernel decrease from middle to both sides. Given a sequence $X = [x_1, \cdots, x_{L_X}] \in \mathbb{R}^{d \times L_X}$, random blur generates an augmented sequence $\tilde{X}$ by convolving X with K. The stride along the 1st dimension is set to 1. The stride along the 2nd dimension is randomly selected from $1, 2, 3$. No padding is applied. Thus, each column element $\tilde{x}_i$ of $\tilde{X}$ is the weighted average of several successive elements of X. The ground-truth alignment values between $\tilde{x}_i$ and the N_k elements are set as the values in K, while those between $\tilde{x}_i$ and all other elements of X are set to 0. In this way, we construct the ground-truth alignment matrix $\tilde{T}$ between X and $\tilde{X}$.

Random merge. For X with a length of L_X, random merge first randomly selects an integer $\tilde{L}$ from $[0.5L_X, 0.8L_X]$. X is then randomly segmented into $\tilde{L}$ parts, where each part has at least one element. For the k-th part with $\tilde{L}_k$ elements, $\tilde{L}_k$ values are randomly sampled from a standard Gaussian distribution and then normalized by softmax to form $\tilde{L}_k$ weights. The $\tilde{L}_k$ elements are averaged with the weights to form a new element $\tilde{x}_k$. The augmented sequence consists of all the generated elements for all parts sequentially: $\tilde{X} = [\tilde{x}_1, \cdots, \tilde{x}_{\tilde{L}_k}]$. The ground-truth alignment values between $\tilde{x}_k$ and the $\tilde{L}_k$ elements in the k-th part of X are set as the $\tilde{L}_k$ corresponding weights, while those between $\tilde{x}_k$ and elements in other parts are set to 0. In this way, the ground-truth alignment matrix $\tilde{T}$ between X and $\tilde{X}$ is constructed.

Self-supervised learning of TAP. Given N unlabeled training sequences $X^n, n = 1, \cdots, N$, the goal is to learn the TAP distance by learning the prediction network. For each X^n, we first randomly select one of the two methods to generate its augmented sequence $\tilde{X}^n$ and the corresponding ground-truth alignment $\tilde{T}^n$. We then calculate the TAP distance $d(X^n, \tilde{X}^n; f)$ and the corresponding non-normalized alignment A^n in Eq. (3) between X^n and $\tilde{X}^n$. Since TAP is asymmetric, we also calculate the dual TAP distance $d(\tilde{X}^n, X^n; f)$ and dual alignment A_d^n between $\tilde{X}^n$ and X^n. We minimize the TAP and its dual distances. We also minimize the Mean Squared Errors (MSEs) between the predicted dual alignments and the ground-truth alignments, which indirectly forces the alignment and the dual alignment to be consistent. The objective for a batch of B sequences is:

$$\min_f \frac{1}{B} \sum_{n=1}^{B} (d(X^n, \tilde{X}^n; f) + d(\tilde{X}^n, X^n; f) + MSE(A^n, \tilde{T}^n) + MSE(A_d^n, \tilde{T}^{nT})). \quad (12)$$

Parameters of the alignment prediction network f in TAP are learned by back-propagation. Since D is fixed with given sequences and T is obtained after softmax and L_1 normalization, the TAP distance between two sequences is bounded. Therefore, f has no trivial collapse solution, so negative sequence samples are naturally not required. Once f is learned, TAP can be applied to measure the difference between two sequences by feedforward calculations. In Section 3.2, the self-supervised loss 12 is added to all supervised losses to improve the stability of the learned TAP.

Figure 3: (a) Running times of SoftDTW and TAP as functions of the length of sequences. (b) Running times of SoftDTW and TAP as functions of the dimensionality of features in sequences.

Table 4: Results on the MSR Action3D dataset.

Distance	MAP	1-NN	5-NN	30-NN
DTW	**0.590**	81.32	**80.95**	72.53
lDTW	0.567	82.78	79.12	64.84
nDTW	0.565	79.85	76.92	67.40
OT	0.544	78.02	75.09	59.34
Sinkhorn	0.546	78.02	74.73	60.44
TCOT	0.578	80.59	79.49	67.03
OPW	0.587	**84.25**	80.22	67.03
SoftDTW	0.589	81.32	**80.95**	**72.89**
SoftDTW*	0.076	4.03	5.50	5.13
TAP	0.557	79.85	78.02	67.77

Table 5: Results on MSR Activity3D dataset.

Distance	MAP	1-NN	5-NN	30-NN
DTW	0.338	58.75	49.38	31.87
lDTW	0.288	50.00	50.00	30.00
nDTW	0.306	55.63	52.50	30.00
OT	0.308	55.63	50.62	25.00
Sinkhorn	0.307	54.37	50.62	25.62
TCOT	0.321	59.38	51.88	28.13
OPW	0.346	58.13	53.75	30.63
SoftDTW	0.339	60.00	50.00	33.75
SoftDTW*	0.108	6.25	6.25	6.25
TAP	**0.362**	**61.25**	**55.63**	**36.25**

Comparison with alignment-based distances. We compare the self-supervised learned TAP with 8 alignment-based sequence distances in the retrieval and classification tasks, including DTW, length-normalized DTW (lDTW), matching step-normalized DTW (nDTW), optimal transport (OT) (Kolouri et al., 2017), Sinkhorn (Cuturi, 2013), TCOT (Su & Hua, 2019), OPW (Su & Hua, 2019), and SoftDTW (Cuturi & Blondel, 2017). We follow the setting in (Su & Hua, 2019) and directly compare with the results reported in Su & Hua (2019). The comparisons on the MSR Action3D and MSR Activity3D datasets are shown in Table 4 and Table 5, respectively. We observe that TAP generally outperforms other distances on the MSR Activity3D dataset, but performs worse on the MSR Action3D dataset. On the small-scale MSR Action3D dataset, the training sequences may not exhibit enough variances and TAP may not be fully trained.

SoftDTW can be used as a differentiable loss on top of a single-layer embedding. SoftDTW* trains the additional linear layer in a self-supervised manner by minimizing the SoftDTW distances between the original training sequences and their augmented ones, but the effect is equivalent to random classification. Without negative sample sampling, SoftDTW* falls into the trivial solution of all zeros. In self-supervised learning, TAP naturally avoids the trivial solution since it calculates D from the original sequences and performs Softmax on T.

A.2 COMPLEXITY

The complexities for calculating D, performing convolutions with a few layers and small kernels, calculating S, and performing Softmax and L_1 normalization are $O(L_X L_Y d)$, $O(L_X L_Y d)$, $O(L_X L_Y)$, and $O(L_X L_Y)$, respectively, where the number of layers, the size of kernels, and the number of kernels are omitted since they are small. The overall complexity of TAP is $O(L_X L_Y d)$.

A.3 COMPARISON OF TAP AND SOFTDTW ON RUNNING TIMES

We study the scalability of the proposed TAP in comparison with SoftDTW as the length and dimensionality increase. We randomly generate two sequences of length L, both consists of d-dimensional features. For different L and d, we compute the SoftDTW distance and the TAP distance with random parameters between the two sequences, respectively, and compare the corresponding running times. We first fix d to 500, and increase L from 100 to 1000 with an interval of 100. The running times of SoftDTW and TAP as functions of L are compared in Fig. 3(a). The running time of SoftDTW grows rapidly as the length increases due to the dynamic programming and backtracking processes. In contrast, since only the forward matrix operations are required, the running time of TAP does not change much as the length increases. The longer the sequences, the more obvious the speed advantage of the proposed TAP.

We then fix L to 500, and increase d from 100 to 1000 with an interval of 100. The running times of SoftDTW and TAP as functions of d are compared in Fig. 3(b). We observe that the proposed TAP is consistently about 10 times faster than SoftDTW. These results demonstrate that TAP can better scale to long and high-dimensional sequences.