Learning in Congestion Games with Bandit Feedback

Abstract

Learning Nash equilibria is a central problem in multi-agent systems. In this paper, we investigate congestion games, a class of games with benign theoretical structure and broad real-world applications. We first propose a centralized algorithm based on the optimism in the face of uncertainty principle for congestion games with (semi-)bandit feedback, and obtain finite-sample guarantees. Then we propose a decentralized algorithm via a novel combination of the Frank-Wolfe method and G-optimal design. By exploiting the structure of the congestion game, we show the sample complexity of both algorithms depends only polynomially on the number of players and the number of facilities, but not the size of the action set, which can be exponentially large in terms of the number of facilities. We further define a new problem class, Markov congestion games, which allows us to model the non-stationarity in congestion games. We propose a centralized algorithm for Markov congestion games, whose sample complexity again has only polynomial dependence on all relevant problem parameters, but not the size of the action set.

1 Introduction

Nash equilibrium (NE) is a widely adopted concept in game theory community, used to describe the behavior of multi-agent systems with selfish players [Roughgarden, 2010]. At the Nash equilibrium, no player has the incentive to change its own strategy unilaterally, which implies it is a steady state of the system. For a general-sum game, computing the Nash equilibrium is PPAD-hard [Daskalakis, 2013] and the query complexity is exponential in the number of players [Rubinstein, 2016]. To help address these issues, a natural approach is to consider games with special structures. In this paper, we focus on congestion games.

Congestion games are general-sum games with *facilities* (resources) shared among players [Rosenthal, 1973]. During the game, each player will decide what combination of facilities to utilize, and popular facilities will become congested, which results in a possibly higher cost on each user. One example of congestion game is the routing game [Fotakis et al., 2002], where each player needs to travel from a given starting point to a destination point through some shared routes. These routes are represented as a traffic graph and the facilities are the edges. Each player will decide her path to go, and the more players use the same edge, the longer the edge travel time will be. Congestion games also have wide applications in electrical grids [Ibars et al., 2010], internet routing [Al-Kashoash et al., 2017] and rate allocation [Johari and Tsitsiklis, 2004]. In many real-world scenarios, players can only have (semi-)bandit feedback, i.e., players know only the payoff of the facilities they choose. This kind of learning under uncertainty has been widely studied in bandits and in reinforcement learning for the single-agent setting, while theoretical understanding for the multi-agent case is still largely missing.

There are two types of algorithms in multi-agent systems, namely centralized algorithms and decentralized algorithms. For centralized algorithms, there exists a central authority that can control and receive feedback from all players in the game. As we have global coordination, centralized algorithms usually have favorable performance. On the other hand, such a central authority may not

Table 1: Comparison of algorithms for congestion games in terms of sample complexity and Nash regret, where "IPPG" stands for "independent projected policy gradient", "IPGA" stands for "independent policy gradient ascent", "I" represents the setting of semi-bandit feedback and "II" represents the setting of bandit feedback. Bandit feedback is assumed for algorithms from previous work. Here, A_i is the size of player i's action space, m is the number of players, $A_{\max} = \max_{i \in [m]} A_i$, F is the number of facilities and T is the number of samples collected.

Algorithms	Sample complexity	Nash regret	Decentralized
Nash-VI [Liu et al., 2021]	$(\prod_{i=1}^{m} A_i)F/\epsilon^2$	$\sqrt{(\prod_{i=1}^{m} A_i)FT}$	No
V-learning [Jin et al., 2021a]	$A_{\max}F/\epsilon^2$ (CCE)	NA	Yes
IPPG [Leonardos et al., 2021]	$A_{\max}mF/\epsilon^6$	NA	Yes
IPGA [Ding et al., 2022]	$A_{\max}^2 m^3 F^5/\epsilon^5$	$mF^{4/3}\sqrt{A_{\max}}T^{4/5}$	Yes
Nash-UCB I	mF^2/ϵ^2	$F\sqrt{mT}$	No
Nash-UCB II	m^2F^3/ϵ^2	$mF^{3/2}\sqrt{T}$	No
Frank-Wolfe with Exploration I	$m^{12}F^9/\epsilon^6$	$m^2F^{3/2}T^{5/6}$	Yes
Frank-Wolfe with Exploration II	$m^{12}F^{12}/\epsilon^6$	$m^2F^2T^{5/6}$	Yes

always be available in practice, and thus people turn to decentralized algorithms, i.e., each player makes decisions individually and can only observe her own feedback. However, decentralized algorithms are vulnerable to *nonstationarity* because each player is making decisions in a nonstationary environment as others' strategies are changing [Zhang et al., 2021a]. In this paper, we will study both centralized and decentralized algorithms in congestion games with bandit feedback, and we will provide motivating scenarios for both algorithms in Section 1.2.

The main challenge in designing algorithms for m-player congestion games with bandit feedback is the curse of exponential action set, i.e., the number of actions can be exponential in the number of facilities F because every subset of facilities can be an action. As a result, an efficient algorithm should have sample complexity polynomial in m and F and has no dependence on the size of the action space. One closely related type of general-sum game is the potential game, in which each individual's payoff changes, resulting from strategy modification, can be quantified by a common potential function. It is well-known that all congestion games are potential games and each potential game has an equivalent congestion game formulation [Monderer and Shapley, 1996]. However, existing algorithms designed for potential games all have sample complexity scaling at least linearly in the number of actions [Leonardos et al., 2021, Ding et al., 2022], which is inefficient for congestion games. This motivates the following question:

Can we design provably efficient centralized and decentralized algorithms that can converge to NE in congestion games with bandit feedback?

We provide the first affirmative answer to this question. We highlight our contributions below and compare our results with previous algorithms in Table 1.

1.1 Main Novelties and Contributions

1. Centralized algorithm for congestion game. We adapt the principle of optimism in the face of uncertainty in stochastic bandits to ensure sufficient exploration in congestion games. We begin with congestion games with semi-bandit feedback, in which each player can observe the reward of every facility in the action. Instead of estimating the action reward as in stochastic multi-armed bandits, we estimate the facility rewards directly, which removes the dependence on the size of action space. Furthermore, we consider congestion games with bandit feedback, in which each player can only observe the overall reward. In this setting, we borrow ideas from linear bandits to estimate the reward function and analyze the algorithm. The algorithm is provably sample efficient in both cases.

2. Decentralized algorithm for congestion game. Our decentralized algorithm is a Frank-Wolfe method with exploration, in which each player only observes her own actions and rewards. To efficiently explore in the congestion game, we utilize the G-optimal design allocation for bandit feedback and a specific distribution for semi-bandit feedback. As a result, the sample complexity does not depend on the number of actions. In addition, the L_1 smoothness of the potential function does not depend on the number of actions, which is exploited by the Frank-Wolfe method. With the

help of these two specific algorithmic designs for congestion games, we give the first decentralized algorithm for both semi-bandit feedback and bandit feedback that has no dependence on the size of the action space in congestion games.

3. Centralized algorithm for independent Markov congestion game. We extend the formulation of congestion game into a Markov setting and propose the independent Markov congestion game (IMCG), in which each facility has its own internal state and state transition happens independently among all the facilities. In Section 1.2, we give some examples that fit in this model. By utilizing techniques from factored MDPs, we extend our centralized algorithms for congestion games to efficiently solve IMCGs, with both semi-bandit and bandit feedback.

1.2 Motivating Examples

We provide several examples here to motivate our proposed models. See Section 3 for the formal definition of (semi-)bandit feedback and (Markov) congestion games.

Example 1 (**Web Advertisements**). Consider a set of websites as the facility set and companies who want to advertise their products as the players. Due to the budget constraints, each company may only choose some of these websites to put its product ad. For each website, the probability that a user will click certain ad (and then buy the product) depends on how many ads are put on the website. If a website receives too many ads, the probability that a user can see certain ad will decrease, thus making it congested.[1] The reward each company will receive is measured by the amount of products sold during certain period of time, which is bandit feedback.

Example 2 (**Server Usage**). Consider a set of servers in a company as the facility set and server users as the players. Each user needs to request several servers to finish her computation task and the cost triggered from each server depends on the number of users requesting that server. Each user will try to minimize the total cost incurred from the servers she requested. As each user can see the cost from all the servers she requested, this is semi-bandit feedback.

Example 3 (**Routing Games**). For a routing game, there exists multiple players in a traffic graph travelling from starting points to destination points, and the facilities are the edges. The cost of each edge is the waiting time, which depends on the number of players using that edge.

• **Centralized algorithm for routing games:** Imagine each player is using Google Maps to navigate. Then Google Maps can serve as a center that knows the starting points and the destination points, as well as the real-time feedback of the waiting time on each edge of all the players. Google Maps itself also has the incentive to assign paths according to the Nash equilibrium strategy as then each player will find out that deviating from the navigation has no benefit and thus stick to the app.

• **Decentralized algorithm for routing games:** Consider the case that players are still using Google Maps but due to privacy concerns or limited bandwidth, they only use the offline version, which only have access to the information of each single user. Then Google Maps need to use decentralized algorithms so that it can still assign Nash equilibrium strategy to each user after repeated plays.

• **Markov routing games:** For Markov routing games, the time cost on each edge will change among different timesteps, which is a more accurate model of the real-world. For instance, some roads are prone to car accidents, which will result in an increasing cost on the next timestep, and the chance of accidents also depends on the number of players using that edge currently. This is modelled by the Markovian facility state transition in independent Markov congestion games.

2 Related Work

Potential Games. Potential games are general-sum games that admit a common potential function to quantify the changes in individual's payoff [Monderer and Shapley, 1996]. Algorithmic game theory community has studied how different dynamics converge to the Nash equilibrium, e.g., best response dynamic [Durand, 2018, Swenson et al., 2018] and no-regret dynamic [Heliou et al., 2017, Cheung and Piliouras, 2020], while usually they provide only asymptotic convergence, with either full information setting or bandit feedback setting. Recently, reinforcement learning community studied Markov potential games with bandit feedback, which can be applied to standard potential games. See the Markov Games part below for more details.

---

[1]Although the website's intelligent recommendation system may more or less mitigate this effect, it can be considered as a part of the reward function's property.

Congestion Games. Congestion games are developed in the nominal work [Rosenthal, 1973] and later Monderer and Shapley [1996] builds the close connection between congestion games and potential games. Congestion games are further divided into atomic congestion games and non-atomic congestion games depending on if each player is separable. Plenty of works consider non-atomic congestion games with non-decreasing cost function, which implies a convex potential function [Roughgarden and Tardos, 2004]. We consider the more difficult atomic congestion game as the potential function can be non-convex. For online non-atomic case, [Krichene et al., 2015] considers partial information setting while they provide convergence in the sense of Cesaro means. [Kleinberg et al., 2009, Krichene et al., 2014] shows that some no-regret online learning algorithm asymptotically converges to Nash equilibrium. [Chen and Lu, 2015, 2016] are two closely related works that consider bandit feedback in atomic congestion games and provide non-asymptotic convergence. However, they still assume a convex potential function and the sample complexity has exponential dependence on the number of facilities, which is far from ideal.

Markov Games. Markov games are widely studied since the seminal work [Shapley, 1953]. Recently, it received much attention due to the advances in reinforcement learning theory. Liu et al. [2021] provides a centralized algorithm for learning the Nash equilibrium in general-sum Markov games, and [Jin et al., 2021a, Song et al., 2021] provide decentralized algorithms for learning the (coarse) correlated equilibrium. One closely related line of research is about Markov potential games [Leonardos et al., 2021, Zhang et al., 2021b, Fox et al., 2021, Cen et al., 2022, Ding et al., 2022]. However, applying their algorithms to congestion games leads to explicit dependence on the number of actions, which would be exponentially worse than our algorithms. See Table 1 for comparisons. Our independent Markov congestion game is motivated by the state-based potential games studied in Marden [2012] and Macua et al. [2018], and its transition kernel is closely related to the factored MDPs, whose single agent algorithms are studied in [Osband and Van Roy, 2014, Chen et al., 2020, Xu and Tewari, 2020, Tian et al., 2020, Rosenberg and Mansour, 2021].

3 Preliminaries

3.1 Matrix Games

General-sum Matrix Games. We consider the model of general-sum matrix games, defined by the tuple $\mathcal{G} = (\{\mathcal{A}_i\}_{i=1}^m, R)$, where m is the number of players, $\mathcal{A}_i$ is the action space of player i and $R(\cdot|\boldsymbol{a})$ is the reward distribution on $[0, r_{\max}]^m$ with mean $\boldsymbol{r}(\boldsymbol{a})$. Let $\mathcal{A} = \mathcal{A}_1 \times \cdots \times \mathcal{A}_m$ be the whole action space and denote its element as $\boldsymbol{a} = (a_1, \ldots, a_m) \in \mathcal{A}$. After all these players take actions $\boldsymbol{a} \in \mathcal{A}$, a reward vector is sampled $\boldsymbol{r} \sim R(\cdot|\boldsymbol{a})$ and player i will receive reward $r_i \in [0, r_{\max}]$ with mean $r_i(\boldsymbol{a})$. Each player's objective is to maximize her own reward.

A general policy π is defined as a vector in $\Delta(\mathcal{A})$, the probability simplex over the action space $\mathcal{A}$. A product policy $\pi = (\pi_1, \ldots, \pi_m)$ is defined as a tuple in $\Delta(\mathcal{A}_1) \times \cdots \times \Delta(\mathcal{A}_m)$, in which $\boldsymbol{a} = (a_1, \ldots, a_m) \sim \pi$ represents $a_i \overset{\text{i.i.d.}}{\sim} \pi_i$. The value of policy π for player i is $V_i^\pi = \mathbb{E}_{\boldsymbol{a} \sim \pi}[r_i(\boldsymbol{a})]$.

Nash Equilibrium and Nash Regret. Given a general policy π, let π_{-i} be the marginal joint policy of players $1, \ldots, i-1, i+1, \ldots, m$. Then, the best response of player i under policy π is $\pi_i^\dagger = \arg\max_{\mu \in \Delta(\mathcal{A}_i)} V_i^{\mu, \pi_{-i}}$ and the corresponding value is $V_i^{\dagger, \pi_{-i}} := V_i^{\pi_i^\dagger, \pi_{-i}}$. Our goal is to find the approximate Nash equilibrium of the matrix game, which is defined below.

Definition 1. A product policy π is an ϵ-approximate Nash equilibrium if $\max_i(V_i^{\dagger, \pi_{-i}} - V_i^\pi) \leq \epsilon$.

An ϵ-approximate Nash equilibrium can be obtained by achieving a sublinear Nash regret, which is defined below. See Section 3 in Ding et al. [2022] for a more detailed discussion.

Definition 2. With π^k being the policy at k-th episode, the *Nash regret* after K episodes is define as

$$\text{Nash-Regret}(K) = \sum_{k=1}^K \max_{i \in [m]} \left(V_i^{\dagger, \pi_{-i}^k} - V_i^{\pi^k} \right).$$

Potential Games. A potential game is a general-sum game such that there exists a potential function $\Phi : \Delta(\mathcal{A}) \to [0, \Phi_{\max}]$ such that for any player $i \in [m]$ and policies π_i, π_i', π_{-i}, it satisfies

$$\Phi(\pi_i, \pi_{-i}) - \Phi(\pi_i', \pi_{-i}) = V_i^{\pi_i, \pi_{-i}} - V_i^{\pi_i', \pi_{-i}}.$$

168 We can immediately see that a policy that maximizes the potential function is a Nash equilibrium.

Congestion Games. A congestion game is defined by $\mathcal{G} = (\mathcal{F}, \{\mathcal{A}_i\}_{i=1}^m, \{R^f\}_{f \in \mathcal{F}})$, where $\mathcal{F} = [F]$ is called the facility set and $R^f(\cdot | n) \in [0, 1]$ is the reward distribution for facility f with mean $r^f(n)$, where $n \in [m]$.[2] Each action $a_i \in \mathcal{A}_i$ is a subset of $\mathcal{F}$ (i.e., $a_i \subseteq \mathcal{F}$). Suppose the joint action chosen by all the players is $\boldsymbol{a} \in \mathcal{A}$, then a random reward is sampled $r^f \sim R^f(\cdot | n^f(\boldsymbol{a}))$ for each facility f, where $n^f(\boldsymbol{a}) = \sum_{i=1}^m \mathbb{1}\{f \in a_i\}$ is the number of players using facility f. The reward collected by player i is $r_i = \sum_{f \in a_i} r^f$ with mean $r_i(\boldsymbol{a}) = \sum_{f \in a_i} r^f(n^f(\boldsymbol{a})) \in [0, F]$.

Connection to Potential Games [Monderer and Shapley, 1996]. As a special class of potential game, all congestion games have the potential function: $\Phi(\boldsymbol{a}) = \sum_{f \in \mathcal{F}} \sum_{i=1}^{n^f(\boldsymbol{a})} r^f(i)$. To see this, we can easily verify that $\Phi(a_i, a_{-i}) - \Phi(a_i', a_{-i}) = r_i(a_i, a_{-i}) - r_i(a_i', a_{-i})$ holds. Then, by defining $\Phi(\pi) = \mathbb{E}_{\boldsymbol{a} \sim \pi}[\Phi(\boldsymbol{a})]$, we can have $\Phi(\pi_i, \pi_{-i}) - \Phi(\pi_i', \pi_{-i}) = V_i^{\pi_i, \pi_{-i}} - V_i^{\pi_i', \pi_{-i}}$.

Types of feedback. There are in general two types of reward feedback for the congestion games, semi-bandit feedback and bandit feedback, both of which are reasonable under different scenarios. In semi-bandit feedback, after taking the action, player i will receive reward information r^f for each $f \in a_i$; in bandit feedback, after taking the action, player i will only receive the reward $r_i = \sum_{f \in a_i} r^f$ with no knowledge about each r^f. In this paper, we will address both of them, with more focus on the bandit feedback, which can be directly generalized to semi-bandit feedback.

3.2 Markov Games

General-sum Markov Games. A finite-horizon time-inhomogeneous tabular general-sum Markov game is defined by $\mathcal{M} = \{\mathcal{S}, \{\mathcal{A}_i\}_{i=1}^m, H, P, R\}$, where $\mathcal{S}$ is the state space, m is the number of players, $\mathcal{A}_i$ is the action space of player i, $\mathcal{A} = \mathcal{A}_1 \times \cdots \times \mathcal{A}_m$ is the whole action space, H is the time horizon, $P = (P_1, P_2, \cdots, P_H)$ with $P_h \in [0, 1]^{S \times \mathcal{A} \times S}$ as the transition kernel at timestep h, $R = \{R_h(\cdot | s_h, \boldsymbol{a}_h)\}_{h=1}^H$ with $R_h(\cdot | s_h, a_h)$ as the reward distribution on $[0, r_{\max}]^m$ with mean $\boldsymbol{r}_h(s_h, a_h) \in [0, r_{\max}]^m$ at timestep $h \in [H]$. At timestep h, all players choose their actions simultaneously and a reward vector is sampled $\boldsymbol{r}_h \sim R_h(\cdot | s_h, \boldsymbol{a}_h)$, where s_h is the current state and $\boldsymbol{a}_h = (a_{h,1}, a_{h,2}, \cdots, a_{h,m})$ is the joint action. Each player i receives reward $r_{h,i}$ and the state transits to $s_{h+1} \sim P_h(\cdot | s_h, \boldsymbol{a}_h)$. The objective for each player is to maximize her own total reward. We assume that the initial state s_1 is fixed, but the results can immediately be extended to the case where s_1 follows some fixed distribution.

A (Markov) policy π is a collection of H functions $\{\pi_h : \mathcal{S} \mapsto \Delta(\mathcal{A})\}$, each of which maps a state to a distribution over the action space. π is a product policy if $\pi_h(\cdot | s)$ is a product policy for each $(h, s) \in [H] \times \mathcal{S}$. The value function and Q-value function of player i at timestep h under policy π are defined as

$$V_{h,i}^{\pi}(s) = \mathbb{E}_{\pi}\left[\sum_{h'=h}^H r_{h',i}(s_{h'}, \boldsymbol{a}_{h'}) \mid s_h = s\right], \quad Q_{h,i}^{\pi}(s, \boldsymbol{a}) = \mathbb{E}_{\pi}\left[\sum_{h'=h}^H r_{h',i}(s_{h'}, \boldsymbol{a}_{h'}) \mid s_h = s, \boldsymbol{a}_h = a\right].$$

The best responses and Nash regret can be defined similarly as those for matrix games. In particular, given a policy π, player i's best response policy is $\pi_{h,i}^\dagger(\cdot | s) = \operatorname{argmax}_{\mu \in \Delta(\mathcal{A}_i)} V_{h,i}^{\mu, \pi_{-i}}(s)$ and the corresponding value function is denoted as $V_{h,i}^{\dagger, \pi_{-i}}$.

Definition 3. With π^k being the policy at kth episode, the *Nash regret* after K episodes is define as

$$\text{Nash-Regret}(K) = \sum_{k=1}^K \max_{i \in [m]} \left(V_{1,i}^{\dagger, \pi_{-i}^k} - V_{1,i}^{\pi^k}\right)(s_1).$$

In this paper, we will define and study the independent Markov congestion game, which is a natural extension of the congestion game.

Independent Markov Congestion Game. A general-sum Markov game is an independent Markov congestion game (IMCG) if there exists a facility set $\mathcal{F}$ such that $a_i \subseteq \mathcal{F}$ for any $a_i \in \mathcal{A}_i$, a state

---

[2]It is straightforward to extend our results to arbitrary reward support.

space $\mathcal{S} = \prod_{f \in \mathcal{F}} \mathcal{S}^f$, a set of facility reward distributions $\{R_h^f\}_{h \in [H], f \in \mathcal{F}}$ such that if the joint action at s_h is $\boldsymbol{a}$, we have $r_{h,i} = \sum_{f \in a_i} r_h^f$, where $r_h^f \sim R_h^f(\cdot|s_h, n^f(\boldsymbol{a}))$ with support on $[0, 1]$ and mean $r_h^f(s_h, n^f(\boldsymbol{a}))$, and a set of transition matrices $\{P_h^f\}_{h \in [H], f \in \mathcal{F}}$ such that $P_h(s'|s, \boldsymbol{a}) = \prod_{f \in \mathcal{F}} P_h^f(s'^f|s^f, n^f(\boldsymbol{a}))$. In other words, at each timestep h and state $s \in \mathcal{S}$, the players are in a congestion game. Meanwhile, each facility has its own state and independent state transition, which only depends on its current state and number of players using that facility. This transition kernel can be viewed as a special case of that in factored MDPs [Szita and Lőrincz, 2009].

The IMCG also admits two types of feedback, semi-bandit feedback and bandit feedback, just like the congestion game. In this paper, we will consider both types of feedback.

4 Centralized Algorithms for Congestion Games

In this section, we introduce two centralized algorithms for congestion games – one for the semi-bandit feedback and one for the bandit feedback. We will see that both of them can achieve sublinear Nash regret with polynomial dependence on both m and F.

4.1 Algorithm for Semi-bandit Feedback

Summarized in Algorithm 1, Nash upper confidence bound (Nash-UCB) for congestion games is developed based on optimism in the face of uncertainty. In particular, the algorithm estimates the reward matrices optimistically in line 5, computes its Nash equilibrium policy in line 6 and then follows this policy.

For convenience, we define the empirical counter $N^{k,f}(n) = \sum_{k'=1}^{k} \mathbb{1}\left\{n^f(\boldsymbol{a}^{k'}) = n\right\}$ and $\tilde{\iota} = 2\log(4(m + 1)K/\delta)$. Then, the reward estimator for f and the bonus term are defined as

$$\hat{r}^{k,f}(n) = \frac{\sum_{k'=1}^{k} r^{k',f} \mathbb{1}\left\{n^f(\boldsymbol{a}^{k'}) = n\right\}}{N^{k,f}(n) \vee 1}, \quad b_i^{k,\mathrm{r}}(\boldsymbol{a}) = \sum_{f \in a_i} \sqrt{\frac{\tilde{\iota}}{N^{k,f}(n^f(\boldsymbol{a})) \vee 1}}, \quad (1)$$

where $r^{k,f} \in [0, 1]$ is the random reward realization of $r^f(n^f(\boldsymbol{a}^k))$. Naturally, the reward estimator for player i is $\hat{r}_i^k(\boldsymbol{a}) = \sum_{f \in a_i} \hat{r}^{k,f}(n^f(\boldsymbol{a}))$.

Algorithm 1 Nash-UCB for Congestion Games

1: **Input:** ϵ, accuracy parameter for Nash equilibrium computation
2: **Initialize:** $\overline{V}_i^k = 0$ for all $(i, k) \in [m] \times [K]$
3: **for** episodes $k = 1, \ldots, K$ **do**
4:     **for** player $i = 1, \ldots, m$ **do**
5:         $\overline{Q}_i^k(\boldsymbol{a}) \leftarrow \hat{r}_i^k(\boldsymbol{a}) + b_i^{k,\mathrm{r}}(\boldsymbol{a})$ for all $\boldsymbol{a} \in \mathcal{A}$
6:         $\pi^k \leftarrow \epsilon\text{-NASH}(\overline{Q}_1^k(\cdot), \cdots, \overline{Q}_m^k(\cdot))$ (Algorithm 3)
7:         Take action $\boldsymbol{a}^k \sim \pi^k$ and observe reward $r^{k,f}$
8:         Update reward estimators $\hat{r}_i^k$ and bonus term $b_i^{k,\mathrm{r}}$

Algorithm 1 is motivated by the Nash-VI algorithm in [Liu et al., 2021] plus a deliberate utilization of the special reward structure in the congestion games. Moreover, notice that a matrix game with reward functions $\overline{Q}_1^k(\cdot), \ldots, \overline{Q}_m^k(\cdot)$ forms a potential game (see Lemma 1). As a result, in line 6, we can *efficiently compute* the ϵ-approximate Nash equilibrium π^k for that matrix game by utilizing Algorithm 3, which is given in Appendix A. In addition, Algorithm 3 guarantees that π^k is always a deterministic product policy.

4.2 Algorithm for Bandit Feedback

When the players can only receive bandit feedback, estimating $\hat{r}^{k,f}$ directly for each $f \in \mathcal{F}$ is no longer feasible. However, notice that the reward function $r_i(\boldsymbol{a}) = \sum_{f \in a_i} r^f(n^f(\boldsymbol{a}))$ can be seen as

an inner product between vectors characterized by action $\boldsymbol{a}$ and reward function $r^f(\cdot)$. Therefore, under bandit feedback, we can treat it as a linear bandit and use ridge regression to build the reward estimator $\tilde{r}_i^k$ and corresponding bonus term $\tilde{b}^{k,\mathrm{r}}$. The new algorithm will use these two terms to replace $\hat{r}_i^k$ and $b_i^{k,\mathrm{r}}$ in line 5 of Algorithm 1.[3]

In particular, define $\theta \in [0,1]^{\tilde{d}}$ with $\tilde{d} = mF$ to be the vector such that $r^f(n) = \theta_{n+m(f-1)}$. Meanwhile, for player $i \in [m]$, define $A_i : \mathcal{A} \mapsto \{0,1\}^{\tilde{d}}$ to be the vector-valued function such that

$$[A_i(\boldsymbol{a})]_j = \mathbb{1}\left\{j = n + m(f-1), f \in a_i, n = n^f(\boldsymbol{a})\right\}.$$

In other words, $A_i(\boldsymbol{a})$ is a 0-1 vector with element 1 only at indices corresponding to those in θ that represents $r^f(n)$ for $f \in a_i$ and $n = n^f(\boldsymbol{a})$. Now, with these definitions, the reward function can be written as $r_i(\boldsymbol{a}) = \langle A_i(\boldsymbol{a}), \theta \rangle$. Then, we build the reward estimator and the bonus term through ridge regression and corresponding confidence bound, which are defined as the following:

$$\tilde{r}_i^k(\boldsymbol{a}) = \left\langle A_i(\boldsymbol{a}), \widehat{\theta}^k \right\rangle, \quad \tilde{b}^{k,\mathrm{r}}(\boldsymbol{a}) = \max_{i\in[m]} \|A_i(\boldsymbol{a})\|_{(V^k)^{-1}} \sqrt{\tilde{\beta}_k}, \tag{2}$$

where $\widehat{\theta}^k = \left(V^k\right)^{-1} \sum_{k'=1}^{k-1} \sum_{i=1}^{m} A_i(\boldsymbol{a}^{k'}) r_i^{k'}$, $V^k = I + \sum_{k'=1}^{k-1} \sum_{i=1}^{m} A_i(\boldsymbol{a}^{k'}) A_i(\boldsymbol{a}^{k'})^\top$ and $\sqrt{\tilde{\beta}_k} = \sqrt{\tilde{d}} + \sqrt{\tilde{d}\log\left(1 + \frac{mkF}{\tilde{d}}\right) + \tilde{\iota}}$.[4] Note that we cannot bound the sum of this bonus terms by directly applying the elliptical potential lemma. We instead prove its variant in Lemma 4.

4.3 Regret Analysis

The Nash regret bounds for the two versions of Algorithm 1 are formally presented in Theorem 1. The proof details are deferred to Appendix C.

Theorem 1. *Let $\epsilon = 1/K$. For congestion games with semi-bandit feedback, by running Algorithm 1 with reward estimator and bonus term in (1), with probability at least $1 - \delta$, we can achieve that*

$$\textit{Nash-Regret}(K) \le \widetilde{\mathcal{O}}\left(F\sqrt{mK}\right).$$

Furthermore, if we only have bandit feedback, then by running Algorithm 1 with reward estimator and bonus term in (2), with probability at least $1 - \delta$, we can achieve that

$$\textit{Nash-Regret}(K) \le \widetilde{\mathcal{O}}\left(mF^{3/2}\sqrt{K}\right).$$

Remark 1. Since each action is a subset of $\mathcal{F}$, the size of each player's action space can be 2^F. As a result, directly applying Nash-VI in [Liu et al., 2021] leads to a regret bound exponential in F.

Remark 2. Note that we assume $r^f \in [0,1]$, which implies $r_i \in [0, F]$ for each player $i \in [m]$.

5 Decentralized Algorithms for Congestion Games

In this section, we present a decentralized algorithm for congestion games. Due to limited space, we only introduce the version of bandit feedback as in Section 4.2. The algorithmic details for the setting of semi-bandit feedback are deferred into Appendix D.3. We will show that under both settings, even though each player can only observe her own actions and rewards, our decentralized algorithm still enjoys sublinear Nash regret with polynomial dependence on m and F.

We first define the vector-valued function $\phi_i : \mathcal{A}_i \mapsto \{0,1\}^{F_i}$ to be the feature map of player i such that $[\phi_i(a_i)]_f = \mathbb{1}\{f \in a_i\}$ for $a_i \in \mathcal{A}_i$ and $f \in \bigcup_{a_i \in \mathcal{A}_i} a_i$. Here, F_i is the size of $\bigcup_{a_i \in \mathcal{A}_i} a_i \subseteq \mathcal{F}$ and we can immediately see that $F_i \le F$ for any $i \in [m]$.

The core idea of our algorithm is that the Nash equilibrium can be found by reaching the stationary points of the potential function since all congestion games are potential games. Summarized in Algorithm 2, our decentralized algorithm is developed based on the Frank-Wolfe method and has the following three major components.

---

[3]We drop the index i for $\tilde{b}^{k,\mathrm{r}}$ since it is the same for all players.

[4]The regularization parameter in ridge regression will not affect the order of the regret. Therefore, we take it to be 1 for simplicity.

Algorithm 2 Frank-Wolfe with Exploration for Congestion Game

1: **Input:** γ, ν, mixture weights; π_i^1, initial policy.
2: **Initialize:** ρ_i, the G-optimal design for player i, defined in (5).
3: **for** episodes $k = 1, \cdots, K$ **do**
4:    **for** round $t = 1, \cdots, \tau$ **do**
5:       Each player takes action $a_i^{k,t} \sim \pi_i^k$, observes reward $r_i^{k,t}$.
6:    **for** player $i = 1, \cdots, m$ **do**
7:       Compute $\widehat{\nabla}_i^k \Phi(a_i)$ by the formula in (4) for all $a_i \in \mathcal{A}_i$
8:       Compute $\widetilde{\pi}_i^{k+1} \leftarrow \text{argmax}_{\pi_i \in \Delta(\mathcal{A}_i)} \left\langle \pi_i, \widehat{\nabla}_i^k \Phi \right\rangle$
9:       Update $\pi_i^{k+1} \leftarrow (1 - \gamma)(\nu \widetilde{\pi}_i^{k+1} + (1 - \nu)\pi_i^k) + \gamma \rho_i$

Gradient Estimator. In line 7, the algorithm builds the estimator $\widehat{\nabla}_i^k \Phi$ defined in (4) by using the τ reward samples collected from line 5. Here, $\widehat{\nabla}_i^k \Phi$ estimates the gradient of potential function Φ with respect to the policy π_i^k. Recall that for a congestion game, we have $\Phi(\boldsymbol{a}) = \sum_{f \in \mathcal{F}} \sum_{i=1}^{n^f(\boldsymbol{a})} r^f(i)$ and $\Phi(\pi) = \mathbb{E}_{\boldsymbol{a} \sim \pi}[\Phi(\boldsymbol{a})]$. Then we can define $\nabla_i \Phi := \nabla_{\pi_i} \Phi$ as a vector of dimension $|\mathcal{A}_i|$. For the component indexed by some $a_i \in \mathcal{A}_i$, we can see that $\Phi(\pi) = \pi_i(a_i)\mathbb{E}_{a_{-i} \sim \pi_{-i}}[r_i(a_i, a_{-i})] + \text{const}$, where const does not depend on $\pi_i(a_i)$. Therefore, we have

$$\nabla_i \Phi(a_i) = \mathbb{E}_{a_{-i} \sim \pi_{-i}}[r_i(a_i, a_{-i})] = \mathbb{E}_{a_{-i} \sim \pi_{-i}}\left[\sum_{f \in a_i} r^f(n^f(a_i, a_{-i}))\right] = \langle \phi_i(a_i), \theta_i(\pi) \rangle, \quad (3)$$

where $[\theta_i(\pi)]_f = \mathbb{E}_{a_{-i} \sim \pi_{-i}}\left[r^f(n^f(a_{-i}) + 1)\right]$. Meanwhile, the mean of the t-th reward that player i received at episode k satisfies

$$\mathbb{E}\left[r_i^{k,t} \mid \boldsymbol{a}^{k,t}\right] = r_i(\boldsymbol{a}^{k,t}) = \sum_{f \in a_i^{k,t}} r^f(n^f(\boldsymbol{a}^{k,t})) = \left\langle \phi_i(a_i^{k,t}), \theta_i^{k,t}(a_{-i}^{k,t}) \right\rangle,$$

where $[\theta_i^{k,t}(a_{-i}^{k,t})]_f = r^f(n^f(a_{-i}^{k,t}) + 1)$ and its mean is $[\theta_i(\pi^k)]_f$. Therefore, we can use linear regression to estimate $\theta_i(\pi^k)$. In particular, we have $\widehat{\theta}_i^k(\pi^k) = \frac{1}{\tau} \sum_{t=1}^{\tau} \left(\Sigma_i^k\right)^{-1} \phi_i(a_i^{k,t})r_i^{k,t}$, with the covariance matrix $\Sigma_i^k = \mathbb{E}_{a_i \sim \pi_i^k}\left[\phi_i(a_i)\phi_i(a_i)^\top\right]$. Then, we have the unbiased gradient estimate

$$\widehat{\nabla}_i^k \Phi(a_i) = \left\langle \phi_i(a_i), \widehat{\theta}_i^k(\pi^k) \right\rangle = \frac{1}{\tau} \sum_{t=1}^{\tau} \phi_i(a_i)^\top \left(\Sigma_i^k\right)^{-1} \phi_i(a_i^{k,t})r_i^{k,t}. \quad (4)$$

G-optimal Design. In line 8 and 9, the algorithm performs standard Frank-Wolfe update and mixes the updated policy with an exploration policy ρ_i, which is defined as the G-optimal allocation for features $\{\phi_i(a_i)\}_{a_i \in \mathcal{A}_i}$. To be specific, we have

$$\rho_i = \underset{\lambda \in \Delta(\mathcal{A}_i)}{\text{argmin}} \max_{a_i \in \mathcal{A}_i} \|\phi_i(a_i)\|^2_{\mathbb{E}_{a_i' \sim \lambda}[\phi_i(a_i')\phi_i(a_i')^\top]^{-1}}. \quad (5)$$

Here ρ_i guarantees that Σ_i^k is invertible and the variance of $\widehat{\nabla}_i^k(a_i) = \left\langle \phi_i(a_i), \widehat{\theta}_i^k(\pi^k) \right\rangle$ depends only on F instead of the size of action space (Lemma 9). This is because by Kiefer-Wolfowitz theorem, we have $\max_{a_i \in \mathcal{A}_i} \|\phi_i(a_i)\|^2_{\mathbb{E}_{a_i' \sim \rho_i}[\phi_i(a_i')\phi_i(a_i')^\top]^{-1}} = F_i \leq F$ [Pukelsheim, 2006].

Frank-Wolfe Update. Finally, we emphasize that it is crucial to use Frank-Wolfe update because it is compatible with L_1 *norm* and we can show that Φ is mF-smooth with respect to the L_1 norm (Lemma 11). In contrast, its smoothness for L_2 norm will depend on the size of the action space.

Before the game starts, each player i can compute her ρ_i based on her own action set $\mathcal{A}_i$. During the game, all players only have access to their own actions and rewards, which means that Algorithm 2 is fully decentralized. The Nash regret bound for this algorithm is formally stated in Theorem 2 and the proof details are given in Appendix D.1 and D.2.

Theorem 2. *Let $T = K\tau$. For congestion game with bandit feedback, by running Algorithm 2 with gradient estimator $\widehat{\nabla}_i^k \Phi$ and exploration distribution ρ_i defined in (4), (5), with probability at least $1 - \delta$, we have*

$$\textit{Nash-Regret}(T) := \sum_{k=1}^{K} \tau \max_{i \in [m]} \left(V_i^{\dagger, \pi_{-i}^k} - V_i^{\pi^k} \right) \leq \widetilde{\mathcal{O}} \left(m^2 F^2 T^{5/6} + m^3 F^3 T^{2/3} \right).$$

For congestion game with semi-bandit feedback, by running Algorithm 2 with gradient estimator $\widetilde{\nabla}_i^k \Phi(a_i)$ and exploration distribution $\tilde{\rho}_i$ described in Appendix D.3, with probability at least $1 - \delta$, we have

$$\textit{Nash-Regret}(T) \leq \widetilde{\mathcal{O}} \left(m^2 F^{3/2} T^{5/6} + m^3 F^2 T^{2/3} \right).$$

6 Algorithms for Independent Markov Congestion Games

In this section, we present the theoretical guarantee of our centralized algorithms for independent Markov congestion games. Summarized in Algorithm 4, it is naturally extended from Nash-UCB (Algorithm 1) by incorporating transition kernel estimators, corresponding bonus terms and Bellman backward update. The key idea is to utilize the independent transition structure to remove the dependence on the exponential size of the state space $S = \prod_{f \in \mathcal{F}} S^f$. We tackle this issue by adapting technique from factored MDP [Chen et al., 2020]. Due to space constraint, the algorithmic details for both types of feedback are deferred into Appendix B. The Nash regret bounds for the two versions of Algorithm 4 are stated in Theorem 3 and the proof details are deferred to Appendix E.

Theorem 3. *For independent Markov congestion game with semi-bandit feedback, by running the centralized Algorithm 4, with probability at least $1 - \delta$, we can achieve that*

$$\textit{Nash-Regret}(K) \leq \widetilde{\mathcal{O}} \left(\sum_{f \in \mathcal{F}} F S^f \sqrt{m H^3 T} \right) + \widetilde{\mathcal{O}} \left(m^2 H^2 F \sum_{f \neq f'} \left(S^f S^{f'} \right)^2 \right).$$

Furthermore, if we only have bandit feedback, then by running Algorithm 4 with reward estimator and bonus term in (11) and (12), with probability at least $1 - \delta$, we can achieve that

$$\textit{Nash-Regret}(K) \leq \widetilde{\mathcal{O}} \left(\sum_{f \in \mathcal{F}} F S^f \sqrt{m^2 H^3 T} \right) + \widetilde{\mathcal{O}} \left(m^2 H^2 F \sum_{f \neq f'} \left(S^f S^{f'} \right)^2 \right).$$

Remark 3. The regret bound in [Liu et al., 2021] is $\widetilde{O}(\sqrt{H^3 S^2 (\Pi_{i=1}^m A_i) T})$, where both A_i and $S = \prod_{f \in \mathcal{F}} S^f$ can be exponential in F. Our bounds have polynomial dependence on all the parameters.

7 Conclusion

In this paper, we study sample-efficient learning in congestion games by utilizing the special reward structure. We propose both centralized and decentralized algorithms for congestion games with the two types of feedback, namely semi-bandit feedback and bandit feedback, all achieving sample complexities only polynomial in the number of facilities, given that the size of the action space can be exponential in it. To the best of our knowledge, each one of them is the first sample-efficient learning algorithm for congestion games in its own setting.

We further define the independent Markov congestion game (IMCG) as a natural extension of the congestion game into the Markov setting. We also propose centralized algorithms for IMCGs with both types of feedback, which achieve sample complexities only polynomial in the number of facilities.

One promising future direction is to find a sample-efficient decentralized algorithm such that from each player's own perspective, the algorithm is still no-regret. In other words, diminishing regret is guaranteed for the player by running this algorithm even though other players may use policies from different algorithms. Another important future direction is to find a sample-efficient decentralized algorithm for IMCGs.

References

Hayder AA Al-Kashoash, Maryam Hafeez, and Andrew H Kemp. Congestion control for 6lowpan networks: A game theoretic framework. *IEEE internet of things journal*, 4(3):760–771, 2017.

Yu Bai and Chi Jin. Provable self-play algorithms for competitive reinforcement learning. In *International conference on machine learning*, pages 551–560. PMLR, 2020.

Shicong Cen, Fan Chen, and Yuejie Chi. Independent natural policy gradient methods for potential games: Finite-time global convergence with entropy regularization. *arXiv preprint arXiv:2204.05466*, 2022.

Po-An Chen and Chi-Jen Lu. Playing congestion games with bandit feedbacks. In *AAMAS*, pages 1721–1722, 2015.

Po-An Chen and Chi-Jen Lu. Generalized mirror descents in congestion games. *Artificial Intelligence*, 241:217–243, 2016.

Xiaoyu Chen, Jiachen Hu, Lihong Li, and Liwei Wang. Efficient reinforcement learning in factored mdps with application to constrained rl. *arXiv preprint arXiv:2008.13319*, 2020.

Yun Kuen Cheung and Georgios Piliouras. Chaos, extremism and optimism: Volume analysis of learning in games. *Advances in Neural Information Processing Systems*, 33:9039–9049, 2020.

Constantinos Daskalakis. On the complexity of approximating a nash equilibrium. *ACM Transactions on Algorithms (TALG)*, 9(3):1–35, 2013.

Dongsheng Ding, Chen-Yu Wei, Kaiqing Zhang, and Mihailo R. Jovanović. Independent policy gradient for large-scale markov potential games: Sharper rates, function approximation, and game-agnostic convergence, 2022.

Stéphane Durand. *Analysis of Best Response Dynamics in Potential Games*. PhD thesis, Université Grenoble Alpes, 2018.

Dimitris Fotakis, Spyros Kontogiannis, Elias Koutsoupias, Marios Mavronicolas, and Paul Spirakis. The structure and complexity of nash equilibria for a selfish routing game. In *International Colloquium on Automata, Languages, and Programming*, pages 123–134. Springer, 2002.

Roy Fox, Stephen McAleer, Will Overman, and Ioannis Panageas. Independent natural policy gradient always converges in markov potential games. *arXiv preprint arXiv:2110.10614*, 2021.

Amélie Heliou, Johanne Cohen, and Panayotis Mertikopoulos. Learning with bandit feedback in potential games. *Advances in Neural Information Processing Systems*, 30, 2017.

Christian Ibars, Monica Navarro, and Lorenza Giupponi. Distributed demand management in smart grid with a congestion game. In *2010 First IEEE International Conference on Smart Grid Communications*, pages 495–500. IEEE, 2010.

Chi Jin, Qinghua Liu, Yuanhao Wang, and Tiancheng Yu. V-learning–a simple, efficient, decentralized algorithm for multiagent rl. *arXiv preprint arXiv:2110.14555*, 2021a.

Chi Jin, Qinghua Liu, Yuanhao Wang, and Tiancheng Yu. V-learning – a simple, efficient, decentralized algorithm for multiagent rl, 2021b.

Ramesh Johari and John N Tsitsiklis. Efficiency loss in a network resource allocation game. *Mathematics of Operations Research*, 29(3):407–435, 2004.

Robert Kleinberg, Georgios Piliouras, and Éva Tardos. Multiplicative updates outperform generic no-regret learning in congestion games. In *Proceedings of the forty-first annual ACM symposium on Theory of computing*, pages 533–542, 2009.

Walid Krichene, Benjamin Drighès, and Alexandre Bayen. On the convergence of no-regret learning in selfish routing. In *International Conference on Machine Learning*, pages 163–171. PMLR, 2014.

Walid Krichene, Benjamin Drighès, and Alexandre M Bayen. Online learning of nash equilibria in congestion games. *SIAM Journal on Control and Optimization*, 53(2):1056–1081, 2015.

Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

Stefanos Leonardos, Will Overman, Ioannis Panageas, and Georgios Piliouras. Global convergence of multi-agent policy gradient in markov potential games, 2021.

Qinghua Liu, Tiancheng Yu, Yu Bai, and Chi Jin. A sharp analysis of model-based reinforcement learning with self-play. In *International Conference on Machine Learning*, pages 7001–7010. PMLR, 2021.

Sergio Valcarcel Macua, Javier Zazo, and Santiago Zazo. Learning parametric closed-loop policies for markov potential games. *arXiv preprint arXiv:1802.00899*, 2018.

Jason R Marden. State based potential games. *Automatica*, 48(12):3075–3088, 2012.

Dov Monderer and Lloyd S Shapley. Potential games. *Games and economic behavior*, 14(1):124–143, 1996.

Ian Osband and Benjamin Van Roy. Near-optimal reinforcement learning in factored mdps. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K.Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014.

Friedrich Pukelsheim. *Optimal design of experiments*. SIAM, 2006.

Aviv Rosenberg and Yishay Mansour. Oracle-efficient regret minimization in factored mdps with unknown structure. *Advances in Neural Information Processing Systems*, 34, 2021.

Robert W Rosenthal. A class of games possessing pure-strategy nash equilibria. *International Journal of Game Theory*, 2(1):65–67, 1973.

Tim Roughgarden. Algorithmic game theory. *Communications of the ACM*, 53(7):78–86, 2010.

Tim Roughgarden and Éva Tardos. Bounding the inefficiency of equilibria in nonatomic congestion games. *Games and economic behavior*, 47(2):389–403, 2004.

Aviad Rubinstein. Settling the complexity of computing approximate two-player nash equilibria. In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 258–265. IEEE, 2016.

Lloyd S Shapley. Stochastic games. *Proceedings of the national academy of sciences*, 39(10): 1095–1100, 1953.

Ziang Song, Song Mei, and Yu Bai. When can we learn general-sum markov games with a large number of players sample-efficiently? *arXiv preprint arXiv:2110.04184*, 2021.

Brian Swenson, Ryan Murray, and Soummya Kar. On best-response dynamics in potential games. *SIAM Journal on Control and Optimization*, 56(4):2734–2767, 2018.

István Szita and András Lőrincz. Optimistic initialization and greediness lead to polynomial time learning in factored mdps. In *Proceedings of the 26th annual international conference on machine learning*, pages 1001–1008, 2009.

Yi Tian, Jian Qian, and Suvrit Sra. Towards minimax optimal reinforcement learning in factored markov decision processes. *Advances in Neural Information Processing Systems*, 33:19896–19907, 2020.

Ziping Xu and Ambuj Tewari. Reinforcement learning in factored mdps: Oracle-efficient algorithms and tighter regret bounds for the non-episodic setting. *Advances in Neural Information Processing Systems*, 33:18226–18236, 2020.

Kaiqing Zhang, Zhuoran Yang, and Tamer Basar. Multi-agent reinforcement learning: A selective overview of theories and algorithms. *Handbook of Reinforcement Learning and Control*, pages 321–384, 2021a.

Runyu Zhang, Zhaolin Ren, and Na Li. Gradient play in stochastic games: stationary points, convergence, and sample complexity. *arXiv preprint arXiv:2106.00198*, 2021b.