Scaling Up Multi-Task
Robotic Reinforcement Learning

Abstract: General-purpose robotic systems must master a large repertoire of diverse skills. While reinforcement learning provides a powerful framework for acquiring individual behaviors, the time needed to acquire each skill makes the prospect of a generalist robot trained with RL daunting. We study how a large-scale collective robotic learning system can acquire a repertoire of behaviors simultaneously, sharing exploration, experience, and representations across tasks. In this framework, new tasks can be continuously instantiated from previously learned tasks improving overall performance and capabilities of the system. To this end, we develop a scalable and intuitive framework for specifying new tasks through user-provided examples of desired outcomes, devise a multi-robot collective learning system for data collection that simultaneously collects experience for multiple tasks, and develop a scalable and generalizable multi-task deep reinforcement learning method, which we call MT-Opt. We demonstrate how MT-Opt can learn a wide range of skills, including semantic picking (i.e., picking an object from a particular category), placing into various fixtures (e.g., placing a food item onto a plate). We train and evaluate our system on a set of 12 real-world tasks with data collected from 7 robots, and demonstrate the performance of our system both in terms of its ability to generalize to structurally similar new tasks, and acquire distinct new tasks more quickly by leveraging past experience. We recommend viewing the videos at `https://mt-opt.github.io/`

Keywords: Multi-Task Reinforcement Learning, Robot Learning

1 Introduction

Today's deep reinforcement learning (RL) methods, when applied to real-world robotic tasks, provide an effective but expensive way of learning skills [1, 2]. While existing methods are effective and able to generalize, they require considerable on-robot training time. For example, the QT-Opt [1] system can learn vision-based robotic grasping, but it requires over $500,000$ trials collected across multiple robots. While such sample complexity may be reasonable if the robot needs to perform a single task, it becomes costly if we consider the prospect of training a general-purpose robot with a large repertoire of behaviors, where each behavior is learned in isolation, starting from scratch. Can we instead *amortize* the cost of learning this repertoire over multiple skills, where the effort needed to learn whole repertoire is reduced compared to learning each skill in isolation?

Prior work suggests that multi-task RL can amortize the cost of single-task learning [3, 4, 5, 6, 7]. Insofar as the tasks share common structure, if that structure is discovered by the learning algorithm, all of the tasks can in principle be learned more efficiently than learning each task individually. In addition, by collecting experience simultaneously using controllers for a variety of tasks with different difficulty, the easier tasks can "bootstrap" the harder tasks. Finally, by enabling the multi-task RL policy to learn shared representations, learning new tasks can become easier over time as the system acquires more skills and learns more widely-useful aspects of the environment.

However, to realize these benefits for a real-world robotic learning system, we need to overcome a number of major challenges [8, 9, 10, 11], which have so far made it difficult to produce a large-scale demonstration of multi-task image-based RL in the real world. First, multi-task reinforcement

learning is known to be exceedingly difficult from the optimization standpoint [8, 12]. Second, a real-world multi-task learning framework requires the ability to easily and intuitively define rewards for a large number of tasks. Third, while all task-specific data could be shared between all the tasks, it has been shown that reusing data from non-correlated tasks can be harmful to the learning process [13]. Lastly, to receive the benefits from shared, multi-task representation, we need to significantly scale up our algorithms, the number of tasks, and the robotic systems themselves.

The main contribution of this paper is a general multi-task learning system, which we call MT-Opt. MT-Opt realizes the hypothesized benefits of multi-task RL in a scalable real-world robotic learning system, addressing the associated challenges through a number of important design decisions, including a carefully designed multi-task data sharing strategy and multi-robot parallelized data collection. We train MT-Opt on a set of 12 real-world tasks that include data collected over the course of over 1.5 years, and provide an extensive evaluation (spanning over 500 real-robot-hours) of our method together with a number of baselines. We show that at such scale, our system can quickly acquire new tasks by taking advantage of prior tasks via shared representations, new data-sharing strategies and learned policies. Our results indicate that, by learning multiple related tasks simultaneously, not only can we increase the data-efficiency of learning each of them, but also solve more complex tasks than in a single-task setup. We present our multi-task system as well as examples of some of the tasks that it is capable of performing in Fig. 1.

Figure 1: A) Data collection. B) Training objects. C) Sample of training tasks. D) Sample of behaviorally and visually distinct tasks such as covering, chasing, alignment, which we show our method can adapt to. MT-Opt learns new tasks faster (potentially zero-shot if there is sufficient overlap with existing tasks), and with less data compared to learning the new task in isolation.

2 Related Work

Multi-task learning, inspired by the ability of humans to transfer knowledge between different tasks [14], is a promising approach for sharing structure and data between tasks to improve overall efficiency. Multi-task architectures have been successful across multiple domains; natural language processing [15, 16, 17, 18] and computer vision [19, 20, 21, 22, 23, 24]. In this work, we apply multi-task learning concept in a RL setting to real robotic tasks.

Combining multiple task policies has been explored in RL by using gating networks [25, 26], conditioning policies on tasks [27], mapping tasks to parameters of a policy [28, 29, 30], distilling separate task policies into a shared multi-task policy [31, 32, 33, 34, 35, 36]. Advantages of multi-task learning for visual representations has been explored in [37]. Pinto and Gupta [4] use a shared multi-task neural network architecture, which is trained with separate task-specific losses. In contrast, in our work, we concentrate on tasks with a common loss structure within a Q-learning framework. Several works explore how to mitigate multi-task interference and conflicting objectives [38, 39]. In our experiments, we find that better data routing helps with not only better mitigating conflicting objectives but also improving learning efficiency through data reuse.

Learning complex skills has been addressed through hierarchical reinforcement learning with options [40, 41, 42], combining multiple sub-tasks [43, 44, 45, 46, 47, 48], reusing samples between tasks [49], relabeling experience in hindsight [50], introducing demonstrations [51, 52, 53, 54, 55, 56, 57]. A range of works employ autonomous supervision to learn diverse skills, e.g. by scaling up data collection [58], sampling suitable tasks [59] or goals [60] to practice, learning a task embedding space amenable to sampling [7], or learning a dynamics model and using model-predictive control to achieve goals [61, 62, 63, 64]. Riedmiller et al. [5] learn sparse-reward tasks by solving easier auxiliary tasks and reusing that experience for offline learning of more complex tasks. In Cabi et al. [65], previously collected experience is relabeled with new reward functions in order to solve new tasks without re-collecting the data. In our work, we similarly design techniques for reusing experience between related tasks and apply them to large-scale data collection on real robots.

3 MT-Opt: a Scalable Multi-Task RL System

Fig. 2 overviews our multi-task learning system. We devise a distributed, off-policy multi-task RL algorithm together with a multi-task visual success detector (SD) to learn multiple robotic manipulation tasks simultaneously. The SD, trained from video examples of desired outcomes, (Fig. 2A) in part determines how episodes are leveraged to train an RL policy (Fig. 2C). During evaluation and fine-tuning (Fig. 2B), at each time step, a policy takes as input a camera image and a one-hot encoding of the task, and sends a motor command to the robot. At episode end, the outcome image of this process is graded by the SD that determines which tasks were accomplished successfully and assigns a sparse reward 0 or 1 for each task. The system then decides whether another task should be attempted or if the environment should be reset. We train this system with multiple robots, where each robot concurrently collects data for a different, randomly selected task. The generated episodes are used as offline data for training future policies (Fig. 2C) and are available to improve SDs.

Figure 2: MT-Opt overview. A) The user defines a success detector (SD) for tasks through examples of desired outcomes, and relabeling outcomes of prior episodes. B) Utilizing the SD and the MT-Opt policy, new episodes are collected for multiple tasks. C) Offline episodes enter the data-sharing pipeline that expands and re-balances the data used to train the MT-Opt policy, while optionally more on-policy data is collected, esp. for new tasks. This is an iterative process, which results in additional experiences that can be leveraged to define new tasks and train future policies.

In order to enable our system to take full advantage of multi-task training, we develop a number of components and evaluate their importance for overall performance. First, we use a single, multi-task deep neural network to learn a policy for all the tasks simultaneously, which enables parameter sharing between tasks. Second, we devise data management strategies that share and re-balance data across certain tasks. Third, since all tasks share data and parameters, we use some tasks as exploration policies for others, which aids in exploration. Although the individual components are based on previously studied concepts in multi-task learning, we show through our experiments that the particular choice and design of these components is essential for our large-scale multi-task learning system to effectively leverage data from all tasks to improve performance, particularly for "underrepresented" tasks that have the least available training data.

3.1 Multi-Task Reinforcement Learning Algorithm

We denote the multi-task RL policy as $\pi(\mathbf{a}|\mathbf{s}, \mathcal{T}_i)$, where $\mathbf{a} \in \mathcal{A}$ denotes the action, which in our case is the desired change in end-effector position, a change in yaw angle, binary gripper open and close commands and a termination command, $\mathbf{s} \in \mathcal{S}$ denotes the state, which corresponds to images from the robot's cameras, and $\mathcal{T}_i$ denotes an encoding of the i^{th} task drawn from a categorical task distribution $\mathcal{T}_i \sim p(\mathcal{T})$, with n possible categories, each corresponding to a different task. At each time step, the policy selects an action $\mathbf{a}$ given the current state $\mathbf{s}$ and the current task $\mathcal{T}_i$ set at the beginning of the episode, and receives a task-dependent reward $r_i(\mathbf{a}, \mathbf{s}, \mathcal{T}_i)$. The goal of the multi-task RL policy is to maximize the expected sum of rewards for all tasks drawn from the distribution $p(\mathcal{T})$. The episode finishes when the policy selects a TERMINATE action or reaches a step limit.

We build on the single-task QT-Opt algorithm [1], which itself is a variant of Q-learning [66], and learns a single-task optimal Q-Function by minimizing the Bellman error: $\mathcal{L}_i(\theta) = \mathbb{E}_{(\mathbf{s}, \mathbf{a}, \mathbf{s}') \sim p(\mathbf{s}, \mathbf{a}, \mathbf{s}')} \big[D(Q_\theta(\mathbf{s}, \mathbf{a}), Q_T(\mathbf{s}, \mathbf{a}, \mathbf{s}')) \big]$, where $Q_T(\mathbf{s}, \mathbf{a}, \mathbf{s}') = r(\mathbf{s}, \mathbf{a}) + \gamma V(\mathbf{s}')$ is a target Q-value and D is a divergence metric, such as cross-entropy, γ is a discount factor, $V(\mathbf{s}')$ is the target value function of the next state computed using stochastic optimization of the form $V(\mathbf{s}') = \max_{\mathbf{a}'} Q(\mathbf{s}', \mathbf{a}')$, and the expectation is taken w.r.t. previously seen transitions $p(\mathbf{s}, \mathbf{a}, \mathbf{s}')$. Similarly to [1], we use the cross-entropy method (CEM) to perform the stochastic optimization to compute the target value function.

To extend this approach to the multi-task setting, let $\mathbf{s}^{(i)}, \mathbf{a}^{(i)}, \mathbf{s}'^{(i)}$ denote a transition that was generated by an episode $e^{(i)}$ for the i^{th} task $\mathcal{T}_i$. Each transition could be used for multiple tasks. In the multi-task case, the loss becomes (with $(\mathbf{s}^{(i)}, \mathbf{a}^{(i)}, \mathbf{s}'^{(i)})$ being transitions generated by tasks $\mathcal{T}_i$):

$$\mathcal{L}_{\text{multi}}(\theta) = \mathbb{E}_{\mathcal{T}_i \sim p(\mathcal{T})} \left[\mathcal{L}_i(\theta) \right] = \mathbb{E}_{\mathcal{T}_i \sim p(\mathcal{T})} \Big[\tag{1}$$
$$\mathbb{E}_{p(\mathbf{s}^{(i)}, \mathbf{a}^{(i)}, \mathbf{s}'^{(i)})} \Big[D(Q_\theta(\mathbf{s}^{(i)}, \mathbf{a}^{(i)}, \mathcal{T}_i), Q_T(\mathbf{s}^{(i)}, \mathbf{a}^{(i)}, \mathbf{s}'^{(i)}, \mathcal{T}_i)) \Big] \Big].$$

3.2 Sharing Data Between Tasks

One advantage of an off-policy RL algorithm is that collected experience can be used to update the policy for other tasks, not just the task for which it was originally collected. This section describes how we effectively train with multi-task data through *task impersonation* and *data re-balancing*, as summarized in Fig. 3.

We leverage experience sharing at the episode level rather than the individual transition level. The goal is to use all transitions of an episode $e^{(i)}$ generated by task $\mathcal{T}_i$ to aid in training a policy for a *set of k_i tasks* $\mathcal{T}_{\{k_i\}}$. We refer to this process as *task impersonation* (see Algorithm 1), where the impersonation function f_I transforms episode data collected for one task into a set of episodes that can be used to also train other tasks, i.e.: $e^{\{k_i\}} = f_I(e^{(i)})$. Note that in general case $\{k_i\}$ is a *subset* of all tasks $\{n\}$, and it depends on the original task $\mathcal{T}_i$ that the episode $e^{(i)}$ was collected for.

We consider two ends of the data-sharing spectrum: an identity impersonation function $f_{I_{\text{orig}}}(e^{(i)}) = e^{(i)}$, where no task impersonation takes place, i.e. an episode $e^{(i)}$ generated by task

Figure 3: Task impersonation: episodes are routed to train relevant tasks, and data re-balancing where the ratio of success (S) and failure (F) episodes and proportion of data per task is controlled. Pale blue and pale red show additional training data coming from other tasks. The bar height indicates different amount of data across tasks and successful outcomes.

Algorithm 1 Task Impersonation

procedure $f_I(e^i : \text{original\_episode})$
    expanded_episodes = []
    $SD\{k_i\} \leftarrow$ set of SDs relevant to task T_i
    for SD_k in $SD\{k_i\}$ **do**
        // e^k: e^i but rewards for task T_k not T_i
        $e^k = SD_k(e^i)$
        expanded_episodes.append(e^k)
    return expanded_episodes

$\mathcal{T}_i$ is used to train the policy only for that task; and $f_{I_{\text{all}}} = e^{\{n\}}$, where each task shares data with *all* $n-1$ tasks (maximal data sharing). While $f_{I_{\text{orig}}}$ fails to leverage the reusable nature of multi-task data, $f_{I_{\text{all}}}$ results in many unrelated episodes used as negative examples for the target task.

For MT-Opt, we devise a new task impersonation strategy $f_{I_{\text{skill}}}$ that uses more fine-grained similarities between tasks. We refer to it as a skill-based task-impersonation strategy, where we overload the term "skill" as a set of tasks that share semantics and dynamics, yet can start from different initial conditions or operate on different objects. In this work we manually assign each task to a particular skill based on the subjective similarity of the required manipulation primitive. For example, tasks such as *place-object-on-plate* and *place-object-in-bowl* belong to the same skill. Our impersonation function $f_{I_{\text{skill}}}$ allows us to impersonate an episode $e^{(i)}$ only as the tasks belonging to the same skill as $\mathcal{T}_i$. Namely, given an episode e_i generated by task $\mathcal{T}_i$, a skill S_j that task belongs to is detected. The e_i will be impersonated only for the tasks $\mathcal{T}_{\{S_j\}}$ belonging to that particular skill. In order to avoid impersonating too many episodes and overloading the replay buffer, we introduce a stochastic impersonation function. An impersonated episode candidate will be routed to training with the probability p_s if it's a success, or with probability p_f if it's a failure. We provide more details on the specific parameters in the Appendix 7.3. In our experiments, we conduct ablation studies comparing $f_{I_{\text{skill}}}$ (ours) with other task impersonation strategies.

While training, due to the design of our task impersonation mechanism, as well as the variability in difficulty between tasks, the resulting training data stream often becomes highly imbalanced, see Fig. 3B. To address this, we re-balance each batch both between tasks, such that the relative proportion of training data for each task is equal, and within each task, such that the relative proportion of successful and unsuccessful examples is kept constant.

Figure 5: 12 evaluation tasks, giving rise to Object Acquisition and Object Manipulation skills.

4 SD-Based Rewards and Continuous Data Collection

We learn tasks evaluated on the final state of an episode. This sparse-reward assumption allows us to train a multi-view multi-task CNN success detector model (SD), conditioned on task ID, which given 3 final images from 3 different camera angles, infers task success (see Appendix 7.1 for details).

To generate training data for the SD, we ask users to collect positive and negative examples of positive and negative outcomes of a task. These examples are not demonstrations – just examples of what successful completion (i.e., the final state) looks like. We use this data to train the initial version of the multi-task SD, which we then continuously fine-tune given the images gathered during autonomous data collection to avoid out of distribution images that might be caused by various real-world factors such as different lighting conditions, and novel states which the robot discovers. We continue to manually label such images and incrementally retrain SD to obtain the most up-to-date SD. In result, we label $\approx 5,000$ images per task and provide more details in the Appendix 8.

Our main observation w.r.t. the multi-task data collection is the use of easier tasks to bootstrap learning of more complex tasks. In particular, an average MT-Opt policy for simple tasks might occasionally yield episodes successful for harder tasks. Over time, this allows us to start training an MT-Opt policy now for the harder tasks, and consequently, to collect better data for those tasks. To kick-start this process and bootstrap our two simplest tasks, we use two crude scripted policies for picking and placing (see Sec. 7.2 for details) following prior work [1]. To simplify exploration for longer-horizon tasks, we allow the individual tasks to be ordered sequentially, where one task is executed after another using simple heuristics such as executing placing tasks after lifting tasks. Our dataset grows over time w.r.t. the amount of per-task data as well as percentage of successful episodes for all the tasks. All data from a variety of different policies is accumulated over time: different versions of trained policies, their epsilon-greedy counterparts ($\epsilon = 20\%$), and scripted policies. Importantly, this data collection process results in an imbalanced dataset, as shown on Fig. 4. Our data impersonation and re-balancing methods address this imbalance by efficiently expanding and normalizing data.

Figure 4: Offline dataset properties. Our data collection strategy collects data for multiple tasks, where it uses easier, more general tasks (e.g. *lift-any*) to bootstrap learning of more specialized tasks (e.g. *lift-carrot*). The resulting dataset is imbalanced across the distribution of exploration policies per task and success rate per task.

5 Experiments

The goal of our real-world experiments is to answer the following questions: **(1)** How does MT-Opt perform, quantitatively and qualitatively, on a large set of vision-based robotic manipulation tasks? **(2)** Does training a shared model on many tasks improve MT-Opt's performance? **(3)** Does data sharing improve performance of the system? **(4)** Can we use easier tasks to bootstrap learning of more difficult tasks? **(5)** Can MT-Opt quickly learn distinct new tasks by adapting learned skills?

5.1 Experimental Setup

MT-Opt provides a general robotic skill learning framework that we use to learn multiple tasks, including semantic picking (i.e., picking an object from a particular category), placing into various

fixtures (e.g., placing a food item onto a plate). We focus on basic manipulation tasks that require repositioning objects relative to each other. A wide range of manipulation behaviors fall into this category, from simple bin-picking to more complex behaviors, such as covering items with a cloth. As described in Sec. 4, our task set grows over time allowing for more and more tasks to be similar. To analyze and ablate various properties of MT-Opt, we focus on a set of different but similar tasks, where multi-task learning shows maximal effectiveness. In the following experiments, we use a set of 12 tasks for quantitative evaluation of our algorithm. These 12 tasks include a set of plastic food objects and divided plate fixtures and they can be split into "object acquisition" and "object manipulation" skills. Since the criteria of what constitutes a task are not well defined, in our system, different tasks correspond to different success conditions as defined by our SD. Our most general object acquisition task is *lift-any*, where the goal is to singulate and lift any object. We also define 7 semantic lifting tasks, where the goal is to search for and lift a particular object (ex: carrot). Importantly, these semantic tasks require search in clutter and singulation before the actual picking can be performed. The placing tasks utilize a divided plate where the simplest task is to place the previously lifted object anywhere on the plate (*place-any*). Harder tasks require placing the object into a particular section of a divided plate, oriented arbitrarily. Fig. 5 visualizes the tasks.

All polices are trained with offline RL from a large dataset summarized in Fig. 4. The resulting policy is deployed on 7 robots attempting each task 100 times for evaluation. To reduce the variance of the evaluation, we shuffle the bins after each episode and use a standard evaluation scene (see Appendix, Fig. 17), where all of objects are present, hence all 12 evaluation tasks are feasible.

5.2 Quantitative and Qualitative Evaluation of MT-Opt

Fig. 6 shows MT-Opt success rates on the 12 evaluation tasks. We compare to three baselines: (i) single-task QT-Opt [1], where each per-task policy is trained separately using only data collected specifically for that task, (ii) an enhanced QT-Opt baseline, which we call QT-Opt Multi-Task, where we train a shared policy for all the tasks but there is no data impersonation or re-balancing between the tasks, and (iii) a Data-Sharing Multi-Task baseline that is based on the data-sharing strategy presented in [65], where we also train a single Q-Function but the data is shared across all tasks. From the average performance across all task, we observe that MT-Opt outperforms the baselines, in some cases with $\approx 3\times$ average improvement. While the single task QT-Opt baseline performs similarly to MT-Opt for the task where we have the most data (see data statistics in Fig. 4), *lift-any*, its performance drastically drops (to $\approx 1\%$) for underrepresented tasks, such as *lift-can*. Note, that we are not able run this baseline for the placing tasks, since they require a separate task to lift the object, which is not present in the single-task baseline. A similar observation applies to QT-Opt Multi-Task, where the performance of rare tasks increases compared to QT-Opt, but is still $\approx 4\times$ worse on average than MT-Opt. Sharing data across all tasks also results in a low performance for semantic lifting and placing tasks and, additionally, it appears to harm the performance of the indiscriminate lifting and placing tasks. The MT-Opt policy, besides attaining the 89% success rate on (*lift-any*), also performs the 7 semantic lifting tasks and the 4 placing and rearrangement tasks at a significantly higher success rate than all baselines. Since all ablated experiments are trained on the same exact offline dataset (except for the case where the multiple policies are trained on the per-task shard of the dataset) and have the same computation budget, we explain these performance gaps by the way MT-Opt shares the representations and data, and provide a more comprehensive analysis of these factors in the following experiments. To highlight learned behaviors, Fig. 7 shows the policy work the carrot out of the corner before picking it up.

Fig. 4, shows amounts and type of data collected for various tasks. Tasks such as *lift-carrot* and *lift-bottle*, which have more data, especially on-policy data, have higher success rates than underrepresented tasks, such as *lift-box*. The performance of these underrepresented tasks could be further improved by focusing the data collection on these tasks.

Parameter Sharing (Success Rate)		
Model:	2-Task	12-Task
lift-any	0.82	**0.89**
place-any	0.63	**0.85**

Table 1: Parameter sharing: the policy that learns two tasks (*lift-any*, *place any*) in addition to 10 other tasks outperforms a policy trained only for the two target tasks. Both policies are trained on the same offline dataset.

5.3 Sharing Representations Between Tasks

To explore the benefits of training a single policy on multiple tasks, we compare the 12-task MT-Opt policy with a 2-task policy that learns *lift-any* and *place-any*. Both of these policies are evaluated on (*lift-any* and *place-any*). We use the same $f_{I_{\text{skill}}}$ task impersonation strategy, and the same offline dataset (i.e. both policies use the data from the extra 10

narrower tasks, which is impersonated as *lift-any* and *place-any* data) without on-policy fine-tuning, so data-wise the experiments are identical.

The 12-task policy outperforms the 2-task policy *even on the two tasks that the 2-task policy is trained on* (Table 1), suggesting that training multiple tasks not only enables the 12-task policy to perform more tasks, but also improves its performance on the tasks through sharing representations. This may suggest that the additional supervision provided by training on more tasks has a beneficial effect on the shared representations.

5.4 Data Sharing Between Tasks

To test the influence of data-sharing and re-balancing on the multi-task policy's performance, we compare our task impersonation strategy $f_{I_{\text{skill}}}$ introduced in Sec. 3.2 to a baseline impersonation function that does not share the data between the tasks $f_{I_{\text{orig}}}$, and a baseline where each task is impersonated for all other tasks $f_{I_{\text{all}}}$. In our skill-based task impersonation strategy $f_{I_{\text{skill}}}$, the data is expanded only for the class of tasks having similar visuals, dynamics and goals. We also test data re-balancing strategy, where we re-balance each training batch between the tasks as well as within each task to keep the relative proportion of successful and unsuccessful trials the same.

The results of this experiment are in Table 2, with the full results reported in the Appendix, Table 4. Sharing data among tasks using our method of task impersonation and re-balancing provides significant improvement across all the tasks, with improvements of up to $10x$ for some tasks. The full data-sharing strategy performs worse than both the no-data-sharing baseline and our method, suggesting that

Data Strategies (min, mean, max, mean of low data tasks)		
Imp.	Data Re-Balancing Strategy	
Fn	uniform sampling	task re-balanced sampling
$f_{I_{\text{orig}}}$	0.10 / 0.32 / 0.94 / 0.18	0.16 / 0.55 / 0.85 / 0.42
$f_{I_{\text{all}}}$	0.07 / 0.21 / 0.62 / 0.13	0.02 / 0.35 / **0.95** / 0.21
$f_{I_{\text{skill}}}$	0.17 / 0.46 / 0.88 / 0.32	**0.29** / **0.58** / 0.89 / **0.50** Ours

Table 2: Min, average and max task performance across 12 tasks, as well as average performance across 6 tasks having least data ($\approx 6K$ episodes) for different data-sharing strategies. $f_{I_{\text{skill}}}$ impersonation and data re-balancing are complimentary: they both improve over the baselines, while the best effect is achieved by combining both. The effect is especially pronounced for the underrepresented tasks.

naïvely sharing all data across all tasks is not effective. Because of our data-collection strategy, the resulting multi-task dataset contains much more data for broader tasks (e.g., *lift-any*) than for more narrow, harder tasks (e.g., *lift-box*), as shown in Fig. 4. Without any additional data-sharing and re-balancing, this data imbalance causes the baseline strategy $f_{I_{\text{orig}}}$ to attain good performance for the easier, overrepresented tasks, but poor performance on the harder, underrepresented tasks (see Table 2, first row), whereas our method performs substantially better on these tasks.

5.5 Using Easier Tasks to Bootstrap Harder Tasks

To explore question (4), we study whether learning an easier, broader task (*lift-any*) helps with a structurally related task that is harder, more specific (*lift-sausage*). We separate out data for *lift-sausage* which consists of 5400 (nearest hundred) episodes collected for that task (i.e. 4600 failures and 800 successes). In addition, there are 11200 episodes of successful sausage lifting and as many as $740K$ failures that were collected during the *lift-any* task. Combining the *lift-sausage* data and the extra successes from *lift-any* yields 16600 episodes (12000 successes and 4600 failures). To investigate the influence of MT-Opt and task impersonation on the bootstrap problem, we compare our 12-task MT-Opt policy to a single-task policy trained on these 16600 episodes, including the same set of successful *lift-sausage* episodes as MT-Opt, but not including failures from other tasks.

The single-task policy learned from the 16600 episodes yields performance of 3%. MT-Opt, using impersonated successes and failures, achieves 39% success for the same task, a $\approx 10\times$ improvement. Both experiments use identical data representing successful episodes. The benefits of MT-Opt are twofold. First, we leverage an easier *lift-any* task to collect data for the harder *lift-sausage* task. Second, MT-Opt benefits from the additional failures impersonated from other tasks. These failures, which often include successful grasps of non-target objects, when re-balanced as described in Sec. 3.2, results in the significant task performance boost. This demonstrates the value of both successful and unsuccessful data collected by other tasks for learning new tasks.

5.6 Learning New Tasks with MT-Opt

In addition to retroactive relabelling of prior data, MT-Opt can learn new tasks via *proactive* adaptation of known tasks, even ones that are visually and behaviorally different than the initial training

To demonstrate this, we perform a fine-tuning experiment, bootstrapping from the MT-Opt 12-task policy (Sec. 5.2). We use the MT-Opt policy to collect data for unseen tasks: *lift-cloth* and *cover-object* (Fig. 7 bottom row). Unlike *lift-sausage*, prior to starting collection of these new tasks, no episodes in our offline dataset can be relabeled as successes for these tasks.

We follow the continuous data collection process (Sec. 4): we define and train the success detector for the new tasks, collect initial data using our *lift-any* and a *place-any* policies, and fine-tune a 14-task MT-Opt model that includes all prior as well as the newly defined tasks. While the new tasks are visually and semantically different, in practice the above mentioned policies give reasonable success rate necessary to start the fine-tuning. We switch to running the new policies on the robots once they are at parity with the *lift-any* and *place-any* policies. After $11K$ *pick-cloth* attempts and $3K$ *cover-object* attempts (requiring < 1 day of data collection on 7 robots), we obtain an extended 14-task MT policy that performs cloth picking at 70% success and object covering at 44% success. The policy trained only for these two tasks, without support of our offline dataset, yields performance of 33% and 5% respectively, confirming the hypothesis that MT-Opt method is beneficial even if the target tasks are sufficiently different, and the target data is scarce. By collecting additional $10K$ *pick-cloth* episodes and $6K$ *cover-object* episodes, we further increase the performance of 14-task MT-Opt to 92% and 79%, for cloth picking and object covering respectively. We perform this fine-tuning procedure with other novel tasks such as previously unseen transparent bottle grasping, which reaches a performance of 60% after 4 days of collection.

Figure 6: Quantitative evaluation of MT-Opt across 12 tasks. QT-Opt [1] trains each task individually using only data collected for that task. QT-Opt Multi-Task [1] trains a single network for all tasks but does not share the data between them. Data-Sharing Multi-Task also trains a single network for all tasks and shares the data across all tasks without further re-balancing. MT-Opt (ours) provides a significant improvement over the baselines, especially for the harder tasks with less data.

Figure 7: Top: Example of *pick-carrot*. The robot repositions the carrot out of the corner to pick it. Bottom: *cover-object*. The deformable covers the object.

5.7   Limitations of MT-Opt

6   Conclusion

We presented a general multi-task learning framework, MT-Opt, that encompasses a number of elements: a multi-task data collection system, a scalable success detector framework, and a multi-task deep RL method that is able to effectively utilize the multi-task data. Our experiments show that by sharing data and parameters across various tasks we can significantly increase the data efficiency of learning individual tasks. Finally, we show how MT-Opt can quickly acquire new tasks by leveraging the shared multi-task representations and exploration strategies.

References

[1] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, et al. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. *arXiv preprint arXiv:1806.10293*, 2018.

[2] I. Akkaya, M. Andrychowicz, M. Chociej, M. Litwin, B. McGrew, A. Petron, A. Paino, M. Plappert, G. Powell, R. Ribas, et al. Solving rubik's cube with a robot hand. *arXiv preprint arXiv:1910.07113*, 2019.

[3] L. Espeholt, H. Soyer, R. Munos, K. Simonyan, V. Mnih, T. Ward, Y. Doron, V. Firoiu, T. Harley, I. Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. *arXiv preprint arXiv:1802.01561*, 2018.

[4] L. Pinto and A. Gupta. Learning to push by grasping: Using multiple tasks for effective learning. In *ICRA*, pages 2161–2168. IEEE, 2017. ISBN 978-1-5090-4633-1.

[5] M. Riedmiller, R. Hafner, T. Lampe, M. Neunert, J. Degrave, T. Van de Wiele, V. Mnih, N. Heess, and J. T. Springenberg. Learning by playing-solving sparse reward tasks from scratch. *arXiv preprint arXiv:1802.10567*, 2018.

[6] A. Wilson, A. Fern, S. Ray, and P. Tadepalli. Multi-task reinforcement learning: a hierarchical bayesian approach. In *Proceedings of the 24th international conference on Machine learning*, pages 1015–1022. ACM, 2007.

[7] K. Hausman, J. T. Springenberg, Z. Wang, N. Heess, and M. Riedmiller. Learning an embedding space for transferable robot skills. In *International Conference on Learning Representations*, 2018.

[8] T. Schaul, D. Borsa, J. Modayil, and R. Pascanu. Ray interference: a source of plateaus in deep reinforcement learning. *arXiv:1904.11455*, 2019.

[9] M. Hessel, H. Soyer, L. Espeholt, W. Czarnecki, S. Schmitt, and H. van Hasselt. Multi-task deep reinforcement learning with popart. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3796–3803, 2019.

[10] Z. Chen, V. Badrinarayanan, C.-Y. Lee, and A. Rabinovich. Gradnorm: Gradient normalization for adaptive loss balancing in deep multitask networks. *arXiv preprint arXiv:1711.02257*, 2017.

[11] T. Yu, S. Kumar, A. Gupta, S. Levine, K. Hausman, and C. Finn. Gradient surgery for multi-task learning. *arXiv preprint arXiv:2001.06782*, 2020.

[12] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, pages 1094–1100, 2020.

[13] B. Eysenbach, X. Geng, S. Levine, and R. Salakhutdinov. Rewriting history with inverse rl: Hindsight inference for policy improvement. *arXiv preprint arXiv:2002.11089*, 2020.

[14] R. Caruana. Multitask learning. *Mach. Learn.*, 28:41–75, 1997.

[15] S. Subramanian, A. Trischler, Y. Bengio, and C. J. Pal. Learning general purpose distributed sentence representations via large scale multi-task learning. *arXiv preprint arXiv:1804.00079*, 2018.

[16] M. Johnson, M. Schuster, Q. V. Le, M. Krikun, Y. Wu, Z. Chen, N. Thorat, F. Viégas, M. Wattenberg, G. Corrado, et al. Google's multilingual neural machine translation system: Enabling zero-shot translation. *Transactions of the Association for Computational Linguistics*, 5:339–351, 2017.

[17] B. McCann, N. S. Keskar, C. Xiong, and R. Socher. The natural language decathlon: Multitask learning as question answering. *arXiv preprint arXiv:1806.08730*, 2018.

[18] X. Liu, P. He, W. Chen, and J. Gao. Multi-task deep neural networks for natural language understanding. In A. Korhonen, D. R. Traum, and L. Màrquez, editors, *ACL (1)*, pages 4487–4496. Association for Computational Linguistics, 2019. ISBN 978-1-950737-48-2.

[19] Z. Chen, V. Badrinarayanan, C.-Y. Lee, and A. Rabinovich. Gradnorm: Gradient normalization for adaptive loss balancing in deep multitask networks. In *International Conference on Machine Learning*, pages 794–803. PMLR, 2018.

[20] I. Misra, A. Shrivastava, A. Gupta, and M. Hebert. Cross-stitch networks for multi-task learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3994–4003, 2016.

[21] O. Sener and V. Koltun. Multi-task learning as multi-objective optimization. In *Advances in Neural Information Processing Systems*, pages 527–538, 2018.

[22] E. Perez, F. Strub, H. De Vries, V. Dumoulin, and A. Courville. Film: Visual reasoning with a general conditioning layer. *arXiv preprint arXiv:1709.07871*, 2017.

[23] A. R. Zamir, A. Sax, W. B. Shen, L. J. Guibas, J. Malik, and S. Savarese. Taskonomy: Disentangling task transfer learning. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, 2018.

[24] T. Standley, A. R. Zamir, D. Chen, L. Guibas, J. Malik, and S. Savarese. Which tasks should be learned together in multi-task learning?, 2020.

[25] M. E. Taylor and P. Stone. Cross-domain transfer for reinforcement learning. In Z. Ghahramani, editor, *ICML*, volume 227 of *ACM International Conference Proceeding Series*, pages 879–886. ACM, 2007. ISBN 978-1-59593-793-3.

[26] K. Mülling, J. Kober, O. Kroemer, and J. Peters. Learning to select and generalize striking movements in robot table tennis. *Int. J. Robotics Res.*, 32(3):263–279, 2013.

[27] M. P. Deisenroth, P. Englert, J. Peters, and D. Fox. Multi-task policy search for robotics. In *ICRA*, pages 3876–3881. IEEE, 2014.

[28] B. C. da Silva, G. D. Konidaris, and A. G. Barto. Learning parameterized skills. In *ICML*. icml.cc / Omnipress, 2012.

[29] J. Kober, A. Wilhelm, E. Öztop, and J. Peters. Reinforcement learning to adjust parametrized motor primitives to new situations. *Auton. Robots*, 33(4):361–379, 2012.

[30] R. Yang, H. Xu, Y. Wu, and X. Wang. Multi-task reinforcement learning with soft modularization. *CoRR*, abs/2003.13661, 2020.

[31] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

[32] Y. Teh, V. Bapst, W. M. Czarnecki, J. Quan, J. Kirkpatrick, R. Hadsell, N. Heess, and R. Pascanu. Distral: Robust multitask reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 4496–4506, 2017.

[33] A. A. Rusu, S. G. Colmenarejo, C. Gulcehre, G. Desjardins, J. Kirkpatrick, R. Pascanu, V. Mnih, K. Kavukcuoglu, and R. Hadsell. Policy distillation. *arXiv preprint arXiv:1511.06295*, 2015.

[34] E. Parisotto, J. L. Ba, and R. Salakhutdinov. Actor-mimic: Deep multitask and transfer reinforcement learning. *arXiv preprint arXiv:1511.06342*, 2015.

[35] D. Ghosh, A. Singh, A. Rajeswaran, V. Kumar, and S. Levine. Divide-and-conquer reinforcement learning. *arXiv preprint arXiv:1711.09874*, 2017.

[36] H. Arora, R. Kumar, J. Krone, and C. Li. Multi-task learning for continuous control. *arXiv preprint arXiv:1802.01034*, 2018.

[37] L. Pinto, D. Gandhi, Y. Han, Y.-L. Park, and A. Gupta. The curious robot: Learning visual representations via physical interactions. In B. Leibe, J. Matas, N. Sebe, and M. Welling, editors, *Computer Vision – ECCV 2016*, pages 3–18, Cham, 2016. Springer International Publishing. ISBN 978-3-319-46475-6.

[38] M. Hessel, H. Soyer, L. Espeholt, W. Czarnecki, S. Schmitt, and H. van Hasselt. Multi-task deep reinforcement learning with popart. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3796–3803, 2019.

[39] T. Yu, S. Kumar, A. Gupta, S. Levine, K. Hausman, and C. Finn. Gradient surgery for multi-task learning. *CoRR*, abs/2001.06782, 2020.

[40] R. S. Sutton, D. Precup, and S. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1):181 – 211, 1999. ISSN 0004-3702.

[41] A. G. Barto and S. Mahadevan. Recent advances in hierarchical reinforcement learning. *Discrete Event Dynamic Systems*, 13(1-2):41–77, 2003.

[42] C. Daniel, G. Neumann, and J. Peters. Hierarchical relative entropy policy search. In N. D. Lawrence and M. A. Girolami, editors, *AISTATS*, volume 22 of *JMLR Proceedings*, pages 273–281. JMLR.org, 2012.

[43] A. G. Barto, S. Singh, and N. Chentanez. Intrinsically motivated learning of hierarchical collections of skills. In *Proceedings of International Conference on Developmental Learning (ICDL)*. MIT Press, Cambridge, MA, 2004.

[44] T. G. Dietterich. Hierarchical reinforcement learning with the maxq value function decomposition. *J. Artif. Intell. Res.*, 13:227–303, 2000.

[45] J. Morimoto and K. Doya. Acquisition of stand-up behavior by a real robot using hierarchical reinforcement learning. *Robotics Auton. Syst.*, 36(1):37–51, 2001.

[46] M. Ghavamzadeh and S. Mahadevan. Hierarchical policy gradient algorithms. In T. Fawcett and N. Mishra, editors, *ICML*, pages 226–233. AAAI Press, 2003. ISBN 1-57735-189-4.

[47] T. Shu, C. Xiong, and R. Socher. Hierarchical and interpretable skill acquisition in multi-task reinforcement learning. *arXiv preprint arXiv:1712.07294*, 2017.

[48] A. Zeng, S. Song, S. Welker, J. Lee, A. Rodriguez, and T. Funkhouser. Learning synergies between pushing and grasping with self-supervised deep reinforcement learning, 2018.

[49] A. Lazaric, M. Restelli, and A. Bonarini. Transfer of samples in batch reinforcement learning. In W. W. Cohen, A. McCallum, and S. T. Roweis, editors, *ICML*, volume 307 of *ACM International Conference Proceeding Series*, pages 544–551. ACM, 2008. ISBN 978-1-60558-205-4.

[50] M. Andrychowicz, D. Crow, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, pages 5048–5058, 2017.

[51] R. Rahmatizadeh, P. Abolghasemi, L. Bölöni, and S. Levine. Vision-based multi-task manipulation for inexpensive robots using end-to-end learning from demonstration. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3758–3765. IEEE, 2018.

[52] A. Xie, F. Ebert, S. Levine, and C. Finn. Improvisation through physical understanding: Using novel objects as tools with visual foresight. *Robotics: Science and Systems (RSS)*, 2019.

[53] K. Hausman, Y. Chebotar, S. Schaal, G. Sukhatme, and J. J. Lim. Multi-modal imitation learning from unstructured demonstrations using generative adversarial nets. In *Advances in Neural Information Processing Systems*, pages 1235–1245, 2017.

[54] Y. Li, J. Song, and S. Ermon. Infogail: Interpretable imitation learning from visual demonstrations. In *Advances in Neural Information Processing Systems*, pages 3812–3822, 2017.

[55] A. Singh, E. Jang, A. Irpan, D. Kappler, M. Dalal, S. Levine, M. Khansari, and C. Finn. Scalable multi-task imitation learning with autonomous improvement. *arXiv preprint arXiv:2003.02636*, 2020.

[56] T. Shankar, S. Tulsiani, L. Pinto, and A. Gupta. Discovering motor programs by recomposing demonstrations. In *International Conference on Learning Representations*, 2020.

[57] L. Shao, T. Migimatsu, Q. Zhang, K. Yang, and J. Bohg. Concept2robot: Learning manipulation concepts from instructions and human demonstrations. *Robotics: Science and Systems (RSS)*, 2020.

[58] L. Pinto and A. Gupta. Supersizing self-supervision: Learning to grasp from 50k tries and 700 robot hours. In *ICRA*, pages 3406–3413. IEEE, 2016. ISBN 978-1-4673-8026-3.

[59] S. Sharma, A. Jha, P. Hegde, and B. Ravindran. Learning to multi-task by active sampling. *arXiv preprint arXiv:1702.06053*, 2017.

[60] A. Nair, V. Pong, M. Dalal, S. Bahl, S. Lin, and S. Levine. Visual reinforcement learning with imagined goals. In S. Bengio, H. M. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *NeurIPS*, pages 9209–9220, 2018.

[61] C. Finn and S. Levine. Deep visual foresight for planning robot motion. *CoRR*, abs/1610.00696, 2016.

[62] F. Ebert, C. Finn, S. Dasari, A. Xie, A. X. Lee, and S. Levine. Visual foresight: Model-based deep reinforcement learning for vision-based robotic control. *CoRR*, abs/1812.00568, 2018.

[63] Y.-C. Lin, M. Bauzá, and P. Isola. Experience-embedded visual foresight. In L. P. Kaelbling, D. Kragic, and K. Sugiura, editors, *CoRL*, volume 100 of *Proceedings of Machine Learning Research*, pages 1015–1024. PMLR, 2019.

[64] H. J. T. Suh and R. Tedrake. The surprising effectiveness of linear models for visual foresight in object pile manipulation. *CoRR*, abs/2002.09093, 2020.

[65] S. Cabi, S. Gómez Colmenarejo, A. Novikov, K. Konyushkova, S. Reed, R. Jeong, K. Zolna, Y. Aytar, D. Budden, M. Vecerik, et al. Scaling data-driven robotics with reward sketching and batch reinforcement learning. *arXiv*, pages arXiv–1909, 2019.

[66] R. S. Sutton and A. G. Barto. *Introduction to Reinforcement Learning*. MIT Press, Cambridge, MA, USA, 1st edition, 1998. ISBN 0262193981.

[67] I. Akinola, J. Varley, and D. Kalashnikov. Learning precise 3d manipulation from multiple uncalibrated cameras. *arXiv preprint arXiv:2002.09107*, 2020.