Boosting Norwegian Automatic Speech Recognition

Anonymous

Abstract

In this paper, we present several baselines for automatic speech recognition (ASR) models for the two official written languages in Norway: Bokmål and Nynorsk. We evaluate these models on several datasets of Norwegian speech and compare their performance to previous state-of-the-art ASR models as well as on out-of-domain datasets. We improve the state of the art on NPSC from a WER score of 17.10 to 7.60. We also discuss the challenges and potential solutions for improving ASR models for Norwegian.

1 Introduction

Automatic Speech Recognition (ASR) is the task of converting speech into text. ASR systems are used in a wide range of applications, such as voice assistants, transcription services, and speech-to-text translation. It is also increasingly becoming a tool for research in spoken language as the accuracy of the more recent neural-based models is approaching that of humans for certain metrics. In a study by Amodei et al. (2016), the authors estimated that the word error rate (WER) in human-produced transcriptions on the LibriSpeech benchmark (Panayotov et al., 2015) is roughly 5.83%, while their end-to-end ASR model, DeepSpeech 2, achieved a WER of 5.33% on a clean test set, although it was outperformed by humans on noisy data. Since the introduction of DeepSpeech 2, the field of ASR has progressed even further, with the current leaderboard of the benchmark containing over ten models with a WER below 2%. Despite the high accuracy in resource-rich languages, ASR models are currently unavailable for the vast majority of the world's languages due to the lack of gold annotated data to train such models. Recent advances in unsupervised learning of acoustic models have further reduced the need for transcribed speech.

In this paper, we focus on developing and evaluating a new set of baselines ASR models for Norwegian based on the wav2vec 2.0 architecture (Baevski et al., 2020). We make use of existing pre-trained models and combine them with other language resources for the Norwegian languages to further improve the accuracy of the resulting ASR systems. Our models seem to perform notably better than previous work on established datasets.

2 Norwegian ASR

The Norwegian language has many spoken dialects, which differ lexically, grammatically, and phonologically. Additionally, there are two official written standards of Norwegian, Bokmål and Nynorsk, which have somewhat different inflection, vocabulary, and spelling. Consequently, high-quality datasets for acoustic modeling of Norwegian require speech data in different dialects and should ideally include transcriptions in both written standards.

Early work on Norwegian speech recognition was mostly focused on very limited vocabularies and numbers, tailored for telephone applications and menu navigation (Svendsen et al., 1989; Paliwal, 1992; Ljøen et al., 1994; Kvale, 1996). Compound words are more frequent in Norwegian than English, but using traditional pronunciation dictionaries seemed sufficient in controlled lexicons. In Norwegian, natural numbers between 20 and 99 can be pronounced differently (e.g. "twenty-four" and "four-and-twenty"), which poses a challenge for natural number recognition. By the year 2000, and under the umbrella of a few EU-funded projects, research focused mostly on overcoming these limitations and extending the use cases to dates, times, nouns, and the spelling out of words, which yielded several important datasets (e.g.,

SpeechDat, SpeechDat-II, TABU.0) and technical improvements over a short period of time (Amdal and Ljøen, 1995; Hoge et al., 1997; Kvåle and Amdal, 1997; Johansen et al., 1997; Amdal et al., 1999; Martens and Fpm, 2000). Most approaches were based on hidden Markov models and some relied on Mel Frequency Cepstral Coefficients (MFCC), commonly by using the Hidden Markov Model Toolkit (HTK) (Young and Young, 1993).

However, these approaches were not designed for open-ended recognition and often struggled with out-of-vocabulary words or real conversations. It was not until the introduction of the newer datasets that systems with reasonable performance started to appear.

2.1 NST

The Nordisk Språkteknologi (NST) dataset is a multi-lingual speech recognition dataset that contains a total 540 hours of speech in Swedish, Danish and Norwegian Bokmål, with their corresponding transcriptions. Developed by the now extinct technology company Nordisk Språkteknologi, the data was manually compiled and mostly validated. It contains telephone conversations, office conversations, read aloud passages, word spellings, and even hesitations. The speaker metadata includes age, gender, region of birth, and regional dialect. The audio quality is generally high, and most recordings have two channels recorded with separate microphones, one placed close to the speaker and one across the room. The dataset comes with training and testing sets. For Norwegian, the training set contains 411.5 hours of speech, while the test contains 115.3 hours. The amount of speech in hours per the regional dialect of the speakers represented in the NST dataset is reported in table 9 of Appendix A. However, due to its nature as a manuscript-read dataset, the dataset has some limitations, as it only contains planned speech and does not include or contains limited degree of dialectal phenomena which deviate from the Bokmål norm.

2.2 NPSC

In Solberg and Ortiz (2022), the authors present the Norwegian Parliamentary Speech Corpus (NPSC, The National Library of Norway, 2021), an open dataset intended for acoustic modeling of Norwegian unscripted speech. The dataset is developed and distributed by the Language Bank at the National Library of Norway, and consists of approximately 100 hours of recordings of meetings at Stortinget, the Norwegian parliament, in 2017 and 2018. Orthographic transcriptions in Norwegian Bokmål and Norwegian Nynorsk were made. The dataset is public domain and can be used with no restrictions. The dataset is already split in training, validation, and test sets (see Table 1).

Solberg and Ortiz trained and tested an ASR system and the results showed that the use of the NPSC dataset improved the recognition performance when compared to the use of only manuscript-read datasets. The authors argue that the NPSC dataset is necessary to fill the gap in the lack of available speech data for Norwegian ASR.

2.3 FLEURS

A very recent addition to the small pool of open datasets suitable for training transformer-based models for ASR comes in the form of a multilingual speech benchmark. The Few-shot Learning Evaluation of Universal Representations of Speech (FLEURS) benchmark (Conneau et al., 2022) is a parallel speech dataset in 102 languages built on top of the FLoRes-101 benchmark for machine translation. FLEURS contains approximately 12 hours of speech per language and can be used for various speech tasks such as automatic speech recognition, speech language identification, translation, and retrieval. The goal of FLEURS is to enable speech technology in more languages and drive research in low-resource speech understanding. The dataset is unique in its coverage of over 100 languages and its suitability for various speech tasks. In their paper, the authors provide baseline results for the different tasks using multilingual pre-trained models, but do not report on single monolingual ones. The almost 11 hours of Norwegian (see Table 2) included in this dataset adhere to Bokmål and represent out of domain speech qualitatively closer to NST than to NPSC.

3 Norwegian wav2vec 2.0

Introduced by Baevski et al. (2020), wav2vec 2.0 is a state-of-the-art self-supervised audio representation learning architecture designed to extract high-quality feature representations from raw audio signals. After pre-training the acoustic model, wav2vec 2.0 models can be used for a wide range

Language	Train		Validation		Test	
	Hours	**Samples**	**Hours**	**Samples**	**Hours**	**Samples**
Norwegian Bokmål	88.62	44,746	11.70	5,973	11.15	5,527
Norwegian Nynorsk	12.96	6,586	1.61	871	1.33	828
Total	**101.58**	**51,332**	**13.31**	**6,844**	**12.48**	**6,355**

Table 1: Distribution of number of hours and samples for each of the Norwegian written languages in the NPSC dataset.

Train		Validation		Test	
Hours	**Samples**	**Hours**	**Samples**	**Hours**	**Samples**
10.91	3,167	0.58	163	1.25	357

Table 2: Distribution of number of hours and samples for each of the splits in Norwegian subset of the FLEURS dataset.

of tasks using a regular fine-tuning mechanism. For ASR, these fine-tuned models can be plugged to rather simple n-gram language models that leverage the connectionist temporal classification (CTC) classification loss to further improve recognition.

It improves upon the original wav2vec architecture by Schneider et al. (2019) in several key ways. First, it uses a transformer-based neural network to predict the audio signal in a context window surrounding a masked center frame. This enables the model to capture long-range dependencies in the audio signal, leading to more accurate feature representations. Second, the model performs multiple prediction tasks simultaneously, including predicting the center frame, predicting the entire context window, and predicting future audio signals. The CTC loss is used to compute the prediction error between the predicted and actual center frame. This multi-task learning approach improves the representational power of the model. Finally, wav2vec 2.0 has a larger number of parameters and a larger training data size, which leads to improved performance on various audio representation learning benchmarks.

In early 2022, we released a series of wav2vec 2.0 models of different sizes. Available for Bokmål in 300 million and 1 billion sizes and for Nynorsk only in 300 million parameters, these models were fine-tuned on the NPSC dataset. The 1 billion parameter models were based on the multilingual XLS-R models, and the 300 million parameters models on the Swedish VoxRex model. XLS-R models (Babu et al., 2021) are trained on more than 436,000 hours of publicly available speech recordings. The data used to train the XLS-R models came from a variety of sources, including parliamentary proceedings and audio books, and covered 128 different languages. VoxRex, developed by Malmsten et al. (2022) at National Library of Sweden (KB), is a Swedish acoustic wav2vec 2.0 model trained on the P4-10k corpus which contains 10,000 hours of Swedish local public service radio as well as 1,500 hours of audio books and other speech from KB's collections. The choice of a Swedish acoustic model to fine-tune Norwegian ASR instead of using the same size XLS-R model was motivated by the topological closeness of both languages. To the best of our knowledge, these models represent the current state of the art on NPSC.

4 Methods

In this work, we evaluate these models, referred to as NPSC-Bokmål and NPSC-Nynorsk, and fine-tune new XLS-R 1 billion parameters and VoxRex 300 million parameters models using the same hyperparameters. We train the models on NPSC and ablate on different data supplementing strategies derived from the NST dataset.

The NST dataset was modernized and reorganized by the National Library of Norway, and is now available in a reader-friendly format (Nordisk språkteknologi, 2020). We omitted the second channel of audio recorded with a distant microphone due to no noticeable differences between the audio recorded with the close microphone. The dataset is representative of the major regions and the language variety spoken in that region, although the representation of the dialectal varieties of the Scandinavian languages in the dataset is debatable (see Table 9). All combinations of NPSC and NST training sets were lowercased, and had removed non-letter characters and

accents from characters (aside from the Norwegian 'æøå'). Any samples with an audio clip under half a second are removed. Transcripts containing digits are also removed, as we expect any numbers to be spelled out. NST data containing words spelled out letter by letter were removed, and instructions to stay silent or dictation commands (e.g., comma, period) were replaced with empty strings. For the hesitations in NPSC and NST, most of the runs replace them using triple letters, e.g. `<ee>` becomes `eee`. These models also use the Bokmål translation of the Nynorsk data in NPSC. The resulting models from the different experiments are listed below:

- NST model. Fine-tuned on the NST dataset as described, with no exta modificatons nor additions.

- NST-NPSC model. These models are fine-tuned using the Bokmål and Nynorsk subsets of NPSC plus the NST dataset as described.

- NST-NPSC-Bokmål model. These models are fine-tuned on the Bokmål subset of NPSC plus the translated version of the Nynorsk subset, the NST, and the hesitations subset of NST. These models also replace the hesitations with single letters in the 1 billion parameters models, and the special character $\hat{\text{h}}$ shared between all types of hesitations in the 300 million parameters models since triple letters require a pad character in between.

- NPSC-Nynorsk. Since the NPSC-Nynorsk model was only available as a 300 million parameter model, this model is a 1 billion parameters version fine-tuned on the Nynorsk subset of NPSC plus the translated version of the Bokmål subset.

We trained all models for 40 epochs on a single NVIDIA RTX A6000 GPU with an effective batch size of 24 by accumulating gradients every 2 steps on a batch size of 12. The learning rate was set to 2e-5, with 2,000 steps of warmup and linear decaying using an Adam optimizer with β_1=0.9, β_2=0.999, and ϵ=1e-8.

After fine-tuning, separate Bokmål and Nynorsk 5-gram Kneser-Ney language model were added where appropriate. Two versions of the NST-NPSC model were also created, one with the Bokmål 5-gram language model, and another one with the Nynorsk language model, as we

evaluate the NST-NPSC model on both subsets of NPSC. These language models were created using a combination of the training and validation sets of NPSC plus a few thousand random documents from the Norwegian Colossal Corpus (Kummervold et al., 2021, 2022). We processed the a total of 78 million words by lowercasing, normalizing, and filtering out the characters that were outside the 28 Norwegian letters used for fine-tuning. We used the implementation of Kneser-Ney models (Ney et al., 1994) available in the KenLM library (Heafield, 2011). The estimation of the CTC α and β values was done by grid search over {0.001, 0.01, 0.1, 0.25, 0.5, 0.75, 1, 1.5, 2, 3} on the validation set of the Bokmål subset of NPSC; we established α=0.5 and β=0.001.

5 Results and Discussion

We evaluate the performance of the models grouping their scores by the written language of the test sets in NPSC and NST. For comparison purposes, we include the figures obtained in the original NPSC paper by Solberg and Ortiz (2022), as well as the work by Ortiz and Burud (2021) who also briefly evaluated ASR on NPSC. Tables 10 and 11 show the WER and CER scores of the 300 million and 1 billion parameters models. In both cases, it can be seen that models trained on the Bokmål subset of NPSC perform not too well on the test set of NST. Similary, models trained only on NST underperform on the test set of the Bokmål subset of NPSC. Adding a 5-gram language model yields significant improvements across the board, ranging from a 5 points increase on the worst performing pairs of model and dataset, to a 1 point increase for the best performing pairs. However, the biggest gain in performance is the addition of extra data. The models fine-tuned on combinations of NPSC and NST produce significantly better results. On the whole NPSC, the 300M NST-NPSC model outperform Solberg and Ortiz (2022) by 9.5 points and the previous state of the art NPSC-Bokmål model by 4.16 points. For the other datasets, the 1 billion parameters model NST-NPSC-Bokmål outperformed the rest of models, yielding increases over the NPSC-Bokmål model of 0.6 points on NPSC (Bokmål) subset and of 14.89 points on NST. Interestingly, the performance of the best 300M and 1B models was very close.

An evaluation of the models for each region in

Model	NPSC	NPSC (Bokmål)	NST
No language model			
NPSC-Bokmål	11.76 / 3.63	9.79 / 3.13	21.46 / 5.05
NST	24.50 / 8.84	22.45 / 8.23	5.52 / 1.75
NST-NPSC	9.58 / 3.08	8.86 / 2.87	5.44 / 1.70
NST-NPSC-Bokmål	10.37 / 3.07	8.33 / 2.55	5.49 / 1.76
5-gram language model			
NPSC-Bokmål	9.07 / 3.24	7.14 / 2.74	19.19 / 4.59
NST	19.41 / 8.17	17.33 / 7.53	**4.38 / 1.55**
NST-NPSC	**7.60 / 2.83**	**6.92 / 2.62**	4.39 / 1.52
NST-NPSC-Bokmål	10.05 / 3.31	7.96 / 2.75	4.42 / 1.56
Ortiz and Burud (2021)	20.64 / NA		
Solberg and Ortiz (2022)	17.10 / NA		

Table 3: Test sets scores (WER/CER) of the 300M models fine-tuned on data containing Bokmål. Best scores in **bold**.

Model	NPSC	NPSC (Bokmål)	NST
No language model			
NPSC-Bokmål	9.49 / 3.17	7.51 / 2.67	17.64 / 4.23
NST	25.07 / 9.32	22.94 / 8.65	5.08 / 1.63
NST-NPSC	8.99 / 2.99	7.14 / 2.54	5.25 / 1.65
NST-NPSC-Bokmål	8.69 / 2.71	6.46 / 2.06	4.93 / 1.64
5-gram language model			
NPSC-Bokmål	8.37 / 3.01	6.41 / 2.51	14.94 / 3.69
NST	21.47 / 8.75	19.36 / 8.09	4.39 / 1.52
NST-NPSC	8.03 / 2.85	6.15 / 2.39	4.54 / 1.53
NST-NPSC-Bokmål	**8.02 / 2.62**	**5.81 / 1.98**	**4.30 / 1.53**
Ortiz and Burud (2021)	20.64 / NA		
Solberg and Ortiz (2022)	17.10 / NA		

Table 4: Test sets scores (WER/CER) of the 1B models fine-tuned on data containing Bokmål. Best scores in **bold**.

the test set of NST can also be found in Appendix A with somewhat similar results and trends. We found that there is virtually no difference in the per region performance of the models, even for the unbalanced (in terms of hours of speech in test set) regions of Oslo and Sør-Vestlandet. It is importante to notice that the regions identified in NST do not reflect the diversity of spoken dialects in Norway.

For Nynorsk, as shown in Tables 7 and 8, our NST-NPSC 300M model with a Nynorsk 5-gram language model attached did not beat the existing NPSC-Nynorsk 300M model. However, our newer NPSC-Nynorsk 1B model outperforms the NPSC-Nynorsk 300M model by 1.14 points.

In order to evaluate the generalization capabilities of our models, we use the Norwegian test set of FLEURS. Transcriptions on FLEURS were

Model	NPSC (Nynorsk)
No language model	
NPSC-Nynorsk	16.29 / 4.91
NST-NPSC	16.52 / 5.03
5-gram language model	
NPSC-Nynorsk	**12.68 / 4.38**
NST-NPSC	14.23 / 4.80

Table 5: Test sets scores (WER/CER) of the 300M models fine-tuned on data containing Nynorsk. Best scores in **bold**.

normalized as closely as possible to those present in the NST and NPSC, with numbers and times written out in text form. We compare the performance of our models against the Whisper models (Radford et al., 2022), which despite of being architecturally different, and being trained su-

Model	NPSC (Nynorsk)
No language model	
NPSC-Nynorsk	13.99 / 4.52
NST-NPSC	26.99 / 7.33
5-gram language model	
NPSC-Nynorsk	**11.54 / 4.12**
NST-NPSC	25.38 / 7.07

Table 6: Test sets scores (WER/CER) of the 1B models fine-tuned on data containing Nynorsk. Best scores in **bold**.

pervisely on almost twice the amount of hours of XLS-R and with subtitles instead of transcriptions, hold the state of the art on almost every language in FLEURS. However, it is important to notice that their WER scores are calculated on non-normalized text and their parameter counts do not match ours. As shown in Tabes 7 and 8, our best 300 million parameters model more than doubles the performance of Whisper small (244M), with a WER of 9.88 versus 24.20. The 1 billion parameters model NST-NPSC still outperforms Whisper large by 1.53 points, and it's only a negligible 0.37 points from its v2, that while having 550M fewer parameters than Whisper large.

Model	FLEURS
No language model	
NPSC-Bokmål	18.51 / 4.96
NST	13.94 / 3.96
NST-NPSC	12.43 / 3.48
NST-NPSC-Bokmål	12.51 / 3.46
5-gram language model	
NPSC-Bokmål	12.98 / 3.83
NST	11.27 / 3.46
NST-NPSC	9.93 / 2.92
NST-NPSC-Bokmål	**9.88 / 2.89**
Whisper small (244M)	24.20 / NA

Table 7: Norwegian test sets scores (WER/CER) on FLEURS of the 300M models. Best scores in **bold**.

6 Future Work

Despite the improved performance of our models compared to the other baselines, ASR models for Norwegian still face several challenges. One major challenge is the complex phonetics and morphology of the different dialects, which makes it difficult for models to accurately transcribe the phonemes in the input speech to the

Model	FLEURS
No language model	
NPSC-Bokmål	16.26 / 4.42
NST	13.05 / 3.88
NST-NPSC	11.17 / 3.13
NST-NPSC-Bokmål	11.53 / 3.24
5-gram language model	
NPSC-Bokmål	13.03 / 3.73
NST	11.53 / 3.58
NST-NPSC	**9.87 / 2.89**
NST-NPSC-Bokmål	10.00 / 2.91
Whisper large (1.55B)	11.4 / NA
Whisper large-v2 (1.55B)	9.5 / NA

Table 8: Norwegian test sets scores (WER/CER) on FLEURS of the 1B models. Best scores in **bold**.

correct spelling. Another challenge is the limited availability of high-quality datasets for Norwegian speech, which limits the amount of training data for ASR models.

To address these challenges, one possible to solution is to combine multiple datasets and sources of training data, such as transcribed speech and synthetic speech, to increase the amount of pre-training data for ASR models. With enough transcribed speech, even other more data-hungry architectures could be tested, such as Whisper.

Finally, the prospect of training wav2vec 2.0 directly on non-normalized text is an interesting avenue for research, as it would make the models directly usable without having to transform the output of the models to make them more readable.

7 Conclusion

In this paper, we presented several new models for automatic speech recognition of Norwegian. We evaluated these models on several datasets of Norwegian speech and compared their performance to previous work, outperforming the previous state of the art. Given that we used almost the same settings than the wav2vec 2.0 models released last year, with the addition of extra training time and data there are some interesting findings. First, adding over 400 hours of extra planned speech to the semi-improvised speech part of NPSC, performance does not plummet, but actually increases from 6.41 to 5.81 WER for Bokmål in the 1B settings. The 300M model seems more sensitive in this regard and the WER decreases from 7.14 to 7.96 WER. For NST, the trend is exactly the same,

although the differences are smaller.

Interestingly, the out of domain performance of the models is also greatly improved by adding the planned speech in NST to NPSC. Models on both sizes increase their WER scores from 12.98 to 9.88 for the 300M model, and from 13.03 to 9.87 for the 1B model.

We are releasing our best performing models and evaluation code for replicability, and hope to contribute to the advance of ASR for Norwegian.

References

I Amdal and H Ljøen. 1995. Tabu. 0-en norsk telefontaledatabase. *Scientific Report*, 40:95.

Ingunn Amdal, Trym Holter, and Torbjørn Svendsen. 1999. Maximum likelihood pronunciation modelling of norwegian natural numbers for automatic speech recognition. In *Proc. Norwegian Signal Processing Symposium (NORSIG)*, pages 145–150.

Dario Amodei, Sundaram Ananthanarayanan, Rishita Anubhai, Jingliang Bai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Qiang Cheng, Guoliang Chen, et al. 2016. Deep speech 2: End-to-end speech recognition in english and mandarin. In *International conference on machine learning*, pages 173–182. PMLR.

Arun Babu, Changhan Wang, Andros Tjandra, Kushal Lakhotia, Qiantong Xu, Naman Goyal, Kritika Singh, Patrick von Platen, Yatharth Saraf, Juan Pino, et al. 2021. Xls-r: Self-supervised cross-lingual speech representation learning at scale. *arXiv preprint arXiv:2111.09296*.

Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. 2020. wav2vec 2.0: A framework for self-supervised learning of speech representations. *Advances in neural information processing systems*, 33:12449–12460.

Alexis Conneau, Min Ma, Simran Khanuja, Yu Zhang, Vera Axelrod, Siddharth Dalmia, Jason Riesa, Clara Rivera, and Ankur Bapna. 2022. Fleurs: Few-shot learning evaluation of universal representations of speech. *arXiv preprint arXiv:2205.12446*.

Kenneth Heafield. 2011. Kenlm: Faster and smaller language model queries. In *Proceedings of the sixth workshop on statistical machine translation*, pages 187–197.

H Hoge, Herbert S Tropf, Richard Winski, Henk van den Heuvel, Reinhold Haeb-Umbach, and Khalid Choukri. 1997. European speech databases for telephone applications. In *1997 IEEE International Conference on Acoustics, Speech, and Signal Processing*, volume 3, pages 1771–1774. IEEE.

Finn Tore Johansen, Ingunn Amdal, and Knut Kvale. 1997. The norwegian part of speechdat: A european speech database for creation of voice driven teleservices. *Proceedings of NORSIG-1997*.

Per Kummervold, Freddy Wetjen, and Javier de la Rosa. 2022. The Norwegian colossal corpus: A text corpus for training large Norwegian language models. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 3852–3860, Marseille, France. European Language Resources Association.

Per E Kummervold, Javier De la Rosa, Freddy Wetjen, and Svein Arne Brygfjeld. 2021. Operationalizing a national digital library: The case for a Norwegian transformer model. In *Proceedings of the 23rd Nordic Conference on Computational Linguistics (NoDaLiDa)*, pages 20–29, Reykjavik, Iceland (Online). Link"oping University Electronic Press, Sweden.

Knut Kvale. 1996. Norwegian numerals: A challenge to automatic speech recognition. In *Proceeding of Fourth International Conference on Spoken Language Processing. ICSLP'96*, volume 4, pages 2028–2031. IEEE.

Knut Andreas Kvåle and Ingunn Amdal. 1997. Improved automatic recognition of norwegian natural numbers by incorporating phonetic knowledge. *1997 IEEE International Conference on Acoustics, Speech, and Signal Processing*, 3:1763–1766 vol.3.

H Ljøen, I Amdal, and FT Johansen. 1994. Norwegian speech recognition for telephone applications. In *Proc. Norsig*, volume 94, pages 121–125.

Martin Malmsten, Chris Haffenden, and Love Börjeson. 2022. Hearing voices at the national library–a speech corpus and acoustic model for the swedish language. *arXiv preprint arXiv:2205.03026*.

Jean-Pierre Martens and Belgium Fpm. 2000. Final report of cost action 249 continuous speech recognition over the telephone country acronym name of institution.

Hermann Ney, Ute Essen, and Reinhard Kneser. 1994. On structuring probabilistic dependences in stochastic language modelling. *Computer Speech & Language*, 8(1):1–38.

Nordisk språkteknologi. 2020. NST Norwegian ASR Database (16 kHz) – Reorganized.

Pablo Ortiz and Simen Burud. 2021. Bert attends the conversation: Improving low-resource conversational asr. *arXiv preprint arXiv:2110.02267*.

Kuldip K Paliwal. 1992. On the use of line spectral frequency parameters for speech recognition. *Digital signal processing*, 2(2):80–87.

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. 2015. Librispeech: an asr corpus based on public domain audio books. In *2015 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pages 5206–5210. IEEE.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2022. Robust speech recognition via large-scale weak supervision.

Steffen Schneider, Alexei Baevski, Ronan Collobert, and Michael Auli. 2019. wav2vec: Unsupervised pre-training for speech recognition. *Proc. Interspeech 2019*, pages 3465–3469.

Per Erik Solberg and Pablo Ortiz. 2022. The norwegian parliamentary speech corpus. *arXiv preprint arXiv:2201.10881*.

Torbjørn Svendsen, Kuldip K Paliwal, Erik Harborg, and PO Husoy. 1989. An improved sub-word based speech recognizer. In *International Conference on Acoustics, Speech, and Signal Processing,*, pages 108–111. IEEE.

The National Library of Norway. 2021. Norwegian Parliamentary Speech Corpus.

Steve J Young and Sj Young. 1993. The htk hidden markov model toolkit: Design and philosophy.

8 Appendix A. NST regions

Region	Train		Test	
	Hours	**Samples**	**Hours**	**Samples**
Oslo-området	53.2	38,688	25.3	17,729
Ytre Oslofjord	48.0	34,008	7.3	4,935
Bergen og Ytre Vestland	45.7	31,824	8.3	5,922
Sør-Vestlandet	42.2	29,328	10.3	6,909
Trøndelag	38.4	27,456	9.3	5,922
Sørlandet	36.9	26,600	9.0	5,922
Voss og omland	33.6	22,776	9.4	5,922
Troms	30.5	19,344	9.6	4,935
Nordland	28.0	20,591	8.8	5,922
Total	**411.5**	**289,934**	**115.3**	**75,965**

Table 9: Distribution of number of hours and speakers for each of the dialect regions (region of youth) of the Norwegian subset of the NST dataset.

Region	NPSC-Bokmål	NPSC-Nynorsk	NST	NST-NPSC	NST-NPSC-Bokmål
No language model					
Bergen og Ytre Vestland	26.14 / 6.24	45.57 / 11.34	6.18 / 1.77	5.92 / 1.75	5.92 / 1.75
Hedmark og Oppland	19.22 / 4.08	42.36 / 10.31	4.71 / 1.12	4.56 / 1.06	4.56 / 1.14
Nordland	21.92 / 4.67	42.62 / 10.03	5.21 / 1.27	5.00 / 1.20	4.99 / 1.25
Oslo-området	20.21 / 5.90	42.50 / 11.87	6.67 / 3.29	6.60 / 3.21	6.65 / 3.26
Sunnmøre	22.72 / 5.00	41.56 / 9.64	5.02 / 1.16	5.04 / 1.15	5.10 / 1.21
Sør-Vestlandet	24.55 / 5.78	45.44 / 11.53	6.23 / 1.57	6.13 / 1.53	6.25 / 1.60
Sørlandet	21.99 / 4.77	44.04 / 10.52	5.52 / 1.34	5.45 / 1.31	5.48 / 1.37
Troms	21.66 / 4.35	42.56 / 9.71	4.21 / 0.97	4.25 / 0.95	4.28 / 1.01
Trøndelag	18.28 / 3.77	40.26 / 9.54	4.32 / 1.02	4.27 / 1.00	4.43 / 1.07
Voss og omland	20.22 / 4.32	38.84 / 8.86	4.10 / 0.98	4.21 / 0.98	4.24 / 1.04
Ytre Oslofjord	21.08 / 4.69	44.45 / 11.36	6.04 / 1.54	5.87 / 1.46	5.94 / 1.50
5-gram language model					
Bergen og Ytre Vestland	22.75 / 5.58	42.64 / 10.81	4.91 / 1.52	4.83 / 1.54	4.70 / 1.55
Hedmark og Oppland	17.69 / 3.75	39.31 / 9.81	3.58 / 0.94	3.48 / 0.88	3.58 / 0.96
Nordland	19.59 / 4.20	39.76 / 9.58	3.89 / 1.04	3.89 / 1.00	3.91 / 1.04
Oslo-området	18.39 / 5.53	39.48 / 11.36	5.70 / 3.10	5.66 / 3.04	5.67 / 3.07
Sunnmøre	19.74 / 4.39	38.94 / 9.25	3.90 / 0.98	4.04 / 0.99	4.03 / 1.04
Sør-Vestlandet	21.44 / 5.17	42.45 / 10.97	4.74 / 1.31	4.84 / 1.31	4.87 / 1.36
Sørlandet	19.64 / 4.30	41.34 / 10.03	4.24 / 1.12	4.29 / 1.10	4.29 / 1.14
Troms	19.10 / 3.87	39.90 / 9.31	3.17 / 0.79	3.26 / 0.78	3.35 / 0.85
Trøndelag	16.78 / 3.48	36.68 / 8.94	3.34 / 0.85	3.38 / 0.84	3.55 / 0.92
Voss og omland	18.56 / 3.97	36.18 / 8.50	3.32 / 0.85	3.36 / 0.83	3.37 / 0.89
Ytre Oslofjord	18.53 / 4.14	40.97 / 10.75	4.51 / 1.26	4.53 / 1.21	4.57 / 1.24

Table 10: Results WER/CER NST dialect region 300m.

Region	NPSC-Bokmål	NPSC-Nynorsk	NST	NST-NPSC	NST-NPSC-Bokmål
No language model					
Bergen og Ytre Vestland	21.88 / 5.41	43.60 / 11.38	5.47 / 1.61	5.85 / 1.73	5.17 / 1.61
Hedmark og Oppland	14.48 / 3.06	39.23 / 9.89	4.29 / 1.02	4.29 / 0.99	4.15 / 1.04
Nordland	17.78 / 3.79	40.67 / 9.97	4.44 / 1.08	4.68 / 1.11	4.39 / 1.10
Oslo-området	16.70 / 5.10	40.45 / 11.58	6.27 / 3.15	6.30 / 3.12	6.14 / 3.16
Sunnmøre	20.41 / 4.57	39.73 / 9.67	4.59 / 1.07	5.19 / 1.19	4.51 / 1.09
Sør-Vestlandet	20.84 / 5.02	43.82 / 11.54	6.23 / 1.55	6.19 / 1.55	6.03 / 1.54
Sørlandet	17.69 / 3.72	41.63 / 10.26	5.23 / 1.29	5.30 / 1.27	4.92 / 1.24
Troms	17.22 / 3.42	40.30 / 9.44	3.75 / 0.86	3.92 / 0.87	3.47 / 0.83
Trøndelag	14.16 / 3.01	37.28 / 9.23	3.80 / 0.89	4.07 / 0.91	3.65 / 0.90
Voss og omland	16.50 / 3.52	36.05 / 8.62	3.72 / 0.90	4.04 / 0.93	3.78 / 0.93
Ytre Oslofjord	17.69 / 3.83	43.30 / 11.26	5.32 / 1.38	5.47 / 1.36	5.25 / 1.39
5-gram language model					
Bergen og Ytre Vestland	18.34 / 4.67	41.20 / 10.92	4.69 / 1.49	5.03 / 1.58	4.54 / 1.50
Hedmark og Oppland	12.37 / 2.64	36.81 / 9.49	3.65 / 0.93	3.61 / 0.88	3.63 / 0.96
Nordland	14.97 / 3.24	38.22 / 9.55	3.68 / 0.96	3.88 / 0.97	3.70 / 0.99
Oslo-området	14.53 / 4.68	37.83 / 11.11	5.67 / 3.04	5.71 / 3.01	5.57 / 3.05
Sunnmøre	16.79 / 3.82	37.81 / 9.36	3.91 / 0.96	4.46 / 1.07	3.88 / 1.00
Sør-Vestlandet	17.63 / 4.32	41.68 / 11.09	5.30 / 1.41	5.31 / 1.40	5.19 / 1.41
Sørlandet	14.95 / 3.19	39.27 / 9.86	4.39 / 1.16	4.46 / 1.13	4.16 / 1.11
Troms	14.54 / 2.95	37.90 / 9.05	3.16 / 0.76	3.27 / 0.77	3.04 / 0.77
Trøndelag	11.86 / 2.54	34.62 / 8.70	3.27 / 0.80	3.44 / 0.80	3.11 / 0.81
Voss og omland	13.43 / 2.93	34.14 / 8.36	3.19 / 0.83	3.51 / 0.84	3.23 / 0.85
Ytre Oslofjord	15.36 / 3.35	40.32 / 10.72	4.42 / 1.22	4.64 / 1.20	4.41 / 1.24

Table 11: Results WER/CER NST dialect region 1B.