General Part Assembly Planing

Abstract: Most successes in autonomous robotic assembly have been restricted to single target or category. We propose to investigate general part assembly, the task of creating novel target assemblies with unseen part shapes. To tackle the planning of general part assembly, we present General Part Assembly Transformer (GPAT), a transformer-based model architecture that accurately predicts part poses by inferring how each part shape corresponds to the target shape. Our experiments on both 3D CAD models and real-world scans demonstrate GPAT's generalization abilities to novel and diverse target and part shapes. [1]

1 Introduction

The ability to assemble new objects is a hallmark of visuo-spatial reasoning. With the mental image of a novel target shape, one can arrange possibly unseen parts at hand to create a resembling assembly, either building an alien spaceship with lego blocks or a rain shelter with stones. Building autonomous robotic systems that exhibit these capabilities may give rise to wide range of robotics applications from autonomously assembling new objects in a manufacturing plant to building shelter in disaster response scenarios.

Figure 1: **General Part Assembly**. We seek to build autonomous robotic systems that can assemble a novel target with previously unseen parts. The visualizations are actual inputs and prediction of our model.

Despite the interest and progress in part assembly, existing methods tend to focus on *specialized part assembly* consisting of fixed targets [1, 2] or seen categories [3, 4]. We propose to instead investigate the task of *general part assembly*, which takes in as inputs both a target shape and a variable set of part shapes to build an assembly resembling the target. Instead of restricting to fixed objects or categories, we require the robotic system to generalize to novel target shapes without additional annotation or supervision. Moreover, the available parts are not guaranteed to be carefully manufactured, and the robotic system has to use parts of slightly differing shapes, the *non-exact parts*, e.g., building a table with rectangular blocks given a round table as the target.

The task of *general part assembly* is an extension of *specialized part assembly* that focus on fixed targets or categories. For fixed-target assembly, the target shape information is implicitly provided to the agent. A general part assembly agent can also solve category-level part assembly by taking in as input a single instance of the category, while a typical learning methods is trained on a large number of instances from the category [3, 4]. For example, given a single table instance, a general part assembly agent can assemble tables with either rectangular tabletop or round tabletop.

In this paper, we focus on planning for general part assembly, i.e., inferring the poses of the given parts. Our key insight is to formulate general part assembly as a goal-conditioned shape rearrangement problem, whereby the target can be viewed as a desired 3D shape layout. Then part assembly

---

[1]More results at https://general-part-assembly.github.io

factorizes into two steps: predict a segmentation of the target, where each segment corresponds to a part, and infer the pose of each part with pose estimation. To predict accurate segmentation of the target, a key challenge is to deal with the ambiguities in the target shape due to geometrically equivalent parts (e.g., legs of a table). To infer accurate segmentations, we propose General Part Assembly Transformer (GPAT), a transformer-based model architecture, that processes input shapes in a fine-to-coarse manner, thereby ensuring consistent segmentation results.

To train and evaluate our model, we build a benchmark based on PartNet [5], a large-scale dataset of 3D objects with part information. We programmatically generate primitive part shapes as non-exact parts. In real-world scenarios, parts may take all possible poses to construct the target assembly. To best model this complexity, we evaluate our algorithm with targets given at random orientations. We demonstrate that GPAT generalizes well to entirely new target structures at random orientations and novel parts that are non-exact matches on both synthetic and real-world data.

In summary, our primary contributions are three-fold:

- We propose the task of general part assembly to study the ability of building novel targets with unseen parts.
- We tackle the planning problem for general part assembly as a goal-conditioned shape rearrangement problem – treating part assembly as an "open-vocabulary" (i.e., vocabulary of parts) target object segmentation task.
- We introduce General Part Assembly Transformer (GPAT) for assembly planning, which can be trained to generalize to novel and diverse target and part shapes.

We believe that GPAT is an exciting step for general part assembly – we discuss both its capabilities and limitations in the report. Code and data will be made available.

2   Related Work

Specialized Part Assembly. A number of learning-based methods have been proposed for part assembly, but they usually have limited generalization abilities, so we refer to them as specialized part assembly. Reinforcement learning (RL) has success in building part assembly for fixed targets [1, 2, 6] or seen categories [7]. They require costly trial-and-error in real-world or physics-based environments to extend to novel targets, and often require low-level state information during training and testing. Another line of work directly works with visual perception and learns shape correspondences, which has success in tasks like kit assembly [8, 9] and shape mating [10], but they have not tackled part assembly which involves more complex and diverse targets and parts. Previously, part assembly with category-level generalization is tackled with models based on graph neural network backbones [3, 4, 11]. In this work, we propose to tackle general part assembly with novel target and part shapes.

Part Assembly with Object Models. Physics-based part assembly assumes precise models and thus the goal poses of the parts are explicitly given or implicitly derived. However, obtaining the precise models is not always possible, and this requirement hinders quick generalization to novel targets and parts. We directly work with visual perception, the 3D point clouds, to predict the precise poses of the parts. With our prediction, one may apply physics-based assembly sequence planning [12, 13, 14, 15] and path planning [16, 17, 18, 19] to obtain a complete assembly plan.

Point cloud Registration. Point cloud registration estimates the transformation matrix between two point clouds from different views of the same 3D scene. Point cloud registration is traditionally solved by optimization-based methods and recently by learning-based methods [20]. If we represent target and part shapes as point clouds, general part assembly is is akin to point cloud registration but differs in two ways. First, general part assembly demands transformation matrices of multiple point clouds, requiring inter-part correlation consideration. Secondly, given the non-exact nature of the parts, significant challenges arise in ensuring the robustness of any registration method to be applied to the general part assembly. As demonstrated in Sec. 4, basic alterations to point cloud registration methods can't directly address general part assembly.

3 Approach

Given a target point cloud $\mathcal{T}$ and part point clouds $\{\mathcal{P}_i\}_{i=1}^N$ as inputs, where N denotes the number of input parts and varies for different shapes, the goal of our task is to predict a 6-DoF part pose $q_i \in SE(3)$ for each input part $\mathcal{P}_i$, forming a final part assembly, $\mathcal{P} = \bigcup_{i=1}^N q_i(\mathcal{P}_i)$, where $q_i(\mathcal{P}_i)$ denotes the transformed part point cloud. To tackle this problem, we propose to solve part assembly in two steps: target segmentation (Sec. 3.1) – which utilizes General Part Assembly Transformer (Sec. 3.2) to decompose the target into disjoint segments, each representing a transformed part – and pose estimation (Sec. 3.3) to obtain the final part poses.

3.1 Part Assembly by Target Segmentation

Given a target point cloud $\mathcal{T}$ and part point clouds $\{\mathcal{P}_i\}_{i=1}^N$ as inputs, we want to segment the target point cloud such that each segment corresponds to a part. From the segmentation, we can infer the part pose with pose estimation, which is a transformation from the part to the corresponding segment.

Figure 2: **Method Overview.**

Formally, we want to predict a set of disjoint segments $\{\mathcal{T}_i\}_{i=1}^N$ such that $\bigcup_{i=1}^N \mathcal{T}_i = \mathcal{T}$ and $\mathcal{T}_i \cap \mathcal{T}_j = \emptyset$ for $i \neq j$. Further $\{\mathcal{T}_i, \mathcal{P}_i\}_{i=1}^N$ represents a bipartite matching between the segments and the parts. Note that $\mathcal{T}_i = \emptyset$ may be empty, suggesting that the part $\mathcal{P}_i$ is not used in the assembly. The goal of target segmentation is to maximize the geometric resemblance for each pair with non-empty $\mathcal{T}_i$, as defined by the following minimization problem,

$$\{\mathcal{T}_i\}_{i=1}^N = \arg\min_{\mathcal{T}_i} \sum_{i=1, \mathcal{T}_i \neq \emptyset}^N \min_{q_i} dist(\mathcal{T}_i, q_i(\mathcal{P}_i))$$

where $dist$ is some distance metric for point clouds (e.g., chamfer distance). This may appear to be a detour since the goal of the task is the transformation q_i, which is implicitly optimized over. Nevertheless, a model can approximate $\min_{q_i} dist(\mathcal{T}_i, q_i(\mathcal{P}_i))$ by learning rotationally invariant representations of point clouds to avoid optimization over part poses. Finally, we can infer a part pose q_i by minimizing $dist(\mathcal{T}_i, q_i(\mathcal{P}_i))$.

3.2 General Part Assembly Transformer (GPAT)

The input to General Part Assembly transformer is a target point cloud and a set of part point clouds, and therefore model backbones designed for a single point cloud is insufficient for the task. GPAT uses PointNet [21] to extract initial features for the point clouds, and then leverages a transformer-based architecture [22] to jointly optimize over the target shape and the part shapes. To predict accurate target segmentation, a key challenge is the ambiguities in the target shape (e.g., the four legs of a chair are interchangeable). As a result, a target shape often admits multiple ground-truth segmentations, and a fine-grained and consistent segmentation of the target is required for successful assembly. In light of this, we design the GPAT layer to fully exploit the spatial structure of the target point cloud from a fine-to-coarse manner, which is inspired by the increasing receptive field of convolutional neural networks [23] and progress in hierarchical feature learning for point clouds [24, 25].

More formally, let the hidden dimension for features be h. For a query feature $\mathbf{q} \in \mathbb{R}^h$ and a set of k key features $\mathbf{K} \in \mathbb{R}^{k \times h}$, we denote the dot-product attention operator as

$$\text{Attention}(\mathbf{q}, \mathbf{K}) = W_v(\mathbf{K})^T \text{softmax}\left(\frac{W_k(\mathbf{K}) \cdot W_q(\mathbf{q})}{\sqrt{h}}\right)$$

where W_q, W_k, W_v are MLPs.

Given a target $\mathcal{T}$ and a set of parts $\{\mathcal{P}_i\}_{i=1}^N$, GPAT uses Pointnet to extract an initial target point feature $\mathbf{v}_t^0$ for each point $X_t \in \mathcal{T}$, and an initial part feature $\mathbf{u}_i^0$ for each part $\mathcal{P}_i$ (with max pooling). Then the features pass through L GPAT layers. At the $(n+1)$-th GPAT layer, we have a target point feature $\mathbf{v}_t^n$ for each point $X_t \in \mathcal{T}$ and part feature $\mathbf{u}_i^n$ for each part $\mathcal{P}_i$. The features are updated in three steps. The first step is multi-scale attention which is parameterized by a positive integer k and denoted by MultiScaleAttention$_k$ in Fig. 2. It updates the target point features as follows:

$$\overline{\mathbf{v}_t^n} = \text{Attention}(\mathbf{v}_t^n, \mathcal{N}_k(\mathbf{v}_t^n))$$

where $\mathcal{N}_k(\mathbf{v}_t^n)$ is the features of the k nearest neighbors of the target point X_t. GPAT gradually increases k to let each point receive global information of the point cloud. The second step is the multi-head attention [22], which updates the part features. In the final step, GPAT applies attention updates between the target point features and part point cloud features, denoted as CrossAttention in Fig. 2:

$$\mathbf{v}_t^{n+1} = \text{Attention}(\overline{\mathbf{v}_t^n}, \overline{\mathbf{U}^n}) \quad \mathbf{u}_i^{n+1} = \text{Attention}(\overline{\mathbf{u}_i^n}, \overline{\mathbf{V}^n})$$

where $\overline{\mathbf{V}^n}$ denotes all target point features and $\overline{\mathbf{U}^n}$ denotes all part point cloud features. Finally, GPAT models how likely a point X_t is matched with an input part $\mathcal{P}_i$ as

$$\mathbb{P}[X_t \in \mathcal{T}_i] = \frac{W_T(\mathbf{v}_t^L) \cdot W_P(\mathbf{u}_i^L)}{\sum_{j=1}^N W_T(\mathbf{v}_t^L) \cdot W_P(\mathbf{u}_j^L)}$$

where W_T and W_P are MLP projections.

Data Augmentation. In order to generalize to targets at random poses, we augment the dataset by randomly rotating the target point cloud but keep the order of the points. Thus the ground truth segmentation label is unchanged, which encourages the model to obtain rotationally invariant feature representations for the target. We always preprocess the input parts so that their principle axes are aligned with world axes. Further, to generalize to unseen categories and non-exact parts, the dataset needs to comprise diverse shapes. We programmatically generate rectangular and spherical primitive shapes of various sizes. For each data sample with exact parts, we construct a new sample with each exact part replaced with the primitive of the most similar sizes. GPAT is trained with both data samples of exact and non-exact parts. Assemblies with non-exact parts can be found in Fig. 3.

Training and Loss. To supervise GPAT, we use the per-point cross entropy loss between the predicted distribution over all parts and the ground truth label. Denote the ground truth segmentation by $\{\mathcal{T}_i^{gt}\}_{i=1}^N$, and the loss function is

$$\mathcal{L} = \sum_{t=1}^{|\mathcal{T}|} \log \mathbb{P}[X_t \in \mathcal{T}_i^{gt}]$$

For part assembly, there are often multiple ground-truth labels due to geometric equivalence between parts (e.g., legs of a chair). We enumerate all permutations of labels corresponding to the geometrically equivalent parts and adopt the lowest possible cost.

3.3 Predicting Part Assembly with Segmentation

Given a set of parts $\{\mathcal{P}_i\}_{i=1}^N$ and a segmentation of the target $\{\mathcal{T}_i\}_{i=1}^N$, we can find the 6-DoF part pose $q_i \in SE(3)$ for each part with pose estimation. Since the parts in our task are not necessarily exact, we use oriented-bounding boxes to estimate part poses which is simple and robust. For each non-empty $\mathcal{T}_i$, we use principle component analysis to find the oriented bounding boxes of $\mathcal{P}_i$ and $\mathcal{T}_i$ to solve for q_i. In practice, we improve the bounding box predictions by filtering the outliers (points that are at least one standard deviation away from the center) in $\mathcal{T}_i$.

	Unseen Instance								Unseen Category							
	Canonical Pose						Random Pose					Canonical Pose						Random Pose					
	Precise Part			Imprecise Part			Precise Part			Imprecise Part			Precise Part			Imprecise Part			Precise Part			Imprecise Part		
	CD	PA	SR	CD	PA	SR	CD	PA	SR	CD	PA	SR	CD	PA	SR	CD	PA	SR	CD	PA	SR	CD	PA	SR
Opt	7.9	18.3	2.4	10.0	16.0	0.9	**6.3**	22.9	3.7	**7.7**	21.0	2.8	**5.1**	23.1	5.7	**5.4**	21.3	4.7	**4.1**	31.3	6.7	**5.0**	28.4	4.2
Go-ICP	72.9	4.2	0.1	67.9	3.9	0.0	72.3	4.4	0.1	66.2	3.9	0.0	49.4	2.0	0.0	42.6	2.6	0.0	45.7	2.2	0.0	39.3	2.6	0.0
GeoTF	54.3	14.5	4.1	63.4	9.5	1.6	53.7	14.9	4.2	62.6	10.1	1.9	57.3	2.8	0.1	53.8	2.3	0.0	57.4	2.9	0.1	53.9	2.9	0.2
NSM	89.8	1.3	0.0	86.3	0.9	0.0	87.1	1.4	0.0	83.1	0.9	0.0	58.0	0.7	0.0	52.0	1.1	0.0	56.4	1.1	0.0	49.7	1.4	0.0
DGL	21.5	45.4	10.9	18.0	51.6	14.4	86.7	1.1	0.0	75.5	1.6	0.2	27.2	13.7	1.1	22.1	18.2	0.7	48.9	1.6	0.0	45.0	1.9	0.0
DGL-aug	53.4	6.7	0.6	44.3	8.1	0.5	52.3	7.0	0.6	44.0	8.7	0.2	31.3	7.3	0.1	26.4	9.3	0.3	28.4	8.5	0.2	23.9	11.1	0.3
Reg	33.6	3.1	0.3	33.5	3.2	0.5	25.6	5.0	0.2	25.7	5.8	0.5	34.5	1.9	0.0	31.4	3.3	0.2	19.0	5.4	0.1	18.7	5.0	0.2
TF	11.4	47.9	16.8	11.5	45.4	14.4	9.1	57.8	21.5	9.7	54.7	18.8	13.5	31.8	5.1	12.3	33.3	4.9	14.1	28.0	4.2	12.2	29.9	3.7
Ours	**7.6**	**61.6**	**23.2**	**7.2**	**64.8**	**26.0**	7.8	**60.8**	**21.7**	7.8	**64.3**	**26.0**	7.1	**53.4**	**20.1**	6.6	**56.3**	**21.7**	7.6	**52.2**	**18.8**	6.9	**55.6**	**19.8**

Table 1: **Quantitative Results and Comparisons.** We adopt three metrics: chamfer distance (CD) measured in ‰, part accuracy (PA) measured in %, and success rate (SR) measured in %.

4 Evaluation

Tasks. For both training and quantitative evaluation, we use PartNet [5], a large-scale dataset of 3D objects with fine-grained and instance-level 3D part information. We use chairs, lamps, and faucets for training and hold out tables and displays as novel categories. We deal with the most fine-grained level of PartNet segmentation, and adopt the default train/test split of the PartNet, which contains 2463 instances of chairs, 1553 instances of lamps, and 510 instances of faucets. We categorize generalization scenarios across three dimensions.

- **Novel target instances or categories:** We evaluate on the unseen instances of chairs, lamps, and faucets, and two novel categories: tables and displays.

- **Random target poses:** We evaluate on targets at either canonical orientation (as defined in the dataset) or a random orientation uniformly sampled from $SO(3)$.

- **Non-exact parts:** Besides exact parts from the dataset, we programatically generated rectangular and spherical blocks as non-exact parts. Sample instances can be found in Fig. 3.

Metrics. For all the tasks, we measure the quality of the predicted assembly with three metrics: chamfer distance, part accuracy, and assembly success rate.

- **Chamfer distance (CD):** Given two point clouds $\mathcal{A}, \mathcal{B}$, the chamfer distance between $\mathcal{A}$ and $\mathcal{B}$ is

$$CD(\mathcal{A}, \mathcal{B}) = \sum_{x \in \mathcal{A}} \min_{y \in \mathcal{B}} ||x - y||_2^2 + \sum_{x \in \mathcal{A}} \min_{y \in \mathcal{B}} ||x - y||_2^2$$

  We use $CD(\mathcal{T}, \mathcal{P})$ as a metric, abbreviated as CD, where $\mathcal{T}$ is the target point cloud, and $\mathcal{P} = \bigcup_{i=1}^{N} q_i(\mathcal{P}_i)$ where q_i is the predicted pose for the i-th part.[2]

- **Part accuracy (PA):** Adopted from the previous work [4], part accuracy is defined as,

$$\frac{1}{N} \sum_{i=1}^{N} \mathbb{1}\left(CD(q_i^{GT}(\mathcal{P}_i), q_i(\mathcal{P}_i)) < \tau_P\right)$$

  where q_i^{GT} is the ground truth pose of the i-th part, $\tau_p = 0.01$. This metric indicates the percentage of the predicted parts that match the GT part up a certain threshold measured in chamfer distance. Due to possible geometric equivalence between parts (e.g., the legs of a chair), we enumerate all possible labels of geometrically equivalent parts to obtain different GT poses and take the highest accuracy value.

- **Assembly Success Rate (SR):** A predicted assembly is considered successful if its part accuracy (PA) is equal to 1. We report the percentage of successful predictions out of all data samples as the assembly success rate (SR).

Algorithm comparisons. Since general part assembly is a novel task, there are no previous methods specifically solving the task. We adapt methods for point cloud registration and specialized part assembly and compare with variants of our method for ablation studies.

---

[2]Note that in the previous work [4], 'shape chamfer distance' is defined differently with $\mathcal{T} = \bigcup_{i=1}^{N} q_i^{GT}(\mathcal{P}_i)$. In our tasks, the target is not a union of the given parts, so the values according to our metric are usually larger.

- **Opt:** Covariant matrix adaptation evolution strategy (CMA-ES) [26] is used to optimize the poses of each part by minimizing the chamfer distance CD as defined above.
- **Go-ICP**: We greedily match each part point cloud to the target point cloud using Go-ICP [27].
- **GeoTF**: Geometric Transformer (GeoTF) [28] is one of the SoTA methods for point cloud registration. We modify the algorithm to simultaneously optimize for all part poses.
- **NSM**: Neural Shape Mating (NSM) [10] uses a transformer-based model to solve pairwise 3D geometric shape mating such as reconstruct two broken pieces of an object. We modify their algorithm to match each part to the target and simultaneously optimize for all part poses.
- **DGL**: Dynamic Graph Learning (DGL) [4] tackles category-level part assembly by leveraging an iterative graph neural network backbone to regress part poses. Designed for category-level generalization, DGL does not take in the target shape as an input. To adapt to our task, we include the target encoding as a node into the graph neural network framework. DGL is trained only with targets at canonical poses following the previous work. DGL-aug uses the same training dataset as our model, with augmentation of targets at random poses.
- **Reg:** Instead of predicting a segmentation of the target for the subsequent pose estimation, we replace the final dot-product segmentation layer of our model with MLPs to directly regress a 6DoF pose for each part. We trained the modified model with the supervision of GT poses.
- **TF:** As an ablation, we replace each GPAT layer with a vanilla transformer layer [22].

5   Experimental Results

Tab. 1 and Fig. 3 summarizes the main quantitative and qualitative results, and the following sections provide detailed discussions. Please refer to the supplementary materials for more results.

Part assembly by target segmentation is more generalizable. The optimization baseline (Opt) achieves the lowest chamfer distance (CD) in some scenarios, but its part accuracy (PA) and success rate (SR) are significantly lower. Directly optimizing the part poses often result in predictions at local minima where the predicted assembly matches the contour of the target, but the assembly makes no semantic sense. (Please refer to supplementary materials for an example.)
As a classical optimization-based algorithm, Go-ICP tries to match individual part to the entire target which fails with no surprises. As a learning-based method, GeoTF achieves better performances for seen categories, but fails nonetheless for unseen categories. Since the parts are non-exact, it is challenging for point cloud registration methods to find suitable correspondences either in spacial coordinates or a learned feature space.
GPAT also outperforms regression-based models (DGL, DGL-aug, NSM, Reg) across all the tasks, especially at scenarios that requires more generalization (Tab. 1 and Fig. 3). For the most challenging scenario, regression-based models achieve less than 1% success rate, while GPAT has 19.8% success rate which is attained for all the test scenarios. To directly regress poses, a model needs to learn rotationally equivariant features for the target shape. However, given non-exact parts, unseen categories, and targets at random poses, we show that the regression-based models fail to capture the distribution of poses. They either overfit certain canonical poses and assembly structures or fail to learn. In contrast, GPAT, a segmentation-based model, is trained to learn rotationally invariant representations of the shapes, and thus it experiences minor performance drops facing generalization scenarios. Further, training with diverse shapes makes the representations generalizable and applicable to new categories.

GPAT is robust against targets with ambiguities. Compared to the alternative segmentation-based model using vanilla transformer, GPAT achieves better results for all test scenarios, especially for unseen target categories (Tab. 1 and Fig. 3). We compare the segmentation accuracy and show the results in Tab. 2 and visualize a typical failure case of TF in Fig. 5. When facing inputs with multi-model ground truths (e.g., a chair with identical legs), TF is unable to produce consistent segmentation, which hinders successful assembly prediction. With GPAT layers, we fully leverage the point cloud structure and process the point cloud in a fine-to-coarse manner, thereby achieving local consistency of the segmentation predictions.

Figure 3: **Assembly Results and Comparisons**. For targets at random poses, targets and predictions are transformed to be *visualized at canonical poses* for better understanding. Please see Fig. 4 for more results of randomly oriented targets. The optimization-based approach (Opt and Go-ICP) tends to stuck at local minima. The learning-based alternatives (GeoTF, NSM, DGL, Reg) overfit the training scenarios and fail to learn rotationally equivariant features for target shapes that are necessary for accurate pose inference. The alternative segmentation-based model that uses the vanilla transformer (TF) fails to produce consistent segmentations for targets with geometrically equivalent parts (see Fig. 5 for a detailed example). With the multi-scale attention layer, GPAT fully leverages the spatial structure of the target point clouds to produce consistent segmentations and accurate assemblies.

Figure 4: **Assembly Results for Targets at Random Orientations.** We show more results for the same targets in Fig. 3 but at random orientations. GPAT is robust against the orientation of the target shape. More results can be found in the supplementary materials.

GPAT solves generalizes well to real-world data. We use the real-world scans from redwood dataset [29] as targets and part point clouds from PartNet. As seen in Fig 6, our method produces diverse assemblies that resemble the target. This result also illustrates how GPAT can be used to assemble different sets of parts given a single target shape from the category.

Figure 5: **GPAT is robust against ambiguities.**

	Unseen Instance				Unseen Category			
	Canonical Pose		Random Pose		Canonical Pose		Random Pose	
	Prc	Imp	Prc	Imp	Prc	Imp	Prc	Imp
TF	70.0	62.2	76.5	69.2	63.7	62.4	62.9	60.9
Ours	**76.7**	**70.9**	**76.6**	**71.1**	**69.5**	**69.3**	**69.6**	**69.5**

Table 2: **Segmentation Accuracy (%)**

Figure 6: **Results on Real-world Data**

Failure mode analysis. GPAT is not without limitations, and Fig. 7 shows some typical failure cases. First, GPAT tends to give incorrect segmentation predictions if some parts are hidden inside a larger part (e.g., the light bulbs in a lamp) or the parts are less separable (e.g., overlapping parts of a microwave). To solve with these issues, it is possible to introduce additional information like colors and normals of the point clouds as inputs. Additionally, oriented bounding box can be insufficient as a pose estimation method for some parts. To tackle this problem, a learning-based pose estimation module can potentially replace the bounding box procedure.

Figure 7: **Typical Failure Cases.**

6 Conclusion

In this work, we formulate the task of general part assembly, which focuses on building novel target assemblies with diverse and unseen parts. To plan for a general part assembly task, we propose General Part Assembly Transformer (GPAT) and factorizes the task into target segmentation and pose estimation. Our experiments show that GPAT performs well under all the generalization scenarios. By integrating with an assembly sequence and motion planning algorithm, we believe that GPAT has great potential in building vision-based general robotic assembly systems.

References

[1] G. Thomas, M. Chien, A. Tamar, J. A. Ojea, and P. Abbeel. Learning robotic assembly from cad. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3524–3531. IEEE, 2018. 1, 2

[2] Y. Narang, K. Storey, I. Akinola, M. Macklin, P. Reist, L. Wawrzyniak, Y. Guo, A. Moravanszky, G. State, M. Lu, et al. Factory: Fast contact for robotic assembly. *arXiv preprint arXiv:2205.03532*, 2022. 1, 2

[3] Y. Li, K. Mo, L. Shao, M. Sung, and L. Guibas. Learning 3d part assembly from a single image. In *European Conference on Computer Vision*, pages 664–682. Springer, 2020. 1, 2

[4] G. Zhan, Q. Fan, K. Mo, L. Shao, B. Chen, L. J. Guibas, H. Dong, et al. Generative 3d part assembly via dynamic graph learning. *Advances in Neural Information Processing Systems*, 33:6315–6326, 2020. 1, 2, 5, 6

[5] K. Mo, S. Zhu, A. X. Chang, L. Yi, S. Tripathi, L. J. Guibas, and H. Su. Partnet: A large-scale benchmark for fine-grained and hierarchical part-level 3d object understanding. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 909–918, 2019. 2, 5

[6] S. K. S. Ghasemipour, S. Kataoka, B. David, D. Freeman, S. S. Gu, and I. Mordatch. Blocks assemble! learning to assemble with large-scale structured reinforcement learning. In *International Conference on Machine Learning*, pages 7435–7469. PMLR, 2022. 2

[7] M. Yu, L. Shao, Z. Chen, T. Wu, Q. Fan, K. Mo, and H. Dong. Roboassembly: Learning generalizable furniture assembly policy in a novel multi-robot contact-rich simulation environment. *arXiv preprint arXiv:2112.10143*, 2021. 2

[8] K. Zakka, A. Zeng, J. Lee, and S. Song. Form2fit: Learning shape priors for generalizable assembly from disassembly. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 9404–9410. IEEE, 2020. 2

[9] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, et al. Transporter networks: Rearranging the visual world for robotic manipulation. In *Conference on Robot Learning*, pages 726–747. PMLR, 2021. 2

[10] Y.-C. Chen, H. Li, D. Turpin, A. Jacobson, and A. Garg. Neural shape mating: Self-supervised object assembly with adversarial shape priors. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12724–12733, 2022. 2, 6

[11] A. Narayan, R. Nagar, and S. Raman. Rgl-net: A recurrent graph learning framework for progressive part assembly. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 78–87, 2022. 2

[12] L. H. De Mello and A. C. Sanderson. A correct and complete algorithm for the generation of mechanical assembly sequences. In *1989 IEEE International Conference on Robotics and Automation*, pages 56–57. IEEE Computer Society, 1989. 2

[13] C. Sinanoğlu and H. R. Börklü. An assembly sequence-planning system for mechanical parts using neural network. *Assembly Automation*, 2005. 2

[14] Y. Huang, C. R. Garrett, I. Ting, S. Parascho, and C. T. Mueller. Robotic additive construction of bar structures: Unified sequence and motion planning. *Construction Robotics*, 5(2):115–130, 2021. 2

[15] Y. Tian, J. Xu, Y. Li, J. Luo, S. Sueda, H. Li, K. D. Willis, and W. Matusik. Assemble them all: Physics-based planning for generalizable assembly by disassembly. *ACM Transactions on Graphics (TOG)*, 41(6):1–11, 2022. 2

[16] R. H. Wilson and J.-C. Latombe. Geometric reasoning about mechanical assembly. *Artificial Intelligence*, 71(2):371–396, 1994. 2

[17] D. Halperin, J.-C. Latombe, and R. H. Wilson. A general framework for assembly planning: The motion space approach. In *Proceedings of the fourteenth annual symposium on Computational geometry*, pages 9–18, 1998. 2

[18] S. Sundaram, I. Remmler, and N. M. Amato. Disassembly sequencing using a motion planning approach. In *Proceedings 2001 ICRA. IEEE International Conference on Robotics and Automation (Cat. No. 01CH37164)*, volume 2, pages 1475–1480. IEEE, 2001. 2

[19] X. Zhang, R. Belfer, P. G. Kry, and E. Vouga. C-space tunnel discovery for puzzle path planning. *ACM Transactions on Graphics (TOG)*, 39(4):104–1, 2020. 2

[20] X. Huang, G. Mei, J. Zhang, and R. Abbas. A comprehensive survey on point cloud registration. *arXiv preprint arXiv:2103.02690*, 2021. 2

[21] C. R. Qi, H. Su, K. Mo, and L. J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 652–660, 2017. 3

[22] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017. 3, 4, 6

[23] A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017. 3

[24] C. R. Qi, L. Yi, H. Su, and L. J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017. 3

[25] H. Zhao, L. Jiang, J. Jia, P. H. Torr, and V. Koltun. Point transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 16259–16268, 2021. 3

[26] N. Hansen, Y. Akimoto, and P. Baudis. CMA-ES/pycma on Github. Zenodo, DOI:10.5281/zenodo.2559634, Feb. 2019. URL https://doi.org/10.5281/zenodo.2559634. 6

[27] J. Yang, H. Li, D. Campbell, and Y. Jia. Go-icp: A globally optimal solution to 3d icp point-set registration. *IEEE transactions on pattern analysis and machine intelligence*, 38(11): 2241–2254, 2015. 6

[28] Z. Qin, H. Yu, C. Wang, Y. Guo, Y. Peng, and K. Xu. Geometric transformer for fast and robust point cloud registration. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11143–11152, 2022. 6

[29] S. Choi, Q.-Y. Zhou, S. Miller, and V. Koltun. A large dataset of object scans. *arXiv preprint arXiv:1602.02481*, 2016. 8