WebSync: A Self-Evolving Web Agent Framework for Co-Evolving Strategic Advice and Executable Skills

Abstract

With the advent of large language models, autonomous web agents have achieved more sophisticated capabilities in planning, reflecting, and tool using, enabling automating navigation in complex and dynamic web environments. Despite this, existing efforts to instill experiential learning through memory-centric retrieval or skill-centric synthesis are respectively limited by computational inefficiency and a lack of robustness, preventing web agents from truly self-evolving. To tackle this problem, we introduce a novel web agent framework called **WebSync**, which is designed to unify strategic advice and skill synthesis through a structured skill recipe to compile experience into executable skills more efficiently and robustly. Furthermore, it enables continuous self-evolving by using runtime feedback to trigger iterative recipe and skill refinement, thus achieving a robust transition from trial-and-error reasoning to proven execution. Experimental results on WebArena and WebVoyager benchmarks demonstrate the superiority and versatility of **WebSync** across multiple backbone large language models.

1 Introduction

Large Language Models (LLMs) significantly advance web automation by enabling agents to navigate complex and dynamic environments with sophisticated planning, reflection, and tool-use capabilities (Zhou et al., 2023; He et al., 2024; Deng et al., 2023, 2024; Luo et al., 2025; Ning et al., 2025). Despite these advances, existing web agents lack sufficient experiential learning, trapping them in a "solve-once, forget-again" cycle where routine tasks never become more efficient over time, and agents repeat costly trial-and-error reasoning for familiar scenarios.

To endow web agents with experiential learning, prior research has pursued two distinct paradigms. 1) **Memory-centric approaches** (Ouyang et al.,

Figure 1: The workflow of WebSync. Unlike the **Base** method (top), which relies on inefficient step-by-step ReAct reasoning for primitive actions (e.g., `click`, `input`), **WebSync** (bottom) significantly reduces interaction steps by integrating strategic advice with executable skills. This allows the agent to transition from granular trial-and-error to robust, high-level function calls (e.g., `search()`).

2025; Wang et al., 2024; Liu et al., 2025a) retrieve prior experiences—execution logs or refined summaries—to guide planning and acting. While improving adaptability, this approach remains computationally expensive as agents must re-interpret unstructured memories and re-reason through each step. 2) **Skill-centric approaches** (Wang et al., 2025; Zheng et al., 2025; Yu et al., 2025) synthesize executable tools directly from successful trajectories. However, skill synthesis remains an isolated trace-to-code pipeline, structurally disconnected from strategic reasoning, yielding tools that lack runtime safeguards and *fail silently* under interface changes.

These two paradigms, though seemingly opposed, capture *complementary* knowledge layers: memory encodes *strategic wisdom*—when to act, what to avoid, and how to recover—providing adaptability, while skills encode *executable procedures* that bypass step-by-step reasoning, provid-

ing efficiency. In isolation, each inherits a critical blind spot: memory without skills forces costly re-derivation of execution plans (*efficiency bottleneck*), while skills without strategic grounding lack awareness of their own applicability boundaries and failure modes (*safety bottleneck*). The fundamental gap is therefore the absence of a formal mechanism that compiles strategic wisdom into executable skills with enforceable runtime contracts.

To bridge this gap, we introduce WebSync, a self-evolving framework that compiles experiential knowledge into *Skill Recipes*—formal contracts specifying *when* a skill applies (trigger conditions), *what* it requires (parameter schemas), *how* to verify success (postconditions), and *how* to recover from failures (fallback strategies). WebSync maintains two co-evolving repositories—an *Advice Library* for strategic knowledge and a *Skill Library* for executable procedures—where recipes act as hard constraints during skill generation and semantic guardrails during reuse, as shown in Figure 1. Runtime feedback continuously triggers recipe refinement, creating a closed loop where the two repositories co-evolve and harden with use, transforming loose experiential guidelines into defensive, context-aware tools.

Our contributions are summarized as follows:

- We present **WebSync**, a self-evolving framework that integrates memory-based guidance and executable skills into a unified learning loop. By formalizing strategic advice as explicit contracts called *Skill Recipe*, WebSync enables agents to progressively transition from costly *System 2* reasoning to efficient *System 1* execution.

- We propose **Recipe-Instructed Skill Synthesis**, a mechanism in which strategic advice acts as hard constraints for skill parameterization and verification. This approach transforms ephemeral traces into defensive, production-ready procedures and mitigates the brittleness of naive trace cloning.

- Extensive experiments on **WebArena** and **WebVoyager** across multiple backbone LLMs demonstrate that WEBSYNC consistently outperforms existing methods, achieving up to a 14.5% absolute gain in success rate and a nearly 40% reduction in interaction steps, confirming that recipe-guided skills attain high robustness along-

side execution efficiency. Our code will be released via `https://anonymous.4open.science/r/WebSync-5DF1/`.

2 Related Work

Web Agents LLM-driven agents have evolved into general-purpose assistants that integrate text and visual signals to navigate complex environments (Yao et al., 2022a; He et al., 2024; Zhou et al., 2023; Deng et al., 2023). To enhance reliability, recent approaches have incorporated supervised fine-tuning (SFT) (Luo et al., 2025; Furuta et al., 2024; Zheng et al., 2024; Lai et al., 2024), reinforcement learning (RL) (Wei et al., 2025; Liu et al., 2025b; Qin et al., 2025; Qi et al., 2024), and explicit planning mechanisms (Zhang et al., 2025b; Fang et al., 2025). However, these systems typically operate in a memory-less manner, treating every task instance as a novel problem. This results in redundant, computationally expensive reasoning for routine activities, underscoring the necessity for experiential learning mechanisms.

Self-Evolving Agents Rather than relying on expensive model re-training, self-evolving agents autonomously refine their capabilities by accumulating experience. By leveraging foundational techniques such as natural language reflection, trajectory optimization, and automated tool synthesis, these systems continuously adapt within open-ended environments (Gao et al., 2025; Zhang et al., 2025a; Zhao et al., 2024; Qiu et al., 2025; Lin et al., 2025). In the domain of autonomous web navigation, such strategies generally manifest in two distinct paradigms: (i) **Memory-Centric Evolution** (Liu et al., 2025a; Ouyang et al., 2025; Wang et al., 2024) which guides planning by retrieving historical insights that range from raw logs to optimized reasoning paths. While adaptable, these methods remain inference-heavy because they require costly re-reasoning even for familiar routines. (ii) **Skill-Centric Evolution** (Zheng et al., 2025; Wang et al., 2025; Yu et al., 2025), which compiles successful trajectories into executable tools. However, as this process often treats synthesis as a simple translation from traces to code, it tends to yield brittle tools that fail under minor interface changes. In this paper, we introduce WebSync, a unified framework that synergizes strategic advice (Memory) with Executable Skills (Skill) via formal recipes.

Figure 2: **Overview of WEBSYNC.** It consists of three stages: (1) **Advice Distillation** ($\tau, x \to A$), where interaction traces are compiled into high-level strategic advice; (2) **Recipe Formulation** ($A \to S$), where advice is formalized into a strict contract defining preconditions, postconditions, and recovery logic; and (3) **Recipe-Instructed Skill Consolidation** ($S, \tau \to f$), where defensive executable tools are generated. The top loop illustrates the continuous consolidation process that refines recipes and hardens tools based on runtime feedback.

3 WebSync

We formulate the autonomous web navigation task as a Partially Observable Markov Decision Process (POMDP). An interaction episode begins with a natural language instruction x and a starting web state s_0. At each time step t, the agent receives an observation o_t (encompassing rendered content and DOM structure), selects an action a_t, and transitions to a new state s_{t+1}, generating a trajectory $\tau = (o_0, a_0, \ldots, o_T)$. To address the inefficiency of low-level operations, we define a hybrid action space $\mathcal{A} = \mathcal{A}_p \cup \mathcal{A}_f$. Here, $\mathcal{A}_p$ represents primitive browser actions (e.g., click, input), while $\mathcal{A}_f$ consists of parameterized executable skills $f(\theta; o_t)$. Each skill encapsulates a multi-step subroutine, enabling the agent to reason at a strategic level while offloading routine execution.

3.1 Architecture

WebSync reconciles the inherent trade-off between flexible but costly reasoning (System 2) and efficient but often brittle execution (System 1). A core design principle is that once a strategy has been validated through experience, its execution should be offloaded to deterministic procedures equipped with environment-facing verification (e.g., DOM state queries, URL parameter checks), rather than re-entrusted to the model's probabilistic reasoning. Rather than treating memory retrieval and

tool synthesis as isolated pipelines, our framework unifies them into a continuous loop. Importantly, the entire pipeline—exploration, advice distillation, recipe formulation, and skill synthesis—is executed by *the same backbone LLM* without relying on any stronger external model, making WebSync a genuinely self-evolving system. The framework operates in an *online* setting: as the agent sequentially processes tasks, it progressively accumulates recipes and skills, following the same continual-learning protocol adopted by prior self-evolving baselines (Zheng et al., 2025; Liu et al., 2025a). As illustrated in Figure 2, this process transforms ephemeral interaction traces into durable capabilities through three formalized stages.

Advice Distillation. Initially, the agent employs System 2 reasoning to explore the environment, generating an interaction trajectory $\tau = (o_0, a_0, \ldots, o_T)$ given an instruction x. Crucially, WebSync learns not only from success but also from failure. The framework distills the experience into the **Advice Library** ($\mathcal{M}_A$), where successful traces (τ^+) provide reusable procedural templates ("how to succeed"), while failed traces (τ^-) contribute critical constraints and failure patterns ("what to avoid"), such as hidden overlays, timing issues, or unclickable elements:

$$A \leftarrow \text{Distill}(\tau, x), \quad \mathcal{M}_A \leftarrow \mathcal{M}_A \cup \{A\} \quad (1)$$

Field	Description & Logic
Name	Canonical skill name (e.g., search, apply_filter, add_to_cart).
Trigger (σ)	Domain + URL patterns + page markers for applicability indexing.
Preconditions ($\mathcal{P}$)	Predicates that must hold before execution (e.g., is_visible(search_box)).
Params (Θ)	Argument schema with types, constraints, and grounding hints.
Postconditions ($\mathcal{Q}$)	Verifiable success evidence (e.g., count_changed(cart)).
Failure Sigs ($\mathcal{F}$)	Detectable failure predicates (modal, login redirect, timeout).
Recovery ($\mathcal{R}$)	Failure $\rightarrow$ recovery actions (close modal, wait/retry).
Bindings ($\mathcal{B}$)	Tool implementations with versions and performance statistics.

Table 1: **Skill Recipe Card.** The skill recipe S standardizes the intent, applicability, and verification logic, serving as the governing contract for the implementation.

This dual-source mechanism converts unstructured interaction logs into structured procedural knowledge that captures both effective strategies and their boundary conditions.

Skill Recipe Formulation. To operationalize the abstract advice A, the system formalizes it into a Skill Recipe (S). Unlike a simple prompt, S acts as a rigorous contract containing five semantic components: applicability triggers (σ), preconditions (P), parameter schemas (Θ), postconditions (Q), and recovery logic (R), as shown in Table 1.

$$S = \langle \sigma, P, \Theta, Q, R \rangle \leftarrow \text{Formulate}(A) \quad (2)$$

This tuple serves as the governing specification: P and Q define the boundaries of valid execution, while R provides the self-correction logic derived from prior failures. Unlike trace-to-code approaches such as PolySkill (Yu et al., 2025), which synthesize tools directly from trajectories without execution contracts, WebSync couples advice-derived constraints with skill implementations through a shared formal recipe, ensuring built-in runtime safeguards.

Skill Synthesis. Finally, WEBSYNC synthesizes an executable skill function f for the Skill Library ($\mathcal{M}_S$). Rather than naively cloning a demonstrated trajectory, the synthesizer uses S as a hard constraint to reconstruct a defensive procedure from the raw trace τ, embedding $\mathcal{P}$ as runtime assertions

and $\mathcal{R}$ as exception handlers:

$$f(\cdot; \Theta) \leftarrow \text{Synthesize}(\tau | S)$$
$$\text{s.t.} \quad \forall o, \mathcal{P}(o) \implies \mathcal{Q}(f(o)) \quad (3)$$

The resulting tool is committed to $\mathcal{M}_S$ only after passing validation against $\mathcal{Q}$, ensuring the agent evolves from probabilistic reasoning to deterministic, defensive execution. We detail the full consolidation pipeline in §3.2.

3.2 Recipe-Instructed Skill Consolidation

Consolidation serves as the evolutionary engine of WebSync, converting candidate traces into robust, reusable skills. Unlike naive cloning strategies, our process treats the Skill Recipe as a governing contract, ensuring that synthesized tools are not merely executable but robust by design. The process unfolds in four distinct stages:

Candidate Trace Selection. During inference, the agent logs execution segments $\tau = (o_{t_0}, a_{t_0}, \ldots, o_{t_1})$ for *successful* subgoals as candidates for skill synthesis. While the executable skill code is derived from these successful segments, the recipe constraints ($\mathcal{P}$, $\mathcal{Q}$, $\mathcal{R}$) that govern synthesis are informed by the Advice Library, which incorporates evidence from both successes and prior failures (see Evidence-Based Recipe Refinement below). To maintain a high-quality library, consolidation is triggered only when a segment satisfies strict reuse heuristics: (1) *Recurrence*, where the intent/signature pair appears frequently; (2) *Utility*, indicating that compressing the segment offers significant step savings; and (3) *Stability*, ensuring argument slots are consistently inferable across episodes.

Evidence-Based Recipe Refinement. Prior to code synthesis, the system leverages accumulated failure evidence to progressively harden the recipe—each observed failure tightens the contract rather than being discarded, making subsequent skills inherently immune to previously encountered failure modes:

- **Tightening Preconditions** (P)**:** If prior failures were caused by missing affordances (e.g., an absent filter panel), predicates are added to explicitly screen out such invalid contexts.

- **Strengthening Postconditions** (Q)**:** To prevent false positives, verification logic is updated to require stricter evidence, such as specific text updates or DOM state changes.

Constraint-Injecting Skill Synthesis. The system synthesizes a parameterized procedure f using the refined recipe as a hard constraint. Specifically, the synthesizer employs the schema Θ to define the function signature, injects P and Q as runtime assertions for defensive execution, and incorporates failure signatures $\mathcal{F}$ to generate recovery branches. This mechanism ensures the output is a robust program capable of handling exceptions, rather than a fragile replay script.

Recipe-Based Validation. Newly synthesized tools undergo a validation phase using the recipe's postconditions Q as an automated oracle. The tool is committed to the Skill Library ($\mathcal{M}_S$) only if it consistently satisfies Q in matching contexts, thereby preventing defective skills from polluting the agent's memory.

3.3 Recipe-Informed Inference

At inference time, recipes couple retrieval, planning, and execution into a *capability-aligned* pipeline.

Retrieval and Planning. At each step t, given instruction x and state signature $\sigma(s_t)$, the agent retrieves relevant recipes $\mathcal{S}_t \leftarrow \mathrm{Retrieve}(\mathcal{M}_A, x, \sigma(s_t))$, which provide plan templates and executable predicates for applicability. The agent then generates a short-horizon plan $\mathbf{g} = (g_1, \ldots, g_K)$ with candidate skill anchors for each subgoal:

$$\mathbf{g}, \{S_k\} \leftarrow \mathrm{Plan}(x, o_t, \mathcal{S}_t). \quad (4)$$

Tool Mapping and Grounding. For each subgoal, the agent filters candidate tools by precondition checks:

$$\mathcal{F}_S^{\mathrm{app}} = \{f \in \mathcal{B}_S \mid \forall \phi \in \mathcal{P}_S, \ \phi(o_t) = \mathrm{true}\}. \quad (5)$$

If $\mathcal{F}_S^{\mathrm{app}}$ is empty, the agent falls back to primitives, preventing execution in invalid states. Arguments θ are grounded according to schema Θ_S and validated against type constraints before invocation.

Execution with Verification. During execution, WEBSYNC monitors progress via *environment-facing checks*—DOM queries, URL pattern matching, and element attribute verification—rather than LLM-based textual judgments. This enables deterministic detection of silent failures that text-based reasoning would miss:

Benchmark	# Tasks	Domains
WEBARENA	655	4 self-built websites
WEBVOYAGER	643	15 live sites

Table 2: Statistics of the benchmarks. We use the standard subset of 655 tasks for WebArena and the full set of 643 tasks for WebVoyager.

- **Postcondition Check:** Evaluates $\mathcal{Q}_S$ on the resulting observation $o_{t'}$ to verify success (e.g., checking `aria-checked` attributes or cart count changes).

- **Failure Detection & Recovery:** If $\mathcal{Q}_S$ fails, evaluates signatures $\mathcal{F}_S$ to identify failure modes and applies the corresponding recovery action $\mathcal{R}_S[f]$ (e.g., close modal and retry).

4 Experiments

4.1 Setup

Evaluation Benchmarks. We evaluate WebSync on two complementary benchmarks. First, we use WEBARENA (Zhou et al., 2023), a self-hosted environment, where we strictly follow the standard protocol by focusing on the 655 tasks across four domains (Shopping, Admin, GitLab, Reddit) to isolate reasoning capabilities. Second, to test robustness in open-world conditions, we employ WEBVOYAGER (He et al., 2024) on the live web, handling dynamic content via the `browser-use` interface. The details of dataset statistics are presented in Table 2.

Base Models & Baselines. Our web agent operates within a standard ReAct-style (Yao et al., 2022b) loop. For controlled comparison on WEBARENA, we use CLAUDE-3.7-SONNET (Anthropic, 2024) as the primary backbone and additionally evaluate on GPT-4.1 and GLM-4.5 to verify cross-model generalization. On WEBVOYAGER, we evaluate with GPT-4O (Hurst et al., 2024), CLAUDE-3.7-SONNET, QWEN3-VL-8B (Bai et al., 2025), and QWEN2.5-VL-7B. We compare against state-of-the-art self-evolving web agent frameworks spanning both paradigms: memory-centric methods AWM (Wang et al., 2024) and REASONINGBANK (Ouyang et al., 2025), and skill-centric methods SKILLWEAVER (Zheng et al., 2025), POLYSKILL (Yu et al., 2025), and ASI (Wang et al., 2025). On WebVoyager, we addition-

Method	Shopping		Admin		Gitlab		Reddit		Overall	
	SR	*Step*	*SR*	*Step*	*SR*	*Step*	*SR*	*Step*	*SR*	*Step*
Claude-3.7-Sonnet										
Claude-3.7-Sonnet (Anthropic, 2024)	38.5	6.1	49.5	8.4	36.7	10.6	53.8	5.5	43.5	7.9
AWM (Wang et al., 2024)	39.6	7.2	47.8	9.3	34.6	10.9	52.8	7.0	42.6	8.8
SkillWeaver (Zheng et al., 2025)	46.2	4.4	52.7	5.3	55.1	7.2	72.5	5.0	54.7	5.5
ASI (Wang et al., 2025)	59.1	3.6	61.3	5.6	64.2	6.4	78.5	4.8	64.3	5.1
PolySkill (Yu et al., 2025)	58.3	3.3	63.5	–	62.5	–	80.4	–	64.5	–
ReasoningBank (Ouyang et al., 2025)	44.9	5.6	53.3	7.6	41.1	9.5	57.5	5.2	48.2	7.2
WebSync (Ours)	**64.2**	**3.1**	**67.5**	**4.2**	**65.8**	**5.5**	**81.8**	**4.7**	**68.4**	**4.3**
GPT-4.1										
GPT-4.1 (Hurst et al., 2024)	37.4	8.3	44.0	8.8	38.9	11.0	66.0	6.0	44.3	8.3
SkillWeaver (Zheng et al., 2025)	39.3	4.8	48.2	5.8	50.3	8.0	71.2	5.8	50.0	6.1
ASI (Wang et al., 2025)	46.3	4.0	53.6	6.0	46.8	7.0	73.7	5.5	52.9	5.6
PolySkill (Yu et al., 2025)	51.4	–	54.8	–	54.2	–	73.2	–	56.6	–
WebSync (Ours)	**54.5**	**3.4**	**58.2**	**4.5**	**57.5**	**5.8**	**76.4**	**4.8**	**59.9**	**4.6**
GLM-4.5										
GLM-4.5 (Zeng et al., 2025)	36.1	8.7	40.9	9.2	37.5	11.5	59.4	6.5	41.6	8.7
SkillWeaver (Zheng et al., 2025)	34.2	5.2	39.7	6.2	39.1	8.5	54.8	6.4	40.4	6.6
ASI (Wang et al., 2025)	38.6	4.5	43.7	6.5	40.8	7.5	62.5	6.0	44.5	6.1
PolySkill (Yu et al., 2025)	39.4	–	44.5	–	41.6	–	63.2	–	45.3	–
WebSync (Ours)	**42.5**	**3.8**	**47.8**	**5.0**	**45.5**	**6.2**	**66.8**	**5.2**	**48.7**	**5.0**

Table 3: **Results on WebArena** (655 tasks across 4 domains). SR (↑) denotes success rate and Step (↓) denotes average interaction steps. Overall SR and Step are the weighted averages over the four domains based on the number of tasks. "–" indicates results not reported or not available (e.g., closed-source method).

ally compare with WEBCOACH (Liu et al., 2025a). For WebArena, most baseline results are adopted directly from the respective original papers under aligned evaluation protocols; however, for Skill-Weaver and ASI, we reran the methods ourselves in order to obtain their step-level trajectories. For WebVoyager, all results (both baselines and Web-Sync) are from our own runs using the Browser Use Agent framework with identical settings. Tasks are evaluated sequentially in the default index order of the official task files, with no curriculum or custom ordering applied.

Metrics Across both benchmarks, we focus on three primary metrics: (1) **Success Rate (SR)**, measuring effective task completion; (2) **Average Interaction Steps**, quantifying efficiency; and (3) **Skill Utilization Rate (SUR)**, defined as the proportion of tool invocations among all executed actions. SUR serves as a proxy for the agent's "evolutionary maturity," indicating how successfully it has consolidated reasoning into executable skills.

4.2 Main Results

Results on WebArena. As presented in Table 3, WEBSYNC establishes a new state-of-the-art on WebArena with CLAUDE-3.7-SONNET, achieving 68.4% overall SR. Compared to **memory-centric baselines** (AWM, REASONING BANK), which still require costly on-the-fly interpretation (System 2) and average 7.2–8.8 steps, WEBSYNC compiles insights into executable skills (System 1) and reduces interaction cost to 4.3 steps, cutting trajectory length by nearly half while elevating SR by over 20 points. Against **skill-centric baselines** (POLYSKILL, ASI), which leverage tool synthesis but lack runtime contracts, WEBSYNC surpasses the strongest prior method by ~4% SR through defensive skill recipes. Crucially, this robustness does not trade off speed: in Shopping—the only subset where POLYSKILL reports steps—WEBSYNC achieves both higher SR (64.2% vs. 58.3%) and fewer steps (3.1 vs. 3.3).

Cross-Backbone Generalization on WebArena. We further evaluate with GPT-4.1 and GLM-4.5 (Table 3). WEBSYNC consistently achieves the highest SR, outperforming the strongest baseline by 3.3% and 3.4% respectively, confirming that the gains stem from recipe-guided skills rather than backbone-specific properties.

Results on WebVoyager. Table 4 summarizes results on WebVoyager, where agents face dynamic content and unpredictable UI interruptions.

Method	SR (%) ↑	Steps ↓
(a) Baseline Comparison (GPT-4o)		
GPT-4o	65.3	10.9
SkillWeaver (Zheng et al., 2025)	68.5	8.4
WebCoach (Liu et al., 2025a)	69.8	9.2
WebSync (Ours)	**72.8**	**6.5**

Backbone	SR (%) ↑		Steps ↓	
	Base	WebSync	Base	WebSync
(b) Cross-Backbone Generalization				
GPT-4o	65.3	**72.8**	10.9	**6.5**
Claude-3.7-Sonnet	76.0	**86.3**	9.8	**5.4**
Qwen3-VL-8B	42.1	**56.6**	16.4	**11.9**
Qwen2.5-VL-7B	32.8	**35.2**	17.4	**14.2**

Table 4: **Results on WebVoyager** (15-site average). **(a)** Baseline comparison under GPT-4o against self-evolving methods; **(b)** Cross-backbone generalization: WebSync consistently improves SR and reduces steps across all four backbones. Per-site breakdowns are in Appendix B.

Under GPT-4O, WEBSYNC achieves 72.8% SR with only 6.5 steps, outperforming WEBCOACH by 3.0% SR while requiring 29% fewer steps. SKILLWEAVER reduces steps (8.4) but lags in SR (68.5%), confirming that step reduction without runtime verification is insufficient. The results also demonstrate strong cross-model generalization (Table 4b). On CLAUDE-3.7-SONNET, WEBSYNC boosts SR from 76.0% to 86.3% (+10.3%). The most pronounced gain appears on QWEN3-VL-8B (+14.5%, from 42.1% to 56.6%), suggesting that recipe-encoded procedural knowledge effectively compensates for smaller models' reasoning limitations. Per-site breakdowns are in Appendix B.

4.3 Ablation Study

To assess the distinct contributions of each component within WEBSYNC, we conducted an ablation study across both benchmarks. We compared the full framework against three variants, analyzing the impact on Success Rate (SR), efficiency (Average Steps), and the Skill Utilization Rate (SUR). The results are summarized in Table 5.

Impact of Executable Skills. The variant *w/o Executable Skills* removes the Skill Library ($\mathcal{M}_S$), forcing the agent to rely solely on primitive actions via ReAct reasoning (System 2). As shown in Table 5, this leads to a marked decline in performance, with SR dropping from 72.8% to 65.2%. Furthermore, the average interaction cost increases

significantly from 6.5 to 9.8 steps. This confirms that encapsulating complex subroutines into executable skills is critical for bypassing the "inference bottleneck" of LLMs, thereby reducing error accumulation in long-horizon tasks.

Impact of Strategic Advice. The *w/o Strategic Advice* variant bypasses the advice distillation phase, synthesizing tools directly from interaction traces without high-level semantic constraints. A key observation is the sharp drop in Skill Utilization Rate (SUR), which falls from 31.5% (Full) to 15.8%. This indicates that without the generalization provided by Strategic Advice, synthesized tools tend to be overfitted to specific trajectory instances (e.g., binding to transient element IDs). Consequently, these "brittle" tools are rarely triggered in future episodes, forcing the agent to revert to inefficient primitive actions and lowering the success rate to 66.8%.

Impact of Skill Recipes. The *w/o Skill Recipes* variant retains the libraries but disables the strict P-B-Q-R specification checks during inference. Interestingly, this variant maintains a relatively high SUR (26.4%), yet the success rate decreases to 69.5%. This discrepancy highlights the danger of "blind execution." Without the guardrails of Preconditions ($\mathcal{P}$) and Postconditions ($\mathcal{Q}$), the agent frequently invokes tools in invalid states or fails to detect silent execution errors. While the agent "thinks" it is using skills efficiently (high SUR), the lack of runtime verification compromises the actual outcome, proving that specifications are essential for ensuring that skill quantity translates into quality.

Self-Evolution vs. External Synthesis. We additionally investigate whether delegating skill synthesis to a stronger external model improves over self-evolution. Results (Appendix C) show that the gain is marginal (+1.4% SR), confirming the self-evolving pipeline is already highly effective without requiring any external model.

4.4 Case Study

To illustrate how WEBSYNC transforms abstract strategic advice into robust, executable procedures, we present a case study on applying product filters on Amazon (Algorithm 1). This task is notoriously brittle for standard agents due to the platform's asynchronous UI loading and deeply nested DOM structures, which often cause standard click actions

Method	WebArena			WebVoyager		
	SR (%)	Steps	SUR (%)	SR (%)	Steps	SUR (%)
WebSync	**68.4**	**4.3**	**28.9**	**72.8**	**6.5**	**31.5**
w/o Executable Skills	55.2	6.8	–	65.2	9.8	–
w/o Strategic Advice	60.8	5.2	14.2	66.8	8.7	15.8
w/o Skill Recipes	65.3	4.8	24.1	69.5	7.8	26.4

Table 5: **Ablation Analysis across Benchmarks.** We compare the full WebSync framework against three variants on both WebArena and WebVoyager. We introduce **Skill Utilization Rate (SUR)** to measure the proportion of steps executed via synthesized tools. The results highlight that strategic advice significantly boosts tool reusability, while specification constraints ensure their robust execution.

Algorithm 1 Skill: ROBUSTFILTERAMAZON

Require: $page$ (Browser State), $target$ (e.g., "Used - Good")
Ensure: SUCCESS or FAILURE with signal
    Constraint: Derived from Advice #AMZ-042 (DOM instability)

```
 1: function APPLYFILTER(page, target)
 2:     // 1. Precondition (P): Guarded Execution
 3:     if ¬ ISVISIBLE(page, "#s-refinements") then
 4:         return FAILURE("Filter panel not loaded")
 5:     end if
 6:     // 2. Execution (B): System 1 Precision
 7:     EXECUTE(page, "click_exact_match", target)
 8:     WAIT(0.5s)
 9:     // 3. Verification (Q): Ground Truth Check
10:     if VERIFYSTATE(page, target) is TRUE then
11:         return SUCCESS
12:     end if
13:     // 4. Recovery (R): Self-Correction
14:     LOG("Exact match failed. Triggering fuzzy recovery...")
15:     Strategy: Relax matching & target parent container
16:     EXECUTE(page, "click_fuzzy_parent", target)
17:     WAIT(1.0s)
18:     // Final Guard
19:     if VERIFYSTATE(page, target) is TRUE then
20:         return SUCCESS                    ▷ Recovered
21:     end if
22:     return FAILURE("Action failed after recovery")
23: end function
```

to fail silently.

Defensive Architecture. As depicted in Algorithm 1, the synthesized skill is structured around formal constraints rather than naive command sequences. Guided by strategic advice noting that "Amazon checkboxes are often unclickable overlays," the synthesizer generates a guarded procedure:

- **Guarded Execution** (P): Lines 2–4 enforce that the refinement panel must be fully rendered before interaction, preventing the "ElementNotInteractable" errors common in baselines.

- **Verifiable Action** (Q): Crucially, the skill does not assume the click succeeded. Lines 9–11 explicitly execute a verification check (checking the `aria-checked` attribute) to establish ground truth.

In-Skill Recovery (R). The most critical feature is the autonomous self-correction mechanism (Lines 13–18). In this specific instance, the initial exact-match click failed to trigger the UI update due to a layout shift—a scenario where standard agents would proceed to hallucinate success. Detecting the verification failure, WEBSYNC's skill triggers its built-in **Recovery Strategy** (R). It executes a "fuzzy click" heuristic targeting the parent container, a tactic learned from prior failures. The subsequent re-verification confirms success, allowing the agent to salvage the task seamlessly without triggering a costly high-level re-planning cycle.

Due to the complete skill code being too long to be displayed in the main text, we have presented the pseudocode form of the code here. Please refer to the appendix E for a more detailed case study.

5 Conclusion

In this paper, we introduced WEBSYNC, a self-evolving framework that transforms transient reasoning into durable execution skills. Unlike prior approaches that isolate memory from tool synthesis, WEBSYNC unifies them through *Skill Recipes*—formal contracts that enforce strict applicability and verification logic. This mechanism allows agents to synthesize defensive tools, effectively bridging the gap between flexible planning and reliable execution. Empirical results on WebArena and WebVoyager confirm that this co-evolutionary approach significantly outperforms existing baselines, establishing a new state-of-the-art in autonomous web navigation.

Limitations

Expressivity of Text-Based recipes. Our current Skill recipes primarily rely on text-based or DOM-selector predicates, such as `visible(selector)`. This symbolic abstraction, however, is ill-equipped to capture tasks that are heavily dependent on visual semantics or spatial dynamics, for instance, instructions to "drag the slider" or "select the visually highlighted item." Even though the multimodal backbone is capable of perceiving these elements, the intermediate recipe's reliance on text limits the system's capacity to formally codify and verify purely visual constraints.

Cold Start and Exploration Costs. Since Web-Sync's self-evolution is predicated on the accumulation of successful trajectories, the system cannot synthesize effective skills for novel domains or long-tail tasks where successful traces are scarce. In these scenarios, the agent must bear the full computational cost of System 2 trial-and-error. Mitigating this "cold start" overhead through cross-domain transfer or few-shot recipe seeding remains an important direction for future research.

Real-World Anti-Bot Constraints. As evidenced by our WebVoyager results, particularly on Google Flights, the agent encounters difficulties with strict anti-bot measures like CAPTCHAs and complex authentication flows. While this challenge is pervasive in web agent research, the high-frequency execution pattern characteristic of synthesized skills may arguably increase the probability of triggering such defenses compared to slower, more human-like browsing behaviors.

References

Anthropic. 2024. Developing a computer use model. https://www.anthropic.com/news/developing-computer-use. Accessed: 2025-04-12.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, and 45 others. 2025. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Sam Stevens, Boshi Wang, Huan Sun, and Yu Su. 2023. Mind2web: Towards a generalist agent for the web. *Advances in Neural Information Processing Systems*, 36:28091–28114.

Yang Deng, An Zhang, Yankai Lin, Xu Chen, Ji-Rong Wen, and Tat-Seng Chua. 2024. Large language model powered agents in the web. In *Companion Proceedings of the ACM Web Conference 2024*, pages 1242–1245.

Tianqing Fang, Hongming Zhang, Zhisong Zhang, Kaixin Ma, Wenhao Yu, Haitao Mi, and Dong Yu. 2025. WebEvolver: Enhancing web agent self-improvement with co-evolving world model. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 8970–8986, Suzhou, China. Association for Computational Linguistics.

Hiroki Furuta, Kuang-Huei Lee, Ofir Nachum, Yutaka Matsuo, Aleksandra Faust, Shixiang Gu, and Izzeddin Gur. 2024. Multimodal web navigation with instruction-finetuned foundation models. In *International Conference on Representation Learning*, volume 2024, pages 29528–29558.

Huan-ang Gao, Jiayi Geng, Wenyue Hua, Mengkang Hu, Xinzhe Juan, Hongzhang Liu, Shilong Liu, Jiahao Qiu, Xuan Qi, Yiran Wu, and 1 others. 2025. A survey of self-evolving agents: On path to artificial super intelligence. *arXiv preprint arXiv:2507.21046*.

Hongliang He, Wenlin Yao, Kaixin Ma, Wenhao Yu, Yong Dai, Hongming Zhang, Zhenzhong Lan, and Dong Yu. 2024. Webvoyager: Building an end-to-end web agent with large multimodal models. *arXiv preprint arXiv:2401.13919*.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Hanyu Lai, Xiao Liu, Iat Long Iong, Shuntian Yao, Yuxuan Chen, Pengbo Shen, Hao Yu, Hanchen Zhang, Xiaohan Zhang, Yuxiao Dong, and Jie Tang. 2024. Autowebglm: A large language model-based web navigating agent. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, KDD 2024, Barcelona, Spain, August 25-29, 2024*, pages 5295–5306. ACM.

Jiaye Lin, Yifu Guo, Yuzhen Han, Sen Hu, Ziyi Ni, Licheng Wang, Mingguang Chen, Hongzhang Liu, Ronghao Chen, Yangfan He, and 1 others. 2025. Seagent: Self-evolution trajectory optimization in multi-step reasoning with llm-based agents. *arXiv preprint arXiv:2508.02085*.

Genglin Liu, Shijie Geng, Sha Li, Hejie Cui, Sarah Zhang, Xin Liu, and Tianyi Liu. 2025a. Webcoach: Self-evolving web agents with cross-session memory guidance. *arXiv preprint arXiv:2511.12997*.

Jiarun Liu, Jia Hao, Chunhong Zhang, and Zheng Hu. 2025b. Wepo: Web element preference optimization for llm-based web navigation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 26614–26622.

Haohao Luo, Jiayi Kuang, Wei Liu, Ying Shen, Jian Luan, and Yang Deng. 2025. Browsing like human: A multimodal web agent with experiential fast-and-slow thinking. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14232–14251.

Liangbo Ning, Ziran Liang, Zhuohang Jiang, Haohao Qu, Yujuan Ding, Wenqi Fan, Xiao-yong Wei, Shanru Lin, Hui Liu, Philip S Yu, and 1 others. 2025. A survey of webagents: Towards next-generation ai agents for web automation with large foundation models. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*, pages 6140–6150.

Siru Ouyang, Jun Yan, I Hsu, Yanfei Chen, Ke Jiang, Zifeng Wang, Rujun Han, Long T Le, Samira Daruki, Xiangru Tang, and 1 others. 2025. Reasoningbank: Scaling agent self-evolving with reasoning memory. *arXiv preprint arXiv:2509.25140*.

Zehan Qi, Xiao Liu, Iat Long Iong, Hanyu Lai, Xueqiao Sun, Wenyi Zhao, Yu Yang, Xinyue Yang, Jiadai Sun, Shuntian Yao, and 1 others. 2024. Webrl: Training llm web agents via self-evolving online curriculum reinforcement learning. *arXiv preprint arXiv:2411.02337*.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, and 1 others. 2025. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*.

Jiahao Qiu, Xuan Qi, Tongcheng Zhang, Xinzhe Juan, Jiacheng Guo, Yifu Lu, Yimin Wang, Zixin Yao, Qihan Ren, Xun Jiang, and 1 others. 2025. Alita: Generalist agent enabling scalable agentic reasoning with minimal predefinition and maximal self-evolution. *arXiv preprint arXiv:2505.20286*.

Zora Zhiruo Wang, Apurva Gandhi, Graham Neubig, and Daniel Fried. 2025. Inducing programmatic skills for agentic tasks. *arXiv preprint arXiv:2504.06821*.

Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2024. Agent workflow memory. *arXiv preprint arXiv:2409.07429*.

Zhepei Wei, Wenlin Yao, Yao Liu, Weizhi Zhang, Qin Lu, Liang Qiu, Changlong Yu, Puyang Xu, Chao Zhang, Bing Yin, and 1 others. 2025. Webagent-r1: Training web agents via end-to-end multi-turn reinforcement learning. *arXiv preprint arXiv:2505.16421*.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. 2022a. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35:20744–20757.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2022b. React: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*.

Simon Yu, Gang Li, Weiyan Shi, and Peng Qi. 2025. Polyskill: Learning generalizable skills through polymorphic abstraction. *arXiv preprint arXiv:2510.15863*.

Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, and 1 others. 2025. Glm-4.5: Agentic, reasoning, and coding (arc) foundation models. *arXiv preprint arXiv:2508.06471*.

Kai Zhang, Xiangchao Chen, Bo Liu, Tianci Xue, Zeyi Liao, Zhihan Liu, Xiyao Wang, Yuting Ning, Zhaorun Chen, Xiaohan Fu, and 1 others. 2025a. Agent learning via early experience. *arXiv preprint arXiv:2510.08558*.

Yao Zhang, Zijian Ma, Yunpu Ma, Zhen Han, Yu Wu, and Volker Tresp. 2025b. Webpilot: A versatile and autonomous multi-agent system for web task execution with strategic exploration. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 23378–23386.

Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. 2024. Expel: Llm agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19632–19642.

Boyuan Zheng, Michael Y Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, Gaowen Liu, Graham Neubig, and 1 others. 2025. Skillweaver: Web agents can self-improve by discovering and honing skills. *arXiv preprint arXiv:2504.07079*.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. 2024. Gpt-4v (ision) is a generalist web agent, if grounded. *arXiv preprint arXiv:2401.01614*.

Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, and 1 others. 2023. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*.

A Prompts

To ensure reproducibility, we provide the detailed system prompts used in WebSync. Please refer to the Figure 3, Figure 5 and Figure 4 for details.

B Detailed WebVoyager Results

Table 6 provides the per-site success rate breakdown on WebVoyager for three backbones (GPT-4o, Claude-3.7-Sonnet, Qwen3-VL-8B). WebSync consistently improves over the base agent across all 15 websites.

C Self-Evolution vs. External Synthesis

To investigate whether a stronger external model can further boost skill quality, we compare self-evolution (the full pipeline run by QWEN3-VL-8B alone) against a variant where Advice Distillation and Skill Synthesis are delegated to GPT-4O while the 8B model only executes the resulting recipes at inference.

As shown in Table 7, the external-synthesizer variant yields 58.0% SR and 11.2 steps, compared to 56.6% SR and 11.9 steps for self-evolution. The marginal gain (+1.4% SR) confirms that while larger models produce slightly higher-quality recipes, the self-evolving pipeline is already highly effective—the 8B-only setup achieves the vast majority of the benefit (14.5% absolute gain over the 42.1% baseline) without requiring any external model.

D Experimental Setup Details

For full reproducibility, we report the hyperparameters and environmental configurations used in our experiments.

WebArena. We strictly follow the official evaluation scripts and default configurations provided by the WebArena benchmark. No custom hyperparameters are introduced; our setup is fully aligned with how other baselines evaluate on WebArena. We use the standard subset of 655 tasks across four domains (Shopping, Admin, GitLab, Reddit). Tasks are evaluated sequentially in the default index order of the official task files, with no curriculum or custom ordering applied.

WebVoyager. All experiments on WebVoyager, including baselines (SkillWeaver and WebCoach) and WebSync, are conducted using the Browser Use Agent framework under identical settings. Table 8 lists the complete configuration. Tasks are evaluated sequentially in the default index order of the official task JSON files.

Baseline Sources. For WebArena, most baseline results are adopted directly from the respective original papers under aligned evaluation protocols; however, for SkillWeaver and ASI, we reran the methods ourselves in order to obtain their step-level trajectories. For WebVoyager, all results (both baselines and WebSync) are from our own runs using the Browser Use Agent framework with identical settings. Tasks are evaluated sequentially in the default index order of the official task files, with no curriculum or custom ordering applied.

E More Case Studies

In this section, we provide detailed examples of the synthesized skills and a step-by-step trajectory analysis to illustrate the robustness of WebSync.

E.1 Skill Examples

To demonstrate the robustness of our framework, Figure 6 presents a qualitative comparison between skills synthesized by baseline methods and those generated by WebSync.

As shown in Figure 6(a), existing skill-centric approaches (e.g., PolySkill, ASI) often rely on naive trace cloning. The resulting code typically manifests as linear action sequences or high-level abstract wrappers. Such implementations are inherently brittle; they lack context awareness and error-handling mechanisms. Consequently, if the web environment exhibits asynchronous loading delays or unpredicted layout shifts, these rigid scripts fail to adapt, leading to immediate task termination.

In contrast, Figure 6(b) illustrates how WEB-SYNC leverages Skill Recipes as a governing contract to synthesize defensive, executable procedures. Using an Amazon product filtering task as a case study, the synthesized skill strictly adheres to the P-B-Q-R defensive structure:

- **Preconditions (P): Resilient Entry Guards.** Instead of relying on fragile instantaneous checks (e.g., `is_visible`), the synthesized function employs robust synchronization primitives. It prioritizes `wait_for_selector` to handle network latency gracefully. Explicit recovery actions (e.g., `page.reload()`) are triggered *only* if the critical element fails to

You are a Senior Web Navigation Analyst. Your job is to analyze interaction traces to distill high-level **Strategic Advice** that prevents future failures or optimizes execution.
Input Data:

- **Task:** {{task_description}}

- **Execution Trace:** {{trace_history}} (Actions, Observations, and Outcomes)

- **Status:** {{success_or_failure}}

Analysis Objectives:

1. **Identify Bottlenecks:** Look for redundant steps, loops, or failed clicks caused by dynamic DOM elements (e.g., pop-ups, layout shifts).

2. **Generalize Patterns:** Abstract specific element IDs into semantic rules (e.g., instead of "Click div#123", suggest "Wait for the 'Sort' dropdown to be fully visible").

3. **Formulate Constraints:** Create explicit applicability conditions (σ) and verification checks (Q) for this type of task.

Output Format: Return a concise advice summary in the following JSON format:

```
{
  "trigger_condition": "When attempting to filter items...",
  "precondition_advice": "Ensure the overlay mask is gone.",
  "recovery_advice": "If click fails, try forcing a page reload."
}
```

Figure 3: The prompt used to distill raw interaction traces into reusable Strategic Advice ($\mathcal{M}_A$), serving as the cognitive foundation for skill synthesis.

appear after a specific timeout, preventing unnecessary reloads on slow connections.

- **Verification (Q): Strict State Confirmation.** Instead of assuming action success based solely on execution completion, the code explicitly verifies the outcome post-execution. In this case, it validates the ground truth by checking for expected URL parameter updates or specific DOM state changes to confirm the filter was applied.

- **Recovery (R) with Closed-Loop Validation.** Crucially, the skill encapsulates verifiable self-correction logic. When the primary execution path (e.g., an exact-match click) fails due to DOM instability, the handler catches the exception and triggers a fallback strategy (e.g., a fuzzy click on the parent container). **Unlike baseline methods, WEBSYNC enforces** a second verification step after recovery. If the state remains invalid even after the fallback action, the skill correctly reports a failure, ensuring that the agent never proceeds with a "false positive" success.

E.2 Example of executing web navigation tasks with WebSync

Figure 7 illustrates a qualitative comparison on an Amazon search task. The **Baseline Agent**, relying on atomic actions, exhibited two critical weaknesses: (1) *Navigational Instability*, getting trapped in a refresh loop due to SPA hydration issues (Steps 1–5); and (2) *Lack of State Verification*. Crucially, while the agent attempted to click the "Used" filter selector, it failed to verify if the filter was successfully applied to the DOM. Consequently, the agent extracted mixed results (New and Used items) but hallucinated task success, resulting

Task Website	GPT-4O		CLAUDE-3.7-SONNET		QWEN3-VL-8B	
	Base	WebSync (Δ)	Base	WebSync (Δ)	Base	WebSync (Δ)
Allrecipes	88.9	**93.3** (+4.4)	93.3	**100.0** (+6.7)	46.7	**62.2** (+15.5)
Amazon	95.1	**100.0** (+4.9)	97.6	**100.0** (+2.4)	65.9	**78.0** (+12.1)
Apple	60.5	**74.4** (+13.9)	72.1	**83.7** (+11.6)	32.6	**48.8** (+16.2)
ArXiv	83.7	**90.7** (+7.0)	88.4	**95.3** (+6.9)	34.9	**48.8** (+13.9)
BBC News	71.4	**83.3** (+11.9)	78.6	**88.1** (+9.5)	31.0	**47.6** (+16.6)
Booking	13.6	**25.0** (+11.4)	25.0	**38.6** (+13.6)	18.2	**31.8** (+13.6)
Cambridge Dict.	95.3	**97.7** (+2.4)	97.7	**100.0** (+2.3)	74.4	**88.4** (+14.0)
Coursera	59.5	**69.0** (+9.5)	76.2	**85.7** (+9.5)	57.1	**69.0** (+11.9)
ESPN	65.9	**79.5** (+13.6)	75.0	**88.6** (+13.6)	29.5	**45.5** (+16.0)
GitHub	85.4	**92.7** (+7.3)	90.2	**95.1** (+4.9)	43.9	**61.0** (+17.1)
Google Flights	7.1	**19.0** (+11.9)	19.0	**33.3** (+14.3)	4.8	**16.7** (+11.9)
Google Map	87.8	**92.7** (+4.9)	92.7	**97.6** (+4.9)	58.5	**73.2** (+14.7)
Google Search	23.3	**37.2** (+13.9)	34.9	**48.8** (+13.9)	39.5	**53.5** (+14.0)
Huggingface	67.4	**76.7** (+9.3)	74.4	**86.0** (+11.6)	39.5	**55.8** (+16.3)
Wolfram Alpha	76.1	**84.8** (+8.7)	84.8	**93.5** (+8.7)	54.3	**69.6** (+15.3)
Avg. SR	65.3	**72.8** (+7.5)	76.0	**86.3** (+10.3)	42.1	**56.6** (+14.5)
Avg. Steps	10.9	**6.5** (-4.4)	9.8	**5.4** (-4.4)	16.4	**11.9** (-4.5)

Table 6: **Per-Site Success Rate Breakdown on WebVoyager.** Columns for WebSync show absolute performance followed by improvement over Base (Δ).

Setting	SR (%) ↑	Steps ↓
Base	42.1	16.4
WebSync (self only)	56.6	11.9
WebSync + GPT-4o synth.	**58.0**	**11.2**

Table 7: Self-evolution vs. external synthesis on WebVoyager (Qwen3-VL-8B, 15-site average).

Category	Setting	Value
Browser	Window / viewport size	1920 × 1080
	Headless mode	true
	Min. wait (page load)	0.5 s
	Wait between actions	0.5 s
	Wait for network idle	0.5 s
Agent	Max steps per episode	30
	Max actions per step	10
	Max consecutive failures	3
	Use vision	true
	Vision detail level	auto
	Use thinking	true

Table 8: Hyperparameter configuration for WebVoyager experiments. All methods (baselines and WebSync) use identical settings.

of the three approaches on a dynamic Amazon filtering task. The baseline agent relies purely on atomic actions, trapping it in a costly trial-and-error loop when facing asynchronous page loading. While the skill-centric baseline employs synthesized tools to reduce steps, the lack of execution contracts causes the tool to crash upon encountering unexpected layout shifts, forcing an inefficient fallback to low-level reasoning. In contrast, WebSync demonstrates the advantage of continuous self-evolution, which naturally consolidates routine actions into more complex, compositional tools like `search_and_filter`. During the inference phase, WebSync leverages retrieved strategic advice to efficiently formulate a short-horizon plan and accurately select the optimal skill for its subgoals. Fortified by strict preconditions and built-in recovery logic, the chosen tool seamlessly resolves dynamic UI exceptions internally, completing the complex task with high efficiency and zero atomic trial-and-error.

in a **false positive**. In contrast, our **Recipe-Guided Agent** utilized a synthesized skill with rigorous `postconditions` (e.g., asserting the presence of the active filter tag). This ensured the browser state was synchronized with the agent's intent before data extraction, achieving verifiable success in just 12 seconds. Moreover, Figure 8, Figure 9 and Figure 10 provide a detailed trajectory comparison

System Prompt: Recipe-Guided Skill Synthesis (WebSync Section 3.4; Appendix A)

You are an expert Web Automation Engineer specializing in robust tool synthesis. Your goal is to convert a raw interaction trace into a reusable, defensive Python skill function based on the provided Skill Recipe contract.

Input Data:

- **Task Description:** `{{task_description}}`

- **Refined Skill Recipe S (JSON):** `{{refined_spec}}`

- **Strategic Advice (optional):** `{{advice_constraints}}`

- **Interaction Trace (optional):** `{{trace_history}}`

Synthesis Requirements (must satisfy the paper):

1. **Preconditions (P):** for EACH predicate in `{{refined_spec.preconditions}}`, add a guarded check (e.g., `assert ...`) before executing the core actions.

2. **Postconditions (Q):** for EACH predicate in `{{refined_spec.postconditions}}`, implement verification at the end; do not silently pass if any postcondition fails.

3. **Failure Signatures (F) + Recovery (R):** if verification fails, detect the failure mode using `{{refined_spec.failure_signatures}}` and run the corresponding `{{refined_spec.recovery}}` steps; retry the core logic at most once.

4. **Parameterization:** follow `{{params_schema}}` exactly; do not hardcode task-specific values.

5. **Defensive execution:** handle dynamic loading, popups/modals, and small UI shifts.

Implementation Notes (align with ToolLibrary style):

- Write an async def Python function whose name matches `{{refined_spec.bindings.tool_name}}` (or `{{refined_spec.name}}` if missing).

- First argument must be `page`.

- Prefer stable selectors and semantic markers; avoid brittle dynamic IDs.

- Use bounded retry logic; avoid infinite loops.

- Return a concise status string (include page title + URL if available) or raise a clear exception on failure.

Output: Return ONLY the Python code (no Markdown fences, no extra commentary).

Figure 4: The system prompt for Recipe-Guided Skill Synthesis.

System Prompt: Recipe-Informed Planning

You are a planning module. Given a user instruction and the current observation, you must produce a short-horizon plan. Each subgoal MUST be grounded in an available Skill Recipe whenever possible.

Input:

- **Task instruction** x: {{task_description}}

- **Current observation** o_t: {{observation}}

- **Retrieved Recipes** S_t (**JSON list**): {{retrieved_specs}}

Your job:

1. Decompose the task into 1–5 subgoals.

2. For each subgoal, choose the BEST matching Recipe as an anchor (or "NO_SPEC" if none fits).

3. Prefer plans that are executable under the available capabilities (do not propose actions that have no supporting spec/tool unless necessary).

Output format (JSON ONLY): {
"plan": [
{
"subgoal": "...",
"spec_anchor": {
"name": "SPEC_NAME | NO_SPEC",
"match_rationale": "1-2 short reasons referencing sigma/page markers/intent"
}
}
]
}
Rules:

- Do NOT include any extra keys.

- Keep subgoals concrete and verifiable.

Figure 5: The system prompt for Recipe-Aware Planning.

Figure 6: **Qualitative Comparison of Skill Synthesis Approaches.** (a) **PolySkill & ASI.** generate abstract classes or linear action sequences without execution guards. (b) **WebSync (Ours)** synthesizes defensive skills with explicit preconditions (P), semantic execution (B), verification (Q), and recovery (R).

(a)PolySkill & ASI

```python
class AbstractShoppingSite:

    def search_product(self, query: str):
        """Searches for a product."""

    def add_to_cart(self, item_id: str, quantity:
     int):
        """Adds a specified item to the shopping
     cart."""

    ## --------------------
    ## Compositional Skills
    ## --------------------

    def find_and_add_to_cart(self, query: str,
     item_id: str):
        """Searches for a product and adds it to the
     cart."""
        # High-level abstraction only
        self.search_product(query)
        self.add_to_cart(item_id)
        self.checkout()
```

```python
def search_product(search_box_id: str, query: str):
    """
    Examples:
    search_product('595', 'sony bluetooth headphones
    ')
    """
    # Linear execution - brittle to async loading
    click(search_box_id)
    fill(search_box_id, query)
    keyboard_press('Enter')

def navigate_category(dropdown_id: str, category_id:
     str):
    """Navigate to a category via dropdown."""
    click(dropdown_id)
    click(category_id)
```

(b) WebSync (Ours)

```python
async def robust_search_filter(
    page, term, filter_txt
):
    # [P] Precondition: Guarded Entry
    # Logic: Wait first, reload only if truly stuck
    try:
        await page.wait_for_selector(
            "#twotabsearchtextbox",
            state="visible", timeout=3000
        )
    except TimeoutError:
        # Only trigger recovery if wait fails
        await page.reload()
        await page.wait_for_selector("#
     twotabsearchtextbox")

    # [B] Execution: Semantic Locators
    await page.fill("#twotabsearchtextbox", term)
    await page.press("#twotabsearchtextbox", "Enter"
     )

    # Wait handles async loading
    await page.wait_for_selector("div.s-main-slot")

    # [B] Execution: Robust Filtering
    try:
        # Fallback to list item containing text
        loc = page.locator(f"li:has-text('{
     filter_txt}')")
        await loc.first.click()
    except Exception:
        return f"Failure: Cannot locate '{filter_txt
     }'"

    # [Q] Verification: Strict State Check
    # Helper to verify server state (URL param)
    verify_func = "url => url.includes('
     p_n_condition')"

    try:
        await page.wait_for_function(
            verify_func, page.url, timeout=3000
        )
    except TimeoutError:
        # [R] Recovery: Self-Correction Strategy
        print("Click failed. Retrying parent span...
     ")
        await page.locator(
            f"span:has-text('{filter_txt}')"
        ).click()

        # [Critical] Re-Verification after Recovery
        try:
            await page.wait_for_function(
                verify_func, page.url, timeout=3000
            )
        except TimeoutError:
            # Algorithm 1: Line 22 (Fail if recovery
      fails)
            return "Failure: Action failed after
     recovery"

    return "Success: Filter Applied & Verified"
```

✅ Our Approach (Recipe-Guided)

Task: Search "Switch Lite" with **"Used"** filter.

Summary: Success in 2 Steps (12.8s).

- **Action:** search_and_filter(..., filter="Used")
- **Robustness:** The synthesized skill internally verified the DOM state change before returning control.
- **Obs:** *"Filter 'Used' clicked: True. Applied: True."*

Final Verdict: True. *Reason:* Valid result with confirmed filter state.

⚠ Baseline Agent (Atomic Actions)

Task: Search "Switch Lite" with **"Used"** filter.

Summary: Failed after 9 Steps (70s).

- **Steps 1–5 (Instability):** Encountered SPA hydration issues (blank page). Wasted tokens on navigation retries.
- **Steps 6–8 (Interaction Error):** Attempted to click the "Used" selector. However, the agent **failed to verify** if the filter was actually applied (e.g., did not check for URL update or active badges).
- **Step 9 (Result):** Extracted mixed results (New & Used).

Final Verdict: False. *Reason:* **"Used" filter not checked.** The extracted list contained non-filtered items because the click action did not register correctly.

Figure 7: **Qualitative Comparison.** Left: Our approach successfully applies the "Used" filter using a synthesized robust skill. Right: The Baseline agent struggles with page stability and ultimately fails because it did not verify that the "Used" checkbox was actually selected.

Case Study: GPT-4o Base Trajectory

Task: Search "Xbox Wireless Controller" and apply "Green" and "4 Stars & Up" filters on Amazon.

[System 2: Atomic Reasoning] Step 0-1 (Initialization & Hydration Failure):

- *Action:* Navigate to https://www.amazon.com/.
- *Observation:* Page appears empty (SPA not loaded). 0 links, 0 interactive elements.
- *Result:* Failure. Agent evaluates: "Encountered an empty page... Need to refresh." Refreshes page.

[System 2: Atomic Reasoning] Step 2-3 (Search Execution & Hydration Failure):

- *Action:* Input 'Xbox Wireless Controller green' into search box (index 2396) and click 'Go' (index 3010).
- *Observation:* The search results page loads as an empty screen.

- *Result:* Failure. Agent evaluates: "The search was executed, but the page did not load correctly." Refreshes page.

[System 2: Atomic Reasoning] Step 4-5 (Filter Execution & Hydration Failure):

- *Action:* Click 'Green' filter (index 19356) and '4 Stars & Up' filter (index 19129).
- *Observation:* The filtered results page loads as an empty screen.
- *Result:* Failure. Agent evaluates: "Encountered an empty page after refreshing the search results." Refreshes page.

[System 2: Atomic Reasoning] Step 6-7 (Extraction & Completion):

- *Action:* Extract details of Xbox controllers matching the criteria and call done.
- *Result:* Success. Task completed, but required 7 steps and 3 manual recovery cycles.

Figure 8: An execution trajectory of a memory-less baseline agent (GPT-4o Base). The agent relies entirely on System 2 atomic reasoning. While it eventually succeeds, it suffers from severe navigational instability, wasting multiple inference cycles (Steps 1, 3, and 5) to manually handle asynchronous UI loading (SPA hydration issues).

Case Study: Skill-Centric Baseline (e.g., SkillWeaver) Trajectory

Task: Search "Xbox Wireless Controller" and apply "Green" and "4 Stars & Up" filters on Amazon.

[System 1: Tool Execution] Step 1 (Search Strategy):

- *Action:* Invoke synthesized tool `search(query="Xbox Wireless Controller green")`.
- *Observation:* The search executes smoothly and the initial results page loads.
- *Result:* Success.

[System 1: Tool Execution] Step 2 (Filter Strategy & Silent Failure):

- *Action:* Invoke synthesized tool `apply_filter(conditions=["Green", "4 Stars & Up"])`.
- *Tool Internal Execution:* The script mechanically attempts to click the filter selectors based on cached DOM paths.

- *Observation:* The Amazon page enters an asynchronous SPA hydration state (blank page) during the click.
- *Result:* Exception Thrown (ElementNotInteractable).

[System 2: Atomic Fallback] Step 3-7 (Trial-and-Error Reasoning):

- *Agent Reflection:* "The filter tool failed. I need to manually locate and apply the filters."
- *Step 3:* Agent refreshes the page to escape the blank state.
- *Step 4:* Agent manually locates the 'Green' filter (index 19356) and issues a primitive `click` action.
- *Step 5:* Page goes blank again (hydration). Agent evaluates failure.
- *Step 6:* Agent refreshes the page again.
- *Step 7:* Agent manually locates and clicks '4 Stars & Up' filter (index 19129).

Figure 9: An execution trajectory of a baseline skill-centric agent (e.g., SkillWeaver). The absence of robust recipes (preconditions and recovery handlers) causes the synthesized `apply_filter` tool to crash upon encountering a dynamic layout shift. Consequently, the agent is forced to revert to expensive, atomic trial-and-error reasoning.

Case Study: WebSync (Ours) Trajectory

Task: Search "Xbox Wireless Controller" and apply "Green" and "4 Stars & Up" filters on Amazon.

[System 2: Recipe-Informed Planning] **Step 1 (Advice Retrieval & Plan Generation):**

- *Context:* Agent observes the Amazon homepage and analyzes the intent.
- *Retrieval:* Retrieves Strategic Advice (#AMZ-042): "Amazon filtering is brittle due to SPA hydration and unclickable overlays. Avoid atomic ReAct clicks; mandate guarded filter tools."
- *Plan Decomposition:* Agent generates a short-horizon plan with bounded skill anchors:
    - **Subgoal 1:** Execute search and apply required filters. → *Skill Anchor:* robust_search_filter
    - **Subgoal 2:** Extract the compliant product list. → *Skill Anchor:* extract_results

---

[System 1: Robust Execution] **Step 2 (Unified Search & Filter):**

- *Action:* Invoke mapped tool robust_search_filter(term="Xbox Wireless Controller green", filter_txt=["Green", "4 Stars & Up"]).
- *Tool Internal Execution (Contract Enforcement):*
    - **[P] Precondition:** Explicitly waits for #twotabsearchtextbox and filter panel to be fully interactive, gracefully bypassing the blank hydration state.
    - **[B] Execution:** Inputs query and executes click events using semantic locators.
    - **[R] Recovery:** Detects a layout shift during the 'Green' filter click; autonomously triggers a fuzzy click on the parent container.
    - **[Q] Verification:** Asserts URL parameters (p_n_condition) and active DOM tags.

- *Result:* Success. Browser state is strictly verified and synchronized with the applied filters.

[System 1: Robust Execution] **Step 3 (Extraction & Completion):**

- *Action:* Invoke mapped tool extract_results(target_rating=">4") and call done.
- *Result:* Success. Task completed efficiently in 3 high-level steps.

Figure 10: An execution trajectory of WebSync. Unlike baseline methods, WebSync begins with a Recipe-Informed Planning phase (System 2), retrieving strategic advice to avoid known pitfalls (e.g., SPA hydration) and anchoring subgoals to specific Skill Recipes. It then seamlessly delegates execution to robust tools (System 1) equipped with strict P-B-Q-R contracts, resolving dynamic UI issues internally and completing the task with zero atomic trial-and-error.