Everybody Needs Good Neighbours: An Unsupervised Locality-based Method for Bias Mitigation

Abstract

Learning models from human behavioural data often leads to outputs that are biased with respect to user demographics, such as gender or race. This effect can be controlled by explicit mitigation methods, but this typically presupposes access to demographically-labelled training data. Such data is often not available, motivating the need for unsupervised debiasing methods. To this end, we propose a new meta-algorithm for debiasing representation learning models, which combines the notions of data locality and accuracy of model fit, such that a supervised debiasing method can optimise fairness between neighbourhoods of poorly vs. well modelled instances as identified by our method. Results over five datasets, spanning natural language processing and structured data classification tasks, show that our technique recovers proxy labels that correlate with unknown demographic data, and that our method outperforms all unsupervised baselines, while also achieving competitive performance with state-of-the-art supervised methods which are given access to demographic labels.

1 Introduction

It is well known that naively-trained models potentially make biased predictions even if demographic information (such as gender, age, or race) is not explicitly observed in training, leading to discrimination such as opportunity inequality (Hovy & Søgaard, 2015; Hardt et al., 2016). Although a range of fairness metrics (Hardt et al., 2016; Blodgett et al., 2016) and debiasing methods (Elazar & Goldberg, 2018; Wang et al., 2019; Ravfogel et al., 2020) have been proposed to measure and improve fairness in model predictions, they generally require access to protected attributes during training. However, protected labels are often not available (e.g., due to privacy or security concerns), motivating the need for unsupervised debiasing methods, i.e., debiasing without access to demographic variables. Previous unsupervised debiasing work has mainly focused on improving the worst-performing groups, which does not generalize well to ensuring performance parity across all protected groups (Hashimoto et al., 2018; Lahoti et al., 2020).

In Section 3, we propose a new meta-algorithm for debiasing representation learning models, named **U**nsupervised **L**ocality-based **P**roxy **L**abel assignment (ULPL). As shown in Figure 1, to minimize performance disparities, ULPL derives binary proxy labels based on model predictions, indicating poorly- vs. well-modelled instances. These proxy labels can then be combined with any supervised debiasing method to optimize fairness without access to actual protected labels. The method is based on the key observation that hidden representations are correlated with protected groups even if protected labels are not observed in model training, enabling the modelling of unobserved protected labels from hidden representations. We additionally introduce the notion of data locality to proxy label assignment, representing neighbourhoods of poorly- vs. well-modelled instances in a nearest-neighbour framework.

In Section 4, we compare the combination of ULPL with state-of-the-art supervised debiasing methods on five benchmark datasets, spanning natural language processing and structured data classification. Experimental results show that ULPL outperforms unsupervised and semi-supervised baselines, while also achieving performance competitive with state-of-the-art supervised techniques which have access to protected attributes at training time.

Figure 1: An overview of ULPL. Given a model trained to predict label y from x by optimizing a particular loss, we derive binary proxy labels over- vs. under-performing within each target class based on training losses. These proxy labels are then smoothed according to the neighbourhood in latent space. Finally, the group-unlabeled data is augmented with z', enabling the application of supervised bias mitigation methods.

In Section 5, we show that the proxy labels inferred by our method correlate with known demographic data, and that it is effective over multi-class intersectional groups and different notions of group-wise fairness. Moreover, we test our hypothesis of locality smoothing by studying the predictability of protected attributes and robustness to hyperparameters in finding neighbours.

2 RELATED WORK

Representational fairness   One line of work in the fairness literature is on protected information **leakage**, i.e., bias in the hidden representations. For example, it has been shown that protected information influences the geometry of the embedding space learned by models (Caliskan et al., 2017; May et al., 2019). Previous work has also shown that downstream models learn protected information such as authorship that is unintentionally encoded in hidden representations, even if the model does not have access to protected information during training Li et al. (2018); Wang et al. (2019); Zhao et al. (2019); Han et al. (2021c).

To learn fair representations, a considerable number of debiasing approaches have been proposed, with common strategies being to: (1) manipulate training datasets to balance protected attributes Zhao et al. (2017); Wang et al. (2019); Zmigrod et al. (2019); (2) adversarially add approximations of the mutual information between representations and sensitive attributes to the learning objectives through adversarial learning (Wadsworth et al., 2018; Elazar & Goldberg, 2018) or contrastive learning (Gupta et al., 2021; Shen et al., 2021); and (3) post-process the representations (Caliskan et al., 2017; May et al., 2019; Ravfogel et al., 2020).

However, it has been shown that although supervised debiasing methods reduce performance disparities in downstream tasks, leakage is still high (Han et al., 2021c).

Rather than reduce leakage, in this work, we make use of leakage as a robust and reliable signal of unobserved protected labels and derive proxy information from biased hidden representations for bias mitigation.

Empirical fairness   Another line of work focuses on empirical fairness by measuring model performance disparities across protected groups, e.g., via demographic parity (Dwork et al., 2012), equalized odds and equal opportunity (Hardt et al., 2016), or predictive parity (Chouldechova, 2017). Based on aggregation across groups, empirical fairness notions can be further broken down into group-wise fairness, which measures relative dispersion across protected groups (Li et al., 2018; Ravfogel et al., 2020; Han et al., 2021b; Lum et al., 2022), and per-group fairness, which reflects

extremum values of bias (Zafar et al., 2017; Feldman et al., 2015; Lahoti et al., 2020). We follow previous work (Ravfogel et al., 2020; Han et al., 2021c; Shen et al., 2022) in focusing primarily on improving group-wise equal opportunity fairness.

There is a broad range of approaches for incorporating these fairness notions into downstream task models, for example, re-balancing instances for each protected group in each minibatch (Roh et al., 2021), or adding constraints on performance disparities to the training objective (Kearns et al., 2018; Subramanian et al., 2021; Shen et al., 2022). Similar to methods for learning fair representations, most techniques for empirical fairness require protected labels for bias mitigation.

Unsupervised bias mitigation   Since upstream representations are agnostic to downstream tasks, bias mitigation of upstream representations is task-agnostic, i.e., protected attributes in downstream datasets are not required (Wang et al., 2020; Dinan et al., 2020; Liang et al., 2020). However, recent work (Steed et al., 2022) shows that debiasing upstream representations is less effective for empirical fairness than debiasing downstream representations, which, as mentioned earlier, are mostly supervised in terms of protected labels. This paper focuses on bias mitigation on downstream models directly, in an unsupervised setting. This distinguishes our proposed method from previous downstream debiasing work.

In terms of downstream bias mitigation, recent work has considered semi-supervised bias mitigation, such as debiasing with partially-labelled protected attributes (Han et al., 2021a), noised protected labels(Awasthi et al., 2020; Wang et al., 2021; Awasthi et al., 2021), or domain adaptation of protected attributes (Coston et al., 2019; Han et al., 2021a). However, these approaches are semi-supervised, as true protected labels are still required for optimizing fairness objectives.

Although Gupta et al. (2018) has proposed to use observed features as proxies for unobserved protected labels, the selection of proxy features is handcrafted and does not generalize to unstructured inputs (e.g., text or images). Therefore, there is no guarantee of correlation between proxy labels and unobserved protected labels (Chen et al., 2019).

The most relevant line of work focuses on the notion of Max-Min fairness (Rawls, 2001), which aims to maximize the minimum performance across protected groups. Hashimoto et al. (2018) optimize worst-performing distributions without access to actual protected labels, but suffer from the risk of focusing on outliers, reducing the effectiveness of bias mitigation. Adversarially reweighted learning (ARL) (Lahoti et al., 2020) extends the idea by employing an additional adversary in training to prevent the optimization from focusing on noisy outliers, based on the notion of computational identifiability (Hébert-Johnson et al., 2017). However, adversarial training is notoriously non-convex, and there is no guarantee that the adversary will learn contiguous regions rather than identifying outliers. In contrast, our proposed neighbourhood smoothing method is memory-based, does not require adversarial training, and one can explicitly adjust the smoothness of neighbourhood search.

3 METHODS

3.1 PROBLEM FORMULATION

Consider a dataset consisting of n instances $\mathcal{D} = \{(\boldsymbol{x}_i, y_i, z_i)\}_{i=1}^n$, where $\boldsymbol{x}_i$ is an input vector to the classifier, $y_i \in [1, \ldots, C]$ represents target class label, and $z_i \in [1, \ldots, G]$ is the group label, such as gender. For unsupervised bias mitigation, protected labels are assumed to be unobserved at training and inference time. $n_{c,g}$ denotes the number of instances in a subset with target label c and protected label g, i.e., $\mathcal{D}_{c,g} = \{(\boldsymbol{x}_i, y_i, z_i) | y_i = c, z_i = g\}_{i=1}^n$. A vanilla model ($m = f \circ e$) consists of two connected parts: the encoder e is trained to compute the hidden representation from an input, $\boldsymbol{h} = e(\boldsymbol{x})$, and the classifier makes prediction, $\hat{y} = f(\boldsymbol{h})$.

Let $\mathcal{L}^{c,g} = \frac{1}{n_{c,g}} \sum_{(\boldsymbol{x}_i, y_i, z_i) \in \mathcal{D}_{c,g}} \ell(m(\boldsymbol{x}_i), y_i)$ be the average empirical risk for $\mathcal{D}_{c,g}$, where ℓ is a loss function such as cross-entropy. Similarly, let $\mathcal{L}^c$ denote the average for instances with target label c ($\mathcal{D}_c$), and $\mathcal{L}$ denote the overall empirical risk.

Fairness measurement   We follow previous work in measuring group-wise performance disparities (Ravfogel et al., 2020; Roh et al., 2021; Shen et al., 2022). Specifically, for a particular utility metric U, e.g., the true positive rate, the results for each protected group are C-dimensional vectors,

one dimension for each class. For the subset of instances $\mathcal{D}_{c,g}$, we denote the corresponding evaluation results as $U_{c,g}$. Let U_c denote the overall utilities of class c, then group-wise fairness is achieved if the utilities of all groups are identical, $U_{c,g} = U_c, \forall c, g \Leftrightarrow |U_{c,g} - U_c| = 0, \forall c, g$. In addition to the overall performance metric U, we denote the fairness metric F, as a measurement of group-wise utility disparities.

3.2 Unsupervised Locality-based Proxy Label Assignment

Proxy label assignment To mitigate bias, the first question is how to minimize disparities of non-differentiable metrics in model training. Previous work has shown that empirical risk-based objectives can form a practical approximation of expected fairness, as measured by various metrics including AUC-ROC (Lahoti et al., 2020), positive rate (Roh et al., 2021), and true positive rate (Shen et al., 2022).

By replacing the utility metrics U with empirical risks w.r.t. an appropriate loss function $\mathcal{L}$, the group-wise fairness metrics are reformulated as $\sum_{c=1}^{C} \sum_{g=1}^{G} |\mathcal{L}^{c,g} - \mathcal{L}^{c}| = 0$, which is an approximation of the desired fairness measurement $\sum_{c=1}^{C} \sum_{g=1}^{G} |U_{c,g} - U_c| = 0$.

However, protected labels (z) are not observed in unsupervised debiasing settings, which raises the question: how can we optimize fairness objectives with unobserved protected labels?

Based on the fairness objective $\sum_{c=1}^{C} \sum_{g=1}^{G} |\mathcal{L}^{c,g} - \mathcal{L}^{c}| = 0$, we propose to focus on groups within each target class that are systematically poorly modelled. To this end, we binarize the numerous unobserved group labels into two types based on their training losses: $z_i' = \mathbf{1}_{\mathcal{L}_i > \mathcal{L}_i^{y_i}}$, where z_i' denotes the augmented proxy group label. The two types of protected labels indicate that the loss of an instance is either greater than the mean (an 'under-represented' group) or $\leq$ the mean (an 'over-represented' group). Each instance can now be assigned with a binary proxy label and used with existing debiasing methods, resulting in augmented datasets $\mathcal{D}' = \{(\boldsymbol{x}_i, y_i, z_i')\}_{i=1}^{n}$.

Neighbourhood smoothing Simply focusing on worse-performing instances can force the classifier to memorize noisy outliers (Arpit et al., 2017), reducing the effectiveness of bias mitigation. To address this problem, we find the neighbourhood that is likely to be from the same demographic based on the observation of protected information leakage (introduced in Section 2, and justified in Section 5.2), and smooth the proxy label of each instance based on its neighbours.

Specifically, we use the notion of data locality and adopt a k-Nearest-Neighbour classifier (k-NN) to smooth the proxy label. Given hidden representations $\{\boldsymbol{h}_1, \boldsymbol{h}_2, \ldots, \boldsymbol{h}_n\}$, where $\boldsymbol{h}_i = e(\boldsymbol{x}_i)$, and a query point $\boldsymbol{h}_j$, k-NN searches for the k points $\{\boldsymbol{h}_{j_1}, \boldsymbol{h}_{j_2}, \ldots, \boldsymbol{h}_{j_k}\}, s.t.\ y_j = y_{j_k}$ is closest in distance to $\boldsymbol{h}_j$, and then makes predictions through majority vote among proxy labels $\{z_{j_1}', z_{j_2}', \ldots, z_{j_k}'\}$. Unlike the standard setting of k-NN, where the query point is excluded from consideration, we include the query instance. As a result, the smoothing process degrades to using naive proxy labels when $k = 1$, where the discriminator prediction is the original proxy label without smoothing. For $k > 1$, on the other hand, neighbourhood smoothing comes into effect.

4 Experimental Results

This section demonstrates the effectiveness of our proposed method through experiments against various competitive baselines and across five widely-used datasets. We report evaluation results of all models based on average values over five runs with different random seeds for each dataset.

4.1 Experiment Setup

Datasets We consider the following benchmark datasets[1] from the fairness literature: (1) **Moji** (Blodgett et al., 2016; Elazar & Goldberg, 2018), sentiment analysis with protected attribute *race*; (2) **Bios** (De-Arteaga et al., 2019; Subramanian et al., 2021), biography classification with protected attributes *gender* and *economy*; (3) **TrustPilot** (Hovy et al., 2015), product rating prediction with protected attributes *age*, *gender*, and *country*; (4) **COMPAS** (Flores et al., 2016), recidivism

---

[1]Key characteristics of the datasets, including dataset statistics, are provided in Appendix A.

(a) Tuning ULPL+GD$_{\text{CLA}}$ trade-off hyperparameter. Shaded areas = 95% CI estimated over 5 runs.

(b) Performance–fairness curve of GD$_{\text{CLA}}$ (red dashed line), and ULPL+GD$_{\text{CLA}}$ (black solid line).

Figure 2: ULPL+GD$_{\text{CLA}}$ degrades to Vanilla performance (dotted lines) when setting $\lambda = 0$. As increase the weight of the fairness objective, fairness (orange dashed line) improves at the cost of performance (blue solid line). Figure 2b focuses on the Pareto frontier, and presents AUC-PFC as shaded area over the **Bios**-gender dataset.

prediction with protected attributes *gender* and *race*; and (5) **Adult** (Kohavi, 1996), income prediction with protected attributes *gender* and *race*.

To enable thorough comparison and explore correlation with unobserved protected attributes, for datasets with more than one protected attribute, we treat each protected attribute as a distinct task, e.g., **Bios**–gender, and **Bios**–economy are treated as two different tasks. As a result, there are ten different tasks in total.

Baselines We employ the following baselines: (1) Vanilla, which trains the classifier without explicit bias mitigation; (2) FairBatch (Roh et al., 2021), which adjusts the resampling probabilities of each protected group for each minibatch to minimize loss disparities; (3) GD$_{\text{CLA}}$ (Shen et al., 2022), which adjusts the weights of each protected group to minimize loss disparities; (4) GD$_{\text{GLB}}$ (Shen et al., 2022), which is a variant of GD$_{\text{CLA}}$ that additionally minimizes loss differences across target classes; (5) Adv (Li et al., 2018), which trains the adversary to identify protected information from hidden representations, and removes protected information through unlearning adversaries; (6) SemiAdv (Han et al., 2021a), which trains the adversary with partially-observed protected labels; and (7) ARL (Lahoti et al., 2020), which employs an adversary to assign larger weights to computationally-identifiable underrepresented instances. Besides the Vanilla model, methods (2)-(5) are supervised debiasing baselines, SemiAdv is a semi-supervised debiasing baseline method, and ARL is the baseline for unsupervised bias mitigation.

In terms of our proposed method, we examine its effectiveness in combination with several supervised debiasing methods, GD$_{\text{CLA}}$, GD$_{\text{GLB}}$, and Adv, denoted ULPL+GD$_{\text{CLA}}$, ULPL+GD$_{\text{GLB}}$, and ULPL+Adv, respectively. To be clear, the supervision in each case is based on the proxy labels z_i' learned in an unsupervised manner by ULPL.

Evaluation Metrics This paper is generalizable to different metrics by varying the objectives of the debiasing methods. For illustration purposes, we follow Ravfogel et al. (2020); Shen et al. (2022) and Han et al. (2021a) in measuring the overall accuracy and equal opportunity fairness, which measures true positive rate (TPR) disparities across groups. Consistent with Section 3.1, we measure the sum of TPR **gap** across subgroups to capture absolute disparities. We focus on less fair classes by using root mean square aggregation for class-wise aggregation. Overall, the fairness metric is $F = 1 - \sqrt{\frac{1}{C} \sum_{c=1}^{C} \left(\frac{1}{G} \sum_{g=1}^{G} |\text{TPR}_{c,g} - \text{TPR}_c| \right)^2}$. For both metrics, larger is better.

Model comparison Previous work has shown that debiasing methods suffer from performance–fairness trade-offs in bias mitigation (Shen et al., 2022). Most debiasing methods involve a trade-off hyperparameter to control the extent to which the model sacrifices performance for fairness, such

Dataset	Moji	Bios		TrustPilot			Adult		COMPAS	
Attribute	R	G	E	G	A	C	G	R	G	R
Vanilla	0.172	0.471	0.490	0.130	0.128	0.125	0.092	0.082	0.111	0.101
GD_{CLA}	0.249	0.498	0.507	0.133	0.131	0.132	0.095	0.084	0.124	0.100
GD_{GLB}	0.230	0.480	0.495	0.132	0.132	0.131	0.096	0.085	0.124	0.102
FairBatch	0.245	0.482	0.495	0.130	0.131	0.130	0.094	0.083	0.119	0.106
Adv	0.247	0.484	0.494	0.132	0.132	0.129	0.094	0.084	0.120	0.102
SemiAdv	0.247	0.483	0.495	0.131	0.132	0.131	0.094	0.082	0.121	0.097
ARL	0.193	0.461	0.484	0.129	0.132	0.129	0.097	0.086	0.123	0.096
ULPL+GD_{CLA}	0.209	0.485	0.503	0.133	0.132	0.131	0.093	0.082	0.126	0.105
ULPL+GD_{GLB}	0.190	0.474	0.495	0.133	0.132	0.131	0.094	0.085	0.127	0.105
ULPL+Adv	0.185	0.472	0.493	0.132	0.131	0.131	0.094	0.084	0.125	0.101

Table 1: AUC-PFC on five datasets w.r.t. different protected attributes: G: gender; E: economy; A: age; C: country; R:race. Debiasing methods are introduced in Section 4. AUC-PFC scores are calculated based on trade-off curves averaged over 5 repeated runs with different random seeds.

as $\lambda_{GD_{CLA}}$, the strength of additional regularization objectives of GD_{CLA} and our proposed method ULPL+GD_{CLA}. As shown in Figure 2a, given the performance–fairness trade-offs, selecting the best performance degrades to vanilla training and choosing the best fairness results in random predictions. As such, performance and fairness must be considered simultaneously in model comparisons, such as early stopping and hyperparameter tuning. We use protected attributes for early stopping over a validation set and report results on the test set. In practice, model selection should be made in a domain-specific manner, where the best method varies. To make quantitative comparisons based on the performance–fairness trade-offs, we follow Han et al. (2022) in reporting the area under the performance–fairness trade-off curves (AUC-PFC) of each method. As shown in Figure 2b, the performance–fairness trade-off curve (PFC) of a particular method consists of a Pareto frontier, which represents the best results that can be achieved in different scenarios, and the area under the curve based on PFC (AUC-PFC) reflects the overall goodness of a method. In particular, the AUC-PFC score of GD_{CLA} (red) and ULPL+GD_{CLA} (blue) are 0.498 and 0.485, respectively, and their difference (i.e., area between the two curves) is 0.013. See Appendix B for further details.

4.2 CAN WE MITIGATE BIAS WITHOUT ACCESS TO PROTECTED ATTRIBUTES?

Table 1 compares our proposed ULPL based methods against baselines.

Vanilla and supervised debiasing baselines: Compared with the Vanilla model, supervised debiasing baselines (GD_{CLA}, GD_{GLB}, FairBatch, and Adv) substantially improve fairness with relatively little performance cost, resulting in larger AUC-PFC scores. Among the four supervised debiasing methods, GD_{CLA} outperforms other methods, which is consistent with previous work (Shen et al., 2022).

Similar to the baseline debiasing methods, debiasing w.r.t. proxy labels (ULPL+∗) also improves fairness over Vanilla, and achieves results that are competitive with supervised debiasing methods.

Semi-supervised debiasing baselines: We examine the effectiveness of SemiAdv by removing 50% of the protected labels, i.e., the adversary is trained over a subset of training instances. Observe that SemiAdv achieves almost identical results to Adv, consistent with (Han et al., 2021a). Although SemiAdv uses protected labels in training, it is substantially outperformed by the proposed unsupervised method ULPL+GD_{CLA}.

Unsupervised debiasing baselines: ARL (Lahoti et al., 2020) is also an unsupervised debiasing method that trains an adversary to predict the weights of each instance such that the weighted empirical risk is maximized. The training objective of ARL does not match with the definition of group-wise fairness, and as such, it results in lower AUC-PFC scores than our proposed methods, that explicitly optimize for performance parity across protected groups.

Dataset	Moji	Bios		TrustPilot			Adult		COMPAS	
Attribute	R	G	E	G	A	C	G	R	G	R
F	0.636	0.837	0.915	0.963	0.971	0.960	0.951	0.751	0.894	0.672
$r_{z'}$	0.996	0.656	0.214	0.056	0.045	0.034	0.600	0.691	0.983	0.855

Table 2: Fairness (F) and Pearson's $r_{z'}$ between proxy labels and signed gaps for Vanilla.

In terms of excluding outliers, the adversary of ARL is intended to predict smooth weights of instances from $(\boldsymbol{x}, \mathrm{y})$, such that the trained model focuses more on worse-performing instances and is discouraged from memorizing noisy outliers. However, our results show that our ULPL method is more robust and effective in implementing these notions.

Different ULPL methods: Among the proxy label-based methods, ULPL+GD$_{\mathrm{CLA}}$ consistently outperforms other methods. ULPL+GD$_{\mathrm{CLA}}$ calculates the loss differences separately before aggregation, which eliminates the influence of group size in debiasing and treats each group and class equally in optimization, which is better aligned with the evaluation metric.

Adv is a popular method for achieving representational fairness, and differs from ULPL+GD$_{\mathrm{CLA}}$ and ULPL+GD$_{\mathrm{GLB}}$ in that it directly optimizes for empirical fairness. Removing protected information from hidden representations requires accurate perceptions of the global geometry of particular protected groups. However, proxy labels are based on local loss differences within each class, meaning that the same proxy label in different classes may conflate different protected groups. As such, the combination of ULPL with Adv is less effective than the two other combinations.

5 ANALYSIS

5.1 PROXY LABEL ASSIGNMENT

We first investigate if the ULPL labels are meaningful through the lens of Pearson's correlation ($r_{z'}$) between proxy labels and signed performance gaps. Given that F is optimized if $\sum_{c,g} |\mathrm{TPR}_{c,g} - \mathrm{TPR}_c| = 0$, an instance $(\boldsymbol{x}_i, \mathrm{y}_i)$ should be assigned $\mathrm{z}'_i = 0$ if $\mathrm{TPR}_{\mathrm{y}_i, \mathrm{z}_i} - \mathrm{TPR}_{\mathrm{z}_i} < 0$, i.e., the unobserved group z is under-performing in class y_i, and $\mathrm{z}'_i = 1$ otherwise. We calculate $r_{z'}$ between $P(\mathrm{z}' = 0|\mathrm{y}, \mathrm{z})$ and $\mathrm{TPR}_{\mathrm{y},\mathrm{z}} - \mathrm{TPR}_{\mathrm{z}}$, and presents the results of Vanilla over each dataset in Table 2.

It can be seen that there exists a strong correlation $r_{z'}$ for all datasets other than **TrustPilot**, indicating that the unsupervised proxy label recovers demographic data and provides a strong signal for bias mitigation. We also observe that better fairness results in smaller $r_{z'}$, for example, for **TrustPilot** and **Bios**-E, which is not surprising as the gaps ($|\mathrm{TPR}_{c,g} - \mathrm{TPR}_c|$) are close to 0.

5.2 EFFECTIVENESS OF THE NEIGHBOURHOOD-SMOOTHING

In smoothing ULPL labels, we hypothesise that an instance's neighbours are likely from the same protected group. Except for instance itself in smoothing, the remaining nearest neighbours are essentially the results of a standard k-nearest-neighbour (KNN) model. Therefore, we perform analysis based on standard KNN models and investigate if the remaining nearest neighbours are helpful for label smoothing, i.e., are they from the same protected group as the target instance.

Protected information predictability: Proxy label smoothing is based on the hypothesis that there is a strong correlation between the hidden representations and the protected labels, even if protected labels are not observed during training. To test this hypothesis, we employ 1-NN for protected label prediction based on Vanilla hidden representations within each target class, using leave-one-out cross-validation over each batch to evaluate the predictability of protected attributes.

Table 3a presents the results (macro F1 score) for each protected attribute, from which we can see a strong correlation between unobserved protected labels and hidden representations.

	Dataset	Moji	Bios		TrustPilot			Adult		COMPAS	
	Attribute	R	G	E	G	A	C	G	R	G	R
(a)	Leakage	83	79	84	40	52	26	80	25	83	43
(b)	ULPL+GD$_{\text{CLA}}$	9	1	1	1	1	1	13	13	3	13
	ULPL+GD$_{\text{GLB}}$	7	1	1	1	1	1	13	7	9	13
	ULPL+Adv	3	1	1	1	1	1	9	13	3	5

Table 3: **(a)** Leakage (%) of protected attributes. **(b)** Best k assignments of each method.

Furthermore, in Appendix D.2, we show that although debiasing methods successfully reduce performance disparities in downstream tasks, leakage of protected attributes in debiased hidden representations is still high, consistent with previous work (Han et al., 2021c).

Sensitivity to k-NN hyperparameters: Estimations of protected labels can be affected by k-NN's hyperparameters, including: (1) p, the norm of distance; (2) whether nearest-neighbours must match the target class versus all classes; and (3) k, the number of nearest neighbours. We explore the sensitivity to these hyperparameters for the **Moji** dataset in Figure 3.

First, we can see that k-NN is highly robust to varying values of p. In terms of whether label smoothing should be class-specific or inspecific, there is a slight empirical advantage to performing it in a class-specific manner.

Figure 3: Hyperparameter sensitivity analysis over the **Moji** dataset.

In terms of k, for **Moji**, higher values result in better estimations of protected labels, although there is a clear plateau. If we explore this effect over the other datasets in terms of the k value that achieves the highest AUC–PFC score, as can be seen in Table 3b, there is no clear trend, with neighbourhood-smoothing ($k > 1$) improving results for **Moji**, **Adult**, and **COMPAS** and the best results being achieved for values from 3 to 13, whereas for **Bios** and **TrustPilot**, no neighbourhood smoothing ($k = 1$) performs best. For **Bios**, we return to discuss this effect in Section 6, whereas for **TrustPilot**, we hypothesise that it is due to the leakage of protected information being very low, and accordingly the neighbourhoods of instances are noisy.

5.3 DEBIASING FOR INTERSECTIONAL GROUPS

We also investigate the robustness of binary proxy labels to non-binary intersectional groups (i.e. the cross product of values across different protected attributes).

Table 4 presents debiasing results for intersectional groups over those datasets that are labelled with more than one protected attribute. Compared to the single protected attribute results, the AUC-PFC scores of Vanilla are consistently smaller, indicating greater bias across intersectional groups, consistent with the

Dataset	Bios	TrustPilot	Adult	COMPAS
Attribute	$G{\times}E$	$G{\times}A{\times}C$	$G{\times}R$	$G{\times}R$
Vanilla	0.455	0.115	0.072	0.098
GD$_{\text{CLA}}$	0.487	0.126	0.072	0.091
GD$_{\text{GLB}}$	0.453	0.122	0.075	0.100
Adv	0.456	0.121	0.072	0.098
ARL	0.426	0.120	0.075	0.097
ULPL+GD$_{\text{CLA}}$	0.470	0.105	0.076	0.098
ULPL+GD$_{\text{GLB}}$	0.459	0.101	0.079	0.101
ULPL+Adv	0.456	0.122	0.071	0.099

Table 4: AUC-PFC w.r.t. intersectional groups.

findings of Subramanian et al. (2021). For ULPL models, on the other hand, the results are competitive with supervised debiasing methods, consistent with the single attribute setting.

Dataset	Moji	Adult			COMPAS		
Attribute	R	G	R	$G{\times}R$	G	R	$G{\times}R$
Vanilla	0.173	0.087	0.076	0.073	0.109	0.097	0.094
GD_{CLA}	0.253	0.091	0.081	0.079	0.121	0.094	0.085
GD_{GLB}	0.233	0.091	0.081	0.077	0.121	0.098	0.094
Adv	0.254	0.091	0.077	0.074	0.117	0.094	0.945
ARL	0.197	0.092	0.081	0.078	0.120	0.092	0.092
$ULPL+GD_{CLA}$	0.214	0.090	0.082	0.080	0.123	0.101	0.095
$ULPL+GD_{GLB}$	0.192	0.090	0.081	0.078	0.124	0.100	0.097
ULPL+Adv	0.186	0.091	0.083	0.080	0.122	0.099	0.092

Table 5: AUC-PFC based on demographic parity fairness.

5.4 Other Fairness Metrics: Demographic Parity

Finally, we investigate the robustness of ULPL to other notions of fairness. For illustration purposes, we focus on demographic parity fairness (DP) (Blodgett et al., 2016), which requires model predictions to be independent of protected attributes. Again, we aggregate accuracy and DP fairness trade-offs as AUC-PFC scores. Since DP is sensitive to class imbalance and there is no standard way of generalizing DP to multi-class classification tasks, we only conduct experiments over binary classification tasks, namely **Moji**, **Adult**, and **COMPAS**.

Table 5 shows the results w.r.t. demographic parity fairness. The overall trend is similar to our original results for equal opportunity fairness, indicating that ULPL is robust to different fairness metrics when combined with a range of debasing methods.

6 Limitations

As observed in Section 5.2, the optimal value of k varies greatly across datasets and debiasing methods, and in the context of this paper, we deal with this through a simple grid search over different values of k, which is computationally expensive.

Class-specific neighbourhood smoothing degrades to naive proxy labels when there are only a few instances in a particular class. For example, there are 28 distinct target classes in the **Bios** dataset, with a highly skewed distribution. There can be only one instance for a particular target class in a minibatch, and the neighbourhood smoothing does not work in this case.

7 Conclusion

Much of previous work in the fairness literature has the critical limitation that it assumes access to training instances labelled with protected attributes. To remove this restriction, we present a novel way of deriving proxy labels, enabling the adaptation of existing methods to unsupervised bias mitigation. We conducted experiments over five widely-used NLP and ML benchmark datasets, and showed that, when combined with different debiasing strategies, our proposed method consistently outperforms naively-trained models and unsupervised debiasing baselines, achieving results which are competitive with supervised debiasing methods. Furthermore, we showed our proposed method to be generalizable to multi-class intersectional groups and different notions of fairness.

Ethics Statement

This work focuses on learning fair models without observation of protected labels at training time. Demographics are assumed to be available only for evaluation purposes, and not used for model training or inference. We only use attributes that the user has self-identified in our experiments. All data and models in this study are publicly available and used under strict ethical guidelines.

REPRODUCIBILITY STATEMENT

All baseline experiments are conducted with the *fairlib* library (Han et al., 2022). Anonymized code is submitted as a .zip supplementary file for reviewing purposes.[2] Appendix A reports relevant statistics, details of train/test/dev splits, etc. for the five benchmark datasets that are used in this paper. Appendix B reports implementation details of evaluation metrics and corresponding aggregation approaches. Appendix C presents details of computing infrastructure used in our experiments, computational budget, hyperparameter search, etc. Appendix E reports PFC and full dis-aggregated results, i.e., mean $\pm$ std over 5 random runs with different random seeds.

REFERENCES

Devansh Arpit, Stanisław Jastrzundefinedbski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S. Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, and Simon Lacoste-Julien. A closer look at memorization in deep networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 233–242. JMLR.org, 2017.

Pranjal Awasthi, Matthäus Kleindessner, and Jamie H. Morgenstern. Equalized odds postprocessing under imperfect group information. In *AISTATS*, 2020.

Pranjal Awasthi, Alex Beutel, Matthaeus Kleindessner, Jamie H. Morgenstern, and Xuezhi Wang. Evaluating fairness of machine learning models under uncertain and incomplete information. *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 2021.

Su Lin Blodgett, Lisa Green, and Brendan O'Connor. Demographic dialectal variation in social media: A case study of African-American English. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 1119–1130, November 2016. doi: 10.18653/v1/D16-1120. URL https://www.aclweb.org/anthology/D16-1120.

Aylin Caliskan, Joanna J. Bryson, and Arvind Narayanan. Semantics derived automatically from language corpora contain human-like biases. *Science*, 356:183 – 186, 2017.

Jiahao Chen, Nathan Kallus, Xiaojie Mao, Geoffry Svacha, and Madeleine Udell. Fairness under unawareness: Assessing disparity when protected class is unobserved. *Proceedings of the Conference on Fairness, Accountability, and Transparency*, 2019.

Alexandra Chouldechova. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big data*, 5(2):153–163, 2017.

Amanda Coston, Karthikeyan Natesan Ramamurthy, Dennis Wei, Kush R. Varshney, Skyler Speakman, Zairah Mustahsan, and Supriyo Chakraborty. Fair transfer learning with missing protected attributes. *Proceedings of the 2019 AAAI/ACM Conference on AI, Ethics, and Society*, 2019.

Maria De-Arteaga, Alexey Romanov, Hanna Wallach, Jennifer Chayes, Christian Borgs, Alexandra Chouldechova, Sahin Geyik, Krishnaram Kenthapadi, and Adam Tauman Kalai. Bias in bios: A case study of semantic representation bias in a high-stakes setting. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, pp. 120–128, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Emily Dinan, Angela Fan, Adina Williams, Jack Urbanek, Douwe Kiela, and Jason Weston. Queens are powerful too: Mitigating gender bias in dialogue generation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 8173–8188, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.656. URL https://aclanthology.org/2020.emnlp-main.656.

---

[2]Source code is also available at https://anonymous.4open.science/r/An-Unsupervised-Locality-based-Method-for-Bias-Mitigation-2B30/

Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Proceedings of the 3rd Innovations in Theoretical Computer Science Conference*, pp. 214–226, 2012.

Yanai Elazar and Yoav Goldberg. Adversarial removal of demographic attributes from text data. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 11–21, 2018.

Bjarke Felbo, Alan Mislove, Anders Søgaard, Iyad Rahwan, and Sune Lehmann. Using millions of emoji occurrences to learn any-domain representations for detecting sentiment, emotion and sarcasm. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2017.

Michael Feldman, Sorelle A Friedler, John Moeller, Carlos Scheidegger, and Suresh Venkatasubramanian. Certifying and removing disparate impact. In *proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 259–268, 2015.

Anthony W. Flores, Kristin A. Bechtel, and Christopher T. Lowenkamp. False positives, false negatives, and false analyses: A rejoinder to "machine bias: There's software used across the country to predict future criminals. and it's biased against blacks". *Federal Probation*, 80:38, 2016.

Maya R. Gupta, Andrew Cotter, Mahdi Milani Fard, and Serena Wang. Proxy fairness. *ArXiv*, abs/1806.11212, 2018.

Umang Gupta, Aaron Ferber, Bistra N. Dilkina, and Greg Ver Steeg. Controllable guarantees for fair outcomes via contrastive information estimation. In *AAAI*, 2021.

Xudong Han, Timothy Baldwin, and Trevor Cohn. Decoupling adversarial training for fair NLP. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 471–477, August 2021a. doi: 10.18653/v1/2021.findings-acl.41. URL https://aclanthology.org/2021.findings-acl.41.

Xudong Han, Timothy Baldwin, and Trevor Cohn. Balancing out bias: Achieving fairness through training reweighting. *arXiv preprint arXiv:2109.08253*, 2021b.

Xudong Han, Timothy Baldwin, and Trevor Cohn. Diverse adversaries for mitigating bias in training. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 2760–2765, April 2021c. URL https://www.aclweb.org/anthology/2021.eacl-main.239.

Xudong Han, Aili Shen, Yitong Li, Lea Frermann, Timothy Baldwin, and Trevor Cohn. fairlib: A unified framework for assessing and improving classification fairness. *arXiv preprint arXiv:2205.01876*, 2022.

Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. *Advances in Neural Information Processing Systems*, 29:3315–3323, 2016.

Tatsunori Hashimoto, Megha Srivastava, Hongseok Namkoong, and Percy Liang. Fairness without demographics in repeated loss minimization. In *International Conference on Machine Learning*, pp. 1929–1938. PMLR, 2018.

Úrsula Hébert-Johnson, Michael P. Kim, Omer Reingold, and Guy N. Rothblum. Calibration for the (computationally-identifiable) masses. *ArXiv*, abs/1711.08513, 2017.

Dirk Hovy and Anders Søgaard. Tagging performance correlates with author age. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pp. 483–488, July 2015. doi: 10.3115/v1/P15-2079. URL https://aclanthology.org/P15-2079.

Dirk Hovy, Anders Johannsen, and Anders Søgaard. User review sites as a resource for large-scale sociolinguistic studies. *Proceedings of the 24th International Conference on World Wide Web*, 2015.

Michael Kearns, Seth Neel, Aaron Roth, and Zhiwei Steven Wu. Preventing fairness gerrymandering: Auditing and learning for subgroup fairness. In *International Conference on Machine Learning*, pp. 2564–2572. PMLR, 2018.

Diederick P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

Ron Kohavi. Scaling up the accuracy of naive-bayes classifiers: A decision-tree hybrid. In *KDD*, 1996.

Preethi Lahoti, Alex Beutel, Jilin Chen, Kang Lee, Flavien Prost, Nithum Thain, Xuezhi Wang, and Ed Chi. Fairness without demographics through adversarially reweighted learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 728–740, 2020. URL https://proceedings.neurips.cc/paper/2020/file/07fc15c9d169ee48573edd749d25945d-Paper.pdf.

Yitong Li, Timothy Baldwin, and Trevor Cohn. Towards robust and privacy-preserving text representations. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 25–30, July 2018. doi: 10.18653/v1/P18-2005. URL https://www.aclweb.org/anthology/P18-2005.

Paul Pu Liang, Irene Mengze Li, Emily Zheng, Yao Chong Lim, Ruslan Salakhutdinov, and Louis-Philippe Morency. Towards debiasing sentence representations. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5502–5515, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.488. URL https://aclanthology.org/2020.acl-main.488.

Marco Lui and Timothy Baldwin. langid. py: An off-the-shelf language identification tool. In *Proceedings of the ACL 2012 system demonstrations*, pp. 25–30, 2012.

Kristian Lum, Yunfeng Zhang, and Amanda Bower. De-biasing "bias" measurement. In *2022 ACM Conference on Fairness, Accountability, and Transparency (FAccT '22)*, Seoul, Republic of Korea, June 2022. ACM. doi: 10.1145/3531146.3533105.

R Timothy Marler and Jasbir S Arora. Survey of multi-objective optimization methods for engineering. *Structural and Multidisciplinary Optimization*, 26(6):369–395, 2004.

Chandler May, Alex Wang, Shikha Bordia, Samuel R. Bowman, and Rachel Rudinger. On measuring social biases in sentence encoders. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 622–628, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1063. URL https://aclanthology.org/N19-1063.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7237–7256, July 2020. doi: 10.18653/v1/2020.acl-main.647. URL https://aclanthology.org/2020.acl-main.647.

John Rawls. *Justice as Fairness: A Restatement*. Harvard University Press, 2001.

Yuji Roh, Kangwook Lee, Steven Euijong Whang, and Changho Suh. Fairbatch: Batch selection for model fairness. In *Proceedings of the 9th International Conference on Learning Representations*, 2021.

Aili Shen, Xudong Han, Trevor Cohn, Timothy Baldwin, and Lea Frermann. Contrastive learning for fair representations. *arXiv preprint arXiv:2109.10645*, 2021.

Aili Shen, Xudong Han, Trevor Cohn, Timothy Baldwin, and Lea Frermann. Optimising equal opportunity fairness in model training. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 4073–4084, Seattle, United States, July 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.naacl-main.299. URL https://aclanthology.org/2022.naacl-main.299.

Ryan Steed, Swetasudha Panda, Ari Kobren, and Michael L. Wick. Upstream mitigation is not all you need: Testing the bias transfer hypothesis in pre-trained language models. In *In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022.

Shivashankar Subramanian, Xudong Han, Timothy Baldwin, Trevor Cohn, and Lea Frermann. Evaluating debiasing techniques for intersectional biases. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 2492–2498, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. URL https://aclanthology.org/2021.emnlp-main.193.

Christina Wadsworth, Francesca Vera, and Chris Piech. Achieving fairness through adversarial learning: an application to recidivism prediction. *FAT/ML Workshop*, 2018.

Jialu Wang, Yang Liu, and Caleb C. Levy. Fair classification with group-dependent label noise. *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 2021.

Tianlu Wang, Jieyu Zhao, Mark Yatskar, Kai-Wei Chang, and Vicente Ordonez. Balanced datasets are not enough: Estimating and mitigating gender bias in deep image representations. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 5310–5319, 2019.

Tianlu Wang, Xi Victoria Lin, Nazneen Fatema Rajani, Bryan McCann, Vicente Ordonez, and Caiming Xiong. Double-hard debias: Tailoring word embeddings for gender bias mitigation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5443–5453, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.484. URL https://aclanthology.org/2020.acl-main.484.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rogriguez, and Krishna P Gummadi. Fairness constraints: Mechanisms for fair classification. In *Artificial Intelligence and Statistics*, pp. 962–970. PMLR, 2017.

Han Zhao, Amanda Coston, Tameem Adel, and Geoffrey J Gordon. Conditional learning of fair representations. In *International Conference on Learning Representations*, 2019.

Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Men also like shopping: Reducing gender bias amplification using corpus-level constraints. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 2979–2989, 2017.

Ran Zmigrod, Sabrina J. Mielke, Hanna Wallach, and Ryan Cotterell. Counterfactual data augmentation for mitigating gender stereotypes in languages with rich morphology. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1651–1661, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1161. URL https://aclanthology.org/P19-1161.

A DATASETS AND PRE-PROCESSING

A.1 MOJI

Following previous studies (Ravfogel et al., 2020; Han et al., 2021c), the original training dataset is balanced with respect to both sentiment and ethnicity but skewed in terms of sentiment–ethnicity combinations (40% happy-AAE, 10% happy-SAE, 10% sad-AAE, and 40% sad-SAE, respectively). The dev and test sets are balanced in terms of sentiment–ethnicity combinations. The dataset contains 100K/8K/8K train/dev/test instances.

When varying training set distributions, we keep the 8k test instances unchanged. We use DeepMoji (Caliskan et al., 2017) to obtain twitter representations, where DeepMoji is a model pretrained over 1.2 billion English tweets and DeepMoji is fixed during model training.

A.2 BIOS

Bios experiments are based on a biography classification dataset (De-Arteaga et al., 2019; Ravfogel et al., 2020), where biographies were scraped from the web, and annotated for the protected attribute of binary gender and target label of 28 profession classes.

Besides the binary gender attribute, we additionally consider economic status as a second protected attribute. Subramanian et al. (2021) semi-automatically labelled economic status based on the individual's home country (wealthy vs. rest of world), as geotagged from the first sentence of the biography. For bias evaluation and mitigation, we consider the intersectional groups, i.e., the Cartesian product of the two protected attributes, leading to 4 intersectional classes: female–wealthy, female–rest, male–wealthy, and male–rest.

Since the data is not directly available, in order to construct the dataset, we use the scraping scripts of Ravfogel et al. (2020), leading to a dataset with 396k biographies.[3] Following Ravfogel et al. (2020), we randomly split the dataset into train (65%), dev (10%), and test (25%).

The augmentation for economic attributes follows previous work (Subramanian et al., 2021), which results in approximate 30% instances that are labelled with both protected attributes.

Profession	Total	Male		Female	
		$	$	$	$
professor	21715	46	9	37	7
physician	7581	42	8	41	8
attorney	6011	51	10	33	6
photographer	4398	53	11	30	6
journalist	3676	41	9	41	9
nurse	3510	8	1	76	15
psychologist	3280	31	6	52	11
teacher	2946	35	6	49	10
dentist	2682	52	11	30	6
surgeon	2465	73	12	13	2
architect	1891	64	12	21	3
painter	1408	47	9	36	8
model	1362	15	2	70	13
poet	1295	46	7	39	8
software engineer	1289	70	14	14	2
filmmaker	1225	56	10	29	6
composer	1045	70	14	14	2
accountant	1012	55	9	29	6
dietitian	730	5	1	82	12
comedian	499	69	9	19	3
chiropractor	474	62	14	21	3
pastor	453	59	15	23	4
paralegal	330	12	3	70	15
yoga teacher	305	13	3	71	12
interior designer	267	16	4	67	12
personal trainer	264	41	10	42	7
DJ	244	71	16	11	2
rapper	221	75	15	9	1
Total	72578	9	45	7	39

Table 6: For each profession in **Bios**, the table shows the number of individuals and the breakdown across demographics as a percentage. $ and $ denote the economic status (high vs. low, respectively).

A.3 TRUSTPILOT

We fellow previous work (Li et al., 2018) in using the **TrustPilot** dataset derived from Hovy et al. (2015), where each review is an-

---

[3]There are slight discrepancies in the dataset composition due to data attrition: the original dataset (De-Arteaga et al., 2019) had 399k instances, while 393k were collected by Ravfogel et al. (2020).

Score	Total	Female				Male			
		UK		US		UK		US	
		Over45	**Under35**	**Over45**	**Under35**	**Over45**	**Under35**	**Over45**	**Under35**
1	5051	13	17	3	3	23	31	4	6
2	1783	15	15	2	5	24	29	4	6
3	2001	14	15	3	4	25	26	4	8
4	4877	13	14	4	7	23	25	5	10
5	29489	17	11	5	4	26	22	5	9

Table 7: For each score in **TrustPilot**, the table shows the number of instances and the breakdown across demographics as a percentage.

notated with the target rating variable and associated with three protected labels gender (male vs. female), age (under-35-year-old vs. over-45-year-old), and, location (UK vs. the US). The original dataset contains 5 different countries (US, UK, Germany, Denmark, and France), and Li et al. (2018) discard non-English reviews after automatic language classification (Lui & Baldwin, 2012). Despite this, there are some non-English reviews in the filtered dataset, and there, we further drop instances from Germany, Denmark and France, resulting in a dataset with 54k instances in total.

A.4 **ADULT** AND **COMPAS**

Except for race features, we use the same pre-processing as in Lahoti et al. (2020) for **COMPAS** (Flores et al., 2016) and **Adult** (Kohavi, 1996) datasets with 5,278 and 43,131 examples, respectively. Lahoti et al. (2020) considers binary race groups (white vs. black). However, there are more than two protected groups in the original dataset. Specifically, there are 3 race groups in **COMPAS**: African-American, Caucasian, and Other; and 5 race groups in **Adult**: White, Asian-Pac-Islander, Amer-Indian-Eskimo, Other, Black..

B EVALUATION METRICS

For fair comparison across different debiasing approaches, we should select the hyperparameters consistently. Previous work has used different criteria for model selection, including: (1) minimum loss (Hashimoto et al., 2018; Li et al., 2018); (2) maximum utility (Lahoti et al., 2020), e.g., based on accuracy or F-measure; (3) manual selection based on visual inspection of the trade-off curve (Elazar & Goldberg, 2018; Ravfogel et al., 2020); and (4) constrained selection (Han et al., 2021c; Subramanian et al., 2021), by selecting the best fairness constrained to a particular level of performance, and vice versa. Each selection criterion reflects the performance at a particular situation, making it very hard to rigorously compare methods.

Instead, the AUC-PFC score is the integral of performance–fairness curves with respect to performance on an interval $[0, 1]$. For a particular dataset, by the definition of fairness metrics, a random classifier achieves the best fairness. Therefore, the integration from 0 to the random prediction accuracy is dataset-specific and is identical to different methods. In this paper, we normalize AUC-PFC scores for each dataset by ignoring the performance worse than random guess. Table 8 summaries the lowest accuracy scores w.r.t. each dataset.

Moji	**Bios**	**TrustPilot**	**Adult**	**COMPAS**
50%	30%	68%	76%	56%

Table 8: Majority label proportion, i.e., lowest accuracy of each dataset.

When calculating AUC-PFC scores, for these methods that are not flexible to achieve best fairness, we manually add the random model to the calculation. Taking the Vanilla model on **Moji** as an example, the performance and fairness are 0.7109 ± 0.0110 and 0.6358 ± 0.1331, respectively. The random model corresponds to 0.5 accuracy and 1.0 fairness. Given these two points, the PFC is the

line form $(0.7109, 0.6358)$ to $(0.5, 1)$, and the AUC-PFC score is

$$(0.7109 - 0.5) \times 0.6358 + 0.5 \times (0.7109 - 0.5) \times (1 - 0.6358) = 0.172,$$

which is consistent with Table 1.

However, we still need to select a model for early stopping before model selection. Instead of considering performance and fairness metrics separately, we use the distance to the optimal point ("DTO"), which quantifies the accuracy–fairness tradeoff (Marler & Arora, 2004; Han et al., 2021b). DTO measures the normalized Euclidean distance for a given combination of accuracy and fairness to the optimal point which denotes the ideal result, e.g., accuracy and fairness of 1.0. It is typically unachievable in practice.

C EXPERIMENTAL DETAILS

We conduct our experiments on an HPC cluster instance with 4 CPU cores, 32GB RAM, and one NVIDIA V100 GPU.

C.1 MODELS AND PARAMETER TUNING

All approaches presented in this paper share the same dataset-specific hyperparameters as the standard model. Hyperparameters are tuned using grid-search, in order to minimize distance to the optimal.

Hyperparameter	Search space	Best assignment				
		Moji	Bios	TrustPilot	Adult	COMPAS
number of epochs	-	100				
patience	-	10				
encoder	-	DeepMoji (Felbo et al., 2017)	BERT (Devlin et al., 2019)		-	-
embedding size	-	2304	768	768	101	447
hidden size	-	300				
number of hidden layers	$choice\text{-}integer[1, 3]$	2				
batch size	$loguniform\text{-}integer[64, 2048]$	1024	1024	1024	512	1024
optimizer	-	Adam (Kingma & Ba, 2015)				
learning rate	$loguniform\text{-}float[10^{-6}, 10^{-1}]$	3×10^{-5}	10^{-5}	3×10^{-5}	3×10^{-4}	10^{-4}
learning rate scheduler	-	reduce on plateau				
LRS patience	-	2 epochs				
LRS reduction factor	-	0.5				
Trainable Parameter	-	782k	329k	323k	122k	225k

Table 9: Search space of dataset-specific hyperparameters.

All debiasing methods in this paper does not introduce extra parameter to the main task model, and will not need to considered at the inference time. As such, we provide method-specific hyperparameters separately, and the search space for method-specific hyperparameters are shared across difference datasets.

- GD_{CLA} tunes the strength of the additional loss for minimizing absolute loss difference within each class. $loguniform\text{-}float[10^{-6}, 10^{-1}]$, 40 times.

- GD_{GLB} tunes the strength of the additional loss for minimizing absolute loss difference. $loguniform\text{-}float[10^{-5}, 10^{-0}]$, 40 times.

- FairBatch tunes the adjustment rate for resampling probabilities. $loguniform\text{-}float[10^{-4}, 10^{-0}]$, 40 times.

- Adv tunes the weights of unlearning adversaries in training. $loguniform\text{-}float[10^{-2}, 10^{+2}]$, 40 times.

- SemiAdv tunes the weights of unlearning adversaries in training. $loguniform\text{-}float[10^{-2}, 10^{+2}]$, 40 times.

Dataset	Moji	Bios			TrustPilot				Adult			COMPAS		
Attribute	R	G	E	$G{\times}E$	G	A	C	$G{\times}A{\times}C$	G	R	$G{\times}R$	G	R	$G{\times}R$
Vanilla	58	47	37	39	20	20	20	18	25	17	22	9	10	10
GD_{CLA}	55	131	131	149	43	36	36	42	26	26	27	10	11	12
GD_{GLB}	54	121	116	157	34	33	33	45	27	28	28	10	12	11
FairBatch	54	46	48	47	26	26	27	24	24	21	21	11	10	11
Adv	47	54	48	41	29	28	28	23	23	29	29	11	9	9
SemiAdv	51	57	53	42	30	29	30	25	24	20	29	11	11	9
ARL	47	71	73	40	27	25	27	20	22	21	23	11	11	12
$ULPL{+}GD_{CLA}$	148	35	37	40	31	33	34	33	51	55	54	15	16	18
$ULPL{+}GD_{GLB}$	148	35	37	38	32	33	34	32	49	54	54	15	16	17
ULPL+Adv	179	49	50	41	47	46	46	36	62	61	68	15	16	17

Table 10: Average computational budget, measured in seconds.

- **ARL** tunes the learning rate of learning adversaries in training. *loguniform-float*$[10^{-4},$ $10^{+2}]$, 40 times.
- **ULPL** methods tunes the k from 1 to 15, and p-norm from 2 to 6.

Notice that, this paper report the AUC-PFC, which eliminate the requirement for model selection, i.e., there is no best-found trade-off hyperparameters w.r.t. bias mitigation.

C.2 COMPUTATIONAL BUDGET

Table 10 shows average GPU time of model training. Noticing that debiasing components will not be used for inference, i.e., different methods have identical inference cost.

D ADDITIONAL RESULTS

D.1 PROXY LABEL ASSIGNMENT – MOJI

Sentiment	Race	$P(z' = 1)$	PPR↑	TPR↑	FPR↓	PPV↑	NPV↓
sad	SAE	17.0 ± 1.2	79.9 ± 0.8	91.2 ± 0.7	35.0 ± 3.1	91.3 ± 0.7	64.8 ± 2.2
	AAE	68.5 ± 1.7	14.3 ± 0.7	45.7 ± 2.6	6.4 ± 0.8	64.2 ± 3.2	87.3 ± 0.6
happy	SAE	55.3 ± 3.0	20.1 ± 0.8	65.0 ± 3.1	8.8 ± 0.7	64.8 ± 2.2	91.3 ± 0.7
	AAE	15.8 ± 2.3	85.7 ± 0.7	93.6 ± 0.8	54.3 ± 2.6	87.3 ± 0.6	64.2 ± 3.2

Table 11: Proxy label assignment without smoothing and evaluations for the Vanilla model over **Moji**. Evaluation results $\pm$ standard deviation (%) are averaged over 5 runs with different random seeds. $\pm P(z' = 1)$ refers to the proportion of instances being assigned with 1, indicating worse-performed groups. Evaluating metrics include: (1) positive predictive rate (PPR), corresponding to the demographic parity fairness (Blodgett et al., 2016), (2) true positive rate (TPR) and false positive rate (FPR), corresponding to equalized odds and equal opportunity fairness (Hardt et al., 2016), and (3) positive predictive value (PPV) and negative predictive value (NPV), corresponding to test fairness (Chouldechova, 2017).

We first investigate if the ULPL labels are meaningful through the lens of training examples in the **Moji** dataset. Table 11 presents the results of the Vanilla model.

It can be seen that, AAE tweets are more likely to be classified as happy, while SAE tweets are more likely to be classified as sad, resulting in consistent trend in gaps with respect to PPR, TPR, FPR, PPV, and NPV. Based on loss-disparities, AAE instances with sad target labels are more possible to be assigned with $z' = 1$ (68.5% vs. 17% for SAE and AAE, respectively), encouraging debiasing methods to focus more on sad-AAE instances in training. Similarly, happy-SAE instances are more likely to be assigned with $z' = 1$, indicating that happy-SAE are upweighted in training.

For the dataset distribution perspective of view, as introduced in Appendix A.1, **Moji** is balanced with respect to both sentiment and ethnicity but skewed in terms of sentiment–ethnicity combinations (40% happy-AAE, 10% happy-SAE, 10% sad-AAE, and 40% sad-SAE, respectively),

which is closely related to the DL assignments that minority groups within each target class are assigned with $z' = 1$. I.e., our proposed proxy label differentiates minority groups with majority groups within each target class without observing demographic labels.

D.2 PROTECTED LABEL PREDICTABILITY AFTER DEBASING

Neighbour smoothing requires protected information in hidden representations during the whole training, requiring encoded protected information in hidden representations. Han et al. (2021c) show that although supervised debiasing methods have shown success in reducing performance disparities in downstream tasks, the predictability of protected attributes in debiased hidden representations is still well above the ideal value. We take $\text{ULPL+GD}_{\text{CLA}}$ as an example and explore the protected label predictability across different debiased models (i.e., different trade-offs).

Figure 4: Predictability after debiasing.

As seen from Figure 4, fairness scores (the blue line) improve at the cost of performance. However, the predictability of protected labels is quite stable at a high level, indicating that protected information is still encoded in debiased models, and our proposed neighbourhood smoothing method is robust to bias mitigation.

D.3 EFFECTIVENESS OF THE NEIGHBOUR SMOOTHING

In smoothing z' labels, we hypothesis that the nearest neighbours of an instance are likely to from the same protected group. Except the instance itself, the remaining nearest neighbours are essentially the results of a standard k-nearest-neighbour (k-NN) model. Therefore, we perform analysis based on standard k-NN models, and investigate if the remaining nearest neighbours are helpful for label smoothing, i.e., from the same protected group as the target instance.

D.4 OTHER FAIRNESS METRICS, DP

We investigate the robustness of ULPL methods to other notions of fairness. For illustration purposes, we focus on demographic parity fairness (DP) (Blodgett et al., 2016) in this experiment, which requires model predictions to be independent with protected attributes. Again, we aggregate accuracy and DP fairness trade-offs as the AUC-PFC scores. Since DP is sensitive to class imbalance and there is no standard way of generalizing DP to multi-class classification tasks, we only conduct experiments over binary classification tasks, including **Moji**, **Adult**, and **COMPAS**. Table 12 shows results w.r.t. demographic parity fairness.

Trends for different methods are similar to the results of equal opportunity fairness, indicating that debasing methods are robust to different fairness metrics.

D.5 HOW DOES BIAS MITIGATION AFFECT FAIRNESS FOR UNOBSERVED GROUPS?

Proxy group labels (z') are dynamically adjusted at each minibatch during training, which differs from fixed protected labels in supervised debiasing. As a result, supervised debiasing methods based on the observed protected attributes z mitigate biases for particular protected groups.

While the proposed proxy label approaches focus on the group of instances that are underrepresented during training, which is expected to be more general than debiasing to a particular protected attribute. Figure 5 demonstrates

Figure 5: PFC of in-domain and cross-domain debiasing over the **Bios**–gender dataset.

Dataset	Moji	Adult			COMPAS		
Attribute	R	G	R	G×R	G	R	G×R
Vanilla	0.173	0.087	0.076	0.073	0.109	0.097	0.094
GD$_{\text{CLA}}$	0.253	0.091	0.081	0.079	0.121	0.094	0.085
GD$_{\text{GLB}}$	0.233	0.091	0.081	0.077	0.121	0.098	0.094
FairBatch	0.254	0.091	0.079	0.073	0.117	0.103	0.094
Adv	0.254	0.091	0.077	0.074	0.117	0.094	0.945
SemiAdv	0.255	0.090	0.077	0.074	0.119	0.093	0.945
ARL	0.197	0.092	0.081	0.078	0.120	0.092	0.092
ULPL+GD$_{\text{CLA}}$	0.214	0.090	0.082	0.080	0.123	0.101	0.095
ULPL+GD$_{\text{GLB}}$	0.192	0.090	0.081	0.078	0.124	0.100	0.097
ULPL+Adv	0.186	0.091	0.083	0.080	0.122	0.099	0.092

Table 12: AUC-PFC based on demographic parity fairness.

Dataset	S	T	Vanilla	GD$_{\text{CLA}}$	FairBatch	SemiAdv	ARL	ULPL+GD$_{\text{CLA}}$
Bios	G	E	-0.0011	0.0003	-0.0054	-0.0021	0.0018	0.0002
	E	G	-0.0041	-0.0131	-0.0166	-0.0188	-0.0028	-0.0120
TrustPilot	G	A	0.0025	0.0021	-0.0007	-0.0018	-0.0018	0.0006
	G	C	0.0047	0.0012	-0.0010	-0.0015	0.0004	0.0008
	A	G	-0.0017	-0.0032	-0.0006	0.0001	0.0009	-0.0020
	A	C	0.0018	-0.0009	-0.0001	-0.0000	0.0012	-0.0006
	C	G	-0.0041	-0.0023	-0.0001	-0.0003	-0.0007	-0.0023
	C	A	-0.0027	0.0011	0.0011	-0.0008	-0.0023	-0.0010
Adult	G	R	0.0053	-0.0098	-0.0045	0.0037	-0.0080	-0.0060
	R	G	-0.0023	-0.0010	-0.0040	-0.0033	-0.0012	-0.0020
COMPAS	G	R	-0.0012	-0.0036	-0.0036	0.0002	-0.0014	0.0011
	R	G	0.0058	-0.0026	0.0025	-0.0064	-0.0083	-0.0035
Average			0.0002	-0.0026	-0.0027	-0.0026	-0.0019	-0.0022

Table 13: AUC-PFC score differences between debiasing w.r.t. target protected attributes (**T**), and source protected attributes (**S**). Larger numbers indicate better generalizations to unobserved protected groups.

the difference in AUC-PFC scores between in-
domain debiasing and cross-domain debiasing. For each debiasing method, we train the debiased model and conduct model selections based on the source protected attribute (Economy). The trained models are then evaluated w.r.t. the target unobserved protected attribute (Gender). The ability to generalize to unobserved protected attributes is measured as the difference between in-domain and cross-domain AUC-PFC.

Table 13 summaries AUC-PFC differences across difference datasets w.r.t a subset of debiasing methods. Overall, Vanilla shows the best generalization to unobserved protected attributes, and unsupervised debiasing methods are better than supervised and semi-supervised debiasing methods.

Intuitively, the Vanilla model and unsupervised debiasing methods (ARL and ULPL+GD$_{\text{CLA}}$) are agnostic to cross-attribute generalization, and their difference should be close to 0 which is clearly not the case. The AUC-PFC decrease of these methods is caused by the model selection, i.e., although the training process is identical, different models may be selection based on their own protected attributes. As shown in Figure 5, the selected model of ULPL+GD$_{\text{CLA}}$ based on economy labels at accuracy around 0.6 is not a Pareto point for gender, confirming that decreases in AUC-PFC of Vanilla and unsupervised debiasing methods are caused by cross-domain model selection.

Selection	Method	Test Set		Development Set	
		Performance	**Fairness**	**Performance**	**Fairness**
F@P-5%	Vanilla	71.1± 1.1	63.6± 1.3	71.4± 1.2	65.9± 1.2
	GD$_{\text{CLA}}$	74.2± 0.3	92.9± 1.4	73.7± 0.3	94.5± 1.0
	GD$_{\text{GLB}}$	75.9± 0.4	77.6± 1.3	75.2± 0.2	79.7± 1.6
	FairBatch	75.4± 0.4	90.3± 0.8	74.8± 0.2	90.9± 0.7
	Adv	75.3± 0.4	89.7± 1.6	74.9± 0.3	91.0± 0.8
	SemiAdv	75.7± 0.2	90.1± 0.5	74.9± 0.4	91.1± 0.5
	ARL	70.7± 1.0	78.5± 5.5	69.2± 1.0	78.1± 5.7
	ULPL+RL	66.3± 2.0	85.7± 4.9	66.1± 2.1	86.7± 4.6
	ULPL+GD$_{\text{CLA}}$	66.7± 2.6	88.0± 7.0	66.2± 2.4	88.8± 6.8
	ULPL+GD$_{\text{GLB}}$	72.6± 0.4	65.1± 1.6	72.5± 0.6	66.9± 1.3
	ULPL+Adv	67.8± 5.6	69.4± 9.2	68.2± 5.5	71.2± 8.9
F@P-10%	Vanilla	71.1± 1.1	63.6± 1.3	71.4± 1.2	65.9± 1.2
	GD$_{\text{CLA}}$	74.2± 0.3	92.9± 1.4	73.7± 0.3	94.5± 1.0
	GD$_{\text{GLB}}$	75.9± 0.4	77.6± 1.3	75.2± 0.2	79.7± 1.6
	FairBatch	75.4± 0.4	90.3± 0.8	74.8± 0.2	90.9± 0.7
	Adv	75.3± 0.4	89.7± 1.6	74.9± 0.3	91.0± 0.8
	SemiAdv	75.7± 0.2	90.1± 0.5	74.9± 0.4	91.1± 0.5
	ARL	63.7± 3.8	84.6± 4.2	63.0± 3.9	85.9± 3.5
	ULPL+GD$_{\text{CLA}}$	64.6± 3.3	92.5± 3.0	64.8± 2.2	92.6± 2.4
	ULPL+GD$_{\text{GLB}}$	72.6± 0.4	65.1± 1.6	72.5± 0.6	66.9± 1.3
	ULPL+Adv	67.8± 5.6	69.4± 9.2	68.2± 5.5	71.2± 8.9

Table 14: Evaluation results ± standard deviation (%) of selected models over the **Moji** dataset.

E   FULL RESULTS

In addition to AUC-PFC scores, we present PFC and evaluation results for each dataset. We investigate two different selection criteria and report the evaluation results over the development and test sets. Specifically, we conduct model selection over the development set based on: (1) maximum fairness within a performance trade-off threshold of 5% (**F@P−5%**); and (2) maximum fairness within a performance trade-off threshold of 10% (**F@P−10%**).

For the demonstration purpose, here we present the results for **Moji**. The full disaggregated results of 15 settings are submitted along with source code in the supplementary file, and can also be seen at `https://anonymous.4open.science/r/An-Unsupervised-Locality-based-Method-for-Bias-Mitigation-2B30/unsupervised_bias_mitigation/NB_Appendix_indomain_tradeoffs_dispaly.ipynb`.

Moji Figure 6 shows performance–fairness trade-off curves of each debiasing methods. table 14 summaries performance and equal opportunity fairness results w.r.t. two different selection criteria over the test set and dev set.

Figure 6: PFC over the **Moji** dataset.