BENCHMARKING BIRD'S EYE VIEW DETECTION ROBUSTNESS TO REAL-WORLD CORRUPTIONS

ABSTRACT

The recent advent of camera-based bird's eye view (BEV) detection algorithms exhibits great potential for in-vehicle 3D object detection. Despite the progressively achieved results on the standard benchmark, the robustness of BEV detectors has not been thoroughly explored, which is critical for safe operations. Different from active sensors like LiDAR or RADAR, cameras tend to be more vulnerable in the presence of natural corruption occurring in real-world environments. To fill in this gap, we introduce nuScenes-C, a test suite that encompasses eight distinct corruptions with a high likelihood to occur due to sensor failure, movement, data processing, or adversarial weather. Based on nuScenes-C, we undertake an extensive evaluation across a wide range of BEV detection models to understand their resilience and reliability. Our findings indicate a strong correlation between absolute performance on in-distribution and out-of-distribution datasets. Nonetheless, there is considerable variation in relative performance across different approaches. Our experiments further demonstrate that pre-training and depth-free BEV transformation have the potential to enhance out-of-distribution robustness. The benchmark is openly accessible at `https://github.com/Daniel-xsy/RoboBEV`.

1 INTRODUCTION

Deep neural network-based 3D object detectors, such as those presented in Li et al. (2022b); Wang et al. (2022b); Huang et al. (2021); Liu et al. (2022a); Wang et al. (2022a; 2021); Lang et al. (2019); Vora et al. (2020); Zhou & Tuzel (2018); Yan et al. (2018), have demonstrated promising performance on various challenging real-world benchmarks, including the KITTI Geiger et al. (2012), Waymo Open Sun et al. (2020), and nuScenes Caesar et al. (2020). These popular approaches utilize either point clouds Lang et al. (2019); Vora et al. (2020); Zhou & Tuzel (2018); Yan et al. (2018) or images Wang et al. (2021; 2022a;b); Li et al. (2022b;a); Huang et al. (2021); Liu et al. (2022a) as inputs for detection tasks. In comparison to LiDAR-based methods, camera-based approaches have caught significant attention due to their low deployment cost, high computational efficiency, and dense semantic information. Additionally, camera-based detection exhibits inherent advantages in detecting long-range objects and identifying vision-based traffic signs.

Despite remarkable progress achieved by recent camera-based 3D object detection methods, their ability to withstand natural corruption remains inadequately understood. The reliability of camera-based 3D object detectors under corruption is crucial because these methods are usually applied in highly safety-critical systems (*e.g.*, autonomous driving systems) in the real world, which introduces a range of external factors, including fluctuations in lighting and diverse meteorological conditions. Moreover, images captured by the camera may become blurred or even fail to register, due to changes in velocity and sensor malfunction, respectively. Therefore, we are motivated to investigate the robustness of these approaches in the face of diverse natural corruptions.

To bridge this knowledge gap, we undertake the initial comprehensive benchmark for assessing the out-of-distribution robustness of camera-based BEV detectors. To facilitate this, we develop a novel dataset, namely **nuScenes-C**, which comprises eight distinct natural corruptions. Each corruption type is divided into three different levels – easy, moderate, and hard since corruptions can manifest themselves at varying intensities Hendrycks & Dietterich (2019). Our study entails a comprehensive investigation of diverse corruption settings, encompassing the failure of sensors, which often occurs

Figure 1: Radar charts of BEV detection model's robustness under different corruptions. The red region corresponds to the corruption error (CE) of DETR3D Wang et al. (2022b), which is chosen as the baseline when calculating the CE scores. We observe diverse behaviors for different detectors.

in real-time systems where individual cameras malfunction or a series of frames are lost during processing. We categorize this type of corruption as *Camera Crash* and *Frame Lost*, respectively. The second category of corruption results from vehicle motion and image processing. Specifically, images captured by cameras while moving at high speed may be *Motion Blur*, or the images may be *Color Quant* when memory is limited. Lastly, real-world scenarios contain diverse light and weather conditions. To analyze model performance under these conditions, we incorporate *Brightness*, *Low Light*, *Fog*, and *Snow* weather to cover the above situations.

Leveraging the proposed nuScenes-C dataset, we present an exhaustive analysis of camera-based 3D object detection models. In particular, our study benchmarks **11** existing models with **22** variants versions and provides noteworthy insights into their out-of-distribution robustness. As shown in Figure 1, the benchmark results indicate that models present competitive performance on clean dataset vary largely on corrupted data and different corrupted types, where methods using pre-training and depth-free BEV transformation exhibits better out-of-distribution robustness than those not. Additionally, temporal fusion should avoid error accumulation to provide better robustness. The above findings provide valuable insights for designing future models to strive for better out-of-distribution robustness.

The key contributions of this work are summarized as follows.

- To the best of our knowledge, we make the first attempt to benchmark the robustness of camera-based BEV 3D object detectors under natural corruptions.
- We conduct exhaustive experiments to benchmark 22 existing camera-only BEV 3D object detectors on the proposed nuScenes-C dataset.
- Our study provides an in-depth analysis of the experimental results, highlighting the factors that contribute to the superior robustness of certain camera-only BEV 3D object detectors on the out-of-distribution dataset.

2 RELATED WORK

Camera-based Bird's Eye View Detection. Compared to the monocular image input Wang et al. (2021); Park et al. (2021), conducting 3D detection by consuming multi-view images and building bird's eye view (BEV) representations Li et al. (2022b); Huang et al. (2021); Li et al. (2022a); Wang et al. (2022b); Liu et al. (2022a); Zhang et al. (2022); Lin et al. (2022); Roh et al. (2022); Shi et al. (2022) enjoys several advantages. First, it allows for joint learning from multi-view images. Second, the bird's eye perspective provides a physics-interpretable way for information fusion from different sensors and different timestamps Ma et al. (2022). Third, BEV output space can be readily applied

Table 1: Comparisons of configurations and performance among camera-based BEV detectors. **Pre-train** denotes the model is initialized from the pre-trained FCOS3D Wang et al. (2021) checkpoint. **Temporal** indicates the use of temporal information. **Depth** denotes models with explicit depth estimation branch. **CBGS** highlight models use class-balanced group-sampling Zhu et al. (2019).

Model	Pre-train	Temporal	Depth	CBGS	Backbone	BEV Encoder	NDS ↑	mCE (%) ↓	mRR (%) ↑
DETR3D	✓				ResNet	Attention	0.4224	100.00	70.77
DETR3D (cbgs)	✓			✓	ResNet	Attention	0.4341	99.21	70.02
BEVFormer (small)	✓	✓			ResNet	Attention	0.4787	101.23	59.07
BEVFormer-S (small)	✓				ResNet	Attention	0.2622	114.43	76.87
BEVFormer (base)	✓	✓			ResNet	Attention	0.5174	97.97	60.40
BEVFormer-S (base)	✓				ResNet	Attention	0.2622	101.87	69.33
PETR (r50)					ResNet	Attention	0.3665	111.01	61.26
PETR (vov)	✓				VoVNet-V2	Attention	0.4550	100.69	65.03
ORA3D	✓				ResNet	Attention	0.4436	99.17	68.63
PolarFormer (r101)	✓				ResNet	Attention	0.4602	96.06	70.88
PolarFormer (vov)	✓				VoVNet-V2	Attention	0.4558	98.75	67.51
SRCN3D (r101)	✓				ResNet	CNN + Attn.	0.4286	99.67	70.23
SRCN3D (vov)	✓				VoVNet-V2	CNN + Attn.	0.4205	102.04	67.95
Sparse4D (r101)	✓	✓			ResNet	CNN + Attn.	0.5438	100.01	55.04
BEVDet (r50)			✓	✓	ResNet	CNN	0.3770	115.12	51.83
BEVDet (r100)			✓	✓	ResNet	CNN	0.3877	113.68	53.12
BEVDet (tiny)			✓	✓	Swin	CNN	0.4037	116.48	46.26
BEVDepth (r50)			✓	✓	ResNet	CNN	0.4058	110.02	56.82
BEVerse (tiny)		✓	✓	✓	Swin	CNN	0.4665	110.67	48.60
BEVerse-S (tiny)			✓	✓	Swin	CNN	0.1603	137.25	28.24
BEVerse (small)		✓	✓	✓	Swin	CNN	0.4951	117.82	49.57
BEVerse-S (small)			✓	✓	Swin	CNN	0.2682	132.13	29.54

in many downstream tasks, like prediction and planning, which leads to substantial improvements in performance for BEV-based detection frameworks. Existing works can be basically divided into two categories based on whether they perform depth estimation explicitly. Inspired by LSS Philion & Fidler (2020), BEVDet Huang et al. (2021) utilizes an extra depth estimation branch to perform the transform from perspective view to bird's eye view (PE2BEV). BEVDepth Li et al. (2022a) makes more accurate depth estimation via explicit depth supervision from point clouds and further improves the performance. Based on the above pipeline, BEVerse proposes a unified framework for multi-task learning and achieving state-of-the-art performance. Another line of work performs PV2BEV without explicit depth estimation. Following DETR Carion et al. (2020), DETR3D represents 3D objects as queries and performs cross-attention via Transformer Vaswani et al. (2017) decoder. PETR Liu et al. (2022a;b) further improves performance by proposing 3D position-aware representations. BEVFormer Li et al. (2022b) introduces temporal cross-attention to extract BEV features from multi-timestamps images. PolarFormer Jiang et al. (2022) explores predicting 3D targets in polar coordinates. Inspired by the success of Sparse RCNN Sun et al. (2021), SRCN3D Shi et al. (2022) introduce sparse proposals for feature aggregation. Despite these works showing competitive results on the standard dataset, it's unclear how they behave in front of natural corruptions.

Robustness under Natural Corruptions. The assessment of model robustness has been an active research area in computer vision, where the evaluation is mainly focused on worst-case robustness against adversarial attacks. On the other hand, natural corruption robustness assesses the average-case performance of models against common corrupted images that are prevalent in real-world applications. Various benchmarks have been proposed to evaluate the robustness of 2D image classification models, including ImageNet-C Hendrycks & Dietterich (2019), ObjectNet Barbu et al. (2019), ImageNetV2 Recht et al. (2019), ImageNet-A Hendrycks et al. (2021b), and ImageNet-R Recht et al. (2019). ImageNet-C corrupts the ImageNet's test set with simulated corruptions like compression loss and motion blur, while ObjectNet collects a test set with rich variations in rotation, background, and viewpoint. ImageNetV2 re-collects a test set following ImageNet's protocol and evaluates the performance gap due to the natural distribution shift. Moreover, ImageNet-A and ImageNet-R benchmark the classifier's robustness to natural adversarial examples and abstract visual renditions, respectively. In this context, Hendrycks et al. (2021a) highlights the correlation between the robustness of simulated corruptions and the improvement of real-world corruptions. However, there is still a lack of comparable benchmarks to evaluate the out-of-distribution robustness of vision-based 3D object detection models, which are commonly used in safety-critical applications. To this end, we make the first attempt to understand the robustness of these models under natural corruptions.

(a) Corruption taxonomy

(b) Pixel histogram

Figure 2: Corruption examples and the pixel distribution from the proposed nuScenes-C dataset.

3 ROBOBEV BENCHMARK

Benchmark Design. Our benchmark is composed of eight distinct corruption types, which are applied to the validation set of nuScenes Caesar et al. (2020). This set contains 6019 images with 360-degree views. We adhere to the experimental protocol established in Hendrycks & Dietterich (2019) and establish three different levels of corruption intensity (easy, moderate, and hard) for each type of corruption. These severity levels are carefully set to avoid drastic performance drops that could hinder drawing meaningful conclusions. Additionally, we incorporate variation within each severity level of corruption to augment the diversity of the dataset.

Natural Corruptions. The initial category of corruption that we examine is sensor failure, which can arise in real-world settings due to physical damage to cameras. In our experiments, we simulate this scenario by introducing the *Camera Crash* corruption. More specifically, we randomly select a fixed set of cameras according to the corruption intensity and uniformly discard the corresponding images. Additionally, we propose *Frame Lost*, where we randomly drop various cameras independently with the same probability at every timestamp, emulating situations where some frames are lost in consecutive time sequences. This procedure is illustrated in Figure 3. The third corruption category, *Motion Blur*, occurs when images are blurred due to camera motion at high speeds. Furthermore, we account for images that are quantized when deployed on devices with strict memory constraints by considering the *Color Quantization* corruption. Lastly, the last four types of corruption pertain to lighting and weather conditions. We address these situations by including *Brightness*, *Low Light*, *Fog*, and *Snow*. The corrupted images are displayed in Figure 2(a).

Robustness Metrics. We follow the nuScenes Caesar et al. (2020) official metric to report performance on the nuScenes-C dataset: we report nuScenes Detection Score (NDS) and mean Average Precision (mAP), along with mean Average Translation Error (mATE), mean Average Scale Error (mASE), mean Average Orientation Error(mAOE), mean Average Velocity Error(mAVE), mean Average Attribute Error(mAAE). To better evaluate the robustness of models on the nuScenes-C dataset, we introduce two new metrics inspired by Hendrycks & Dietterich (2019) based on the nuScenes detection score (NDS). The first is the mean corruption error (mCE) which measures the

Figure 3: Temporal corruption. *Camera Crash* drop fixed set of camera images along timestamps; *Frame Lost* randomly drop frame along timestamps.

Table 2: Results for the Corruption Error (CE) of each model in our *RoboBEV* benchmark. **Bold**: Best in the column. Underline: Second best in the column. Blue : Best in the row if improve upon baseline. Yellow : Worst in the row if decline upon baseline.

Model	NDS ↑	mCE ↓	Camera	Frame	Quant	Motion	Bright	Dark	Fog	Snow
DETR3D	0.4224	100.00	100.00	100.00	100.00	100.00	100.00	**100.00**	100.00	100.00
DETR3D (cbgs)	0.4341	99.21	98.15	98.90	99.15	101.62	97.47	100.28	98.23	99.85
BEVFormer (small)	0.4787	102.40	101.23	101.96	98.56	101.24	104.35	105.17	105.40	101.29
BEVFormer (base)	0.5174	97.97	95.87	94.42	95.13	99.54	96.97	103.76	97.42	100.69
PETR (r50)	0.3665	111.01	107.55	105.92	110.33	104.93	119.36	116.84	117.02	106.13
PETR (vov)	0.4550	100.69	99.09	97.46	103.06	102.33	102.40	106.67	103.43	91.11
BEVDet (r50)	0.3770	115.12	105.22	109.19	111.27	108.18	123.96	123.34	123.83	115.93
BEVDepth (r50)	0.4058	110.02	103.09	106.26	106.24	102.02	118.72	114.26	116.57	112.98
BEVerse (tiny)	0.4665	110.67	95.49	94.15	108.46	100.19	122.44	130.40	118.58	115.69
BEVerse (small)	0.4951	107.82	92.93	101.61	105.42	100.40	110.14	123.12	117.46	111.48
ORA3D	0.4436	99.17	97.26	98.03	97.32	100.19	98.78	102.40	99.23	100.19
PolarFormer (r101)	0.4602	96.06	96.16	97.24	95.13	92.37	94.96	103.22	94.25	95.17
PolarFormer (vov)	0.4558	98.75	96.13	97.2	101.48	104.32	95.37	104.78	97.55	93.14
SRCN3D (r101)	0.4286	99.67	98.77	98.96	97.93	100.71	98.80	102.72	99.54	99.91
SRCN3D (vov)	0.4205	102.04	99.78	100.34	105.13	107.06	101.93	107.1	102.27	92.75
Sparse4D(R101)	**0.5438**	100.01	99.80	99.91	98.05	102.00	100.30	103.83	100.46	95.72

relative robustness of candidate models compared to the baseline model:

$$\text{CE}_i \;=\; \frac{\sum_{l=1}^{3}(1-\text{NDS})_{i,l}}{\sum_{l=1}^{3}(1-\text{NDS}_{i,l}^{\text{baseline}})}\;, \quad \text{mCE} \;=\; \frac{1}{N}\sum_{i=1}^{N}\text{CE}_i\;, \tag{1}$$

where i denotes the corruption type and l is the severity level.

To compare the relative robustness between nuScenes-C and the clean performance, we define a simple mean resilience rate (mRR) metric, which is calculated across three severity levels as:

$$\text{RR}_i \;=\; \frac{\sum_{l=1}^{3}\text{NDS}_{i,l}}{3\times\text{NDS}_{\text{clean}}}\;, \quad \text{mRR} \;=\; \frac{1}{N}\sum_{i=1}^{N}\text{RR}_i\;. \tag{2}$$

4 EXPERIMENT

In our study, we conduct a comprehensive benchmarking analysis of 22 models on the nuScenes-C dataset. We use DETR3D Wang et al. (2022b) as our baseline for the mCE metric, given that many of the state-of-the-art approaches are based on it. The main results are in Table 2 and Table 3.

Broadly speaking, we observe a solid linear relationship between the absolute performance on the nuScenes-C dataset and the performance on the clean nuScenes Caesar et al. (2020) dataset. Specifically, models with leading performance on the clean dataset are also more likely to perform better on the out-of-distribution dataset, as demonstrated in Figure 4(a). However, a closer examination reveals that the situation becomes more complex. We find that models with similar performance on the clean dataset exhibit diverse robustness under different types of corruption. For example, BEVerse (small)Zhang et al. (2022) significantly improves the robustness of *Camera Crash* over the

Table 3: Results for the Resilience Rate (RR) of each model in our *RoboBEV* benchmark. **Bold**: best in column. Underline: second best in column.

Model	mRR ↑	Camera	Frame	Quant	Motion	Bright	Dark	Fog	Snow
DETR3D	70.77	67.68	61.65	75.21	63.00	94.74	**65.96**	**92.61**	45.29
DETR3D (cbgs)	70.02	**68.90**	61.85	74.52	58.56	**95.69**	63.72	**92.61**	44.34
BEVFormer (small)	59.07	57.89	51.37	68.41	53.69	78.15	50.41	74.85	37.79
BEVFormer (base)	60.40	60.96	58.31	67.82	52.09	80.87	48.61	78.64	35.89
PETR (r50)	61.26	63.30	59.10	67.45	62.73	77.52	42.86	78.47	38.66
PETR (vov)	65.03	64.26	61.36	65.23	54.73	84.79	50.66	81.38	**57.85**
BEVDet (r50)	51.83	65.94	51.03	63.87	54.67	68.04	29.23	65.28	16.58
BEVDepth (r50)	56.82	65.01	52.76	67.79	61.93	70.95	43.30	71.54	21.27
BEVerse (tiny)	48.60	68.19	**65.10**	55.73	56.74	56.93	12.71	59.61	13.80
BEVerse (small)	49.57	67.95	50.19	56.70	53.16	68.55	22.58	57.54	19.89
ORA3D	68.63	68.87	61.99	75.74	59.67	91.86	58.90	89.25	42.79
PolarFormer (r101)	**70.88**	68.08	61.02	76.25	**69.99**	93.52	55.50	**92.61**	50.07
PolarFormer (vov)	67.51	68.78	61.67	67.49	51.43	93.9	53.55	89.10	54.15
SRCN3D (r101)	70.23	68.76	62.55	**77.41**	60.87	95.05	60.43	91.93	44.80
SRCN3D (vov)	67.95	68.37	61.33	67.23	50.96	92.41	54.08	89.75	59.43
Sparse4D$_{(R101)}$	55.04	52.83	48.01	60.87	46.23	73.26	46.16	71.42	41.54

(a) mCE *vs.* NDS   (b) mRR *vs.* NDS

Figure 4: The performance on nuScenes-C is improved as the performance on the clean nuScenes dataset. The relation of absolute performance is close to linear. However, when considering the relative performance, the mRR metric is more randomly distributed without a clear trend to increase.

baseline, while PETR (vov)Liu et al. (2022a) performs well in *Snow* weather. However, both models struggle to make accurate predictions under *Low Light* conditions.

Although the mCE metric reveals a clear linear relationship between the absolute performance on the clean dataset and that on the out-of-distribution nuScenes-C dataset, the mRR metric shows a large variation among models that exhibit similar performance on the clean dataset, as depicted in Figure 4(b). This indicates that models may overfit the clean dataset and fail to generalize well to the nuScenes-C dataset. Moreover, we observe that models with superior performance on the clean dataset do not necessarily perform better in terms of the mRR metric compared to the mCE metric. For example, Sparse4D Lin et al. (2022) outperforms DETR3D Wang et al. (2022b) on nuScenes with a significant margin (0.5504 *vs.* 0.4224), while all the mRR metrics of Sparse4D are lower than that of DETR3D. Additionally, DETR3D exhibits the most robust performance towards *Low Light* conditions, while BEVerse (tiny), which has better clean performance (0.4665 *vs.* 0.4224), only achieves a relative performance of approximately 12% under dark lighting conditions. These results suggest that the performance on the clean nuScenes Caesar et al. (2020) dataset cannot provide a comprehensive understanding of the model's performance, and therefore it is crucial to benchmark the state-of-the-art models from multiple perspectives.

To further investigate the behavior of model robustness, we break down the models into various components, namely, training strategies (e.g., FCOS3D Wang et al. (2021) pretraining and CBGS Zhu et al. (2019) resampling strategy for addressing unbalanced classes), model architectures (e.g., backbone and detection head), and approach pipelines (e.g., temporal cue learning and depth estimation). The results of this analysis are in Table 1. Specifically, we focus on FCOS3D Wang et al. (2021) pretraining and CBGS Zhu et al. (2019) resampling strategy, as they are commonly utilized in these

Figure 5: Depth estimation of BEVDepth Li et al. (2022a) under the *Snow* corruption.

approaches and have demonstrated effectiveness in improving the performance of the clean dataset. We find using pre-training and depth-free BEV transformation shows superior performance than those not. Additionally, different ways to fuse temporal information also lead to opposite results.

5 DISCUSSION

(a) mCE *vs.* NDS   (b) mRR *vs.* NDS

Figure 6: Pretrain largely improves the robustness of models on the out-of-distribution dataset.

5.1 DEPTH ESTIMATION

Prior works in this area can be classified into two categories based on their approach to depth estimation. The first category, including works such as BEVDet Huang et al. (2021), BEVDepth Li et al. (2022a), and BEVerse Zhang et al. (2022), incorporates an explicit depth-estimation branch in the pipeline. This is done because predicting 3D bounding boxes from monocular images is an ill-posed problem. These approaches first predict a per-pixel depth map, which is then used to map image features to corresponding 3D locations. Subsequently, they predict 3D targets in the bird's-eye view (BEV) perspective by aggregating BEV features in a bottom-up fashionWang et al. (2022b).

The second category of works uses predefined object queries Li et al. (2022b); Wang et al. (2022b) or sparse proposals Lin et al. (2022); Shi et al. (2022) to index 2D features in a top-down manner. These designs exhibit competitive performance on clean data, and we extend the analysis by examining their performance on out-of-distribution datasets.

Our evaluation results, as shown in Figure 1, demonstrate that the depth-based approaches, including BEVerse Zhang et al. (2022), BEVDet Huang et al. (2021), and BEVDepth Li et al. (2022a), struggle under most of corruption types. In addition, as shown in Table 2 and Table 3, all the depth-based approaches experience severe performance degradation when exposed to corrupted images, which may be attributed to inaccurate depth estimation, as illustrated in Figure 5. Due to the inaccurate depth intermediate, all the errors increase drastically compared to depth-free methods, whose mAAE and mASE are lower with considerable margin, as shown in Figure 7.

5.2 PRE-TRAINING

In recent years, pretraining has emerged as a promising technique for enhancing the performance of computer vision models across a range of tasks. In the context of 3D detection, it is common to use the FCOS3D Wang et al. (2021) weights as initialization. For the ResNet He et al. (2016) backbone. FCOS3D employs a depth weight of 0.2 for stable training, which is then switched to 1

(a) DETR3D   (b) BEVFormer

(c) BEVerse   (d) PolarFormer

Figure 7: Other metric reported on nuScenes Caesar et al. (2020) other than NDS.

for fine-tuning, as described in Wang et al. (2021). Alternatively, the VoVNet-V2 Lee & Park (2020) backbone is first trained on the DDAD15M Guizilini et al. (2020) dataset for depth estimation and then fine-tuned on the nuScenes Caesar et al. (2020) train set for the detection task. These two pretraining strategies can be categorized as semantic and depth pretraining, respectively. The results of these strategies are shown in Figure 6(a) and Figure 6(b), which demonstrate the benefits of pretraining for improving model robustness.

5.3 Temporal Modeling

In the context of autonomous driving applications, it remains challenging for models to accurately estimate the velocity of moving objects based on a single-frame input. Therefore, it is crucial for vision systems to leverage temporal cues to better perceive the surrounding environment. Previous works have proposed various approaches to learn effective temporal cues. In this study, we investigate whether temporal information can mitigate the influence of corrupted images. To this end, we compare the performance of BEVFormer Li et al. (2022b) and BEVerse Zhang et al. (2022), both of which have single-frame and multi-frame versions that allow us to analyze the impact of temporal information. Our experimental results, shown in Table 1, indicate that the use of multi-frame information largely improves the robustness for both the mCE and mRR metrics for BEVerse (*e.g.*, the BEVerse Small Zhang et al. (2022) improves from 132.12 to 117.82 on mCE and from 29.54 to 49.57 on mRR). Surprisingly, for BEVFormer Li et al. (2022b), the temporal cross-attention operation seems to improve the mCE metric but significantly degrades the mRR metric from 69.33 to 60.40. This can be attributed to that BEVFormer Li et al. (2022b) stores all the history information inside and updates it on-the-fly, the error caused by corruption can accumulate over time. On the other hand, BEVerse Zhang et al. (2022) only utilize fixed size past timestampes.

6 Conclusion

In this work, we utilize a corpus of eight diverse natural corruptions to create the nuScenes-C dataset, which is used to assess the out-of-distribution robustness of leading camera-only BEV 3D object detection approaches. Exhaustive experiments are conducted to investigate the factors that impact the model's robustness. The findings of this study provide valuable insights for designing future models that can achieve better out-of-distribution robustness.

REFERENCES

Andrei Barbu, David Mayo, Julian Alverio, William Luo, Christopher Wang, Dan Gutfreund, Josh Tenenbaum, and Boris Katz. Objectnet: A large-scale bias-controlled dataset for pushing the limits of object recognition models. *Advances in neural information processing systems*, 32, 2019.

Holger Caesar, Varun Bankiti, Alex H Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 11621–11631, 2020.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European conference on computer vision*, pp. 213–229. Springer, 2020.

Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *2012 IEEE conference on computer vision and pattern recognition*, pp. 3354–3361. IEEE, 2012.

Vitor Guizilini, Rares Ambrus, Sudeep Pillai, Allan Raventos, and Adrien Gaidon. 3d packing for self-supervised monocular depth estimation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2485–2494, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8340–8349, 2021a.

Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15262–15271, 2021b.

Junjie Huang, Guan Huang, Zheng Zhu, and Dalong Du. Bevdet: High-performance multi-camera 3d object detection in bird-eye-view. *arXiv preprint arXiv:2112.11790*, 2021.

Yanqin Jiang, Li Zhang, Zhenwei Miao, Xiatian Zhu, Jin Gao, Weiming Hu, and Yu-Gang Jiang. Polarformer: Multi-camera 3d object detection with polar transformers. *arXiv preprint arXiv:2206.15398*, 2022.

Alex H Lang, Sourabh Vora, Holger Caesar, Lubing Zhou, Jiong Yang, and Oscar Beijbom. Pointpillars: Fast encoders for object detection from point clouds. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 12697–12705, 2019.

Youngwan Lee and Jongyoul Park. Centermask: Real-time anchor-free instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 13906–13915, 2020.

Yinhao Li, Zheng Ge, Guanyi Yu, Jinrong Yang, Zengran Wang, Yukang Shi, Jianjian Sun, and Zeming Li. Bevdepth: Acquisition of reliable depth for multi-view 3d object detection. *arXiv preprint arXiv:2206.10092*, 2022a.

Zhiqi Li, Wenhai Wang, Hongyang Li, Enze Xie, Chonghao Sima, Tong Lu, Qiao Yu, and Jifeng Dai. Bevformer: Learning bird's-eye-view representation from multi-camera images via spatiotemporal transformers. *arXiv preprint arXiv:2203.17270*, 2022b.

Xuewu Lin, Tianwei Lin, Zixiang Pei, Lichao Huang, and Zhizhong Su. Sparse4d: Multi-view 3d object detection with sparse spatial-temporal fusion. *arXiv preprint arXiv:2211.10581*, 2022.

Yingfei Liu, Tiancai Wang, Xiangyu Zhang, and Jian Sun. Petr: Position embedding transformation for multi-view 3d object detection. *arXiv preprint arXiv:2203.05625*, 2022a.

Yingfei Liu, Junjie Yan, Fan Jia, Shuailin Li, Qi Gao, Tiancai Wang, Xiangyu Zhang, and Jian Sun. Petrv2: A unified framework for 3d perception from multi-camera images. *arXiv preprint arXiv:2206.01256*, 2022b.

Yuexin Ma, Tai Wang, Xuyang Bai, Huitong Yang, Yuenan Hou, Yaming Wang, Yu Qiao, Ruigang Yang, Dinesh Manocha, and Xinge Zhu. Vision-centric bev perception: A survey. *arXiv preprint arXiv:2208.02797*, 2022.

Dennis Park, Rares Ambrus, Vitor Guizilini, Jie Li, and Adrien Gaidon. Is pseudo-lidar needed for monocular 3d object detection? In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3142–3152, 2021.

Jonah Philion and Sanja Fidler. Lift, splat, shoot: Encoding images from arbitrary camera rigs by implicitly unprojecting to 3d. In *European Conference on Computer Vision*, pp. 194–210. Springer, 2020.

Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do imagenet classifiers generalize to imagenet? In *International conference on machine learning*, pp. 5389–5400. PMLR, 2019.

Wonseok Roh, Gyusam Chang, Seokha Moon, Giljoo Nam, Chanyoung Kim, Younghyun Kim, Sangpil Kim, and Jinkyu Kim. Ora3d: Overlap region aware multi-view 3d object detection. *arXiv preprint arXiv:2207.00865*, 2022.

Yining Shi, Jingyan Shen, Yifan Sun, Yunlong Wang, Jiaxin Li, Shiqi Sun, Kun Jiang, and Diange Yang. Srcn3d: Sparse r-cnn 3d surround-view camera object detection and tracking for autonomous driving. *arXiv preprint arXiv:2206.14451*, 2022.

Pei Sun, Henrik Kretzschmar, Xerxes Dotiwalla, Aurelien Chouard, Vijaysai Patnaik, Paul Tsui, James Guo, Yin Zhou, Yuning Chai, Benjamin Caine, et al. Scalability in perception for autonomous driving: Waymo open dataset. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2446–2454, 2020.

Peize Sun, Rufeng Zhang, Yi Jiang, Tao Kong, Chenfeng Xu, Wei Zhan, Masayoshi Tomizuka, Lei Li, Zehuan Yuan, Changhu Wang, et al. Sparse r-cnn: End-to-end object detection with learnable proposals. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 14454–14463, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Sourabh Vora, Alex H Lang, Bassam Helou, and Oscar Beijbom. Pointpainting: Sequential fusion for 3d object detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4604–4612, 2020.

Tai Wang, Xinge Zhu, Jiangmiao Pang, and Dahua Lin. Fcos3d: Fully convolutional one-stage monocular 3d object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 913–922, 2021.

Tai Wang, Xinge Zhu, Jiangmiao Pang, and Dahua Lin. Probabilistic and geometric depth: Detecting objects in perspective. In *Conference on Robot Learning*, pp. 1475–1485. PMLR, 2022a.

Yue Wang, Vitor Campagnolo Guizilini, Tianyuan Zhang, Yilun Wang, Hang Zhao, and Justin Solomon. Detr3d: 3d object detection from multi-view images via 3d-to-2d queries. In *Conference on Robot Learning*, pp. 180–191. PMLR, 2022b.

Yan Yan, Yuxing Mao, and Bo Li. Second: Sparsely embedded convolutional detection. *Sensors*, 18(10):3337, 2018.

Yunpeng Zhang, Zheng Zhu, Wenzhao Zheng, Junjie Huang, Guan Huang, Jie Zhou, and Jiwen Lu. Beverse: Unified perception and prediction in birds-eye-view for vision-centric autonomous driving. *arXiv preprint arXiv:2205.09743*, 2022.

Yin Zhou and Oncel Tuzel. Voxelnet: End-to-end learning for point cloud based 3d object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4490–4499, 2018.

Benjin Zhu, Zhengkai Jiang, Xiangxin Zhou, Zeming Li, and Gang Yu. Class-balanced grouping and sampling for point cloud 3d object detection. *arXiv preprint arXiv:1908.09492*, 2019.

A APPENDIX

A.1 FULL RESULT

In this section, we provide the full results of our benchmark. The results can be seen from Table 4 to Table 25.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4224	0.3468	0.7647	0.2678	0.3917	0.8754	0.2108
Cam Crash	0.2859	0.1144	0.8400	0.2821	0.4707	0.8992	0.2202
Frame Lost	0.2604	0.0898	0.8647	0.3030	0.5041	0.9297	0.2439
Color Quant	0.3177	0.2165	0.8953	0.2816	0.5266	0.9813	0.2483
Motion Blur	0.2661	0.1479	0.9146	0.3085	0.6351	1.0385	0.2526
Brightness	0.4002	0.3149	0.7915	0.2703	0.4348	0.8733	0.2028
Low Light	0.2786	0.1559	0.8768	0.2947	0.5802	1.0290	0.2654
Fog	0.3912	0.3007	0.7961	0.2711	0.4326	0.8807	0.2110
Snow	0.1913	0.0776	0.9714	0.3752	0.7486	1.2478	0.3797

Table 4: DETR3D Wang et al. (2022b) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4341	0.3494	0.7163	0.2682	0.3798	0.8421	0.1997
Cam Crash	0.2991	0.1174	0.7932	0.2853	0.4575	0.8471	0.2131
Frame Lost	0.2685	0.0923	0.8268	0.3135	0.5042	0.8867	0.2455
Color Quant	0.3235	0.2152	0.8571	0.2875	0.5350	0.9354	0.2400
Motion Blur	0.2542	0.1385	0.8909	0.3355	0.6707	1.0682	0.2928
Brightness	0.4154	0.3200	0.7357	0.2720	0.4086	0.8302	0.1990
Low Light	0.2766	0.1539	0.8419	0.3262	0.5682	1.09520	0.2847
Fog	0.4020	0.3012	0.7552	0.2710	0.4237	0.8302	0.2054
Snow	0.1925	0.0702	0.9246	0.3793	0.7648	1.2585	0.3577

Table 5: DETR3D Wang et al. (2022b) with cbgs results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4787	0.3700	0.7212	0.2792	0.4065	0.4364	0.2201
Cam Crash	0.2771	0.1130	0.8627	0.3099	0.5398	0.8376	0.2446
Frame Lost	0.2459	0.0933	0.8959	0.3411	0.5742	0.9154	0.2804
Color Quant	0.3275	0.2109	0.8476	0.2943	0.5234	0.8539	0.2601
Motion Blur	0.2570	0.1344	0.8995	0.3264	0.6774	0.9625	0.2605
Brightness	0.3741	0.2697	0.8064	0.2830	0.4796	0.8162	0.2226
Low Light	0.2413	0.1191	0.8838	0.3598	0.6470	1.0391	0.3323
Fog	0.3583	0.2486	0.8131	0.2862	0.5056	0.8301	0.2251
Snow	0.1809	0.0635	0.9630	0.3855	0.7741	1.1002	0.3863

Table 6: BEVFormer-Small Li et al. (2022b) results.

A.2 ADDITIONAL VISUALIZATION RESULT

More visualization results of the nuScenes-C dataset can be seen in Figure8.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.2622	0.1324	0.9352	0.3024	0.5556	1.1106	0.2466
Camera Crash	0.2013	0.0425	0.9844	0.3306	0.6330	1.0969	0.2556
Frame Lost	0.1638	0.0292	1.0051	0.4294	0.6963	1.1418	0.3954
Color Quant	0.2313	0.1041	0.9625	0.3131	0.6435	1.1686	0.2882
Motion Blur	0.1916	0.0676	0.9741	0.3644	0.7525	1.3062	0.3307
Brightness	0.2520	0.1250	0.9484	0.3034	0.6046	1.1318	0.2486
Low Light	0.1868	0.0624	0.9414	0.3984	0.7185	1.3064	0.3859
Fog	0.2442	0.1181	0.9498	0.3055	0.6343	1.1806	0.2592
Snow	0.1414	0.0294	1.0231	0.4242	0.8644	1.3622	0.4444

Table 7: BEVFormer-SingleFrame-Small Li et al. (2022b) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.5174	0.4164	0.6726	0.2734	0.3704	0.3941	0.1974
Cam Crash	0.3154	0.1545	0.8015	0.2975	0.5031	0.7865	0.2301
Frame Lost	0.3017	0.1307	0.8359	0.3053	0.5262	0.7364	0.2328
Color Quant	0.3509	0.2393	0.8294	0.2953	0.5200	0.8079	0.2350
Motion Blur	0.2695	0.1531	0.8739	0.3236	0.6941	0.9334	0.2592
Brightness	0.4184	0.3312	0.7457	0.2832	0.4721	0.7686	0.2024
Low Light	0.2515	0.1394	0.8568	0.3601	0.6571	1.0322	0.3453
Fog	0.4069	0.3141	0.7627	0.2837	0.4711	0.7798	0.2046
Snow	0.1857	0.0739	0.9405	0.3966	0.7806	1.0880	0.3951

Table 8: BEVFormer-Base Li et al. (2022b) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4129	0.3461	0.7549	0.2832	0.4520	0.8917	0.2194
Cam Crash	0.2879	0.1240	0.8041	0.2966	0.5094	0.8986	0.2323
Frame Lost	0.2642	0.0969	0.8352	0.3093	0.5748	0.8861	0.2374
Color Quant	0.3207	0.2243	0.8488	0.2992	0.5422	1.0003	0.2522
Motion Blur	0.2518	0.1434	0.8845	0.3248	0.7179	1.1211	0.2860
Brightness	0.3819	0.3093	0.7761	0.2861	0.4999	0.9466	0.2201
Low Light	0.2381	0.1316	0.8640	0.3602	0.6903	1.2132	0.3622
Fog	0.3662	0.2907	0.7938	0.2870	0.5162	0.9702	0.2254
Snow	0.1793	0.0687	0.9472	0.3954	0.8004	1.2524	0.4078

Table 9: BEVFormer-SingleFrame-Base Li et al. (2022b) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.3665	0.3174	0.8397	0.2796	0.6158	0.9543	0.2326
Cam Crash	0.2320	0.1065	0.9383	0.2975	0.7220	1.0169	0.2585
Frame Lost	0.2166	0.0868	0.9513	0.3041	0.7597	1.0081	0.2629
Color Quant	0.2472	0.1734	0.9121	0.3616	0.7807	1.1634	0.3473
Motion Blur	0.2299	0.1378	0.9587	0.3164	0.8461	1.1190	0.2847
Brightness	0.2841	0.2101	0.9049	0.3080	0.7429	1.0838	0.2552
Low Light	0.1571	0.0685	0.9465	0.4222	0.9201	1.4371	0.4971
Fog	0.2876	0.2161	0.9078	0.2928	0.7492	1.1781	0.2549
Snow	0.1417	0.0582	1.0437	0.4411	1.0177	1.3481	0.4713

Table 10: PETR (r50) Liu et al. (2022a) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4550	0.4035	0.7362	0.2710	0.4316	0.8249	0.2039
Cam Crash	0.2924	0.1408	0.8167	0.2854	0.5492	0.9014	0.2267
Frame Lost	0.2792	0.1153	0.8311	0.2909	0.5662	0.8816	0.2144
Color Quant	0.2968	0.2089	0.8818	0.3455	0.5997	1.0875	0.3123
Motion Blur	0.2490	0.1395	0.9521	0.3153	0.7424	1.0353	0.2639
Brightness	0.3858	0.3199	0.7982	0.2779	0.5256	0.9342	0.2112
Low Light	0.2305	0.1221	0.8897	0.3645	0.6960	1.2311	0.3553
Fog	0.3703	0.2815	0.8337	0.2778	0.4982	0.8833	0.2111
Snow	0.2632	0.1653	0.8980	0.3138	0.7034	1.1314	0.2886

Table 11: PETR (VoVNet-V2) Liu et al. (2022a) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4602	0.3916	0.7060	0.2718	0.3610	0.8079	0.2093
Cam Crash	0.3133	0.1425	0.7746	0.2840	0.4440	0.8524	0.2250
Frame Lost	0.2808	0.1134	0.8034	0.3093	0.4981	0.8988	0.2498
Color Quant	0.3509	0.2538	0.8059	0.2999	0.4812	0.9724	0.2592
Motion Blur	0.3221	0.2117	0.8196	0.2946	0.5727	0.9379	0.2258
Brightness	0.4304	0.3574	0.7390	0.2738	0.4149	0.8522	0.2032
Low Light	0.2554	0.1393	0.8418	0.3557	0.6087	1.2004	0.3364
Fog	0.4262	0.3518	0.7338	0.2735	0.4143	0.8672	0.2082
Snow	0.2304	0.1058	0.9125	0.3363	0.6592	1.2284	0.3174

Table 12: PolarFormer (r101) Jiang et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4558	0.4028	0.7097	0.2690	0.4019	0.8682	0.2072
Cam Crash	0.3135	0.1453	0.7626	0.2815	0.4519	0.8735	0.2216
Frame Lost	0.2811	0.1155	0.8019	0.3015	0.4956	0.9158	0.2512
Color Quant	0.3076	0.2000	0.8846	0.2962	0.5393	1.0044	0.2483
Motion Blur	0.2344	0.1256	0.9392	0.3616	0.6840	1.0992	0.3489
Brightness	0.4280	0.3619	0.7447	0.2696	0.4413	0.8667	0.2065
Low Light	0.2441	0.1361	0.8828	0.3647	0.6506	1.2090	0.3419
Fog	0.4061	0.3349	0.7651	0.2743	0.4487	0.9100	0.2156
Snow	0.2468	0.1384	0.9104	0.3375	0.6427	1.1737	0.3337

Table 13: PolarFormer (vov) Jiang et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4436	0.3677	0.7319	0.2698	0.3890	0.8150	0.1975
Cam Crash	0.3055	0.1275	0.7952	0.2803	0.4549	0.8376	0.2145
Frame Lost	0.2750	0.0997	0.8362	0.3075	0.4963	0.8747	0.2340
Color Quant	0.3360	0.2382	0.8479	0.2848	0.5249	0.9516	0.2432
Motion Blur	0.2647	0.1527	0.8656	0.3497	0.6251	1.0433	0.3160
Brightness	0.4075	0.3252	0.7740	0.2741	0.4620	0.8372	0.2029
Low Light	0.2613	0.1509	0.8489	0.3445	0.6207	1.2113	0.3278
Fog	0.3959	0.3084	0.7822	0.2753	0.4515	0.8685	0.2048
Snow	0.1898	0.0757	0.9404	0.3857	0.7665	1.2890	0.3879

Table 14: ORA3D Roh et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.3770	0.2987	0.7336	0.2744	0.5713	0.9051	0.2394
Cam Crash	0.2486	0.0990	0.8147	0.2975	0.6402	0.9990	0.2842
Frame Lost	0.1924	0.0781	0.8545	0.4413	0.7179	1.0247	0.4780
Color Quant	0.2408	0.1542	0.8718	0.3579	0.7376	1.2194	0.3958
Motion Blur	0.2061	0.1156	0.8891	0.4020	0.7693	1.1521	0.4645
Brightness	0.2565	0.1787	0.8380	0.3736	0.7216	1.2912	0.3955
Low Light	0.1102	0.0470	0.9867	0.5308	0.9443	1.2841	0.6708
Fog	0.2461	0.1404	0.8801	0.3018	0.7483	1.1610	0.3112
Snow	0.0625	0.0254	0.9853	0.7204	1.0029	1.1642	0.8160

Table 15: BEVDet (r50) Huang et al. (2021) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.3877	0.3008	0.7035	0.2752	0.5384	0.8715	0.2379
Cam Crash	0.2622	0.1042	0.7821	0.3004	0.6028	0.9783	0.2715
Frame Lost	0.2065	0.0805	0.8248	0.4175	0.6754	1.0578	0.4474
Color Quant	0.2546	0.1566	0.8457	0.3361	0.6966	1.1529	0.3716
Motion Blur	0.2265	0.1278	0.8596	0.3785	0.7112	1.1344	0.4246
Brightness	0.2554	0.1738	0.8094	0.3770	0.7228	1.3752	0.4060
Low Light	0.1118	0.0426	0.9659	0.5550	0.8904	1.3003	0.6836
Fog	0.2495	0.1412	0.8460	0.3269	0.7007	1.1480	0.3376
Snow	0.0810	0.0296	0.9727	0.6758	0.9027	1.1803	0.7869

Table 16: BEVDet (r101) Huang et al. (2021) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4037	0.3080	0.6648	0.2729	0.5323	0.8278	0.2050
Cam Crash	0.2609	0.1053	0.7786	0.3246	0.5761	0.9821	0.2822
Frame Lost	0.2115	0.0826	0.8174	0.4207	0.6710	1.0138	0.4294
Color Quant	0.2278	0.1487	0.8236	0.4518	0.7461	1.1668	0.4742
Motion Blur	0.2128	0.1235	0.8455	0.4457	0.7074	1.1857	0.5080
Brightness	0.2191	0.1370	0.8300	0.4523	0.7277	1.2995	0.4833
Low Light	0.0490	0.0180	0.9883	0.7696	1.0083	1.1225	0.8607
Fog	0.2450	0.1396	0.8459	0.3656	0.6839	1.2694	0.3520
Snow	0.0680	0.0312	0.9730	0.7665	0.8973	1.2609	0.8393

Table 17: BEVDet (swin-tiny) Huang et al. (2021) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4058	0.3328	0.6633	0.2714	0.5581	0.8763	0.2369
Cam Crash	0.2638	0.1111	0.7407	0.2959	0.6373	1.0079	0.2749
Frame Lost	0.2141	0.0876	0.7890	0.4134	0.6728	1.0536	0.4498
Color Quant	0.2751	0.1865	0.8190	0.3292	0.6946	1.2008	0.3552
Motion Blur	0.2513	0.1508	0.8320	0.3516	0.7135	1.1084	0.3765
Brightness	0.2879	0.2090	0.7520	0.3646	0.6724	1.2089	0.3766
Low Light	0.1757	0.0820	0.8540	0.4509	0.8073	1.3149	0.5410
Fog	0.2903	0.1973	0.7900	0.3021	0.6973	1.0640	0.2940
Snow	0.0863	0.0350	0.9529	0.6682	0.9107	1.2750	0.7802

Table 18: BEVDepth (r50) Li et al. (2022a) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4665	0.3214	0.6807	0.2782	0.4657	0.3281	0.1893
Cam Crash	0.3181	0.1218	0.7447	0.3545	0.5479	0.4974	0.2833
Frame Lost	0.3037	0.1466	0.7892	0.3511	0.6217	0.6491	0.2844
Color Quant	0.2600	0.1497	0.8577	0.4758	0.6711	0.6931	0.4676
Motion Blur	0.2647	0.1456	0.8139	0.4269	0.6275	0.8103	0.4225
Brightness	0.2656	0.1512	0.8120	0.4548	0.6799	0.7029	0.4507
Low Light	0.0593	0.0235	0.9744	0.7926	0.9961	0.9437	0.8304
Fog	0.2781	0.1348	0.8467	0.3967	0.6135	0.6596	0.3764
Snow	0.0644	0.0251	0.9662	0.7966	0.8893	0.9829	0.8464

Table 19: BEVerse (tiny) Zhang et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.1603	0.0826	0.8298	0.5296	0.8771	1.2639	0.5739
Cam Crash	0.0639	0.0165	0.9135	0.7574	0.9522	1.1890	0.8201
Frame Lost	0.0508	0.0141	0.9455	0.8181	0.9221	1.1765	0.8765
Color Quant	0.0642	0.0317	0.9478	0.7735	0.9723	1.2508	0.8397
Motion Blur	0.0540	0.0230	0.9556	0.8028	0.9339	1.2137	0.8826
Brightness	0.0683	0.0360	0.9369	0.7315	0.9878	1.3048	0.8531
Low Light	0.0100	0.0005	1.0097	0.9474	1.0048	1.1073	0.9561
Fog	0.0402	0.0179	0.9789	0.8230	1.0094	1.3083	0.8962
Snow	0.0107	0.0017	1.0021	0.9468	0.9968	1.1652	0.9612

Table 20: BEVerse-SingleFrame (tiny) Zhang et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4951	0.3512	0.6243	0.2694	0.3999	0.3292	0.1827
Cam Crash	0.3364	0.1156	0.6753	0.3331	0.4460	0.4823	0.2772
Frame Lost	0.2485	0.0959	0.7413	0.4389	0.5898	0.8170	0.4445
Color Quant	0.2807	0.1630	0.8148	0.4651	0.6311	0.6511	0.4455
Motion Blur	0.2632	0.1455	0.7866	0.4399	0.5753	0.8424	0.4586
Brightness	0.3394	0.1935	0.7441	0.3736	0.4873	0.6357	0.3326
Low Light	0.1118	0.0373	0.9230	0.6900	0.8727	0.8600	0.7223
Fog	0.2849	0.1291	0.7858	0.4234	0.5105	0.6852	0.3921
Snow	0.0985	0.0357	0.9309	0.7389	0.8864	0.8695	0.7676

Table 21: BEVerse (small) Zhang et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.2682	0.1513	0.6631	0.4228	0.5406	1.3996	0.4483
Cam Crash	0.1305	0.0340	0.8028	0.6164	0.7475	1.2273	0.6978
Frame Lost	0.0822	0.0274	0.8755	0.7651	0.8674	1.1223	0.8107
Color Quant	0.1002	0.0495	0.8923	0.7228	0.8517	1.1570	0.7850
Motion Blur	0.0716	0.0370	0.9117	0.7927	0.8818	1.1616	0.8833
Brightness	0.1336	0.0724	0.8340	0.6499	0.8086	1.2874	0.7333
Low Light	0.0132	0.0041	0.9862	0.9356	1.0175	0.9964	0.9707
Fog	0.0910	0.0406	0.8894	0.7200	0.8700	1.0564	0.8140
Snow	0.0116	0.0066	0.9785	0.9385	1.0000	1.0000	1.0000

Table 22: BEVerse-SingleFrame (small) Zhang et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4286	0.3373	0.7783	0.2873	0.3665	0.7806	0.1878
Cam Crash	0.2947	0.1172	0.8369	0.3017	0.4403	0.8506	0.2097
Frame Lost	0.2681	0.0924	0.8637	0.3303	0.4798	0.8725	0.2349
Color Quant	0.3318	0.2199	0.8696	0.3041	0.4747	0.8877	0.2458
Motion Blur	0.2609	0.1361	0.9026	0.3524	0.5788	0.9964	0.2927
Brightness	0.4074	0.3133	0.7936	0.2911	0.3974	0.8227	0.1877
Low Light	0.2590	0.1406	0.8586	0.3642	0.5773	1.1257	0.3353
Fog	0.3940	0.2932	0.7993	0.2919	0.3978	0.8428	0.1944
Snow	0.1920	0.0734	0.9372	0.3996	0.7302	1.2366	0.3803

Table 23: SRCN3D (r101) Shi et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.4205	0.3475	0.7855	0.2994	0.4099	0.8352	0.2030
Cam Crash	0.2875	0.1252	0.8435	0.3139	0.4879	0.8897	0.2165
Frame Lost	0.2579	0.0982	0.8710	0.3428	0.5324	0.9194	0.2458
Color Quant	0.2827	0.1755	0.9167	0.3443	0.5574	1.0077	0.2747
Motion Blur	0.2143	0.1102	0.9833	0.3966	0.7434	1.1151	0.3500
Brightness	0.3886	0.3086	0.8175	0.3018	0.4660	0.8720	0.2001
Low Light	0.2274	0.1142	0.9192	0.3866	0.6475	1.2095	0.3435
Fog	0.3774	0.2911	0.8227	0.3045	0.4646	0.8864	0.2034
Snow	0.2499	0.1418	0.9299	0.3575	0.6125	1.1351	0.3176

Table 24: SRCN3D (vov) Shi et al. (2022) results.

Corruption	NDS ↑	mAP ↑	mATE ↓	mASE ↓	mAOE ↓	mAVE ↓	mAAE ↓
Clean	0.5438	0.4409	0.6282	0.2721	0.3853	0.2922	0.1888
Cam Crash	0.2873	0.1319	0.7852	0.2917	0.4989	0.9611	0.2510
Frame Lost	0.2611	0.1050	0.8175	0.3166	0.5404	1.0253	0.2726
Color Quant	0.3310	0.2345	0.8348	0.2956	0.5452	0.9712	0.2496
Motion Blur	0.2514	0.1438	0.8719	0.3553	0.6780	1.0817	0.3347
Brightness	0.3984	0.3296	0.7543	0.2835	0.4844	0.9232	0.2187
Low Light	0.2510	0.1386	0.8501	0.3543	0.6464	1.1621	0.3356
Fog	0.3884	0.3097	0.7552	0.2840	0.4933	0.9087	0.2229
Snow	0.2259	0.1275	0.8860	0.3875	0.7116	1.1418	0.3936

Table 25: Sparse4D Lin et al. (2022) results.

Figure 8: More visualization results of nuScenes-C dataset. From left to right: easy, moderate, and hard.