Multilingual Automatic Speech Recognition for Scandinavian Languages

Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
`email@domain`

Anonymouser Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
`email@domain`

Abstract

We investigate the effectiveness of multilingual automatic speech recognition models for Scandinavian languages by further fine-tuning a Swedish model on Swedish, Danish, and Norwegian Bokmål. We first explore zero-shot models, which perform poorly across the three languages. However, we show that a multilingual model based on an existing strong Swedish further fine-tuned on all three languages performs well for Norwegian and Danish, with a relatively low decrease in the performance for Swedish. With a language classification module, we improve the performance of the multilingual model even further.

1 Introduction

Automatic speech recognition (ASR) is the task of transforming speech into text, often referred to as transcription. Multilingual ASR tackles the task in multiple languages with the same model or pipeline. Modern monolingual ASR architectures such as DeepSpeech (Hannun et al., 2014), Wav2Vec (Baevski et al., 2020), and Whisper (Radford et al., 2022) are capable of transcribing speech with Word Error Rates (WERs) well below 10 percent. To achieve this, models require copious amounts of data, which is unavailable for the vast majority of languages. For low-resource languages, multilingual models as means of bootstrapping the performance are often the only solution.

Conneau et al. (2021) demonstrate that a multilingual setting can be beneficial even for high-resource languages. Pratap et al. (2020), however, suggest that limiting models to smaller, typologically related languages is more productive than training on all languages at once. As such, it can be argued that Scandinavian languages are a great fit for multilingual NLP models. Swedish, Danish, and Norwegian all originate from old Norse and share numerous similarities, such as largely overlapping lexicons and similar grammar. As noted by Delsing (2005), the similarities across the three languages are not linear, since Swedish and Norwegian are most similar in speech, whereas Danish and Norwegian are most similar in writing. Nevertheless, Sahlgren et al. (2021) argue that Scandinavian languages are so similar that large text-based language models for these languages should be trained jointly. It has also been shown that utilizing the similarities between the Scandinavian languages can improve text-based tasks such as machine translation (e.g. Tiedemann, 2009) and parsing (e.g. Smith et al., 2018). However, to the best of our knowledge, we are not aware of any work where the usefulness of combining the Scandinavian languages is reported for some speech-based tasks, such as ASR.

In this paper, we focus on identifying whether a multilingual ASR model for Swedish, Danish, and Norwegian can be trained to utilize an existing high-quality monolingual model, as we fine-tune a strong Swedish end-to-end model to also handle the Danish and Norwegian languages. In addition, we analyze how well the monolingual ASR models transfer across the Scandinavian languages in a zero-shot setting. We also evaluate how the multilingual setting affects the quality of transcription as opposed to monolingual settings. Lastly, we show that a language classification module can be used for selecting a language model in the multilingual setting.

2 Previous Work

Language Models for ASR The usage of a language model in speech recognition has continuously proven to boost the quality of transcription. Positive results have been observed with

both statistical n-gram language models (Amodei et al., 2016; Håkansson and Hoogendijk, 2020) and transformer-based models, such as BERT (Baevski et al., 2020). Most considerable improvements seem to result from domain-specific language models, as contextualization and biasing of models have repeatedly improved the quality of transcription (Aleksic et al., 2015).

Multilingual ASR Transcription of multiple languages via a single model or pipeline has been made possible through a variety of architectures. Approaches range from an assemble of monolingual models connected through a preceding language classification component (Lyu and Lyu, 2008; Mabokela and Manamela, 2013; Barroso et al., 2010), to models sharing the phone models (Lin et al., 2009) or hidden layers of acoustic models (Benesty et al., 2008) across two or more languages, to being conjunct on all levels, sharing all components and treating all input languages as one (Pratap et al., 2020; Conneau et al., 2021).

As a general rule, the effects of a multilingual setting on the quality of transcription are twofold. Low-resource languages tend to reap the benefits, as models seemingly generalize from the patterns learned in higher-resource languages (Benesty et al., 2008; Bhable and Kayte, 2020). High-resource languages, however, tend to suffer (Lin et al., 2009; Conneau et al., 2021), likely due to the noise introduced through the exposure of models to data in a foreign language(s). Nevertheless, Pratap et al. (2020) demonstrated that there appear to be ways of mitigating the toll of a multilingual setting on the resource-rich languages by means of a typologically motivated choice of languages in a cluster as well as cluster-specific rather than one-for-all decoders.

3 Methodology

We first evaluate the performance of monolingual Swedish, Danish, and Norwegian models on the test sets of each language (i.e. Swedish model was evaluated on Swedish, Danish, and Norwegian test sets). For comparison, we also evaluate the performance of an English ASR model on the three Scandinavian languages. We do so first to obtain comparable word error rates of each model for their intended language, with the exception of English; second, to explore a zero-shot setting, where we explore whether the typological similarity of Scandinavian languages enables the ASR models

trained on one of the languages to transcribe the data in the other two languages.

In a second set of experiments, we fine-tune trial multilingual ASR models for Swedish, Danish, and Norwegian. We aim to utilize the high quality of the fine-tuned Swedish model (Malmsten et al., 2022) to bootstrap the transcription in Danish and Norwegian instead of training a model from scratch. As such, we attempt fine-tuning the Swedish model in the following settings:

1. **Retraining DA+NO** - using complete training sets in Danish and Norwegian (30,000 entries total)

2. **Retraining DA+No+SE_half** - using complete training sets in Danish and Norwegian, as well as half of the Swedish training data (37,500 entries in total)

3. **Retraining DA+NO+SE_full** - using complete training sets of all three languages (45,000 entries in total)

For comparison, we also fine-tune a model on all three languages (15,000 entries per language) from scratch on the pre-trained (but not fine-tuned) Swedish model[1]. We evaluate all models on the trilingual development set every 1,000 updates. These models were trained for 5 epochs.

In order to investigate the effect of adding a language model for the multilingual models, we train a language classifier on speech segments. The language classifier is described in Appendix A. It gives an overall strong performance of at least 0.97 percent for each language pair.

In our final experiment, we select the best-performing trail model (Retraining DA+NO+SE_full) to train a multilingual model for 20 epochs. We evaluate the model in two settings. In the first, we use no language model in the decoding. In the second, we use the trained classifier to predict the language, in order to select a 4-gram language model for the predicted language. We train the 4-gram language models on the entirety of the original NST training sets, except for Swedish, where we exclude the sample used as test set.

We report Word Error Rate as our main evaluation metric.

---

[1] https://huggingface.co/KBLab/wav2vec2-large-voxrex

Table 1: WERs of monolingual models on the three Scandinavian languages, no language model versus a 4-gram language model.

Model	Test Set	No LM	With LM
Swedish	Swedish	2.19%	2.74%
	Danish	78.58%	72.69%
	Norwegian	61.78%	52.06%
Danish	Swedish	120.10%	98.93%
	Danish	19.14%	13.82%
	Norwegian	104.56%	90.06%
Norwegian	Swedish	83.51%	73.82%
	Danish	83.79%	75.05%
	Norwegian	16.47%	12.03%
English	Swedish	110.06%	93.59%
	Danish	99.50%	88.71%
	Norwegian	102.52%	90.35%

4 Data and Models

Data We created testing, training, and development subsets for Swedish, Danish, and Norwegian from two datasets: Nordisk Språkteknologi (NST)[2] and Common Voice (CV) 8.0 (Ardila et al., 2020). For testing subsets of Danish and Norwegian, we used the entire test sets from NST, which amount to 77.1 and 115.3 hours of speech respectively. For Swedish, due to the lack of a modernized version of the NST test set, we randomly sampled 20% of the training set - roughly 73,2 hours of speech. For training, we limit the subsets to 15,000 entries per language (roughly 7 hours of speech) per language due to limited computational resources. We ensure that the Swedish train and test subsets do not overlap.

We use the CV dataset to construct a validation set for the multilingual models. For Swedish and Danish, we randomly sampled 2,000 validated entries per language. No validated data were available for Norwegian Bokmål; we, therefore, used a held-out sample of 2,000 entries from the Norwegian NST training dataset. In total, we used roughly one hour of speech per language for validation.

We processed each subset by downsampling the audio to 16 kHz and normalizing the transcriptions. The normalization involved lower-casing all characters and removing non-alphanumeric characters, such as punctuation markers.

Models For monolingual baselines in Swedish, Norwegian, and English, we use the publicly available Wav2Vec 2.0 models[3] on Huggingface. Due to the lack of an existing fine-tuned Danish model, we fine-tuned one ourselves: we used the publicly available pre-trained Danish Wav2Vec model[4], which we then fine-tuned on one GPU for 10 epochs on our Danish NST train subset. In the encoder, we retain the original parameters of the pre-trained model, whereas in the decoder, we set the batch size to 10, gradient accumulation steps to 3, learning rate to 1e-4, and weight decay to 0.005.

5 Results and Discussion

WER for Swedish, Danish, Norwegian, and English ASR models on the three Scandinavian languages is shown in Table 1. While the results on zero-shot ASR are poor, we can still see some general patterns in the performance across languages. The patterns are largely the same on character error rate (not shown). Swedish and Norwegian models perform better for all three Scandinavian languages than the English model. However, the Danish model performs as poorly on Swedish and Norwegian data as the English model. This could stem from the fact that our Danish model was trained on very little data compared to the Swedish and Norwegian models, or that Danish pronunciation is quite different from Swedish and Norwegian. Overall, the results for the Scandinavian languages largely follow the patterns for mutual intelligibility between human speakers (Delsing, 2005); the Swedish ASR model is better at transcribing Norwegian than Danish, the Danish model is better for Norwegian than Swedish, and the Norwegian model is somewhat better for Swedish than Danish. The latter difference is more pronounced for character error rate.

The scores confirm that the addition of a simple language model leads to stable improvements of the quality of transcription, even in a crosslingual setting. The Swedish model is an exception, though, likely due to the overall high quality

---

[2]Swedish: `https://www.nb.no/sprakbanken/en/resource-catalogue/oai-nb-no-sbr-56/`;
Danish: `https://www.nb.no/sprakbanken/en/resource-catalogue/oai-nb-no-sbr-55/`;
Norwegian: `https://www.nb.no/sprakbanken/en/resource-catalogue/oai-nb-no-sbr-54/`

[3]Swedish: `https://huggingface.co/KBLab/wav2vec2-large-voxrex-swedish`
Norwegian: `https://huggingface.co/NbAiLab/nb-wav2vec2-1b-bokmaal`
English: `https://huggingface.co/facebook/wav2vec2-base-960h`

[4]`https://huggingface.co/Alvenir/wav2vec2-base-da`

Figure 1: Word Error Rates of the multilingual trial models and a monolingual baseline on the evaluation set, mapped over training steps.

of the model, which is only limited by such a language model.

Table 2: The performance **Mono**lingual baselines versus our **Multi**lingual model.

Test Set	Model	No LM	With LM
Swedish	Mono	**2.19%**	2.74%
	Multi	4.61%	3.26%
Danish	Mono	19.14%	13.82%
	Multi	12.69%	**10.43%**
Norwegian	Mono	16.47%	12.03%
	Multi	9.64%	**6.51%**

WER for the trial multilingual models are shown in Figure 1. The results indicate that the initialization of the multilingual model from a monolingual model is only effective in low-resource settings. This is because a model trained from scratch on all three languages reaches comparable WER within roughly 5,000 steps. Nevertheless, even though the difference is small, the average WERs on all three languages indicate that re-training a fine-tuned model with equal amounts of data (**Retraining DA+NO+SE_full**) is second only to monolingual baselines. Hence, we choose this setting for training our final multilingual model.

The scores of the final multilingual ASR model able to transcribe Swedish, Danish, and Norwegian, as opposed to the monolingual baselines are shown in Table 2. Using a language classification model for selecting which language model to add, leads to improvements for all three languages. We observe stable improvement over monolingual baselines for Norwegian and Danish both with and without language models, with only a slight drop in performance for Swedish. However, more analysis is needed to investigate the influence of matching the language versus matching the domain, since both our training and test sets are from the NST dataset.

6 Conclusions

Multilingual automatic speech recognition is often considered to be useful only for low-resource languages. Though a multilingual model can hardly compete in ultra-high-resource languages, our results show that the multilingual Scandinavian model can perform comparably or even better than monolingual models. Our results indicate that it could be useful to combine the Scandinavian languages not only for text, but also for speech processing. More extensive evaluation of models is needed to conclude whether the model benefits from a multilingual setting, or only from in-domain training.

References

Petar S. Aleksic, Mohammad Reza Ghodsi, Assaf Hurwitz Michaely, Cyril Allauzen, Keith B. Hall, Brian Roark, David Rybach, and Pedro J. Moreno. 2015. Bringing contextual information to google speech recognition. In *Interspeech*.

Dario Amodei, Sundaram Ananthanarayanan, Rishita Anubhai, Jingliang Bai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Qiang Cheng, Guoliang Chen, Jie Chen, Jingdong Chen, Zhijie Chen, Mike Chrzanowski, Adam Coates, Greg Diamos, Ke Ding, Niandong Du, Erich Elsen, Jesse Engel, Weiwei Fang, Linxi Fan, Christopher Fougner, Liang Gao, Caixia Gong, Awni Hannun, Tony Han, Lappi Johannes, Bing Jiang, Cai Ju, Billy Jun, Patrick LeGresley, Libby Lin, Junjie Liu, Yang Liu, Weigao Li, Xiangang Li, Dongpeng Ma, Sharan Narang, Andrew Ng, Sherjil Ozair, Yiping Peng, Ryan Prenger, Sheng Qian, Zongfeng Quan, Jonathan Raiman, Vinay Rao, Sanjeev Satheesh, David Seetapun, Shubho Sengupta, Kavya Srinet, Anuroop Sriram, Haiyuan Tang, Liliang Tang, Chong Wang, Jidong Wang, Kaifu Wang, Yi Wang, Zhijian Wang, Zhiqian Wang, Shuang Wu, Likai Wei, Bo Xiao, Wen Xie, Yan Xie, Dani Yogatama, Bin Yuan, Jun Zhan, and Zhenyao Zhu. 2016. Deep speech 2 : End-to-end speech recognition in english and mandarin. In *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pages 173–182, New York, New York, USA. PMLR.

Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis Tyers, and Gregor Weber. 2020. Common voice: A massively-multilingual speech corpus. In *Proceedings of the 12th Language Resources and Evaluation Conference*, pages 4218–4222, Marseille, France. European Language Resources Association.

Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. 2020. wav2vec 2.0: A framework for self-supervised learning of speech representations. *Advances in Neural Information Processing Systems*, 33:12449–12460.

Nora Barroso, Odei Barroso, Unai Susperregi, Aitzol Ezeiza, and Karmele López de Ipiña. 2010. Language identification oriented to multilingual speech recognition in the basque context. In *2010 IEEE 15th Conference on Emerging Technologies Factory Automation (ETFA 2010)*, pages 1–8.

J Benesty, J Chen, and Y Huang. 2008. *Automatic speech recognition: A deep learning approach*. Springer, Berlin.

Suvarnsing G. Bhable and Charansing N. Kayte. 2020. Review: Multilingual acoustic modeling of automatic speech recognition(asr) for low resource languages. In *2020 IEEE International Conference on Advent Trends in Multidisciplinary Research and Innovation (ICATMRI)*, pages 1–4.

Alexis Conneau, Alexei Baevski, Ronan Collobert, Abdelrahman Mohamed, and Michael Auli. 2021. Unsupervised Cross-Lingual Representation Learning for Speech Recognition. In *Proc. Interspeech 2021*, pages 2426–2430.

Lars-Olof Delsing. 2005. *Håller språket ihop Norden?: en forskningsrapport om ungdomars förståelse av danska, svenska och norska [Does the Language Keep the Nordic Countries Together? A Research Report on How Well Young People Understand Danish, Swedish and Norwegian]*. Nordic Council of Ministers, Copenhagen, Denmark.

Awni Hannun, Carl Case, Jared Casper, Bryan Catanzaro, Greg Diamos, Erich Elsen, Ryan Prenger, Sanjeev Satheesh, Shubho Sengupta, Adam Coates, and Andrew Y. Ng. 2014. Deep speech: Scaling up end-to-end speech recognition.

Alexander Håkansson and Kevin Hoogendijk. 2020. Transfer learning for domain specific automatic speech recognition in swedish: An end-to-end approach using mozilla's deepspeech. Master's thesis, Chalmers tekniska högskola / Institutionen för data och informationsteknik, Gothenburg, Sweden.

Hui Lin, Li Deng, Dong Yu, Yi-fan Gong, Alex Acero, and Chin-Hui Lee. 2009. A study on multilingual acoustic modeling for large vocabulary asr. In *2009 IEEE International Conference on Acoustics, Speech and Signal Processing*, pages 4333–4336.

Dau-Cheng Lyu and Ren-Yuan Lyu. 2008. Language identification on code-switching utterances using multiple cues. In *INTERSPEECH 2008, 9th Annual Conference of the International Speech Communication Association, Brisbane, Australia, September 22-26, 2008*, pages 711–714.

Koena Ronny Mabokela and Madimetja Jonas Manamela. 2013. An integrated language identification for code- switched speech using decoded-phonemes and support vector machine. In *2013 7th Conference on Speech Technology and Human - Computer Dialogue (SpeD)*, pages 1–6.

Martin Malmsten, Chris Haffenden, and Love Borjeson. 2022. Hearing voices at the national library - a speech corpus and acoustic model for the swedish language. *ArXiv*, abs/2205.03026.

Vineel Pratap, Anuroop Sriram, Paden Tomasello, Awni Hannun, Vitaliy Liptchinsky, Gabriel Synnaeve, and Ronan Collobert. 2020. Massively multilingual asr: 50 languages, 1 model, 1 billion parameters. In *Proceedings of Interspeech 2020*, pages 4751–4755.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2022. Robust speech recognition via large-scale weak supervision. *arXiv preprint arXiv:2212.04356*.

Magnus Sahlgren, Fredrik Carlsson, Fredrik Olsson, and Love Börjeson. 2021. It's basically the same language anyway: the case for a nordic language model. In *Proceedings of the 23rd Nordic Conference on Computational Linguistics (NoDaLiDa)*, pages 367–372, Reykjavik, Iceland (Online). Linköping University Electronic Press, Sweden.

Aaron Smith, Bernd Bohnet, Miryam de Lhoneux, Joakim Nivre, Yan Shao, and Sara Stymne. 2018. 82 treebanks, 34 models: Universal Dependency parsing with multi-treebank models. In *Proceedings of the CoNLL 2018 Shared Task: Multilingual Parsing from Raw Text to Universal Dependencies*, pages 113–123, Brussels, Belgium. Association for Computational Linguistics.

Jörg Tiedemann. 2009. Character-based PSMT for closely related languages. In *Proceedings of the 13th Annual conference of the European Association for Machine Translation*, Barcelona, Spain. European Association for Machine Translation.

Appendix A: Language Classification

The language classification module is trained to predict the language from the values outputted by the encoder of the ASR model. We train the classifier on a shuffled concatenation of the training subsets in each language (45,000 entries in total) for roughly 10 epochs with a batch size of 4, 2 gradient accumulation steps, a learning rate of 1e-4, and mean pooling. We evaluate the classification component on a concatenation of the test sets in all three languages.

The overall quality of the classification module is high. Figure 2 shows how well the language classifier performs across languages, reaching an accuracy of 0.97–0.98 for each language. However, the accuracy differs based on the duration of the audio sequence, with low accuracy on very short sequences, as shown in Figure 3.

Figure 2: The normalized accuracy scores of the trained language classifier.

Figure 3: The accuracy of the language classification module mapped over the quantized lengths of the entries in the test set. Averaged over all three languages.