A Near-Optimal Best-of-Both-Worlds Algorithm for Online Learning with Feedback Graphs

Abstract

We consider online learning with feedback graphs, a sequential decision-making framework where the learner's feedback is determined by a directed graph over the action set. We present a computationally efficient algorithm for learning in this framework that simultaneously achieves near-optimal regret bounds in both stochastic and adversarial environments. The bound against oblivious adversaries is $\tilde{O}(\sqrt{\alpha T})$, where T is the time horizon and α is the independence number of the feedback graph. The bound against stochastic environments is $O\big((\ln T)^2 \max_{S \in \mathcal{I}(G)} \sum_{i \in S} \Delta_i^{-1}\big)$ where $\mathcal{I}(G)$ is the family of all independent sets in a suitably defined undirected version of the graph and Δ_i are the suboptimality gaps. The algorithm combines ideas from the EXP3++ algorithm for stochastic and adversarial bandits and the EXP3.G algorithm for feedback graphs with a novel exploration scheme. The scheme, which exploits the structure of the graph to reduce exploration, is key to obtain best-of-both-worlds guarantees with feedback graphs. We also extend our algorithm and results to a setting where the feedback graphs are allowed to change over time.

1 Introduction

Online learning is a general framework for studying sequential decision-making in unknown environments (see, for example, (Cesa-Bianchi and Lugosi, 2006; Bubeck and Cesa-Bianchi, 2012; Orabona, 2019)). We consider a setting where, at each round, the player chooses an action (a.k.a. arm) from a fixed set of K actions and incurs the loss associated with the chosen action. The performance of the learner is quantified in terms of regret, which is the difference between the total loss incurred by the learner over the duration of the game, and the smallest cumulative loss obtained by a player that would only ever play the same action throughout the game.

The smallest achievable regret is determined by a number of parameters. One of these parameters is the amount of feedback that the learner receives at each round. There is a whole spectrum of problems, characterized by the amount of feedback received by the learner. At the one extreme of this spectrum is the bandit setting, where the learner only observes the loss of the action taken. At the other extreme is the full information setting, where the learner observes the full loss vector at the end of each round, irrespective of the action played.

There are two common ways to interpolate between full information and bandit feedback. One is to allow the learner to make a limited number of additional observations without restricting how the additional observations are selected. Then no additional observations correspond to the bandit setting and $K - 1$ additional observations correspond to the full information setting. This way of interpolation was proposed by Seldin et al. (2014) in two variants, "prediction with limited advice" and "multiarmed bandits with paid observations". It was also studied by Thune and Seldin (2018).

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

The second way of interpolation, which we focus on in this paper, is via feedback graphs (Alon et al., 2014). In this setting observations of the learner are governed by a feedback graph on the actions. When an action is played, the learner observes the losses of all of its neighbors in the feedback graph. A complete graph corresponds to the full information setting, whereas a graph containing only self-loops corresponds to the bandit setting. This setting has multiple variants, depending on whether the graph is directed or undirected, observed or unobserved, static or dynamic.

Another important parameter characterizing online learning problems is the type of environment. The two primary types that we focus on are stochastic and adversarial environments. In stochastic environments each action is associated with a fixed, but unknown distribution, and in each round the loss of each action is sampled independently from the corresponding distribution. In adversarial environments the loss sequence is chosen arbitrarily. We consider oblivious adversarial environments, where the loss sequences are chosen independently of the actions taken by the learner.

For a long time stochastic and adversarial environments where studied separately, but in practice the exact nature of environment is rarely known. In recent years this has led to a growing interest in "best-of-both-worlds" algorithms that are robust against adversarial loss sequences and, at the same time, provide tighter regret guarantees in the stochastic regime. Most work has focused on the bandit setting (Bubeck and Slivkins, 2012; Seldin and Slivkins, 2014; Auer and Chiang, 2016; Seldin and Lugosi, 2017; Wei and Luo, 2018), where the Tsallis-INF algorithm proposed by Zimmert and Seldin (2019, 2021) was shown to achieve the optimal regret rates in both stochastic and adversarial regimes, as well as a number of intermediate regimes. The analysis was further improved by Masoudian and Seldin (2021) and Ito (2021). In the full information setting Mourtada and Gaïffas (2019) have shown that the well-known Hedge algorithm originally designed for the adversarial setting (Littlestone and Warmuth, 1994) also achieves the optimal stochastic regret. Best-of-both-world results also spilled over to other domains, including additional approaches to full information games and online convex optimization (Koolen et al., 2016; Van Erven et al., 2021; Negrea et al., 2021), decoupled exploration and exploitation (Rouyer and Seldin, 2020), combinatorial bandits (Zimmert et al., 2019), bandits with switching costs (Rouyer et al., 2021), MDPs (Jin and Luo, 2020; Jin et al., 2021), and linear bandits (Lee et al., 2021).

In the context of online learning with feedback graphs the only best-of-both-worlds result known to us is by Erez and Koren (2021) for undirected graphs. They present an intricate FTRL-based algorithm with a regularization function that is a product of the Tsallis and Shannon entropies. The algorithm simultaneously enjoys an $O\big(\sqrt{\chi T}\big(\ln(KT)\big)^2\big)$ pseudo-regret bound in the adversarial regime and an $O\big(\big(\ln(KT)\big)^4 \sum_k \frac{\ln T}{\Delta_k}\big)$ pseudo-regret bound in the stochastic regime, where T is the number of prediction rounds, χ is the clique covering number of the undirected feedback graph, and the summation in the second bound is on the smallest non-zero gap within each clique.

It is tempting to apply an FTRL-based algorithm with Tsallis entropy regularization to online learning with feedback graphs, since Tsallis entropy with power $a = 1/2$ leads to the optimal Tsallis-INF algorithm for the bandit setting (Zimmert and Seldin, 2021) and Tsallis entropy with power $a = 1$ leads to the Hedge algorithm, which is optimal in the full information setting. However, as also noted by Erez and Koren (2021), extension of the analysis to online learning with feedback graphs when the power $a \in (1/2, 1)$ is not straightforward and, so far, there was no success in this direction. Furthermore, at the moment it is unclear whether it is possible to derive bounds that take further advantage of the graph structure and depend on the independence number of the graph when $a < 1$.

Our contribution. We significantly extend and improve on the bounds of Erez and Koren (2021). Our results hold for directed graphs (with self-loops), depend on the independence number of the graph, have a better dependence on T in the stochastic regime, and extend to time-varying feedback graphs. Our approach takes advantage of the common structure shared by two exponential weights algorithms: EXP3.G (Alon et al., 2015) and EXP3++ (Seldin and Slivkins, 2014; Seldin and Lugosi, 2017), to obtain near-optimal best-of-both worlds guarantees. By using similar ideas as in the proof of the regret bound of EXP3.G, the proposed algorithm adapts to the independence number of the graph. We derive an $O(\sqrt{\tilde{\alpha}T \ln K})$ pseudo-regret bound against adversarial sequences of losses, where $\tilde{\alpha}$ is the strong independence number, which is a graph dependent quantity smaller than the clique covering number. For undirected graphs, independence number and strong independence number are equal and the result matches the best known lower bound $\Omega(\sqrt{\alpha T})$ within logarithmic factors (Alon et al., 2014). In the stochastic setting we use the idea of injected exploration from

EXP3++ to estimate the suboptimality gaps of each arm. By introducing a novel dynamic exploration set and an appropriate exploration rate, we derive an almost optimal regret bound in the stochastic setting. Along the way, we also improve the regret bound of EXP3++ in the stochastic bandit setting. Our exploration set is constructed by sorting the arms by ascending gap estimates, and then adding a new arm to the exploration set if the arm cannot be observed by playing another arm previously added to the set. If we play each arm i in the exploration set at a rate $1/\hat{\Delta}_i^2$, where $\hat{\Delta}_i$ is the gap estimate, then all arms j in the graph are observed with probability at least $1/\hat{\Delta}_j^2$.

To present our main result we introduce some notations. Let $G = (V, E)$ be a directed feedback graph with independence number α (where the independence number is computed on G ignoring edge directions). We define a strongly independent set on G as an independent set on the subgraph $G' = (V, E')$, where $(i, j) \in E'$ if and only if $(i, j) \in E$ and $(j, i) \in E$. We use $\tilde{\alpha}$ to denote the strong independence number of G, and $\mathcal{I}(G)$ to denote the collection of all the strongly independent sets in G. We note that $\alpha = \tilde{\alpha}$ for undirected graphs and $\alpha \leq \tilde{\alpha}$ for directed graphs. Now we can present an informal statement of our main result.

Theorem 1 (Informal). *Given a directed feedback graph $G = (V, E)$ with strong independence number $\tilde{\alpha}$, there exists an algorithm (Algorithm 1) whose pseudo-regret can simultaneously be bounded by $O(\sqrt{\tilde{\alpha}T \ln K})$ against adversarial loss sequences and by $O\left((\ln T)^2 \max_{S \in \mathcal{I}(G)} \sum_{i \in S} \Delta_i^{-1}\right)$ against stochastic loss sequences.*

We emphasize that Algorithm 1 requires neither prior knowledge of the type of the environment (adversarial or stochastic), nor the time horizon.

1.1 Additional Related Work

The study of bandits with feedback graphs was initiated by Mannor and Shamir (2011) in the adversarial regime and by Caron et al. (2012) in the stochastic regime. In the adversarial regime, the optimal regret rates for arbitrary directed graphs were characterized (up to log factors) by Alon et al. (2015). They showed an $\Omega(T)$ lower bound for graphs that have non-observable nodes (i.e., with an empty in-neighborhood). For graphs with observable nodes, they derived pseudo-regret bounds of order $O(\sqrt{\alpha T} \log(KT))$ when all nodes are strongly observable (i.e., they have a self-loop or their in-neighborhood contains all of the other nodes) and of order $O((\delta \ln K)^{1/3} T^{2/3})$ for weakly observable graphs (where each non-strongly observable node is in the out-neighborhood of some observable node). Here α is the independence number of the graph and δ is the dominating number of the weakly observable portion of the graph. Van der Hoeven et al. (2021) derived results for the multiclass classification with feedback graphs setting. The setting where the graph can adversarially change over time has been studied by Alon et al. (2014) in the case of directed graphs with self-loops. For learners that are allowed to observe the feedback graph at the beginning of each round, they achieved a bound of $O\left(\ln K \sqrt{\ln(KT) \sum_{t=1}^{T} \alpha_t}\right)$, where α_t is the independence number of the graph at time t. For the case of undirected graphs, they proved a refined bound $O\left(\sqrt{\ln K \sum_{t=1}^{T} \alpha_t}\right)$ that holds even when the learner can only observe the graph at the end of each round. Note that, as shown by Cohen et al. (2016), in order to take advantage of the graph structure in the adversarial regime, it not sufficient to observe the neighborhood of the played action at the end of each round.

In the stochastic regime, Buccapatnam et al. (2014, 2017) considered a fixed, possibly directed, feedback graph. They derived an asymptotic lower bound showing that the regret scales as $\Omega(c^* \ln T)$, where c^*—which is related to the domination number of the graph—is the solution to a linear program expressing the trade-off between the loss incurred from playing an action and the observations that can be gathered from playing that action. They proposed an algorithm that can achieve a matching $O(c^* \ln T + Kd)$ pseudo-regret bound, where d is the maximum degree in the feedback graph. In the case of graphs that change over time, Cohen et al. (2016) derived an $O(\sum_{i \in S} (\ln T)/\Delta_i)$ bound, where S is a set containing an order of α arms (up to log factors), and α is an upper bound on the independence number of the graphs in the sequence. They achieved this result without requiring to observe the graphs fully, and having only access to the neighbourhood of the arm played at the end of the round. Both of these approaches are based on arm elimination algorithms, which—by construction—are not suitable for best-of-both worlds guarantees. The proof strategy of Cohen et al. (2016) was adapted by Lykouris et al. (2020) to provide refined bounds for both UCB-N and Thompson Sampling-N, which are variants of UCB1 (Auer et al., 2002) and Thompson Sampling

(Thompson, 1933). In both cases, Lykouris et al. (2020) considered undirected feedback graphs and obtained pseudo-regret bounds that scale as $O\left(\max_{\mathrm{Ind}\in\mathcal{I}(G)}\sum_{i\in\mathrm{Ind}}\ln(KT)(\ln T)/\Delta_i\right)$, where $\mathcal{I}(G)$ is the collection of all the independence sets of the graph.

2 Problem Setting and Definitions

Problem Setting We consider a sequential decision-making game, where in each round $t = 1, 2, \ldots$, the learner repeatedly plays an action $I_t \in V$, where $|V| = K$, receives a feedback based on a feedback graph $G = (V, E)$, and suffers a loss ℓ_{t,I_t}. We consider directed feedback graphs with self-loops, meaning that $(i, i) \in E$ for each vertex $i \in V$. The feedback received by the learner at the end of round t is $\{(i, \ell_{t,i}) : i \in N^{\mathrm{out}}(I_t)\}$, where $N^{\mathrm{out}}(i) = \{j \in V : (i, j) \in E\}$ is the out-neighbourhood of i. Similarly, we define $N^{\mathrm{in}}(i) = \{j \in V : (j, i) \in E\}$ to be the in-neighbourhood of i. For each arm $i \in V$, $\ell_{t,i} \in [0, 1]$ for $t \geq 1$. In the adversarial regime the losses are generated arbitrarily by an oblivious adversary. In the stochastic regime they are independently drawn from a fixed but unknown distribution with expectation $\mathbb{E}[\ell_{1,i}]$. The performance of the learner is measured in terms of the pseudo-regret:

$$\mathcal{R}_T = \mathbb{E}\left[\sum_{t=1}^{T}\ell_{t,I_t}\right] - \min_{i\in V}\mathbb{E}\left[\sum_{t=1}^{T}\ell_{t,i}\right].$$

In the stochastic regime, we define the best arm i^* as the arm with the smallest expected loss, i.e. $i^* = \mathrm{argmin}_{i\in V}\mathbb{E}[\ell_{1,i}]$. The pseudo-regret can then be expressed in terms of the suboptimality gaps $\Delta_i = \mathbb{E}[\ell_{1,i} - \ell_{1,i^*}]$,

$$\mathcal{R}_T = \sum_{t=1}^{T}\sum_{i\in V}\mathbb{E}\left[p_{t,i}\right]\Delta_i, \tag{1}$$

where $p_{t,i}$ is the probability that the learner plays action i at round t. We define the smallest suboptimality gap $\Delta_{\min} = \min_{i:\Delta_i>0}\{\Delta_i\}$, and for all i, we define $\bar{\Delta}_i = \max\{\Delta_{\min}, \Delta_i\}$, so that $\bar{\Delta}_{i^*} = \Delta_{\min}$. We use $\mathbb{E}_t$ to express expectation conditioned on all randomness up to round t.

Properties of Graphs Recall that a dominating set in G is a subset $D \subseteq V$, such that for all $i \in V$ there exists $j \in D$, such that $(j, i) \in E$. An independent set in G is a subset $S \subseteq V$, such that for all $i, j \in S$, $(i, j) \notin E$ and $(j, i) \notin E$. We define the independence number $\alpha(G)$ as the size of the largest independent set in the graph G. For clarity, we restate below here the definition of the strong independence number which was already mentioned in the introduction.

Definition 1. *Let $G = (V, E)$ be a directed graph. We define a strongly independent set on G as an independent set on the subgraph $G' = (V, E')$, where $(i, j) \in E'$ if and only if $(i, j) \in E$ and $(j, i) \in E$. Furthermore, we define $\tilde{\alpha}(G)$ as the independence number of the subgraph G'.*

We use $\mathcal{I}(G)$ to denote a collection of all the strongly independent sets in G. We note that $\alpha = \tilde{\alpha}$ for undirected graphs and $\alpha \leq \tilde{\alpha}$ for directed graphs.

3 Algorithm

We present the EXP3.G++ algorithm (Algorithm 1), which is a combination of the EXP3.G algorithm of Alon et al. (2015) and the EXP3++ algorithm of Seldin and Lugosi (2017) with a novel exploration scheme described in Algorithm 2. This scheme ensures that the additional feedback the learner obtains (relative to the bandit setting) is used nearly optimally.

To understand the motivation behind the novel exploration scheme, note that in the stochastic setting EXP3.G++ needs to ensure that the loss of each arm is observed sufficiently often. However, if we would play each arm too often, the regret would scale with the number of arms, rather than with the independence number or some other graph-theoretic quantity. To avoid that, we exploit the central property of feedback graphs: since we can gather information on certain arms by playing adjacent arms in the graph, we can restrict exploration to a subset of nodes and yet obtain sufficient information on *all* the arms. We exploit this observation, to design a strategy for selecting an exploration set S_t at each round t. S_t is defined in terms of estimated suboptimality gaps $\hat{\Delta}_{t,i}$, which are maintained by

---

Algorithm 1: EXP3.G++

Input: Feedback graph $G = (V, E)$,
Learning rates $\eta_1 \geq \eta_2 \geq \cdots > 0$; exploration rates $\varepsilon_{t,i}$ for $i \in V$, see Equation (2)
Initialize: $\tilde{L}_0 = \mathbf{0}_K$, $\hat{L}_0 = \mathbf{0}_K$ and $O_0 = \mathbf{0}_K$. Play each arm once to initialize $\hat{L}$ and O
for $t = K + 1, K + 2, \ldots$ **do**

$$\forall i \in V : \text{UCB}_{t,i} = \min \left\{ 1, \frac{\hat{L}_{t-1,i}}{O_{t-1,i}} + \sqrt{\frac{\gamma \ln\left(tK^{1/\gamma}\right)}{2O_{t-1,i}}} \right\}$$

$$\forall i \in V : \text{LCB}_{t,i} = \max \left\{ 0, \frac{\hat{L}_{t-1,i}}{O_{t-1,i}} - \sqrt{\frac{\gamma \ln\left(tK^{1/\gamma}\right)}{2O_{t-1,i}}} \right\}$$

$\forall i \in V : \hat{\Delta}_{t,i} = \max \left\{ 0, \text{LCB}_{t,i} - \min_j \text{UCB}_{t,j} \right\}$
$\forall i \in V :$ update $\varepsilon_{i,t}$ based on the gap estimates $\hat{\Delta}_t$

$$\forall i \in V : q_{t,i} = \frac{\exp(-\eta_t \tilde{L}_{t,i})}{\sum_{i \in V} \exp(-\eta_t \tilde{L}_{t,j})}, \ p_{t,i} = \left(1 - \sum_{j \in V} \varepsilon_{t,j}\right) q_{t,i} + \varepsilon_{t,i}$$

Sample $I_t \sim p_t$ and play it
Observe $\{(j, \ell_{t,j}) : j \in N^{\text{out}}(I_t)\}$ and suffer ℓ_{t,I_t}.
$\forall i \in V : \tilde{\ell}_{t,i} = \dfrac{\ell_{t,i} \mathbb{1}\left[i \in N^{\text{out}}(I_t)\right]}{P_{t,i}}$, where $P_{t,i} = \sum_{j \in N^{\text{in}}(i)} p_{t,j}$
$\forall\, i \in V : \quad \tilde{L}_{t,i} = \tilde{L}_{t-1,i} + \tilde{\ell}_{t,i}$
$\forall i \in V : \hat{L}_{t,i} = \hat{L}_{t-1,i} + \ell_{t,i} \mathbb{1}\left[i \in N^{\text{out}}(I_t)\right]$ and $O_{t,i} = O_{t-1,i} + \mathbb{1}\left[i \in N^{\text{out}}(I_t)\right]$
end for

Algorithm 2: Exploration Set Construction

Input: K arms with associated gaps: $\Delta_1, \Delta_2, \ldots$
Initialize: Exploration set $S = \emptyset$.
Let Λ be the list of arms sorted in ascending order of their associated gaps.
for $i \in \Lambda$ **do**
    Add i to S
    for $j \in N^{\text{out}}(i)$ **do**
        remove j from Λ
    end for
end for
Output: S

EXP3.G++. Crucially, the exploration set ensures that, with high probability, the empirical gaps are reliable estimates of the true suboptimality gaps Δ_i. In turn, this ensures that we observe the loss of each arm sufficiently often.

The construction of the exploration set S_t is detailed in Algorithm 2, which is used by EXP3.G++ to update the exploration rates $\varepsilon_{t,i}$ according to Equation (2). Algorithm 2 starts by sorting the arms according to their gap estimates in ascending order. The exploration set is then greedily constructed by sequentially selecting the next arm with the smallest $\hat{\Delta}_{t,i}$, and discarding all the arms in the out-neighborhood of that arm. The exploration set can be constructed in $O(K^3)$ time, but note that we only need to recompute it only when the order of the estimated suboptimality gaps changes. The exploration set S_t has several useful properties, as shown in Proposition 1 below.

Proposition 1. *Let $G = (V, E)$ be a directed feedback graph on K arms with self-loops, and let $\hat{\Delta}_1, \ldots, \hat{\Delta}_K$ be a sequence of suboptimality gaps estimates. Let S be the exploration set constructed by Algorithm 2 based on the sequence of suboptimality gaps. Then S is a dominating set of G with the following property: for all $i \in V$ there exists $j \in S$, such that $i \in N^{\text{out}}(j)$ and $\hat{\Delta}_j \leq \hat{\Delta}_i$. Furthermore, S is also a strongly independent set of G.*

Proof. Let S be the output of Algorithm 2. Since G contains self-loops, if $i \in S$, then $i \in N^{\text{out}}(i)$ and $\hat{\Delta}_i \leq \hat{\Delta}_i$. If $i \notin S$, then i was removed from Λ because $i \in N^{\text{out}}(j)$ for some j that, in a previous iteration, was added to S. Since j was considered before i, we must have $\hat{\Delta}_j \leq \hat{\Delta}_i$. Now, for all $i, j \in S$, we know by construction that $j \notin N^{\text{out}}(i)$. Thus (i, j) is not a directed edge in G, and so S is a strongly independent set in G. $\qquad\square$

We define the exploration rates at round t in terms of the exploration set S_t, which is constructed using the aforementioned procedure. For all arms i in V,

$$\varepsilon_{t,i} = \min\left\{\frac{1}{2K}, \frac{1}{2}\sqrt{\frac{\lambda \ln K}{tK^2}}, \xi_{t,i}\right\}, \tag{2}$$

for some constant $\lambda \in [1, K]$ and where $\xi_{t,i}$ depends on whether $i \in S_t$ or not:

$$\xi_{t,i} = \begin{cases} (\beta \ln t)/(t\hat{\Delta}_{t,i}^2), & \text{if } i \in S_t, \\ 4/t^2, & \text{otherwise,} \end{cases} \tag{3}$$

where $\beta > 0$ is a constant. The role of $\xi_{t,i}$ changes depending on whether we are in an adversarial or stochastic environment. In an adversarial environment, we use $4/t^2 \leq \xi_{t,i}$ to ensure that we sample each arm with a small positive probability, which is essential to bound the second-order term in the regret bound in terms of the independence number. Note that $\varepsilon_{t,i} \leq \frac{1}{2}\sqrt{\frac{\lambda \ln K}{tK^2}}$, so choosing $\lambda = \tilde{\alpha}$ ensures that the cost of exploration is bounded by $\tilde{O}(\sqrt{\tilde{\alpha}T})$. In the stochastic environment, the construction of the exploration set and the choice of $\xi_{t,i}$ ensure that, at each round t, each $i \in V$ is observed with probability at least $(\beta \ln t)/(t\hat{\Delta}_{t,i}^2)$, independently of whether i is in the exploration set at round t.

Formally, our procedure ensures that we can lower bound the probability with which any arm is observed. In the algorithm we use $P_{t,i} = \mathbb{P}\left[i \in N^{\text{out}}(I_t)\right]$ to denote the probability that arm i is observed at round t. We can lower bound this quantity by only considering the minimum rate at which each arm is observed according to the exploration rate $\varepsilon_{t,i}$ and our construction of the exploration sets. We use $o_{t,i}$ to denote that quantity, and we have for all t and i,

$$P_{t,i} \geq o_{t,i} = \min\left\{\frac{1}{2K}, \frac{1}{2}\sqrt{\frac{\lambda \ln K}{tK^2}}, \frac{\beta \ln t}{t\hat{\Delta}_{t,i}^2}\right\}. \tag{4}$$

The definition of $o_{t,i}$ uses that S_t is a dominating set. The difference between $\varepsilon_{t,i}$ and $o_{t,i}$ is key to take advantage of the graph structure. First, we need to lower bound $o_{t,i}$ to ensure that enough observations (counted by $O_{t,i}$ in Algorithm 1) are made for each arm, such that our gap estimates are reliable. Simultaneously, we upper bound $\varepsilon_{t,i}$ to ensure that the extra exploration is not too costly. Here we benefit from the fact that S_t is a strongly independent set on G.

We ensure that all arms get sufficiently many observations and derive the following concentration bounds on the gap estimates $\hat{\Delta}_{t,i}$ computed by Algorithm 1. Concentration of the gap estimates around the true gaps is crucial for bounding the regret in the stochastic setting.

Lemma 1. *If Algorithm 1 is run with parameters $\gamma \geq 3$, $\beta \geq 64(\gamma + 1) \geq 256$, and exploration rates $\varepsilon_{t,i}$, such that for all $t \geq 1$ and $i \in V$, $P_{t,i}$ satisfies equation (4) for some $\lambda \in [1, K]$, then for all $i \in V$ and $t \geq 1$,*

$$\mathbb{P}\left[\hat{\Delta}_{t,i} \geq \overline{\Delta}_i\right] \leq \frac{1}{Kt^{\gamma-1}}.$$

Furthermore, for any arm i with $\Delta_i > 0$ let $t_{\min}(i) := \max\left\{t \geq 0 : \frac{1}{2}\sqrt{\frac{\lambda \ln K}{tK^2}} \leq \frac{\beta \ln t}{t\Delta_i^2}\right\}$. Then for any arm i with $\Delta_i > 0$ and $t \geq t_{\min}(i)$,

$$\mathbb{P}\left[\hat{\Delta}_{t,i} \leq \frac{1}{2}\Delta_i\right] \leq \left(\frac{\ln t}{t\Delta_i^2}\right)^{\gamma-2} + \frac{2}{Kt^{\gamma-1}} + 2\left(\frac{1}{t}\right)^{\frac{\beta}{10}}. \tag{5}$$

A proof of the lemma is provided in Appendix C.

237 We run the algorithm with $\gamma = 4$ and $\beta = 64(\gamma + 1) = 320$ which is a different parameterization
238 from the EXP3++ algorithm (Seldin and Lugosi, 2017), which uses $\gamma = 3$ and $\beta = 256$. Picking a
239 larger value of γ means that the confidence intervals are slightly larger, which allows us to obtain a
240 better dependency on the suboptimality gaps.

241 Indeed, under the same assumptions as in Lemma 1, if $\gamma = 4$ and $t \geq t_{\min}(i)$, we have that

$$\frac{(\ln t)^2}{t} \leq \frac{\lambda \Delta_i^4 \ln K}{4K^2\beta^2} \text{ , implying } \left(\frac{\ln t}{t\Delta_i^2} \right)^2 = \frac{(\ln t)^2}{t^2\Delta_i^4} = \frac{(\ln t)^2}{t} \frac{1}{t\Delta_i^4} \leq \frac{\lambda \Delta_i^4 \ln K}{4K^2\beta^2} \frac{1}{t\Delta_i^4} = \frac{1}{t} \frac{\lambda \ln K}{4K^2\beta^2}.$$

4 Adversarial Analysis

243 Our result for the adversarial regime is given in the following theorem.

244 **Theorem 2.** *Assume that Algorithm 1 is run with a directed feedback graph $G = (V, E)$, a learning*
245 *rate $\eta_t = \sqrt{\frac{\ln K}{2\tilde{\alpha}t}}$ and the exploration rate defined in (2)–(3) with $\lambda = \tilde{\alpha}$, $\gamma = 4$, and $\beta = 320$.*
246 *Then the pseudo-regret against any oblivious loss sequence satisfies $\mathcal{R}_T \leq 4\sqrt{\tilde{\alpha}T \ln K} + K$, where*
247 *$K = |V|$ and $\tilde{\alpha}$ is the strong independence number of G.*

248 On undirected graphs, this bound matches the one of Alon et al. (2014) which implies that in the
249 adversarial regime we are not paying a price for the extra guarantees that we derive in the stochastic
250 regime. On directed graphs, if the difference between α and $\tilde{\alpha}$ is large, it may be advantageous
251 to express the bound in terms of the independence number of the graph rather than its strong
252 independence number at the cost of a logarithmic factor. See Section 6 for additional results in this
253 direction.

254 We give a sketch of the proof here and defer the detailed proof to Appendix B.

255 **Proof sketch.** We separate the first K rounds, in which the algorithm plays deterministically, from
256 the remaining rounds, where we bound separately the contributions to the regret from the exponential
257 weights and from the extra exploration. To bound the contribution of the extra exploration, we use that
258 $\varepsilon_{t,i} \leq \frac{1}{2}\sqrt{\frac{\tilde{\alpha}\ln K}{tK^2}}$ for all t and i, meaning that the extra exploration contributes at most $O(\sqrt{\tilde{\alpha}T \ln K})$
259 to the regret. For bounding the contribution of the exponential weights to the regret, we follow the
260 standard analysis of EXP3 with time varying learning rate (Bubeck and Cesa-Bianchi, 2012). We
261 bound the second order term by exploiting the fact that $p_{t,i}$ and $q_{t,i}$ are close to each other because
262 $\varepsilon_{t,i} \leq \frac{1}{2K}$ for all t and i. This allows us to bound the second order term in terms of $\sum_{i \in V} \frac{p_{t,i}}{P_{t,i}}$, which
263 is the sum on the ratios between the probability of playing an arm and the probability of observing it.
264 This quantity can be bounded by the strong independence number of the graph (Lemma 10 Alon et al.
265 (2014)).

5 Stochastic Analysis

267 Our result for the stochastic regime is given in the following theorem.

268 **Theorem 3.** *Let $G = (V, E)$ be a directed feedback graph with $K = |V|$ and a strong independence*
269 *number $\tilde{\alpha}$. Under the same conditions as in Theorem 2, the pseudo-regret of Algorithm 1 against any*
270 *stochastic stochastic loss sequence, satisfies:*

$$\mathcal{R}_T \leq \max_{\text{Ind} \in \mathcal{I}(G)} \left\{ \sum_{i \in \text{Ind}:\Delta_i > 0} \frac{4\beta(\ln T)^2}{\Delta_i} \right\} + 2\tilde{\alpha}\ln T + \frac{81\beta K}{\Delta_{min}^2} \ln \left(\frac{6\beta^2 K^2}{\Delta_{min}^4} \right) + \sum_{i:\Delta_i > 0} \frac{4\tilde{\alpha}}{\Delta_i}.$$

271 We remark that the last two terms do not depend on T. Moreover, the leading coefficient of the
272 term scaling with $(\ln T)^2$ sums over an independence set (as opposed to summing over the entire
273 action set). The lower bound for this problem scales as $\Omega(c^* \ln T)$, where c^* is a graph dependent
274 quantity which takes the size of the suboptimality gaps into account (Buccapatnam et al., 2014).
275 Compared to that, our result is suboptimal by a logarithmic factor and our dependency on the strong
276 independence number of G is weaker. The algorithms of Buccapatnam et al. (2014, 2017) and Cohen
277 et al. (2016) almost match the lower bound, but their elimination based structure prevents them

from being applicable in best-of-both-worlds settings. In the undirected case, we obtain the same dependence on T and on the set of arms as the UCB-N algorithm analysed by Lykouris et al. (2020).

We provide a sketch of the proof here. The detailed version can be found in Appendix D.

Proof sketch. Let $t_{\min} = \max_{i:\Delta_i>0}\{t_{\min}(i)\} = \max\left\{t \geq 0 : \frac{1}{2}\sqrt{\frac{\tilde{\alpha}\ln K}{tK^2}} \leq \frac{\beta\ln t}{t\Delta_{\min}^2}\right\}$. The pseudo-regret can be decomposed by treating the first $t_{\min}$ rounds like in the adversarial case, and by using a refined bound for the stochastic regime in the remaining rounds.

$$R_T = R_{t_{\min}} + \sum_{t=t_{\min}}^{T}\sum_{i\,:\,\Delta_i>0}\Delta_i\mathbb{E}\left[p_{t,i}\right] \leq R_{t_{\min}} + \sum_{t=t_{\min}}^{T}\sum_{i\,:\,\Delta_i>0}\Delta_i\left(\mathbb{E}\left[q_{t,i}\right] + \mathbb{E}\left[\varepsilon_{t,i}\right]\right). \quad (6)$$

Note that $t_{\min}$ is time independent: $t_{\min} = \frac{c}{\Delta_{\min}^4}\left(\ln\left(\frac{c}{\Delta_{\min}^4}\right)\right)^2$ for a positive constant c, therefore,

$$R_{t_{\min}} = C_0\sqrt{\tilde{\alpha}\,t_{\min}} = C_1\frac{K}{\Delta_{\min}^2}\left(\ln\left(\frac{K}{\Delta_{\min}}\right)\right),$$

where the first equality follows from Theorem 2 and C_0, C_1 are universal constants. After the initial $t_{\min}$ rounds, enough observations on all arms have been gathered to ensure with high probability that the gap estimates of all arms are close to their true gaps, as stated in Lemma 1. These concentration inequalities allow us to show that the two following propositions hold.

Proposition 2 (informal). *The contribution of the exponential weights to the pseudo-regret can be bounded as:*

$$\sum_{t=t_{\min}}^{T}\sum_{i\,:\,\Delta_i>0}\Delta_i\mathbb{E}\left[q_{t,i}\right] \leq C_2\sum_{i\,:\,\Delta_i>0}\frac{\tilde{\alpha}}{\Delta_i} + O\left(\tilde{\alpha}\ln T\right)$$

for a universal constant C_2.

Proposition 3 (informal). *The contribution of the extra exploration to the pseudo-regret can be bounded as:*

$$\sum_{t=t_{\min}}^{T}\sum_{i\,:\,\Delta_i>0}\Delta_i\mathbb{E}\left[\varepsilon_{t,i}\right] = O\left(\max_{\mathrm{Ind}\in\mathcal{I}(G)}\left\{\sum_{i\in\mathrm{Ind}\,:\,\Delta_i>0}\frac{\ln^2 T}{\Delta_i}\right\} + \tilde{\alpha}\ln T\right).$$

Formal statements and proofs of the above propositions are in Appendix D. These propositions ensure that after $t_{\min}$ steps the exponential weights of all suboptimal arms i are small, the extra exploration $\varepsilon_{t,i}$ achieves the correct rate, and that the sum of the probabilities that the suboptimality gap estimates fail in any of the rounds is of order $O(\tilde{\alpha}\ln T)$. Applying these propositions to Equation (6) finishes the proof.

Our approach to bound the pseudo-regret in the initial rounds differs from the one of Seldin and Lugosi (2017) as we take advantage of the adversarial bound in these rounds. (Mourtada and Gaïffas (2019) used a similar approach to derive best-of-both worlds guarantees for the Hedge algorithm.) This refinement improves upon the result of Seldin and Lugosi (2017) by replacing $\sum_{i:\Delta_i>0}\frac{1}{\Delta_i^3}$ with $\frac{1}{\Delta_{\min}^2}$ (numerical constants ignored) in the time-independent part of the bound.

6 Extension to Time Varying Feedback Graphs

A natural extension of our results is to the setting where the feedback graphs are allowed to change over time. We consider a setting, where an oblivious adversary chooses a feedback graph at each round and the algorithm observes the graph at the beginning of the round. In the stochastic regime, the knowledge of the full feedback graph is required at the beginning of the round in order to construct the exploration set. Since computation of the independence number is an NP-hard problem, it is vital that we tune our algorithm so that it can adapt to the independence number of the graphs without needing to actually compute it. In order to do so, we define the quantity:

$$\theta_t := \sum_{i\in V}\frac{p_{t,i}}{P_{t,i}}, \quad (7)$$

which is the sum of the ratios of the probability of playing an arm to the probability of observing its loss. By adapting the learning rate we show that in the adversarial setting our regret bound is of order $\sqrt{\sum_{t=1}^{T} \theta_t}$, for which we can use Lemma 5 of Alon et al. (2015) to upper bound θ_t in terms of α_t to obtain the desired result. As we do not know the independence numbers ahead of time, we tune the exploration rates defined in equation (2) with $\lambda = 1$ to ensure that the exploration is never too large. This exploration rate allows us to apply Lemma 1 with $\lambda = 1$, and derive the following result.

Theorem 4. *Assume that Algorithm 1 is run on a sequence of arbitrarily generated feedback graphs* $G_1, G_2, \ldots$ *with learning rate* $\eta_t = \sqrt{\frac{\ln K}{2 \sum_{s=K}^{t-1} \theta_s}}$ *and exploration rates defined in* (2) *and* (3) *with* $\lambda = 1$, $\gamma = 4$ *and* $\beta = 320$. *Then the pseudo-regret against any oblivious loss sequence satisfies*

$$\mathcal{R}_T \leq 9\sqrt{\ln K}\sqrt{\ln(KT)}\sqrt{\sum_{t=1}^{T} \alpha_t} + 2K,$$

where for all $t \geq 1$, α_t *is the independence number of* G_t. *Simultaneously, the pseudo-regret against stochastic losses satisfies:*

$$R_T \leq \inf_{0 \leq n \leq T} \left\{ \max_{S \subset V:|S|=\tilde{\alpha}_n} \left\{ \sum_{i \in S:\Delta_i > 0} \frac{4\beta \ln^2 T}{\Delta_i} \right\} + n \right\}$$
$$+ 2\ln T + \sum_{i:\Delta_i > 0} \frac{16K}{\Delta_i} + \frac{181\beta K^{3/2}}{\Delta_{min}^2} \left(\ln\left(\frac{20\beta^2 K^{5/2}}{\Delta_{min}^4}\right) \right)^2,$$

where $\tilde{\alpha}_n$ *is the* n^{th} *largest element in the set containing the strong independence number of all the* G_t *for* $t \leq T$.

A proof of this theorem is provided in Appendix E. In the adversarial regime, adapting to graphs that change over time replaces the dependence on the strong independence number by the average on the independence numbers of the sequence of graphs, but comes at the cost of a multiplicative logarithmic factor. In the stochastic regime, the first term of the bound is a sum over the $\tilde{\alpha}_n$ arms that have the smallest non-zero suboptimality gaps. In the case of undirected graphs, if we upper bound the infimum by taking $n = 0$, we have $\tilde{\alpha}_0 = \max_{t>1}\{\alpha(G_t)\}$, which matches the dependency on gaps achieved by Cohen et al. (2016), who got an $O\left(\max_{S \subset V \setminus \{i^*\}:|S|=O(\alpha)} \sum_{i \in S} \frac{\ln T}{\Delta_i}\right)$ bound.

7 Conclusion

Erez and Koren (2021) left open the following questions: is it possible to achieve best-of-both-worlds regret bounds in terms of the independence number, and can the dependence on T in their regret bounds be improved? We partially answered these questions with the EXP3.G++ algorithm and derived near-optimal best-of-both-worlds guarantees for directed feedback graphs. Our regret bounds depend on the independence number of the feedback graphs and improve upon the results of Erez and Koren (2021) by poly-logarithmic factors in both the adversarial and stochastic regimes. Furthermore, we extended our results to time-varying feedback graphs with a computationally efficient algorithm.

References

Noga Alon, Nicolò Cesa-Bianchi, Claudio Gentile, Shie Mannor, Yishay Mansour, and Ohad Shamir. Nonstochastic multi-armed bandits with graph-structured feedback. *CoRR*, 2014.

Noga Alon, Nicolò Cesa-Bianchi, Ofer Dekel, and Tomer Koren. Online learning with feedback graphs: Beyond bandits. *CoRR*, 2015.

Peter Auer and Chao-Kai Chiang. An algorithm with nearly optimal pseudo-regret for both stochastic and adversarial bandits. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2016.

Peter Auer, Nicolò Cesa-Bianchi, Yoav Freund, and Robert E. Schapire. The nonstochastic multiarmed bandit problem. *SIAM Journal of Computing*, 2002.

Sébastien Bubeck and Nicolò Cesa-Bianchi. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends in Machine Learning*, 5, 2012.

Sébastien Bubeck and Aleksandrs Slivkins. The best of both worlds: stochastic and adversarial bandits. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2012.

Swapna Buccapatnam, Atilla Eryilmaz, and Ness B. Shroff. Stochastic bandits with side observations on networks. *Association for Computing Machinery*, 2014.

Swapna Buccapatnam, Fang Liu, Atilla Eryilmaz, and Ness B. Shroff. Reward maximization under uncertainty: Leveraging side-observations on networks. *Journal of Machine Learning Research*, 2017.

Stéphane Caron, Branislav Kveton, Marc Lelarge, and Smriti Bhagat. Leveraging side observations in stochastic bandits. *CoRR*, 2012.

Nicolò Cesa-Bianchi and Gábor Lugosi. *Prediction, Learning, and Games*. Cambridge University Press, 2006.

Ioannis Chatzigeorgiou. Bounds on the lambert function and their application to the outage analysis of user cooperation. *IEEE Communications Letters*, 2013.

Alon Cohen, Tamir Hazan, and Tomer Koren. Online learning with feedback graphs without the graphs. In *Proceedings of the International Conference on Machine Learning (ICML)*, Proceedings of Machine Learning Research, 2016.

Liad Erez and Tomer Koren. Towards best-of-all-worlds online learning with feedback graphs. In *Advances in Neural Information Processing Systems*. Curran Associates, Inc., 2021.

Tim van Erven, Wouter M. Koolen, and Dirk van der Hoeven. Metagrad: Adaptation using multiple learning rates in online learning. *Journal of Machine Learning Research*, 2021.

Pierre Gaillard, Gilles Stoltz, and Tim van Erven. A second-order bound with excess losses. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2014.

Dirk van der Hoeven, Federico Fusco, and Nicolo Cesa-Bianchi. Beyond bandit feedback in online multiclass classification. In *Advances in neural information processing systems*, 2021.

Shinji Ito. Parameter-free multi-armed bandit algorithms with hybrid data-dependent regret bounds. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2021.

Tiancheng Jin and Haipeng Luo. Simultaneously learning stochastic and adversarial episodic MDPs with known transition. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Tiancheng Jin, Longbo Huang, and Haipeng Luo. The best of both worlds: Stochastic and adversarial episodic MDPs with unknown transition. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

Wouter M Koolen, Peter Grünwald, and Tim Van Erven. Combining adversarial guarantees and stochastic fast rates in online learning. *Advances in Neural Information Processing Systems*, 29, 2016.

Chung-Wei Lee, Haipeng Luo, Chen-Yu Wei, Mengxiao Zhang, and Xiaojin Zhang. Achieving near instance-optimality and minimax-optimality in stochastic and adversarial linear bandits simultaneously. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2021.

Nick Littlestone and Manfred K. Warmuth. The weighted majority algorithm. *Information and Computation*, 108, 1994.

Thodoris Lykouris, Éva Tardos, and Drishti Wali. Feedback graph regret bounds for thompson sampling and ucb. *Proceedings of Machine Learning Research*, 2020.

Shie Mannor and Ohad Shamir. From bandits to experts: On the value of side-observations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2011.

Saeed Masoudian and Yevgeny Seldin. Improved analysis of the Tsallis-INF algorithm in stochastically constrained adversarial bandits and stochastic bandits with adversarial corruptions. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2021.

Jaouad Mourtada and Stéphane Gaïffas. On the optimality of the hedge algorithm in the stochastic regime. *Journal of Machine Learning Research*, 20, 2019.

Jeffrey Negrea, Blair Bilodeau, Nicolò Campolongo, Francesco Orabona, and Dan Roy. Minimax optimal quantile and semi-adversarial regret via root-logarithmic regularizers. *Advances in Neural Information Processing Systems*, 34, 2021.

Francesco Orabona. A modern introduction to online learning. *CoRR*, 2019.

Chloé Rouyer and Yevgeny Seldin. Tsallis-inf for decoupled exploration and exploitation in multi-armed bandits. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2020.

Chloé Rouyer, Yevgeny Seldin, and Nicolò Cesa-Bianchi. An algorithm for stochastic and adversarial bandits with switching costs. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2021.

Yevgeny Seldin and Gábor Lugosi. An improved parametrization and analysis of the EXP3++ algorithm for stochastic and adversarial bandits. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2017.

Yevgeny Seldin and Aleksandrs Slivkins. One practical algorithm for both stochastic and adversarial bandits. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2014.

Yevgeny Seldin, Peter L. Bartlett, Koby Crammer, and Yasin Abbasi-Yadkori. Prediction with limited advice and multiarmed bandits with paid observations. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2014.

William R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25, 1933.

Tobias Sommer Thune and Yevgeny Seldin. Adaptation to easy data in prediction with limited advice. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Chen-Yu Wei and Haipeng Luo. More adaptive algorithms for adversarial bandits. In *Proceedings of the International Conference on Computational Learning Theory (COLT)*, 2018.

Julian Zimmert and Yevgeny Seldin. An optimal algorithm for stochastic and adversarial bandits. In *Proceedings on the International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2019.

Julian Zimmert and Yevgeny Seldin. Tsallis-INF: An optimal algorithm for stochastic and adversarial bandits. *Journal of Machine Learning Research*, 2021.

Julian Zimmert, Haipeng Luo, and Chen-Yu Wei. Beating stochastic and adversarial semi-bandits optimally and simultaneously. In *International Conference on Machine Learning*, pages 7683–7692. PMLR, 2019.