Cooperative adversarial learning via Closed-Loop Transcription

Abstract

This paper proposes a generative model that implements cooperative adversarial learning via closed-loop transcription. In the generative model training, the encoder and decoder are trained simultaneously, and not only the adversarial process but also a cooperative process is included. In the adversarial process, the encoder plays as a critic to maximize the distance between the original and transcribed images, in which the distance is measured by rate reduction in the feature space; in the cooperative process, the encoder and the decoder cooperatively minimize the distance to improve the transcription quality. Cooperative adversarial learning possesses the concepts and properties of Auto-Encoding and GAN, and it is unique in that the encoder actively controls the training process as it is trained in both learning processes in two different roles. Experiments demonstrate that without regularization techniques, our generative model is robust to net architectures and easy to train, sample-wise reconstruction performs well in terms of sample features, and disentangled visual attributes are well modeled in independent principal components.

1 Introduction

Minimax game provides an unsupervised learning method, which is widely used in generative models such as generative adversarial nets (GAN) (Goodfellow et al., 2014; Chen et al., 2016; Radford et al., 2015) and the recently-proposed closed-loop transcription framework (CTRL) (Dai et al., 2022). Generative modeling based on minimax two-player game faces some problems, like the instability in training processes, the difficulty in maintaining the balance between the discriminator and the generator (as in GAN) or between the encoder and the decoder (as in CTRL), and the sensitiveness to net architectures (He et al., 2016a;b).

Maintaining balance and stability in the adversarial process attracts a lot of attention. The mainstream is to provide a constrained discriminator (Kurach et al., 2019). Some regularization techniques are provided, such as weight normalization (Salimans & Kingma, 2016), weight clip (Arjovsky et al., 2017), gradient penalty (Gulrajani et al., 2017), spectral normalization (Miyato et al., 2018), and adversarial lipschitz regularization (Terjék, 2019).

Different from the mainstream regularization methods, this paper considers the feasibility of letting the discriminator actively adapt to the rhythm of the generator. The reason why maintaining balance in the generative models via adversarial process is difficult is that the generator and the discriminator tend to merely play against each other. However, balance will break sooner or later once the discriminator learns faster than the generator. In contrast, generative models based on Auto-Encoding like variational Auto-Encoding (VAE) (Kingma & Welling, 2013; Lopez et al., 2018) tend to be stable, not facing instability and collapse problems. The reason is that the encoder and decoder in the Auto-Encoding framework learn and update themselves cooperatively to improve reconstruction quality and reduce data dimensions in the same direction. In one word, models work cooperatively rather than against each other. Inspired by this cooperation idea, this paper attempts to combine cooperative learning and adversarial learning in the generative model.

In this paper, a generative model via cooperative adversarial learning (CoA-CTRL) is proposed. CoA-CTRL employs the closed-loop transcription framework (CTRL) proposed by (Dai et al., 2022; Ma et al., 2022) and naturally combines the learning strategies of the adversarial process and cooperative process. Firstly, like the discriminator in GAN, the encoder in CoA-CTRL plays as a critic to maximize the feature distance between the real data and the transcribed data. Secondly, consistent

with Auto-Encoding, the encoder and decoder cooperatively minimize the difference between the real data and transcribed data. The confrontation and cooperation between the two take turns and intersect, which will actively keep the system in balance.

2 RELATED WORK

Auto-Encoding and its variants. Auto-Encoding is a typical neural network for representation learning and data dimension reduction (Kramer, 1991; Hinton & Zemel, 1993; Hinton & Salakhutdinov, 2006). Auto-Encoding aims to learn the encoder E_θ and the decoder D_η simultaneously, and this process can be demonstrated by equation (1). Generally, Auto-Encoding tends to learn from L2 pixel-wise distance.

$$\min_{\theta,\eta} \mathcal{L}(\theta,\eta) = \frac{1}{N} \sum_{i=1}^{N} ||x_i - E_\theta(D_\eta(x_i))||_2^2 \tag{1}$$

Generative adversarial nets (GAN). Generative adversarial nets (GAN) provides a generative model based on the adversarial process (Goodfellow et al., 2014; Chen et al., 2016). GAN includes a discriminator and a generator. The discriminator evaluates the performance of the generated images, and the generator tends to fool the discriminator. The two networks are trained based on the two-player minimax game by the value function $V(G(\eta), D(\theta))$ as equation (2) displays, where $G(\eta)$ and $D(\theta)$ donate to the generator and discriminator respectively.

$$\min_\eta \max_\theta V(\eta,\theta) = \mathbb{E}_{x \sim p(x)}[\log D(x)] + \mathbb{E}_{z \sim p(z)}[\log(1 - D(G(z)))] \tag{2}$$

MCR^2 and CTRL. Recently, (Chan et al., 2022; Yu et al., 2020) proposed a new learning objective, the so-called principle of maximal coding rate reduction (MCR^2), which is to learn the low-dimension intrinsic structures from high dimension data and obtain discriminative representation between classes. Encoder $f(x,\theta)$ maps high dimension data X to the low dimension features Z. As is shown in equation (3), MCR^2 provides a method called coding rate ($R(Z,\epsilon)$) to measure the compactness of learned feature Z integrally subject to the distortion ϵ. The rate reduction (ΔR) measures the distance in the feature space. In a special case of two classes [1], as shown in equation (6), there will be data features Z and $\hat{Z}$. The distance between Z and $\hat{Z}$ can be measured by coding rate reduction ($\Delta R(Z, \hat{Z})$), that is, the difference between the coding rate of ($Z \cup \hat{Z}$) and the average sum of them (R_c).

$$R(Z,\epsilon) = \frac{1}{2} \log \det(I + \alpha Z Z^*) \tag{3}$$

$$\underbrace{X \xrightarrow{f(x,\theta)} Z \xrightarrow{g(x,\eta)} \hat{X} \xrightarrow{f(x,\theta)} \hat{Z}}_{h(x,\theta,\eta)=f \circ g \circ f} \tag{4}$$

$$h(x,\theta,\eta) = f(g(f(x,\theta),\eta),\theta) \tag{5}$$

$$\Delta R(Z,\hat{Z}) = R(Z \cup \hat{Z}) - \underbrace{\frac{1}{2}(R(Z) + R(\hat{Z}))}_{R_c} \tag{6}$$

$$\min_\theta \max_\eta \mathcal{T}(\theta,\eta) = \Delta R(f(X,\theta), h(X,\theta,\eta)) = \Delta R(Z(\theta), \hat{Z}(\theta,\eta)) \tag{7}$$

CTRL (Dai et al., 2022) provides a closed-loop framework based on MCR^2, consisting an encoder ($f(x,\theta)$) and a decoder ($g(z,\eta)$). As equation (7) shows, CTRL aims to transcribe data via minimaxing coding rate reduction, in which $h(x,\theta,\eta)$ captures a closed-loop map as demonstrated by equations (4) and (5). The first segment ($x \to z \to \hat{x}$) in (4) resembles Auto-Encoding, and the second segment ($z \to \hat{x} \to \hat{z}$) resembles GAN. While GAN generates images from Random Gaussian Distribution noise, in CTRL, as (4) displays, decoder $g(z,\eta)$ maps from feature Z (which is encoded from X), and then encoder $f(x,\theta)$ maps $\hat{X}$ to feature $\hat{Z}$. The distance between X and $\hat{X}$ is described by the coding rate reduction (ΔR) in equation (6). $R(Z \cup \hat{Z})$ refers to the

---

[1]Where $X \in \mathbb{R}^{D \times n}$ refers to data samples, $Z \in \mathbb{R}^{d \times n}$ refers to features, $\alpha = \frac{d}{n\epsilon^2}$

coding rate of joint space of Z and $\hat{Z}$. R_c describes the average sum coding rate of Z and $\hat{Z}$. The encoder maximizes ΔR, and the decoder minimizes it. In this adversarial learning process, CTRL is consistent with GAN (Goodfellow et al., 2014).

(Chan et al., 2022) shows that the gradient of ΔR will disappear when ΔR is large enough, which leads to low learning efficiency of encoder $f(x, \theta)$ and decoder $g(z, \eta)$. The ΔR (the yellow ball) in the left part of Figure 1 demonstrates this situation. This is consistent with (Arjovsky & Bottou, 2017), which shows that when the distribution of real images and fake images does not intersect in GAN, the gradient of the generator disappears. Therefore, keeping ΔR at a small value is important. The ΔR of the right part of Figure 1 is better than the left part for the minimax game.

Figure 1: Two different representations compared based on different rate reductions. (Yu et al., 2020; Chan et al., 2022) $R(Z \cup \hat{Z})$ is demonstrated by a number of ϵ-balls in the joint space of Z and $\hat{Z}$ (all the balls). R_c is the sum of a number of subspaces of Z (green ball) and $\hat{Z}$ (red ball). ΔR describes their difference (yellow ball). While MCR^2 prefers the left representation for large rate reduction, in the minimax game, the right is better.

3 COOPERATIVE ADVERSARIAL LEARNING

3.1 CLOSED-LOOP TRANSCRIPTION: ONE ENCODER, TWO ROLES

Closed-loop transcription structure (Dai et al., 2022) uses the encoder $f(x, \theta)$ twice, and it gives the encoder $f(x, \theta)$ two different roles. As Figure 2 demonstrates, in the first segment of $x \to z \to \hat{x}$ (red dotted frame), the encoder takes the responsibility as the encoder in Auto-Encoding; in the second segment of $z \to \hat{x} \to \hat{z}$ (grey dotted frame), the encoder takes the responsibility consistent with the discriminator in GAN. Equation (8) shows this mechanism.

$$H(X, \theta, \eta) = f(g(f(X, \theta), \eta), \theta) = \hat{Z}(\theta, \eta) \tag{8}$$

The way Closed-loop transcription combines the structures of Auto-Encoding and GAN is ingenious, as it gives the encoder two different roles. Different from the former works such as VAE-GAN (Larsen et al., 2016) and BiGAN (Donahue et al., 2016; Dumoulin et al., 2016) who add a discriminator to estimate the decoder, closed-loop transcription trains only the encoder and the decoder, and it is the encoder that estimates the performance of the decoder.

Figure 2: Closed-loop structure and cooperative adversarial learning: encoder $f(x, \theta)$ and decoder $g(z, \eta)$ play against each other in the adversarial process (grey dotted frame) and cooperate with each other in the cooperative process (red dotted frame).

3.2 COOPERATIVE ADVERSARIAL LEARNING: TWO ROLES, LEARN TWICE

Cooperative adversarial learning attempts combine the learning strategies of Auto-Encoding and GAN. As discussed in section 2, Auto-Encoding and GAN follow different learning strategies. GAN optimizes the generator and discriminator via an adversarial process, in which the generator tries to produce images to fool the discriminator, while the discriminator tries to distinguish the difference between real and fake images. However, Auto-Encoding optimizes the encoder and decoder via a reconstruction task, in which the encoder and the decoder cooperatively improve the reconstruction quality and reduce data dimensions. Therefore, since the encoder in closed-loop transcription takes two roles, a natural idea is to let the encoder and decoder follow not only the adversarial but also the cooperative learning strategies. In CoA-CTRL, we implement cooperative adversarial learning (as equation (11) demonstrates) that naturally combines the adversarial process and the cooperative process.

$$\max_{\theta} \Delta R(f(X,\theta), H(X,\theta,\eta)) = \Delta R(Z(\theta), \hat{Z}(\theta,\eta)) \tag{9}$$

$$\updownarrow adversarial$$

$$\min_{\theta,\eta} \quad \Delta R(f(X,\theta), H(X,\theta,\eta)) = \Delta R(Z(\theta), \hat{Z}(\theta,\eta)) \tag{10}$$

$$\underbrace{\phantom{\min_{\theta,\eta}}}_{cooperation}$$

(1) Adversarial process. The adversarial process is demonstrated by the grey dotted frame in Figure 2, which is inherited from GAN (Goodfellow et al., 2014) and CTRL (Dai et al., 2022). Segment $z \to \hat{x} \to \hat{z}$ resembles the GAN structure, in which the encoder plays the role of the discriminator in GAN. As equation (9) shows, the encoder plays as a critic to maximize the distance between the original data and the transcribed data in the feature space.

(2) Cooperative process. The cooperative process is demonstrated by the red dotted frame in Figure 2. Segment $x \to z \to \hat{x}$ is naturally the Auto-Encoding structure. In CoA-CTRL, the encoder and decoder learn cooperatively in this segment, which is demonstrated by equation (10). CoA-CTRL's cooperative learning process resembles the Auto-Encoding loss function (equation (1)). However, Auto-Encoding optimizes the reconstruction quality based on pixel-wise loss, while CoA-CTRL optimizes the reconstruction quality based on the distribution distance (ΔR) in the feature space, and the feature distribution is defined by the encoder itself, which can be seen as a self-consistent learning strategy in the closed-loop framework. When the encoder tries to find the distribution distance and maximizes it in equation (9), it provides an iterative learning signal (ΔR) for the reconstruction task in equation (10). The encoder takes the responsibility for two roles and learns twice. It minimizes what it maximizes, which is a self-consistent learning strategy (Ma et al., 2022).

In this sense, CoA-CTRL is an adaptive learning strategy and naturally unifies an adversarial process consistent with GAN and a cooperative process consistent with Auto-Encoding, which will contribute to its learning quality and stability. In conclusion, cooperative adversarial learning that follows the value function $\mathcal{T}(\theta,\eta)$ is displayed in equation (11):

$$\min_{\theta,\eta} \max_{\theta} \mathcal{T}(\theta,\eta) = \Delta R(f(X,\theta), H(X,\theta,\eta)) = \Delta R(Z(\theta), \hat{Z}(\theta,\eta)) \tag{11}$$

3.3 COOPERATIVE ADVERSARIAL RATIO (COA-RATIO): A HYPERPARAMETER TO ADJUST THE COOPERATIVE PROCESS AND THE ADVERSARIAL PROCESS

Active control of the adversarial process and the cooperative process. As discussed before, the encoder works and learns in two different roles in the adversarial process and the cooperative process respectively. Therefore, through the functioning of the encoder in both processes, we can actively control the adversarial process and the cooperative process. We introduce a hyperparameter cooperative adversarial ratio (CoA-ratio), which is the ratio of the encoder's learning rate in the adversarial process to its learning rate in the cooperative process, to adjust the learning rate of the encoder in two learning processes. In every iteration, before going through equation (9), the learning rate of the encoder would be multiplied by the CoA-ratio, and before going through equation (10), the encoder's learning rate would be restored to the previous value.

Balance achieved through active control. The discriminator and generator in GAN work in the opposite direction. The learning process of the discriminator is hard to control, and therefore the balance of the training is hard to keep. Benefited by the encoder learning twice in the cooperative and adversarial processes and its different learning rates and speeds realized by the CoA-ratio, the encoder becomes the controller and regulator of the training process. The training process and the loss value ΔR thus can be easily controlled without paying too much attention to constrained network design.

3.4 ADVANTAGES AND DIFFERENCES

Training stability. Encoder's learning twice provides a way to actively balance the learning processes through its two roles. As equation (11) shows, the encoder not only maximizes ΔR but also minimizes it, which relieves the need to design special networks or adjust parameters. Compared with former balance techniques, CoA-CTRL does not add constraint techniques or computing processes. It is simple and computationally efficient. In experiments, classic deep nets ResNet18, ResNet50, and ResNet101 (He et al., 2016a;b) are used to validate CoA-CTRL's active balance.

Sample-consistent reconstruction and disentangled latent space. As mentioned in 3.2, CoA-CTRL naturally unifies the learning strategies of Auto-Encoding and GAN, which will help the encoder learn better and faster. Other than that, it will benefit the sample-wise reconstruction. Sample-wise consistent reconstruction $g(f(x)) \approx x$ is the ideal solution to $\Delta R(Z(\theta), Z(\theta, \eta)) \approx 0$, and $\Delta R(Z(\theta), Z(\theta, \eta))$ is determined by encoder $f(x, \theta)$ and decoder $g(z, \eta)$. CTRL (Dai et al., 2022) would minimize $\Delta R(\theta, \eta)$ merely through the decoder $g(z, \eta)$, which would give an approximate optimization choice that results in poor sample-wise consistency. However, if we optimize $\Delta R(\theta, \eta)$ by decoder $g(z, \eta)$ and encoder $f(x, \theta)$, the optimization process would become simple, and the ideal sample-consistent solution would be easily obtained. In addition, cooperative adversarial learning via closed-loop transcription produces good disentangled feature space. Later experiments will demonstrate this advantage.

Simpler. As Auto-Encoding, its variants (Kingma & Welling, 2013), and GAN all gain a lot of attention in the generative model area, many works have attempted to combine Auto-Encoding and GAN, like Bigan (Donahue et al., 2016), ALI (Dumoulin et al., 2016), adversarial autoencoders (Makhzani et al., 2015) and VAE-GAN (Larsen et al., 2016). Different from those attempts, CoA-CTRL implements the closed-loop transcription (Dai et al., 2022), and invites no other discriminator, Based on the closed-loop framework, the cooperative process is introduced. The encoder learns twice in different roles within one iteration without investing more computing resources. Stability and balance are controlled actively without regulation techniques, which contributes to computing resource saving compared to other regulation techniques like spectral normalization (Miyato et al., 2018).

4 EXPERIMENTS

4.1 SETTING

To verify the advantages of CoA-CTRL, we implement CoA-CTRL on the simple handwritten digits data set MNIST (LeCun et al., 1998), diverse data set CIFAR-10 (Krizhevsky et al., 2009) and STL-10 (Coates et al., 2011), and facial data set Celeb-A (Liu et al., 2015). In this paper, we intend to justify two main advantages of CoA-CTRL: firstly, CoA-CTRL's robustness to different net architectures through our cooperative adversarial learning; secondly, CoA-CTRL's sample-consistent reconstruction and disentangled latent space.

The settings of the base experiments are as follows. Adam (Kingma & Ba, 2014) would be used as the optimizer. The learning rate is set at 0.0001, and the linear decay is applied. For the classic hyperparameters β_1 and β_2, we set them at 0.0 and 0.9 respectively. We fix ϵ at 0.5 in all experiments. CoA-ratio is set at 1.3 for MNIST and 1.5 for other data sets. The value of the feature dimension (nz) is set at 128. The batchsize (bs) for MNIST is 256, and the batchsize for other diverse data sets is 512. For the decoder, we adopt the widely used networks in DCGAN (Radford et al., 2015), SNGAN (Miyato et al., 2018), and CTRL (Dai et al., 2022). For the encoder, we apply deep nets 18-layer preaction resnet (ResNet18), 50-layer preaction resnet (ResNet50), and 101-layer preaction resnet (ResNet101) to verify CoA-CTRL's stability and robustness to deep nets. Detailed information about the encoder and decoder used in the experiments can be found in the Appendix.

As for ResNet18, ResNet50, and ResNet101 in this paper, we use preaction (He et al., 2016b) and average pooling to downsample, which will contribute to better feature extraction. For STL-10 and Celeb-A, we add a downsample at the first ResBlock of ResNet18. Spectral normalization (Miyato et al., 2018), batch normalization (Ioffe & Szegedy, 2015), or other regulation techniques are not applied, instead, just a simple and standard convolution layer without constraint is employed.

We run 10,000 iterations on MNIST, 100,000 iterations on CIFAR-10, 150,000 iterations on STL-10 and Celeb-A. We resize the resolution of MNIST to 32×32, STL-10 to 48×48, and Celeb-A to 64×64.

4.2 EMPIRICAL VERIFICATION OF COA-CTRL'S ACTIVE BALANCE

4.2.1 ACTIVE BALANCE TO NET ARCHITECTURES

To verify CoA-CTRL's active balance, we conduct several comparative tests on CIFAR-10, using ResNet18, ResNet50, and ResNet101 as the encoder, and the widely used 8-layer resnet (De8) (Miyato et al., 2018) as the decoder. We intend to prove that even with an unbalanced combination of the encoder and decoder, CoA-CTRL can perform well in a stable manner. We apply the same settings on GAN and CTRL, aiming to compare their stability and performances with CoA-CTRL. Results in Table 1 show that CoA-CTRL works well, while GAN and CTRL fail and collapse in the training process.

To quantity CoA-CTRL's performance, we test CoA-CTRL by the widely used Inception score (IS) (Salimans et al., 2016) and Fréchet Inception Distance (FID) (Heusel et al., 2017). We further compare CoA-CTRL's IS and FID with other major generative models, which are displayed in Table 3. Interested in the parts nz and batchsize play in CoA-CTRL's performance and stability, we additionally adjust nz and batchsize to see whether CoA-CTRL can maintain balance. As shown in Table 1, we find that CoA-CTRL works well with different combinations of nz and batchsize, and it performs better when we increase nz and batchsize at the same time.

We also explore the loss value ΔR in the training process. As shown in Figure 3, CoA-CTRL keeps low and stable ΔR and high $R(Z \cup \hat{Z})$, while CTRL shows unstable training loss ΔR. CoA-CTRL's stable training loss contributes to its training success and excellent performance.

Table 1: Stability and performance of CoA-CTRL compared with GAN and CTRL on CIFAR-10. Experiments show that CoA-CTRL gets excellent performances in a stable manner even with unbalanced settings of a deep encoder and a shallow decoder. Avg. of R and Avg. of ΔR refer to the average value of $R(Z \cup \hat{Z})$ and ΔR in the training process. $\uparrow$ means higher is better, and $\downarrow$ means lower is better.

Methods	Encoder/ Discriminator	Decoder/ Generator	nz	bs	Result	Avg. of R	Avg. of ΔR	IS $\uparrow$	FID $\downarrow$
(1) Comparisons of stability and performance									
GAN	ResNet18	De8	128	128	fail	-	-	-	-
GAN	ResNet18	De8	128	512	fail	-	-	-	-
CTRL	ResNet18	De8	128	512	fail	45.57	9.77	-	-
CoA-CTRL	ResNet18	De8	128	512	succeed	65.03	1.65	7.94	10.49
CoA-CTRL	ResNet50	De8	128	512	succeed	64.04	1.84	7.82	11.17
CoA-CTRL	ResNet101	De8	128	512	succeed	63.79	1.76	7.12	19.12
(2) Ablation study on nz and batchsize									
CoA-CTRL	ResNet18	De8	128	512	succeed	65.03	1.65	7.94	10.49
CoA-CTRL	ResNet18	De8	128	1024	succeed	63.85	1.25	7.91	10.92
CoA-CTRL	ResNet18	De8	256	512	succeed	127.92	6.15	7.38	12.72
CoA-CTRL	ResNet18	De8	256	1024	succeed	127.15	2.81	**8.21**	**9.54**
CoA-CTRL	ResNet18	De8	512	1024	succeed	244.38	11.17	7.60	11.61

Table 2: Ablation study on CoA-ratio on CIFAR-10. Avg. of R and Avg. of ΔR refer to the average value of $R(Z \cup \hat{Z})$ and ΔR in the training process.

CoA-ratio	1.25	1.5	1.75	2.0
Avg. of R	64.08	65.03	63.45	64.16
Avg. of ΔR	0.62	1.65	3.92	4.07
IS↑	6.55	7.94	7.02	6.64
FID↓	22.34	10.49	38.04	38.20

(a) CTRL

(b) CoA-CTRL

Figure 3: Loss evaluation of CTRL and CoA-CTRL in the training process on CIFAR-10, using ResNet18. CoA-CTRL keeps ΔR in a stable curve even with an unbalanced setting of a deep encoder and a shallow decoder.

4.2.2 ASSOCIATION BETWEEN THE LOSS VALUE ΔR AND PERFORMANCE

As shown in Table 1 and Figure 3, CoA-CTRL's performance seems to be associated with ΔR. As discussed in section 3.3, we introduce CoA-ratio to adjust the learning rate of the encoder in the adversarial process and the cooperative process, which would influence the loss value ΔR. Therefore, we set CoA-catio at 1.25,1.5,1.75 and 2.0 respectively to explore the influence of ΔR on CoA-CTRL's performance. We conduct the experiment on CIFAR-10, using ResNet18 as the encoder, with nz and batchsize set at 128 and 512. Results in Table 2 show that different CoA-ratios are associated with ΔR and R, and the performance score IS and FID are highly influenced by ΔR. This paper just points out that CoA-ratio, ΔR, and performance are highly associated. Future works will explore the mechanisms.

4.2.3 EXCELLENT PERFORMANCE ACHIEVED THROUGH A SIMPLE DECODER

We compare CoA-CTRL's performance with other generative models on CIFAR-10 and STL-10. The data in Table 3 is directly cited from those relevant papers except for CoA-CTRL. For CoA-CTRL, We use ResNet18 as the encoder on both CIFAR-10 and STL-10. Table 3 shows that CoA-CTRL performs better with a simple decoder and experiment setting, compared with other generative models, such as GANs with regularization techniques (SNGAN, WGAN-GP, WGAN-ALP) (Miyato et al., 2018; Gulrajani et al., 2017; Terjék, 2019), self-supervised GAN (Chen et al., 2019), latent optimisation GAN (LOGAN) (Wu et al., 2019), complex model GAN (BIGGAN) (Brock et al., 2018), a recent combination of GAN and VAE (DCVAE) (Parmar et al., 2021), and the original CTRL (Dai et al., 2022). Compared with CTRL, the FID value of CoA-CTRL is decreased by 10.06 on CIFAR-10 and 20.06 on STL-10. The improvements are clear and substantial.

4.3 SAMPLE-WISE CONSISTENCY

CoA-CTRL performs well on sample-wise reconstruction in terms of sample features, which is demonstrated by our experiments on several mainstream data sets. For MNIST, we applied the classic encoder and decoder in DCGAN (Radford et al., 2015) and run 10,000 iterations. Figure 4 shows CoA-CTRL's reconstruction performance on MNIST compared with CTRL. We can see

Table 3: Comparison of performances of CoA-CTRL and other generative methods on CIFAR-10 and STL-10. Data of other generative models are cited from relevant papers. For CoA-CTRL (1), the nz is 128, and the bs is 512; for CoA-CTRL (2), the nz is 256, and the bs is 1024.

Methods	CIFAR-10		STL-10	
	IS↑	FID↓	IS↑	FID↓
SNGAN	8.2	21.7	9.1	40.1
WGAN-GP	7.9	29.3	-	-
WGAN-ALP	8.3	13.0	-	-
SSGAN	-	17.1	-	-
LOGAN	8.7	17.7	-	-
BIGGAN	9.2	14.7	-	-
DCVAE	8.2	17.9	8.1	41.9
CTRL	8.1	19.6	8.4	38.6
CoA-CTRL (1)	7.94	**10.49**	8.68	**22.96**
CoA-CTRL (2)	8.21	**9.54**	9.28	**18.54**

(a) X

(b) $\hat{X}$ by CoA-CTRL

(c) $\hat{X}$ by CTRL

(d) CIFAR-10 X

(e) CIFAR-10 $\hat{X}$ by CoA-CTRL

Figure 4: Comparison of sample-wise reconstruction. CoA-CTRL performs well in sample-wise reconstruction on MNIST and CIFAR-10.

that CoA-CTRL's reconstruction is almost the same as the original input, better and more consistent than CTRL. For the more complex CIFAR-10, STL-10 and Celeb-A, we employ ResNet18 as the encoder. We run 100,000 iterations on CIFAR-10 and 150,000 iterations on STL-10 and Celeb-A. Figure 4 displays CoA-CTRL's performance on CIFAR-10. The results on STL-10 and Celeb-A can be found in Figure 6 in the Appendix. In Figure 4, We can see that CoA-CTRL reconstructs well in terms of features, color, and classes, which is benefited from cooperative adversarial learning and a loss function based on the feature space.

4.4 DISENTANGLED FEATURE SPACE

The latent space of GAN has no certain meanings and lacks inverse maps from data to the latent space. Some following works discussed this issue (Chen et al., 2016; Karras et al., 2019; 2020; Tov et al., 2021). The latent space in Cooperative adversarial learning has clear and disentangled meanings. CoA-CTRL possesses the concept of dual consistent maps, $x \rightarrow z$, and $z \rightarrow x$. Images in Figure 5 are the generated samples of CIFAR-10 along independent principal components. We select the top 10 components with every row referring to a component from top to bottom. We choose the class of bird and ship to evaluate CoA-CTRL's disentangled feature space. As shown in Figure

5, different shapes, styles, backgrounds, and other visual attributes are well modeled in different principal components, and the images vary with the scale value. Generated samples of other classes can be found in Figure 7 in the Appendix. In addition, we test the classification accuracy on MNIST based on feature representations with one Nearest Neighbor (1NN) classifier and compare the result with other methods. As Table 4 shows, CoA-CTRL's performance is competitive compared with other methods (Springenberg, 2015; Kingma & Welling, 2013; Donahue et al., 2016; Dumoulin et al., 2016; Makhzani et al., 2015; Parmar et al., 2021; Dai et al., 2022).

Table 4: Class-wise accuracy performance with respect to unsupervised representation on MNIST

Method	VAE	BIGAN	catGAN	AAE	DC-VAE	CTRL	CoA-CTRL
Accuracy	97.12%	97.39%	95.7%	95.9%	98.71%	89.12%	95.89%

(a) bird   (b) ship

Figure 5: Generated samples of two classes (bird and ship) along 10 principal components from the feature subspace on CIFAR-10. Every row refers to a principal component, and the scale value varies from -1.5 to 1.5. More class samples can be found in the Appendix.

5 DISCUSSION AND CONCLUSION

In this paper, we propose cooperative adversarial learning, and based on this new learning method and closed-loop transcription, we build a promising generative model, which possesses the properties of active balance, better generative performance, and disentangled latent space. Other than that, we find it competitive in unsupervised representation. Although cooperative adversarial learning provides a way to balance deep nets, some questions are still unclear. For example, whether a deeper encoder would benefit to better performance, and how big a coop-ratio or ΔR is best for the training process and model performance. These questions deserve further explorations.

REFERENCES

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. *arXiv preprint arXiv:1701.04862*, 2017.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pp. 214–223. PMLR, 2017.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Kwan Ho Ryan Chan, YD Yu, Chong You, Haozhi Qi, John Wright, and Yi Ma. Redunet: A white-box deep network from the principle of maximizing rate reduction. *J Mach Learn Res*, 23(114): 1–103, 2022.

Ting Chen, Xiaohua Zhai, Marvin Ritter, Mario Lucic, and Neil Houlsby. Self-supervised gans via auxiliary rotation loss. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 12154–12163, 2019.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. *Advances in neural information processing systems*, 29, 2016.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223. JMLR Workshop and Conference Proceedings, 2011.

Xili Dai, Shengbang Tong, Mingyang Li, Ziyang Wu, Michael Psenka, Kwan Ho Ryan Chan, Pengyuan Zhai, Yaodong Yu, Xiaojun Yuan, Heung-Yeung Shum, et al. Ctrl: Closed-loop transcription to an ldr via minimaxing rate reduction. *Entropy*, 24(4):456, 2022.

Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. *arXiv preprint arXiv:1605.09782*, 2016.

Vincent Dumoulin, Ishmael Belghazi, Ben Poole, Olivier Mastropietro, Alex Lamb, Martin Arjovsky, and Aaron Courville. Adversarially learned inference. *arXiv preprint arXiv:1606.00704*, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. *Advances in neural information processing systems*, 30, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016a.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pp. 630–645. Springer, 2016b.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.

Geoffrey E Hinton and Ruslan R Salakhutdinov. Reducing the dimensionality of data with neural networks. *science*, 313(5786):504–507, 2006.

Geoffrey E Hinton and Richard Zemel. Autoencoders, minimum description length and helmholtz free energy. *Advances in neural information processing systems*, 6, 1993.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4401–4410, 2019.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8110–8119, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Mark A Kramer. Nonlinear principal component analysis using autoassociative neural networks. *AIChE journal*, 37(2):233–243, 1991.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Karol Kurach, Mario Lučić, Xiaohua Zhai, Marcin Michalski, and Sylvain Gelly. A large-scale study on regularization and normalization in gans. In *International conference on machine learning*, pp. 3581–3590. PMLR, 2019.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. In *International conference on machine learning*, pp. 1558–1566. PMLR, 2016.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pp. 3730–3738, 2015.

Romain Lopez, Jeffrey Regier, Michael I Jordan, and Nir Yosef. Information constraints on autoencoding variational bayes. *Advances in neural information processing systems*, 31, 2018.

Yi Ma, Doris Tsao, and Heung-Yeung Shum. On the principles of parsimony and self-consistency for the emergence of intelligence. *Frontiers of Information Technology & Electronic Engineering*, pp. 1–26, 2022.

Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, Ian Goodfellow, and Brendan Frey. Adversarial autoencoders. *arXiv preprint arXiv:1511.05644*, 2015.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

Gaurav Parmar, Dacheng Li, Kwonjoon Lee, and Zhuowen Tu. Dual contradistinctive generative autoencoder. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 823–832, 2021.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Tim Salimans and Durk P Kingma. Weight normalization: A simple reparameterization to accelerate training of deep neural networks. *Advances in neural information processing systems*, 29, 2016.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.

Jost Tobias Springenberg. Unsupervised and semi-supervised learning with categorical generative adversarial networks. *arXiv preprint arXiv:1511.06390*, 2015.

Dávid Terjék. Adversarial lipschitz regularization. *arXiv preprint arXiv:1907.05681*, 2019.

Omer Tov, Yuval Alaluf, Yotam Nitzan, Or Patashnik, and Daniel Cohen-Or. Designing an encoder for stylegan image manipulation. *ACM Transactions on Graphics (TOG)*, 40(4):1–14, 2021.

Yan Wu, Jeff Donahue, David Balduzzi, Karen Simonyan, and Timothy Lillicrap. Logan: Latent optimisation for generative adversarial networks. *arXiv preprint arXiv:1912.00953*, 2019.

Yaodong Yu, Kwan Ho Ryan Chan, Chong You, Chaobing Song, and Yi Ma. Learning diverse and discriminative representations via the principle of maximal coding rate reduction. *Advances in Neural Information Processing Systems*, 33:9422–9434, 2020.

A   APPENDIX

Table 5: Decoder for MNIST

$z \in \mathbb{R}^{dim}$
4×4,stride=1,pad=0 deconv.BN256 ReLU
4×4,stride=2,pad=0 deconv.BN128 ReLU
4×4,stride=1,pad=0 deconv.BN64 ReLU
4×4,stride=1,pad=0 deconv 1 Tanh

Table 6: Encoder for MNIST

$x \in \mathbb{R}^{32 \times 32 \times 1}$
4 × 4, stride=2, pad=1 conv 64 lReLU
4 × 4, stride=2, pad=1 conv. BN 128 lReLU
4 × 4, stride=2, pad=1 conv. BN 256 lReLU
4 × 4, stride=1, pad=0 conv 128

Table 7: Decoder for CIFAR10

$z \in \mathbb{R}^{dim}$
dense → 4 × 4× 256
ResBlock up 256
ResBlock up 256
ResBlock up 256
BN, ReLU, 3×3 conv, 3 Tanh

Table 8: Decoder for STL10

$z \in \mathbb{R}^{dim}$
dense → 6 × 6× 512
ResBlock up 256
ResBlock up 128
ResBlock up 64
BN, ReLU, 3×3 conv, 3 Tanh

Table 9: Decoder for Celeb-A-64

$z \in \mathbb{R}^{dim}$
dense → 4 × 4× 1024
ResBlock up 512
ResBlock up 256
ResBlock up 128
ResBlock up 64
BN, ReLU, 3×3 conv, 3 Tanh

(a) STL-10 X

(b) STL-10 $\hat{X}$ by CoA-CTRL

(c) Celeb-A X

(d) Celeb-A $\hat{X}$ by CoA-CTRL

Figure 6: Comparison of sample-wise reconstruction. CoA-CTRL performs good sample-wise reconstruction STL-10 and Celeb-A.

Figure 7: Generated samples of ten classes along 10 principal components from the feature subspace on CIFAR-10. Every row refers to a principal component, and the scale value varies from -1.5 to 1.5.

(a) CoA-ratio:1.25

(b) CoA-ratio:1.5

(c) CoA-ratio:1.75

(d) CoA-ratio:2.0

Figure 8: Loss evaluation of CoA-CTRL in the training process on CIFAR-10, using ResNet18 as the encoder and De8 as the decoder. Different CoA-ratio of 1.25, 1.5, 1.75, and 2.0 are used.