UV-ATTACK: PHYSICAL-WORLD ADVERSARIAL ATTACKS FOR PERSON DETECTION VIA DYNAMIC-NERF-BASED UV MAPPING

ABSTRACT

In recent research, adversarial attacks on person detectors using patches or static 3D model-based texture modifications have struggled with low success rates due to the flexible nature of human movement. Modeling the 3D deformations caused by various actions has been a major challenge. Fortunately, advancements in Neural Radiance Fields (NeRF) for dynamic human modeling offer new possibilities. In this paper, we introduce UV-Attack, a groundbreaking approach that achieves high success rates even with extensive and unseen human actions. We address the challenge above by leveraging dynamic-NeRF-based UV mapping. UV-Attack can generate human images across diverse actions and viewpoints, and even create novel actions by sampling from the SMPL parameter space. While dynamic NeRF models are capable of modeling human bodies, modifying clothing textures is challenging because they are embedded in neural network parameters. To tackle this, UV-Attack generates UV maps instead of RGB images and modifies the texture stacks. This approach enables real-time texture edits and makes the attack more practical. We also propose a novel Expectation over Pose Transformation loss (EoPT) to improve the evasion success rate on unseen poses and views. Our experiments show that UV-Attack achieves a 92.75% attack success rate against the FastRCNN model across varied poses in dynamic video settings, significantly outperforming the state-of-the-art AdvCamou attack, which only had a 28.50% ASR. Moreover, we achieve 49.5% ASR on the latest YOLOv8 detector in black-box settings. This work highlights the potential of dynamic NeRF-based UV mapping for creating more effective adversarial attacks on person detectors, addressing key challenges in modeling human movement and texture modification.

1 INTRODUCTION

Adversarial attacks have become significant concerns in both digital and physical domains, impacting areas like facial recognition (Gong et al., 2023; Yang et al., 2023) and object detection (Huang et al., 2023; Li et al., 2023c). To improve the physical attack success rate, researchers have attempted to use 2D transformations-such as translation, rescaling, and shearing (Zhong et al., 2022)-and 3D modeling (Huang et al., 2024; Suryanto et al., 2022) to simulate changes in viewpoints for objects like stop signs and cars. However, compared with attacks on rigid objects, attacks on non-rigid objects like human beings are more challenging because of the variability in clothing distortions and human poses. These non-rigid distortions are difficult to simulate using basic transformations or static 3D modeling. Consequently, previous attempts at person detection attacks often relied on adding an adversarial patch to the front of the T-shirt (Xu et al., 2020; Wang et al., 2021b; Lin et al., 2023) or assumed minimal movement (Hu et al., 2022; 2023), which limits the real-world attack success rate when the subject undergoes significant movement and unseen poses.

To address these challenges, in this work, we propose the UV-Attack, which successfully addresses this challenge by incorporating dynamic NeRF-based UV mapping into the attack pipeline. Recent advancements have applied neural radiance fields (NeRF) (Barron et al., 2021) to dynamically modeling human bodies (Geng et al., 2023; Weng et al., 2022). These methods enable the modeling of human bodies as neural networks and generate novel poses with minimal parameters. Nevertheless, directly modifying the texture of NeRF models is challenging due to the texture information being

embedded within neural network parameters (Dong et al., 2022). To solve this issue, inspired by the latest work of editable NeRF model (Chen et al., 2023c), we model the 3D human body's shape and textures respectively. Then we focus on editing the 3D textures through learnable Densepose-like UV-maps (Güler et al., 2018). This approach enables real-time editing of 3D textures without requiring gradient backpropagation on the NeRF model. Moreover, to improve the physical attack success rate on *unseen* poses, we sample novel poses from the SMPL parameter spaces and generate human images with unobserved poses and viewpoints. Moreover, we propose a novel Expectation over Pose Transformation(EoPT) loss function to enhance the attack's effectiveness.

Furthermore, recent studies have explored the use of diffusion models to enhance the transferability of adversarial examples (Xue et al., 2023; Lin et al., 2023; Chen et al., 2023b). However, these methods show limited success in physical attacks due to restricted noise levels. To address this problem, we improve the physical attack success rate by expanding the perturbation space. By tweaking the starting point of the stable diffusion model and removing classifier-free guidance, we achieve a higher ASR, as our method allows for the exploration of larger and less familiar areas in the latent space compared to previous approaches.

We compare `UV-Attack` with the latest person detection attacks (Hu et al., 2022; 2023) and diffusion-based attacks (Xue et al., 2023; Lin et al., 2023). Our experiments demonstrate the superiority of our approach over in terms of evasion success rates in free-pose scenarios. As shown in Figure 1, we physically printed the Bohemian-style clothing and successfully fooled person detectors in dynamic video settings, even when the subjects were in continuous and significant movement. Our key contributions are:

1. We propose a novel person detection attack algorithm that effectively handles pose variation through UV mapping. Our method can generate unseen actions and can edit human clothes in real-time. Moreover, we propose a novel Expectation over Pose Transformation loss (EoPT) to improve the evasion success rate on unseen poses and views.

2. We utilize the stable diffusion model to enhance the transferability of adversarial patches. We expand the search space by adjusting the starting point of the conditional latent diffusion model without employing classifier-free guidance, which results in a higher physical ASR.

3. Our attack is designed to be physically realizable. We manufacture adversarial clothing in the real world and achieve a physical ASR of 85% in a free-pose setting. This significantly surpasses the performance of the state-of-the-art Adv-Camou (Hu et al., 2023) attack, which attains only a 25% ASR. Moreover, we achieve 49.5% ASR on the latest YOLOv8 detector in black-box settings.

2 BACKGROUND

Adversarial Attacks against Object Detection   Recent work has employed elaborate adversarial examples to attack real-world image classifiers (Wang et al., 2023; Zhong et al., 2022) and object detectors (Zhang et al., 2023; Huang et al., 2023; Li et al., 2023c; Wang et al., 2022). Unlike digital attacks, physical attacks introduce greater complexity due to the physical variables. Early efforts to improve the efficacy using basic 2D transformations like translation, rescaling, and shearing (Zhao et al., 2019; Zhong et al., 2022). However, these approaches are largely effective only for planar objects such as stop signs. For 3D objects, more advanced techniques involving static 3D modeling and differentiable rendering have been employed to modify the textures (Wang et al., 2022; 2021a; Ravi et al., 2020). However, such methods are generally limited to rigid objects and fail to adequately address the dynamic and non-rigid targets. Specifically, static 3D models do not effectively simulate human poses, and the use of 2D and 3D Thin Plate Splines (TPS) Xu et al. (2020) has only been successful in modeling minor clothing distortions, falling short in replicating the impact of diverse human poses. Consequently, most previous person detection attacks have merely added an adversarial patch to the front of the T-shirt Hu et al. (2021); Duan et al. (2022); Tan et al. (2021) to avoid distortion problems. More recent approaches have incorporated 3D texture-based modifications Hu et al. (2023; 2022) to improve attack success rates from varying viewpoints. However, these approaches relied on static modeling and did not consider the influence of human poses. This highlights the critical challenge of creating novel attack techniques that effectively address the dynamic nature of human movements and pose variations.

(a) Adv-Yolo   (b) Adv-T-shirt   (c) NaturalPatch   (d) Adv-Texture   (e) Adv-Camou

(f) Ours (Front1)   (g) Ours (Front2)   (h) Ours (Turn left)   (i) Ours (Back)   (j) Ours (Turn right)

Figure 1: Visualization of different person detector attacks. We compare our attack with different person detection attacks, including Adv-Yolo (Thys et al., 2019), Adv-Tshirt (Xu et al., 2020), Natual-Patch (Hu et al., 2021), Adv-Texture (Hu et al., 2022) and Adv-Camou (Hu et al., 2023). Our attacks achieve higher ASR under diverse poses and viewpoints than previous attacks.

Adversarial Attacks based on NeRF   Neural Radiance Fields (NeRF) (Mildenhall et al., 2021) have demonstrated significant potential in rendering free-view images, making them attractive for physical attacks. Recent methodologies have explored the integration of NeRF in various adversarial contexts. ViewFool (Dong et al., 2022) leverages NeRF to find adversarial viewpoints that can generate adversarial images. It does not modify the object itself. VIAT (Ruan et al., 2023) follows ViewFool by learning a Gaussian mixture distribution of adversarial viewpoints to cover multiple local maxima of the loss landscape. Adv3D (Li et al., 2023a) utilizes Lift3D (Li et al., 2023b) to alter the texture latent of NeRF models, specifically targeting the textures of cars. However, it only considers rigid objects and is not physically realizable. TT3D (Huang et al., 2024) also considers the rigid objects. It modifies texture latent within grid-based NeRF architectures (Müller et al., 2022). Their method can change the textures but cannot be applied to non-rigid objects. In contrast to previous methods, our attack is the first specifically designed to target person detection. Unlike attacks focused on rigid objects, modeling a person is more challenging due to non-rigid deformations. `UV-Attack` is the first to utilize dynamic NeRF and UV mapping in non-rigid 3D adversarial attacks.

3 METHODOLOGY

In this section, we detail the proposed `UV-Attack`. `UV-Attack` adopts the dynamic NeRF to model humans as digital representations and perform the optimization in the latent space of the diffusion model to generate the adversarial textures. In the following, we first introduce the background knowledge of dynamic NeRF and then present our methodology.

3.1 PRELIMINARY: DYNAMIC NEURAL RADIANCE FIELDS

NeRF enables novel-view photorealistic synthesis by modeling 3D objects as a continuous volumetric radiance field allowing control over illuminations and materials (Mildenhall et al., 2021). It can be formulated as $F : (\mathbf{x}, \mathbf{d}) \to (\mathbf{c}, \sigma)$, where F is a MLP and takes the 3D coordinate $\mathbf{x} \in \mathbb{R}^3$ and the view direction $\mathbf{d} \in \mathbb{R}^3$ as input and outputs the corresponding color $\mathbf{c}$ and volume density σ. Then NeRF computes the pixel color $C(\mathbf{r})$ by accumulating all colors along a ray $\mathbf{r} = \mathbf{o} + t\mathbf{d}$ that emitting from the camera's original point o and passing the pixel with near and far bounds t_n and t_f,

$$C(\mathbf{r}) = \int_{t_n}^{t_f} T(t) \cdot \sigma(\mathbf{r}(t)) \cdot c(\mathbf{r}(t), \mathbf{d}) \, dt, \quad \text{where } T(t) = \exp\left(-\int_{t_n}^{t} \sigma(\mathbf{r}(s)) \, ds\right), \quad (1)$$

where σ is the volume density at any point s along the ray. $\mathbf{c}(\mathbf{r}(t), \mathbf{d})$ and $\sigma(\mathbf{r}(t))$ are the color and density for the 3D coordinate $\mathbf{r}(t)$ and view direction $\mathbf{d}$.

Figure 2: The pipeline of `UV-Attack`. `UV-Attack` first samples random pose parameters from a Gaussian Mixture Model. We then use the sampled pose, camera and light parameters to generate IUV maps and texture stacks. We employ a pre-trained stable diffusion model and modify the initial latent to generate adversarial patches. Finally, we modify the texture stacks using the adversarial patch and get the human image in RGB space. The solid lines below indicate the direction of gradient propagation, while the dashed lines above do not require gradients.

More recently, dynamic NeRF models have been proposed to accurately depict non-rigid objects like human beings (Geng et al., 2023; Weng et al., 2022). In response to the need for fast rendering and editable textures, we utilize UV-Volume (Chen et al., 2023c) to model the human body.

The core idea of UV-Volume is to render a NeRF model into UV maps rather than RGB images. UV maps contain UV coordinates (or texture coordinates), which are assigned pixel coordinates of a predefined texture image $\mathcal{E}$. The UV mapping process assigns pixels in the predefined texture image $\mathcal{E}$ to a rendered RGB image according to the UV coordinates. The UV-Volume input is the pose parameter θ, the camera position η and the light parameter τ. It firstly computes a pixel feature $\mathcal{F}(\mathbf{r})$ by a rendering equation similar to Eq. 1, where $\mathbf{r}$ is a camera ray. Then $\mathcal{F}(\mathbf{r})$ is fed into a UV decoder and is decoded as part assignment and UV coordinates through $[\hat{\mathcal{P}}(\mathbf{r}), \hat{\mathcal{U}}(\mathbf{r}), \hat{\mathcal{V}}(\mathbf{r})] = M_{uv}(\mathcal{F}(\mathbf{r}))$. $\hat{\mathcal{P}}$ is a part assignment corresponding to different human body parts.

UV-volume also incorporates a texture generator, denoted by G, to generate texture stack images $\mathcal{E}_k = G(\theta, \boldsymbol{k})$, where $\boldsymbol{k}$ is a one-hot vector that specifies the body part (e.g., arm, leg). A texture feature, $\mathbf{e}_k$, is then sampled from $\mathcal{E}_k$ based on the UV coordinate using the differentiable grid sampling: $\mathbf{e}_k(\mathbf{r}) = \mathcal{E}_k[\hat{\mathcal{U}}_k(\mathbf{r}), \hat{\mathcal{V}}_k(\mathbf{r})]$. Finally, the RGB color for the camera ray $\boldsymbol{r}$ is calculated as a weighted sum of individual body part colors $\hat{C}_k(\mathbf{r})$: $\hat{C}(\mathbf{r}) = \Sigma_{k=1}^{K} \hat{\mathcal{P}}_k(\mathbf{r}) \hat{C}_k(\mathbf{r})$. Each $\hat{C}_k(\mathbf{r})$ is determined by a MLP, M_c, which takes input the UV coordinates (with positional encoding), the sampled texture feature, and the encoded view direction:

$$\hat{C}_k(\mathbf{r}) = M_c\left(\gamma(\hat{\mathcal{U}}_k(\boldsymbol{r}), \hat{\mathcal{V}}_k(\mathbf{r})), \mathbf{e}_k(\mathbf{r}), k, \gamma(\boldsymbol{d})\right), \tag{2}$$

where K is the total number of human body parts, $\gamma(\cdot)$ is a positional encoding function and M_c is an MLP to map UV coordinates, sampled texture pixels and view directions into RGB images.

3.2 THE PIPELINE OF UV-ATTACK

We present the pipeline of `UV-Attack` in Figure 2. `UV-Attack` first samples poses, camera, and lighting parameters to generate IUV maps and texture stacks. Then it creates an adversarial patch using a pre-trained Stable Diffusion model and uses it to modify the texture stacks. These textures are then applied to the IUV maps, resulting in a final adversarial image.

GMM-based Pose Sampling   To generate unseen poses for the target person, we use a Gaussian Mixture Model (GMM) to fit a human pose distribution on target person images and an annotated

pose dataset MPII (Andriluka et al., 2014). Then we sample pose parameters from this Gaussian Mixture distribution as the UV-Volume model's input. Specifically, We first use the SPIN model (Kolotouros et al., 2019) to estimate the poses $\hat{\boldsymbol{\theta}}$ and shapes parameters $\hat{\boldsymbol{\beta}}$ from the target person's video and add auxiliary poses $\tilde{\boldsymbol{\theta}}$ from public annotated poses datasets like MPII (Andriluka et al., 2014). Then we parameterize the distribution $p([\hat{\boldsymbol{\theta}}, \tilde{\boldsymbol{\theta}}])$ by a mixture of K Gaussian components and take the transformation of random variable approach to ensure the support of $p([\hat{\boldsymbol{\theta}}, \tilde{\boldsymbol{\theta}}])$ is in scope of $[\boldsymbol{\theta}_{min}, \boldsymbol{\theta}_{max}]$ by

$$\boldsymbol{\theta} = \boldsymbol{a} \cdot \tanh(\boldsymbol{u}) + \boldsymbol{b}, \quad \text{where} \quad p(\boldsymbol{u} \mid \boldsymbol{\Psi}) = \sum_{k=1}^{K} \omega_k \mathcal{N}(\boldsymbol{u} \mid \boldsymbol{\mu}_k, \boldsymbol{\sigma}_k^2 \boldsymbol{I}), \tag{3}$$

where $\boldsymbol{a} = \frac{(\boldsymbol{\theta}_{\max} - \boldsymbol{\theta}_{\min})}{2}$, $\boldsymbol{b} = \frac{(\boldsymbol{\theta}_{\max} + \boldsymbol{\theta}_{\min})}{2}$, $\boldsymbol{\Psi} = \{\omega_k, \boldsymbol{\mu}_k, \boldsymbol{\sigma}_k\}_{k=1}^{K}$ are the parameters of the GMM with weight $\omega_k \in [0, 1]$ $\left(\sum_{k=1}^{K} \omega_k = 1\right)$. The $\boldsymbol{\mu}_k$ and $\boldsymbol{\sigma}_k$ are parameters of k-th Gaussian component.

Real-Time Dynamic Texture Modification To improve the speed of adversarial attacks, it's crucial to efficiently modify and render clothing on 3D human models. We slightly adjust the UV-Volume architecture to further improve the texture modification speed. Specifically. we firstly define linearly spaced vectors $\mathbf{u}, \mathbf{v} \in \text{linespace}(0, 1, N_t)$, where N_t is the texture's size. Then we create 2D grids using a mesh grid defined as $[\tilde{\mathcal{U}}, \tilde{\mathcal{V}}] = [\mathbf{1}_{N_t} \otimes \mathbf{u}, (\mathbf{1}_{N_t} \otimes \mathbf{v})^T]$, where is $\mathbf{1}_{N_t}$ is a column vector of ones with dimension N_t and $\otimes$ denotes the Kronecker product. Then we remove the viewing direction $\boldsymbol{d}$ from Eq.2 to generate the view-independent texture stacks Besides the texture stack $\tilde{C}$, we also generate IUV maps according to the pose, camera, and light parameters, which can be expressed $x_{\text{IUV}} = [\hat{\mathcal{P}}, \hat{\mathcal{U}}, \hat{\mathcal{V}}] = M_{uv}(\mathcal{F}_{\theta, \eta, \tau})$, where θ is the pose parameter and η, τ are the camera and light parameters.

During the process of image rendering for new actions, we randomly sample the camera views from different elevation and azimuth angles and different light positions and backgrounds. The rendered images can be expressed as

$$x = g(x_{\text{IUV}}(\theta, \tau), \text{TPS}(\tilde{C}, x_{adv})) \odot M + x_{\text{b}} \odot (1 - M), \tag{4}$$

where x_{adv} is an adversarial patch generated by the latent diffusion model, τ is the camera and light parameters and M a human mask that can be estimated by the accumulated transmittance $M = \exp\left(-\sum_{j=1}^{N_i - 1} \sigma(\mathbf{x}_j)\delta_j\right)$. We simply repeat the adversarial patch on the texture stacks, which have shown to be able to improve the attack robustness (Hu et al., 2022). Because of the texture stacks are disentangled, we can easily modify any part of the human body. Then we distort the texture stacks through Thin Plate Spline (TPS) (Hu et al., 2023) to simulate cloth distortions. Finally, we use the grid sampling function $g(\cdot, \cdot)$ to sample pixel colors from the modified texture stack according to the IUV map x_{IUV} and combine it with background image x_b.

Adversarial Patch Generation Diffusion models have been found to be able to enhance the transferability of adversarial examples (Xue et al., 2023; Lin et al., 2023; Chen et al., 2023b). However, previous work either modifying the intermediate latent (Chen et al., 2023a;b) or diffusing and denoising an initial image (Lin et al., 2023; Xue et al., 2023), which has limited noise levels, resulting in impractical for physical adversarial attacks. `UV-Attack` contaminates the initial, highly noisy latent variable z_T of a pre-trained stable diffusion model (Rombach et al., 2022) and remove classifier-free guidance. These approaches facilitate more substantial modifications and explore broader latent spaces and less familiar areas, resulting in significantly higher physical attack success rates while maintaining the transferability. However, due to the larger optimization space, relying solely on gradient-based algorithms may lead to local minima. To enhance optimization efficiency, we combined black-box and white-box algorithms. Initially, we employed the Particle Swarm Optimization (PSO) algorithm to find a suitable starting point. Subsequently, we utilized the Adam optimizer to fine-tune this point to further decrease the loss. To exclude the influence of stable diffusion prompts, we evaluated the average ASR by using different class labels except "person" in the COCO dataset as prompts.

The Expection over Pose Transformation Loss Suppose the victim detector D takes the rendered image x as input and outputs a set of bounding boxes $b_i^{(x)}$ with confidence $\text{Conf}_i^{(x)}$ and class label y,

we define the detection loss as $\mathcal{L}_{det} = \text{Conf}_{i^*}^{(x)}$, where $i^* = \arg\ \max_i \text{IoU}(\text{gt}^x, b_i^x)$. The adversarial loss $\mathcal{L}_{adv}$ can be expressed as the expectation over sampled pose parameters ($\boldsymbol{\theta}$), camera parameters ($\boldsymbol{\eta}$), light parameters ($\boldsymbol{\tau}$), and background images (x_b). The objective function is

$$\min_{z_T} \mathcal{L}_{adv} := \mathbb{E}_{\boldsymbol{\theta}\sim\Theta, \boldsymbol{\eta}\sim H, \boldsymbol{\tau}\sim T, x_b\sim B} \left[\mathcal{L}_{det}(x|z_T, \boldsymbol{\theta}, \boldsymbol{\eta}, \boldsymbol{\tau}, x_b) \right] \tag{5}$$

By minimizing $\mathcal{L}_{adv}$ with respect to z_T, we find a texture that makes the detector fail under a variety of realistic scenarios. Sampling over the camera and light parameters, including the camera and light positions and light intensity, can improve the attack success rate in real-world situations.

The final attack algorithm is shown in Algorithm 1.

Algorithm 1 The `UV-Attack`

Require: Target detector D, pretrained latent diffusion model ϕ, GMM parameters Θ, background images B, number of PSO iterations T_{PSO}, number of PSO swarms N_{PSO}, number of Adam iterations T_{Adam}, pretrained UV-Volume model M_{UV}, batchsize N_{batch}.

1: Initialize N_{PSO} particle swarms with random positions z_i and velocities v_i
2: **for** $t = 1, \ldots, T_{\text{PSO}}$ **do**
3:     Update velocities $v_i^{(t+1)} = \omega v_i^{(t)} + c_1 r_1 (p_i^{(t)} - z_i^{(t)}) + c_2 r_2 (g^{(t)} - z_i^{(t)})$
4:     Update positions $z_i^{(t+1)} = z_i^{(t)} + v_i^{(t+1)}$
5:     Evaluate fitness $(-\mathcal{L}_{adv})$ of particles and update $p_i^{(t)}$ and $g^{(t)}$
6: **end for**
7: Initialize z_T with the best position found by PSO: $z_T \leftarrow g^{(T_{\text{PSO}})}$
8: **for** $t = 1, \ldots, T_{\text{Adam}}$ **do**
9:     Generate x_{adv} through denoising $x_{adv} = Decoder(R_\phi(\ldots R_\phi(R_\phi(z_T, T), T-1)\ldots, 0))$.
10:     Sampling $\theta \sim \Theta, \boldsymbol{d} \sim D, \boldsymbol{\tau} \sim T, x_b \sim B$ with number N_{batch}
11:     Generate N_{batch} image through Eq. 4.
12:     Compute adversarial loss through Eq. 5.
13:     Update z_T using Adam optimizer
14: **end for**
15: **return** Adversarial patch x_{adv}

---

4 EXPERIMENTS

4.1 EXPERIMENTAL SETTINGS

Training Details. We evaluate the success rate of digital attacks on the ZJU-Mocap dataset (Peng et al., 2021). For the physical attack, we collected videos of five individuals and used SPIN and DensePose to extract SMPL parameters and pseudo-supervised IUV maps for training the UV-Volumes. The model training and attack implementation are conducted on a single Nvidia 3090 GPU. We utilize a pretrained stable-diffusion model finetuned on 256×256 images. The diffusion process was set to 10 steps. The Particle Swarm Optimization (PSO) ran for 30 epochs with 50 swarms, and the Adam optimizer ran for 300 epochs. We collected 100 different backgrounds from both indoor and outdoor scenarios. For each epoch, we randomly sampled 100 poses, camera and light positions, and backgrounds for training. The camera is sampled from $azim \in [-180°, 180°]$ and $elev \in [0°, 30°]$.

Victim Models and Evaluation Metrics. To evaluate the attack success rate transferability of our attack, we trained the adversarial textures on FastRCNN (Girshick, 2015) and YOLOv3 (Redmon & Farhadi, 2018) respectively, and tested the transferability on a variety of the person detectors, including MaskRCNNHe et al. (2018), Deformable DETR (Zhu et al., 2020), RetinaNet (Lin et al., 2018), SSD (Liu et al., 2016), FCOS(Tian et al., 2019) and the most recent YOLO variant, YOLOv8 (Jocher et al., 2023). To evaluate the effectiveness of our attack, we measure the attack success rate (ASR) in both the digital world and the physical world. Most previous attacks set the IoU threshold τ_{IOU} as 0.5, which overestimated the attack effectiveness. In this work, we test the ASR under different IoU thresholds from 0.01 to 0.5. To exclude the influence of stable diffusion prompts, we evaluated the average ASR by using all class labels except "person" in the COCO dataset as

Table 1: Comparison of different methods' ASR (%) on the multi-pose datasets using FastRCNN and YOLOv3. The confidence threshold τ_{conf} is set as 0.5.

Victim Models	FastRCNN				YOLOv3			
τ_{IoU}	IoU0.01	IoU0.1	IoU0.3	IoU0.5	IoU0.01	IoU0.1	IoU0.3	IoU0.5
AdvYolo	15.05	16.20	16.45	16.40	13.25	14.05	14.20	14.30
AdvTshirt	10.20	11.30	12.15	12.50	8.35	10.30	10.35	10.50
NatPatch	12.40	13.20	14.35	15.20	10.50	11.40	12.55	12.60
AdvTexture	1.50	6.75	10.05	17.90	1.40	8.40	14.50	18.10
AdvCamou	24.40	25.50	25.60	28.50	22.50	23.40	23.60	24.00
Diff2Conf	10.30	12.60	12.65	14.25	19.20	20.00	20.05	20.35
DiffPGD	12.40	12.70	12.80	13.40	15.10	17.50	17.80	19.40
LDM	24.50	25.40	25.45	25.50	26.40	27.50	28.30	28.45
Ours$_{video}$	82.50	82.50	84.30	85.60	80.25	82.10	83.40	84.20
Ours$_{GMM}$	**85.65**	**85.80**	**86.65**	**92.75**	**84.50**	**88.40**	**89.50**	**90.40**

prompts. This approach ensures that the ASR is not biased by specific prompts and provides a more generalized measure of the attack's effectiveness.

Baseline attacks. We compared our attack with different person detection attacks, including AdvYolo (Thys et al., 2019), AdvTshirt (Xu et al., 2020), AdvTexture (Hu et al., 2022), AdvCamou (Hu et al., 2023), and the latest diffusion-model-based attacks, including Diff2Conf (Lin et al., 2023) and DiffPGD (Xue et al., 2023). We also compared our method with a GAN-based attack, NatPatch (Hu et al., 2021). AdvTexture (Hu et al., 2022) and AdvCamou (Hu et al., 2023) are both texture-based attacks that can be directly compared. For AdvTshirt, Diff2Conf, and DiffPGD, which only add a single patch on the T-shirt, the attack performance drops significantly when the viewing angles change. Therefore, we tiled the patches produced by them onto the texture stacks for fair comparisons.

4.2 DIGITAL ATTACK RESULTS

Evaluation on the Unseen Pose Dataset (A) **Dataset and baseline settings.** To evaluate the ASR of different attacks under unseen pose scenarios, we randomly sample 1000 poses from the GMM and combine them with different backgrounds and camera and light conditions to construct an unseen pose dataset. Then we evaluate the average ASR on five different individuals from the ZJU-Mocap dataset, as shown in Figure 6. Because previous attacks did not consider the multi-pose scenarios, they cannot be directly evaluated. Therefore, we combine their methodologies with the UV-Volume model to generate images under different poses for test. For AdvCamou (Hu et al., 2023), we first train a Voronoi diagram using their methods and then apply it to the texture stacks under a *fixed* pose. Then we test the generated Voronoi diagram on the multi-pose dataset. For other patch-based attacks, we use a fixed pose and put the generated patch on the texture stacks for training, followed by testing on the multi-pose dataset. Additionally, we added two additional baselines. One is to use the latent diffusion model with fixed poses to train the adversarial textures, referred to as the LDM attack. The other is to sample frames from a multi-pose video and then extract the pose parameters for the UV-Volume, referred to as Ours$_{video}$. (B) **Results analysis**. We present the test ASRs under different IoU thresholds in Table 1. All attacks were trained and tested on the same detectors . It indicates that our attack significantly outperforms previous attacks under unseen pose scenarios. Additionally, our attack maintains consistently high ASRs as the IoU thresholds decrease, in contrast to some previous attacks like AdvTexture which significantly drops in performance. Experimental results demonstrate that our method can significantly improve attack resilience against pose variations. In addition, it is shown that sampling pose parameters from a GMM distribution rather than from video frames can improve the ASR. This is because we can synthesize unseen poses for training.

Transferability (A) We trained our attacks on FastRCNN and YOLOv3, respectively, and tested the transferability on various person detectors. Because AdvCamou is based on a static 3D model, we disable pose sampling in the training and test in this table for fair comparisons. As shown in Table 2, our attack trained on FastRCNN has high transferability on Deformable-DETR, MaskRCNN, and RetinaNet. It is also shown that previous diffusion-based attacks, Diff2Conf and DiffPGD, have very low ASRs in our attack settings, even on the white-box models. We think this is because only

Table 2: The white-box ASR (%) and transferability of different attacks. The IOU threshold is set as 0.1 and the confidence threshold is set as 0.5. Numbers with underline are white-box attacks. We **disable** pose sampling in the training and test process in this table for fair comparison.

Method	Victim Models							
	FRCNN	YOLOv3	DDETR	MRCNN	Retina	FCOS	SSD	YOLOv8
AdvTshirt	61.04	17.02	12.90	56.10	25.00	24.00	15.05	15.20
AdvTexture	22.54	10.01	9.05	15.30	8.00	15.60	8.24	6.50
AdvCamou	97.20	28.50	67.50	92.20	45.65	35.20	20.24	25.25
Diff2Conf	31.45	12.10	10.05	27.15	19.34	10.50	11.45	7.90
DiffPGD	35.37	16.24	13.40	29.50	16.18	12.43	14.29	10.50
Ours	**98.36**	**50.45**	**68.18**	**93.50**	**75.95**	**64.50**	**38.50**	**49.50**
AdvTshirt	11.03	75.00	15.44	8.20	18.32	15.40	10.05	16.50
AdvTexture	16.54	45.89	10.55	13.28	11.30	11.40	5.50	6.40
AdvCamou	**24.40**	93.18	16.38	22.57	25.40	22.66	25.40	18.30
Diff2Conf	15.45	42.10	10.20	18.40	15.20	6.40	12.47	10.02
DiffPGD	14.37	46.40	10.40	16.40	18.08	5.20	10.40	9.55
Ours	23.26	**97.21**	**48.03**	**31.60**	**35.80**	**37.40**	**39.25**	**58.55**

Figure 3: Physical attack success rates with different detectors and confidence thresholds. The attack is trained on FastRCNN model, and the IoU threshold is set as 0.5.

adding noise to an initial image and then denoising it can not fully explore the LDM's latent space and, therefore cannot find an optimum latent. In addition, our attack achieves high ASRs on the latest YOLOv8 detector (Jocher et al., 2023), which previous attacks did not perform very well.

4.3 PHYSICAL ATTACK RESULTS

To evaluate the physical ASR, we first capture videos from targets and then estimate the pose and camera parameters to train the UV-Volume. Compared with AdvCamou, which requires calibrated 3D meshes, our attack only needs a short video of the target, making it easier to conduct. We find that the trained textures are transferable to different people, thereby allowing us to fine-tune the latent z_T trained on the ZJU-Mocap datasets instead of training from scratch, which greatly reduces the training time. We set the finetuning epoch as 100 in the physical attacks. Then we print the textures on fabric materials and manufacture long sleeves and pants. As shown in Figure 1, our attack is robust to changes in pose, view, and distance. For quantitative analysis, we compute the ASR through $ASR = 1 - N_{\text{succeed}}/N_{\text{total}}$, where N_{succeed} and N_{total} represent the number of succeeded and total frames, respectively. We trained the texture on FastRCNN and tested the real-world ASRs on multiple detectors. The physical attack success rate with different detectors and confidence thresholds is shown in Figure 3. We achieved a high success rate on FastRCNN (0.82), MaskRCNN (0.78), and Deformable DETR (0.65) when τ_{conf} is 0.5 and is consistent when τ_{conf} changes, while RetinaNet, FCOS and YOLOv8 are relatively sensitive to τ_{conf}'s change. The ASR for SSD is relatively low, which can be attributed to their fundamentally different model architectures.

Figure 4: Visualization of adversarial textures and rendering results for different body parts.

Figure 5: Ablation study on tile/crop methods and the classifier-free guidance.

Table 3: Attack performance on different body parts.

Body Parts	UpperBody	UpperBody+Arms	UpperBody + Thighs	UpperBody+Arms+Thighs
RCNN	23.26	47.38	56.39	84.35
YOLOv3	41.16	64.67	66.93	87.68

4.4 ABLATION STUDY

The influence of modifying different body parts. Benefiting from the disentangled texture stacks, we can render arbitrary body parts, as shown in Figure 4. We evaluate the ASR of modifying different body parts and present these results in Table 3. As the coverage area of the adversarial textures increases, the attack success rate also progressively increases.

The influence of different settings. We tested the impact of different attack settings on the ASRs. Firstly, we crop from the generated textures rather than stitching them together and refer to this method as *cropping*. Additionally, we set the diffusion model with classifier-free guidance, which we denote as *guidance*. We plot these methods' ASR on the white-box FastRCNN and the black-box YOLOv3 as the epochs progress, as shown in Figure 5. We observe that although the diffusion model with classifier-free guidance can achieve high white-box ASR (95%), it reduces transferability on the YOLOv3. We think this reduction is due to the truncation effect, which normalizes the latent representations within the high-probability areas to improve image quality. This normalization restricts the generated images' noise levels and also reduces the transferability of untargeted attacks. Additionally, the cropping method does not achieve ASRs as high as those obtained with tiling functions. This is likely because the cropping function can degrade the adversarial effect due to limited resolution.

The influence of physical environment. To test the Attack Success Rate (ASR) under more complex real-world environments, we compared the effectiveness of our attack in both indoor and outdoor scenes. For indoor scenes, data were collected from three different locations: a classroom, a home, and an office. For outdoor scenes, three videos were captured at 10 am, 2 pm, and 6 pm. Videos were recorded from various distances (1-5 meters) and included different poses, with 100 frames extracted from each video. The results are presented in Table 4, demonstrating that our attacks are effective across different scenes. We used RCNN as both the training and victim model.

Table 4: Physical ASR in different scenes

Scene	Outdoor			Indoor		
	10am	2pm	6pm	Classroom	Home	Office
ASR	0.94	0.98	0.92	0.94	0.92	0.96

Figure 6: Compare with normal images and adversarial images in digital attacks.

The influence of different NeRF models. We compare the time needed to edit the clothing textures for different dynamic NeRF models (Weng et al., 2022; Geng et al., 2023; Shao et al., 2024). Our method, based on the UV-Volume, has the fastest speed that previous methods.

Table 5: Time required to edit clothing textures for different dynamic NeRF models

Method	Control4D	HumanNeRF	Fast-HumanNeRF	Ours
Render time for one image	~10h	~2h	~15min	<0.5s

5 CONCLUSION

We introduce `UV-Attack`, a novel physical adversarial attack leveraging dynamic NeRF-based UV mapping. Unlike previous methodologies that struggled with dynamic human poses, `UV-Attack` computes the expectation loss on the pose transformations, making our attack achieve high ASR to variable human poses and movements. The use of UV maps to directly edit textures without the need for gradient calculations of the NeRF model significantly enhances attack feasibility in real-world scenarios. Our experimental results show that `UV-Attack` outperforms the state-of-the-art method by large margins on unseen pose datasets, achieving high ASRs in diverse and challenging conditions. Ultimately, our attack not only advances the research of person detection attacks but also introduces a new methodology for real-world adversarial attacks on non-rigid 3D objects.

REFERENCES

Mykhaylo Andriluka, Leonid Pishchulin, Peter Gehler, and Bernt Schiele. 2d human pose estimation: New benchmark and state of the art analysis. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2014.

Jonathan T Barron, Ben Mildenhall, Matthew Tancik, Peter Hedman, Ricardo Martin-Brualla, and Pratul P Srinivasan. Mip-nerf: A multiscale representation for anti-aliasing neural radiance fields. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5855–5864, 2021.

Jianqi Chen, Hao Chen, Keyan Chen, Yilan Zhang, Zhengxia Zou, and Zhenwei Shi. Diffusion models for imperceptible and transferable adversarial attack. *arXiv preprint arXiv:2305.08192*, 2023a.

Xinquan Chen, Xitong Gao, Juanjuan Zhao, Kejiang Ye, and Cheng-Zhong Xu. Advdiffuser: Natural adversarial example synthesis with diffusion models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4562–4572, 2023b.

Yue Chen, Xuan Wang, Xingyu Chen, Qi Zhang, Xiaoyu Li, Yu Guo, Jue Wang, and Fei Wang. Uv volumes for real-time rendering of editable free-view human performance. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16621–16631, 2023c.

Yinpeng Dong, Shouwei Ruan, Hang Su, Caixin Kang, Xingxing Wei, and Jun Zhu. Viewfool: Evaluating the robustness of visual recognition to adversarial viewpoints. *Advances in Neural Information Processing Systems*, 35:36789–36803, 2022.

Yexin Duan, Jialin Chen, Xingyu Zhou, Junhua Zou, Zhengyun He, Jin Zhang, Wu Zhang, and Zhisong Pan. Learning coated adversarial camouflages for object detectors, 2022.

Chen Geng, Sida Peng, Zhen Xu, Hujun Bao, and Xiaowei Zhou. Learning neural volumetric representations of dynamic humans in minutes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8759–8770, 2023.

Ross Girshick. Fast r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 1440–1448, 2015.

Huihui Gong, Minjing Dong, Siqi Ma, Seyit Camtepe, Surya Nepal, and Chang Xu. Stealthy physical masked face recognition attack via adversarial style optimization. *IEEE Transactions on Multimedia*, 2023.

Rıza Alp Güler, Natalia Neverova, and Iasonas Kokkinos. Densepose: Dense human pose estimation in the wild. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7297–7306, 2018.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn, 2018.

Yu-Chih-Tuan Hu, Bo-Han Kung, Daniel Stanley Tan, Jun-Cheng Chen, Kai-Lung Hua, and Wen-Huang Cheng. Naturalistic physical adversarial patch for object detectors. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 7848–7857, 2021.

Zhanhao Hu, Siyuan Huang, Xiaopei Zhu, Fuchun Sun, Bo Zhang, and Xiaolin Hu. Adversarial texture for fooling person detectors in the physical world. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 13307–13316, 2022.

Zhanhao Hu, Wenda Chu, Xiaopei Zhu, Hui Zhang, Bo Zhang, and Xiaolin Hu. Physically realizable natural-looking clothing textures evade person detectors via 3d modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16975–16984, 2023.

Hao Huang, Ziyan Chen, Huanran Chen, Yongtao Wang, and Kevin Zhang. T-sea: Transfer-based self-ensemble attack on object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 20514–20523, 2023.

Yao Huang, Yinpeng Dong, Shouwei Ruan, Xiao Yang, Hang Su, and Xingxing Wei. Towards transferable targeted 3d adversarial attack in the physical world. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

Glenn Jocher, Ayush Chaurasia, and Jing Qiu. Ultralytics YOLO. `https://github.com/ultralytics/ultralytics`, 2023.

Nikos Kolotouros, Georgios Pavlakos, Michael J Black, and Kostas Daniilidis. Learning to reconstruct 3d human pose and shape via model-fitting in the loop. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 2252–2261, 2019.

Leheng Li, Qing Lian, and Ying-Cong Chen. Adv3d: Generating 3d adversarial examples in driving scenarios with nerf. *arXiv preprint arXiv:2309.01351*, 2023a.

Leheng Li, Qing Lian, Luozhou Wang, Ningning Ma, and Ying-Cong Chen. Lift3d: Synthesize 3d training data by lifting 2d gan to 3d generative radiance field. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 332–341, 2023b.

Yanjie Li, Yiquan Li, Xuelong Dai, Songtao Guo, and Bin Xiao. Physical-world optical adversarial attacks on 3d face recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24699–24708, 2023c.

Shuo-Yen Lin, Ernie Chu, Che-Hsien Lin, Jun-Cheng Chen, and Jia-Ching Wang. Diffusion to confusion: Naturalistic adversarial patch generation based on diffusion model for object detector. *arXiv preprint arXiv:2307.08076*, 2023.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection, 2018.

Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11–14, 2016, Proceedings, Part I 14*, pp. 21–37. Springer, 2016.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. *Communications of the ACM*, 65(1):99–106, 2021.

Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. *ACM transactions on graphics (TOG)*, 41(4): 1–15, 2022.

Sida Peng, Yuanqing Zhang, Yinghao Xu, Qianqian Wang, Qing Shuai, Hujun Bao, and Xiaowei Zhou. Neural body: Implicit neural representations with structured latent codes for novel view synthesis of dynamic humans. In *CVPR*, 2021.

Nikhila Ravi, Jeremy Reizenstein, David Novotny, Taylor Gordon, Wan-Yen Lo, Justin Johnson, and Georgia Gkioxari. Accelerating 3d deep learning with pytorch3d. *arXiv preprint arXiv:2007.08501*, 2020.

Joseph Redmon and Ali Farhadi. Yolov3: An incremental improvement. *arXiv preprint arXiv:1804.02767*, 2018.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10684–10695, 2022.

Shouwei Ruan, Yinpeng Dong, Hang Su, Jianteng Peng, Ning Chen, and Xingxing Wei. Towards viewpoint-invariant visual recognition via adversarial training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4709–4719, 2023.

Ruizhi Shao, Jingxiang Sun, Cheng Peng, Zerong Zheng, Boyao Zhou, Hongwen Zhang, and Yebin Liu. Control4d: Efficient 4d portrait editing with text. 2024.

Naufal Suryanto, Yongsu Kim, Hyoeun Kang, Harashta Tatimma Larasati, Youngyeo Yun, Thi-Thu-Huong Le, Hunmin Yang, Se-Yoon Oh, and Howon Kim. Dta: Physical camouflage attacks using differentiable transformation network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15305–15314, 2022.

Jia Tan, Nan Ji, Haidong Xie, and Xueshuang Xiang. Legitimate adversarial patches: Evading human eyes and detection models in the physical world. In *Proceedings of the 29th ACM international conference on multimedia*, pp. 5307–5315, 2021.

Simen Thys, Wiebe Van Ranst, and Toon Goedemé. Fooling automated surveillance cameras: adversarial patches to attack person detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, pp. 0–0, 2019.

Zhi Tian, Chunhua Shen, Hao Chen, and Tong He. Fcos: Fully convolutional one-stage object detection, 2019.

Donghua Wang, Tingsong Jiang, Jialiang Sun, Weien Zhou, Zhiqiang Gong, Xiaoya Zhang, Wen Yao, and Xiaoqian Chen. Fca: Learning a 3d full-coverage vehicle camouflage for multi-view physical adversarial attack. In *Proceedings of the AAAI conference on artificial intelligence*, volume 36, pp. 2414–2422, 2022.

Donghua Wang, Wen Yao, Tingsong Jiang, Chao Li, and Xiaoqian Chen. Rfla: A stealthy reflected light adversarial attack in the physical world. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4455–4465, 2023.

Jiakai Wang, Aishan Liu, Zixin Yin, Shunchang Liu, Shiyu Tang, and Xianglong Liu. Dual attention suppression attack: Generate adversarial camouflage in physical world. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8565–8574, 2021a.

Yajie Wang, Haoran Lv, Xiaohui Kuang, Gang Zhao, Yu-an Tan, Quanxin Zhang, and Jingjing Hu. Towards a physical-world adversarial patch for blinding object detection models. *Information Sciences*, 556:459–471, 2021b.

Chung-Yi Weng, Brian Curless, Pratul P Srinivasan, Jonathan T Barron, and Ira Kemelmacher-Shlizerman. Humannerf: Free-viewpoint rendering of moving people from monocular video. In *Proceedings of the IEEE/CVF conference on computer vision and pattern Recognition*, pp. 16210–16220, 2022.

Kaidi Xu, Gaoyuan Zhang, Sijia Liu, Quanfu Fan, Mengshu Sun, Hongge Chen, Pin-Yu Chen, Yanzhi Wang, and Xue Lin. Adversarial t-shirt! evading person detectors in a physical world. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part V 16*, pp. 665–681. Springer, 2020.

Haotian Xue, Alexandre Araujo, Bin Hu, and Yongxin Chen. Diffusion-based adversarial sample generation for improved stealthiness and controllability. *Advances in Neural Information Processing Systems*, 36, 2023.

Xiao Yang, Chang Liu, Longlong Xu, Yikai Wang, Yinpeng Dong, Ning Chen, Hang Su, and Jun Zhu. Towards effective adversarial textured 3d meshes on physical face recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4119–4128, 2023.

Yu Zhang, Zhiqiang Gong, Yichuang Zhang, Kangcheng Bin, Yongqian Li, Jiahao Qi, Hao Wen, and Ping Zhong. Boosting transferability of physical attack against detectors by redistributing separable attention. *Pattern Recognition*, 138:109435, 2023.

Yue Zhao, Hong Zhu, Ruigang Liang, Qintao Shen, Shengzhi Zhang, and Kai Chen. Seeing isn't believing: Towards more robust adversarial attack against real world object detectors. In *Proceedings of the 2019 ACM SIGSAC conference on computer and communications security*, pp. 1989–2004, 2019.

Yiqi Zhong, Xianming Liu, Deming Zhai, Junjun Jiang, and Xiangyang Ji. Shadows can be dangerous: Stealthy and effective physical-world adversarial attack by natural phenomenon. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15345–15354, 2022.

Xizhou Zhu, Weijie Su, Lewei Lu, Bin Li, Xiaogang Wang, and Jifeng Dai. Deformable detr: Deformable transformers for end-to-end object detection. *arXiv preprint arXiv:2010.04159*, 2020.