Neural Conservation Laws:
A Divergence-Free Perspective

Abstract

We investigate the parameterization of deep neural networks that are by design divergence-free. To motivate the importance of divergence-free models, we observe that the continuity equation, a fundamental conservation law, can be characterized through a divergence-free vector field. We hence propose an approach to building divergence-free neural networks through the concept of differential forms, and with the aid of automatic differentiation, realize two practical constructions with differing trade offs. Furthermore, we show these models are universal and can be used to represent any divergence-free vector field if given sufficient capacity. As a result, we can parameterize density and vector fields that always satisfy the continuity equation simply by design, foregoing the need for expensive numerical simulation. We experimentally validate our approaches on neural network-based solutions to fluid equations and on learning dynamical optimal transport maps.

1 Introduction

Modern successes in deep learning are often attributed to the expressiveness of black-box neural networks. These models are known to be universal function approximators [Hornik et al., 1989] – but this flexibility comes at a cost. In contrast to other parametric function approximators such as Finite Elements [Schroeder and Lube, 2017], it is hard to design networks that have *baked-in* constraints at a structural level. Existing approaches often resort to penalty methods for constraints—but these increase the cost of training and can produce inaccuracies in downstream applications when the constraints are not perfectly satisfied. Theoretical analysis of soft-constrained models also becomes more difficult, as constraints cannot be assumed to be exactly satisfied. On the other hand, enforcing hard constraints on the architecture can be difficult, and even once enforced, it is often unclear whether the model remains sufficiently expressive within the constrained function class.

In this work, we discuss an approach to directly bake in two constraints into deep neural networks: (i) having a divergence of zero, and (ii) satisfying the continuity equation. One of our key insights is that the former directly leads into the latter, so the first portion of the paper focuses on divergence-free vector fields. These represent a special class of vector fields which have widespread use in the physical sciences. In computational fluid dynamics, divergence-free vector fields are often used to model incompressible fluid interactions formalized by the Euler or Navier-Stokes equations. In $\mathbb{R}^3$ we know that the curl of a vector field has a divergence of zero, which has seen many uses in graphics simulations (*e.g.* Eisenberger et al. [2018]). Lurking behind this fact is the generalization of divergence and curl through differential forms [Cartan, 1899], and the powerful identity $d^2 = 0$. We first explore this generalization, then discuss two constructions derived from it for parmaterizing divergence-free vector fields. While this approach has been partially discussed previously [Barbarosie, 2011, Kelliher, 2021], it is not extensively known and has not been validated in the machine learning community.

Figure 1: Divergence-free vector fields $v : \mathbb{R}^d \to \mathbb{R}^d$ can be constructed from an antisymmetric matrix field $A : \mathbb{R}^d \to \mathbb{R}^{d \times d}$ or an arbitrary vector field $b : \mathbb{R}^d \to \mathbb{R}^d$. A_1 and A_2 are the first and second rows of A. Color denotes divergence.

Concretely, we derive two approaches—visualized in Figure 1—to transform sufficiently smooth neural networks into divergence-free neural networks, which are made efficient by automatic differentiation and recent advances in practical composable transformations [Bradbury et al., 2018]. Furthermore, we show that our approaches can theoretically represent any divergence-free vector field.

We combine these new modeling tools with a novel observation that solutions of the continuity equation—a partial differential equation describing the relation between a flow and its transformed density—can be characterized jointly as a divergence-free vector field. As a result, we can parameterize neural networks that, by design, always satisfy the continuity equation, which we coin *Neural Conservation Laws*. While prior works either resorted to penalizing errors [Raissi et al., 2019] or numerically simulating the density given a flow [Chen et al., 2018], baking this directly into the model as a constraint allows us to forego extra penalty terms and expensive numerical simulations.

2 Constructing divergence-free vector fields

We will use the notation of *differential forms* in $\mathbb{R}^n$ for deriving the divergence-free and universality properties of our vector field constructions. We provide a concise overview of differential forms in Appendix A. For a more extensive introduction see *e.g.*, Do Carmo [1998], Morita [2001]. Without this formalism, it is difficult to show either of these two properties; however, readers who wish to skip the derivations can jump to the matrix formulations in equation 4 and equation 7.

Let us denote $\mathcal{A}^k(\mathbb{R}^n)$ as the space of differential k-forms, $d : \mathcal{A}^k(\mathbb{R}^n) \to \mathcal{A}^{k+1}(\mathbb{R}^n)$ as the exterior derivative, and $\star : \mathcal{A}^k(\mathbb{R}^n) \to \mathcal{A}^{n-k}(\mathbb{R}^n)$ as the hodge star operator that maps each k-form to an $(n\text{-}k)$-form. Then we can express the divergence $\text{div}(v)$ as the composition $d \star v$.

To parameterize a divergence-free vector field $v : \mathbb{R}^n \to \mathbb{R}^n$, we note that from the properties of differential forms, taking an arbitrary $(n\text{-}2)$-form $\mu \in \mathcal{A}^{n-2}(\mathbb{R}^n)$ we have that

$$0 = d^2\mu = d(d\mu) \tag{1}$$

and therefore the vector field (1-form) v defined via $\star v = d\mu$ is divergence free. Applying the hodge star to both sides we get that $v = (-1)^{n-1} \star d\mu$ is divergence-free. The same is true without the constant $(-1)^{n-1}$, so it suffices to take

$$v = \star d\mu. \tag{2}$$

We write the parameterization $v = \star d\mu$ explicitly. Since a basis for $\mathcal{A}^{n-2}(\mathbb{R}^n)$ can be chosen to be $\star(dx_i \wedge dx_j)$ for all $i < j$ we can write $\mu = \sum_{i<j} \mu_{ij} \star (dx_i \wedge dx_j)$. Now a direct calculation shows that up to a constant sign

$$\star d\mu = \sum_{i=1}^{n} \left[\sum_{j>i} \frac{\partial \mu_{ij}}{\partial x_j} - \sum_{j<i} \frac{\partial \mu_{ji}}{\partial x_j} \right] dx_i. \tag{3}$$

This formula leads to a simple matrix formulation: If we let $A : \mathbb{R}^n \to \mathbb{R}^{n \times n}$ be the anti-symmetric matrix-valued function where $A_{ij} = \mu_{ij}$ for $i > j$ and $A_{ij} = -\mu_{ji}$ then the divergence free vector field $v = \star d\mu$ can be written as taking row-wise divergence of A, *i.e.*,

$$v = \begin{pmatrix} \mathrm{div}(A_1) \\ \vdots \\ \mathrm{div}(A_n) \end{pmatrix}. \tag{4}$$

However, this requires parameterizing $O(n^2)$ functions. A more compact representation, which starts from a vector field, can also be derived. The idea behind this second construction is to model μ instead as $\mu = \delta\nu$, where $\nu \in \mathcal{A}^{n-1}(\mathbb{R}^n)$. Putting this together with equation 2 we get that

$$v = \star d\delta\nu \tag{5}$$

is a divergence free vector field. To provide equation 5 in matrix formulation we first write $\nu \in \mathcal{A}^{n-1}(\mathbb{R}^n)$ in the (n-1)-form basis, *i.e.* $\nu = \sum_{i=1}^{n} \nu_i \star dx_i$. Then a direct calculation provides up to a constant sign

$$\delta\nu = \sum_{i<j} \left[\frac{\partial \nu_i}{\partial x_j} - \frac{\partial \nu_j}{\partial x_i} \right] \star (dx_i \wedge dx_j). \tag{6}$$

This means that, given an arbitrary vector field $b : \mathbb{R}^n \to \mathbb{R}^n$, and denoting J_b as the Jacobian of b, we can construct A as

$$A = J_b - J_b^T. \tag{7}$$

By using automatic differentiation and recent advances in composable function transforms, we can compute this expression and then its row-wise divergence (equation 4).

To summarize, we have two constructions for divergence free vector fields v:

Matrix-field: (equations 2 and 4) v is represented using an anti-symmetric matrix field A.

Vector-field: (equations 5 and 4+7) v is represented using a vector field b.

As we show in the next section, these two approaches are maximally expressive (*i.e.* universal), meaning they can approximate arbitrary smooth divergence-free vector fields. However, empirically these two constructions can exhibit different practical trade-offs. The matrix-field construction has a computational advantage as it requires one less Jacobian computation, though it requires more components— $O(n)$ vs. $O(n^2)$—to represent than the vector-field construction. This generally isn't a concern as all components can be computed in parallel. However, the vector-field construction can make it easy to bake in additional constraints; an example of this is discussed in Section 7.1, where a non-negativity constraint is imposed for modeling continuous-time probability density functions. In Figure 2 we show wallclock times for evaluating the divergence-free vector field based on our two constructions. Both exhibit quadratic scaling with the number of dimensions due to the row-wise divergence in equation 4, while the vector-field construction has an extra Jacobian computation.

Figure 2: Compute times.

2.1 Universality

Both the matrix-field and vector-field representations are universal, *i.e.* they can model arbitrary divergence-free vector fields. The main tool in the proof is the Hodge decomposition theorem [Morita, 2001, Berger, 2003]. For simplicity we will be working on a periodic piece of $\mathbb{R}^n$, namely the torus $\mathbb{T} = [-M, M]^n / \sim$ where $\sim$ means identifying opposite edges of the n-dimensional cube, and $M > 0$ is arbitrary. Vector fields with compact support can always be encapsulated in $\mathbb{T}$ with $M > 0$ sufficiently large. Since $\mathbb{T}$ is locally identical to $\mathbb{R}^n$, all the previous definitions and constructions hold.

Theorem 2.1. *The matrix and vector-field representations are universal in* $\mathbb{T}$*, possibly only missing a constant vector field.*

A formal proof of this result is in Appendix B.

3 Neural Conservation Laws

We now discuss a key aspect of our work, which is parameterizing solutions of scalar conservation laws. Conservation laws are a focal point of mathematical physics and have seen applications in machine learning, with the most well known examples being conserved scalar quantities often referred to as density, energy, or mass. Formally, a conservation law can be expressed as a first-order PDE written in divergence form as $\frac{\partial \rho}{\partial t} + \text{div}(j) = 0$, where j is known as the flux, and the div is taken over spatial variables. In the case of the continuity equation, there is a velocity field u which describes the flow and the flux is equal to the density times the velocity field:

$$\frac{\partial \rho}{\partial t} + \text{div}(\rho u) = 0 \tag{8}$$

where $\rho : \mathbb{R}^n \to \mathbb{R}$ and $u : \mathbb{R}^n \to \mathbb{R}^n$. One can then interpret the equation to mean that u transports $\rho(0, \cdot)$ to $\rho(t, \cdot)$ *continuously*—without teleporting, creating or destroying mass. Such an interpretation plays a key role in physics simulations as well as the dynamic formulation of optimal transport [Benamou and Brenier, 2000]. In machine learning, the continuity equation appears when using continuous normalizing flows [Chen et al., 2018]—which also have been used to approximate solutions to dynamical optimal transport. [Finlay et al., 2020, Tong et al., 2020, Onken et al., 2021] These, however, only model the velocity u and rely on numerical simulation to solve for the density ρ, which can be costly and time-consuming.

Instead, we observe that equation 8 can be expressed as a divergence-free field by augmenting the spatial dimensions with the time variable, resulting in a vector field v that as input (t, x) and outputs $(\rho, \rho u)$. Then equation 8 is equivalent to

$$\text{div}(v) = \text{div}\begin{pmatrix} \rho \\ \rho u \end{pmatrix} = 0 \tag{9}$$

where the divergence operator is now taken with respect to the joint system (t, x), *i.e.* $\frac{\partial}{\partial t} + \sum_{i=1}^n \frac{\partial}{\partial x_i}$. We thus propose modeling solutions of conservation laws by parameterizing the divergence-free vector field v. This allows us to enforce the continuity equation at an architecture level. Specifically, we parameterize a divergence-free vector field v and set $v_1 = \rho$ and $v_{2:n+1} = \rho u$, allowing us to recover the vector field as $u = \frac{v_{2:n+1}}{\rho}$ assuming $\rho \neq 0$. This allows us to forego computationally expensive procedures for approximating or simulating ρ given the flow.

4 Related Works

Deep learning   Existing approaches to enforcing constraints in deep neural networks can induce constraints on the derivatives, such as convexity [Amos et al., 2017] or Lipschitz continuity [Miyato et al., 2018]. More complicated formulations involve solving numerical problems such as using solutions of convex optimization problems [Amos and Kolter, 2017], solutions of fixed-points iterations [Bai et al., 2019], and solutions of ordinary differential equations [Chen et al., 2018]. These models can help provide more efficient approaches or alternative algorithms for handling downstream applications such as constructing flexible density models [Chen et al., 2019, Lu et al., 2021] or approximating optimal transport paths [Tong et al., 2020, Makkuva et al., 2020, Onken et al., 2021]. However, in many cases, there is a need to solve a numerical problem in which the solution may only be approximated up to some numerical accuracy; for instance, the need to compute the density flowing through a vector field under the continuity equation [Chen et al., 2018].

Applications of differential forms   Differential forms and more generally, differential geometry, have been previously applied in manifold learning—see *e.g.* Arvanitidis et al. [2021] and Bronstein et al. [2017] for an in-depth overview. Most of the applications thus far have been restricted to 2 or 3 dimensions—either using identities like $\text{div} \circ \text{curl} = 0$ in 3D for fluid simulations [Rao et al., 2020], or for learning geometric invariances in 2D images or 3D space [Gerken et al., 2021, Li et al., 2021].

5 Neural approximations to PDE solutions

As a demonstration of our method, we apply it to neural-based PDE simulations of fluid dynamics. First, we apply it to a problem consisting of modelling idealized fluid flow on the flat Torus, then, to

156 showcase the ability to handle boundaries, another in the open unit ball $\mathbb{B} \subseteq \mathbb{R}^3$. While these are toy
157 examples, they demonstrate the value of our method in comparison to existing approaches—namely
158 that we can exactly satisfy the continuity equation and preserve exact mass.

The Euler equations of incompressible flow The incompressible Euler equations [Feynman et al.,
160 1989] form an idealized model of inviscid fluid flow, governed by the system of partial differential
161 equations[1]

$$\frac{\partial \rho}{\partial t} + \operatorname{div}(\rho u) = 0, \qquad \frac{\partial u}{\partial t} + \nabla_u u = \frac{\nabla p}{\rho}, \qquad \operatorname{div}(u) = 0 \qquad (10)$$

162 in three unknowns: the fluid velocity $u(t, x) \in \mathbb{R}^3$, the pressure $p(t, x)$, and the fluid density $\rho(t, x)$.
163 While the fluid velocity and density are usually given at $t = 0$, the initial pressure is not required.
164 Typically, on a bounded domain $\Omega \subseteq \mathbb{R}^n$, these are supplemented by the *free-slip* boundary condition
165 and initial conditions

$$u \cdot n = 0 \text{ on } \partial\Omega \qquad u(0, x) = u_0 \text{ and } \rho(0, x) = \rho_0 \qquad \text{on } \Omega \qquad (11)$$

166 The density ρ plays a critical role since in addition to being a conserved quantity, it influences the
167 dynamics of the fluid evolution over time. In numerical simulations, satisfying the continuity equation
168 as closely as possible is desirable since equations in equation 10 are coupled. Error in the density
169 feeds into error in the velocity and then back into the density over time. In the finite element literature,
170 a great deal of effort has been put towards developing conservative schemes that preserve mass (or
171 energy in the more general compressible case)—see Guermond and Quartapelle [2000] and Almgren
172 et al. [1998] for an overview. But since the application of physics informed neural networks (PINNs)
173 to fluid problems is much newer, conservative constraints have only been incorporated as penalty
174 terms into the loss [Mao et al., 2020, Jin et al., 2021].

5.1 Physics informed neural networks

176 Physics Informed Neural Networks (PINNs; Raissi et al. [2019, 2017]) have recently received renewed
177 attention as an application of deep neural networks. While using neural networks as approximate
178 solutions to PDE had been explored before Lagaris et al. [1998], modern advances in automatic
179 differentiation algorithms have made the application to much more complex problems feasible [Raissi
180 et al., 2019]. The "physics" in the name is derived from the incorporation of *physical* terms into the
181 loss function, which consist of adding the squared residual norm of a PDE. For example, to train a
182 neural network $\phi = [\rho, p, u]$ to satisfy the Euler equations, the standard choice of loss to fit to is

$$L_F = \left\| u_t + \nabla_u u + \frac{\nabla p}{\rho} \right\|_\Omega^2 \quad L_{\text{div}} = \|\operatorname{div}(u)\|_\Omega \quad L_I = \|u(0, \cdot) - u_0(\cdot)\|_\Omega^2 + \|\rho(0, \cdot) - \rho_0(\cdot)\|_\Omega$$

$$L_{\text{Cont}} = \left\| \frac{\partial \rho}{\partial t} + \operatorname{div}(\rho u) \right\|_\Omega^2 \qquad L_G = \|u \cdot n\|_{\partial\Omega}^2 \qquad L_{\text{total}} = \gamma \cdot [L_F, L_I, L_{\text{div}}, L_{\text{Cont}}, L_G]$$

183 where $\gamma = (\gamma_F, \gamma_I, \gamma_{\text{div}}\gamma_{Cont}, \gamma_G)$ denotes suitable coefficients (hyperparameter). The loss term L_G
184 ensures fluid does not pass through boundaries, when they are present. Similar approaches were taken
185 in [Mao et al., 2020] and [Jagtap et al., 2020] for related equations. While schemes of this nature are
186 very easy to implement, they have the drawback that since PDE terms are only penalized and not
187 strictly enforced, one cannot make guarantees as to the properties of the solution.

188 To showcase the ability of our method to model conservation laws, we will parameterize the density
189 and vector field as $v = [\rho, \rho u]$, as detailed in Section 3. This means we can omit the term L_{Cont} as
190 described in Section 5.1 from the training loss. The divergence penalty, L_{div} remains when modeling
191 incompressible fluids, since u is not necessarily itself divergence-free. In order to stablize training,
192 we can modify the loss terms L_F, L_G, L_I to avoid division by ρ. This is detailed in Appendix B.2.

5.2 Incompressible variable density inside the 3D unit ball

194 We first construct a simple unit within a bounded domain, specifically, we will consider the Euler
195 equations inside $B(0, 1) \subseteq \mathbb{R}^3$, with the initial conditions

$$\rho(0, x) = 3/2 - \|x\|^2 \qquad v(0, x) = (-2, x_0 - 1, 1/2) \qquad (12)$$

---

[1]The convective derivative appearing in equation 10, $\nabla_u u(x) = \lim_{h \to 0} \frac{u(x + hu(x)) - u(x)}{h} = [Du](u)$ is
also often written as $(\nabla \cdot u)u$.

$t = 0.00 \qquad t = 0.25 \qquad t = 0.50 \qquad\qquad t = 0.00 \qquad t = 0.25 \qquad t = 0.50$

(a) Incompressible baseline (b) Neural Conservation Law (Ours)

Figure 3: Being able to exactly satisfy the continuity equation allows us to perform much better than only satisfying the incompressible (divergence-free) condition of the vector field, even though both approaches obtain very small loss values. 2D slices of the learned solution of u and ρ are shown.

As a baseline, we compare against a parameterization that uses the divergence-free vector field only for the incompressible constraint. This is equivalent to the curl approach described in Rao et al. [2020]; another neural network is used to parameterize ρ. In contrast, our generalized formulation of divergence-free fields allow us to model the continuity equation is this case as it requires four dimensional inputs. We parameterize our method using $v = [\rho, \rho u]$, as detailed in Section 3, with the vector-field approach Section 2.

The results for training both networks in the described manner are shown in Figure 3. Surprisingly, even though both architectures achieve similar training loss after a comparable number of iterations (see Appendix C), the curl approach fails to advect the density accurately, whereas our conservation approach evolves the density as it should given the initial conditions.

5.3 Incompressible variable density flow on $\mathbb{T}^2$

As a more involved experiment, we model the Euler equations on the flat 2-Torus $\mathbb{T}^2$. This was parameterized as a multilayer perceptron pre-composed with the periodic embedding $\iota : [0,1]^2 \to \mathbb{T}^2$

$$\iota(x,y) = [\cos(2\pi x), \sin(2\pi x), \cos(2\pi y), \sin(2\pi y)]$$

The continuity equation is enforced exactly, using the method detailed in Section 3, so the L_{Cont} term is omitted from L_{total}. The initial velocity and density are

$$\rho_0(x,y) = (z_1 + z_3)^2 + 1 \qquad v_0(x,y) = [e^{z_3}, e^{z_1}/2]$$

where $z = \theta(x, y, 1)$. Here we used the matrix-field parameterization as referred to in Section 2, as it is empirically more flexible in low dimensions. We also include the harmonic component from Hodge decomposition, which is just a constant vector field, to ensure we have full universality. Full methodology for the experiment is detailed in Appendix C. The results of evolving the flow for time $t \in [0, 1/3]$ are shown in Figure 4, as well as a comparison with a reference finite element solution generated by the conservative splitting method from [Guermond and Quartapelle, 2000]. In general, our model fits the initial conditions well and results in fluid-like movement of the density, however small approximation errors can accumulate from simulating over a longer time horizon. To highlight this, we also plotted the best result we were able to achieve with a standard PINN. Although the PINN made progress minimizing the loss, was unable to properly model the dynamics of the fluid evolution. While this failure can likely be corrected by tuning the γ constant (see Section 5.1), we were unable to find a combination that fit the equation correctly. By contrast, our model worked with the first configuration we tried.

6 Learning the Hodge decomposition

With our divergence-free neural network, we can also learn the Hodge decomposition of a vector field itself. Informally, the Hodge decomposition states that any vector field can be expressed as

(a) Learned density function

(b) Convergence of training loss

(c) Comparison to FEM solution

Figure 4: While both PINN and NCL models minimize the training loss effectively and fit the initial conditions, the PINN fails to learn the dynamics of the advected density. When compared to a gold standard FEM solution, our NCL model exhibits nice linear convergence to the solution.

the combination of a gradient field (*i.e.* gradient of a scalar function) and a divergence-free field. To motivate, there are many scenarios where the neural network should be a gradient field at the optimum, such as score matching [Song and Ermon, 2019], iterative denoising [Hurault et al., 2022], amortized optimization [Xue et al., 2020], and meta-learned optimization [Andrychowicz et al., 2016]. Even though the target is a gradient field, many works have reported that it is easier to work with unconstrained vector field. Learning the Hodge decomposition can then correspond to removing any extra divergence-free, *i.e.* rotational, components of the vector field.

For this experiment, we construct a synthetic scenario where we have access to the ground truth Hodge decomposition, in order to validate the accuracy of our method. As such, we construct the target field $\hat{v}$ as

$$\hat{v} = \nabla w + \eta \tag{13}$$

where η is a fixed divergence-free neural network, and w is a fixed scalar network. We use the same embedding from Section 5.3, but extended to $\mathbb{T}^n$, for $n \in \{25, 50, 100\}$. We then parameterize another divergence-free model v_θ which has a different architecture than the target η. We propose using the following objective for training:

$$\ell(\theta) = \|D(\hat{v} - v_\theta) - [D(\hat{v} - v_\theta)]^T\|_F. \tag{14}$$

In the notation of differential forms, this corresponds to $\|\delta(\hat{v} - v_\theta)\|_F$, which when zero implies $v_\theta = \hat{v} + \delta\mu$, where μ is an arbitrary n-form. However, since v_θ is divergence free, it must hold $\delta\mu = -\nabla w$, *i.e.* the left-over portion of $\hat{v} - v_\theta$ is a gradient field. This follows because the components of the Hodge decomposition are orthogonal [Do Carmo, 1998].

For evaluation, we plot the squared L_2 norm to the ground truth η against wall clock time. While these dimensions are not high by machine learning standards, they are significantly beyond those achievable using grid based discretizations of divergence-free fields. The results are shown in Figure 5. While larger dimensions are slower, we are still able to recover the ground truth in a reasonable amount of time in dimensions up to 100.

Figure 5: L_2 to ground truth.

7 Dynamical optimal transport

The calculation of optimal transport (OT) maps between two densities of interest p_0 and p_1 serves as a powerful tool for computing distances between distributions. Moreover, the inclusion of OT into machine learning has inspired multiple works on building efficient or stable generative models [Arjovsky et al., 2017, Tong et al., 2020, Makkuva et al., 2020, Huang et al., 2020, Finlay et al., 2020, Rout et al., 2021, Rozen et al., 2021]. In particular, we are interested in the dynamical

formulation of Benamou and Brenier [2000], which is a specific instance where the transport map is characterized through a vector field. Specifically, we wish to solve the optimization problem

$$\min_{\rho,u} \int_0^1 \int_{\mathcal{M}} \|u(t,x)\|^2 \rho(t,x) \, dx dt \tag{15}$$

subject to the boundary constraints, $\rho(0,\cdot) = p_0(\cdot)$ and $\rho(1,\cdot) = p_1(\cdot)$, as well as remaining non-negative $\rho \geq 0$ on the domain and satisfying the continuity equation $\frac{\partial \rho}{\partial t} + \text{div}(\rho u) = 0$.

In many existing cases, the models for estimating either ρ and equation 15 are completely decoupled from the generative model or transport map [Arjovsky et al., 2017, Makkuva et al., 2020], or in some cases ρ would be computed through numerical simulation and equation 15 estimated through samples [Chen et al., 2018, Finlay et al., 2020, Tong et al., 2020]. These approaches may not be ideal as they require an auxiliary process to satisfy or approximate the continuity equation.

In contrast, our NCL approach allows us to have access to a pair of ρ and u that always satisfies the continuity equation, without the need for any numerical simulation. As such, we only need to match the boundary conditions, and will automatically have access to a vector field u that transports mass from $\rho(0,\cdot)$ to $\rho(1,\cdot)$. In order to find an optimal vector field, we can then optimize u with respect to the objective in equation 15.

7.1 Parameterizing non-negative densities with subharmonic functions

In this setting, it is important that our density is non-negative for the entire domain and within the time interval between 0 and 1. Instead of adding another loss function to satisfy this condition, we show how we can easily bake this condition into our model through the vector-field parameterization.

Recall for the vector-field parameterization of the continuity equation, we have a vector field $b_\theta(y)$ with $y = [t,x]$, for $t \in [0,1]$, $x \in \mathbb{R}^n$. This results in the parameterization

$$\rho = \text{div} \left(\frac{\partial b_1}{\partial x} - \frac{\partial b_{2:n+1}}{\partial t}^\mathsf{T} \right) \quad \text{for } i = 1, \ldots, n+1. \tag{16}$$

We now make the adjustment that $\frac{\partial b_{2:n+1}}{\partial t} = 0$. This condition does not reduce the expressivity of the formulation, as ρ can still represent any density function. Interestingly, this modification does imply that $\rho = \nabla^2 b_1$ with ∇^2 being the Laplacian operator, so that satisfying the boundary conditions is equivalent to solving a time-dependent Poisson's equation $\nabla^2 b_1(t,\cdot) = p_t$.

Furthermore, the class of *subharmonic* functions is exactly the set of functions g that satisfies $\nabla^2 g(0,\cdot) \geq 0$. In one dimension, this corresponds to the class of convex functions but is a strict generalization of convex functions in higher dimensions. With this in mind, we propose using the parameterization

$$b_1(t,x) = \sum_{k=1}^{K} w_k(t)\phi(a_k(t)x + b_k(t)) \quad \text{where } \phi(z) = \frac{1}{4\pi} \left(\log(\|z\|^2) + E_1(\|z\|^2/4) \right) \tag{17}$$

with E_1 being the exponential integral function, and $w_k, a_k \in \mathbb{R}^+$ and $b_k \in \mathbb{R}^n$ are free functions of t. This weighted sum of generalized linear models, where the choice of nonlinear function ϕ is chosen because it is the exact solution to the Poisson's equation for a standard normal distribution when $n = 2$, *i.e.* $\nabla^2 \phi = \mathcal{N}(0,I)$, while for $n \geq 2$ this remains a subharmonic function. As such, this can be seen as a generalization of a mixture model, which are often referenced to be universal density approximators [Goodfellow et al., 2016], albeit requiring many mixture components.

7.2 Experiments

We experiment with pairs of 2D densities (visualized in Figure 6) and fit a pair of (ρ, u) to equation 15 while satisfying boundary conditions. Specifically, we train with the loss

$$\min_{\rho,u} \lambda \mathbb{E}_{x \sim \tilde{p}_0} \left[|\rho(0,x) - p_0(x)| \right] + \lambda \mathbb{E}_{x \sim \tilde{p}_1} \left[|\rho(1,x) - p_1(x)| \right] + \int_0^1 \int_{\mathcal{M}} \|u(t,x)\|^2 \rho(t,x) \, dx dt \tag{18}$$

where $\tilde{p}_i$ is a mixture between p_i and a uniform density over a sufficiently large area, for $i = 0, 1$, and λ is a hyperparameter. We use a batch size of 256 and set K=128 (from equation 17). Qualitative results are displayed in Figure 6, which include interpolations between pairs of densities.

(a) Circles ⟷ Pinwheel   (b) Pinwheel ⟷ 8Gaussians

Figure 6: Learned approximation to the dynamical optimal transport map. (*top*) Density ρ. (*mid*) Transformed samples in orange, with samples from p_0 and p_1 in blue. (*bottom*) Learned vector field.

(a) Circles ↔ Pinwheel   (b) Pinwheel ↔ 8Gaussians   (c) 8Gaussians ↔ Circles

Figure 7: Neural Conservation Laws on approximating dynamical optimal transport converges in minutes. The alternative minimax formulation tends to underestimate the Wasserstein distance. Dashed line is an estimate from a discrete OT algorithm. Shaded region denotes standard deviation.

Furthermore, we can use the trained models to estimate the Wasserstein distance, by transforming samples from p_0 through the learned vector field to time $t=1$. We do this for 5000 samples and compare the estimated value to (i) one estimated by that of a neural network trained through a minimax optimization formulation [Makkuva et al., 2020], and (ii) one estimated by that of a discrete OT solver [Bonneel et al., 2011] based on kernel density approximation and interfaced through the `pot` library [Flamary et al., 2021].

Estimated squared Wasserstein distance as a function of wallclock time are shown in Figure 7. We see that our estimated values roughly agree with the discrete OT algorithm. However, the baseline minimax approach consistently underestimates the optimal transport distance. This is an issue with the minimax formulation not being able to cover all of the modes, and has been commonly observed in the literature (*e.g.* Salimans et al. [2016], Che et al. [2017], Srivastava et al. [2017]). Moreover, in order to stabilize minimax optimization in practice, Makkuva et al. [2020] made use of careful optimization tuning such as reducing momentum [Radford et al., 2016]. In contrast, our NCL approach is a simple optimization problem.

8 Conclusion

We proposed two constructions for building divergence-free neural networks from an original unconstrained smooth neural network. This resulted in two practical approaches where either an original matrix field or vector field is parameterized. We found both to be useful in practice; the matrix field approach is more flexible in lower dimensions while the vector field approach allows the addition of extra constraints such as a positive constraint. We combine these methods with the insight that the continuity equation itself is a divergence-free vector field. This resulted in a method for building deep neural networks that are constrained to always satisfy the continuity equation, which we refer to as Neural Conservation Laws. Currently, these models are difficult to scale due to extensive use of automatic differentiation for computing divergence of neural networks. It may be possible to combine our approach with parameterizations that provide cheap divergence computations [Chen and Duvenaud, 2019]. Nevertheless, the development of efficient batching and automatic differentiation tools is an active research area, so we expect these tools to improve as development progresses.

References

A. S. Almgren, J. B. Bell, P. Colella, L. H. Howell, and M. L. Welcome. A Conservative Adaptive Projection Method for the Variable Density Incompressible Navier–Stokes Equations. *Journal of Computational Physics*, 142(1):1–46, May 1998. ISSN 00219991. doi:10.1006/jcph.1998.5890. URL https://linkinghub.elsevier.com/retrieve/pii/S0021999198958909.

B. Amos and J. Z. Kolter. Optnet: Differentiable optimization as a layer in neural networks. In *International Conference on Machine Learning*, pages 136–145. PMLR, 2017.

B. Amos, L. Xu, and J. Z. Kolter. Input convex neural networks. In *International Conference on Machine Learning*, pages 146–155. PMLR, 2017.

M. Andrychowicz, M. Denil, S. Gomez, M. W. Hoffman, D. Pfau, T. Schaul, B. Shillingford, and N. De Freitas. Learning to learn by gradient descent by gradient descent. *Advances in neural information processing systems*, 29, 2016.

M. Arjovsky, S. Chintala, and L. Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. PMLR, 2017.

G. Arvanitidis, L. K. Hansen, and S. Hauberg. Latent Space Oddity: on the Curvature of Deep Generative Models, Dec. 2021. URL http://arxiv.org/abs/1710.11379. Number: arXiv:1710.11379 arXiv:1710.11379 [stat].

S. Bai, J. Z. Kolter, and V. Koltun. Deep equilibrium models. *Advances in Neural Information Processing Systems*, 32, 2019.

C. Barbarosie. Representation of divergence-free vector fields. *Quarterly of applied mathematics*, 69 (2):309–316, 2011.

J.-D. Benamou and Y. Brenier. A computational fluid mechanics solution to the monge-kantorovich mass transfer problem. *Numerische Mathematik*, 84(3):375–393, 2000.

M. Berger. A panoramic view of riemannian geometry. 2003.

N. Bonneel, M. Van De Panne, S. Paris, and W. Heidrich. Displacement interpolation using lagrangian mass transport. In *Proceedings of the 2011 SIGGRAPH Asia conference*, pages 1–12, 2011.

J. Bradbury, R. Frostig, P. Hawkins, M. J. Johnson, C. Leary, D. Maclaurin, G. Necula, A. Paszke, J. VanderPlas, S. Wanderman-Milne, and Q. Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

M. M. Bronstein, J. Bruna, Y. LeCun, A. Szlam, and P. Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 34(4):18–42, 2017.

É. Cartan. On certain differential expressions and the pfaff problem. In *Scientific Annals of the ŚchoolNormal Superior*, volume 16, pages 239–332, 1899.

T. Che, Y. Li, A. P. Jacob, Y. Bengio, and W. Li. Mode regularized generative adversarial networks. *International Conference on Learning Representations*, 2017.

R. T. Q. Chen and D. K. Duvenaud. Neural networks with cheap differential operators. *Advances in Neural Information Processing Systems*, 32, 2019.

R. T. Q. Chen, Y. Rubanova, J. Bettencourt, and D. K. Duvenaud. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

R. T. Q. Chen, J. Behrmann, D. K. Duvenaud, and J.-H. Jacobsen. Residual flows for invertible generative modeling. *Advances in Neural Information Processing Systems*, 32, 2019.

M. P. Do Carmo. *Differential forms and applications*. Springer Science & Business Media, 1998.

M. Eisenberger, Z. Lähner, and D. Cremers. Divergence-Free Shape Interpolation and Correspondence, Oct. 2018. URL http://arxiv.org/abs/1806.10417. Number: arXiv:1806.10417 arXiv:1806.10417 [cs].

R. Feynman, R. Leighton, and M. Sands. *The Feynman Lectures on Physics: Commemorative Issue*. Advanced book program. Addison-Wesley, 1989. ISBN 978-0-201-50064-6. URL https://books.google.ca/books?id=UHp1AQAACAAJ.

C. Finlay, J.-H. Jacobsen, L. Nurbekyan, and A. M. Oberman. How to train your neural ode. *arXiv preprint arXiv:2002.02798*, 2020.

R. Flamary, N. Courty, A. Gramfort, M. Z. Alaya, A. Boisbunon, S. Chambon, L. Chapel, A. Corenflos, K. Fatras, N. Fournier, L. Gautheron, N. T. Gayraud, H. Janati, A. Rakotomamonjy, I. Redko, A. Rolet, A. Schutz, V. Seguy, D. J. Sutherland, R. Tavenard, A. Tong, and T. Vayer. Pot: Python optimal transport. *Journal of Machine Learning Research*, 22(78):1–8, 2021. URL http://jmlr.org/papers/v22/20-451.html.

J. E. Gerken, J. Aronsson, O. Carlsson, H. Linander, F. Ohlsson, C. Petersson, and D. Persson. Geometric deep learning and equivariant neural networks, 2021. URL https://arxiv.org/abs/2105.13926.

I. Goodfellow, Y. Bengio, and A. Courville. *Deep learning*. MIT press, 2016.

J.-L. Guermond and L. Quartapelle. A Projection FEM for Variable Density Incompressible Flows. *Journal of Computational Physics*, 165(1):167–188, Nov. 2000. ISSN 00219991. doi:10.1006/jcph.2000.6609. URL https://linkinghub.elsevier.com/retrieve/pii/S0021999100966099.

K. Hornik, M. Stinchcombe, and H. White. Multilayer feedforward networks are universal approximators. *Neural networks*, 2(5):359–366, 1989.

C.-W. Huang, R. T. Q. Chen, C. Tsirigotis, and A. Courville. Convex potential flows: Universal probability distributions with optimal transport and convex optimization. *arXiv preprint arXiv:2012.05942*, 2020.

S. Hurault, A. Leclaire, and N. Papadakis. Gradient step denoiser for convergent plug-and-play. *International Conference on Learning Representations*, 2022.

A. D. Jagtap, E. Kharazmi, and G. E. Karniadakis. Conservative physics-informed neural networks on discrete domains for conservation laws: Applications to forward and inverse problems. *Computer Methods in Applied Mechanics and Engineering*, 365:113028, June 2020. ISSN 00457825. doi:10.1016/j.cma.2020.113028. URL https://linkinghub.elsevier.com/retrieve/pii/S0045782520302127.

X. Jin, S. Cai, H. Li, and G. E. Karniadakis. NSFnets (Navier-Stokes Flow nets): Physics-informed neural networks for the incompressible Navier-Stokes equations. *Journal of Computational Physics*, 426:109951, Feb. 2021. ISSN 00219991. doi:10.1016/j.jcp.2020.109951. URL http://arxiv.org/abs/2003.06496. arXiv: 2003.06496.

J. Kelliher. Stream functions for divergence-free vector fields. *Quarterly of Applied Mathematics*, 79 (1):163–174, 2021.

I. E. Lagaris, A. Likas, and D. I. Fotiadis. Artificial neural networks for solving ordinary and partial differential equations. *IEEE transactions on neural networks*, 9(5):987–1000, 1998.

C. Li, W. Wei, J. Li, J. Yao, X. Zeng, and Z. Lv. 3dmol-net: learn 3d molecular representation using adaptive graph convolutional network based on rotation invariance. *IEEE Journal of Biomedical and Health Informatics*, 2021.

C. Lu, J. Chen, C. Li, Q. Wang, and J. Zhu. Implicit normalizing flows. *arXiv preprint arXiv:2103.09527*, 2021.

A. Makkuva, A. Taghvaei, S. Oh, and J. Lee. Optimal transport mapping via input convex neural networks. In *International Conference on Machine Learning*, pages 6672–6681. PMLR, 2020.

Z. Mao, A. D. Jagtap, and G. E. Karniadakis. Physics-informed neural networks for high-speed flows. *Computer Methods in Applied Mechanics and Engineering*, 360:112789, Mar. 2020. ISSN 00457825. doi:10.1016/j.cma.2019.112789. URL https://linkinghub.elsevier.com/retrieve/pii/S0045782519306814.

T. Miyato, T. Kataoka, M. Koyama, and Y. Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

S. Morita. *Geometry of differential forms*. Number 201. American Mathematical Soc., 2001.

D. Onken, S. Wu Fung, X. Li, and L. Ruthotto. Ot-flow: Fast and accurate continuous normalizing flows via optimal transport. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, 2021.

A. Radford, L. Metz, and S. Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *International Conference on Learning Representations*, 2016.

M. Raissi, P. Perdikaris, and G. E. Karniadakis. Physics Informed Deep Learning (Part I): Data-driven Solutions of Nonlinear Partial Differential Equations, Nov. 2017. URL http://arxiv.org/abs/1711.10561. Number: arXiv:1711.10561 arXiv:1711.10561 [cs, math, stat].

M. Raissi, P. Perdikaris, and G. E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019. ISSN 0021-9991. doi:https://doi.org/10.1016/j.jcp.2018.10.045. URL https://www.sciencedirect.com/science/article/pii/S0021999118307125.

C. Rao, H. Sun, and Y. Liu. Physics-informed deep learning for incompressible laminar flows. *Theoretical and Applied Mechanics Letters*, 10(3):207–212, 2020.

L. Rout, A. Korotin, and E. Burnaev. Generative modeling with optimal transport maps. *arXiv preprint arXiv:2110.02999*, 2021.

N. Rozen, A. Grover, M. Nickel, and Y. Lipman. Moser flow: Divergence-based generative modeling on manifolds. *Advances in Neural Information Processing Systems*, 34, 2021.

T. Salimans, I. Goodfellow, W. Zaremba, V. Cheung, A. Radford, and X. Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.

P. W. Schroeder and G. Lube. Pressure-robust analysis of divergence-free and conforming FEM for evolutionary incompressible navier–stokes flows. *Journal of Numerical Mathematics*, 25(4), dec 2017. doi:10.1515/jnma-2016-1101. URL https://doi.org/10.1515%2Fjnma-2016-1101.

Y. Song and S. Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in Neural Information Processing Systems*, 32, 2019.

A. Srivastava, L. Valkov, C. Russell, M. U. Gutmann, and C. Sutton. Veegan: Reducing mode collapse in gans using implicit variational learning. *Advances in neural information processing systems*, 30, 2017.

A. Tong, J. Huang, G. Wolf, D. Van Dijk, and S. Krishnaswamy. Trajectorynet: A dynamic optimal transport network for modeling cellular dynamics. In *International Conference on Machine Learning*, pages 9526–9536. PMLR, 2020.

T. Xue, A. Beatson, S. Adriaenssens, and R. Adams. Amortized finite element analysis for fast PDE-constrained optimization. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 10638–10647. PMLR, 13–18 Jul 2020.