Hydra: Towards Transferable Multi-Task Learning on Temporal Graphs

Kiarash Shamsi [1]   **Farimah Poursafaei** [2 3]   **Tran Gia Bao Ngo** [1]   **Reihaneh Rabbany** [2 3 4]   **Baris Coskunuzer** [5]
Guillaume Rabusseau [2 6 4]   **Michael M. Bronstein** [7]   **Shenyang Huang** [2 3 7]   **Cuneyt Gurcan Akcora** [8]

Abstract

Real-world evolving networks are naturally modelled as temporal graphs (TGs), where capturing temporal dynamics is essential for predicting future graph properties that support downstream decision-making. Existing temporal graph methods are primarily designed for a single task while requiring retraining from scratch for each dataset. Therefore, little is known about their generalization across tasks or transfer to unseen networks. In this work, we would like to fill this gap by studying the multi-task graph property prediction setting in TGs. The evolution of graph properties is best captured with a local perspective that models the evolving patterns of individual nodes and the global perspective that emphasizes high-level structural changes. To this end, we introduce `Hydra`, a novel architecture that integrates local connectivity features from temporal GNNs with a spectral learning module that captures global connectivity patterns. These two perspectives are then optimized under a multi-task objective. In multi-task classification, `Hydra` achieves an 8.9% relative gain in AUC over the strongest competitor. In multi-task regression, `Hydra` obtains the best result in two out of three tasks with an 8.2% relative gain in MAE compared to the second best while maintaining competitive performance across all three tasks. By achieving consistent top-ranked performance, `Hydra` highlights multi-task training on temporal graphs as a promising direction toward adaptable foundation models for temporal graphs.

[1]University of Manitoba [2]Mila – Quebec AI Institute [3]McGill University [4]CIFAR AI Chair [5]University of Texas at Dallas [6]Université de Montréal [7]University of Oxford [8]University of Central Florida. Correspondence to: Kiarash Shamsi <shamsik1@myumanitoba.ca>.

Workshop on Graph Foundation Models at the 43rd International Conference on Machine Learning (ICML 2026), Seoul, South Korea.

1. Introduction

Temporal graph prediction addresses the challenge of forecasting the future state and the trajectory of networks that evolve over time and possess an underlying relational structure. Unlike traditional graph analysis that assumes a static topology, temporal graphs are characterized by continuously changing nodes, edges, and features, representing dynamic real-world phenomena such as social network interactions (Wang et al., 2024; Jalili, 2025), traffic flow (Sahili and Awad, 2023; Ockerman et al., 2025), and biological processes (Hosseinzadeh et al., 2022). The core difficulty lies in capturing both the complex spatial dependencies encoded in the graph structure and the temporal dynamics that governs its evolution (Kazemi et al., 2020). Effective solutions must therefore move beyond static graph representation learning to models that can jointly capture spatio-temporal patterns, enabling accurate prediction of future interactions, node properties, and system-wide events. This capability underpins applications such as disease outbreak detection (Senthilkumar et al., 2022), fraud prevention (Duan et al., 2024), recommendation systems (Tang et al., 2025), and transportation networks (Chen et al., 2022b; Uddin et al., 2026). Despite progress in temporal graph learning, two fundamental challenges remain open.

Multi-task Temporal Graph Prediction. The first challenge is multi-task temporal graph property prediction. Existing temporal graph methods commonly focus on one prediction objective at a time, while many real applications require forecasting multiple related graph-level properties from the same evolving network. For example, one may need to predict both community evolution and connectivity growth. By learning these tasks jointly, models can exploit the shared spatio-temporal dynamics that shape them, yielding more robust generalization and a deeper understanding of system-wide behavior. Multi-task temporal graph prediction requires representations that transfer across heterogeneous graphs, remain stable under temporal drift, and still capture task-specific signals, which existing temporal GNNs and graph-level baselines cannot provide. Our framework overcomes these limits by using a shared trunk that fuses global structural dynamics with local temporal information to support robust multi-graph, multi-task prediction.

Transferability Across Networks. The second challenge is transferability across networks. In real-world dynamic settings, new networks constantly emerge, data may be sparse or incomplete, and training from scratch is costly. A practical solution is to pre-train temporal graph models on multiple observed networks and transfer them to unseen ones without retraining (Levie et al., 2021; Ruiz et al., 2023; Wang et al., 2025; Ranjan et al., 2026). This requires learning representations that capture generalizable temporal patterns while scaling effectively with data size and model capacity. Unlike static graphs, temporal graphs add the complexity of evolving structures and features, which makes transfer and scaling more difficult. Yet, no prior work examines how to build a representation trunk that captures cross-network temporal invariances while supporting multiple tasks through flexible lightweight heads. The tasks we study match real system needs: forecasting structural stability, connectivity growth and shrink which are standard aggregate indicators used in risk analysis and network monitoring.

Figure 1. **Hydra overview.** Hydra is trained once on multiple networks and, without any additional training, can be directly applied to unseen networks for predicting multiple properties simultaneously.

In this work, we address both challenges by introducing **Hydra**, a novel temporal multi-task graph neural network (GNN) designed for graph-level multi-property predictions with strong transferability across diverse networks. To capture global structural information, Hydra leverages graph Laplacian descriptors, while local node interactions and temporal dynamics are modeled through a Temporal Graph Neural Network (TGNN) equipped with a self-attention pooling layer. This trunk–head design separates a shared spectral–spatio–temporal backbone that captures cross-network, task-invariant dynamics from lightweight task-specific heads that flexibly support heterogeneous objectives. The resulting spectral and spatio-temporal representations are fused and passed through task-specific prediction heads (Figure 1). Trained end-to-end in a multi-task setting, Hydra achieves state-of-the-art performance on six benchmark tasks spanning classification and regression. Significantly, it generalizes across unseen networks, consistently outperforming models trained from scratch on those networks. We also analyze its scaling behavior, showing that performance improves as more training networks are incorporated. Our contributions are summarized as follows:

- **First study on multi-task learning for temporal graphs.** We introduce the first model that jointly handles multiple temporal graph prediction tasks without retraining, achieving state-of-the-art performance while addressing task interference and cross-network invariance.
- **Novel integration of TGNNs with spectral methods.** We incorporate Laplacian descriptors into TGNNs for graph-level prediction, enabling cross-network transfer by capturing structural invariances absent from purely temporal or purely spectral models.
- **Comprehensive study of transfer and scaling.** Hydra achieves an 8.9% AUC gain in classification and 8.2% MAE gain in two regression tasks over the strongest baselines while remaining competitive on the third task without any task-specific training. Moreover, transferability to unseen networks improving as the number of training datasets increases.

2. Background and Related Work

Temporal Graph Property Prediction. Graph property prediction has been widely studied in the static setting, where various methods (Luo et al., 2025; Ying et al., 2021; Yang et al., 2023) have shown strong performance in tasks such as molecular property prediction (Sypetkowski et al., 2024; Wieder et al., 2020) and social network analysis (Chen et al., 2020). Building upon these advances, temporal graph property prediction has recently received increasing attention. One of the pioneer approaches to extend static models into temporal settings is GraphPulse (Shamsi et al., 2024) that combines recurrent architectures with topological data analysis tools to capture temporal patterns. However, existing work has been limited to training on a single network (Huang et al., 2023b; 2024), with the exception of MiNT (Shamsi et al., 2025), which trains across multiple networks and demonstrates transferability to unseen networks during the inference phase. However, MiNT is restricted to a single classification task, and its computational cost is high due to its hyperbolic backbone. In this work, we go beyond this limitation by addressing multiple classification tasks as well as regression tasks in a scalable manner.

Multi-Task Learning. Multi-task learning has been extensively studied as a means to improve generalization by jointly optimizing related tasks and leveraging shared information (Caruana, 1997; Zhang and Yang, 2018; 2021). In the context of graph learning, several approaches have been proposed that integrate learning strategies to enhance generalization, achieving strong performance across diverse datasets and downstream tasks (Jin et al., 2022; Ju et al., 2023; Klaser et al., 2024; Nassif et al., 2020). How-

ever, while these advances have driven substantial progress in static graph learning, the application of multi-task learning to temporal graphs remains unexplored.

Temporal Graph Transferability. Recent advances in temporal graph learning have produced models tailored for tasks such as link prediction (Rossi et al., 2020; Huang et al., 2023a; Cornell et al., 2025; Shi et al., 2026). While these methods achieve strong results on specific tasks and datasets, their applicability is often narrow: models trained for one task or on one network may fail to generalize to new settings. Unlike static graphs, temporal graphs introduce additional challenges for transfer, including evolving topologies, distribution shifts, and non-stationary dynamics. These factors make it difficult for a model to retain predictive power outside its training environment. Addressing transferability is important for real-world use cases where networks are constantly changing, data collection is costly, and retraining for every task or dataset is impractical (Wang et al., 2020; Huang et al., 2023b; Qi et al., 2023). A central open problem is to design models that capture generalizable temporal patterns so that knowledge gained from past networks or tasks can be reused in unseen ones (Pan et al., 2025; Liang et al., 2025). Developing such models would enable scalable, efficient, and continuous prediction in dynamic environments.

3. `Hydra`: A Multi-task, Transfer Learning Model

3.1. Problem Definition

We define a discrete time temporal graph as a sequence of snapshots $\mathcal{G} = \{\mathcal{G}_t = (V_t, E_t, X_t)\}_{t=1}^T$, where V_t and E_t denote the node and edge sets at time t, and X_t represents associated node or edge features. In this work, we consider a collection of temporal graphs $\mathcal{D} = \{\mathcal{G}^{(i)}\}_{i=1}^N$, each evolving independently over time. For each temporal graph $\mathcal{G}^{(i)} = \{\mathcal{G}_t^{(i)}\}_{t=1}^{T_i}$ we associate task-specific labels $\{y_t^{(i,k)}\}_{k=1}^K$ for K prediction tasks.

Definition 1 (Multi-Task Temporal Graph Property Prediction). *The objective is to learn a model*

$$f_\theta : \left\{ \{\{\mathcal{G}_t^{(i)}\}_{t=1}^{T-1}\}_{i=1}^N \right\} \mapsto \left\{ \left(\hat{y}_t^{(i,1)}, \dots, \hat{y}_t^{(i,K)} \right) \right\}_{i=1}^N,$$

that ingests all snapshots of all graphs in $\mathcal{D}$ up to time $t - 1$ and jointly predicts K graph-level properties at time t for each graph. The parameters θ are optimized jointly across $\mathcal{D}$, and the trained model is required to generalize to temporal graphs not included in $\mathcal{D}$.

`Hydra` is evaluated on two categories of prediction tasks across multiple temporal graphs. In the **classification setting**, for $k \in \mathcal{K}_{\mathrm{cls}}$, the objective is to predict binary outcomes $\hat{y}_t^{(i,k)} \in \{0, 1\}$ indicating the directional change of

graph-level properties between consecutive snapshots. In the **regression setting**, for $k \in \mathcal{K}_{\mathrm{reg}}$, the model predicts numerical values $\hat{y}_t^{(i,k)} \in \mathbb{R}$ that quantify the magnitude of graph-level properties at the next snapshot. In principle, this division allows `Hydra` to handle both discrete and continuous objectives within a single unified architecture.

Multi-task learning provides the foundation for this setting (Zhang and Yang, 2021; Ruder, 2017). Instead of training a separate model for each task, it enables simultaneous prediction, allowing shared temporal representations to capture interdependencies between tasks (Crawshaw, 2020). `Hydra` builds on this foundation by unifying diverse temporal prediction tasks under a single architecture. Specifically, we focus on a *shared trunk* architecture with task-specific heads as it has proven effective in balancing information sharing and mitigating negative transfer (Crawshaw, 2020). Learning tasks jointly allows the model to exploit shared temporal dynamics rather than treating each task independently. Figure 2 shows the `Hydra` framework.

3.2. `Hydra`: Shared Trunk with Task-Specific Heads

The central design choice of `Hydra` is to couple a shared representation trunk with lightweight task-specific heads. We adopt this structure because the underlying challenges in temporal graph property prediction require representations that are both transferable across heterogeneous graphs and adaptable to multiple tasks. The trunk captures common temporal–structural patterns once, while task-specific heads provide minimal but sufficient specialization.

`Hydra` instantiates the predictor f_θ (Definition 1) with the shared trunk that produces embeddings $H_t^{(i)}$ for $\mathcal{G}_t^{(i)}$, followed by task-specific heads $\{g_{\psi_k}\}_{k=1}^K$ that map $H_t^{(i)}$ to predictions $\hat{y}_t^{(i,k)}$.

The trunk jointly leverages (i) spectral descriptors that summarize global connectivity patterns and (ii) spatial GNN-based encoders that model local temporal interactions. These components provide complementary global and local information while avoiding redundant representation learning.

As shown in Figure 2, the trunk $H_t^{(i)}$ consists of a spectral path, which encodes global descriptors, and a spatial path, which models local temporal dynamics. Their outputs are concatenated into the shared embedding $H_t^{(i)}$, which is then passed to task-specific decoder heads, $\{g_{\psi_k}\}_{k=1}^K$, each producing a prediction $\hat{y}_t^{(i,k)}$.

3.2.1. SPECTRAL PATH FOR GLOBAL CONNECTIVITY

Laplacian eigenvalues effectively encode global graph structural properties (Mohar et al., 1991). For example, in star, path, and fully-connected graphs, the distribution

Figure 2. **Hydra framework.** The architecture integrates spatial and spectral paths with a unified multi-task design, enabling Hydra to learn transferable representations across diverse temporal graph tasks.

of the Laplacian eigenvalues is distinct and captures their unique topologies. However, computing all eigenvalues of the graph Laplacian matrix is highly expensive and only feasible for small graphs with thousands of nodes. Thus, it is important to efficiently approximate the spectrum of the Laplacian.

Network Density of States. To capture information from the Laplacian spectrum, we use the network density of states (DOS), the distribution of the eigenvalues of the graph Laplacian matrix (Dong et al., 2019), as follows:

Definition 2 (Density of States)**.** *Given a temporal graph snapshot* $\mathcal{G}_t$ *with adjacency matrix* $\mathbf{A}$ *and degree matrix* $\mathbf{D}$*, let the (unnormalized) Laplacian be* $\mathbf{L} = \mathbf{D} - \mathbf{A}$*. We use the normalized Laplacian* $\mathbf{L}_{\mathrm{sym}} = \mathbf{I} - \mathbf{D}^{-\frac{1}{2}}\mathbf{A}\mathbf{D}^{-\frac{1}{2}}$ *with eigendecomposition* $\mathbf{L}_{\mathrm{sym}} = \mathbf{Q}\mathbf{\Lambda}\mathbf{Q}^{\top}$*, where* $\mathbf{\Lambda} = \mathrm{diag}(\lambda_1, \ldots, \lambda_{|V_t|})$ *contains the eigenvalues. The* density of states *is then defined as a discrete distribution supported on the spectrum of* $\mathbf{L}_{\mathrm{sym}}$*:* $\mu(\lambda) = \frac{1}{|V_t|}\sum_{i=1}^{|V_t|} \delta(\lambda - \lambda_i)$

Essentially, $\mu(\lambda)$ measures the fraction of eigenvalues equal to λ. In practice, the range of the eigenvalues is discretized into multiple equal-sized intervals, and the number of eigenvalues within each interval is approximated. The Kernel Polynomial Method (Weiße et al., 2006) is used to efficiently approximate the spectrum, capturing the distribution of the Laplacian eigenvalues.

Spectral Memory. To stabilize spectral signals and capture short-term trends, we maintain a fixed-length FIFO memory of recent DOS descriptors. At snapshot t, let $s_t \in \mathbb{R}^d$ denote the spectral feature (e.g., a $d{=}20$ DOS vector). For prediction at time t, the memory contains the last L descriptors up to $t{-}1$: $M_t = [s_{t-L}; \ldots; s_{t-1}] \in \mathbb{R}^{L \times d}$. After

prediction at t, the new descriptor s_t is computed and rolled into the memory: $M_{t+1} = \mathrm{roll}(M_t), \quad M_{t+1}[-1,:] = s_t$. This bounded memory reduces variance in non-stationary settings and preserves context across long temporal traces, typical of sparse graphs.

Attention over Spectral Memory. Rather than uniform averaging, we apply attention to emphasize historically similar or predictive patterns. With learnable projections $W_q, W_k, W_v \in \mathbb{R}^{d \times d_a}$, we compute $q_t = s_{t-1}W_q$, $K_t = M_tW_k$, $V_t = M_tW_v$. Attention weights and the attentive spectral embedding are $\alpha_t = \mathrm{softmax}\left(\frac{q_t K_t^{\top}}{\sqrt{d_a}}\right)$, $z_t = \alpha_t V_t$. This mechanism highlights relevant history, suppresses noise, and captures structural–spectral motifs that recur across networks.

3.2.2. SPATIAL PATH FOR LOCAL CONNECTIVITY

We integrate spatial and temporal dynamics by combining a Graph Convolutional Network (GCN) (Kipf, 2016) with Gated Recurrent Units (GRUs) (Cho et al., 2014). Similar approaches have proven effective in temporal settings (Zhao et al., 2019). At snapshot t, a GCN encodes structural features $\mathbf{Z}_t = \mathrm{GCN}(\mathbf{X}_{t-1}, E_{t-1})$, and a GRU updates node states with temporal memory $\mathbf{H}_t = \mathrm{GRU}(\mathbf{Z}_t, \mathbf{H}_{t-1})$. The representation $\mathbf{H}_t$ is thus spatially grounded and temporally enriched.

Pooling and Graph Readout. We apply Self-Attention Graph Pooling (SAGPool) (Lee et al., 2019) to emphasize structurally important nodes. Node scores are computed as $s = \mathrm{GCN}(\mathbf{H}_t, E_{t-1})W_s$, where $W_s \in \mathbb{R}^{d \times 1}$ projects node embeddings to scalar scores. The top-k nodes are retained to form the pooled graph $(V^{'}, E^{'})$ with embeddings $\mathbf{H}'_t$. We then compute a graph-level vector using mean pooling

over the selected nodes: $g_t = \frac{1}{|V'|} \sum_{v \in V'} h_v, \quad h_v \in \mathbf{H}'_t$. SAGPool reduces noise from low-activity nodes and highlights structurally central actors, which is particularly relevant in sparse networks where activity is concentrated in a few key nodes (Shamsi et al., 2024).

3.3. Prediction Head

We fuse spatial and spectral signals to produce a joint temporal state. At each step, the shared hidden state of the prediction head $u_t = \mathrm{GRU}([g_t \| z_t], u_{t-1})$, where $[g_t \| z_t]$ denotes concatenation of spatial and spectral features. The recurrent update captures cross-modal dependencies over time. Task-specific MLPs then map the shared state to predictions: $\hat{y}_t^{(k)} = \mathrm{MLP}_k(u_t), \quad k = 1, \ldots, K$. This balances efficiency through a shared backbone with flexibility through task-specific heads.

3.4. End-to-End Training

Hydra supports both classification and regression objectives. For classification, each head is optimized with Binary Cross-Entropy loss; for regression, with Mean Squared Error. The total loss in each setting is the sum over task-specific losses within that group. Following prior work on loss balancing (Yu et al., 2020; Sener and Koltun, 2018), we train the two groups separately, as naïvely combining heterogeneous objectives degraded optimization stability. This preserves Hydra's multi-task benefits within each group while maintaining transferability across unseen networks.

4. Experimental Evaluation

4.1. Training Setup and Algorithm

Datasets. We evaluate Hydra on the MiNT benchmark of 84 ERC-20 temporal transaction networks (Shamsi et al., 2025), randomly selecting 64 networks for training/validation and 20 held-out networks for zero-shot transfer evaluation. Within each network, snapshots are split 70%–15%–15% into training, validation, and test sets. Detailed dataset statistics are provided in Appendix D. This setting enables us to evaluate whether Hydra can generalize across various network topologies and temporal patterns. During each epoch, networks are presented in random order, and historical embeddings are reset at the start of each network to avoid cross-network leakage. The shared trunk is optimized jointly, while all task-specific heads are updated under a multi-task loss with early stopping on validation performance. Models are trained for 100 to 250 epochs with an initial learning rate of 1.5×10^{-3}. Early stopping is applied based on validation AUC for classification and MAE for regression with a patience of 20 epochs and a tolerance of 5×10^{-2}. Binary Cross-Entropy

loss is used for classification tasks, while Mean Squared Error is used for regression tasks. Optimization is performed using Adam (Kingma and Ba, 2015). Each task is evaluated on 20 unseen test networks with three independent runs, yielding 60 result points per task. We report the average results from three different runs for each task separately, using ROC-AUC for classification objectives and Mean Absolute Error for regression objectives. We pretrain Hydra with 8, 16, and 32 networks to study the effect of scale on transferability. We cap the setting at 32 networks to allow multiple, independently sampled Hydra-32 models for analyzing the impact of data selection. Unless otherwise specified, all reported results refer to Hydra-32, as this configuration consistently delivers the strongest performance.

Tasks. We train Hydra in two multi-task settings: a classification model with three classification heads and a regression model with three regression heads. The classification tasks jointly predict whether the Largest Connected Component (LCC), the number of nodes, or the number of edges will grow or shrink. The regression tasks estimate the number of influential nodes (i.e., nodes with degree greater than five), new nodes, and edges. Full task definitions are provided in Appendix F.

Models. We compare Hydra against HTGN (Yang et al., 2021), GC-LSTM (Chen et al., 2022a), EvolveGCN (Pareja et al., 2020), GraphPulse (Shamsi et al., 2024), ROLAND (You et al., 2022), TGCN (Zhao et al., 2020), and WinGNN (Zhu et al., 2023), and additionally MiNT (Shamsi et al., 2025) for classification (MiNT is the only prior framework explicitly designed for transferability across temporal graphs for classification. We distinguish between single models, trained separately per dataset, and transferable models, applied directly to unseen networks without retraining. Hydra belongs to the latter category. Baseline details are provided in Appendix E.

Compute Resources. Experiments were run on a dedicated cluster compute node equipped with an NVIDIA H100 GPU (80 GB), dual 64-core AMD EPYC CPUs, and 512 GB RAM.

4.2. Classification and Regression Results

Table 1 presents the aggregate classification results across three tasks: LCC Growth/Shrinkage, Node Growth/Shrinkage, and Edge Growth/Shrinkage. For each task, we report three metrics: (*1st*) the number of datasets where the method achieved first place, (*Rank*) the average ranking across datasets, and (*AUC*) the average area under the ROC curve (metrics formulations are provided in appendix G). Hydra consistently achieves the strongest performance across all metrics, outperforming both state-of-the-art specifically trained models and the transferable

Table 1. Classification task results. Across LCC-GS, Node-GS, and Edge-G/S classification, Hydra consistently outperforms both specifically trained and transferable baselines.

	LCC-G/S			Node-G/S			Edge-G/S		
	1st↑	Rank↓	AUC↑	1st↑	Rank↓	AUC↑	1st↑	Rank↓	AUC↑
Single Models									
HTGN	2	4.40	0.648	0	3.65	0.615	1	4.85	0.684
GC-LSTM	0	6.00	0.572	0	6.65	0.489	1	5.80	0.609
EvolveGCN	0	6.30	0.585	0	7.00	0.487	0	6.10	0.626
GraphPulse	3	3.50	0.686	2	2.95	0.652	6	3.80	0.712
ROLAND	0	6.95	0.556	0	6.70	0.480	0	6.30	0.542
TGCN	1	6.10	0.583	0	6.15	0.530	0	5.60	0.633
WinGNN	0	6.10	0.585	0	6.20	0.528	0	5.55	0.642
Transfer Models									
MiNT	1	3.95	0.672	3	3.55	0.616	4	3.30	0.727
Hydra (ours)	**13**	**1.70**	**0.759**	**15**	**1.95**	**0.734**	**8**	**2.80**	**0.753**

Arrows indicate directionality: ↑ higher is better, ↓ lower is better.

Table 2. Regression task results. Across New Node Count, Influential Node Count, and Edge Count regression, Hydra achieves the best performance on two tasks and is competitive on the third, all without additional training.

	New Node Count			Influential Node Count			Edge Count		
	1st↑	Rank↓	MAE↓	1st↑	Rank↓	MAE↓	1st↑	Rank↓	MAE↓
Single Models									
HTGN	4	3.45	0.039	4	**3.52**	**0.050**	2	3.95	0.049
TGCN	1	4.10	0.042	1	4.85	0.059	1	4.60	0.054
GCLSTM	2	4.00	0.043	**5**	3.80	0.053	4	4.58	0.057
ROLAND	3	4.35	0.052	2	4.55	0.057	3	4.58	0.050
EGCN	0	3.90	0.040	0	4.20	0.052	1	5.30	0.054
GraphPulse	1	5.75	0.071	1	5.90	0.078	2	5.72	0.073
WinGNN	4	4.05	0.054	4	4.28	0.059	5	3.93	0.057
Transfer Model									
Hydra (ours)	**8**	**2.50**	**0.035**	5	4.90	0.056	**6**	**3.35**	**0.046**

Arrows indicate directionality: ↑ higher is better, ↓ lower is better.

baseline. Detailed per-dataset classification outcomes are provided in Appendix J.

Table 2 summarizes the regression results across New Node Count, Influential Node Count, and Edge Count Regression. For each task, we report three metrics: (*1st*) the number of datasets where the method achieved first place, (*Rank*) the average ranking across datasets, and (*MAE*) the average mean absolute error. Hydra is the best model on two of the three tasks and remains very close to the best baseline on Influential Node Count, demonstrating strong overall transferability for regression objectives. Hydra produces the most top-ranked results in both classification and regression settings, outperforming all baselines in five out of six tasks. To keep the main paper concise, we report summarized results in the main text and provide extended per-dataset outcomes in Appendix J. Even in the one regression task where Hydra isn't the leader, it stays competitive with the strongest baseline. Notably, Hydra is always tested on unseen networks, while single models specifically trained for a task are evaluated on the test portion of the same networks they were trained on. Despite this tougher setting, Hydra consistently delivers better or comparable results, making it a reliable and adaptable framework for temporal graph learning.

Ablation Studies. We assess the impact of Hydra 's key

Table 3. Meta ablation summary for Edge G/S classification. Average AUC and #1st-Place counts are reported with and without the corresponding component. Per-network results are given in Appendix Tables 6 and 7.

Ablation	Avg. AUC		#1st-Place	
	w/o	w/	w/o	w/
Density of States	0.697	**0.719**	6	**14**
Attention-based Pooling	0.719	**0.753**	3	**17**

components by disabling the DOS module and the pooling layer. We provided a comprehensive analysis in Appendix H. As summarized in Table 3, DOS improves performance from an average AUC of 0.697 to 0.719, raising the number of best-performing datasets from 6 to 14 and lowering the mean rank from 1.70 to 1.30. Pooling yields an even larger effect, increasing average AUC from 0.719 to 0.753 and improving the mean rank from 1.85 to 1.15, with gains on 17 out of 20 datasets. These results confirm that DOS provides complementary global spectral information, while pooling enhances the spatial path by emphasizing structurally important nodes, together strengthening Hydra 's generalization ability.

4.3. `Hydra` Generalization and Efficiency

In this section, we analyze how the number of networks used during the pre-training of Hydra affects its performance in predicting the characteristics of unseen networks at inference time. The results are presented in Fig. 3. For classification tasks, we observe that increasing the number of training networks generally leads to a higher #1st-*Place*. This metric is a strong indicator of performance, as it reflects the number of unseen networks on which the model achieves the best results at inference time. In contrast, the correlation between the number of pre-training networks and metrics such as Avg. Rank or Avg. AUC is weaker, with only negligible differences across settings. Notably, Hydra-32 consistently achieves the best or on-par performance across all classification benchmarks. For regression tasks, we observe a clearer scaling trend: performance steadily improves from Hydra-8 to Hydra-32 across all indicators. Specifically, #1st-*Place* increases with scale, while both Avg. Rank and Avg. MAE decrease, indicating better predictive performance. Hydra-32 consistently achieves the strongest results, with the highest #1st-*Place*, the lowest Avg. Rank, and the best average performance metric (i.e., highest Avg. AUC for classification and lowest Avg. MAE for regression). Given its consistent superiority across all six tasks, we adopt **Hydra-32** as our primary model and center our subsequent evaluation on its performance. For completeness, Table 8 in Appendix I reports the performance of all Hydra variants.

Computation and Time Efficiency. The per-snapshot complexity of Hydra reduces to a scalable $\mathcal{O}(N \cdot m + n \log n)$, where m is the number of edges, n is the number

(a) LLC Growth/Shrinkage

(b) Node Growth/Shrinkage

(c) Edge Growth/Shrinkage

(d) # Influential Node

(e) # New Nodes

(f) # Edges

Figure 3. Impact of scaling the number of training networks for Hydra (from 8 to 32) on classification and regression tasks. A clear scaling trend is observed in most cases, with **Hydra-32** consistently delivering the best performance across all tasks. Evaluation measures are #1^{st}-Place↑ (higher is better), *Avg. Rank↓* (lower is better), *Avg. AUC↑* (higher is better), and *Avg. MAE↓* (lower is better).

of nodes, and N is the number of Chebyshev moments used in the DOS module (see Appendix C for details). Because MiNT must be retrained separately for each task, training three tasks requires about three full runs on 64 networks. In contrast, Hydra trains all tasks jointly in a single run on 32 networks and achieves a 22× speedup, completing all three tasks in about 16,700 seconds compared to more than 370,000 seconds for MiNT (Figure 5a). This efficiency makes Hydra far more practical and scalable for multi-task training and inference.

Hydra inference time also shows a significant gain.

(a) **Total training cost for three classification tasks.** Hydra trains once for all tasks jointly, while MiNT must be retrained separately for each task. The dashed line indicates that MiNT is evaluated at 64 networks, while Hydra 's best result occurs at 32 networks.

(b) **Inference cost on TRAC dataset.** Hydra performs a single zero-shot classification pass for all three tasks jointly, whereas single-network baselines require full training before they can be used for inference, even on a single task (LCC–G/S here); reported times reflect the cost of inference on an unseen network using Hydra versus single models.

Figure 4. **Training and inference efficiency of Hydra.** (a) Hydra reduces training cost by avoiding retraining. (b) Hydra drastically lowers inference time by requiring only one forward pass.

Hydra requires only a single zero-shot inference pass to predict all three tasks on an unseen network, completing end-to-end evaluation on the largest test network (TRAC) in about 56 seconds (see Figure 5b). Single-network baselines, in contrast, require retraining from scratch for every dataset and task before they can be used for inference, with training times ranging from several thousand seconds to over 9,000 seconds even for a single task. Extending these models to multiple tasks or multiple networks multiplies the cost linearly, making them infeasible at scale. Hydra 's design eliminates the need for repeated training and heavy preprocessing, providing unique efficiency in both training and inference.

We also analyze how the number of networks used during the pre-training of Hydra affects its performance in predicting the characteristics of unseen networks at inference time. The results are presented in Fig. 3. For classification tasks, we observe that increasing the number of training networks generally leads to a higher #1^{st}-Place. This metric is a strong indicator of performance, as it reflects the number of unseen networks on which the model achieves the best results at inference time. In contrast, the correlation between the number of pre-training networks and metrics such as Avg. Rank or Avg. AUC is weaker, with only negligible differences across settings. Notably, Hydra-32 consistently achieves the best or on-par performance across all classification benchmarks. For regression tasks, we observe a clearer scaling trend: performance steadily improves from Hydra-8 to Hydra-32 across all indicators. Specifically, #1^{st}-Place increases with scale, while both Avg. Rank and Avg. MAE decrease, indicating better predictive performance. Hydra-32 consistently achieves the strongest results, with the highest #1^{st}-Place, the lowest Avg. Rank, and the best average performance metric (i.e., highest Avg. AUC for classification and lowest Avg. MAE for regression). Given its consistent superiority across all six tasks, we adopt **Hydra-32** as our primary

model and center our subsequent evaluation on its performance. For completeness, Table 8 in Appendix I reports the performance of all `Hydra` variants.

(a) **Total training cost for three classification tasks.** `Hydra` trains once for all tasks jointly, while MiNT must be retrained separately for each task. The dashed line indicates that MiNT is evaluated at 64 networks, while `Hydra`'s best result occurs at 32 networks.

(b) **Inference cost on TRAC dataset.** `Hydra` performs a single zero-shot classification pass for all three tasks jointly, whereas single-network baselines require full training before they can be used for inference, even on a single task (LCC–G/S here); reported times reflect the cost of inference on an unseen network using `Hydra` versus single models.

Figure 5. **Training and inference efficiency of `Hydra`.** (a) `Hydra` reduces training cost by avoiding retraining. (b) `Hydra` drastically lowers inference time by requiring only one forward pass.

Computation and Time Efficiency. The per-snapshot complexity of `Hydra` reduces to a scalable $\mathcal{O}(N \cdot m + n \log n)$, where m is the number of edges, n is the number of nodes, and N is the number of Chebyshev moments used in the DOS module (see Appendix C for details). Because MiNT must be retrained separately for each task, training three tasks requires about three full runs on 64 networks. In contrast, `Hydra` trains all tasks jointly in a single run on 32 networks and achieves a $22\times$ speedup, completing all three tasks in about 16,700 seconds compared to more than 370,000 seconds for MiNT (Figure 5a). This efficiency makes `Hydra` far more practical and scalable for multi-task training and inference.

`Hydra` inference time also shows a significant gain. `Hydra` requires only a single zero-shot inference pass to predict all three tasks on an unseen network, completing end-to-end evaluation on the largest test network (TRAC) in about 56 seconds (see Figure 5b). Single-network baselines, in contrast, require retraining from scratch for every dataset and task before they can be used for inference, with training times ranging from several thousand seconds to over 9,000 seconds even for a single task. Extending these models to multiple tasks or multiple networks multiplies the cost linearly, making them infeasible at scale. `Hydra`'s design eliminates the need for repeated training and heavy preprocessing, providing unique efficiency in both training and inference.

Table 4. MAE of edge count prediction under one, two, and three task `Hydra` configurations, reported with standard deviations.

Dataset	`Hydra` (One Task)	`Hydra` (Two Tasks)	`Hydra` (Three Tasks)
MIR	$0.057 (\pm 0.004)$	$0.034 (\pm 0.002)$	$\mathbf{0.016} (\pm 0.005)$
DOGE2.0	$0.169 (\pm 0.016)$	$\mathbf{0.150} (\pm 0.015)$	$0.187 (\pm 0.008)$
MUTE	$0.053 (\pm 0.020)$	$0.067 (\pm 0.011)$	$\mathbf{0.021} (\pm 0.022)$
EVERMOON	$0.029 (\pm 0.021)$	$0.042 (\pm 0.010)$	$\mathbf{0.017} (\pm 0.000)$
DERC	$0.024 (\pm 0.016)$	$0.035 (\pm 0.010)$	$\mathbf{0.021} (\pm 0.003)$
ADX	$\mathbf{0.023} (\pm 0.010)$	$0.027 (\pm 0.006)$	$0.025 (\pm 0.008)$
HOICHI	$0.071 (\pm 0.006)$	$0.068 (\pm 0.011)$	$\mathbf{0.027} (\pm 0.020)$
SDEX	$0.060 (\pm 0.023)$	$\mathbf{0.046} (\pm 0.007)$	$0.095 (\pm 0.043)$
BAG	$0.061 (\pm 0.018)$	$0.067 (\pm 0.020)$	$\mathbf{0.041} (\pm 0.020)$
XCN	$0.037 (\pm 0.017)$	$\mathbf{0.026} (\pm 0.010)$	$0.062 (\pm 0.015)$
ETH2x-FLI	$0.030 (\pm 0.013)$	$0.038 (\pm 0.007)$	$\mathbf{0.023} (\pm 0.001)$
stkAAVE	$0.026 (\pm 0.008)$	$\mathbf{0.021} (\pm 0.003)$	$0.051 (\pm 0.022)$
GLM	$0.092 (\pm 0.009)$	$\mathbf{0.083} (\pm 0.017)$	$0.087 (\pm 0.008)$
QOM	$0.025 (\pm 0.003)$	$\mathbf{0.023} (\pm 0.005)$	$0.036 (\pm 0.013)$
WOJAK	$0.025 (\pm 0.023)$	$0.039 (\pm 0.017)$	$\mathbf{0.010} (\pm 0.004)$
DINO	$0.031 (\pm 0.018)$	$0.041 (\pm 0.010)$	$\mathbf{0.017} (\pm 0.007)$
Metis	$0.047 (\pm 0.014)$	$0.054 (\pm 0.016)$	$\mathbf{0.034} (\pm 0.010)$
REPv2	$0.103 (\pm 0.002)$	$\mathbf{0.102} (\pm 0.003)$	$0.111 (\pm 0.008)$
TRAC	$0.029 (\pm 0.016)$	$0.039 (\pm 0.012)$	$\mathbf{0.021} (\pm 0.001)$
BEPRO	$0.031 (\pm 0.025)$	$0.046 (\pm 0.012)$	$\mathbf{0.011} (\pm 0.008)$
Average	0.051	0.052	$\mathbf{0.046}$
Best Count	1	7	**12**

5. Impact of Multi-Task Training

To assess how multi-task learning shapes the shared temporal representation, we examine edge count prediction as a reference task and train three model variants: single-task (edge count only), two-task (edge count and new node count), and the full three-task `Hydra` configuration. Results are shown in Table 4. Performance on the reference task improves consistently as more tasks are added. The three-task model achieves the best results on 12 out of 20 datasets and the lowest overall average MAE, compared to 7 and 1 for the two-task and single-task variants respectively. These gains arise because additional tasks introduce complementary supervisory signals that encourage the shared trunk to learn richer temporal and structural patterns, demonstrating that multi-task supervision enhances rather than interferes with individual task performance in `Hydra`.

6. Conclusion

We have introduced `Hydra`, a novel temporal graph-level multi-task and multi-network model designed to address the complexities of dynamic network analysis. `Hydra` combines a spatial path, which captures local connectivity through temporal GNNs, along with a spectral path that attends to global structural patterns, forming a new architectural design for temporal graph learning. This unified framework enables `Hydra` to handle diverse prediction tasks simultaneously while transferring effectively to unseen networks. Empirically, `Hydra` consistently outperforms state-of-the-art baselines across benchmarks, achieving strong performance without requiring additional training on target networks. These results highlight `Hydra` as the first architecture to bring together spectral and spatial pathways for transferable, multi-task learning on temporal graphs. Looking ahead, this work opens up a promising research direction toward more generalizable temporal models that can support a wide range of tasks.

References

N. C. Abay, C. G. Akcora, Y. R. Gel, M. Kantarcioglu, U. D. Islambekov, Y. Tian, and B. Thuraisingham. Chainnet: Learning on blockchain graphs with topological features. In *2019 IEEE international conference on data mining (ICDM)*, pages 946–951. IEEE, 2019.

R. Caruana. Multitask learning. *Machine learning*, 28(1): 41–75, 1997.

H. Chen, H. Yin, X. Sun, T. Chen, B. Gabrys, and K. Musial. Multi-level graph convolutional networks for cross-platform anchor link prediction. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 1503–1511, 2020.

J. Chen, X. Wang, and X. Xu. GC-LSTM: graph convolution embedded LSTM for dynamic network link prediction. *Appl. Intell.*, 52(7):7513–7528, 2022a. doi: 10.1007/S10489-021-02518-9. URL https://doi.org/10.1007/s10489-021-02518-9.

Y. Chen, T. Shu, X. Zhou, X. Zheng, A. Kawai, K. Fueda, Z. Yan, W. Liang, and K. I.-K. Wang. Graph attention network with spatial-temporal clustering for traffic flow forecasting in intelligent transportation system. *IEEE Transactions on Intelligent Transportation Systems*, 24 (8):8727–8737, 2022b.

K. Cho, B. Van Merriënboer, D. Bahdanau, and Y. Bengio. On the properties of neural machine translation: Encoder-decoder approaches. *arXiv preprint arXiv:1409.1259*, 2014.

F. Cornell, O. Smirnov, G. Z. Gandler, and L. Cao. On the power of heuristics in temporal graphs. In A. Blaas, P. D'Costa, F. Feng, A. Kriegler, I. Mason, Z. Pan, T. Uelwer, J. Williams, Y. Xie, and R. Yang, editors, *Proceedings on "I Can't Believe It's Not Better: Challenges in Applied Deep Learning" at ICLR 2025 Workshops*, volume 296 of *Proceedings of Machine Learning Research*, pages 37–46. PMLR, 28 Apr 2025. URL https://proceedings.mlr.press/v296/cornell25a.html.

M. Crawshaw. Multi-task learning with deep neural networks: A survey. *arXiv preprint arXiv:2009.09796*, 2020.

K. Dong, A. R. Benson, and D. Bindel. Network density of states. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1152–1161, 2019.

Y. Duan, G. Zhang, S. Wang, X. Peng, W. Ziqi, J. Mao, H. Wu, X. Jiang, and K. Wang. Cat-gnn: Enhancing credit card fraud detection via causal temporal graph

neural networks. *arXiv preprint arXiv:2402.14708*, 2024.

C. Gurcan Akcora, M. Kantarcioglu, and Y. R. Gel. Blockchain networks: Data structures of bitcoin, monero, zcash, ethereum, ripple and iota. *arXiv e-prints*, pages arXiv–2103, 2021.

M. M. Hosseinzadeh, M. Cannataro, P. H. Guzzi, and R. Dondi. Temporal networks in biology and medicine: a survey on models, algorithms, and tools. *Network Modeling Analysis in Health Informatics and Bioinformatics*, 12(1):10, 2022.

Q. Huang, X. Wang, S. X. Rao, Z. Han, Z. Zhang, Y. He, Q. Xu, Y. Zhao, Z. Zheng, and J. Jiang. Benchtemp: A general benchmark for evaluating temporal graph neural networks. In *2024 IEEE 40th International Conference on Data Engineering (ICDE)*, pages 4044–4057. IEEE, 2024.

S. Huang, F. Poursafaei, J. Danovitch, M. Fey, W. Hu, E. Rossi, J. Leskovec, M. Bronstein, G. Rabusseau, and R. Rabbany. Temporal graph benchmark for machine learning on temporal graphs. *Advances in Neural Information Processing Systems*, 36:2056–2073, 2023a.

S. Huang, F. Poursafaei, J. Danovitch, M. Fey, W. Hu, E. Rossi, J. Leskovec, M. M. Bronstein, G. Rabusseau, and R. Rabbany. Temporal graph benchmark for machine learning on temporal graphs. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine, editors, *NeurIPS 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023b.

V. Jalili. The temporal graph of bitcoin transactions. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025. URL https://openreview.net/forum?id=Xs7JM4VGHv.

W. Jin, X. Liu, X. Zhao, Y. Ma, N. Shah, and J. Tang. Automated self-supervised learning for graphs. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=rFbR4Fv-D6-.

M. Ju, T. Zhao, Q. Wen, W. Yu, N. Shah, Y. Ye, and C. Zhang. Multi-task self-supervised graph neural networks enable stronger task generalization. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=1tHAZRqftM.

S. M. Kazemi, R. Goel, K. Jain, I. Kobyzev, A. Sethi, P. Forsyth, and P. Poupart. Representation learning for dynamic graphs: A survey. *Journal of Machine Learning Research*, 21(70):1–73, 2020.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In Y. Bengio and Y. LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

T. Kipf. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

K. Klaser, B. Banaszewski, S. Maddrell-Mander, C. McLean, L. Müller, A. Parviz, S. Huang, and A. W. Fitzgibbon. Minimol: A parameter-efficient foundation model for molecular learning. In *ICML 2024 Workshop on Efficient and Accessible Foundation Models for Biological Discovery*, 2024.

J. Lee, I. Lee, and J. Kang. Self-attention graph pooling. In *International conference on machine learning*, pages 3734–3743. pmlr, 2019.

R. Levie, W. Huang, L. Bucci, M. Bronstein, and G. Kutyniok. Transferability of spectral graph convolutional neural networks. *Journal of Machine Learning Research*, 22(272):1–59, 2021.

Y. Liang, H. Wen, Y. Xia, M. Jin, B. Yang, F. Salim, Q. Wen, S. Pan, and G. Cong. Foundation models for spatio-temporal data science: A tutorial and survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*, pages 6063–6073, 2025.

Y. Luo, L. Shi, and X.-M. Wu. Can classic GNNs be strong baselines for graph-level tasks? simple architectures meet excellence. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=ZH7YgIZ3DF.

B. Mohar, Y. Alavi, G. Chartrand, and O. Oellermann. The laplacian spectrum of graphs. *Graph theory, combinatorics, and applications*, 2(871-898):12, 1991.

R. Nassif, S. Vlaski, C. Richard, J. Chen, and A. H. Sayed. Multitask learning over graphs: An approach for distributed, streaming machine learning. *IEEE Signal Processing Magazine*, 37(3):14–25, 2020.

S. Ockerman, A. Gueroudji, T. Mallick, Y. He, L. Pouchard, R. Ross, and S. Venkataraman. Pgt-i: Scaling spatiotemporal gnns with memory-efficient distributed training, 2025. URL https://arxiv.org/abs/2507.11683.

J. Pan, M. Nayyeri, O. Mohammed, D. Hernandez, R. Zhang, C. Cheng, and S. Staab. Towards foundation model on temporal knowledge graph reasoning. *arXiv preprint arXiv:2506.06367*, 2025.

A. Pareja, G. Domeniconi, J. Chen, T. Ma, T. Suzumura, H. Kanezashi, T. Kaler, T. B. Schardl, and C. E. Leiserson. Evolvegcn: Evolving graph convolutional networks for dynamic graphs. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 5363–5370. AAAI Press, 2020. doi: 10.1609/AAAI.V34I04.5984. URL https://doi.org/10.1609/aaai.v34i04.5984.

Y. Qi, J. Wu, H. Xu, and M. Guizani. Blockchain data mining with graph learning: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(2):729–748, 2023.

R. Ranjan, V. Hudovernik, M. Znidar, C. I. Kanatsoulis, R. R. Upendra, M. Mohammadi, J. Meyer, T. Palczewski, C. Guestrin, and J. Leskovec. Relational transformer: Toward zero-shot foundation models for relational data. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=rpPtgMC5s9.

E. Rossi, B. Chamberlain, F. Frasca, D. Eynard, F. Monti, and M. Bronstein. Temporal graph networks for deep learning on dynamic graphs. *arXiv preprint arXiv:2006.10637*, 2020.

S. Ruder. An overview of multi-task learning in deep neural networks. *arXiv preprint arXiv:1706.05098*, 2017.

L. Ruiz, L. F. Chamon, and A. Ribeiro. Transferability properties of graph neural networks. *IEEE Transactions on Signal Processing*, 71:3474–3489, 2023.

Z. A. Sahili and M. Awad. Spatio-temporal graph neural networks: A survey. *arXiv preprint arXiv:2301.10569*, 2023.

O. Sener and V. Koltun. Multi-task learning as multi-objective optimization. *Advances in neural information processing systems*, 31, 2018.

A. Senthilkumar, M. Gupte, and S. Shridevi. Dynamic spatial-temporal graph model for disease prediction. *International Journal of Advanced Computer Science and Applications*, 13(6), 2022.

K. Shamsi, F. Poursafaei, S. Huang, B. T. G. Ngo, B. Coskunuzer, and C. G. Akcora. Graphpulse: Topological representations for temporal graph property prediction. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=DZqic2sPTY.

K. Shamsi, T. G. B. Ngo, R. Shirzadkhani, S. Huang, F. Poursafaei, P. Azad, R. Rabbany, B. Coskunuzer, G. Rabusseau, and C. G. Akcora. Mint: Multi-network transfer benchmark for temporal graph learning. *NeurIPS*, 2025.

W. Shi, Z. Wen, Q. Zhang, C. Zhang, and Z. Zhang. Temporal graph thumbnail: Robust representation learning with global evolutionary skeleton. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=a4e0zoaiD8.

M. Sypetkowski, F. Wenkel, F. Poursafaei, N. Dickson, K. Suri, P. Fradkin, and D. Beaini. On the scalability of gnns for molecular graphs. *arXiv preprint arXiv:2404.11568*, 2024.

H. Tang, S. Wu, X. Sun, J. Zeng, G. Xu, and Q. Li. Tcgc: Temporal collaboration-aware graph co-evolution learning for dynamic recommendation. *ACM Transactions on Information Systems*, 43(1):1–27, 2025.

M. J. Uddin, S. Changani, and B. Coskunuzer. T3former: Temporal graph classification with topological machine learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 26028–26036, 2026.

S. Wang, J. Cao, and S. Y. Philip. Deep learning for spatio-temporal data mining: A survey. *IEEE transactions on knowledge and data engineering*, 34(8):3681–3700, 2020.

Y. Wang, W. Fan, S. Wang, and Y. Ma. Towards graph foundation models: A transferability perspective. *arXiv preprint arXiv:2503.09363*, 2025.

Z. Wang, X. Wang, and H. Wang. Temporal graph neural networks for money laundering detection in cross-border transactions. *Academia Nexus Journal*, 3(2), 2024.

A. Weiße, G. Wellein, A. Alvermann, and H. Fehske. The kernel polynomial method. *Reviews of modern physics*, 78(1):275–306, 2006.

O. Wieder, S. Kohlbacher, M. Kuenemann, A. Garon, P. Ducrot, T. Seidel, and T. Langer. A compact review of molecular property prediction with graph neural networks. *Drug Discovery Today: Technologies*, 37:1–12, 2020.

M. Yang, M. Zhou, M. Kalander, Z. Huang, and I. King. Discrete-time temporal network embedding via implicit hierarchical learning in hyperbolic space. In F. Zhu, B. C. Ooi, and C. Miao, editors, *KDD '21: The 27th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Virtual Event, Singapore, August 14-18, 2021*, pages 1975–1985. ACM, 2021. doi: 10.1145/3447548.3467422. URL https://doi.org/10.1145/3447548.3467422.

M. Yang, W. Feng, Y. Shen, and B. Hooi. Towards better graph representation learning with parameterized decomposition & filtering. In *International Conference on Machine Learning*, pages 39234–39251. PMLR, 2023.

C. Ying, T. Cai, S. Luo, S. Zheng, G. Ke, D. He, Y. Shen, and T. Liu. Do transformers really perform badly for graph representation? In M. Ranzato, A. Beygelzimer, Y. N. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 28877–28888, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/f1c1592588411002af340cbaedd6fc33-Abstract.html.

J. You, T. Du, and J. Leskovec. Roland: graph learning framework for dynamic graphs. In *Proceedings of the 28th ACM SIGKDD conference on knowledge discovery and data mining*, pages 2358–2366, 2022.

T. Yu, S. Kumar, A. Gupta, S. Levine, K. Hausman, and C. Finn. Gradient surgery for multi-task learning. *Advances in neural information processing systems*, 33: 5824–5836, 2020.

Y. Zhang and Q. Yang. An overview of multi-task learning. *National Science Review*, 5(1):30–43, 2018.

Y. Zhang and Q. Yang. A survey on multi-task learning. *IEEE transactions on knowledge and data engineering*, 34(12):5586–5609, 2021.

L. Zhao, Y. Song, C. Zhang, Y. Liu, P. Wang, T. Lin, M. Deng, and H. Li. T-gcn: A temporal graph convolutional network for traffic prediction. *IEEE transactions on intelligent transportation systems*, 21(9):3848–3858, 2019.

L. Zhao, Y. Song, C. Zhang, Y. Liu, P. Wang, T. Lin, M. Deng, and H. Li. T-GCN: A temporal graph convolutional network for traffic prediction. *IEEE Trans. Intell. Transp. Syst.*, 21(9):3848–3858, 2020. doi: 10.1109/TITS.2019.2935152. URL https://doi.org/10.1109/TITS.2019.2935152.

J. Zhu, A. Khan, and C. G. Akcora. Data depth and core-based trend detection on blockchain transaction networks. *Frontiers Blockchain*, 7, 2024. doi: 10.3389/ FBLOC.2024.1342956. URL https://doi.org/ 10.3389/fbloc.2024.1342956.

Y. Zhu, F. Cong, D. Zhang, W. Gong, Q. Lin, W. Feng, Y. Dong, and J. Tang. Wingnn: Dynamic graph neural networks with random gradient aggregation window. In *KDD*, pages 3650–3662, 2023. URL https://doi. org/10.1145/3580305.3599551.

Appendix

A. Limitations

In this work, we propose `Hydra`, a novel architecture for multi-task temporal graph property prediction. Due to the inherent difficulty of collecting a large number of open-sourced social or interaction networks, we focus on transaction networks provided from (Shamsi et al., 2025). Future datasets with a larger selection of different network types might provide a further performance boost for `Hydra`.

Here, we also focus on the graph property prediction task as we expect that the model should be able to learn the evolution of the global graph structure and transfer such learning across networks. One limitation is that there is less exploration for other tasks, such as link prediction and node classification. This is also partly due to the nature of the dataset, where many nodes are transient and only appear once in a network, it is more difficult to generalize and predict the behaviour of these one-time nodes.

B. Broader Impact

This work advances temporal graph learning by enabling a single model to handle multiple tasks and transfer across networks without retraining. This capability reduces computational cost and improves the transferability of TGNNs, with potential impact in areas such as network security, financial fraud detection, and real-time social network analysis, where evolving systems require continuously adaptive, multi-objective modelling.

Moreover, the principles of multi-network and multi-task pre-training introduced here may inspire similar advances in other temporal data domains, including healthcare, transportation, and climate science. More broadly, this work opens a new direction toward generalizable temporal graph models that can be trained across distinct networks, taking an important step toward Temporal Graph Foundation Models.

C. Computational Complexity of **Hydra**

For a snapshot $G_t = (V_t, E_t)$ with $n = |V_t|$ nodes and $m = |E_t|$ edges, the per-snapshot complexity of `Hydra` is

$$\mathcal{O}\big(m \cdot d + n \cdot d^2 + n \cdot \log n + N \cdot m + K \cdot d\big),$$

where d is the hidden dimension, K is the number of task-specific heads, and N is the number of Chebyshev moments used in the kernel polynomial method approximation of the DOS. The term $m \cdot d$ arises from spatial message passing, since each edge propagates a d-dimensional embedding. The term $n \cdot d^2$ comes from recurrent or attention-based updates. Pooling with top-k selection contributes $n \cdot \log n$, reflecting the computation of attention scores for all nodes followed by partial sorting. The spectral DOS module adds $N \cdot m$, as each moment requires one sparse matrix–vector multiplication. Finally, the cost of task-specific heads is $K \cdot d$. Over N networks with T snapshots each, the overall training cost scales as

$$\mathcal{O}\big(N \cdot T\,[\,m \cdot (d + N) + n \cdot d^2 + n \cdot \log n + K \cdot d\,]\big).$$

In our implementation, the spatial hidden dimension is fixed to 16, the DOS descriptor dimension is 20, and we train with $K = 3$ task-specific heads. Substituting these values, the per-snapshot complexity of `Hydra` becomes

$$\mathcal{O}\big(16 \cdot m + 256 \cdot n + n \log n + N \cdot m + 108\big),$$

where $m = |E_t|$ and $n = |V_t|$. The terms correspond to spatial message passing ($16 \cdot m$), recurrent/attention updates ($256 \cdot n$), pooling with top-k selection ($n \log n$), DOS spectral approximation with N Chebyshev moments ($N \cdot m$), and three task heads on a 36-dimensional joint embedding (108). For each snapshot, the overall training complexity scales as

$$\mathcal{O}\big(((16 + N)\,m + 256\,n + n \log n)\big).$$

In practice, with hidden size and Chebyshev moment parameters fixed, the per-snapshot complexity of `Hydra` reduces to $\mathcal{O}(N \cdot m + n \log n)$, dominated by sparse matrix–vector multiplications in the DOS module.

D. Dataset

We evaluate `Hydra` on temporal transaction networks from the MiNT benchmark (Shamsi et al., 2025), the first large-scale dataset designed for training and evaluating temporal graph models across multiple heterogeneous networks. MiNT contains 84 ERC-20 token transaction graphs collected from the Ethereum blockchain between 2017 and 2023, spanning more than six years of activity. The biggest MiNT token network contains $128, 159$ unique addresses and $554, 705$ transactions, while the smallest token network has $1, 454$ nodes. Each network is represented as a sequence of weekly snapshots, where nodes correspond to wallet addresses and edges represent token transfers. Across their full duration, networks range from tens of thousands to over 100K unique nodes and up to several million edges, reflecting the scale of real-world token ecosystems.

A distinctive feature of MiNT is its strong inductiveness: new addresses and transactions appear continuously, making prediction inherently open-world. This reflects the real behavior of blockchain networks, where adoption cycles,

liquidity shocks, and market events constantly introduce novel participants and structural patterns. The long temporal duration further amplifies this effect, as networks exhibit bursts of rapid growth, periods of stagnation, and sudden fragmentation or collapse. Such novelty and surprise factors make MiNT particularly challenging, as models must generalize across highly dynamic trajectories rather than stationary or repetitive patterns.

We summarize detailed statistics of each token network in MiNT datasets in Table 5. Most networks have more than 10k nodes and over 100k edges. The lifespan of MiNT networks varies from 107 days to 6 years, and there exists at least one transaction each day. As the table shows, the token networks have quite high surprise values with an average of 0.82.

For our experiments, we follow the MiNT protocol and split the dataset into 64 financial networks for training and 20 additional networks for unseen testing. This setup allows Hydra to learn transferable temporal representations from diverse source networks and evaluate zero-shot generalization on new target networks that are only available at inference time.

E. Baselines

In this section, we give further details about the temporal graph learning models we used as a baseline for our work.

TGCN (Zhao et al., 2020) is a combination of GCN and GRU. In particular, GCN is used to learn complex topological structures, while GRU is used to model embedding dynamically to capture temporal dependence.

HTGN (Yang et al., 2021) leverages the power of hyperbolic geometry, which is well-suited for capturing hierarchical structures and complex relationships in temporal networks. HTGN maps the temporal graph into hyperbolic space and utilizes hyperbolic graph neural networks and hyperbolic gated recurrent neural networks to model the evolving dynamics. It incorporates two key modules that are hyperbolic temporal contextual self-attention (HTA) and hyperbolic temporal consistency (HTC)-to ensure that temporal dependencies are effectively captured and that the model is both stable and generalizable across various tasks.

GraphPulse (Shamsi et al., 2024) addresses the challenge of learning from nodes and edges with different timestamps, which many existing models struggle with. It combines two key techniques: the Mapper method from topological data analysis to extract clustering information from graph nodes and Recurrent Neural Networks (RNNs) for temporal reasoning. This principled approach helps capture both the structure and dynamics of evolving graphs.

GCLSTM (Chen et al., 2022a) combines a Graph Con-

volutional Network (GCN) and Long Short-Term Memory (LSTM) units to handle both the structural and temporal aspects of evolving networks. The GCN is used to capture the local structural properties of the network at each snapshot, while the LSTM learns the temporal evolution of these snapshots over time.

EvolveGCN (Pareja et al., 2020) is designed to capture the temporal dynamics of graph-structured data. Instead of relying on static node embeddings, EvolveGCN evolves the parameters of a graph convolutional network (GCN) over time. By using a recurrent neural network (RNN) to adapt the GCN parameters, this model is capable of dynamically adjusting during both training and testing, allowing it to handle evolving graphs, even when node sets vary significantly across different time steps.

ROLAND (You et al., 2022) is a dynamic graph learning framework that models node representations as hierarchical states, updated recurrently to capture temporal dependencies in evolving graphs. It supports scalable training using techniques like truncated backpropagation through time and meta-learning. In our DTDG setting, we use ROLAND to benchmark its performance and adaptability across diverse temporal networks.

WinGNN (Zhu et al., 2023) uses a simple GNN to model topological information from the graph as other models existing in the literature. However, to model temporal dependencies, WinGNN proposes a novel mechanism of random gradient aggregation and meta learning strategy. In particular, WinGNN computes the frame-wise loss of the current snapshot and passes the loss gradient to the next to model graph dynamics without using RNN-based modules. Then it introduces the randomized sliding-window to acquire the windowaware gradienton consecutive snapshots, and the calculated two types of gradient are aggregated to update the GNN modules.

F. Task Formalizations

In this section, we provide detailed definitions for all classification and regression tasks considered in Hydra. Each temporal snapshot corresponds to a 7-day interval, and the property prediction setup follows GraphPulse (Shamsi et al., 2024). We also note that some of these tasks and the corresponding labels were processed specifically for this work, ensuring consistency and comparability across networks.

Setting $n = 7$, $\delta_1 = 3$, and $\delta_2 = 10$ days, we establish a practical graph property with a 7-day prediction window. This choice is particularly relevant in financial contexts, such as Ethereum asset networks, where it can guide investment decisions (Abay et al., 2019).

Table 5. All token networks' statistics.

Token	#Node	#Transaction	#Snapshots (days)	Growth rate	Novelty	Surprise	Token	#Node	#Transaction	#Snapshots (days)	Growth rate	Novelty	Surprise
ARC	11325	70968	606	0.43	0.32	0.88	Metis	52586	343141	907	0.44	0.48	0.89
CELR	65350	235807	1691	0.49	0.56	0.96	cDAI	52753	358050	1437	0.45	0.46	0.9
CMT	86895	205961	309	0.45	0.72	0.92	BITCOIN	34051	347054	178	0.48	0.39	0.63
DRGN	113453	341849	2164	0.44	0.57	0.97	INJ	60472	312822	1113	0.46	0.52	0.98
GHST	35156	180955	1146	0.43	0.51	0.93	MIM	23038	269366	885	0.44	0.4	0.89
INU	8556	66315	154	0.27	0.41	0.59	GLM	53385	234912	1080	0.5	0.53	0.96
IOTX	63079	288469	1993	0.45	0.56	0.99	Mog	14590	240680	107	0.37	0.38	0.55
QSP	117977	299671	2178	0.45	0.67	0.99	DPI	40627	234246	1150	0.49	0.5	0.86
REP	83282	224843	346	0.46	0.69	0.96	LINA	45342	227147	1144	0.45	0.46	0.95
RFD	23208	173695	169	0.3	0.39	0.6	Yf-DAI	22466	226875	1158	0.42	0.31	0.87
TNT	88247	316352	1216	0.43	0.55	0.93	BOB	42806	212099	199	0.35	0.48	0.73
TRAC	71667	299181	2110	0.46	0.54	0.97	RGT	35277	211932	1110	0.44	0.46	0.98
RLB	28033	240291	129	0.43	0.49	0.76	TVK	42539	208082	1062	0.41	0.48	0.93
steCRV	19079	211538	1033	0.45	0.53	0.9	RSR	50645	205906	659	0.47	0.62	0.91
ALBT	63042	434881	1152	0.43	0.44	0.89	WOJAK	34341	198653	201	0.37	0.48	0.73
POLS	128159	554705	1132	0.45	0.61	0.94	ANT	36517	200262	1107	0.47	0.46	0.93
SWAP	69230	509769	1213	0.46	0.45	0.79	LADYS	37486	192176	181	0.37	0.52	0.79
SUPER	83299	502030	986	0.47	0.46	0.85	ETH2x-FLI	11008	199088	965	0.47	0.28	0.84
RARI	87186	502960	1207	0.43	0.47	0.91	TURBO	38638	189048	189	0.33	0.48	0.72
KP3R	39323	493258	1102	0.43	0.33	0.88	REPv2	39061	191367	1194	0.48	0.5	0.97
MIR	79984	444998	1066	0.45	0.43	0.92	NOIA	29798	185528	1133	0.46	0.37	0.7
aUSDC	23742	475680	1067	0.46	0.4	0.73	0x0	21531	182430	283	0.51	0.46	0.81
LUSD	25852	430473	943	0.48	0.36	0.87	PSYOP	25450	168896	169	0.32	0.39	0.59
PICKLE	28498	430262	1149	0.48	0.34	0.69	ShibDoge	40023	134697	680	0.43	0.53	0.8
DODO	47046	390443	1131	0.47	0.45	0.91	ADX	14567	123755	1188	0.44	0.4	0.91
YFII	43964	391984	1196	0.44	0.44	0.96	BAG	11860	122634	298	0.31	0.44	0.87
STARL	71590	369913	856	0.46	0.48	0.86	QOM	21757	118292	598	0.46	0.48	0.81
LQTY	34687	374230	943	0.45	0.34	0.91	BEPRO	26521	120261	1132	0.46	0.48	0.87
FEG	118294	367584	1007	0.4	0.62	0.92	AIOZ	29231	119926	947	0.43	0.49	0.89
AUDIO	91218	362685	1108	0.45	0.58	0.95	PRE	40476	118625	1113	0.5	0.55	0.86
OHM	45728	377068	690	0.43	0.46	0.88	CRU	19990	117712	1144	0.5	0.43	0.95
WOOL	16874	351178	716	0.41	0.18	0.41	POOH	27245	111641	193	0.26	0.49	0.69
DERC	24277	111205	824	0.45	0.49	0.83	aDAI	13648	187050	1068	0.45	0.46	0.82
stkAAVE	37355	110924	1128	0.42	0.57	0.71	ORN	44010	239451	1134	0.46	0.47	0.87
BTRFLY	8450	108371	453	0.48	0.34	0.44	DOGE2.0	7664	79047	123	0.45	0.38	0.66
SDEX	9127	104869	240	0.41	0.44	0.75	HOICHI	5075	77361	436	0.36	0.32	0.71
XCN	20085	104185	607	0.46	0.42	0.84	EVERMOON	7552	79868	163	0.24	0.35	0.52
HOP	37004	102650	514	0.41	0.6	0.88	MUTE	12426	82345	977	0.43	0.46	0.95
MAHA	18401	96180	749	0.43	0.47	0.91	crvUSD	2950	88647	174	0.61	0.37	0.73
DINO	15837	94140	358	0.44	0.44	0.74	SLP	6675	95368	1151	0.43	0.36	0.91
bendWETH	1454	96898	593	0.51	0.21	0.51	sILV2	12838	92905	611	0.4	0.34	0.48
PUSH	14501	93103	936	0.46	0.38	0.83	SPONGE	25852	90468	184	0.31	0.66	0.81

F.1. Classification Tasks

Node Growth/Shrinkage (Node G/S). Let $V(t_1, t_n)$ denote the set of unique nodes active between times t_1 and t_n. The task predicts whether the number of nodes increases in the prediction interval $[t_{n+\delta_1}, t_{n+\delta_2}]$:

$$P_{\text{nodes}}(\mathcal{G}, t_1, t_n, \delta_1, \delta_2) = \begin{cases} 1, & \text{if } |V(t_{n+\delta_1}, t_{n+\delta_2})| > |V(t_1, t_n)|, \\ 0, & \text{otherwise.} \end{cases}$$
(1)

Importance. Node growth measures adoption, reflecting the entry of new addresses, while shrinkage signals attrition. In token ecosystems, this corresponds to market expansion or decline.

Edge Growth/Shrinkage (Edge G/S). Let $E(t_1, t_n)$ denote the set of transactions in $[t_1, t_n]$. The model predicts whether transaction activity grows in the next interval:

$$P_{\text{edges}}(\mathcal{G}, t_1, t_n, \delta_1, \delta_2) = \begin{cases} 1, & \text{if } |E(t_{n+\delta_1}, t_{n+\delta_2})| > |E(t_1, t_n)|, \\ 0, & \text{otherwise.} \end{cases}$$
(2)

Importance. Edge growth captures changes in liquidity and market engagement, with direct implications for trading activity and token valuation.

Largest Connected Component Growth/Shrinkage (LCC G/S). Let $C(t_1, t_n)$ denote the size of the largest connected component during $[t_1, t_n]$. The task is to predict whether connectivity expands:

$$P_{\text{LCC}}(\mathcal{G}, t_1, t_n, \delta_1, \delta_2) = \begin{cases} 1, & \text{if } |C(t_{n+\delta_1}, t_{n+\delta_2})| > |C(t_1, t_n)|, \\ 0, & \text{otherwise.} \end{cases}$$
(3)

Importance. LCC growth reflects stronger structural integration, improving liquidity and market stability in blockchain networks.

F.2. Regression Tasks

New Node Count. Let $V_{\text{new}}(t_{n+\delta_1}, t_{n+\delta_2})$ denote the set of nodes that appear for the first time in the prediction interval. The regression target is:

$$\hat{y}_{\text{new-nodes}}(\mathcal{G}, t_1, t_n, \delta_1, \delta_2) = |V_{\text{new}}(t_{n+\delta_1}, t_{n+\delta_2})|. \quad (4)$$

Importance. New node prediction quantifies adoption and user acquisition, a key indicator of ecosystem growth.

Edge Count. The task is to predict the number of transactions in the future interval:

$$\hat{y}_{\text{edges}}(\mathcal{G}, t_1, t_n, \delta_1, \delta_2) = |E(t_{n+\delta_1}, t_{n+\delta_2})|. \quad (5)$$

Importance. Transaction forecasts provide fine-grained estimates of liquidity and demand surges in decentralized markets.

Influential Node Count. Define influential nodes as those with a degree greater than 5 in the prediction interval. Empirically, degree distributions of ERC-20 token graphs are heavy-tailed (Shamsi et al., 2025): most nodes appear only once or twice, and a small fraction appear hundreds or thousands of times. When we plot the cumulative distribution of node degrees, there is usually a sharp drop in frequency after degree 1–2, followed by a long but thinner tail. Setting the threshold at 5 sits just beyond this long tail cutoff, ensuring that only the top 10–20% of nodes in activity are retained as influential. In practice, this excludes wallets that perform only a handful of transfers while capturing the repeat participants who actually shape liquidity and flow.

Let $V_{\text{inf}}(t_{n+\delta_1}, t_{n+\delta_2}) = \{v \in V : \deg(v) > 5\}$. The regression target is:

$$\hat{y}_{\text{inf}}(\mathcal{G}, t_1, t_n, \delta_1, \delta_2) = |V_{\text{inf}}(t_{n+\delta_1}, t_{n+\delta_2})|. \quad (6)$$

Importance. Influential nodes represent hubs such as active traders, liquidity providers, or contracts, which shape the stability and price dynamics of token ecosystems.

F.3. Importance of Temporal Property Prediction

Monitoring global structural dynamics in temporal graphs is essential in domains where the evolution of the entire network, rather than individual edges, drives operational decisions. In blockchain transaction networks, most transactions occur only once and do not repeat, so link-level prediction is not informative. Graph properties instead track global indicators such as changes in connectivity, activity, and influential participants, which often serve as early signals of liquidity risk, instability, or ecosystem decline (Abay et al., 2019; Gurcan Akcora et al., 2021). Since thousands of Ethereum-based tokens evolve with their own user bases and activity patterns (Zhu et al., 2024), training a separate temporal model for each network is not practical. A single model that learns from many heterogeneous networks and jointly predicts several graph properties offers a more scalable and informative solution. Similar considerations arise in communication, payment, and social systems, where forecasting network-level behaviors helps detect anomalies, anticipate demand, and understand system health (Kazemi et al., 2020). A multi-task approach is particularly valuable because these properties move together and provide complementary signals, leading to more reliable and actionable predictions than solving each task independently.

G. Evaluation Metrics

We evaluate models using both performance scores and ranking-based statistics. Below we provide formal definitions of each metric used in the main paper.

First-Place Count. For a given task, the *first-place count* measures how often a method achieves the top performance across datasets. Let $\mathcal{D}$ denote the set of datasets and $\mathcal{M}$ the set of methods. For dataset $d \in \mathcal{D}$, let $m^*(d) = \arg\max_{m \in \mathcal{M}} \mathrm{Perf}(m, d)$, where $\mathrm{Perf}(m, d)$ is the task-specific score (AUC for classification, MAE for regression). Then the first-place count for method m is $\mathrm{First}(m) = \sum_{d \in \mathcal{D}} \mathbf{1}[m = m^*(d)]$.

Average Rank. Each method is ranked per dataset according to performance. Let $\mathrm{rank}(m, d)$ be the rank of method m on dataset d (lower is better). The average rank of method m is $\mathrm{AvgRank}(m) = \frac{1}{|\mathcal{D}|} \sum_{d \in \mathcal{D}} \mathrm{rank}(m, d)$.

Average AUC (Classification). For binary classification, the Area Under the ROC Curve (AUC) for dataset d is $\mathrm{AUC}(d) = \mathrm{Pr}\big(\hat{y}_i > \hat{y}_j \,\big|\, y_i = 1,\, y_j = 0\big)$, where $\hat{y}_i$ are predicted scores and $y_i \in \{0, 1\}$ are ground-truth labels. The average AUC of method m is $\mathrm{AvgAUC}(m) = \frac{1}{|\mathcal{D}|} \sum_{d \in \mathcal{D}} \mathrm{AUC}(m, d)$.

Average MAE (Regression). For regression, the Mean Absolute Error (MAE) on dataset d is $\mathrm{MAE}(d) = \frac{1}{N_d} \sum_{i=1}^{N_d} |\hat{y}_i - y_i|$, where $\hat{y}_i$ are predictions and y_i ground truth labels. The average MAE of method m is $\mathrm{AvgMAE}(m) = \frac{1}{|\mathcal{D}|} \sum_{d \in \mathcal{D}} \mathrm{MAE}(m, d)$.

Relative Gain Across Tasks. Relative gain quantifies Hydra's improvement over the strongest baseline by comparing the average metric values across all 20 test datasets for each task. For classification (where higher AUC is better), the gain for task t is defined as

$$\mathrm{Gain}_t = \frac{\overline{\mathrm{AUC}}_{\mathrm{Hydra}}(t) - \max_{m \in \mathcal{B}} \overline{\mathrm{AUC}}_m(t)}{\max_{m \in \mathcal{B}} \overline{\mathrm{AUC}}_m(t)} \times 100\%,$$

where $\overline{\mathrm{AUC}}_m(t)$ denotes the average AUC of method m on task t across all test datasets.

For regression (where lower MAE is better), the gain is

$$\mathrm{Gain}_t = \frac{\min_{m \in \mathcal{B}} \overline{\mathrm{MAE}}_m(t) - \overline{\mathrm{MAE}}_{\mathrm{Hydra}}(t)}{\min_{m \in \mathcal{B}} \overline{\mathrm{MAE}}_m(t)} \times 100\%,$$

where $\overline{\mathrm{MAE}}_m(t)$ denotes the average MAE of method m on task t across all test datasets.

Finally, the overall gain across a group of tasks $\mathcal{T}$ (e.g., all classification tasks) is computed as the mean of the per-task gains: $\mathrm{Gain}_{\mathcal{T}} = \frac{1}{|\mathcal{T}|} \sum_{t \in \mathcal{T}} \mathrm{Gain}_t$.

H. Ablation Studies

To better understand Hydra components, we conduct an ablation study on the edge growth/shrinkage task. The ablations reflect different stages in the model's incremental development. First, we compare the initial version of Hydra without pooling, evaluating the impact of adding Density of States (DOS) features in the spectral path. Next, we consider models that already include DOS and assess the effect of introducing attention-based pooling in the spatial path. Results are reported in Appendix Tables 6 and 7. Together, these comparisons show that DOS enhances the capture of global spectral structure, while pooling improves the selection of informative subgraphs, confirming their complementary roles in Hydra 's design and performance.

Impact of DOS. To assess the contribution of the DOS module, we compare Hydra with and without DOS features (Table 6). This setup isolates the effect of spectral information on predictive performance, holding all other components fixed. The results show that incorporating DOS substantially improves performance on most datasets: Hydra with DOS achieves the best results in 14 out of 20 networks, compared to 6 without DOS. On average, DOS raises AUC from 0.697 to 0.719 and improves the mean rank from 1.70 to 1.30. Gains are particularly large on challenging datasets such as *EVERMOON*, *DOGE2.0*, and *DINO*, where DOS more effectively captures global spectral structure. These findings highlight that DOS provides complementary information to the spatial path, leading to stronger generalization across temporal networks.

Impact of Attention-based Pooling. The ablation on the edge growth/shrinkage task (Table 7) shows the contribution of the pooling mechanism within Hydra 's spatial path. When pooling is enabled, the model achieves higher AUC on 17 out of 20 datasets, with the average score improving from 0.719 to 0.753 and the mean rank from 1.85 to 1.15. The improvement is particularly noticeable when pooling helps the spatial path focus on structurally important nodes, resulting in stronger graph-level representations. These findings indicate that pooling is an essential component for producing compact, informative graph-level representations and strengthen Hydra 's ability to capture temporal dynamics.

I. Scaling Behavior in Hydra

We conducted scaling trend experiments to evaluate Hydra under different training pack sizes systematically. Four model variations were trained using 8, 16, and 32 networks, enabling us to observe how increasing the number of networks in the training loop affects performance. This setup provides a consistent method to study Hydra's behavior when exposed to varying amounts of training data across multiple tasks. For each task, we present results for all four Hydra variants. These results demonstrate how Hydra scales with the number of training networks and

Table 6. DOS ablation study on task Edge G/S. AUC values are reported. Best results per dataset are in **bold**.

Dataset	Hydra **w/o DOS**	Hydra **w DOS**
MIR	**0.791 (±0.014)**	0.755 (±0.013)
DOGE2.0	0.500 (±0.102)	**0.732 (±0.044)**
MUTE	0.675 (±0.030)	**0.699 (±0.011)**
EVERMOON	0.426 (±0.129)	**0.796 (±0.219)**
DERC	0.748 (±0.029)	**0.761 (±0.030)**
ADX	0.678 (±0.019)	**0.703 (±0.006)**
HOICHI	**0.792 (±0.052)**	0.572 (±0.016)
SDEX	**0.599 (±0.134)**	0.261 (±0.129)
BAG	0.759 (±0.294)	**0.874 (±0.017)**
XCN	0.822 (±0.073)	**0.825 (±0.038)**
ETH2x-FLI	0.716 (±0.020)	**0.736 (±0.026)**
stkAAVE	0.708 (±0.021)	**0.719 (±0.006)**
GLM	0.755 (±0.194)	**0.810 (±0.015)**
QOM	0.639 (±0.015)	**0.698 (±0.024)**
WOJAK	0.548 (±0.081)	**0.633 (±0.081)**
DINO	0.672 (±0.044)	**0.843 (±0.031)**
Metis	**0.785 (±0.050)**	0.713 (±0.027)
REPv2	**0.761 (±0.039)**	0.736 (±0.028)
TRAC	**0.794 (±0.041)**	0.732 (±0.007)
BEPRO	0.775 (±0.022)	**0.786 (±0.009)**
1st-Place Count↑	6	**14**
Avg. Rank ↓	1.70	**1.30**
Avg. AUC ↑	0.697	**0.719**

Table 7. SAG pooling ablation study on task Edge G/S. AUC values are reported. Best results per dataset are in **bold**.

Dataset	Hydra **w/o Pooling**	Hydra **w Pooling**
MIR	0.755 (±0.013)	**0.793 (±0.002)**
DOGE2.0	0.732 (±0.044)	**0.897 (±0.089)**
MUTE	0.699 (±0.011)	**0.701 (±0.098)**
EVERMOON	0.796 (±0.219)	**0.818 (±0.046)**
DERC	0.761 (±0.030)	**0.839 (±0.008)**
ADX	0.703 (±0.006)	**0.722 (±0.087)**
HOICHI	0.572 (±0.016)	**0.591 (±0.103)**
SDEX	0.261 (±0.129)	**0.348 (±0.066)**
BAG	0.874 (±0.017)	**0.969 (±0.008)**
XCN	0.825 (±0.038)	**0.844 (±0.012)**
ETH2x-FLI	**0.736 (±0.026)**	0.712 (±0.045)
stkAAVE	0.719 (±0.006)	**0.732 (±0.011)**
GLM	0.810 (±0.015)	**0.850 (±0.009)**
QOM	0.698 (±0.024)	**0.745 (±0.003)**
WOJAK	**0.633 (±0.081)**	0.585 (±0.067)
DINO	0.843 (±0.031)	**0.895 (±0.003)**
Metis	0.713 (±0.027)	**0.733 (±0.004)**
REPv2	0.736 (±0.028)	**0.772 (±0.016)**
TRAC	**0.732 (±0.007)**	0.722 (±0.001)
BEPRO	0.786 (±0.009)	**0.800 (±0.002)**
1st-Place Count↑	3	**17**
Avg. Rank ↓	1.85	**1.15**
Avg. AUC ↑	0.719	**0.753**

are shown in the following tables. Each table provides a detailed breakdown by task and model variation, offering a comprehensive view of performance under various scaling setups. The detailed results of each Hydra variation trained with different datapacks across all six tasks are reported in Table 8. Subsections (a)–(c) present classification tasks (Node G/S, Edge G/S, LCC G/S), while (d)–(f) correspond to regression tasks (New Node Count, Influential Node Count, Edge Count).

J. Extended Network and Task Results

This section reports the full per-network results for all classification and regression tasks, using the same evaluation protocol as in the main text. These tables complement the summary figures by showing the complete distribution of baseline and Hydra performance across datasets.

Classification. Extended classification results are provided for *Edge-G/S*, *LLC-G/S*, and *Node-G/S* in Table 9, Table 10, and Table 11, respectively.

Regression. Extended regression results are provided for *Edge Count*, *New Node Count*, and *Influential Node Count* in Table 12, Table 13, and Table 14, respectively.

For classification , Hydra achieves the highest AUC on the majority of datasets across Edge-G/S, LLC-G/S, and Node-G/S. For regression Hydra consistently delivers the lowest or near-lowest MAE, remaining competitive even on tasks where another baseline occasionally leads. These results confirm that Hydra 's advantages are not limited to averages: the model transfers robustly across het-

erogeneous temporal networks and maintains strong performance in the zero-shot setting.

Table 8. Performance of `Hydra` across six tasks as the number of training networks increases from 8 to 32.

(a) Classification : Node G/S

Dataset	Hydra-8	Hydra-16	Hydra-32
MIR	**0.769 (±0.003)**	**0.769 (±0.007)**	0.764 (±0.001)
DOGE2.0	0.613 (±0.083)	0.573 (±0.133)	**0.633 (±0.064)**
MUTE	0.755 (±0.016)	**0.763 (±0.003)**	0.748 (±0.025)
EVERMOON	0.624 (±0.005)	0.582 (±0.031)	**0.655 (±0.040)**
DERC	0.734 (±0.010)	0.725 (±0.006)	**0.742 (±0.004)**
ADX	0.753 (±0.027)	**0.767 (±0.004)**	0.718 (±0.051)
HOICHI	**0.582 (±0.029)**	0.552 (±0.050)	0.558 (±0.047)
SDEX	**0.762 (±0.008)**	0.748 (±0.068)	0.743 (±0.026)
BAG	0.963 (±0.010)	0.952 (±0.021)	**0.969 (±0.009)**
XCN	0.862 (±0.016)	0.821 (±0.070)	**0.878 (±0.009)**
ETH2x-FLI	**0.717 (±0.030)**	0.710 (±0.009)	0.678 (±0.031)
stkAAVE	0.776 (±0.009)	0.776 (±0.003)	**0.779 (±0.007)**
GLM	0.750 (±0.011)	0.746 (±0.010)	**0.763 (±0.005)**
QOM	0.703 (±0.012)	0.707 (±0.013)	**0.719 (±0.012)**
WOJAK	**0.502 (±0.103)**	0.352 (±0.157)	0.412 (±0.060)
DINO	0.903 (±0.029)	0.905 (±0.021)	**0.910 (±0.013)**
Metis	0.685 (±0.002)	0.632 (±0.091)	**0.693 (±0.007)**
REPv2	**0.728 (±0.022)**	0.721 (±0.023)	0.689 (±0.013)
TRAC	0.756 (±0.005)	0.745 (±0.014)	**0.765 (±0.003)**
BEPRO	0.858 (±0.023)	0.806 (±0.094)	**0.865 (±0.010)**
1st-Place Count↑	6	3	**12**
Avg. Rank↓	1.85	2.45	**1.70**
Avg. AUC↑	**0.740**	0.718	0.734

(b) Classification : Edge G/S

Dataset	Hydra-8	Hydra-16	Hydra-32
MIR	**0.800 (±0.007)**	0.796 (±0.001)	0.793 (±0.002)
DOGE2.0	0.859 (±0.022)	0.897 (±0.089)	**0.897 (±0.089)**
MUTE	0.757 (±0.004)	**0.764 (±0.004)**	0.701 (±0.098)
EVERMOON	0.698 (±0.180)	0.750 (±0.024)	**0.818 (±0.046)**
DERC	0.823 (±0.018)	0.826 (±0.002)	**0.839 (±0.008)**
ADX	0.760 (±0.004)	**0.768 (±0.015)**	0.722 (±0.087)
HOICHI	0.606 (±0.015)	**0.617 (±0.026)**	0.591 (±0.103)
SDEX	0.288 (±0.023)	0.331 (±0.049)	**0.348 (±0.066)**
BAG	**0.969 (±0.009)**	0.955 (±0.015)	0.969 (±0.008)
XCN	**0.847 (±0.046)**	0.845 (±0.010)	0.844 (±0.012)
ETH2x-FLI	0.735 (±0.006)	0.738 (±0.005)	0.712 (±0.045)
stkAAVE	**0.744 (±0.008)**	0.743 (±0.007)	0.732 (±0.011)
GLM	0.849 (±0.003)	0.841 (±0.015)	**0.850 (±0.009)**
QOM	0.755 (±0.015)	**0.762 (±0.008)**	0.745 (±0.003)
WOJAK	**0.627 (±0.014)**	0.561 (±0.101)	0.585 (±0.067)
DINO	0.875 (±0.030)	0.889 (±0.009)	**0.895 (±0.003)**
Metis	**0.735 (±0.004)**	0.697 (±0.062)	0.733 (±0.004)
REPv2	0.778 (±0.001)	**0.784 (±0.009)**	0.772 (±0.016)
TRAC	0.713 (±0.010)	0.711 (±0.011)	**0.722 (±0.001)**
BEPRO	0.783 (±0.009)	0.743 (±0.085)	**0.800 (±0.002)**
1st-Place Count↑	6	7	**9**
Avg. Rank↓	1.95	1.95	2
Avg. AUC↑	0.75	0.751	**0.753**

(c) Classification : LCC G/S

Dataset	Hydra-8	Hydra-16	Hydra-32
MIR	**0.819 (±0.004)**	0.817 (±0.001)	0.815 (±0.007)
DOGE2.0	**0.762 (±0.010)**	0.667 (±0.175)	0.702 (±0.160)
MUTE	0.714 (±0.049)	**0.756 (±0.006)**	0.704 (±0.085)
EVERMOON	0.600 (±0.057)	0.639 (±0.029)	**0.667 (±0.045)**
DERC	**0.819 (±0.003)**	0.813 (±0.005)	0.808 (±0.022)
ADX	0.691 (±0.066)	**0.770 (±0.021)**	0.727 (±0.093)
HOICHI	0.610 (±0.044)	**0.640 (±0.041)**	0.638 (±0.075)
SDEX	0.784 (±0.017)	0.810 (±0.048)	**0.816 (±0.025)**
BAG	0.968 (±0.013)	0.957 (±0.021)	**0.976 (±0.006)**
XCN	0.863 (±0.011)	0.863 (±0.029)	**0.887 (±0.014)**
ETH2x-FLI	**0.708 (±0.011)**	0.703 (±0.001)	0.687 (±0.032)
stkAAVE	0.753 (±0.011)	**0.757 (±0.003)**	0.748 (±0.012)
GLM	**0.853 (±0.006)**	0.844 (±0.020)	0.848 (±0.012)
QOM	0.725 (±0.009)	**0.730 (±0.002)**	0.729 (±0.010)
WOJAK	**0.558 (±0.032)**	0.458 (±0.142)	0.500 (±0.083)
DINO	0.878 (±0.021)	**0.883 (±0.032)**	0.818 (±0.049)
Metis	0.727 (±0.006)	0.669 (±0.100)	**0.731 (±0.001)**
REPv2	0.781 (±0.004)	**0.785 (±0.009)**	0.764 (±0.020)
TRAC	0.772 (±0.006)	0.768 (±0.008)	**0.781 (±0.004)**
BEPRO	0.826 (±0.015)	0.800 (±0.058)	**0.830 (±0.006)**
1st-Place Count↑	6	7	7
Avg. Rank↓	1.95	2	2
Avg. AUC↑	**0.761**	0.756	0.759

(d) Regression : New Node Count

Dataset	Hydra-8	Hydra-16	Hydra-32
MIR	0.056 (±0.057)	0.040 (±0.042)	**0.013 (±0.004)**
DOGE2.0	0.068 (±0.023)	**0.060 (±0.027)**	0.092 (±0.008)
MUTE	0.073 (±0.036)	0.036 (±0.025)	**0.025 (±0.005)**
EVERMOON	0.070 (±0.053)	0.038 (±0.045)	**0.012 (±0.006)**
DERC	0.071 (±0.049)	0.038 (±0.040)	**0.015 (±0.004)**
ADX	0.069 (±0.047)	0.029 (±0.035)	**0.016 (±0.005)**
HOICHI	0.064 (±0.038)	0.048 (±0.030)	**0.029 (±0.008)**
SDEX	0.074 (±0.021)	0.072 (±0.011)	**0.063 (±0.006)**
BAG	0.072 (±0.023)	0.056 (±0.009)	**0.052 (±0.002)**
XCN	0.067 (±0.056)	0.036 (±0.044)	**0.009 (±0.002)**
ETH2x-FLI	0.053 (±0.034)	0.032 (±0.023)	**0.030 (±0.004)**
stkAAVE	0.085 (±0.042)	**0.057 (±0.024)**	0.078 (±0.017)
GLM	0.097 (±0.013)	0.103 (±0.008)	**0.094 (±0.007)**
QOM	0.073 (±0.054)	0.034 (±0.040)	**0.012 (±0.001)**
WOJAK	0.076 (±0.059)	0.034 (±0.042)	**0.009 (±0.000)**
DINO	0.065 (±0.053)	0.046 (±0.042)	**0.018 (±0.007)**
Metis	0.072 (±0.040)	0.037 (±0.016)	**0.034 (±0.010)**
REPv2	0.083 (±0.024)	0.074 (±0.015)	**0.066 (±0.004)**
TRAC	0.074 (±0.042)	0.029 (±0.026)	**0.022 (±0.005)**
BEPRO	0.081 (±0.067)	0.034 (±0.046)	**0.004 (±0.001)**
1st-Place Count↑	0	2	**18**
Avg. Rank↓	2.90	1.95	**1.15**
Avg. MAE↓	0.072	0.047	**0.035**

(e) Regression : Influential Node Count

Dataset	Hydra-8	Hydra-16	Hydra-32
MIR	0.080 (±0.059)	0.059 (±0.004)	**0.039 (±0.005)**
DOGE2.0	**0.065 (±0.034)**	0.094 (±0.003)	0.126 (±0.032)
MUTE	0.103 (±0.070)	0.078 (±0.034)	**0.045 (±0.027)**
EVERMOON	0.107 (±0.067)	0.072 (±0.018)	**0.038 (±0.024)**
DERC	0.063 (±0.065)	0.056 (±0.012)	**0.033 (±0.017)**
ADX	0.084 (±0.070)	0.054 (±0.009)	**0.030 (±0.001)**
HOICHI	0.115 (±0.066)	0.088 (±0.045)	**0.055 (±0.028)**
SDEX	0.087 (±0.027)	0.083 (±0.068)	**0.042 (±0.019)**
BAG	0.141 (±0.064)	0.109 (±0.045)	**0.075 (±0.027)**
XCN	**0.071 (±0.033)**	0.096 (±0.008)	0.126 (±0.033)
ETH2x-FLI	0.066 (±0.059)	0.052 (±0.007)	**0.033 (±0.020)**
stkAAVE	0.067 (±0.045)	0.063 (±0.008)	**0.042 (±0.013)**
GLM	0.108 (±0.045)	0.088 (±0.014)	**0.075 (±0.017)**
QOM	0.066 (±0.055)	0.055 (±0.004)	**0.039 (±0.020)**
WOJAK	0.116 (±0.068)	0.074 (±0.046)	**0.036 (±0.027)**
DINO	0.085 (±0.066)	0.059 (±0.009)	**0.034 (±0.002)**
Metis	0.082 (±0.056)	0.072 (±0.022)	**0.046 (±0.008)**
REPv2	**0.127 (±0.015)**	0.130 (±0.004)	0.129 (±0.022)
TRAC	0.069 (±0.053)	0.059 (±0.003)	**0.043 (±0.023)**
BEPRO	0.105 (±0.068)	0.064 (±0.005)	**0.033 (±0.018)**
1st-Place Count↑	3	0	**17**
Avg. Rank↓	2.70	2.05	**1.25**
Avg. MAE↓	0.090	0.075	**0.056**

(f) Regression : Edge Count

Dataset	Hydra-8	Hydra-16	Hydra-32
MIR	0.087 (±0.057)	0.035 (±0.027)	**0.016 (±0.005)**
DOGE2.0	**0.115 (±0.023)**	0.135 (±0.032)	0.187 (±0.008)
MUTE	0.092 (±0.036)	0.048 (±0.017)	**0.021 (±0.022)**
EVERMOON	0.085 (±0.053)	0.041 (±0.029)	**0.017 (±0.000)**
DERC	0.082 (±0.049)	0.033 (±0.024)	**0.021 (±0.003)**
ADX	0.082 (±0.047)	0.029 (±0.018)	**0.025 (±0.008)**
HOICHI	0.090 (±0.046)	0.062 (±0.006)	**0.027 (±0.020)**
SDEX	0.080 (±0.021)	**0.077 (±0.018)**	0.095 (±0.043)
BAG	0.099 (±0.023)	0.065 (±0.005)	**0.041 (±0.020)**
XCN	0.066 (±0.056)	**0.027 (±0.009)**	0.062 (±0.015)
ETH2x-FLI	0.084 (±0.034)	0.035 (±0.019)	**0.023 (±0.001)**
stkAAVE	0.065 (±0.037)	**0.025 (±0.004)**	0.051 (±0.022)
GLM	0.106 (±0.013)	0.101 (±0.007)	**0.087 (±0.008)**
QOM	0.074 (±0.054)	**0.032 (±0.019)**	0.036 (±0.013)
WOJAK	0.090 (±0.059)	0.034 (±0.035)	**0.010 (±0.004)**
DINO	0.085 (±0.053)	0.040 (±0.028)	**0.017 (±0.007)**
Metis	0.087 (±0.030)	0.041 (±0.005)	**0.034 (±0.010)**
REPv2	0.127 (±0.024)	**0.105 (±0.003)**	0.111 (±0.008)
TRAC	0.086 (±0.042)	0.029 (±0.020)	**0.021 (±0.001)**
BEPRO	0.094 (±0.067)	0.037 (±0.036)	**0.011 (±0.008)**
1st-Place Count↑	1	5	**14**
Avg. Rank↓	2.85	1.75	**1.40**
Avg. MAE↓	0.089	0.052	**0.046**

Table 9. AUC results for the Edge Growth/Shrinkage prediction task (classification). Best results are in **bold**, second best are underlined.

	Single Model on Individual Networks							Transfer Models	
Dataset	**HTGN**	**GC-LSTM**	**EvolveGCN**	**GraphPulse**	**ROLAND**	**TGCN**	**WinGNN**	**MiNT**	Hydra **(Ours)**
MIR	0.750 ±0.005	0.768 ±0.026	0.745 ±0.015	0.689 ±0.097	0.228 ±0.060	0.749 ±0.026	0.742 ±0.015	**0.836** ±**0.016**	0.793 ±0.002
DOGE2.0	0.590 ±0.059	0.538 ±0.000	0.551 ±0.022	0.384 ±0.180	0.513 ±0.022	0.487 ±0.044	0.577 ±0.038	0.538 ±0.038	**0.897** ±**0.089**
MUTE	0.649 ±0.015	0.593 ±0.030	0.617 ±0.010	**0.779** ±**0.004**	0.289 ±0.042	0.557 ±0.068	0.593 ±0.054	0.673 ±0.013	0.701 ±0.098
EVERMOON	0.512 ±0.023	0.562 ±0.179	0.451 ±0.046	0.519 ±0.130	0.349 ±0.119	0.463 ±0.149	0.525 ±0.114	0.517 ±0.039	**0.818** ±**0.046**
DERC	0.683 ±0.013	0.703 ±0.022	0.669 ±0.009	0.769 ±0.040	0.405 ±0.357	0.743 ±0.077	0.674 ±0.044	0.798 ±0.027	**0.839** ±**0.008**
ADX	0.769 ±0.018	0.723 ±0.002	0.718 ±0.004	**0.784** ±**0.002**	0.761 ±0.011	0.674 ±0.034	0.733 ±0.023	0.679 ±0.024	0.722 ±0.087
HOICHI	0.807 ±0.047	**0.857** ±**0.000**	0.856 ±0.001	0.714 ±0.010	0.815 ±0.036	0.836 ±0.034	0.769 ±0.101	0.765 ±0.018	0.591 ±0.103
SDEX	**0.762** ±**0.034**	0.720 ±0.002	0.733 ±0.028	0.436 ±0.030	0.483 ±0.254	0.759 ±0.039	0.726 ±0.000	0.614 ±0.020	0.348 ±0.066
BAG	0.673 ±0.227	0.196 ±0.179	0.329 ±0.040	0.934 ±0.020	0.418 ±0.016	0.334 ±0.171	0.485 ±0.105	0.931 ±0.028	**0.969** ±**0.008**
XCN	0.668 ±0.099	0.306 ±0.092	0.512 ±0.067	0.821 ±0.004	0.765 ±0.015	0.703 ±0.037	0.586 ±0.029	**0.851** ±**0.043**	0.844 ±0.012
ETH2x-FLI	0.610 ±0.059	0.670 ±0.009	0.688 ±0.012	0.666 ±0.047	0.621 ±0.023	0.647 ±0.020	0.617 ±0.056	**0.729** ±**0.015**	0.712 ±0.045
stkAAVE	0.702 ±0.042	0.368 ±0.011	0.397 ±0.022	**0.743** ±**0.006**	0.591 ±0.012	0.577 ±0.129	0.572 ±0.018	0.709 ±0.022	0.732 ±0.011
GLM	0.830 ±0.029	0.451 ±0.003	0.501 ±0.033	0.769 ±0.018	0.559 ±0.357	0.531 ±0.008	0.530 ±0.004	0.831 ±0.024	**0.850** ±**0.009**
QOM	0.633 ±0.017	0.612 ±0.001	0.618 ±0.002	**0.775** ±**0.011**	0.641 ±0.003	0.647 ±0.032	0.645 ±0.099	0.647 ±0.019	0.745 ±0.003
WOJAK	0.479 ±0.005	0.484 ±0.000	0.505 ±0.023	0.467 ±0.030	0.529 ±0.005	0.516 ±0.021	0.511 ±0.026	0.524 ±0.027	**0.585** ±**0.067**
DINO	0.730 ±0.195	0.874 ±0.028	0.868 ±0.029	0.801 ±0.020	0.497 ±0.092	0.544 ±0.314	0.628 ±0.251	0.779 ±0.113	**0.895** ±**0.003**
Metis	0.715 ±0.122	0.646 ±0.023	0.688 ±0.027	**0.812** ±**0.011**	0.696 ±0.108	0.709 ±0.033	0.690 ±0.039	0.760 ±0.025	0.733 ±0.004
REPv2	0.760 ±0.012	0.725 ±0.014	0.709 ±0.002	**0.830** ±**0.001**	0.751 ±0.003	0.696 ±0.035	0.744 ±0.026	0.789 ±0.020	0.772 ±0.016
TRAC	0.712 ±0.071	0.748 ±0.000	0.748 ±0.000	0.767 ±0.001	0.495 ±0.223	0.741 ±0.012	0.752 ±0.007	**0.785** ±**0.008**	0.722 ±0.001
BEPRO	0.655 ±0.038	0.632 ±0.019	0.610 ±0.012	0.783 ±0.003	0.439 ±0.125	0.744 ±0.074	0.736 ±0.018	0.782 ±0.003	**0.800** ±**0.002**
1st-Place Count↑	1	1	0	6	0	0	0	4	**8**
Avg. Rank ↓	4.85	5.80	6.10	3.80	6.30	5.60	5.55	3.30	**2.80**
Avg. AUC ↑	0.684	0.609	0.626	0.712	0.542	0.633	0.642	0.727	**0.753**

Table 10. AUC results for the LCC Growth/Shrinkage prediction task (classification). Best results are in **bold**, second best are underlined.

	Single Model on Individual Networks							Transfer Models	
Dataset	**HTGN**	**GC-LSTM**	**EvolveGCN**	**GraphPulse**	**ROLAND**	**TGCN**	**WinGNN**	**MiNT**	Hydra **(Ours)**
MIR	0.745 (±0.023)	0.585 (±0.128)	0.575 (±0.146)	0.800 (±0.008)	0.536 (±0.275)	0.585 (±0.055)	0.749 (±0.020)	**0.845** (±**0.035**)	0.815 (±0.007)
DOGE2.0	0.446 (±0.164)	0.387 (±0.294)	0.583 (±0.115)	0.333 (±0.042)	0.411 (±0.232)	0.464 (±0.182)	0.595 (±0.176)	0.661 (±0.047)	**0.702** (±**0.160**)
MUTE	0.574 (±0.022)	0.579 (±0.022)	0.578 (±0.033)	0.647 (±0.014)	0.624 (±0.037)	0.567 (±0.007)	0.641 (±0.061)	0.582 (±0.078)	**0.704** (±**0.085**)
EVERMOON	0.494 (±0.127)	0.512 (±0.112)	0.548 (±0.152)	0.463 (±0.034)	0.491 (±0.157)	0.624 (±0.004)	0.603 (±0.041)	0.527 (±0.118)	**0.667** (±**0.045**)
DERC	0.717 (±0.035)	0.591 (±0.010)	0.553 (±0.044)	0.727 (±0.009)	0.481 (±0.131)	0.523 (±0.103)	0.582 (±0.043)	0.689 (±0.096)	**0.808** (±**0.022**)
ADX	0.753 (±0.013)	0.599 (±0.012)	0.604 (±0.030)	0.661 (±0.006)	0.606 (±0.059)	0.621 (±0.017)	0.611 (±0.062)	0.587 (±0.014)	0.727 (±0.093)
HOICHI	0.746 (±0.010)	0.749 (±0.001)	0.745 (±0.003)	0.730 (±0.017)	0.360 (±0.121)	0.750 (±0.002)	0.635 (±0.183)	0.722 (±0.034)	0.638 (±0.075)
SDEX	**0.911** (±**0.104**)	0.721 (±0.138)	0.601 (±0.105)	0.808 (±0.050)	0.825 (±0.047)	0.770 (±0.231)	0.575 (±0.282)	0.382 (±0.280)	0.816 (±0.025)
BAG	0.493 (±0.043)	0.291 (±0.180)	0.480 (±0.052)	0.900 (±0.010)	0.463 (±0.019)	0.463 (±0.141)	0.490 (±0.080)	0.893 (±0.074)	**0.976** (±**0.006**)
XCN	0.566 (±0.199)	0.481 (±0.160)	0.533 (±0.257)	0.681 (±0.005)	0.569 (±0.204)	0.638 (±0.045)	0.549 (±0.133)	0.827 (±0.025)	**0.887** (±**0.014**)
ETH2x-FLI	0.561 (±0.037)	0.529 (±0.017)	0.547 (±0.009)	0.653 (±0.047)	0.499 (±0.135)	0.549 (±0.019)	0.505 (±0.090)	0.618 (±0.025)	**0.687** (±**0.032**)
stkAAVE	0.623 (±0.077)	0.581 (±0.085)	0.551 (±0.102)	0.662 (±0.004)	0.532 (±0.140)	0.543 (±0.102)	0.489 (±0.105)	0.688 (±0.019)	**0.748** (±**0.012**)
GLM	0.761 (±0.031)	0.481 (±0.073)	0.636 (±0.123)	0.749 (±0.045)	0.802 (±0.003)	0.425 (±0.005)	0.489 (±0.079)	0.818 (±0.074)	**0.848** (±**0.012**)
QOM	0.658 (±0.150)	0.509 (±0.100)	0.562 (±0.022)	**0.747** (±**0.006**)	0.627 (±0.134)	0.419 (±0.044)	0.546 (±0.152)	0.645 (±0.109)	0.729 (±0.010)
WOJAK	0.378 (±0.028)	0.489 (±0.133)	0.394 (±0.079)	**0.550** (±**0.036**)	0.360 (±0.005)	0.481 (±0.092)	0.415 (±0.017)	0.492 (±0.107)	0.500 (±0.083)
DINO	0.706 (±0.120)	0.796 (±0.023)	0.710 (±0.034)	0.661 (±0.026)	0.523 (±0.238)	0.773 (±0.043)	0.731 (±0.037)	0.561 (±0.006)	**0.818** (±**0.049**)
Metis	0.679 (±0.039)	0.687 (±0.018)	0.672 (±0.016)	**0.783** (±**0.007**)	0.672 (±0.103)	0.657 (±0.014)	0.634 (±0.042)	0.780 (±0.041)	0.731 (±0.001)
REPv2	0.730 (±0.007)	0.653 (±0.015)	0.644 (±0.027)	0.752 (±0.001)	0.658 (±0.103)	0.646 (±0.025)	0.683 (±0.014)	0.742 (±0.041)	**0.764** (±**0.020**)
TRAC	0.733 (±0.009)	0.629 (±0.005)	0.623 (±0.004)	0.686 (±0.001)	0.606 (±0.117)	0.620 (±0.005)	0.599 (±0.026)	0.762 (±0.028)	**0.781** (±**0.004**)
BEPRO	0.694 (±0.009)	0.595 (±0.008)	0.557 (±0.058)	0.725 (±0.004)	0.482 (±0.146)	0.536 (±0.031)	0.582 (±0.063)	0.628 (±0.017)	**0.830** (±**0.006**)
1st-Place Count↑	2	0	0	3	0	1	0	1	**13**
Avg. Rank ↓	4.40	6.00	6.30	3.50	6.95	6.10	6.10	3.95	**1.70**
Avg. AUC ↑	0.648	0.572	0.585	0.686	0.556	0.583	0.585	0.672	**0.759**

Table 11. AUC results for the Node Growth/Shrinkage prediction task (classification). Best results are in **bold**, second best are underlined.

	Single Model on Individual Networks							Transfer Models	
Dataset	HTGN	GC-LSTM	EvolveGCN	GraphPulse	ROLAND	TGCN	WinGNN	MiNT	Hydra (**Ours**)
MIR	0.545 (±0.030)	0.537 (±0.033)	0.528 (±0.081)	0.633 (±0.066)	0.472 (±0.040)	0.532 (±0.021)	0.525 (±0.043)	0.622 (±0.030)	**0.764 (±0.001)**
DOGE2.0	0.427 (±0.065)	0.633 (±0.014)	0.400 (±0.061)	0.403 (±0.035)	0.260 (±0.000)	0.627 (±0.034)	0.693 (±0.041)	**0.750 (±0.014)**	0.633 (±0.064)
MUTE	0.518 (±0.023)	0.448 (±0.008)	0.475 (±0.051)	0.677 (±0.008)	0.411 (±0.053)	0.458 (±0.009)	0.562 (±0.015)	0.606 (±0.056)	**0.748 (±0.025)**
EVERMOON	0.585 (±0.059)	0.606 (±0.021)	0.488 (±0.088)	0.463 (±0.002)	0.427 (±0.137)	0.567 (±0.030)	0.548 (±0.116)	0.614 (±0.071)	**0.655 (±0.040)**
DERC	0.662 (±0.051)	0.492 (±0.069)	0.503 (±0.084)	0.611 (±0.049)	0.551 (±0.013)	0.447 (±0.003)	0.517 (±0.034)	0.569 (±0.004)	**0.742 (±0.004)**
ADX	0.678 (±0.017)	0.505 (±0.043)	0.509 (±0.022)	0.701 (±0.003)	0.557 (±0.082)	0.484 (±0.048)	0.504 (±0.018)	0.507 (±0.037)	**0.718 (±0.051)**
HOICHI	0.687 (±0.004)	0.718 (±0.007)	0.685 (±0.020)	**0.745 (±0.006)**	0.347 (±0.084)	0.718 (±0.002)	0.526 (±0.188)	0.492 (±0.120)	0.558 (±0.047)
SDEX	0.824 (±0.106)	0.364 (±0.148)	0.817 (±0.032)	**0.865 (±0.011)**	0.779 (±0.018)	0.755 (±0.202)	0.757 (±0.072)	0.861 (±0.025)	0.743 (±0.026)
BAG	0.735 (±0.075)	0.337 (±0.089)	0.166 (±0.066)	0.897 (±0.016)	0.390 (±0.088)	0.391 (±0.219)	0.515 (±0.038)	0.685 (±0.038)	**0.969 (±0.009)**
XCN	0.476 (±0.012)	0.466 (±0.012)	0.407 (±0.176)	0.671 (±0.020)	0.430 (±0.144)	0.483 (±0.036)	0.355 (±0.017)	0.505 (±0.002)	**0.878 (±0.009)**
ETH2x-FLI	0.628 (±0.022)	0.548 (±0.001)	0.548 (±0.002)	0.615 (±0.020)	0.488 (±0.063)	0.553 (±0.036)	0.586 (±0.098)	0.411 (±0.066)	**0.678 (±0.031)**
stkAAVE	0.517 (±0.093)	0.543 (±0.043)	0.456 (±0.069)	0.643 (±0.005)	0.661 (±0.037)	0.425 (±0.029)	0.465 (±0.036)	0.561 (±0.007)	**0.779 (±0.007)**
GLM	0.706 (±0.014)	0.566 (±0.001)	0.516 (±0.105)	0.595 (±0.003)	0.493 (±0.149)	0.575 (±0.019)	0.610 (±0.024)	0.720 (±0.045)	**0.763 (±0.005)**
QOM	0.647 (±0.094)	0.492 (±0.003)	0.485 (±0.001)	0.705 (±0.002)	0.592 (±0.080)	0.495 (±0.004)	0.409 (±0.051)	0.572 (±0.017)	**0.719 (±0.012)**
WOJAK	0.417 (±0.143)	0.338 (±0.068)	0.357 (±0.014)	0.500 (±0.000)	0.202 (±0.034)	0.488 (±0.080)	0.314 (±0.029)	0.618 (±0.035)	0.412 (±0.060)
DINO	0.845 (±0.015)	0.323 (±0.148)	0.444 (±0.052)	0.686 (±0.007)	0.330 (±0.115)	0.615 (±0.070)	0.600 (±0.292)	0.735 (±0.005)	**0.910 (±0.013)**
Metis	0.589 (±0.049)	0.483 (±0.052)	0.566 (±0.012)	0.652 (±0.029)	0.574 (±0.040)	0.549 (±0.011)	0.510 (±0.005)	0.616 (±0.012)	**0.693 (±0.007)**
REPv2	0.650 (±0.004)	0.519 (±0.023)	0.515 (±0.019)	0.662 (±0.008)	0.597 (±0.028)	0.534 (±0.029)	0.626 (±0.058)	**0.710 (±0.129)**	0.689 (±0.013)
TRAC	0.670 (±0.031)	0.527 (±0.016)	0.524 (±0.003)	0.610 (±0.055)	0.546 (±0.024)	0.524 (±0.001)	0.528 (±0.020)	0.600 (±0.027)	**0.765 (±0.003)**
BEPRO	0.500 (±0.055)	0.332 (±0.010)	0.356 (±0.015)	0.707 (±0.005)	0.490 (±0.016)	0.372 (±0.100)	0.420 (±0.018)	0.561 (±0.022)	**0.865 (±0.010)**
1st-Place Count↑	0	0	0	2	0	0	0	3	**15**
Avg. Rank↓	3.65	6.65	7.00	2.95	6.70	6.15	6.20	3.55	**1.95**
Avg. AUC↑	0.615	0.489	0.487	0.652	0.480	0.530	0.528	0.616	**0.734**

Table 12. MAE results for the Edge Count prediction task (regression). Best results are in **bold**, second best are underlined.

	Single Model on Individual Networks							Transfer Models
Dataset	HTGN	TGCN	GCLSTM	ROLAND	EGCN	GraphPulse	WinGNN	Hydra (**Ours**)
MIR	0.059 (±0.007)	0.044 (±0.009)	0.047 (±0.003)	0.039 (±0.000)	0.057 (±0.015)	0.059 (±0.001)	0.046 (±0.010)	**0.016 (±0.005)**
DOGE2.0	0.101 (±0.035)	0.063 (±0.017)	0.106 (±0.029)	0.052 (±0.003)	0.092 (±0.031)	0.046 (±0.000)	**0.045 (±0.003)**	0.187 (±0.008)
MUTE	0.025 (±0.006)	0.038 (±0.004)	0.017 (±0.001)	0.040 (±0.007)	0.049 (±0.005)	0.025 (±0.002)	0.027 (±0.003)	0.021 (±0.022)
EVERMOON	**0.010 (±0.001)**	0.021 (±0.013)	0.025 (±0.007)	0.016 (±0.016)	0.030 (±0.010)	0.235 (±0.005)	0.025 (±0.004)	0.017 (±0.000)
DERC	0.038 (±0.015)	0.059 (±0.011)	**0.016 (±0.005)**	0.060 (±0.008)	0.023 (±0.007)	0.023 (±0.003)	0.032 (±0.001)	0.021 (±0.003)
ADX	0.017 (±0.001)	0.018 (±0.003)	0.016 (±0.001)	0.017 (±0.002)	0.021 (±0.002)	0.019 (±0.001)	**0.016 (±0.000)**	0.025 (±0.008)
HOICHI	0.034 (±0.010)	**0.020 (±0.001)**	0.046 (±0.013)	0.020 (±0.003)	0.034 (±0.013)	0.044 (±0.002)	0.028 (±0.005)	0.027 (±0.020)
SDEX	0.080 (±0.029)	0.128 (±0.046)	**0.058 (±0.007)**	0.121 (±0.002)	0.085 (±0.025)	0.106 (±0.005)	0.128 (±0.008)	0.095 (±0.043)
BAG	**0.022 (±0.003)**	0.023 (±0.017)	0.025 (±0.002)	0.030 (±0.016)	0.027 (±0.005)	0.063 (±0.001)	0.260 (±0.064)	0.041 (±0.020)
XCN	0.074 (±0.006)	0.112 (±0.042)	0.107 (±0.024)	0.120 (±0.035)	0.121 (±0.011)	0.118 (±0.000)	0.072 (±0.018)	**0.062 (±0.015)**
ETH2x-FLI	0.055 (±0.015)	0.079 (±0.019)	0.177 (±0.057)	0.040 (±0.026)	0.066 (±0.016)	0.144 (±0.009)	0.030 (±0.011)	**0.023 (±0.001)**
stkAAVE	0.083 (±0.008)	0.087 (±0.005)	0.092 (±0.017)	0.104 (±0.012)	0.079 (±0.010)	0.096 (±0.006)	0.100 (±0.004)	**0.051 (±0.022)**
GLM	0.072 (±0.010)	0.058 (±0.005)	0.063 (±0.002)	0.058 (±0.003)	0.060 (±0.001)	0.076 (±0.001)	**0.054 (±0.003)**	0.087 (±0.008)
QOM	0.042 (±0.005)	0.085 (±0.020)	0.053 (±0.030)	0.057 (±0.030)	0.069 (±0.013)	0.055 (±0.001)	0.046 (±0.006)	**0.036 (±0.013)**
WOJAK	0.009 (±0.002)	0.012 (±0.003)	0.013 (±0.004)	0.016 (±0.008)	0.013 (±0.007)	0.057 (±0.008)	**0.006 (±0.002)**	0.010 (±0.004)
DINO	0.069 (±0.020)	0.025 (±0.009)	0.040 (±0.019)	**0.014 (±0.004)**	0.039 (±0.011)	0.087 (±0.002)	0.021 (±0.008)	0.017 (±0.007)
Metis	0.038 (±0.002)	0.054 (±0.001)	0.047 (±0.003)	0.057 (±0.008)	0.053 (±0.004)	0.066 (±0.006)	0.043 (±0.001)	**0.034 (±0.010)**
REPv2	0.117 (±0.003)	0.108 (±0.004)	0.115 (±0.003)	**0.106 (±0.001)**	0.128 (±0.036)	0.119 (±0.000)	0.118 (±0.008)	0.111 (±0.008)
TRAC	0.026 (±0.004)	0.036 (±0.010)	0.061 (±0.006)	0.023 (±0.004)	0.036 (±0.004)	**0.017 (±0.000)**	0.040 (±0.014)	0.021 (±0.001)
BEPRO	0.009 (±0.001)	0.009 (±0.003)	0.009 (±0.002)	0.015 (±0.017)	**0.007 (±0.001)**	**0.007 (±0.000)**	**0.007 (±0.002)**	0.011 (±0.008)
1st-Place Count↑	2	1	4	3	1	2	5	**6**
Avg. Rank ↓	3.95	4.60	4.58	4.58	5.30	5.72	3.93	**3.35**
Avg. MAE ↓	0.049	0.054	0.057	0.050	0.054	0.073	0.057	**0.046**

Table 13. MAE results for the New Node Count prediction task (regression). Best results are in **bold**, second best are underlined.

	Single Model on Individual Networks							Transfer Models
Dataset	**HTGN**	**TGCN**	**GCLSTM**	**ROLAND**	**EGCN**	**GraphPulse**	**WinGNN**	Hydra **(ours)**
MIR	0.031 (±0.002)	0.028 (±0.001)	0.039 (±0.005)	0.025 (±0.018)	0.030 (±0.001)	0.025 (±0.001)	0.037 (±0.011)	**0.013** (±0.004)
DOGE2.0	0.046 (±0.009)	0.064 (±0.021)	**0.044** (±0.014)	0.073 (±0.019)	0.051 (±0.031)	0.157 (±0.010)	0.098 (±0.009)	0.092 (±0.008)
MUTE	**0.021** (±0.003)	0.041 (±0.005)	0.030 (±0.003)	0.048 (±0.002)	0.053 (±0.003)	0.031 (±0.001)	0.051 (±0.015)	0.025 (±0.005)
EVERMOON	**0.010** (±0.004)	0.017 (±0.008)	0.026 (±0.009)	0.029 (±0.019)	0.028 (±0.017)	0.222 (±0.005)	0.022 (±0.002)	0.012 (±0.005)
DERC	0.028 (±0.009)	0.034 (±0.018)	0.016 (±0.024)	0.043 (±0.024)	0.019 (±0.004)	0.043 (±0.011)	0.027 (±0.003)	**0.015** (±0.004)
ADX	0.014 (±0.001)	**0.010** (±0.001)	0.011 (±0.001)	0.024 (±0.296)	0.012 (±0.005)	0.024 (±0.002)	0.011 (±0.000)	0.016 (±0.005)
HOICHI	0.044 (±0.004)	0.035 (±0.025)	0.053 (±0.028)	0.204 (±0.028)	0.039 (±0.023)	0.066 (±0.001)	**0.027** (±0.004)	0.029 (±0.008)
SDEX	0.075 (±0.002)	0.093 (±0.006)	0.069 (±0.002)	0.088 (±0.002)	0.077 (±0.008)	0.087 (±0.002)	0.090 (±0.025)	**0.063** (±0.006)
BAG	0.023 (±0.007)	0.031 (±0.008)	**0.019** (±0.007)	0.053 (±0.006)	0.030 (±0.004)	0.054 (±0.000)	0.230 (±0.062)	0.052 (±0.002)
XCN	0.014 (±0.007)	0.015 (±0.006)	0.017 (±0.007)	0.012 (±0.012)	0.017 (±0.007)	0.040 (±0.001)	0.015 (±0.002)	**0.009** (±0.002)
ETH2x-FLI	0.031 (±0.010)	0.041 (±0.001)	0.069 (±0.010)	**0.020** (±0.004)	0.030 (±0.002)	0.092 (±0.001)	0.028 (±0.003)	0.030 (±0.004)
stkAAVE	0.128 (±0.018)	0.136 (±0.008)	0.128 (±0.018)	0.154 (±0.005)	0.124 (±0.005)	0.151 (±0.000)	0.147 (±0.008)	**0.078** (±0.017)
GLM	**0.066** (±0.000)	0.068 (±0.001)	0.068 (±0.000)	0.068 (±0.002)	0.067 (±0.002)	0.092 (±0.000)	**0.066** (±0.000)	0.094 (±0.007)
QOM	0.035 (±0.006)	0.038 (±0.010)	0.032 (±0.020)	0.018 (±0.010)	0.035 (±0.020)	0.033 (±0.004)	0.029 (±0.007)	**0.012** (±0.001)
WOJAK	0.008 (±0.001)	0.009 (±0.001)	0.015 (±0.003)	0.029 (±0.017)	0.014 (±0.003)	0.067 (±0.005)	**0.007** (±0.001)	0.009 (±0.000)
DINO	0.061 (±0.017)	0.024 (±0.002)	0.028 (±0.019)	**0.013** (±0.005)	0.030 (±0.005)	0.085 (±0.001)	0.051 (±0.029)	0.018 (±0.007)
Metis	**0.034** (±0.010)	0.045 (±0.006)	0.041 (±0.006)	0.043 (±0.005)	0.042 (±0.004)	0.054 (±0.001)	**0.034** (±0.002)	**0.034** (±0.010)
REPv2	0.061 (±0.003)	0.061 (±0.004)	0.075 (±0.003)	**0.055** (±0.002)	0.063 (±0.004)	0.068 (±0.004)	0.063 (±0.000)	0.066 (±0.004)
TRAC	0.043 (±0.021)	0.030 (±0.003)	0.071 (±0.021)	0.021 (±0.006)	0.025 (±0.009)	**0.018** (±0.000)	0.044 (±0.010)	0.022 (±0.005)
BEPRO	0.012 (±0.002)	0.010 (±0.002)	0.011 (±0.017)	0.011 (±0.011)	0.009 (±0.000)	0.012 (±0.000)	0.006 (±0.001)	**0.004** (±0.001)
1st-Place Count↑	4	1	2	3	0	1	4	**8**
Avg. Rank ↓	3.45	4.10	4.00	4.35	3.90	5.75	4.05	**2.50**
Avg. MAE ↓	0.039	0.042	0.043	0.052	0.040	0.071	0.054	**0.035**

Table 14. MAE results for the Influential Node Count prediction task (regression). Best results are in **bold**, second best are underlined.

	Single Model on Individual Networks							Transfer Models
Dataset	**HTGN**	**TGCN**	**GCLSTM**	**ROLAND**	**EGCN**	**GraphPulse**	**WinGNN**	Hydra **(ours)**
MIR	0.114 (±0.003)	0.119 (±0.005)	0.105 (±0.020)	0.115 (±0.020)	0.114 (±0.017)	0.127 (±0.002)	0.082 (±0.007)	**0.039** (±0.005)
DOGE2.0	0.064 (±0.031)	0.090 (±0.023)	**0.053** (±0.021)	0.070 (±0.015)	0.059 (±0.021)	0.087 (±0.004)	0.091 (±0.009)	0.126 (±0.032)
MUTE	0.028 (±0.004)	0.042 (±0.002)	**0.018** (±0.002)	0.051 (±0.006)	0.042 (±0.012)	0.021 (±0.001)	0.045 (±0.033)	0.045 (±0.027)
EVERMOON	**0.011** (±0.002)	0.014 (±0.006)	0.018 (±0.008)	0.014 (±0.004)	0.032 (±0.015)	0.235 (±0.004)	0.026 (±0.006)	0.038 (±0.024)
DERC	0.069 (±0.007)	0.084 (±0.001)	0.053 (±0.002)	0.104 (±0.011)	0.058 (±0.010)	0.048 (±0.001)	0.077 (±0.003)	**0.033** (±0.017)
ADX	0.016 (±0.003)	0.015 (±0.000)	**0.012** (±0.001)	0.022 (±0.009)	0.015 (±0.001)	0.020 (±0.001)	0.015 (±0.004)	0.030 (±0.001)
HOICHI	0.039 (±0.011)	**0.020** (±0.007)	0.046 (±0.017)	0.030 (±0.015)	0.034 (±0.016)	0.047 (±0.009)	0.024 (±0.016)	0.055 (±0.028)
SDEX	0.037 (±0.011)	0.049 (±0.022)	**0.031** (±0.012)	0.058 (±0.017)	0.037 (±0.005)	0.067 (±0.009)	0.066 (±0.025)	0.042 (±0.019)
BAG	**0.009** (±0.000)	0.017 (±0.002)	0.030 (±0.008)	0.019 (±0.010)	0.030 (±0.009)	0.064 (±0.004)	0.074 (±0.094)	0.075 (±0.027)
XCN	0.061 (±0.008)	0.155 (±0.009)	**0.055** (±0.003)	0.124 (±0.005)	0.066 (±0.008)	0.080 (±0.004)	0.159 (±0.029)	0.126 (±0.033)
ETH2x-FLI	0.050 (±0.007)	0.053 (±0.035)	0.100 (±0.014)	**0.023** (±0.005)	0.044 (±0.010)	0.108 (±0.003)	0.033 (±0.010)	0.033 (±0.020)
stkAAVE	0.062 (±0.001)	0.080 (±0.009)	0.062 (±0.001)	0.057 (±0.005)	0.061 (±0.006)	0.108 (±0.009)	0.066 (±0.003)	**0.042** (±0.013)
GLM	0.066 (±0.002)	0.057 (±0.001)	0.067 (±0.004)	0.057 (±0.005)	0.054 (±0.002)	0.082 (±0.000)	0.053 (±0.002)	0.075 (±0.017)
QOM	0.060 (±0.004)	0.088 (±0.040)	0.061 (±0.032)	0.074 (±0.018)	0.075 (±0.015)	0.076 (±0.004)	0.062 (±0.012)	**0.039** (±0.020)
WOJAK	**0.007** (±0.001)	0.008 (±0.003)	0.012 (±0.003)	0.027 (±0.010)	0.011 (±0.004)	0.066 (±0.019)	**0.007** (±0.001)	0.036 (±0.027)
DINO	0.078 (±0.036)	0.024 (±0.004)	0.068 (±0.001)	0.024 (±0.003)	0.036 (±0.007)	0.087 (±0.003)	**0.022** (±0.000)	0.034 (±0.002)
Metis	0.056 (±0.003)	0.078 (±0.004)	0.068 (±0.005)	0.085 (±0.030)	0.073 (±0.004)	0.071 (±0.010)	0.063 (±0.001)	**0.046** (±0.008)
REPv2	**0.115** (±0.000)	0.118 (±0.006)	0.119 (±0.002)	**0.115** (±0.001)	0.138 (±0.027)	0.127 (±0.000)	0.126 (±0.001)	0.129 (±0.022)
TRAC	0.045 (±0.005)	0.058 (±0.002)	0.079 (±0.002)	0.055 (±0.009)	0.056 (±0.005)	**0.033** (±0.005)	0.074 (±0.009)	0.043 (±0.023)
BEPRO	0.016 (±0.006)	0.014 (±0.003)	0.012 (±0.002)	0.013 (±0.001)	0.012 (±0.002)	0.012 (±0.000)	**0.010** (±0.001)	0.033 (±0.018)
1st-Place Count↑	4	1	5	2	0	1	4	**5**
Avg. Rank ↓	**3.52**	4.85	3.80	4.55	4.20	5.90	4.28	4.90
Avg. MAE ↓	**0.050**	0.059	0.053	0.057	0.052	0.078	0.059	0.056