EBM Life Cycle: MCMC Strategies for Synthesis, Defense, and Density Modeling

Abstract

This work presents strategies to learn an Energy-Based Model (EBM) according to the desired length of its MCMC sampling trajectories. MCMC trajectories of different lengths correspond to models with different purposes. Our experiments cover three different trajectory magnitudes and learning outcomes: 1) shortrun sampling for image generation; 2) midrun sampling for classifier-agnostic adversarial defense; and 3) longrun sampling for principled modeling of image probability densities. To achieve these outcomes, we introduce three novel methods of MCMC initialization for negative samples used in Maximum Likelihood (ML) learning. With standard network architectures and an unaltered ML objective, our MCMC initialization methods alone enable significant performance gains across the three applications that we investigate. Our results include state-of-the-art FID scores for unnormalized image densities on the CIFAR-10 and ImageNet datasets; state-of-the-art adversarial defense on CIFAR-10 among purification methods and the first EBM defense on ImageNet; and scalable techniques for learning valid probability densities.

1 Introduction

Generative modeling of complex signals is one of the fundamental challenges of computational cognition. The importance of studying generative models is often justified by the Analysis-by-Synthesis hypothesis, which posits that human cognition is an interplay of bottom-up information and top-down synthesis from world states. Powerful generative models could provide the foundation of the imaginative capabilities of future machine intelligence. One approach is to posit the existence of a density $q(x)$ of signals x that generates data samples, and to learn $q(x)$ using a flexible model $p(x; \theta)$, where θ is a model parameter. This approach is taken by Energy-Based Models (EBMs) (Xie et al., 2016), normalizing flows (Kingma & Dhariwal, 2018), score-based models (Song & Ermon, 2019; 2020), and auto-regressive models (Oord et al., 2016), as well as by Variational Auto-encoders (VAEs) (Kingma & Welling, 2013) using a joint model $p(x, z; \theta)$. In this work we consider modeling $q(x)$ using an EBM density $p(x; \theta)$ for image signals x. See Appendix A for a brief review of Maximum Likelihood learning with an EBM.

The primary goal of most deep generative modeling is to generate realistic images. It is well-known that shortrun sampling with an EBM is an effective method for image generation, but synthesis results still lag behind GANs (Goodfellow et al., 2014), score models, and diffusion models (Ho et al., 2020). Other directions of EBM research include learning valid densities (Nijkamp et al., 2020), combining discriminative and generative learning via the Joint Energy Model (Grathwohl et al., 2020) and relatives, and using an EBM for defense against adversarial attacks (Hill et al., 2021). In this work, we focus on unconditional learning where EBMs are trained exclusively on unlabeled images. We explore the tasks of image synthesis, adversarial defense, and density modeling to examine a breadth of capabilities for the unconditional EBM. Image synthesis is a shared goal across all generative models, while defense and density modeling are tasks that are especially suitable for EBMs. See Appendix B for a thorough comparison of EBM and other generative models from the perspective of synthesis, defense, and density estimation.

Each task is naturally associated with a certain length of MCMC trajectory. Image synthesis is most effective with shortrun trajectories (about 20 to 200 steps) that can rapidly generate new images. Adversarial defense requires midrun trajectories (about 200 to 2000 steps) that can preserve the class

Figure 1: Illustration of the sampling trajectories that we study in this work. The shortrun samples are initialized from a generator that is trained in tandem with the EBM because the goal is self-contained synthesis. Midrun and longrun samples are initiated from a high-quality starting image obtained from a pre-trained SNGAN, and we study the ability of the EBMs to preserve the quality of the input image from defense and density estimation points of view. The plots show the FID score (Heusel et al., 2017) of 5,000 samples across Langevin steps. The shortrun samples improve on the generator initialization to achieve high-quality synthesis around 250 steps. The midrun samples achieve reasonably low FID in a critical range of about 2k steps where defense can be achieved. The longrun sample maintains reasonable synthesis across the entire trajectory, and much further. The shortrun and midrun samples eventually produce defective results outside of their tuned window of stability.

features while sampling removes adversarial signals. Density modeling requires longrun trajectories (50K steps or more) to ensure proper calibration of probability mass for the model steady-state. It is known that EBMs have a near universal tendency to learn an misaligned steady-state focusing on unrealistic images (Nijkamp et al., 2020), and there are very few existing solutions to correct this. We intuitively refer to the spectrum of trajectories as the life cycle of an MCMC sample, from youth through middle age to maturity. Young samples have the highest quality visual appearance, middle age samples are useful for securing classifiers, and mature samples represent grounded knowledge of the data density (or lack thereof in the widespread case of a misaligned steady-state). Figure 1 illustrates the sampling paths that we study in this work.

Ideally, a valid density estimator would also be a good synthesizer and a good defender. However, synthesis quality and density modeling are goals that tend to be at odds with each other. High-quality synthesis is easier to achieve using shortrun sampling with a defective density than long-run sampling with a stable density (Nijkamp et al., 2020). Unfortunately, models with high-quality shortrun synthesis lack the stability needed for defense. The EBM defense from Hill et al. (2021) advocates for the use of a valid density approximation to stabilize trajectories, but this requirement might be too strict given the difficulty of density estimation. Learning midrun sampling trajectories sufficient for defense is much more feasible for complex datasets such as ImageNet than full density estimation, even if longrun samples from the defensive model are not realistic. Our work is the first to explore this possibility. The overarching purpose of this paper is to discuss techniques for building sample paths from shortrun to longrun, with the hope that these techniques will eventually enable both high quality synthesis and defense to be accomplished with a model that is also a valid density. For now, the difficulty of valid density modeling leads us to restrict our focus to separate time scales of the sampling regime necessary for each task. Interestingly, EBM learning naturally accommodates learning at many different trajectory lengths.

Strategies for improving EBM learning beyond the standard framework (e.g. Xie et al. (2018); Du & Mordatch (2019); Nijkamp et al. (2020)) can broadly be divided into methods that focus on the initialization of MCMC samples (Xie et al., 2018; Gao et al., 2018; Nijkamp et al., 2019) and methods that focus on the ML learning objective (Yu et al., 2020b). Some works explore both (Gao et al., 2020a; Du et al., 2020). Our novel learning methods focus on MCMC initialization, and we retain the standard ML objective and use conventional network architectures. We introduce three new MCMC initialization strategies which are tailored to the three different trajectories lengths we explore. During training we exclusively use shortrun MCMC to ensure computational feasibility. Learning models with midrun and longrun trajectories is accomplished by simulating longer trajectories via well-

chosen initialization and optimizer annealing. Our initialization strategies are able to significantly improve the state-of-the-art across the tasks we investigate. We summarize our contributions below.

- We propose a hybridization of persistent (Tieleman, 2008) and cooperative (Xie et al., 2018) initialization to overcome limitations of each. The proposed method yields state-of-the-art FID scores for unconditional unnormalized image densities for the CIFAR-10 and ImageNet datasets. The ImagetNet results surpass GANs trained with similar resources. See Section 2.

- We show that persistent initialization with appropriately tuned rejuvenation from in-distribution states can be used to train EBMs with stable trajectories of several thousand MCMC steps. This allows us to extend the method of Hill et al. (2021) to obtain state-of-the-art purification-based defense for CIFAR-10 and to scale the EBM defense to ImageNet. See Section 3.

- We propose a method for principled density estimation that allows incorporation of a rejuvenation step for persistent states. Incorporating rejuvenation allows us to learn well-formed EBM densities at a greater scale than previously possible. See Section 4.

Our initialization methods will primarily build upon persistent (Tieleman, 2008; Du & Mordatch, 2019) and cooperative (Xie et al., 2018) initialization. All of our methods will use a generator network as the source of rejuvenation for persistent states. Our shortrun experiments will learn the generator in tandem with the EBM so the synthesis process is self-contained, while our midrun and longrun experiments will use pretrained generators since we will apply sampling paths from in-distribution initial images rather than synthesizing from scratch.

2 HYBRID PERSISTENT COOPERATIVE LEARNING FOR IMAGE SYNTHESIS

In this section, we focus on on the conventional task of learning an EBM for high quality synthesis with shortrun sampling. We restrict our attention to achieving high quality synthesis without use of pretrained models, in contrast with works such as Che et al. (2020); Alayrac et al. (2019). Our method involves hybridizing persistent (Tieleman, 2008) and cooperative (Xie et al., 2018) initialization. We first briefly cover the strengths and weaknesses of these methods, then discuss our hybridization, and finally present experimental results.

2.1 MOTIVATION: LIMITATIONS OF PERSISTENT AND COOPERATIVE INITIALIZATION

A common framework for learning synthesis with an EBM is to use persistent initialization for MCMC samples with a certain rate of rejuvenation (e.g. 5% chance) from a noise distribution (Du & Mordatch, 2019). This approach can cause instability because shortrun samples used to update the model include a mix of higher-energy burn-in samples and lower-energy realistic images, which can destabilize training by increasing the variance of the gradient of the negative samples in (4). On the other hand, removing rejuvenation can decrease the quality of the learned images because persistent images often become stuck in local modes and develop defects that linger for many updates. Persistent banks also scale poorly to large datasets such as ImageNet because the bank cannot efficiently represent the diversity of the data. Initialization from a cooperative generator network is an appealing alternative because it could enable efficient in-distribution generation of highly diverse appearances. Using a generator for rejuvenation allows samples to begin much closer to the correct energy spectrum, thereby avoid the instability of noise rejuvenation. However, we observe a major limitation of cooperative learning that affects the generator ability to produce diverse initial states. In particular, a generator trained with the cooperative learning objective has difficulty breaking the symmetry of its activations. This happens because shortrun EBM samples are unable to provide novel diversity if the generator initialization already lacks diversity. This is illustrated in Figure 5. Learning quickly becomes unstable without auxiliary techniques such as batch normalization to break generator symmetry. The lack of diversity of shortrun EBM samples limits the results of cooperative learning even when training succeeds.

The strengths and limitations of these methods are complementary. Persistent initialization can reliably provide a diverse set of initial images that represent prior samples of several different model snapshots. Even if a single EBM update is biased to a certain image defect (e.g. MCMC samples are blue-tinged or too bright), on average samples across previous iterations have the correct

diversity. On the other hand, the generator can quickly propose in-distribution states for rejuvenation instead of relying on out-of-distribution noise samples or aggressively augmented persistent samples. Furthermore, training the generator in tandem with the EBM provides an efficient way of generating new samples from scratch after training that match the samples used during training. In contrast, models trained with persistent initialization often cannot produce good samples after training without an in-distribution initialization (Nijkamp et al., 2020). Learning a generator and EBM jointly enables self-contained and reproducible FID implementation to evaluate the learned model.

2.2 HYBRID PERSISTENT COOPERATIVE INITIALIZATION

We visualize our proposed initialization technique in Figure 2. The method features two banks of persistent states. One bank is for persistent images and the other bank is for persistent latent vectors. There will always be a one-to-one pairing between persistent images and persistent latents, meaning that paired states will be drawn from the banks, return to the banks, and experience rejuvenation at the same time. All samples are rejuvenated from the current generator. Other than the pairing and generator rejuvenation source, sampling from banks and rejuvenation with a fixed probability is conducted in the same way as persistent initialization. This pairing is necessary for the cooperative learning loss used to train the generator. Given a batch of paired samples $\{Z_i\}_{i=1}^n$ and $\{X_{i,0}^-\}_{i=1}^n$ drawn from the latent and image bank respectively and a generator network $g(z; \phi)$, we learn ϕ using gradient descent on the reconstruction loss

$$\mathcal{L}(\phi) \propto \sum_{i=1}^n \|g(Z_i; \phi) - T(X_{i,0}^-; \theta)\|_2^2 \tag{1}$$

Figure 2: Cooperative-persistent initialization uses paired latent and image states that a drawn from persistent banks to learn the EBM and generator.

where $T(X_{i,0}^-; \theta) = X_i^-$ represents a shortrun Langevin trajectory with the EBM $p(x; \theta)$. This loss can be derived in the ML framework as a way to teach the output of $g(z; \phi)$ to match the distribution of $p(x; \theta)$. A full implementation of cooperative learning requires an additional sampling process on Z_i, but we use a straight-through estimator (Bengio et al., 2013) and approximate latent sampling with the identity function as originally done in the official MATLAB implementation from Xie et al. (2018). We review further details of the cooperative learning loss in Appendix C.

Intuitively, the loss (1) encourages the output of the generator to match the outcome of the Langevin sampling process (5). Cooperative learning always uses $X_{i,0} = g(Z_i; \phi)$, which corresponds to rejuvenating with probability 1 in our method. This is the root of the limitation of cooperative learning. If $g(z; \phi)$ has little diversity, $T(g(z; \phi); \theta)$ will also have little diversity. This causes extreme oscillation in both the EBM and generator output as $p(x; \theta)$ attempts to cover the modes of $q(x)$ with shortrun samples from low diversity initialization. Despite oscillation in appearance across ϕ, generator samples tend to remain nearly identical for any fixed ϕ, thereby perpetuating the instability and preventing further learning. By drawing samples from the image bank, we are effectively choosing $X_{i,0} = T'(g(z; \phi'))$ where ϕ' represents a past generator parameter and $T'(x)$ represents the composition of Langevin sampling with past EBMs. This allows us to learn ϕ using appropriately diverse initializations spanning samples of several past models. We observe that this simple adjustment has a dramatic effect for improving EBM learning with generator initialization.

2.3 EXPERIMENTS: IMAGE SYNTHESIS WITH SHORTRUN MCMC

We present the results of our new learning process applied to the CIFAR-10, Celeb-A, and ImageNet benchmark datasets, using the image sizes 32×32, 64×64, and 128×128 respectively. A sketch of the hybrid learning algorithm is given in Appendix D. Besides standard deep learning techniques for

Table 1: Comparison of FID scores among representative generative models. (*=EBM, †=conditional)

CIFAR-10 32×32

Model	FID
Ours*	**22.9**
Du et al. (2020)*	25.1
Grathwohl et al. (2021)*	27.5
Gao et al. (2020a)*	37.3
Grathwohl et al. (2020)*	38.4
Du & Mordatch (2019)*	40.6
Yu et al. (2020a)*†	30.9
Du & Mordatch (2019)*†	37.9
Ho et al. (2020)	**3.2**
Song & Ermon (2020)	10.9
Brock et al. (2019)	14.7
Miyato et al. (2018)	21.7

Celeb-A 64×64

Model	FID
Ours*	15.3
Miyato et al. (2018)	**5.7**
Song & Ermon (2020)	10.2
Han et al. (2019)*	31.9

ImageNet 128×128

Model	FID
Ours*	**40.6**
Chen et al. (2019)	43.9
Lee et al. (2021)	58.9
Miyato et al. (2018)	65.7
Miyato et al. (2018)†	**27.6**
Du & Mordatch (2019)*†	43.7

stable optimization, our framework is fully described by the ML objective and MCMC initialization above. We use the SNGAN (Miyato et al., 2018) architectures for all models, where EBMs use the SNGAN discriminator with no normalization. The generator has batch normalization for the CIFAR-10 and Celeb-A experiments only. Table 1 displays the FID scores achieved by our model in comparison with prior methods.

When calculating FID scores, samples are first initialized from the generator then updated with the EBM using a number of Langevin updates tuned to provide optimal synthesis quality. As mentioned before, an appealing aspect of EBM learning with generator initialization is the ease of generating new images from scratch, in contrast with persistent initialization. We use 50K samples with the official FID code from Heusel et al. (2017) to calculate all FID scores. In particular, our scores and framework are consistent with the GAN replication library from Lee & Town (2020). We publicly release the checkpoints, learning code, and FID code for each model. The checkpoints are representative of what is achievable within an ordinary run of the code provided. Our CIFAR-10 results show a significant improvement over prior EBM synthesis and contribute to closing the gap between EBMs and other generative models. Surprisingly, our ImageNet results surpass the results of GANs such as SNGAN (Miyato et al., 2018) and SSGAN (Chen et al., 2019) on unconditional synthesis using a similar magnitude of computational resources.

3 MIDRUN SAMPLERS FOR ADVERSARIAL DEFENSE

This section presents a method for learning EBMs that are capable of preserving the appearance of an in-distribution initial state across several thousand MCMC steps. Such models are useful for the purpose of adversarial defense. Our defense framework is based on the approach in Hill et al. (2021), which uses an EBM to defend an independent naturally trained classifier. Appendix E briefly reviews of the EBM defense and compares this approach with other defense methods. We then present our proposed method for learning a defensive EBM (3), which is based on persistent initialization using a fixed pretrained generator as a source of rejuvenation. Finally, we apply our defense to achieve state-of-the-art performance for purification-based defense on CIFAR-10 and ImageNet.

One limitation of prior EBM defense is the reliance on persistent initialization with no rejuvenation to learn the defensive model. This is done to ensure that defensive sampling trajectories remain stable for arbitrary numbers of steps. However, removing rejuvenation from persistent learning has drawbacks discussed in Section 2.1. In particular, it becomes very difficult to learn meaningful EBMs for large and complex datasets such as ImageNet in this framework because the persistent bank cannot represent the diversity of the dataset and the quality of persistent images without rejuvenation quickly degrades. Methods for efficient learning of defensive EBMs at a greater scale are needed to extend the EBM defense to more realistic situations.

We propose to overcome this obstacle by building on the observation that fully stable sampling paths are not required for successful defense. While the defense from Hill et al. (2021) uses EBMs with stable sampling for 100K steps or more, the defense results require less than 2000 steps. A natural question is whether it is possible to learn stable MCMC trajectories for only a predefined midrun range to achieve the defensive benefits without fully stabilizing samples over longrun trajectories. Defining a learning procedure to obtain such models is the goal of this section. Efficiently learning EBMs with stable midrun trajectories allows us to scale up the EBM defense to significantly more challenging domains.

3.1 IN-DISTRIBUTION REJUVENATION FOR LEARNING A DEFENSIVE EBM

The initialization method for our midrun sampler is similar to standard persistent initialization with the adjustment that persistent states are rejuvenated from a frozen pretrained generator rather than noise. We use a generator in our experiments so that the EBM and generator could be used after training to sample from scratch. This choice is not necessary and rejuvenation from data samples, or another efficient in-distribution initialization, is also effective for learning defensive EBMs. We note that MCMC initialization from a trained generator or from data samples is not explored in recent work because the goal of most current EBM learning is image synthesis, which becomes trivial if EBM trajectories are always initialized from high-quality samples. From the perspective of synthesis our learning process is nearly invisible but from the perspective of defense its utility becomes concrete.

Figure 3: Persistent initialization. Positive samples are from data samples and negative samples are MCMC samples initialized from a batch from an image bank. Some states are randomly rejuvenated.

Learning an EBM for defense involves tuning the length of the sampling trajectory via the number of shortrun training steps and the rejuvenation rate, and tuning the annealing schedule of the EBM optimizer. Given a desired number of MCMC steps K_{def} for a defensive update and a shortrun trajectory $K \approx 100$, we simply set the rejuvenation rate to $p_{\mathrm{rejuv}} = K/K_{\mathrm{def}}$ to ensure that on average samples will travel K_{def} steps before rejuvenation. While in practice we use $K_{\mathrm{def}} = 2000$ and $p_{\mathrm{rejuv}} = 0.05$, we have found that this method can yield stable paths for at least $K_{\mathrm{def}} = 50K$ MCMC steps when p_{rejuv} is low.

Initialization alone is insufficient to stabilize MCMC pathways when model weights are changing quickly. Using a low learning rate late in training is a key aspect of stabilizing sampling paths (Nijkamp et al., 2020; Hill et al., 2021). Intuitively, if the EBM optimizer has a sufficiently low learning rate then MCMC trajectories in the persistent image bank can function as approximate trajectories from the current model, since weights change very little as the persistent states are updated. By annealing in tandem with our initialization, we are effectively using midrun trajectories of length K_{def} initialized from the generator to update the EBM while we are actually using shortrun trajectories of length K from the persistent bank. Annealing is a crucial component for stabilizing both midrun and longrun trajectories. Without annealing, sampling paths are not able to maintain realism for large K_{def}.

3.2 EXPERIMENTS: DEFENDING NATURAL CLASSIFIERS WITH AN EBM

We train our EBMs using the persistent initialization described above in tandem with a pretrained generator on both CIFAR-10 and ImageNet to learn defensive EBMs. We use the same SNGAN models as before for our CIFAR-10 experiments, with the exception that the generator is pretrained instead of learned. For our ImageNet experiments, we use the BigGAN (Brock et al., 2019) discriminator architecture for our EBM modified for input size 224×224 and a pretrained BigGAN Generator. Our naturally trained classifier $f(x)$ is a pretrained WideResNet 28-10 (Zagoruyko & Komodakis, 2016) for CIFAR-10 and a pretrained EfficientNetB-7 architecture (Tan & Le, 2020) for ImageNet.

We evaluate our models using the attack gradient (8) and Algorithm 2. For CIFAR-10 we use $K_{\mathrm{def}} = 1500$ Langevin steps with l_∞ adversarial parameters $\varepsilon = \frac{8}{255}$ and $\alpha = \frac{2}{255}$, where ε is the size of the l_∞ ball and α is the gradient step size. For ImageNet we used $K_{\mathrm{def}} = 200$ Langevin steps for defense with l_∞ adversarial parameters $\varepsilon = \frac{2}{255}$ and $\alpha = \frac{1}{255}$. We attack ImageNet for 50 attacks

Table 2: Defense vs. whitebox attacks with l_∞ perturbation $\varepsilon = 8/255$ for CIFAR-10.

Defense	$f(x)$ Train Ims.	$T(x)$ Method	Attack	Nat.	Adv.
Ours	Natural	Langevin	BPDA+EOT	0.79	**0.0.567**
(Hill et al., 2021)	Natural	Langevin	BPDA+EOT	0.8412	0.5490
(Song et al., 2018)	Natural	Gibbs Update	BPDA	0.95	0.09
(Srinivasan et al., 2019)	Natural	Langevin	PGD	–	0.0048
(Yang et al., 2019)	Transformed	Mask + Recon.	BPDA+EOT	0.94	0.15
(Carmon et al., 2019)	Adversarial	–	PGD	0.897	**0.625**
(Zhang et al., 2019)	Adversarial	–	PGD	0.849	0.5643
(Shafahi et al., 2019)	Adversarial	–	PGD	0.859	0.4633
(Madry et al., 2018)	Adversarial	–	PGD	0.873	0.458

steps across 10K val samples. For CIFAR-10 we perform the same number of attacks across 5K validation samples.

Table 3: Defense vs. l_∞ whitebox attacks for ImageNet.

Defense	$f(x)$ Train Ims.	ε	Nat.	Adv.
Ours	Natural	$\frac{2}{255}$	0.684	0.418
(Wong et al., 2020)	Adversarial	$\frac{2}{255}$	0.609	0.4339
(Shafahi et al., 2019)	Adversarial	$\frac{2}{255}$	0.644	0.4339
(Qin et al., 2019)	Adversarial	$\frac{4}{255}$	0.822	0.427
(Xie et al., 2021)	Adversarial	$\frac{4}{255}$	0.822	**0.586**

On CIFAR-10, we surpass the robustness of the existing EBM defense on CIFAR-10 using a much more reliable learning framework. The importance of midrun learning is clearly demonstrated by our successful application of EBM defense to ImageNet at the resolution 224×224. The robustness of a naturally trained classifier secured by our EBM is comparable with methods such as Fast and Free Adversarial training. While the ImageNet results for EBM defense are not yet on par with state-of-the-art adversarially trained models, our experiments are an important proof of concept that the method can be scaled. See Appendix F for diagnostics and further discussion.

4 LONGRUN SAMPLING FOR DENSITY ESTIMATION

Our final objective is to introduce scalable tools for learning a valid image density with an EBM. Nijkamp et al. (2020) revealed that, in the absence of careful implementation, EBM learning always results in an unexpected outcome where steady-state samples from the learned density $p(x; \theta)$ have an oversaturated and unrealistic appearance that differs drastically from shortrun samples used during learning. This outcome affects all EBMs that are not specifically trained to overcome this defect, as well as related models such as Score Matching (Song & Ermon, 2019; 2020) as shown in Figure 7. To our knowledge, across different generative models, the only way to learn a well-formed potential energy surface approximating a complex density $q(x)$ that is compatible with efficient MCMC sampling is using an EBM.

Despite the theoretical formulation of the EBM as a potential surface, the problem of principled density estimation has received relatively little attention. Successful image synthesis is sometimes used as misleading evidence of successful density estimation, but we emphasize these outcomes not equivalent. In this section, we address the lack scalable methods to learn valid densities of complex signals by introducing an MCMC initialization can incoporate rejuvenation while still simulating extremely long trajectories. Learning a valid density is a fundamental computational problem that is important in its own right, and we further hope that our learning method leads to EBM clustering techniques based on the potential energy basins of a well-formed density (Nijkamp et al., 2020).

4.1 INCORPORATING REJUVENATION IN DENSITY ESTIMATION

Prior work has suggested that persistent learning is the most effective method for learning a valid EBM density. Furthermore, works that learn a valid density have avoided rejuvenation because

the incorporation of newly rejuvenated samples into the persistent bank ensures that EBM updates will always include samples that are not at the steady-state. However, persistent learning without rejuvenation has shortcomings mentioned in Section 3. We present hypothesized conditions for learning a valid density that motivate the design of our MCMC initialization:

- After a certain point in training, all samples used to update the EBM must be approximate steady-state samples of the current model $p(x; \theta)$.

- Persistent samples that are newly rejuvenated (up to about 50K Langevin steps since rejuvenation, and possibly many more) cannot be approximate steady-state samples for any current known rejuvenation sources, including data, generators, and noise.

- Persistent samples that have undergone sufficiently many *lifetime* Langevin updates for a model whose weights are changing very slowly can be approximate steady-state samples.

Figure 4: Visualization of our longrun initializatin procedure. Newly rejuvenated samples must remain the the burnin bank until they have approach the model steady-state, at which point they move to the update bank to be used for model gradients.

Both the second and third point are corroborated by prior work (Nijkamp et al., 2020; Hill et al., 2021) as well as our own observations. The third point means that persistent states updated with shortrun Langevin can eventually act as longrun Langevin samples if the optimizer learning rate is small, because the EBM samples in previous timesteps are essentially samples from the current EBM.

Learning a valid density that includes rejuvenation while satisfying the conditions above requires separating the newly rejuvenated samples from samples that are used to update the EBM. This leads us to introduce two persistent image banks: one for newly rejuvenated samples, and one for samples that will be used to update the EBM. Samples in the newly rejuvenated bank that have been updated sufficiently many times will eventually replace samples from the bank used to update the EBM, at which point newly rejuvenated states will be added to the first bank. Figure 4 shows a visualization of the MCMC initialization method. As in Section 3, we will use a pre-trained generator to efficiently obtain high-quality rejuvenated samples so that the generation process is fully synthetic, although data samples could be used as well. Our goal is to preserve the sample quality for an arbitrary number of MCMC steps. We note that this is a sufficient but not necessary condition for learning a valid EBM density. Nonetheless, stable sampling is an important step towards rigorous probabilistic EBMs.

Table 4: FID for 5K samples after 100K Steps.

Data	FID
CIFAR-10	39.7
Celeb-A	37.4
ImageNet	82.3

Even with our improved initialization, we find that extremely longrun trajectories of 1 million or more MCMC steps still tend to oversaturate, although to a much lesser degree. To further stabilize the appearance of extremely longrun Langevin samples, we include prior energy terms in the model. Our longrun EBMs have the form

$$U_{\theta_0, \sigma}(x; \theta) = U'(x; \theta) + U_0(x; \theta_0) + \frac{1}{2\sigma^2} \|x\|_2^2 \qquad (2)$$

where $U'(x; \theta)$ is the model whose weights are updated, $U'(x; \theta')$ is a prior EBM with fixed weights θ' and σ is a parameter controlling the strength of a Gaussian prior. We used a prior EBM trained to be a midrun sampler on the same dataset as the target EBM. The role of the prior EBM is to provide some stability but also to provide a tendency to oversaturate at longer trajectories so that the current EBM learns to correct oversaturation. The Gaussian prior is meant to discourage unbounded activations outside of the image hypercube. We find that including both of these terms significantly improves the ability to learn quality synthesis over long trajectories.

4.2 EXPERIMENTS: EBM DENSITY ESTIMATION

In these experiments, we learn EBM models that have stable MCMC trajectories for an arbitrary number of steps. We apply the longrun learning method in Algorithm 4 to CIFAR-10, Celeb-A, and

ImageNet at the resolutions 32×32, 64×64, and 64×64 respectively. Pre-trained SNGANs are used to rejuvenate images for CIFAR-10 and Celeb-A, while a resized images from a pre-trained BigGAN are used to rejuvenate ImageNet samples. We require that samples have been updated for 50K to 75K Langevin steps since the last rejuvenation before states are moved from the burn-in bank to the update bank. Our EBMs all use the discriminator architecture of the SNGAN model without spectral normalization. We use pretrained midrun samples for our prior EBM terms in the learned energy (2). See Appendix H for an algorithm sketch. Figure 1 shows the evolution of FID score over Langevin steps starting from the generator network for our CIFAR-10 model. Table 4 shows the FID scores of 5K samples for each dataset. Visualizations of longrun samples with 100K steps and extremely longrun samples using 1 million Langevin steps are shown in Appendix J.

5 RELATED WORK

Energy-Based Models. Early forms of EBMs include the exponential family distribution, the FRAME model (Zhu et al., 1998) and Restricted Boltzmann Machines (Hinton, 2002). Recent work has introduced the EBM with a ConvNet potential (Xie et al., 2016; Du & Mordatch, 2019). This dramatically increased the learning capacity of the model which led to many follow-up works on image synthesis (Gao et al., 2018; Lee et al., 2018; Nijkamp et al., 2019), adversarial robustness (Hill et al., 2021), and joint learning of discriminative and generative models (Grathwohl et al., 2020). Several works investigate training and EBM in tandem with an auxilary model. Kim & Bengio (2016) train an EBM and generator and tandem without MCMC by using samples from the generator as direct approximations of the EBM density and training the generator using a variational objective. A similar approach is explored by Grathwohl et al. (2021). Cooperative learning (Xie et al., 2018) trains the EBM and generator by using the generator to initialize samples needed to train the EBM and uses reconstruction loss between generator and EBM samples to learn the generator. Gao et al. (2020a) learn an EBM using Noise Contrastive Estimation with an auxiliary flow model. Xiao et al. (2021) use a pretrained VAE to facilitate EBM learning. Our work builds on cooperative learning by identifying and resolving symmetry breaking problems in early training, leading to state-of-the-art EBM synthesis for unconditional ImageNet. Despite the formulation of the EBM as an unnormalized density, it has been shown that most EBMs have strong misaligned steady-state distributions (Nijkamp et al., 2020). Our work introduces new methods to learn a model with correct steady-state alignment.

Adversarial Robustness. Adversarial Training (AT) (Madry et al., 2018), which trains a classifier using PGD-generated adversaries, is the most popular and studied adversarial defense. Many variations and improvements have been introduced, including optimizing the training loop by recycling gradients of past adversaries (Shafahi et al., 2019), combining single step FGSM with random initialization to achieve similar robustness Wong et al. (2020), learning with auxiliary unlabeled data Carmon et al. (2019), local linearization (Qin et al., 2019), and the use of smooth activation functions Xie et al. (2021). An alternative approach to adversarial training involves the use of preprocessing transformations. Randomized smoothing (Cohen et al., 2019) and related methods (Salman et al., 2020) add noise to the input signal to remove adversarial signals. Many other preprocessing defenses have been proposed (Guo et al., 2018; Song et al., 2018; Yang et al., 2019), but nearly all of these methods can be broken by adaptive attacks that are aware of the preprocessing method (Athalye et al., 2018). A notable exception is the EBM defense (Hill et al., 2021), which uses midrun MCMC trajectories to purify images. We ease the restriction of learning EBMs with stability for arbitrary MCMC runs in the EBM defense (Hill et al., 2021) by introducing a midrun sampler that enables faster learning of defensive EBMs and allows the EBM defense to scale to more complex datasets.

6 CONCLUSION AND FUTURE WORK

We have described three unique MCMC initializations for EBM using different sampling trajectories: shortrun for synthesis, midrun for defense, and long-run for density estimation. Furthermore, we have elaborated on different MCMC initialization strategies used to stabilize these models for different sampling lengths. We have demonstrated the flexibility of these mechanisms by using similar architectures, data, and training platforms to create different EBMs for different applications. We hope that future research incorporates these new training initialization schemes to improve their generative models for a wide variety of tasks.

7 REPRODUCIBILITY

We have made our results reproducible by releasing the anonymized github repository `https://anonymous.4open.science/r/lifecycle-3346/`. All hyperparameters can be found in the configuration files, all checkpoints for the various EBMs are also under the release section and there is a README.MD describing how to use this repository to reproduce the results described herein. We will release a non-anonymous repository at a later date. All our results were trained on the standard CIFAR-10, ImageNet, and Celeb-A datasets which are publicly available. Our computational resources were primarily 5 TPUv2-8 machines and 5 TPUv3-8 machines made available by the Tensorflow Research Cloud (TRC) program sponsored by Google. These resources are widely available to researchers who apply to the program from accredited institutions. We are very grateful to Google for granting us access to the resources that made this work possible.

REFERENCES

Jean-Baptiste Alayrac, Jonathan Uesato, Po-Sen Huang, Alhussein Fawzi, Robert Stanforth, and Pushmeet Kohli. Are labels required for improving adversarial robustness? In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 274–283, 2018.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=B1xsqj09Fm`.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled data improves adversarial robustness. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Tong Che, Ruixiang Zhang, Jascha Sohl-Dickstein, Hugo Larochelle, Liam Paull, Yuan Cao, and Yoshua Bengio. Your gan is secretly an energy-based model and you should use discriminator driven latent sampling. *arXiv preprint arXiv:2003.06060*, 2020.

Ting Chen, Xiaohua Zhai, Marvin Ritter, Mario Lucic, and Neil Houlsby. Self-supervised gans via auxiliary rotation loss. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12154–12163, 2019.

Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 1310–1320, 2019.

Yilun Du and Igor Mordatch. Implicit generation and modeling with energy based models. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Yilun Du, Shuang Li, Joshua Tenenbaum, and Igor Mordatch. Improved contrastive divergence training of energy based models. *arXiv preprint arXiv:2012.01316*, 2020.

Ruiqi Gao, Yang Lu, Junpei Zhou, Song-Chun Zhu, and Ying Nian Wu. Learning generative convnets via multi-grid modeling and sampling. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9155–9164, 2018.

Ruiqi Gao, Erik Nijkamp, Diederik P Kingma, Zhen Xu, Andrew M Dai, and Ying Nian Wu. Flow contrastive estimation of energy-based models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7518–7528, 2020a.

Ruiqi Gao, Yang Song, Ben Poole, Ying Nian Wu, and Diederik P Kingma. Learning energy-based models by diffusion recovery likelihood. *arXiv preprint arXiv:2012.08125*, 2020b.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Will Grathwohl, Kuan-Chieh Wang, Joern-Henrik Jacobsen, David Duvenaud, Mohammad Norouzi, and Kevin Swersky. Your classifier is secretly an energy based model and you should treat it like one. In *International Conference on Learning Representations*, 2020.

Will Sussman Grathwohl, Jacob Jin Kelly, Milad Hashemi, Mohammad Norouzi, Kevin Swersky, and David Duvenaud. No {mcmc} for me: Amortized sampling for fast and stable training of energy-based models. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=ixpSxO9flk3`.

Cheng-En Guo, Song-Chun Zhu, and Ying Nian Wu. Modeling visual patterns by integrating descriptive and generative methods. *International Journal of Computer Vision*, 53:5–29, 2003.

Chuan Guo, Mayank Rana, Moustapha Cisse, and Laurens van der Maaten. Countering adversarial images using input transformations. In *International Conference on Learning Representations*, 2018.

Tian Han, Erik Nijkamp, Xiaolin Fang, Mitch Hill, Song-Chun Zhu, and Ying Nian Wu. Divergence triangle for joint training of generator model, energy-based model, and inferential model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8670–8679, 2019.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, volume 33, pp. 6629–6640, 2017.

Mitch Hill, Jonathan Craig Mitchell, and Song-Chun Zhu. Stochastic security: Adversarial defense using long-run dynamics of energy-based models. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=gwFTuzxJW0`.

Geoffrey E. Hinton. Training products of experts by minimizing contrastive divergence. *Neural Computation*, 14(8):1771–1800, 2002.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models, 2020.

Taesup Kim and Yoshua Bengio. Deep directed generative models with energy-based probability estimation, 2016.

Diederik P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. *arXiv preprint arXiv:1807.03039*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Kwonjoon Lee, Weijian Xu, Fan Fan, and Zhuowen Tu. Wasserstein introspective neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3702–3711, 2018.

Kwot Sin Lee and Christopher Town. Mimicry: Towards the reproducibility of gan research. *arXiv preprint arXiv:2005.02494*, 2020.

Kwot Sin Lee, Ngoc-Trung Tran, and Ngai-Man Cheung. Infomax-gan: Improved adversarial image generation via information maximization and contrastive learning. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 3942–3952, 2021.

Kyungmin Lee and Seyoon Oh. Efficient randomized smoothing by denoising with learned score function, 2021. URL `https://openreview.net/forum?id=sI4SVtktqJ2`.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=B1QRgziT-.

Erik Nijkamp, Mitch Hill, Song-Chun Zhu, and Ying Nian Wu. Learning non-convergent non-persistent short-run MCMC toward energy-based model. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Erik Nijkamp, Mitch Hill, Tian Han, Song-Chun Zhu, and Ying Nian Wu. On the anatomy of MCMC-based maximum likelihood learning of energy-based models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, 2020.

Aaron van den Oord, Nal Kalchbrenner, Oriol Vinyals, Lasse Espeholt, Alex Graves, and Koray Kavukcuoglu. Conditional image generation with pixelcnn decoders. *arXiv preprint arXiv:1606.05328*, 2016.

Chongli Qin, James Martens, Sven Gowal, Dilip Krishnan, Krishnamurthy Dvijotham, Alhussein Fawzi, Soham De, Robert Stanforth, and Pushmeet Kohli. Adversarial robustness through local linearization, 2019.

Hadi Salman, Mingjie Sun, Greg Yang, Ashish Kapoor, and J. Zico Kolter. Denoised smoothing: A provable defense for pretrained classifiers. In *Advances in Neural Information Processing Systems*, volume 33, pp. 21945–21957, 2020.

Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S. Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free!, 2019.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *arXiv preprint arXiv:1907.05600*, 2019.

Yang Song and Stefano Ermon. Improved techniques for training score-based generative models, 2020.

Yang Song, Taesup Kim, Sebastian Nowozin, Stefano Ermon, and Nate Kushman. Pixeldefend: Leveraging generative models to understand and defend against adversarial examples. In *International Conference on Learning Representations*, 2018.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*, 2020.

Vignesh Srinivasan, Arturo Marban, Klaus-Robert Muller, Wojciech Samek, and Shinichi Nakajima. Defense against adversarial attacks by langevin dynamics. *arxiv preprint arXiv:1805.12017*, 2019.

Mingxing Tan and Quoc V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks, 2020.

Tijmen Tieleman. Training restricted boltzmann machines using approximations to the likelihood gradient. In *Proceedings of the 25th international conference on Machine learning*, pp. 1064–1071, 2008.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. In *Advances in Neural Information Processing Systems*, volume 33, pp. 1633–1645, 2020.

Eric Wong, Leslie Rice, and J. Zico Kolter. Fast is better than free: Revisiting adversarial training. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BJx040EFvH.

Zhisheng Xiao, Karsten Kreis, Jan Kautz, and Arash Vahdat. {VAEBM}: A symbiosis between variational autoencoders and energy-based models. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=5m3SEczOV8L.

Cihang Xie, Mingxing Tan, Boqing Gong, Alan Yuille, and Quoc V. Le. Smooth adversarial training, 2021.

Jianwen Xie, Yang Lu, Song-Chun Zhu, and Yingnian Wu. A theory of generative convnet. In *Proceedings of the 33rd International Conference on Machine Learning*, pp. 2635–2644, 2016.

Jianwen Xie, Yang Lu, Ruiqi Gao, and Ying Nian Wu. Cooperative learning of energy-based model and latent variable model via mcmc teaching. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Yuzhe Yang, Guo Zhang, Dina Katabi, and Zhi Xu. Me-net: Towards effective adversarial robustness with matrix estimation. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 7025–7034, 2019.

Jongmin Yoon, Sung Ju Hwang, and Juho Lee. Adversarial purification with score-based generative models. *arXiv preprint arXiv:2106.06041*, 2021.

Lantao Yu, Yang Song, Jiaming Song, and Stefano Ermon. Training deep energy-based models with f-divergence minimization, 2020a.

Lantao Yu, Yang Song, Jiaming Song, and Stefano Ermon. Training deep energy-based models with f-divergence minimization. In *International Conference on Machine Learning*, pp. 10957–10967. PMLR, 2020b.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 7472–7482, 2019.

Song-Chun Zhu. Statistical modeling and conceptualization of visual patterns. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 25:691–712, 2003.

Song-Chun Zhu, Ying Nian Wu, and David Mumford. Filters, random fields and maximum entropy (FRAME): towards a unified theory for texture modeling. *International Journal of Computer Vision*, 27(2):107–126, 1998.

A   REVIEW OF EBM LEARNING AND MCMC INITIALIZATION

We briefly review the main components of EBM learning following the standard method derived from works such as Hinton (2002); Zhu et al. (1998); Xie et al. (2016). Throughout our experiments, we will use this framework and focus on exploring different possibilities for MCMC initialization. A deep EBM has the form

$$p(x; \theta) = \frac{1}{Z(\theta)} \exp\{-U(x; \theta)\} \tag{3}$$

where $U(x; \theta)$ is a ConvNet with weights θ and $Z(\theta)$ is the intractable normalizing constant. Maximum Likelihood (ML) learning uses the objective $\arg\min_\theta D_{KL}(q(x)||p(x; \theta))$, which can be minimized using the stochastic gradient

$$\nabla \mathcal{L}(\theta) \approx \frac{1}{n} \sum_{i=1}^{n} \nabla_\theta U(X_i^+; \theta) - \frac{1}{n} \sum_{i=1}^{n} \nabla_\theta U(X_i^-; \theta) \tag{4}$$

where the positive samples $\{X_i^+\}_{i=1}^n$ are a set of data samples and the negative samples $\{X_i^-\}_{i=1}^n$ are samples from the current model $p(x; \theta)$. To obtain the negative samples for a deep EBM, it is common to use MCMC sampling with the K steps of Langevin equation

$$X^{(k+1)} = X^{(k)} - \frac{\eta^2}{2} \nabla_{X^{(k)}} U(X^{(k)}; \theta) + \eta Z_k, \tag{5}$$

where η is the step size and $Z_k \sim N(0, I)$. The Langevin trajectories are initialized from a set of states $\{X_{i,0}^-\}_{i=1}^n$ obtained from a certain initialization strategy. The method of MCMC initialization determines many of the properties of the learned model.

There are a number of different methods of MCMC initialization for EBM learning. Early Restricted Boltzmann Machines use data samples as the initial states in every iteration (Hinton, 2002). Persistent initialization (Zhu et al., 1998; Tieleman, 2008) maintains a bank of MCMC samples from previous model updates as the source of MCMC states in the current iteration. Persistent states can be rejuvenated with a certain probability instead of returning to the image bank. Potential sources for rejuvenation include noise samples (Du & Mordatch, 2019), data augmentation applied to persistent states (Du et al., 2020), data samples, or samples from a generator network. Cooperative learning initializes MCMC states from a generator learned in tandem with an EBM (Xie et al., 2018). The Multi-grid model (Gao et al., 2018) initializes samples from lower resolution images. Noise initialization is explored by Nijkamp et al. (2019). The VAEBM (Xiao et al., 2021) initializes samples from a pretrained VAE generator. EBMs can learn stable shortrun synthesis from virtually any initialization distribution as long as the initialization distribution remains fairly consistent across training updates. EBM sampling can produce realistic images after training when the testing initialization closely matches the training initialization, while synthesis can fail for test initializations unseen during training. (Nijkamp et al., 2020).

B   COMPARISON OF EBM AND OTHER GENERATIVE MODELS

In this section, we briefly compare the EBM with other kinds of generative models. Besides the probabilistic model families mentioned in the introduction, we consider two other popular approaches. One approach is to design an objective that promotes realistic synthesis by producing fake samples and distinguishing these from real samples, as done by the Generative Adversarial Network (GAN) model (Goodfellow et al., 2014) and its many variations. Another approach comes from recent diffusion models that define a sequence of intermediate distributions to transport a signal between a reference density $p_0(x)$ and $q(x)$ (Ho et al., 2020; Song et al., 2020).

Among probabilistic models, the synthesis quality is typically the highest for score matching models that only try to learn distribution gradients and typically lower for models like normalizing flows and auto-regressive objectives that model the full normalized density. EBM synthesis usually lies somewhere in between. Score-matching does not require MCMC sampling during learning and as a consequence learning tends to be more straightforward than learning for EBMs. Yet we believe that MCMC sampling is not yet fully optimized for EBM learning and that EBMs can match or surpass score-matching models. Our shortrun initialization method is an effort in this direction.

Coop. (w/ BN)   Coop. (w/o BN)   Ours (w/ BN)   Ours (w/o BN)

Figure 5: Comparison of cooperative learning (Xie et al., 2018) and our hybrid cooperative-persistent learning using appearance of shortrun samples after 500 updates of the EBM using a generator with and without batch norm. The cooperative models have difficulty achieving diversity in the shortrun samples because the EBM is unable to significantly change the appearance of initial generator images. In fact, we find cooperative learning is not possible at all without generator batch normalizatin. Our hybrid initialization increases the diversity of shortrun samples by including persistent samples from previous EBM updates. This accelerates learning and dramatically improves synthesis results.

GANs and diffusion models differ fundamentally from probabilistic models of the form $p(x; \theta)$ in the sense that the former are explicitly formulated from the perspective of synthesis while the latter are formulated for density modeling and synthesis is a byproduct. In the literature, the former types of models are sometimes referred to as *generative* models (in a more specific sense of the term than typical) while the latter are called *descriptive* models (Guo et al., 2003; Zhu, 2003). Generative models map one set to another (e.g. a generator mapping a latent vector to an image), while descriptive models define a concept in terms of the set of states that have a certain descriptive property (e.g. steady-state samples of an EBM). A descriptive model can be used for generative purposes (e.g. Langevin sampling with an EBM) but this is not the direct goal of descriptive learning.

From this perspective, it is perhaps unsurprising that generative methods such as GANs and diffusion models surpass EBMs in terms of synthesis, since that the model formulations are geared directly towards generation. Nonetheless, we believe that EBMs have unique properties that distinguish them from generative models and other descriptive models. In particular, EBM learning offers a control of the MCMC sampling paths from a learned model that $p(x; \theta)$ is, to our knowledge, is unobtainable under other current frameworks. Unlike GAN models which map a trivial distribution to a complex signal distribution without actually describing the signal distribution, EBMs directly model the complex signal distribution via a potential energy surface. Normalizing flow models are too large for efficient MCMC sampling. VAE models cannot be efficiently marginalized. Score-based models exhibit the same oversaturation behavior as miscalibrated EBMs when sampling at a constant noise level for many steps (see Figure 7), and one cannot adjust MCMC stability during learning as we do for EBMs, because sampling is not used when training a score model. Diffusion-based methods do not learn an approximation $p(x; \theta)$, but rather can be formulated as learning a conditional probability $p(x|x'; \theta)$ that describes a state x given a state x' a rung above or below x in the ladder of distributions between $p_0(x)$ and $q(x)$ (Gao et al., 2020b). Auto-regressive models depend on a certain sequence of components for generation, and are not compatible with joint updates of all pixels. On the other hand, MCMC sampling with an EBM is a natural and relatively efficient process. Uniquely among all methods, the desired stability and length of MCMC sampling trajectories for an EBM can easily be controlled by adjusting the sampling phase of Maximum Likelihood (ML) learning. This can yield model capabilities not obtainable by other kinds of unsupervised models.

C   COOPERATIVE LEARNING FOR GENERATOR NETWORK

In this section we briefly review the Maximum Likelihood framework for cooperatively learning the generator in tandem with the EBM (Xie et al., 2018). The generator model assumes a joint distribution (X, Z) of images X and latent signals Z given by

$$Z \sim \mathrm{N}(0, I) \quad \text{and} \quad X|Z \sim \mathrm{N}(g(Z; \phi), \tau^2 I)$$

for a generator network g with weights ϕ and a Gaussian parameter τ controls the spread of X around $g(Z; \phi)$. Given i.i.d. pairs $\{X_i, Z_i\}_{i=1}^n$, the observations have a joint negative log probability

$$-\log p(\{X_i, Z_i\}_{i=1}^n; \phi) = \sum_{i=1}^n \left[\|X_i - g(Z_i; \phi)\|_2^2 / (2\tau^2) + \frac{1}{2}\|Z_i\|_2^2 \right] + C.$$

In practice, the X_i are shortrun MCMC samples from an EBM and the Z_i are unobserved. The full formulation of cooperative learning involves latent MCMC using the conditional distribution $p(Z|X_i; \phi)$ to infer each Z_i. In practice, since the X_i are shortrun samples that are paired with Z_i through the process of rejuvenation, one can roughly approximate the latent MCMC process with an identity function and obtain a gradient (1). We find that this works as well or better than including a latent sampling step on Z, and it is consistent with the original implementation from Xie et al. (2018).

Figure 5 illustrates the importance of including a persistent image bank in the cooperative learning framework. Shortrun samples from the generator in standard cooperative learning have low diversity and it is difficulty for the generator to break the symmetry of its activations early in training. This can lead to catastrophic instability without auxiliary techniques like batch norm to help break the symmetry. Incorporating persistent states from prior EBM updates when updating the generator helps the shortrun distribution achieve a health diversity that enables stable and effective learning.

D   COOPERATIVE-PERSISTENT ALGORITHM FOR SHORTRUN LEARNING

Algorithm 1 Cooperative-Persistent Hybrid Learning

Require: Natural images $\{x_m^+\}_{m=1}^M$, EBM $U(x; \theta)$, generator $g(z; \phi)$ Langevin noise η, number of shortrun steps K, EBM optimizer h_U, generator optimizer h_g, initial weights θ_0 and ϕ_0, rejuvenation probability p, number of training iterations T.
Ensure: Learned weights θ_T and ϕ_T.
    Initialize bank of random latent states $\{Z_i\}_{i=1}^N$.
    Initialize image bank $\{X_i^-\}_{i=1}^N$ from generator using $X_i^- = g(Z_i; \phi_0)$
    for $1 \leq t \leq T$ **do**
        Select batch $\{\tilde{X}_b^+\}_{b=1}^B$ from data samples $\{x_m^+\}_{m=1}^M$.
        Get paired batches $\{\tilde{Z}_b\}_{b=1}^B$ and $\{\tilde{X}_{b,0}^-\}_{b=1}^B$ from $\{Z_i\}_{i=1}^N$ and $\{X_i^-\}_{i=1}^N$.
        Update $\{\tilde{X}_{b,0}^-\}_{b=1}^B$ with K Langevin steps (5) to obtain negative samples $\{\tilde{X}_b^-\}_{b=1}^B$.
        Get learning gradient $\Delta_U^{(t)}$ using (4) with samples $\{\tilde{X}_b^+\}_{b=1}^B$ and $\{\tilde{X}_b^-\}_{b=1}^B$.
        Update θ_t using gradient $\Delta_U^{(t)}$ and optimizer h_U.
        Get learning gradient $\Delta_g^{(t)}$ using (1) with samples $\{\tilde{Z}_b\}_{b=1}^B$ and $\{\tilde{X}_b^-\}_{b=1}^B$.
        Update ϕ_t using gradient $\Delta_g^{(t)}$ and optimizer h_g.
        Rejuvenate each $\tilde{Z}_b$ from latent distribution with probability p.
        If $\tilde{Z}_b$ is rejuvenated, rejuvenate $\tilde{X}_b = g(\tilde{Z}_b; \phi_t)$.
        Return $\{\tilde{Z}_b\}_{b=1}^B$ to $\{Z_i\}_{i=1}^N$ and $\{\tilde{X}_b^-\}_{b=1}^B$ to $\{X_i^-\}_{i=1}^N$ by overwriting previous states.
    end for

E   BACKGROUND ON EBM DEFENSE

The most popular method for adversarial defense is adversarial training (AT) (Madry et al., 2018; Wong et al., 2020; Shafahi et al., 2019) which aims to train a classifier to correctly predict adversarial samples within a small ball around a natural input. Another popular defense method is randomized smoothing (Cohen et al., 2019), which adds Gaussian noise to images to remove adversarial signals before classification. Both of these approaches modify classifier training. Although many methods have been proposed to secure a naturally trained classifier, most have been broken by stronger attacks. A recent method that has been shown to secure a natural classifier is Langevin sampling with an EBM (Hill et al., 2021).

The EBM defense uses a classifier trained with labelled natural images and an EBM trained with unlabelled natural images. The two networks are trained independently, which is a key advantage of EBM defense over adversarial training and randomized smoothing. Since the EBM is independent of

the classifier, EBM defense has the potential to secure many classifiers across diverse tasks with a single defensive model, while existing methods are typically tailored to a single method. Starting with a naturally classifier trained on natural images $f(x)$, we define its robust counterpart as

$$F(x) = E_{T(x)}[f(T(x))] \tag{6}$$

where $T(x)$ is a random variable representing K steps of the Langevin transformation (5) initialized from a state x. We cannot evaluate $F(x)$ directly so we approximate it using

$$\hat{F}_H(x) = \frac{1}{H} \sum_{h=1}^{H} f(\hat{x}_h) \quad \text{where} \quad \hat{x}_h \sim T(x) \text{ i.i.d.,} \tag{7}$$

where $f(.)$ is a forward pass of our classifier to return logits and where the accuracy of approximation is driven by the number of replicates H. Meaningful evaluation of adversarial defenses must be based on adaptive attack methods which are aware of both $f(x)$ and $T(x)$. For our attack we use the BPDA+EOT formulation from (Athalye et al., 2018; Tramer et al., 2020) to obtain the attack gradient

$$\Delta_{\text{BPDA+EOT}}(x, y) = \frac{1}{H_{\text{adv}}} \sum_{h=1}^{H_{\text{adv}}} \nabla_{\hat{x}_h} L \left(\frac{1}{H_{\text{adv}}} \sum_{h=1}^{H_{\text{adv}}} f(\hat{x}_h), y \right), \quad \hat{x}_h \sim T(x) \text{ i.i.d.} \tag{8}$$

which we use in the standard PGD framework to generate adversarial examples. Algorithm 2 gives a sketch of the defense evaluation.

Algorithm 2 EBM Defense Algorithm

Require: Natural images $\{x_m^+\}_{m=1}^M$, EBM $U(x;\theta)$, classifier f, Langevin noise η, attack replicates H_{adv}, defense replicates H_{def}, l_∞ radius ε, attack step size, α, Langevin steps K
Ensure: Defense record $\{D_m\}_{m=1}^M$ for each image initialized as ones.
  for $1 \leq i \leq M$ **do**
    select(X_i, y_i) from batch
    Randomly initialize adversary $\hat{X}_0$ inside L_∞ ball around X_i
    for $1 \leq j \leq N$ **do**
      $c_j = \arg\max_\ell [\hat{F}_{H_{\text{adv}}}(\hat{X}_{j-1})]_\ell$
      $\Delta_j = \Delta_{\text{BPDA+EOT}}(\hat{X}_{j-1}, y_i)$
      if $c_j \neq y_i$ **then**
        $c_j' = \arg\max_\ell [\hat{F}_{H_{\text{def}}}(\hat{X}_{j-1})]_\ell$
        if $c_j' \neq y_i$ **then**
          $D_i = 0$
        end if
      end if
      $\hat{X}_j = \text{PGD}(\hat{X}_{j-1}, \Delta_j, \varepsilon, \alpha)$
    end for
  end for

F EBM Defense Experiment Details and Diagnostics

Table 5: Defense for l_∞ against high-power whitebox attacks on ImageNet and 100 on CIFAR-10.

Dataset	Nat	Adv	H_{adv}	H_{def}	samples
ImageNet	0.683	0.38	32	64	1600
CIFAR-10	0.79	0.56	48	128	500

To verify the integrity of our results we ran an attack with heavily increased resources for ImageNet and CIFAR-10 compared to our standard evaluation. While using these resources for all attacks is infeasible in practice, we want to ensure our defense maintains robustness as attacker resources

---

Algorithm 3 Training a midrun sampler for EBM defense

Require: Natural images $\{x_m^+\}_{m=1}^M$, EBM $U(x;\theta)$, frozen pre-trained generator $g(z)$, Langevin noise η, Langevin steps K, EBM optimizer h_U, initial weights θ_0, rejuvenation probability p, number of training iterations T.
Ensure: Weights θ_T for defensive EBM.
   Initialize image bank $\{X_i^-\}_{i=1}^N$ from generator using $X_i^- = g(Z)$
   for $1 \leq t \leq T$ **do**
      Select batch $\{\tilde{X}_b^+\}_{b=1}^B$ from data samples $\{x_m^+\}_{m=1}^M$.
      Get negative sample batch $\{\tilde{X}_{b,0}^-\}_{b=1}^B$ from $\{X_i^-\}_{i=1}^N$.
      Update $\{\tilde{X}_{b,0}^-\}_{b=1}^B$ with K Langevin steps (5) to obtain negative samples $\{\tilde{X}_b^-\}_{b=1}^B$.
      Get learning gradient $\Delta_U^{(t)}$ using (4) with samples $\{\tilde{X}_b^+\}_{b=1}^B$ and $\{\tilde{X}_b^-\}_{b=1}^B$.
      Update θ_t using gradient $\Delta_U^{(t)}$ and optimizer h_U.
      Rejuvenate each $\tilde{X}_b$ from a pretrained generator g with probability p.
      Return $\{\tilde{X}_b^-\}_{b=1}^B$ to $\{X_i^-\}_{i=1}^N$ by overwriting previous states.
   end for

---

increase. As shown in Table 5, our benchmark accuracy remains consistent when we increase the number of attack steps and EOT attack replicates.

We also demonstrate results over varying numbers of langevin steps K. We can see in Fig 6 that our sampling trajectory for defending imagenet at $K = 200$ is reasonable to achieve high natural image classification as well as robustness.

Figure 6: Accuracy across langevin steps each experiment used over 400 samples.

G   COMPARISON TO SCORE-BASED DENOISERS

The score-based model from (Song & Ermon, 2020) and its annealed Langevin dynamics process has recently been used for purifying adversarial signals (Lee & Oh, 2021; Yoon et al., 2021). One approach is add noise and the using the score model to denoise (Lee & Oh, 2021). The robustness of this method is upper-bounded by standard randomized smoothing (Cohen et al., 2019). Another approach is to initiate the Langevin process of the score model from a natural image as done in the EBM defense. A score model can be used in a langevin process $T(x)$ that is a direct analogue to the EBM langevin process in (5) and (8). Given a score model $S_\theta(x)$ for a low noise value σ, one can define the Langevin equation

$$X_t = X_{t-1} \frac{\eta^2}{2} S_\theta(X_{t-1}) + \eta Z_t$$

Figure 7: Score-based Langevin experiment on the CIFAR-10 dataset. Left: Accuracy of natural and adversarial images resulting from a BPDA+EOT defense using a score-based model with an annealed langevin purification method for 125 samples over varying steps. Right: Samples received from this annealed langevin diffusion process over the same sampling lengths.

where $S_\theta(x) \approx \nabla_x \log q(x)$ since σ is low. In both cases, the score-based model is trained with the loss:

$$\mathcal{L}(\theta) = \frac{1}{2L} \sum_{i=1}^{L} E_{q(x)} E_{q_{\sigma_i}(\tilde{x}|x)} \left[\left\| \sigma_i s_\theta(\tilde{x}, \sigma_i) + \frac{\tilde{x} - x}{\sigma_i} \right\|_2^2 \right]$$

where $q_{\sigma_i}(\tilde{x}|x)$ represents adding Gaussian noise of standard deviation σ_i to an image x sampled from q.

We experimented with this process as a defense mechanism by selecting the smallest trained noise value $\sigma = 0.01$ and using the Langevin process as a method to purify adversaries. We evaluated this method using our BPDA+EOT attack framework over different numbers of Langevin steps during purification. In contrast to reports from Yoon et al. (2021), we were unable to obtain any significant defense using a pretrained score model when initializing sampling directly from adversarial or natural images. In Figure 7, one can see that the score-based model drives natural images toward saturation quickly, leading to a sharp decrease in natural classification that undermines the possibility of robustness from sampling. Since the score-based model does not perform sampling during training, and one cannot adjust the stability of its sampling process as we do in this work. While it is not immediately clear how to overcome this problem, we believe that defense with a score model is possible and we hope that our observation lead to efforts to stabilize the sampling paths of score models as we do for EBMs in this work.

H   LONGRUN LEARNING ALGORITHM

Algorithm 4 Training a longrun sampler for density estimation

---

Require: Natural images $\{x_m^+\}_{m=1}^M$, EBM $U(x;\theta)$, frozen pre-trained generator $g(z)$ Langevin noise η, Langevin steps K, EBM optimizer h_U, initial weights θ_0, update threshold D, number of training iterations T.

Ensure: Weights θ_T for EBM with stable longrun samples.

    Initialize burn-in image bank $\{X_i^*\}_{i=1}^{N_1}$ and update image bank $\{X_i^+\}_{i=1}^{N_2}$ from generator using $X_i^- = g(Z)$.

    Initialize update counts $\{d_i\}_{i=1}^{N_1}$ using $d_i \sim \text{Unif}(\{0, \dots, D\})$.

    for $1 \leq t \leq T$ **do**

        Select batch $\{\tilde{X}_b^+\}_{b=1}^B$ from data samples $\{x_m^+\}_{m=1}^M$.

        Get initial sample batch $\{\tilde{X}_{b,0}^*\}_{b=1}^B$ from $\{X_i^*\}_{i=1}^{N_1}$ and $\{\tilde{X}_{b,0}^-\}_{b=1}^B$ from $\{X_i^-\}_{i=1}^{N_2}$.

        Get counts $\tilde{d}_b$ corresponding to samples $\{\tilde{X}_{b,0}^*\}_{b=1}^B$.

        Update $\{\tilde{X}_{b,0}^-\}_{b=1}^B$ with K Langevin steps (5) to obtain negative samples $\{\tilde{X}_b^-\}_{b=1}^B$.

        Update $\{\tilde{X}_{b,0}^*\}_{b=1}^B$ with K Langevin steps (5) to obtain updated burn-in samples $\{\tilde{X}_b^*\}_{b=1}^B$.

        Get learning gradient $\Delta_U^{(t)}$ using (4) with samples $\{\tilde{X}_b^+\}_{b=1}^B$ and $\{\tilde{X}_b^-\}_{b=1}^B$.

        Update θ_t using gradient $\Delta_U^{(t)}$ and optimizer h_U.

        Update the burn-in count $\tilde{d}_b \leftarrow \tilde{d}_b + 1$.

        for $1 \leq b \leq B$ **do**

            if $\tilde{d}_b \geq D$ **then**

                Randomly overwrite one $\tilde{X}_b^-$ using $\tilde{X}_b^*$.

                Rejuvenate $\tilde{X}_b$ from generator and set $\tilde{d}_b$ to 0.

            end if

        end for

        Return $\{\tilde{X}_{b,0}^*\}_{b=1}^B$ from $\{X_i^*\}_{i=1}^{N_1}$ and $\{\tilde{X}_b^-\}_{b=1}^B$ to $\{X_i^-\}_{i=1}^{N_2}$ by overwriting previous states.

    end for

I   SHORTRUN SYNTHESIS RESULTS

Figure 8: Shortrun samples from CIFAR-10 EBM at resolution 32×32.

Figure 9: Shortrun samples from Celeb-A EBM at resolution 64×64.

Figure 10: Shortrun samples from ImageNet EBM at resolution 128×128.

J   LONGRUN SYNTHESIS RESULTS

Figure 11: Longrun samples at 100K steps and extremely longrun samples at 1 million steps for EBMs trained on three datasets. Our initialization is able to preserve a high degree of realism over the first 100K steps, and a reasonable degree of realism over very long trajectories. While oversaturation is noticeable for some samples using 1M steps, especially in the CIFAR-10 results, many samples have reasonable appearance and there is high diversity. Our method makes significant progress towards aligning longrun samples with high-quality samples from training to ensure that the model is a valid density.