ENABLING BINARY NEURAL NETWORK TRAINING ON THE EDGE

ABSTRACT

The ever-growing computational demands of increasingly complex machine learning models frequently necessitate the use of powerful cloud-based infrastructure for their training. Binary neural networks are known to be promising candidates for on-device inference due to their extreme compute and memory savings over higher-precision alternatives. In this paper, we demonstrate that they are also strongly robust to gradient quantization, thereby making the training of modern models on the edge a practical reality. We introduce a low-cost binary neural network training strategy exhibiting sizable memory footprint reductions and energy savings vs Courbariaux & Bengio's standard approach. Against the latter, we see coincident memory requirement and energy consumption drops of 2–6×, while reaching similar test accuracy, across a range of small-scale models trained to classify popular datasets. We also showcase ImageNet training of ResNetE-18, achieving a 3.12× memory reduction over the aforementioned standard. Such savings will allow for unnecessary cloud offloading to be avoided, reducing latency and increasing energy efficiency while also safeguarding user privacy.

1 INTRODUCTION

Although binary neural networks (BNNs) feature weights and activations with just single-bit precision, many models are able to reach accuracies indistinguishable from those of their higher-precision counterparts (Courbariaux & Bengio, 2016; Wang et al., 2019b). Since BNNs are functionally complete, their limited precision does not impose an upper bound on achievable accuracy (Constantinides, 2019). BNNs represent the ideal class of neural networks for edge inference, particularly for custom hardware implementation, due to their use of XNOR for multiplication: a fast and cheap operation to perform. Their use of compact weights also suits systems with limited memory and increases opportunities for caching, providing further potential performance boosts. FINN, the seminal BNN implementation for field-programmable gate arrays (FPGAs), reached the highest CIFAR-10 and SVHN classification rates to date at the time of its publication (Umuroglu et al., 2017).

Despite featuring binary forward propagation, existing BNN training approaches perform backward propagation using high-precision floating-point data types—typically `float32`—making training infeasible on resource-constrained devices. The high-precision activations used between forward and backward propagation commonly constitute the largest proportion of the total memory footprint of a training run (Cai et al., 2020; Sohoni et al., 2019). Additionally, backward propagation with high-precision gradients is costly, challenging the energy limitations of edge platforms. An understanding of standard BNN training algorithms led us to ask two questions: why are high-precision weight gradients used when we are only concerned with weights' *signs*, and why are high-precision activations used when the computation of weight gradients only requires *binary* activations as input? In this paper, we present a low-memory, low-energy BNN training scheme based on this intuition featuring (i) the use of binary, power-of-two and 16-bit floating-point data types, and (ii) batch normalization modifications enabling the buffering of binary activations.

By increasing the viability of learning on the edge, this work will reduce the domain mismatch between training and inference—particularly in conjunction with federated learning (McMahan et al., 2017; Bonawitz et al., 2019)—and ensure privacy for sensitive applications (Agarwal et al., 2018). Via the aggressive energy and memory footprint reductions they facilitate, our proposals will enable

networks to be trained without the reliance on network access, latency and energy overheads or data divulgence inherent to cloud offloading. To this end, we make the following novel contributions.

- We conduct the first variable representation and lifetime analysis of the standard BNN training process, informing the application of beneficial approximations. In particular, we
  - binarize weight gradients owing to the lack of importance of their magnitudes;
  - modify the forward and backward batch normalization operations such that we remove the need to buffer high-precision activations; and
  - determine and apply appropriate additional quantization schemes—power-of-two activation gradients and reduced-precision floating-point data—taken from the literature.
- Against the approach introduced by Courbariaux & Bengio (2016), we demonstrate the preservation of test accuracy when training BNNs to classify MNIST, CIFAR-10, SVHN and ImageNet while lowering memory and energy needs by up to $5.67\times$ and $4.53\times$.
- We provide an open-source release of our training software, along with our memory and energy estimation tools, to the community[1].

2 Related Work

The authors of all published works on BNN inference acceleration to date made use of high-precision floating-point data types during training (Courbariaux et al., 2015; Courbariaux & Bengio, 2016; Lin et al., 2017; Ghasemzadeh et al., 2018; Wang et al., 2019a; 2020; Umuroglu et al., 2020). There is precedent, however, for the use of gradient quantization with non-binary neural networks.

The effects of quantizing the gradients of networks with high-precision data, either fixed or floating point, have been studied extensively. Zhou et al. (2016) and Wu et al. (2018a) trained networks with fixed-point weights and activations using fixed-point gradients, reporting no accuracy loss for AlexNet classifying ImageNet with gradients wider than six bits. Bernstein et al. (2018) and Wen et al. (2017) focused solely on aggressive weight gradient quantization, aiming to reduce communication costs for distributed learning. Weight gradients were losslessly quantized into binary or ternary formats, respectively, with forward propagation and activation gradients kept in high precision. In this work, we make the novel observations that activation gradient dynamic range is more important than precision, and that BNNs are more robust to approximation than higher-precision networks. We thus propose a data representation scheme more aggressive than all of the aforementioned works combined, delivering large memory and energy savings with near-lossless performance.

Gradient checkpointing—the recomputation of activations during backward propagation—has been proposed as a method to reduce the memory consumption of training (Chen et al., 2016; Gruslys et al., 2016). Such methods introduce additional forward passes, however, and so increase each run's duration and energy cost. Graham (2017) and Chakrabarti & Moseley (2019) saved memory during training by buffering activations in low-precision formats, achieving comparable accuracy to all-`float32` baselines. Wu et al. (2018b) and Hoffer et al. (2018) reported reduced computational costs via l_1 batch normalization. Finally, Helwegen et al. (2019) asserted that the use of both trainable weights and momenta is superfluous in BNN optimizers, proposing a weightless BNN-specific optimizer, Bop, able to reach the same level of accuracy as Adam. We took inspiration from these works in locating sources of redundancy present in standard BNN training schemes, and propose BNN-specific modifications to l_1 batch normalization allowing for activation quantization all the way down to binary, thus saving both memory and energy without inducing latency degradation.

3 Standard Training Flow

For simplicity, we assume the use of a multi-layer perceptron (MLP), although the presence of convolutional layers would not change any of the principles that follow. Let $\boldsymbol{W}_l$ and $\boldsymbol{X}_l$ denote matrices of weights and activations, respectively, in the network's l^{th} layer, with $\partial \boldsymbol{W}_l$ and $\partial \boldsymbol{X}_l$ being their gradients. For $\boldsymbol{W}_l$, rows and columns span input and output channels, respectively, while for $\boldsymbol{X}_l$ they represent feature maps and channels. Henceforth, we use decoration to indicate low-precision data representation, with $\hat{\bullet}$ and $\tilde{\bullet}$ respectively denoting binary and power-of-two encoding.

---

[1]Source supplied in `.zip` for review.

Algorithm 1 Standard BNN training step.

1: **for** $l \leftarrow \{1, \cdots, L-1\}$ **do** ▷ Forward
2:     $\hat{X}_l \leftarrow \text{sgn}(X_l)$
3:     $\hat{W}_l \leftarrow \text{sgn}(W_l)$
4:     $Y_l \leftarrow \hat{X}_l \hat{W}_l$
5:     **for** $m \leftarrow \{1, \cdots, M_l\}$ **do**
6:       $x_{l+1}^{(m)} \leftarrow \dfrac{y_l^{(m)} - \mu\left(y_l^{(m)}\right)}{\sigma\left(y_l^{(m)}\right)} + \beta_l^{(m)}$

7: **for** $l \leftarrow \{L-1, \cdots, 1\}$ **do** ▷ Backward
8:     **for** $m \leftarrow \{1, \cdots, M_l\}$ **do**
9:       $v \leftarrow \dfrac{1}{\sigma\left(y_l^{(m)}\right)} \partial x_{l+1}^{(m)}$
10:       $\partial y_l^{(m)} \leftarrow v - \mu(v) -$
             $\mu\left(v \odot x_{l+1}^{(m)}\right) x_{l+1}^{(m)}$
11:       $\partial \beta_l^{(m)} \leftarrow \sum \partial x_{l+1}^{(m)}$
12:     $\partial X_l \leftarrow \partial Y_l \hat{W}_l^{\text{T}}$
13:     $\partial W_l \leftarrow \hat{X}_l^{\text{T}} \partial Y_l$
14: **for** $l \leftarrow \{1, \cdots, L-1\}$ **do** ▷ Update
15:     $W_l \leftarrow \text{Optimize}(W_l, \partial W_l, \eta)$
16:     $\beta_l \leftarrow \text{Optimize}(\beta_l, \partial \beta_l, \eta)$
17: $\eta \leftarrow \text{LearningRateSchedule}(\eta)$

Algorithm 2 Proposed BNN training step.

1: **for** $l \leftarrow \{1, \cdots, L-1\}$ **do** ▷ Forward
2:     $\hat{X}_l \leftarrow \text{sgn}(X_l)$
3:     $\hat{W}_l \leftarrow \text{sgn}(W_l)$
4:     $Y_l \leftarrow \hat{X}_l \hat{W}_l$
5:     **for** $m \leftarrow \{1, \cdots, M_l\}$ **do**
6:       $x_{l+1}^{(m)} \leftarrow \dfrac{y_l^{(m)} - \mu\left(y_l^{(m)}\right)}{\left\| y_l^{(m)} - \mu\left(y_l^{(m)}\right) \right\|_1 / B} + \beta_l^{(m)}$

7: **for** $l \leftarrow \{L-1, \cdots, 1\}$ **do** ▷ Backward
8:     **for** $m \leftarrow \{1, \cdots, M_l\}$ **do**
9:       $v \leftarrow \dfrac{1}{\left\| y_l^{(m)} - \mu\left(y_l^{(m)}\right) \right\|_1 / B} \partial x_{l+1}^{(m)}$
10:       $\partial y_l^{(m)} \leftarrow v - \mu(v) -$
          $\mu\left(v \odot \hat{x}_{l+1}^{(m)} \left\| x_{l+1}^{(m)} \right\|_1 / B \right) \hat{x}_{l+1}^{(m)}$
11:       $\partial \beta_l^{(m)} \leftarrow \sum \partial x_{l+1}^{(m)}$
12:     $\partial \tilde{Y}_l \leftarrow \text{po2}(\partial Y_l)$
13:     $\partial X_l \leftarrow \partial \tilde{Y}_l \hat{W}_l^{\text{T}}$
14:     $\partial W_l \leftarrow \hat{X}_l^{\text{T}} \partial \tilde{Y}_l$
15:     $\partial \hat{W}_l \leftarrow \text{sgn}(\partial W_l)$
16: **for** $l \leftarrow \{1, \cdots, L-1\}$ **do** ▷ Update
17:     $W_l \leftarrow \text{Optimize}\left(W_l, \partial \hat{W}_l / \sqrt{M_{l-1}}, \eta\right)$
18:     $\beta_l \leftarrow \text{Optimize}(\beta_l, \partial \beta_l, \eta)$
19: $\eta \leftarrow \text{LearningRateSchedule}(\eta)$

Figure 1: Standard BNN training graph for fully connected layer l. "sgn," "×" and "BN" are sign, matrix multiplication and batch normalization. Forward propagation dependencies are shown in black; those for backward passes are gray.

Figure 1 shows the training graph of a fully connected binary layer. A detailed description of the standard BNN training procedure introduced by Courbariaux & Bengio (2016) for each batch of training samples, which we henceforth refer to as as a *step*, is provided in Algorithm 1. Therein, "$\odot$" signifies element-wise multiplication. For brevity, we omit some of the intricacies of the baseline implementation—lack of first-layer quantization, use of a final softmax layer and the inclusion of weight gradient cancellation (Courbariaux & Bengio, 2016)—as these standard BNN practices are not impacted by our work. We initialize weights as outlined by Glorot & Bengio (2010).

Many authors have found that BNNs require batch normalization in order to reach high accuracy (Alizadeh et al., 2018; Qin et al., 2020), thus we apply it as standard. Matrix products Y_l are channel-wise batch-normalized across each layer's M_l output channels (Algorithm 1 lines 5–6) to form the subsequent layer's inputs, X_{l+1}. β constitutes the batch normalization biases. Layer-wise moving means $\mu(y_l)$ and standard deviations $\sigma(y_l)$ are retained for use during backward propagation and inference. We forgo trainable scaling factors, commonly denoted γ; these are of irrelevance to BNNs since their activations are binarized prior to use during forward propagation (line 2).

4   VARIABLE ANALYSIS

In order to quantify the potential gains from approximation, we conducted a variable representation and lifetime analysis of Algorithm 1 following the approach taken by Sohoni et al. (2019). Table 1

Table 1: Memory-related properties of variables used during training. To obtain the exemplary quantities of total memory given, BinaryNet was trained for CIFAR-10 classification with Adam.

Variable	Per-layer lifetime[1]	Standard training			Proposed training		
		Data type	Size (MiB)	%	Data type	Size (MiB)	Saving ($\times$)
X	✘	float32	111.33	26.18	bool	**3.48**	**32.00**
$\partial X, Y^2$	✔	float32	50.00	11.76	float16	**25.00**	**2.00**
$\mu(y_l)$	✘	float32	0.01	0.00	float16	**0.01**	**2.00**
$\sigma(y_l)$	✘	float32	0.01	0.00	float16	**0.01**	**2.00**
∂Y	✔	float32	50.00	11.76	po2_5[3]	**7.81**	**6.40**
W	✘	float32	53.49	12.58	float16	**26.74**	**2.00**
∂W	✘	float32	53.49	12.58	bool	**1.67**	**32.00**
β	✘	float32	0.01	0.00	float16	**0.01**	**2.00**
$\partial\beta$	✘	float32	0.01	0.00	float16	**0.01**	**2.00**
Momenta	✘	float32	106.98	25.15	float16	**53.49**	**2.00**
Total			425.33	100.00		**118.23**	**3.60**

[1] Variables that need not be retained between forward, backward or update phases of Algorithms 1 and 2.
[2] ∂X and Y can share memory since they are equally sized and have non-overlapping lifetime.
[3] 5-bit power-of-two format comprising sign bit and 4-bit exponent.

lists the properties of all variables in Algorithm 1, with each variable's contributions to the total footprint shown for a representative example. Variables are divided into two classes: those that must remain in memory between computational phases (forward propagation, backward propagation and weight update), and those that need not. This is of pertinence since, for those in the latter category, only the largest layer's contribution counts towards the total memory occupancy. For example, ∂X_l is read during the backward propagation of layer $l-1$ only, thus ∂X_{l-1} can safely overwrite ∂X_l for efficiency. Additionally, Y and ∂X are shown together since they are equally sized and only need to reside in memory during the forward and backward pass for each layer, respectively.

5 LOW-COST BNN TRAINING

As shown in Table 1, all variables within the standard BNN training flow use float32 representation. In the subsections that follow, we detail the application of aggressive approximations specifically tailored to BNN training. Further to these, and in line with the observation by many authors that float16 can be used for ImageNet training without inducing accuracy loss (Ginsburg et al., 2017; Wang et al., 2018; Micikevicius et al., 2018), we also switch all remaining variables to this format. Our final training procedure is captured in Algorithm 2, with modifications from Algorithm 1 in red and the corresponding data representations used shown in bold in Table 1. We provide both theoretical and empirical evidence that our proposed approximations do not cause material degradation to convergence rates in Appendix A.

5.1 GRADIENT QUANTIZATION

Binarized weight gradients. Intuitively, BNNs should be particularly robust to weight gradient binarization since their weights only constitute signs. On line 15 of Algorithm 2, therefore, we quantize and store weight gradients in binary format, $\partial\hat{W}$, for use during weight update. During the latter, we attenuate the gradients by $\sqrt{N_l}$, where N_l is layer l's fan-in, to reduce the learning rate and prevent premature weight clipping as advised by Sari et al. (2019). Since fully connected layers are used as an example in Algorithm 2, $N_l = M_{l-1}$ in this instance.

Table 1 shows that, with binarization, the portion of our exemplary training run's memory consumption attributable to weight gradients dropped from 53.49 to just 1.41 MiB, leaving the scarce resources available for more quantization-sensitive variables such as W and momenta. Energy consumption will also decrease due to the associated reduction in memory traffic.

Power-of-two activation gradients. The tolerance of BNN training to weight gradient binarization further suggests that activation gradients can be aggressively approximated without causing significant accuracy loss. Unlike previous proposals, in which activation gradients were quantized into fixed- or block floating-point formats (Zhou et al., 2016; Wu et al., 2018a), we hypothesize that power-of-two representation is more suitable due to their typically high inter-channel variance.

We define power-of-two quantization into k-bit "$\texttt{po2\_k}$" format as $\mathrm{po2}_k(\bullet) = \mathrm{sgn}(\bullet) \odot 2^{\exp(\bullet)-b}$, comprising a sign bit and $k-1$-bit exponent $\exp(\bullet) = \max\!\left(-2^{k-2}, [\log_2(\bullet) + b]\right)$ with bias $b = 2^{k-2} - 1 - [\log_2(\|\bullet\|_\infty)]$. Square brackets signify rounding to the nearest integer. With b, we scale $\exp(\bullet)$ layer-wise to make efficient use of its dynamic range. This is applied to quantize matrix product gradients $\partial \boldsymbol{Y}_l$ on line 12 of Algorithm 2. We chose to use $k = 5$ as standard, generally finding this value to result in high compression while inducing little loss in accuracy. While we elected not to similarly approximate $\partial \boldsymbol{X}$ due to its use in the computation of quantization-sensitive $\boldsymbol{\beta}$, our use of of $\partial \tilde{\boldsymbol{Y}} = \mathrm{po2}(\partial \boldsymbol{Y})$ nevertheless leads to sizeable reductions in total memory footprint. Our use of $\partial \tilde{\boldsymbol{Y}}$ further allows us to reduce the energy consumption associated with lines 13–14 in Algorithm 2, for both of which we now have one binary and one power-of-two operand. Assuming that the target training platform has native support for only 32-bit fixed- and floating-point arithmetic, these matrix multiplications can be computed by (i) converting powers-of-two into $\texttt{int32s}$ via shifts, (ii) performing sign-flips and (iii) accumulating the $\texttt{int32}$ outputs. This consumes far less energy than the standard training method's high-precision floating-point-based equivalent.

5.2 Batch Normalization Approximation

Analysis of the backward pass of Algorithm 1 reveals conflicting requirements for the precision of $\boldsymbol{X}$. When computing weight gradients $\partial \boldsymbol{W}$ (line 13), only binary activations $\hat{\boldsymbol{X}}$ are needed. For the batch normalization training (lines 8–11), however, high-precision $\boldsymbol{X}$ is used. As was shown in Table 1, the storage of $\boldsymbol{X}$ between forward and backward propagation constitutes the single largest portion of the algorithm's total memory. If we are able to use $\hat{\boldsymbol{X}}$ in place of $\boldsymbol{X}$ for these operations, there will be no need to retain the high-precision activations, significantly reducing memory footprint as a result. We achieve this goal via the following two steps.

Step 1: l_1 normalization. Standard batch normalization sees channel-wise l_2 normalization performed on each layer's centralized activations. Since batch normalization is immediately followed by binarization in BNNs, however, we argue that less-costly l_1 normalization is good enough in these circumstances. Replacement of batch normalization's backward propagation operation with our l_1 norm-based version sees lines 9–10 of Algorithm 1 replaced with

$$\boldsymbol{v} \leftarrow \frac{\partial \boldsymbol{x}_{l+1}^{(m)}}{\left\|\boldsymbol{y}_l^{(m)} - \mu\!\left(\boldsymbol{y}_l^{(m)}\right)\right\|_1 / B} \qquad \partial \boldsymbol{y}_l^{(m)} \leftarrow \boldsymbol{v} - \mu(\boldsymbol{v}) - \mu\!\left(\boldsymbol{v} \odot \boldsymbol{x}_{l+1}^{(m)}\right) \hat{\boldsymbol{x}}_{l+1}^{(m)}, \tag{1}$$

where B is the batch size. Not only does our use of l_1 batch normalization eliminate all squares and square roots, it also transforms one occurrence of $\boldsymbol{x}_{l+1}^{(m)}$ into its binary form, $\hat{\boldsymbol{x}}_{l+1}^{(m)}$.

Step 2: $\boldsymbol{x}_{l+1}^{(m)}$ approximation. Since $\partial \boldsymbol{Y}$ is quantized into our power-of-two format immediately after its calculation (line 12 of Algorithm 2), we hypothesize that it should be robust to approximation. Consequently, we replace the $\boldsymbol{x}_{l+1}^{(m)}$ term remaining in (1) with the product of its signs and mean magnitude: $\hat{\boldsymbol{x}}_{l+1}^{(m)} \big\| \boldsymbol{x}_{l+1}^{(m)} \big\|_1 / B$. Our complete batch normalization training functions are shown on lines 8–11 of Algorithm 2, which only require the storage of binary $\hat{\boldsymbol{X}}$ along with layer- and channel-wise scalars. With elements of $\hat{\boldsymbol{X}}$ now binarized, we not only reduce its memory cost by $32\times$ but also save energy thanks to the corresponding memory traffic reduction.

6 Evaluation

We implemented our BNN training method using Keras and TensorFlow, and experimented with the small-scale MNIST, CIFAR-10 and SVHN datasets, as well as large-scale ImageNet, using a range of network models. Our baseline for comparison was the standard BNN training method introduced

Table 2: Test accuracy of non-binary and BNNs using standard and proposed training approaches for various models and datasets optimized with Adam. Results for our training approach applied to the former are included for reference only; we do not advocate for its use with non-binary networks.

Model	Dataset	Standard training			Reference training		Proposed training	
		NN (%)[1]	BNN (%)	Δ (pp)	NN (%)[1]	Δ (pp)[2]	**BNN (%)**	Δ **(pp)**[3]
MLP	MNIST	98.22	98.24	0.02	89.98	−8.24	**96.83**	**−1.41**
CNV	CIFAR-10	86.37	82.67	−3.70	69.88	−16.49	**82.31**	**−0.36**
CNV	SVHN	97.30	96.37	−0.93	79.44	−17.86	**94.22**	**−2.15**
BinaryNet	CIFAR-10	88.20	89.81	1.61	76.56	−11.64	**88.36**	**−1.45**
BinaryNet	SVHN	96.54	97.40	0.86	85.71	−10.83	**95.78**	**−1.62**

[1] Non-binary neural network.
[2] Baseline: non-binary network with standard training.
[3] Baseline: BNN with standard training.

Table 3: Memory footprint and per-batch energy consumption of the standard and our proposed training schemes for various models using the Adam optimizer.

Model	Memory			Energy/batch		
	Standard (MiB)	**Proposed (MiB)**	**Saving** ($\times$)	Standard (mJ)	**Proposed (mJ)**	**Saving** ($\times$)
MLP	7.40	**2.56**	**2.89**	2.40	**0.97**	**2.48**
CNV	128.33	**27.13**	**4.73**	144.24	**52.61**	**2.74**
BinaryNet	425.31	**118.21**	**3.60**	855.41	**196.26**	**4.36**

by Courbariaux & Bengio (2016). Energy consumption results were obtained using the inference energy estimator from QKeras (Coelho Jr. et al., 2020), which we extended to also estimate the energy consumption of training. This tool assumes the use of an in-order processor fabricated on a 45 nm process and a cacheless memory hierarchy, as modeled by Horowitz (2014). Note that we did not tune hyperparameters, thus it is likely that higher accuracy than we report is achievable.

For MNIST we evaluated using a five-layer MLP—henceforth simply denoted "MLP"—with 256 neurons per hidden layer, and CNV (Umuroglu et al., 2017) and BinaryNet (Courbariaux & Bengio, 2016) for both CIFAR-10 and SVHN. We used three popular BNN optimizers: Adam (Kingma & Ba, 2015), stochastic gradient descent (SGD) with momentum and Bop (Helwegen et al., 2019). While all three function reliably with our training scheme, we used Adam by default due to its outstanding stability in performance. Experimental setup minutiae can be found in Appendix B.1.

Our choice of quantization targets primarily rested on the intuition that BNNs should be more robust to approximation in backward propagation than their higher-precision counterparts. To illustrate that this is indeed the case, we compared our method's loss when applied to BNNs vs `float32` networks with identical topologies and hyperparameters. Generally, per Table 2, significantly higher accuracy degradations were observed for the non-binary networks, as expected. While our proposed BNN training method does exhibit limited accuracy degradation—a geomean drop of 1.21 percentage points (pp) for these examples—this comes in return for simultaneous geomean memory and energy savings of 3.66× and 3.09×, respectively, as shown in Table 3.

In order to explore the impacts of the various facets of our scheme, we applied them sequentially while training BinaryNet to classify CIFAR-10 with multiple optimizers. The results of these experiments are shown in Table 4. Major memory savings are attributable to the use of `float16` variables and through the use of our l_1 norm-based batch normalization. The bulk of our scheme's energy savings come from the power-of-two representation of $\partial \boldsymbol{Y}$, which eliminates floating-point operations from lines 13–14 of Algorithm 2. We also evaluated the quantization of $\partial \boldsymbol{Y}$ in five-bit layer-wise block floating-point format, denoted "`int5`" in Table 4 since the individual elements are fixed-point values. With this encoding, significantly higher accuracy loss was observed than when

Table 4: Accuracy, memory and energy impacts of moving from standard to our proposed data representations. We include block floating-point ∂X to illustrate the importance of dynamic range over precision for its representation. For these experiments, BinaryNet was trained to classify CIFAR-10.

| Optimizer | Data type | | Proposed batch norm. | Top-1 test accuracy | | Memory saving $(\times)^1$ | Energy saving $(\times)^1$ |
	∂W	∂Y		%	Δ (pp)[1]		
	float32	float32	✗	88.74	–	–	–
	float16	float16	✗	88.71	−0.03	2.00	1.09
Adam	bool	float16	✗	87.93	−0.81	2.27	1.10
	bool	int5[2]	✗	81.12	−7.62	2.50	4.32
	bool	po2_5	✗	89.47	0.73	2.50	4.01
	bool	po2_5	✔	**88.59**	**−0.15**	**3.60**	**4.36**
	float32	float32	✗	88.52	–	–	–
	float16	float16	✗	88.54	0.02	2.00	1.09
SGD with	bool	float16	✗	87.35	−1.17	2.31	1.10
momentum	bool	int5	✗	81.89	−6.63	2.59	4.40
	bool	po2_5	✗	89.08	0.56	2.59	4.06
	bool	po2_5	✔	**87.45**	**−1.07**	**4.07**	**4.45**
	float32	float32	✗	91.38	–	–	–
	float16	float16	✗	91.36	−0.02	2.00	1.09
Bop	bool	float16	✗	90.54	−0.84	2.37	1.10
	bool	int5	✗	40.55	−50.83	2.72	4.48
	bool	po2_5	✗	89.34	−2.04	2.72	4.11
	bool	po2_5	✔	**86.28**	**−5.10**	**4.92**	**4.53**

[1] Baseline: float32 ∂W and ∂X with standard batch normalization.
[2] 5-bit fixed-point elements of layer-wise block floating-point format.

∂Y was quantized into the proposed, equally sized power-of-two format, confirming that representation of this variable's range is more important than its precision.

Figure 2 shows the memory footprint savings from our proposed BNN training method for different optimizers and batch sizes, again for BinaryNet with the CIFAR-10 dataset. Across all of these, we achieved a geomean reduction of 4.86×. Also observable from Figure 2 is that, for all three optimizers, movement from the standard to our proposed BNN training allows the batch size used to increase by 10×, facilitating faster completion, without a material increase in memory consumption. With respect to energy, we see an estimated geomean 4.49× reduction, split into contributions attributable to arithmetic operations and memory traffic by 18.27× and 1.71×. Figure 2 also shows that test accuracy does not drop significantly due to our approximations. With Adam, there are small drops (geomean 0.87 pp), while with SGD and Bop we actually see modest improvements.

We trained ResNetE-18, a mixed-precision model with most convolutional layers binarized (Bethge et al., 2019), to classify ImageNet. The specifics of our setup can be found in Appendix B.2. We show the performance of this network and dataset when applying each of our proposed approximations in turn, as well as with the combination we found to work best, in Table 5. Since the Tensor Processing Units we used here natively support bfloat16 rather than float16, we switched to the former for these experiments. Where bfloat16 variables were used, these were employed across all layers; the remaining approximations were applied only to binary layers. Despite increasing the precision of our power-of-two quantized ∂Y by moving from $k = 5$ to 8, this scheme unfortunately induced significant accuracy degradation, suggesting incompatibility with large-scale datasets. Consequently, we disapplied it for our final experiment, which saw our remaining three approximations deliver memory and energy reductions of 3.12× and 1.17× in return for a 2.25 pp drop in test accuracy. While these savings are smaller than those of our small-scale experiments, we note that ResNetE-18's first convolutional layer is both its largest and is non-binary, thus its activation storage dwarfs that of the remaining layers. The effects of binarized ∂W are also insignificant since ImageNet's large images result in proportionally small weight memory occupancy. Nevertheless, this proof of concept demonstrates the feasibility of large-scale neural network training on the edge.

Figure 2: Batch size vs training memory footprint, achieved test accuracy and per-batch training energy consumption for BinaryNet with CIFAR-10. The upper plots show memory and accuracy results for the standard (memory: ▯, accuracy: ◯) and our proposed (▤, △) approaches. In the lower plots, total energy is split into compute- and memory-related components for the standard (compute: ▯, memory: ▤) and proposed (◩, ▨) training flows. Annotations show reductions.

Table 5: Test accuracy, memory footprint and per-batch energy consumption of the standard and our proposed training schemes for ResNetE-18 classifying ImageNet with Adam used for optimization.

Approximations	Top-1 test accuracy		Memory		Energy/batch	
	%	Δ (pp)[1]	GiB	Saving (×)[1]	J	Saving (×)[1]
None	58.57	–	57.84	–	185.08	–
Proposed batch norm. only	57.25	−1.32	35.59	1.63	176.87	1.05
`bool` ∂W only	57.30	−1.27	57.80	1.00	185.08	1.00
`po2_8` ∂Y only	29.56	−29.01	57.84	1.00	116.06	1.59
All-`bfloat16`	58.55	0.02	29.32	1.97	162.41	1.14
Final combination[2]	**56.32**	**−2.25**	**18.54**	**3.12**	**158.44**	**1.17**

[1] Baseline: approximation-free training.
[2] Proposed batch normalization, `bool` ∂W and `bfloat16` remaining variables.

7 CONCLUSION

In this paper, we introduced the first training scheme tailored specifically to BNNs. Moving first to 16-bit floating-point representations, we selectively and opportunistically approximated beyond this based on careful analysis of the standard training algorithm presented by Courbariaux & Bengio. With a comprehensive evaluation conducted across multiple models, datasets, optimizers and batch sizes, we showed the generality of our approach and reported significant memory and energy reductions vs the prior art, challenging the notion that the resource constraints of edge platforms present insurmountable barriers to on-device learning. In the future, we will explore the potential of our training approximations in the custom hardware setting, within which we believe there to be vast energy-saving potential through the design of tailor-made arithmetic operators.

REFERENCES

Naman Agarwal, Ananda Theertha Suresh, Felix Yu, Sanjiv Kumar, and H. Brendan McMahan. CpSGD: Communication-efficient and differentially-private distributed SGD. In *International Conference on Neural Information Processing Systems*, 2018.

Milad Alizadeh, Javier Fernández-Marqués, Nicholas D. Lane, and Yarin Gal. An empirical study of binary neural networks' optimisation. In *International Conference on Learning Representations*, 2018.

Jeremy Bernstein, Yu-Xiang Wang, Kamyar Azizzadenesheli, and Animashree Anandkumar. SignSGD: Compressed optimisation for non-convex problems. In *International Conference on Machine Learning*, 2018.

Joseph Bethge, Haojin Yang, Marvin Bornstein, and Christoph Meinel. Back to simplicity: How to train accurate BNNs from scratch? *arXiv preprint arXiv:1906.08637*, 2019.

Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konečný, Stefano Mazzocchi, H. Brendan McMahan, Timon van Overveldt, David Petrou, Daniel Ramage, and Jason Roselander. Towards federated learning at scale: System design. In *Conference on Machine Learning and Systems*, 2019.

Han Cai, Chuang Gan, Ligeng Zhu, and Song Han. Tiny Transfer Learning: Towards memory-efficient on-device learning. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

Ayan Chakrabarti and Benjamin Moseley. Backprop with approximate activations for memory-efficient network training. In *Advances in Neural Information Processing Systems*, 2019.

Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost. *arXiv preprint arXiv:1604.06174*, 2016.

Claudionor N. Coelho Jr., Aki Kuusela, Hao Zhuang, Thea Aarrestad, Vladimir Loncar, Jennifer Ngadiuba, Maurizio Pierini, and Sioni Summers. Ultra low-latency, low-area inference accelerators using heterogeneous deep quantization with QKeras and hls4ml. *arXiv preprint arXiv:2006.10159*, 2020.

George A. Constantinides. Rethinking arithmetic for deep neural networks. *Philosophical Transactions of the Royal Society A*, 378(2166), 2019.

Matthieu Courbariaux and Yoshua Bengio. BinaryNet: Training deep neural networks with weights and activations constrained to +1 or -1. *arXiv preprint arXiv:1602.02830*, 2016.

Matthieu Courbariaux, Yoshua Bengio, and Jean-Pierre David. BinaryConnect: Training deep neural networks with binary weights during propagations. In *Conference on Neural Information Processing Systems*, 2015.

Mohammad Ghasemzadeh, Mohammad Samragh, and Farinaz Koushanfar. ReBNet: Residual binarized neural network. In *IEEE International Symposium on Field-Programmable Custom Computing Machines*, 2018.

Boris Ginsburg, Sergei Nikolaev, and Paulius Micikevicius. Training of deep networks with half-precision float. In *Nvidia GPU Technology Conference*, 2017.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *International Conference on Artificial Intelligence and Statistics*, 2010.

Benjamin Graham. Low-precision batch-normalized activations. *arXiv preprint arXiv:1702.08231*, 2017.

Audrunas Gruslys, Rémi Munos, Ivo Danihelka, Marc Lanctot, and Alex Graves. Memory-efficient backpropagation through time. In *Advances in Neural Information Processing Systems*, 2016.

Koen Helwegen, James Widdicombe, Lukas Geiger, Zechun Liu, Kwang-Ting Cheng, and Roeland Nusselder. Latent weights do not exist: Rethinking binarized neural network optimization. In *Advances in Neural Information Processing Systems*, 2019.

Elad Hoffer, Ron Banner, Itay Golan, and Daniel Soudry. Norm matters: Efficient and accurate normalization schemes in deep networks. In *Advances in Neural Information Processing Systems*, 2018.

Mark Horowitz. Computing's energy problem (and what we can do about it). In *International Solid-State Circuits Conference*, 2014.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Xiaofan Lin, Cong Zhao, and Wei Pan. Towards accurate binary convolutional neural network. In *Conference on Neural Information Processing Systems*, 2017.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *International Conference on Artificial Intelligence and Statistics*, 2017.

Paulius Micikevicius, Sharan Narang, Jonah Alben, Gregory Diamos, Erich Elsen, David Garcia, Boris Ginsburg, Michael Houston, Oleksii Kuchaiev, Ganesh Venkatesh, and Hao Wu. Mixed precision training. In *International Conference on Learning Representations*, 2018.

Haotong Qin, Ruihao Gong, Xianglong Liu, Xiao Bai, Jingkuan Song, and Nicu Sebe. Binary neural networks: A survey. *Pattern Recognition*, 105, 2020.

Eyyüb Sari, Mouloud Belbahri, and Vahid P. Nia. How does batch normalization help binary training. *arXiv preprint arXiv:1909.09139*, 2019.

Nimit S. Sohoni, Christopher R. Aberger, Megan Leszczynski, Jian Zhang, and Christopher Ré. Low-memory neural network training: A technical report. *arXiv preprint arXiv:1904.10631*, 2019.

Yaman Umuroglu, Nicholas J. Fraser, Giulio Gambardella, Michaela Blott, Philip H. W. Leong, Magnus Jahre, and Kees Vissers. FINN: A framework for fast, scalable binarized neural network inference. In *ACM/SIGDA International Symposium on Field-Programmable Gate Arrays*, 2017.

Yaman Umuroglu, Yash Akhauri, Nicholas J. Fraser, and Michaela Blott. LogicNets: Co-designed neural networks and circuits for extreme-throughput applications. In *International Conference on Field-Programmable Logic and Applications*, 2020.

Erwei Wang, James J. Davis, Peter Y. K. Cheung, and George A. Constantinides. LUTNet: Rethinking inference in FPGA soft logic. In *IEEE International Symposium on Field-Programmable Custom Computing Machines*, 2019a.

Erwei Wang, James J. Davis, Ruizhe Zhao, Ho-Cheung Ng, Xinyu Niu, Wayne Luk, Peter Y. K. Cheung, and George A. Constantinides. Deep neural network approximation for custom hardware: Where we've been, where we're going. *ACM Computing Surveys*, 52(2), 2019b.

Erwei Wang, James J. Davis, Peter Y. K. Cheung, and George A. Constantinides. LUTNet: Learning FPGA configurations for highly efficient neural network inference. *IEEE Transactions on Computers*, 2020.

Naigang Wang, Jungwook Choi, Daniel Brand, Chia-Yu Chen, and Kailash Gopalakrishnan. Training deep neural networks with 8-bit floating point numbers. In *Advances in Neural Information Processing Systems*, 2018.

Wei Wen, Cong Xu, Feng Yan, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. TernGrad: Ternary gradients to reduce communication in distributed deep learning. In *Advances in Neural Information Processing Systems*, 2017.

Ashia C. Wilson, Rebecca Roelofs, Mitchell Stern, Nati Srebro, and Benjamin Recht. The marginal value of adaptive gradient methods in machine learning. In *Advances in Neural Information Processing Systems*, 2017.

Shuang Wu, Guoqi Li, Feng Chen, and Luping Shi. Training and inference with integers in deep neural networks. In *International Conference on Learning Representations*, 2018a.

Shuang Wu, Guoqi Li, Lei Deng, Liu Liu, Dong Wu, Yuan Xie, and Luping Shi. $l1$-norm batch normalization for efficient training of deep neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 30(7), 2018b.

Shuchang Zhou, Zekun Ni, Xinyu Zhou, He Wen, Yuxin Wu, and Yuheng Zou. DoReFa-Net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv preprint arXiv:1606.06160*, 2016.

A   CONVERGENCE RATE ANALYSIS

A.1   THEORETICAL SUPPORT

Figure 3: Weight gradient density $\phi\Big([\mu(\partial \boldsymbol{W}_1), \cdots, \mu(\partial \boldsymbol{W}_S)]^{\mathrm{T}}\Big)$ (——) and weight noise density $\phi\Big([\sigma(\partial \boldsymbol{W}_1), \cdots, \sigma(\partial \boldsymbol{W}_S)]^{\mathrm{T}}\Big)$ (----) of the sixth convolutional layer of BinaryNet trained with `bool` weight and `po2_5` activation gradients using Adam and the CIFAR-10 dataset.

Bernstein et al. (2018) proved that training non-binary networks with binary weight gradients may result in similar convergence rates to those of unquantized training if *weight gradient density* $\phi\Big([\mu(\partial \boldsymbol{W}_1), \cdots, \mu(\partial \boldsymbol{W}_S)]^{\mathrm{T}}\Big)$ and *weight noise density* $\phi\Big([\sigma(\partial \boldsymbol{W}_1), \cdots, \sigma(\partial \boldsymbol{W}_S)]^{\mathrm{T}}\Big)$ remain within an order of magnitude throughout a training run. Here, S is the training step size and $\phi(\bullet) = \frac{\|\bullet\|_1^2}{N\|\bullet\|_2^2}$ denotes the density function of an N-element vector.

We repeated Bernstein et al.'s evaluation with our proposed gradient quantization applied during BinaryNet training with the CIFAR-10 dataset using Adam and hyperparameters as detailed in Appendix B.1. The results of this experiment can be found in Figure 3. We chose to show the densities of BinaryNet's sixth convolutional layer since this is the largest layer in the network. Each batch of inputs was trained using quantized gradients $\partial \hat{\boldsymbol{W}}$ and $\partial \tilde{\boldsymbol{Y}}$. The trained network was then evaluated using the same training data to obtain the `float32` (unquantized) $\partial \boldsymbol{W}$ used to plot the data shown in Figure 3. We found that the weight gradient density ranged from 0.55–0.62, and weight noise density 0.92–0.97, therefore concluding that our quantization method may result in similar convergence rates to the unquantized baseline.

It should be noted that Bernstein et al.'s derivations assumed the use of smooth objective functions. Although the forward propagation of BNNs is not smooth due to binarization, their training functions still assume smoothness due to the use of straight-through estimation.

A.2   EMPIRICAL SUPPORT

Figure 4 represents a subset of the training accuracy curves of the experiments conducted for Figure 2. The training curves of the standard and our proposed training methods are broadly similar, supporting the conclusion from Appendix A: our approximations do not induce significant changes in convergence rate.

Figure 4: Achieved training accuracy over time for BinaryNet and CIFAR-10 using the standard (———) and our proposed (- - - -) methods with a range of optimizers and batch sizes.

B EXPERIMENTAL SETUP

B.1 SMALL-SCALE DATASETS

We used the development-based learning rate scheduling approach proposed by Wilson et al. (2017) with an initial learning rate η of 0.001 for all optimizers except for SGD with momentum, for which we used 0.1. We used batch size $B = 100$ for all except for Bop, for which we used $B = 50$ as recommended by Helwegen et al. (2019). MNIST and CIFAR-10 were trained for 1000 epochs; SVHN for 200.

B.2 IMAGENET

Finding development-based learning rate scheduling to not work well with ResNetE-18, we resorted to the fixed decay schedule described by Bethge et al. (2019). η began at 0.001 and decayed by a factor of 10 at epochs 70, 90 and 110. We trained for 120 epochs with $B = 4096$.