DOMAIN-INDEXING VARIATIONAL BAYES FOR DOMAIN ADAPTATION

ABSTRACT

Previous studies have shown that leveraging *domain index* can significantly boost domain adaptation performance (Wang et al., 2020; Xu et al., 2022). However, such domain indices are not always available. To address this challenge, we first provide a formal definition of domain index from the probabilistic perspective, and then propose an adversarial variational Bayesian framework that infers domain indices from multi-domain data, thereby providing additional insight on domain relations and improving domain adaptation performance. Our theoretical analysis shows that our adversarial variational Bayesian framework finds the optimal domain index at equilibrium. Empirical results on both synthetic and real data verify that our model can produce interpretable domain indices which enable us to achieve superior performance compared to state-of-the-art domain adaptation methods.

1 INTRODUCTION

In machine learning, it is standard to assume that training data and test data share an identical distribution. However, this assumption is often violated (Ganin & Lempitsky, 2015; Romera et al., 2019; Sun et al., 2017; Yuan et al., 2019; Ramponi & Plank, 2020) when training and test data come from different domains. Domain adaptation (DA) tries to solve such a cross-domain generalization problem by producing domain-invariant features. Typically, DA methods enforce independence between a data point's latent representation and its *domain identity*, which is a *one-hot* vector indicating which domain the data point comes from (Ganin et al., 2016; Tzeng et al., 2017; Zhao et al., 2017; Zhang et al., 2019).

More recent studies have found that using *domain index*, which is a *real-value* scalar (or vector) to embed domain semantics, as a replacement of domain identity, significantly boosted domain adaptation performance (Wang et al., 2020; Xu et al., 2022). For instance, Wang et al. (2020) adapted sleeping stage prediction models across patients with different ages, with "age" as the domain index, and achieved superior performance compared to traditional models that split patients into groups by age and used discrete group IDs as domain identities.

Although significant progress has been made in leveraging domain indices to improve domain adaptation (Wang et al., 2020; Xu et al., 2022), a major challenge exists: domain indices are not always available. This severely limits the applicability of such indexed DA methods. Thus a natural question is motivated: Can one infer the domain index as a latent variable from data?

This prompts us to first develop an expressive and formal definition of "domain index". We argue that an effective "domain index" (1) is independent of the data's encoding, (2) retains as much information on the data as possible, and (3) maximizes adaptation performance, e.g., accuracy (see Sec. 3.2 for rigorous descriptions). With this definition, we then develop an adversarial variational Bayesian model that describes intuitive conditional dependencies among the input data, labels, encodings, and the associated domain indices. Our theoretical analysis shows that maximizing our model's evidence lower bound while adversarially training an additional discriminator (Ganin et al., 2016; Wang et al., 2020) is equivalent to inferring the optimal domain indices (according to our definition) that maximize the mutual information among the input data, labels, encodings, and the associated domain indices while minimizing the mutual information between the data's encodings and the domain indices.

We summarize our contributions as follows:

- We identify the problem of inferring domain indices as latent variables, provide a rigorous definition of "domain index", and develop the first general method, dubbed variational domain indexing (VDI), for inferring such domain indices.

- Our theoretical analysis shows that training with VDI's final objective function is equivalent to inferring the optimal domain indices according to our definition.

- Experiments on both synthetic and real-world datasets show that VDI can infer non-trivial domain indices, thereby significantly improving performance over state-of-the-art DA methods.

2 RELATED WORK

Typical Domain Adaptation. There is a rich literature on domain adaptation (Pan & Yang, 2009; Pan et al., 2010; Long et al., 2018; Saito et al., 2018; Sankaranarayanan et al., 2018; Peng et al., 2019; Prabhu et al., 2021; Wang et al., 2020; Xu et al., 2022). Typically they try to align source-domain and target-domain data in the latent space, with the hope that such domain-invariant encodings can generalize well on unseen data. There are multiple ways to achieve such alignment, including distribution matching (Pan et al., 2010; Tzeng et al., 2014; Sun & Saenko, 2016; Peng et al., 2019; Nguyen-Meidine et al., 2021), self-training (Zou et al., 2018; Kumar et al., 2020; Prabhu et al., 2021), domain-specific normalization (Maria Carlucci et al., 2017; Mancini et al., 2019; Tasar et al., 2020), and deep learning models with adversarial training (Ganin et al., 2016; Tzeng et al., 2017; Zhang et al., 2019; Zhao et al., 2017; Chen et al., 2019; Dai et al., 2019). Most of these methods rely on (one-hot) *domain identities* for feature alignment.

Domain Adaptation with Domain Identities and Domain Indices. There are also works that generate domain identities from data to improve domain adaptation. Chen & Chao (2021) generates a sequence of domain identities for intermediate domains between a source domain and a target domain, trying to facilitate better incremental domain adaptation (Bobu et al., 2018). Deecke et al. (2021) generates a set of domain identities to split a dataset into different domains and perform multi-domain learning. Both works above focus on generating (ordinal or one-hot) domain identities. In contrast, our VDI assumes such domain identities are *already given* and focuses on inferring (continuous) domain indices, which contain richer and more interpretable information. Note that in our setting, since domain identities are *given*, methods such as Deecke et al. (2021) are equivalent to typical domain adaptation methods (Ganin et al., 2016; Tzeng et al., 2017; Prabhu et al., 2021), which are considered as our baselines in Sec. 5.

Recent studies have found that replacing (one-hot) domain identities with (continuous) domain indices improves adaptation performance (Wang et al., 2020; Xu et al., 2022). However, none of these works provide a canonical definition of "domain index"; instead they mainly rely on intuition, e.g., using rotation angles as domain indices for RotatingMNIST (Wang et al., 2020) and using graph node embeddings as domain indices for adaptation across graph-relational domains (Xu et al., 2022). More importantly, they assume that such domain indices are always available, which may not be true (Matsuura & Harada, 2020; Rebuffi et al., 2017); hence they are not applicable to our setting.

3 METHOD

In this section, we formalize the definition of "domain index" and describe our VDI for inferring domain indices. We provide theoretical guarantees that VDI infers optimal domain indices in Sec. 4.

3.1 PROBLEM SETTING AND NOTATION

We consider the unsupervised domain adaptation setting with N domains in total. Each domain has domain identity $k \in \mathcal{K} = [N] \triangleq \{1, \dots, N\}$; k is in either the source domain identity set $\mathcal{K}_s$ or the target domain identity set $\mathcal{K}_t$. Each domain k has D_k data points. Given n labeled data points $\{(\mathbf{x}_i^s, y_i^s, k_i^s)\}_{i=1}^n$ from source domains ($k_i^s \in \mathcal{K}_s$), and m unlabeled data points $\{\mathbf{x}_i^t, k_i^t\}_{i=1}^m$ from target domains ($k_i^t \in \mathcal{K}_t$), we want to (1) predict the label $\{y_i^t\}_{i=1}^m$ for target domain data, and (2) infer global domain indices $\boldsymbol{\beta}_k \in \mathbb{R}^{B_\beta}$ for *each domain* and local domain indices $\mathbf{u}_i \in \mathbb{R}^{B_u}$ for *each data point*. $\boldsymbol{\alpha} = \{\boldsymbol{\mu}_\alpha, \boldsymbol{\sigma}_\alpha\}$ are the hyper-parameters for $\{\boldsymbol{\beta}_k\}_{k=1}^N$'s prior distributions. Note

Figure 1: **Left:** Probabilistic graphical model for VDI's generative model. We introduce a new edge type, "---", to denote independence. $\boldsymbol{\beta}_k$ --- $\mathbf{z}$ enforces independence between $\mathbf{z}$ and $\boldsymbol{\beta}_k$, i.e, $p(\mathbf{z}|\boldsymbol{\beta}_k) = p(\mathbf{z})$ (see Appendix Sec. E for detailed discussion). **Right:** Probabilistic graphical model for the VDI's inference model.

that each domain has only one global domain index, but has multiple local domain indices, one for each data point in the domain (more details in Sec. 3.3). We denote as $\mathbf{z} \in \mathbb{R}^{B_z}$ the data encoding generated from an encoder that takes $\mathbf{x}$ as input. We use $I(\cdot; \cdot)$ to denote mutual information.

3.2 FORMAL DEFINITION OF DOMAIN INDEX

We formally define "domain index" as follows (please refer to notations in Sec. 3.1 if needed):

Definition 3.1 (**Domain Index**). *Given data $\mathbf{x}$ and label y, a domain-level variable $\boldsymbol{\beta}$ and a data-level variable $\mathbf{u}$ are called global and local domain indices, respectively, if there exists a data encoding $\mathbf{z}$ such that the following holds:*

(1) ***Independence between $\boldsymbol{\beta}$ and $\mathbf{z}$:*** *Global domain index $\boldsymbol{\beta}$ is independent of data encoding $\mathbf{z}$, i.e., $\boldsymbol{\beta} \perp\!\!\!\perp \mathbf{z}$, or equivalently $I(\boldsymbol{\beta}; \mathbf{z}) = 0$. This is to encourage domain-invariant data encoding $\mathbf{z}$.*

(2) ***Information Preservation of $\mathbf{x}$:*** *Data encoding $\mathbf{z}$, local domain index $\mathbf{u}$, and global domain index $\boldsymbol{\beta}$ preserves as much information on $\mathbf{x}$ as possible, i.e., maximizing $I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})$. This is to prevent $\boldsymbol{\beta}$ and $\mathbf{u}$ from collapsing to trivial solutions.*

(3) ***Label Sensitivity of $\mathbf{z}$:*** *The data encoding $\mathbf{z}$ should contain as much information on the label y as possible to maximize prediction power, i.e., maximizing $I(y; \mathbf{z})$ conditioned on $\mathbf{z} \perp\!\!\!\perp \boldsymbol{\beta}$. This is to make sure the previous two constraints on $\boldsymbol{\beta}$, $\mathbf{u}$, and $\mathbf{z}$ do not harm prediction performance.*

To summarize, $\boldsymbol{\beta}$ and $\mathbf{u}$ are considered the global and local domain indices, respectively, if $(\boldsymbol{\beta}, \mathbf{u}) = \mathrm{argmax}_{\boldsymbol{\beta}, \mathbf{u}} I(\mathbf{x}; \boldsymbol{\beta}, \mathbf{u}, \mathbf{z}) + I(y; \mathbf{z})$ s.t. $I(\boldsymbol{\beta}, \mathbf{z}) = 0$.

Later in Sec. 4, our theoretical analysis shows that maximizing our model's evidence lower bound while adversarially training an additional discriminator (Sec. 3.4) is equivalent to inferring the optimal domain indices according Definition 3.1. In Appendix A, we provides a rigorous discussion on the definition of "domain index".

3.3 DOMAIN-INDEXING VARIATIONAL BAYES FOR DOMAIN ADAPTATION

Generative Process and Probabilistic Graphical Model. Based on our definition, we propose our model: Variational Domain Indexing (VDI). The basic idea is to infer the domain indices as latent variables during domain adaptation. VDI is a generative model assuming the following generative process (see the corresponding graphical model in Fig. 1(left)). For each domain k,

(1) Draw global domain index $\boldsymbol{\beta}_k$ from the Gaussian distribution $p_\theta(\boldsymbol{\beta}|\boldsymbol{\alpha})$.
(2) For each data point i with domain identity k:
    (a) Draw local domain index $\mathbf{u}_i$ from the Gaussian distribution $p_\theta(\mathbf{u}_i|\boldsymbol{\beta}_k)$.
    (b) Draw input $\mathbf{x}_i$ from the Gaussian distribution $p_\theta(\mathbf{x}_i|\mathbf{u}_i)$.
    (c) Draw data encoding $\mathbf{z}_i$ from the Gaussian distribution $p_\theta(\mathbf{z}_i|\mathbf{u}_i, \boldsymbol{\beta}_k, \mathbf{x}_i)$.
    (d) Draw label y_i from the distribution $p_\theta(y_i|\mathbf{z}_i)$.

Besides typical conditional dependencies defined in the graphical model (Fig. 1(left)), we enforce additional independence between $\boldsymbol{\beta}$ and $\mathbf{z}$; such independence is represented as a dashed line "---" in Fig. 1(left). Note that there are multiple ways to satisfy such constraints during learning, e.g., using adversarial methods (Ganin et al., 2016; Tzeng et al., 2017; Zhang et al., 2019; Wang et al., 2020; Xu et al., 2022) and using the concentration loss (Xiao et al., 2021).

Figure 2: Network structure. For clarity, we omit subscripts of q_ϕ and p_θ as well as $p_\theta(\mathbf{z}|\mathbf{x}, \mathbf{u}, \boldsymbol{\beta})$'s input $(\mathbf{x}, \mathbf{u})$.

Generative Model and Inference Model. Based on Fig. 1(left), we factorize the generative model $p_\theta(\boldsymbol{\beta}, \mathbf{u}, \mathbf{x}, \mathbf{z}, y|\boldsymbol{\alpha})$ into five conditional distributions (omitting the subscript i for clarity below):

$$p_\theta(\boldsymbol{\beta}, \mathbf{u}, \mathbf{x}, \mathbf{z}, y|\boldsymbol{\alpha}) = p_\theta(\boldsymbol{\beta}|\boldsymbol{\alpha})p_\theta(\mathbf{u}|\boldsymbol{\beta})p_\theta(\mathbf{x}|\mathbf{u})p_\theta(\mathbf{z}|\boldsymbol{\beta}, \mathbf{u}, \mathbf{x})p_\theta(y|\mathbf{z}), \tag{1}$$

where $\boldsymbol{\theta}$ denotes the collection of parameters for the generative model, and $p_\theta(\boldsymbol{\beta}|\boldsymbol{\alpha}) = \mathcal{N}(\boldsymbol{\mu}_\alpha, \boldsymbol{\sigma}_\alpha^2)$ is a Gaussian distribution. The predictor $p_\theta(y|\mathbf{z})$ is a categorical distribution $Cat(f_y(\mathbf{z};\boldsymbol{\theta}))$ for classification tasks and a Gaussian distribution $\mathcal{N}(\mu_y(\mathbf{z};\boldsymbol{\theta}), \sigma_y^2(\mathbf{z};\boldsymbol{\theta}))$ for regression tasks; here $f_y(\mathbf{z};\boldsymbol{\theta})$, $\mu_y(\mathbf{z};\boldsymbol{\theta})$, and $\sigma_y(\mathbf{z};\boldsymbol{\theta})$ are neural networks taking $\mathbf{z}$ as input. Similarly, we have

$$p_\theta(\mathbf{u}|\boldsymbol{\beta}) = \mathcal{N}(\mu_u(\boldsymbol{\beta};\boldsymbol{\theta}), \sigma_u^2(\boldsymbol{\beta};\boldsymbol{\theta})),$$
$$p_\theta(\mathbf{x}|\mathbf{u}) = \mathcal{N}(\mu_x(\mathbf{u};\boldsymbol{\theta}), \sigma_x^2(\mathbf{u};\boldsymbol{\theta})),$$
$$p_\theta(\mathbf{z}|\mathbf{x}, \mathbf{u}, \boldsymbol{\beta}) = \mathcal{N}(\mu_z(\mathbf{x}, \mathbf{u}, \boldsymbol{\beta};\boldsymbol{\theta}), \sigma_z^2(\mathbf{x}, \mathbf{u}, \boldsymbol{\beta};\boldsymbol{\theta})).$$

We use an inference model $q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})$ to approximate the posterior distributions of the latent variables, i.e., $p_\theta(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})$. As shown in Fig. 1(right), we factorize $q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})$ as

$$q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x}) = q_\phi(\mathbf{u}|\mathbf{x})q_\phi(\boldsymbol{\beta}|\mathbf{u})q_\phi(\mathbf{z}|\mathbf{x}, \mathbf{u}, \boldsymbol{\beta}), \tag{2}$$

where ϕ denotes the collection of parameters for the inference model. Specifically, we have

$$q_\phi(\mathbf{u}|\mathbf{x}) = \mathcal{N}(\mu_u(\mathbf{x};\boldsymbol{\phi}), \sigma_u^2(\mathbf{x};\boldsymbol{\phi})),$$
$$q_\phi(\boldsymbol{\beta}|\mathbf{u}) = \mathcal{N}(\mu_\beta(\mathbf{u};\boldsymbol{\phi}), \sigma_\beta^2(\mathbf{u};\boldsymbol{\phi})),$$
$$q_\phi(\mathbf{z}|\boldsymbol{\beta}, \mathbf{u}, \mathbf{x}) = \mathcal{N}(\mu_z(\boldsymbol{\beta}, \mathbf{u}, \mathbf{x};\boldsymbol{\phi}), \sigma_z^2(\boldsymbol{\beta}, \mathbf{u}, \mathbf{x};\boldsymbol{\phi})).$$

Note that $\mu.(\cdot;\cdot)$ and $\sigma.(\cdot;\cdot)$ denote neural networks; $\boldsymbol{\theta}$, $\boldsymbol{\phi}$ are neural network parameters.

3.4 OBJECTIVE FUNCTION

Evidence Lower Bound. With Eqn. 1 and Eqn. 2, we can form the evidence lower bound (ELBO) as an objective to learn the generative and inference models. Maximizing the ELBO learns to optimal variational distribution $q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})$ that best approximates the posterior distribution of the latent variables (including the domain indices) $p_\theta(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})$. Specifically we have the ELBO as:

$$\mathcal{L}_{ELBO}(\mathbf{x}, y) = \mathbb{E}_{q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}[p_\theta(\boldsymbol{\beta}, \mathbf{u}, \mathbf{x}, \mathbf{z}, y|\boldsymbol{\alpha})] - \mathbb{E}_{q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}[q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})]. \tag{3}$$

Using the factorization in Eqn. 1 and Eqn. 2, we have (omitting $\boldsymbol{\alpha}$ to avoid clutter):

$$\mathcal{L}_{ELBO}(\mathbf{x}, y) = \mathbb{E}_{q_\phi(\mathbf{u}|\mathbf{x})}[\log p_\theta(\mathbf{x}|\mathbf{u})] \tag{4}$$

$$+ \mathbb{E}_{q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}[\log p_\theta(y|\mathbf{z})] \tag{5}$$

$$+ \mathbb{E}_{q_\phi(\mathbf{u}|\mathbf{x})}\mathbb{E}_{q_\phi(\boldsymbol{\beta}|\mathbf{u})}[\log p_\theta(\mathbf{u}|\boldsymbol{\beta})] \tag{6}$$

$$- \mathbb{E}_{q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}\big[KL[q_\phi(\boldsymbol{\beta}|\mathbf{u})||p_\theta(\boldsymbol{\beta})]\big] - KL[q_\phi(\mathbf{z}|\mathbf{x}, \mathbf{u}, \boldsymbol{\beta})||p_\theta(\mathbf{z}|\mathbf{x}, \mathbf{u}, \boldsymbol{\beta})] - \mathbb{E}_{q_\phi(\mathbf{u}|\mathbf{x})}[\log q_\phi(\mathbf{u}|\mathbf{x})], \tag{7}$$

where $q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x}) = q_\phi(\mathbf{u}|\mathbf{x})q_\phi(\boldsymbol{\beta}|\mathbf{u})q_\phi(\mathbf{z}|\mathbf{u}, \boldsymbol{\beta}, \mathbf{x})$. We describe each term's intuition below (see the corresponding network structure in Fig. 2).

(1) **Reconstruction Term for Data $\mathbf{x}$ (Eqn. 4).** $q_\phi(\mathbf{u}|\mathbf{x})$ and $p_\theta(\mathbf{x}|\mathbf{u})$ aim to reconstruct data $\mathbf{x}$ using the inferred $\mathbf{u}$, encouraging $\mathbf{u}$ to preserve as much information on $\mathbf{x}$ as possible.

(2) **Prediction Terms (Eqn. 5).** These two terms in Eqn. 5 sample $\mathbf{u}$, $\boldsymbol{\beta}$, and $\mathbf{z}$ from $q_\phi(\mathbf{u}|\mathbf{x})$, $q_\phi(\boldsymbol{\beta}|\mathbf{u})$ and $q_\phi(\mathbf{z}|\mathbf{x}, \mathbf{u}, \boldsymbol{\beta})$, respectively, and then use $\mathbf{z}$ to predict y in $p_\theta(y|\mathbf{z})$, encouraging $\mathbf{z}$ to contain as much information on y as possible to maximize prediction performance.

(3) **Reconstruction Term for Local Domain Index $\mathbf{u}$ (Eqn. 6).** Eqn. 6 samples $\mathbf{u}$ and $\boldsymbol{\beta}$ from $q_\phi(\mathbf{u}|\mathbf{x})$ and $q_\phi(\boldsymbol{\beta}|\mathbf{u})$, respectively, and then use the inferred $\boldsymbol{\beta}$ to reconstruct local domain index $\mathbf{u}$ in $p_\theta(\mathbf{u}|\boldsymbol{\beta})$, encouraging $\boldsymbol{\beta}$ to preserve as much information on $\mathbf{u}$ and $\mathbf{x}$ as possible.

(4) **Regularization Terms for All Latent Variables $\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}$ (Eqn. 7).** Eqn. 7 include two KL divergence terms between the inference model $q_\phi(\cdot)$ and the generative model $p_\theta(\cdot)$ as well as an entropy term for $q_\phi(\mathbf{u}|\mathbf{x})$; they all serve as regularizers to prevent these approximate posteriors of latent variables $\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}$ from overfitting.

Global Domain Index $\boldsymbol{\beta}$ and Local Domain Index $\mathbf{u}$. VDI uses a bi-level structure for domain indices: local domain index $\mathbf{u} \in \mathbb{R}^{B_u}$ and global domain index $\boldsymbol{\beta} \in \mathbb{R}^{B_\beta}$. Both $\mathbf{u}$ and $\boldsymbol{\beta}$ are low-dimensional compared to $\mathbf{x} \in \mathbb{R}^{B_x}$, i.e., $B_u \ll B_x$ and $B_\beta \ll B_x$. The local domain index $\mathbf{u}$ is a low-dimensional vector (e.g., $B_u = 4$) containing domain information for high-dimensional data $\mathbf{x}$ (e.g., an image with $B_x = 256 \times 256$). The global domain index $\boldsymbol{\beta}$ is an aggregation of all local domain indices $\mathbf{u}$ for data from the same domain. Note that different data points $\mathbf{x}_i$ and $\mathbf{x}_j$ in the same domain ($k_i = k_j$) have *different local domain indices*, i.e., $\mathbf{u}_i \neq \mathbf{u}_j$, but *share the same global domain index*, i.e., $\boldsymbol{\beta}_{k_i} = \boldsymbol{\beta}_{k_j}$. VDI's final goal is to infer the optimal global domain indices $\{\boldsymbol{\beta}_k\}_{k=1}^N$ given only the data $(\mathbf{x}_i, y_i)$ and domain identities k_i, thereby providing better interpretability and domain adaptation performance.

Difference between Domain Identities k and Global Domain Indices $\boldsymbol{\beta}$. Note that domain identities k are discrete values and therefore cannot describe rich relations (e.g., similarity and distance) among domains. In contrast, global domain indices $\boldsymbol{\beta}$ are continuous vectors and therefore contain much richer information that describes relations (e.g., similarity and distance) among domains (see Sec. 5 for empirical results). Our VDI assumes k is available and tries to infer $\boldsymbol{\beta}$.

Inferring Global Domain Indices $q_\phi(\boldsymbol{\beta}|\mathbf{u})$. For each domain k, global domain index $\boldsymbol{\beta}_k$ should aggregate domain information of all data in this domain. We therefore propose to leverage local domain indices of all domain k's data points, $\mathbf{U}_k = [\mathbf{u}_i]_{k_i=k} \in \mathbb{R}^{D_k \times B_u}$, to infer the global domain index $\boldsymbol{\beta}_k$. Specifically, our process consists of four steps: (1) **Grouping $\mathbf{u}_i$ in Domain k.** Group all local domain indices from the same domain k into one local index matrix (set), i.e., $\mathbf{U}_k = [\mathbf{u}_i]_{k_i=k} \in \mathbb{R}^{D_k \times B_u}$. (2) **Pairwise Domain Distance.** Calculate the Earth Mover's distance (EMD) (Rubner et al., 2000) between each pair of local index matrices (sets) $\mathbf{S}_{k,j} = \mathbf{f}_{EMD}(\mathbf{U}_k, \mathbf{U}_j) \in \mathbb{R}^{N \times N}$, where $\mathbf{S}_{k,j}$ is the EMD between domain k and j. (3) **Raw Global Domain Indices.** According to the pairwise domain distance matrix $\mathbf{S}$, use multi-dimensional scaling (MDS) (Borg & Groenen, 2005) to map each domain k into a B_β-dimensional space and obtain the raw global domain index $\boldsymbol{\beta}_k^r \in \mathbb{R}^{B_\beta}$, i.e., $[\boldsymbol{\beta}_k^r]_{k=1}^N = \mathbf{f}_{MDS}(\mathbf{S}) = [\mathbf{f}_{MDS}^k(\mathbf{S})]_{k=1}^N$. (4) **Final Global Domain Indices.** Feed the raw index $\boldsymbol{\beta}_k^r$ into the inference neural network to obtain the variational distribution $\mathcal{N}\big(\mu_r(\boldsymbol{\beta}_k^r; \boldsymbol{\phi}), \sigma_r^2(\boldsymbol{\beta}_k^r; \boldsymbol{\phi})\big)$ for the final global domain index $\boldsymbol{\beta}_k \in \mathbb{R}^{B_\beta}$, where $\boldsymbol{\phi}$ is the inference network parameters. We summarize these four steps below:

$$\text{Grouping } \mathbf{u}_i \text{ in Domain } k: \quad \mathbf{U}_k = [\mathbf{u}_i]_{k_i=k} \in \mathbb{R}^{D_k \times B_u}, \tag{8}$$

$$\text{Pairwise Domain Distance:} \quad \mathbf{S} = [\mathbf{f}_{EMD}(\mathbf{U}_k, \mathbf{U}_j)]_{k=1, j=1}^{N,N} \in \mathbb{R}^{N \times N}, \tag{9}$$

$$\text{Raw Global Domain Indices:} \quad \boldsymbol{\beta}_k^r = \mathbf{f}_{MDS}^k(\mathbf{S}) \in \mathbb{R}^{B_\beta}, \tag{10}$$

$$\text{Final Global Domain Indices:} \quad \boldsymbol{\beta}_k \sim \mathcal{N}\big(\mu_r(\boldsymbol{\beta}_k^r), \sigma_r^2(\boldsymbol{\beta}_k^r); \boldsymbol{\phi}\big) \in \mathbb{R}^{B_\beta}. \tag{11}$$

Discriminator with an Adversarial Loss. To enforce independence between $\boldsymbol{\beta}$ and $\mathbf{z}$, i.e., Part (1) of Definition 3.1, we train an additional discriminator D with an adversarial loss while maximizing the ELBO in Eqn. 3. The discriminator is a neural network $D(\cdot)$ that takes $\mathbf{z}$ as input and predicts the global domain index $\hat{\boldsymbol{\beta}}$ and domain identity $\hat{k}$. Essentially, $D(\cdot)$ plays a minimax game with the encoder inference network $q_\phi(\mathbf{z}|\boldsymbol{\beta}, \mathbf{u}, \mathbf{x})$: $D(\cdot)$ tries to reconstruct the global domain index $\hat{\boldsymbol{\beta}}$ and domain identity $\hat{k}$, while the encoder $q_\phi(\mathbf{z}|\boldsymbol{\beta}, \mathbf{u}, \mathbf{x})$ tries to prevent $D(\cdot)$ from doing so by generating domain-invariant encoding $\mathbf{z}$. Denoting as R_D the reconstruction loss, the discriminator loss $\mathcal{L}_D$ can be written as:

$$\mathcal{L}_D = R_D(\boldsymbol{\beta}, \hat{\boldsymbol{\beta}}, k, \hat{k}) \tag{12}$$

In Sec. 4, we will prove that $\boldsymbol{\beta}$ is guaranteed to be independent of $\mathbf{z}$ if k is independent of $\mathbf{z}$. We therefore simplify Eqn. 12 into only classifying the domain identity k and use the log-likelihood as $\mathcal{L}_{D,\phi}$:

$$\mathcal{L}_{D,\phi} = \mathbb{E}_{p(k,\mathbf{x})} \mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] \tag{13}$$

Final Objective Function. Putting Eqn. 3 and Eqn. 13 together, we have our final objective function:

$$\max_{\theta,\phi} \min_D \mathcal{L}_{VDI} = \max_{\theta,\phi} \min_D \mathcal{L}_{\theta,\phi} - \lambda_d \mathcal{L}_{D,\phi}$$

$$= \max_{\theta,\phi} \min_D \mathbb{E}_{p(\mathbf{x},y)}[\mathcal{L}_{ELBO}(\mathbf{x}, y)] - \lambda_d \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})], \quad (14)$$

where λ_d is a hyper-parameter balancing two terms.

4 THEORY

In this section, we provide theoretical guarantees for VDI's objective function (Eqn. 14). We analyze the first term in Lemma 4.1 and the second term in Lemma 4.2, show that Eqn. 14 lower-bounds a combination of mutual information terms (including $I(y; \mathbf{z})$, $I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})$, and $I(\mathbf{z}; \boldsymbol{\beta})$) plus some constants in Theorem 4.1, and then show that one can learn domain indices $\boldsymbol{\beta}$ that satisfies Definition 3.1 when Eqn. 14's global optimum is achieved (Theorem 4.2). **All proofs are in Appendix B.**

We start by analyzing VDI's ELBO term $\mathcal{L}_{ELBO}(\mathbf{x}, y)$ in Eqn. 14 and proving that it is upper bounded by $I(y; \mathbf{z}) + I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})$ plus some constants in Lemma 4.1 below.

Lemma 4.1 (Upper Bound of the ELBO of $p_\theta(\mathbf{x}, y)$). *The ELBO of $p_\theta(\mathbf{x}, y)$ is upper bounded by the mutual information among observable variables $\mathbf{x}, y$ and latent variables $\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}$ as below:*

$$\mathbb{E}_{p(\mathbf{x},y)}[\mathcal{L}_{ELBO}(p_\theta(\mathbf{x}, y))] \leq I(y; \mathbf{z}) + I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) - [H(y) + H(\mathbf{x})]. \quad (15)$$

Since the entropy terms $H(y)$ and $H(\mathbf{x})$ in Eqn. 15 are both constant, maximizing the ELBO term $\mathcal{L}_{ELBO}(\mathbf{x}, y)$ in Eqn. 14 is equivalent to maximizing $I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})$ and $I(y; \mathbf{z})$, corresponding to Parts (2) and (3) of Definition 3.1, respectively.

Next we analyze VDI's adversarial term $\mathcal{L}_{D,\phi}$ of Eqn. 14 in Lemma 4.2 below.

Lemma 4.2 (Information Decomposition of the Adversarial Loss). *The global maximum of adversarial loss w.r.t. discriminator D is decomposed as below:*

$$\max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] = I(\mathbf{z}; \boldsymbol{\beta}) + I(\mathbf{z}; k|\boldsymbol{\beta}) - H(k), \quad (16)$$

and the global minimum of $\max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})]$ is achieved if and only if $I(\mathbf{z}; \boldsymbol{\beta}) = I(\mathbf{z}; k|\boldsymbol{\beta}) = 0$.

Lemma 4.2 above shows that one can decompose $\max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})]$ into several information theoretic terms, including $I(\mathbf{z}; \boldsymbol{\beta})$, which is related to Part (1) of Definition 3.1.

With Lemma 4.1 and Lemma 4.2, we then show that VDI's objective function in Eqn. 14 lower-bounds a combination of mutual information terms plus some constant entropy terms in Theorem 4.1 below.

Theorem 4.1 (Objective Function as a Lower Bound). *The objective function involves both the ELBO of $p_\theta(\mathbf{x}, y)$ and adversarial loss $\mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})]$, and it is the lower bound for a combination mutual information and entropy terms:*

$$\mathbb{E}_{p(\mathbf{x},y)}[\mathcal{L}_{ELBO}(\mathbf{x}, y)] - \max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] \quad (17)$$

$$\leq I(y; \mathbf{z}) + I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) - I(\mathbf{z}; \boldsymbol{\beta}) - I(\mathbf{z}; k|\boldsymbol{\beta}) - [H(y) + H(\mathbf{x}) - H(k)]. \quad (18)$$

With Theorem 4.1, we are now ready to analyze the global optimum of the minimax game in Eqn. 14.

Theorem 4.2 (Global Optimum of VDI). *In VDI, when the global optimum (Eqn. 14) is achieved, it is guaranteed that (1) $I(\mathbf{z}; \boldsymbol{\beta}) = 0$, (2) $I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})$ is maximized, and (3) $I(y; \mathbf{z})$ is maximized.*

As Theorem 4.2 states, the global optimum of Eqn. 14 is guaranteed to satisfy all three conditions in Definition 3.1; therefore training VDI using the minimax game objective Eqn. 14 is equivalent to inferring the optimal domain indices.

5 EXPERIMENTS

In this section, we compare VDI with existing DA methods on both synthetic and real-world datasets.

Figure 3: **(a)** The *Circle* dataset (Wang et al., 2020) with 30 domains, with different colors indicating ground-truth domain indices. The first 6 domains (in the green box) are source domains. **(b)** Ground-truth labels for *Circle*, with red dots and blue crosses as positive and negative data points, respectively. **(c)** *Ground-truth* domain graph for *DG-15*. We use 'red' and 'blue' to roughly indicate positive and negative data points in a domain. **(d)** VDI's *inferred* domain graph for *DG-15*, with an AUC of 0.83.

Figure 4: Domain graphs for two adaptation tasks on *TPT-48*; black nodes indicate source domains, and white nodes indicate target domains. **Left:** Adaptation from the 6 states in the west to the 42 states in the east. **Right:** Adaptation from the 24 states in the north to the 24 states in the south.

5.1 DATASETS

Circle (Wang et al., 2020) is a synthetic dataset with 30 domains for binary classification. Fig. 3(a) shows 30 domains of *Circle* in different colors. Fig. 3(b) shows positive (red) and negative (blue) data points, The first 6 domains are source domains, and the remaining 24 domains are target domains.

DG-15 **and** ***DG-16*** (Xu et al., 2022). *DG-15* is a synthetic dataset with 15 domains for binary classification. As shown in Fig. 3(c), these domains form a domain graph (DG) of 15 nodes, with adjacent domains having similar decision boundaries. Each domain contains 100 data points. We use 6 connected domains as the source domains and use others as target domains. Similarly, *DG-60* is another synthetic dataset with 60 domains, each of which contains 100 data points. We use 6 connected domains as source domains and the remaining 54 domains as target domains.

TPT-48 (Xu et al., 2022) is a real-world regression dataset that contains monthly average temperature for the 48 contiguous states in the US from 1996 to 2019. We use the first 6 months' temperature as model input to predict the next 6 months' temperature. We formulate two DA tasks (Fig. 4):

- W (6) $\rightarrow$ E (42): Adapting models from the 6 states in the west to the 42 states in the east.

- N (24) $\rightarrow$ S (24): Adapting models from the 24 states in the north to the 24 states in the south.

We treat target domains one hop away from the closest source domain as *Level-1 Target Domains*, those two hops away as *Level-2 Target Domains*, and those more than two hops away as *Level-3 Target Domains* (see Fig. 4 for an illustration).

CompCars (Yang et al., 2015) is a car image dataset with attributes including car types, viewpoints, and years of manufacture (YOMs). The task is to recognize the car type given an image. In *CompCars*, data with each view point and each YOM is treated as a single domain. We choose a subset of CompCars with 4 car types (MPV, SUV, sedan and hatchback), 5 viewpoints (front (F), rear (R), side (S), front-side (FS), and rear-side (RS)), ranging from 2009 to 2014. It contains 30 domains (5 viewpoints × 6 YOMs) with 18735 images in total. In order to eliminate the influence of imbalanced labels, we ensure that each domain shares similar label distributions.

Table 1: Accuracy (%) on *Circle*, *DG-15* and *DG-60*.

Method	Source-Only	DANN	ADDA	CDANN	MDD	SENTRY	VDI (Ours)
Circle	55.5	53.4	56.2	54.9	53.4	59.5	**94.3**
DG-15	39.7	43.4	33.5	38.8	37.2	42.6	**94.7**
DG-60	55.0	66.3	60.8	65.3	54.6	51.3	**95.9**

Table 2: MSE for various DA methods for both tasks W (6) → E (42) and N (24) → S (24) on *TPT-48*. We report the average MSE of all domains as well as more detailed average MSE of Level-1, Level-2, Level-3 target domains, respectively (see Fig. 4). Note that there is only one single DA model per column. We mark the best result with **bold face**.

Task	Domain	Source-Only	DANN	ADDA	CDANN	MDD	SENTRY	VDI (Ours)
W (6)→E (42)	Average of 4 Level-1 Domains	**0.148**	0.248	0.681	0.771	0.693	0.314	0.270
	Average of 6 Level-2 Domains	0.391	0.639	0.953	0.877	0.989	0.642	**0.375**
	Average of 32 Level-3 Domains	0.659	0.735	0.907	0.871	1.001	0.734	**0.306**
	Average of All 42 Domains	0.572	0.675	0.892	0.862	0.970	0.682	**0.312**
N (24)→S (24)	Average of 10 Level-1 Domains	0.206	0.229	0.734	0.229	0.342	0.497	**0.192**
	Average of 6 Level-2 Domains	0.391	0.412	0.861	0.357	0.768	0.470	**0.323**
	Average of 8 Level-3 Domains	1.160	0.843	0.886	0.961	1.326	0.459	**0.703**
	Average of All 24 Domains	0.570	0.480	0.816	0.505	0.777	0.477	**0.395**

5.2 BASELINES

We compared our proposed VDI with state-of-the-art DA methods, including Domain Adversarial Neural Networks (**DANN**) (Ganin et al., 2016), Adversarial Discriminative Domain Adaptation (**ADDA**) (Tzeng et al., 2017), Conditional Domain Adaptation Neural Networks (**CDANN**) (Zhao et al., 2017), Margin Disparity Discrepancy (**MDD**) (Zhang et al., 2019), and a recent entropy-based method **SENTRY**. We also report results when the model is only trained in the source domains without adapting to the target domains (**Source-Only**). Different from VDI that works for both classification and regression tasks, recent methods such as MDD and SENTRY were proposed to handle only classification tasks. We therefore make several modifications to adapt them for the regression tasks on *TPT-48* (See Appendix D for details). Note that both Wang et al. (2020) and Xu et al. (2022) assume domain indices are available; therefore they are not applicable to our settings where the goal is to infer domain indices (which are *unavailable* from data).

5.3 RESULTS

Circle, DG-15 and DG-60. Table 1 shows the classification accuracy of evaluated methods on *Circle*, *DG-15*, and *DG-60*; all these datasets have complex domain relations, therefore making it challenging to perform domain adaptation without knowing ground-truth domain indices. Indeed, we observe that on *Circle* and *DG-60*, all baselines only perform marginally better than random guess (50% accuracy). Moreover, on *DG-15* these baselines perform even worse than a random guess, possibly due to overfitting the source domains[1]. In contrast, our VDI achieves very high accuracy (over 94%) on all three datasets, significantly outperforming all baselines.

To verify that VDI infers non-trivial domain indices β, we connect the domain pairs within a distance threshold ($\|\beta_k - \beta_j\| < \epsilon$) to reconstruct the domain graph on *DG-15* and *DG-60*. Compared with the ground-truth domain graphs, VDI achieves area under the ROC curve (AUC) of 0.83 for *DG-15* and 0.91 for *DG-60*. Fig. 3(d) shows an example inferred domain graph for *DG-15*.

TPT-48. Table 2 shows the mean square error (MSE) for all the methods on *TPT-48*. In terms of average MSE across all domains, we observe that most methods suffer from negative transfer on both tasks, with only DANN and SENTRY marginally improving upon Source-Only. In contrast, our VDI can further improve the performance and achieve the lowest average MSE on both tasks.

Fig. 5 plots the inferred domain indices $\beta \in \mathbb{R}^2$ for all 48 domains. For reference, we color the inferred domain indices according to ground-truth latitude (Fig. 5(left)) and longitude (Fig. 5(right)); note that *VDI does not have access to latitude and longitude during training*. The plots show that

---

[1]Note that different from (Wang et al., 2020; Xu et al., 2022), all evaluated methods only have access to domain identities k, but not ground-truth domain indices β, since the goal is to infer β in our setting.

Figure 5: Inferred domain indices for 48 domains in *TPT-48*. We color inferred domain indices according to ground-truth indices, latitude (**left**) and longitude (**right**). VDI's inferred indices are correlated with true indices, even though *VDI does not have access to true indices during training*.

Figure 6: Inferred domain indices for 30 domains in *CompCars*. We color inferred domain indices according to ground-truth indices, viewpoints (**left**) and YOMs (**right**). VDI's inferred indices are correlated with true indices, even though *VDI does not have access to true indices during training*.

Table 3: Accuracy (%) on CompCars (4-Way Classification).

Method	Source-Only	DANN	ADDA	CDANN	MDD	SENTRY	VDI (Ours)
CompCars	39.1	38.9	42.8	41.8	41.4	41.8	**43.9**

VDI's inferred domain indices are highly correlated with each domain's latitude and longitude. For example, Florida (FL) has the lowest latitude among all 48 states and is hence the left-most circle in Fig. 5(left). We also observe that states with similar latitude or longitude do have similar domain indices $\boldsymbol{\beta}$. These results demonstrate that VDI can infer reasonable domain indices.

CompCars. Table 3 shows the classification accuracy on all DA methods. Results show that all the methods outperform Source-Only, with our VDI achieving the most significant improvement. Fig. 6 plots the inferred domain indices $\boldsymbol{\beta} \in \mathbb{R}^2$ for all 30 domains. For reference, we also color the plotted circles according to YOMs (Fig. 6(left)) and viewpoints (Fig. 6(right)); note that *VDI does not have access to YOMs and viewpoints during training*. Interestingly, we have the following observations that are consistent with intuition: (1) domains with the same viewpoint or YOM have similar domain indices; (2) domains with "front-side" and "rear-side" viewpoints have similar domain indices; (3) domains with "front" and "rear" viewpoints have similar domain indices.

6 CONCLUSION

We identify the problem of inferring domain indices as latent variables, provide a rigorous definition of "domain index", develop the first general method for addressing it, and provide detailed theoretical analysis as well as empirical results. We demonstrate the effectiveness of our proposed VDI for inferring domain indices and show its potential for significant practical applications. As a limitation, our method still assumes the availability of domain identities to identify different domains. Therefore it would be interesting future work to explore jointly inferring domain indices, domain identities, as well as the number of domains from data to facilitate domain adaptation.

REFERENCES

Andreea Bobu, Eric Tzeng, Judy Hoffman, and Trevor Darrell. Adapting to continuously shifting domains. 2018.

Ingwer Borg and Patrick JF Groenen. *Modern multidimensional scaling: Theory and applications*. Springer Science & Business Media, 2005.

Hong-You Chen and Wei-Lun Chao. Gradual domain adaptation without indexed intermediate domains. *Advances in Neural Information Processing Systems*, 34, 2021.

Ziliang Chen, Jingyu Zhuang, Xiaodan Liang, and Liang Lin. Blending-target domain adaptation by adversarial meta-adaptation networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2248–2257, 2019.

Shuyang Dai, Kihyuk Sohn, Yi-Hsuan Tsai, Lawrence Carin, and Manmohan Chandraker. Adaptation across extreme variations using unlabeled domain bridges. *arXiv preprint arXiv:1906.02238*, 2019.

Lucas Deecke, Timothy Hospedales, and Hakan Bilen. Visual representation learning over latent domains. In *International Conference on Learning Representations*, 2021.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pp. 1180–1189. PMLR, 2015.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, Franccois Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *JMLR*, 17(1):2096–2030, 2016.

Ananya Kumar, Tengyu Ma, and Percy Liang. Understanding self-training for gradual domain adaptation. In *International Conference on Machine Learning*, pp. 5468–5479. PMLR, 2020.

Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I. Jordan. Conditional adversarial domain adaptation. In *NIPS*, pp. 1647–1657, 2018.

Massimiliano Mancini, Samuel Rota Bulo, Barbara Caputo, and Elisa Ricci. Adagraph: Unifying predictive and continuous domain adaptation through graphs. In *CVPR*, pp. 6568–6577, 2019.

Fabio Maria Carlucci, Lorenzo Porzi, Barbara Caputo, Elisa Ricci, and Samuel Rota Bulo. Autodial: Automatic domain alignment layers. In *Proceedings of the IEEE international conference on computer vision*, pp. 5067–5075, 2017.

Toshihiko Matsuura and Tatsuya Harada. Domain generalization using a mixture of multiple latent domains. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 11749–11756, 2020.

Le Thanh Nguyen-Meidine, Atif Belal, Madhu Kiran, Jose Dolz, Louis-Antoine Blais-Morin, and Eric Granger. Unsupervised multi-target domain adaptation through knowledge distillation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1339–1347, 2021.

Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *TKDE*, 22(10):1345–1359, 2009.

Sinno Jialin Pan, Ivor W Tsang, James T Kwok, and Qiang Yang. Domain adaptation via transfer component analysis. *TNN*, 22(2):199–210, 2010.

Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1406–1415, 2019.

Viraj Prabhu, Shivam Khare, Deeksha Kartik, and Judy Hoffman. Sentry: Selective entropy optimization via committee consistency for unsupervised domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8558–8567, 2021.

Alan Ramponi and Barbara Plank. Neural unsupervised domain adaptation in nlp—a survey. *arXiv preprint arXiv:2006.00632*, 2020.

Sylvestre-Alvise Rebuffi, Hakan Bilen, and Andrea Vedaldi. Learning multiple visual domains with residual adapters. *Advances in neural information processing systems*, 30, 2017.

Eduardo Romera, Luis M Bergasa, Kailun Yang, Jose M Alvarez, and Rafael Barea. Bridging the day and night domain gap for semantic segmentation. In *2019 IEEE Intelligent Vehicles Symposium (IV)*, pp. 1312–1318. IEEE, 2019.

Yossi Rubner, Carlo Tomasi, and Leonidas J Guibas. The earth mover's distance as a metric for image retrieval. *International journal of computer vision*, 40(2):99–121, 2000.

Kuniaki Saito, Kohei Watanabe, Yoshitaka Ushiku, and Tatsuya Harada. Maximum classifier discrepancy for unsupervised domain adaptation. In *CVPR*, pp. 3723–3732, 2018.

Swami Sankaranarayanan, Yogesh Balaji, Carlos D. Castillo, and Rama Chellappa. Generate to adapt: Aligning domains using generative adversarial networks. In *CVPR*, pp. 8503–8512, 2018.

Baochen Sun and Kate Saenko. Deep CORAL: correlation alignment for deep domain adaptation. In *ICCV workshop on Transferring and Adapting Source Knowledge in Computer Vision (TASK-CV)*, pp. 443–450, 2016.

Sining Sun, Binbin Zhang, Lei Xie, and Yanning Zhang. An unsupervised deep domain adaptation approach for robust speech recognition. *Neurocomputing*, 257:79–87, 2017.

Onur Tasar, Yuliya Tarabalka, Alain Giros, Pierre Alliez, and Sébastien Clerc. Standardgan: Multi-source domain adaptation for semantic segmentation of very high resolution satellite images by data standardization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 192–193, 2020.

Eric Tzeng, Judy Hoffman, Ning Zhang, Kate Saenko, and Trevor Darrell. Deep domain confusion: Maximizing for domain invariance. *arXiv preprint arXiv:1412.3474*, 2014.

Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *CVPR*, pp. 7167–7176, 2017.

Hao Wang, Hao He, and Dina Katabi. Continuously indexed domain adaptation. In *ICML*, 2020.

Zehao Xiao, Jiayi Shen, Xiantong Zhen, Ling Shao, and Cees GM Snoek. A bit more bayesian: Domain-invariant learning with uncertainty. *arXiv preprint arXiv:2105.04030*, 2021.

Zihao Xu, Guang-He Lee, Yuyang Wang, Hao Wang, et al. Graph-relational domain adaptation. *arXiv preprint arXiv:2202.03628*, 2022.

Linjie Yang, Ping Luo, Chen Change Loy, and Xiaoou Tang. A large-scale car dataset for fine-grained categorization and verification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3973–3981, 2015.

Feng Yuan, Lina Yao, and Boualem Benatallah. Darec: Deep domain adaptation for cross-domain recommendation via transferring rating patterns. *arXiv preprint arXiv:1905.10760*, 2019.

Yuchen Zhang, Tianle Liu, Mingsheng Long, and Michael I Jordan. Bridging theory and algorithm for domain adaptation. *arXiv preprint arXiv:1904.05801*, 2019.

Mingmin Zhao, Shichao Yue, Dina Katabi, Tommi S. Jaakkola, and Matt T. Bianchi. Learning sleep stages from radio signals: A conditional adversarial architecture. In *ICML*, pp. 4100–4109, 2017.

Yang Zou, Zhiding Yu, B.V.K. Vijaya Kumar, and Jinsong Wang. Unsupervised domain adaptation for semantic segmentation via class-balanced self-training. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

A FORMAL DEFINITION OF DOMAIN INDEX

Given predefined variables of data $\mathbf{x}$, label y and domain, let $\boldsymbol{\beta}$ be a domain associated variable, i.e., in each domain it has the same value, and let $\mathbf{u}$ be a data associated variable, i.e., for each data point it can have a different value.

Definition A.1 (Orthogonal Information). *For any domain associated variable $\boldsymbol{\beta}$ and data associated variable $\mathbf{u}$, we define their orthogonal information as the following:*

(1) Data orthogonal information $I_{\mathbf{x}}(\boldsymbol{\beta}, \mathbf{u})$: $I_{\mathbf{x}}(\boldsymbol{\beta}, \mathbf{u}) := \max_{\mathbf{z}: \mathbf{z} \perp\!\!\!\perp \boldsymbol{\beta}} I(\mathbf{x}; \boldsymbol{\beta}, \mathbf{u}, \mathbf{z})$.

(1) Label orthogonal information $I_{\mathbf{y}}(\boldsymbol{\beta})$: $I_{\mathbf{y}}(\boldsymbol{\beta}) := \max_{\mathbf{z}: \mathbf{z} \perp\!\!\!\perp \boldsymbol{\beta}} I(\mathbf{y}; \mathbf{z})$.

Lemma A.1. *Given $(\boldsymbol{\beta}, \mathbf{u})$, the data orthogonal information and label orthogonal can be achieved at the same time, i.e., $\exists \mathbf{z}$, s.t. $I_{\mathbf{x}}(\boldsymbol{\beta}, \mathbf{u}) = I(\mathbf{x}; \boldsymbol{\beta}, \mathbf{u}, \mathbf{z})$ and $I_{\mathbf{y}}(\boldsymbol{\beta}) = I(\mathbf{y}; \mathbf{z})$.*

Proof. Let us consider $\mathbf{z}_1 \in \operatorname{argmax}_{\mathbf{z}} I(\mathbf{x}; \boldsymbol{\beta}, \mathbf{u}, \mathbf{z})$ and $\mathbf{z}_2 \in \operatorname{argmax}_{\mathbf{z}} I(y; \mathbf{z})$. Now let $\mathbf{z}_3 = (\mathbf{z}_1, \mathbf{z}_2)$. Since $\mathbf{z}_1 \perp\!\!\!\perp \boldsymbol{\beta}$ and $\mathbf{z}_2 \perp\!\!\!\perp \boldsymbol{\beta}$, we have $z_3 \perp\!\!\!\perp \boldsymbol{\beta}$. Further, apparently $I(\mathbf{x}; \boldsymbol{\beta}, \mathbf{u}, \mathbf{z}_3) \geq I(\mathbf{x}; \boldsymbol{\beta}, \mathbf{u}, \mathbf{z}_1)$ and $I(y; \mathbf{z}_3) \geq I(y; \mathbf{z}_2)$. Thus both maximum is achieved at $\mathbf{z}_3$. $\square$

Definition A.2 (Domain Index). *We call $(\boldsymbol{\beta}, \mathbf{u})$ domain index if they maximize the sum of data orthogonal information and label orthogonal information, i.e., $\boldsymbol{\beta}, \mathbf{u} \in \operatorname{argmax}_{\boldsymbol{\beta}', \mathbf{u}'} I_{\mathbf{x}}(\boldsymbol{\beta}', \mathbf{u}') + I_{\mathbf{y}}(\boldsymbol{\beta}')$.*

B THEORETICAL ANALYSIS

Lemma B.1 (Upper Bound of the ELBO of $p_{\theta}(\mathbf{x}, y)$). *The ELBO of $p_{\theta}(\mathbf{x}, y)$ is upper bounded by the mutual information among observable variables $\mathbf{x}, y$ and latent variables $\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}$ as below:*

$$\mathbb{E}_{p(\mathbf{x},y)}[\mathcal{L}_{ELBO}(p_{\theta}(\mathbf{x}, y))] \leq I(y; \mathbf{z}) + I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) - [H(y) + H(\mathbf{x})] \tag{19}$$

Optimizing the ELBO of $p_{\theta}(\mathbf{x}, y)$ is equivalent to enhancing mutual information between label $\mathbf{y}$ and classification latent variable $\mathbf{z}$ and between data variable $\mathbf{x}$ and all latent variables $\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}$.

Proof. Firstly, we provide the ELBO of $\log p_{\theta}(\mathbf{x}, y)$ as below:

$$\begin{aligned}
\log p_{\theta}(\mathbf{x}, y) &= \log \int \int p_{\theta}(\mathbf{x}, y, \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) d\boldsymbol{\beta} d\mathbf{u} d\mathbf{z} \\
&= \log \int \int \frac{p_{\theta}(\mathbf{x}, y, \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}{q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})} d\boldsymbol{\beta} d\mathbf{u} d\mathbf{z} \\
&= \log \mathbb{E}_q \frac{p_{\theta}(\mathbf{x}, y, \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})}{q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})} \\
&\geq \mathbb{E}_q \log \frac{p_{\theta}(\mathbf{x}, y, \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})}{q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})} \\
&= \mathbb{E}_q[\log \frac{p_{\theta}(y|\mathbf{x}, \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) p_{\theta}(\mathbf{x}|\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) p_{\theta}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta})}{q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}] \\
&= \mathbb{E}_q[\log p_{\theta}(y|\mathbf{z})] + \mathbb{E}_q[\log p_{\theta}(\mathbf{x}|\mathbf{u}, \mathbf{z}, \boldsymbol{\beta})] - KL[q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})||p_{\theta}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta})]
\end{aligned}$$

Then we have:

$$\mathcal{L}_{ELBO}(p_{\theta}(\mathbf{x}, y)) = \mathbb{E}_q \log[p_{\theta}(y|\mathbf{z})] + \mathbb{E}_q[\log p_{\theta}(\mathbf{x}|\mathbf{u}, \mathbf{z}, \boldsymbol{\beta})] - KL[q_{\phi}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})||p_{\theta}(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta})] \tag{20}$$

To help our analysis, we introduce a helper joint distribution of variables $\mathbf{x}, y, \mathbf{z}$, which is $r(\mathbf{x}, y, \mathbf{z}) = p(\mathbf{x}, y) q_{\phi}(\mathbf{z}|\mathbf{x})$. This distribution has the following properties, $r(y|\mathbf{z}, \mathbf{x}) = p(y|\mathbf{x})$, $r(y) = p(y)$.

The First Term of the ELBO. Its upper bound is provided as follows:

$$
\begin{aligned}
\mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log p_\theta(y|\mathbf{z})] &= \mathbb{E}_{r(\mathbf{x},y,\mathbf{z})}[\log p_\theta(y|\mathbf{z})] \\
&= \mathbb{E}_{r(y,\mathbf{z})}[\log p_\theta(y|\mathbf{z})] \\
&\leq \mathbb{E}_{r(y,\mathbf{z})}[\log r(y|\mathbf{z})] \\
&= \mathbb{E}_{r(y,\mathbf{z})}[\log \frac{r(y|\mathbf{z})}{p(y)}p(y)] \\
&= \mathbb{E}_{r(y,\mathbf{z})}[\log \frac{r(y|\mathbf{z})}{p(y)}] + \mathbb{E}_{p(y)}[\log p(y)] \\
&= I_r(y;\mathbf{z}) - H(y)
\end{aligned}
$$

when $\log p_\theta(y|\mathbf{z}) = r(y|\mathbf{z})$, we have $\mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[p_\theta(y|\mathbf{z})] = I_r(y;\mathbf{z}) + H(y)$. So, $\max_{p_\theta} \mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})} \log p_\theta(y|\mathbf{z}) = I_r(y;\mathbf{z}) - H(y)$.

Then we have:

$$\mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})} \log p_\theta(y|\mathbf{z}) \leq I_r(y;\mathbf{z}) - H(y) \tag{21}$$

The Second Term of the ELBO. Its upper bound is proved as follows:

$$
\begin{aligned}
\mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_q[\log p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})] &= \mathbb{E}_{p(\mathbf{x})}\mathbb{E}_q[\log p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})] \\
&= \mathbb{E}_{p(\mathbf{x})}\mathbb{E}_q[\log p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})] \\
&= \mathbb{E}_{p(\mathbf{x})}\mathbb{E}_q[\log \frac{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}{p(\mathbf{x})}\frac{p(\mathbf{x})p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}] \\
&= \mathbb{E}_{p(\mathbf{x})}\mathbb{E}_q[\log \frac{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}{p(\mathbf{x})}] + \mathbb{E}_{p(\mathbf{x})}\mathbb{E}_q[\log p(\mathbf{x})] + \mathbb{E}_{p(\mathbf{x})}\mathbb{E}_q[\log \frac{p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}] \\
&= I(\mathbf{x};\mathbf{u},\mathbf{z},\boldsymbol{\beta}) - H(\mathbf{x}) + \mathbb{E}_{q_\phi(\mathbf{x},\mathbf{u},\mathbf{z},\boldsymbol{\beta})}[\log \frac{p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}] \\
&= I(\mathbf{x};\mathbf{u},\mathbf{z},\boldsymbol{\beta}) - H(\mathbf{x}) + \mathbb{E}_{q_\phi(\mathbf{u},\mathbf{z},\boldsymbol{\beta})}\mathbb{E}_{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}[\log \frac{p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}{q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})}] \\
&= I(\mathbf{x};\mathbf{u},\mathbf{z},\boldsymbol{\beta}) - H(\mathbf{x}) - \mathbb{E}_{q_\phi(\mathbf{u},\mathbf{z},\boldsymbol{\beta})}\big[KL[q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})||p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})]\big] \\
&\leq I(\mathbf{x};\mathbf{u},\mathbf{z},\boldsymbol{\beta}) - H(\mathbf{x}) - 0
\end{aligned}
$$

Then we have:

$$\mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_q[\log p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})] \leq I(\mathbf{x};\mathbf{u},\mathbf{z},\boldsymbol{\beta}) - H(\mathbf{x}) \tag{22}$$

Applying Eqn. 21 and Eqn. 22 to Eqn. 20, we have:

$$
\begin{aligned}
&\mathbb{E}_{p(\mathbf{x},y)}\mathcal{L}_{ELBO}(p_\theta(\mathbf{x},y)) \\
&= \mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_q[\log p_\theta(y|\mathbf{z})] + \mathbb{E}_{p(\mathbf{x},y)}\mathbb{E}_q[\log p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})] - \mathbb{E}_{q_\phi(\mathbf{u},\mathbf{z},\boldsymbol{\beta})}\big[KL[q_\phi(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})||p_\theta(\mathbf{x}|\mathbf{u},\mathbf{z},\boldsymbol{\beta})]\big] \\
&\leq I_r(y;\mathbf{z}) + I(\mathbf{x};\mathbf{u},\mathbf{z},\boldsymbol{\beta}) - [H(y) + H(\mathbf{x})]
\end{aligned}
$$

For clarity, we use $I(y;\mathbf{z})$ in place of $I_r(y;\mathbf{z})$ later in the Appendix and the main paper. $\qquad\square$

Lemma B.2 (**Information Decomposition of the Adversarial Loss**). *The global maximum of adversarial loss w.r.t. discriminator D is decomposed as below:*

$$\max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] = I(\mathbf{z};\boldsymbol{\beta}) + I(\mathbf{z},k|\boldsymbol{\beta}) - H(k) \tag{23}$$

and the global minimum of $\max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})]$ is achieved if and only if $I(\mathbf{z};\boldsymbol{\beta}) = I(\mathbf{z},k|\boldsymbol{\beta}) = 0$.

The optimization of adversarial loss is to reduce the mutual information between data encoding $\mathbf{z}$ and domain identity k while the mutual information is reduced between data encoding $\mathbf{z}$ and domain identity $\boldsymbol{\beta}$.

Proof. Define

$$s(k, \mathbf{x}, \boldsymbol{\beta}, \mathbf{z}) = p(k, \mathbf{x})q_\phi(\mathbf{z}|\mathbf{x})q_\phi(\boldsymbol{\beta}|k)$$
$$s(k, \boldsymbol{\beta}, \mathbf{z}) = q_\phi(\boldsymbol{\beta}, z|k)p(k) = q_\phi(\mathbf{z}|\boldsymbol{\beta}, k)q_\phi(\boldsymbol{\beta}|k)p(k)$$
$$s(k, \mathbf{z}) = p(k)q_\phi(\mathbf{z}|k) = s(k|\mathbf{z})q_\phi(\mathbf{z}) = p(k)\mathbb{E}_{p(\mathbf{x}|k)}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}$$

Then we have:

$$-\mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] = -\mathbb{E}_{s(\mathbf{z},k)}[\log D(k|\mathbf{z})] \leq -\mathbb{E}_{s(\mathbf{z},k)}[\log s(k|\mathbf{z})]$$

When the equality holds, the discriminator becomes optimal, i.e., $D(k|\mathbf{z}) = s(k|\mathbf{z})$. Due to $p(\boldsymbol{\beta}|k)$ is a function $f(k)$ mapping from k to $\boldsymbol{\beta}$. Therefore, we have:

$$p(\mathbf{z}|\boldsymbol{\beta}, k) = p(\mathbf{z}|f(k), k) = p(\mathbf{z}|k)$$

Thus, $s(k, \boldsymbol{\beta}, \mathbf{z}) = q_\phi(\mathbf{z}|k)q_\phi(\boldsymbol{\beta}|k)p(k)$. The three random variables meet the Markov chain $\boldsymbol{\beta} \leftarrow k \rightarrow \mathbf{z}$. By chain rule for mutual information, we have:

$$I(\mathbf{z}; \boldsymbol{\beta}) + I(\mathbf{z}, k|\boldsymbol{\beta}) = I(\mathbf{z}; \boldsymbol{\beta}, k) = I(\mathbf{z}; k) + I_q(\mathbf{z}, \boldsymbol{\beta}|k)$$

where $I_q(\mathbf{z}, \boldsymbol{\beta}|k) = 0$. So,

$$I(\mathbf{z}; k) = I(\mathbf{z}; \boldsymbol{\beta}) + I(\mathbf{z}, k|\boldsymbol{\beta})$$

We also have:

$$\mathbb{E}_{s(\mathbf{z},k)}[\log s(k|\mathbf{z})] = \mathbb{E}_{s(\mathbf{z},k)}[\log \frac{s(k|\mathbf{z})}{q_\phi(k)}q_\phi(k)]$$
$$= \mathbb{E}_{s(\mathbf{z},k)}[\log \frac{s(k|\mathbf{z})}{q_\phi(\mathbf{z})}] + \mathbb{E}_{s(\mathbf{z},k)}[\log q_\phi(k)]$$
$$= I(\mathbf{z}; k) - H(k)$$

$$\max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] = I(\mathbf{z}; k) - H(k) = I(\mathbf{z}; \boldsymbol{\beta}) + I(\mathbf{z}, k|\boldsymbol{\beta}) - H(k)$$

Therefore, $\min_\phi \max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] = 0 - H(k)$ while $I(\mathbf{z}; k) = 0$ and thus $I(\mathbf{z}; \boldsymbol{\beta}) = I(\mathbf{z}, k|\boldsymbol{\beta}) = 0$. $\square$

Theorem B.1 (**Objective Function as a Lower Bound**). *The objective function involves both the ELBO of $p_\theta(\mathbf{x}, y)$ and adversarial loss $\mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})]$, and it is the lower bound for a combination mutual information and entropy terms:*

$$\mathbb{E}_{p(\mathbf{x},y)}[\mathcal{L}_{ELBO}(\mathbf{x}, y)] - \max_D \mathbb{E}_{p(k,\mathbf{x})}\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log D(k|\mathbf{z})] \tag{24}$$
$$\leq I(y; \mathbf{z}) + I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta}) - I(\mathbf{z}; \boldsymbol{\beta}) - I(\mathbf{z}, k|\boldsymbol{\beta}) - [H(y) + H(\mathbf{x}) - H(k)]. \tag{25}$$

Proof. Theorem B.1 is proved by applying Eqn. 20 mine Eqn. 23. $\square$

Theorem B.2 (**Global Optimum of VDI**). *In VDI, the global optimum (Eqn. 14) is achieved, if and only if (1) $I(\mathbf{z}; \boldsymbol{\beta}) = I(\mathbf{z}, k; \boldsymbol{\beta}) = 0$, (2) $I(\mathbf{x}; \mathbf{u}, \mathbf{z}, \boldsymbol{\beta})$ is maximized, and (3) $I(y; \mathbf{z})$ is maximized.*

Proof. The condition (1) is gotten from Lemma B.2. The last two conditions (2) and (3) are gotten from Lemma B.1. $\square$

As Theorem B.2 states, the global optimum of Eqn. 14 is guaranteed to satisfy all three conditions in Definition 3.1; therefore training VDI using the minimax game objective Eqn. 14 is equivalent to inferring the optimal domain indices.

C DG-15 AND DG-60

For completeness, we show *DG-15* and *DG-60* in Fig. 7. We use 'red' and 'blue' to indicate positive and negative data points inside a domain. The boundaries between 'red' half circles and 'blue' half circles show the direction of ground-truth decision boundaries in the datasets.

(a) *DG-15*   (b) *DG-60*

Figure 7: Visualization of the *DG-15* (a) and *DG-60* (b) datasets. We use 'red' and 'blue' to indicate positive and negative data points inside a domain. The boundaries between 'red' half circles and 'blue' half circles show the direction of ground-truth decision boundaries in the datasets.

Figure 8: (Copied Fig. 1 here for easier reference.) **Left:** Probabilistic graphical model for VDI's generative model. We introduce a new edge type, "---", to denote independence. $\boldsymbol{\beta}_k$ --- $\mathbf{z}$ enforces independence between $\mathbf{z}$ and $\boldsymbol{\beta}_k$, i.e, $p(\mathbf{z}|\boldsymbol{\beta}_k) = p(\mathbf{z})$; note that this does *not* contradict $\boldsymbol{\beta}_k \rightarrow \mathbf{z}$ in our case. **Right:** Probabilistic graphical model for the VDI's inference model.

D   ADAPTING MDD AND SENTRY FOR REGRESSION TASKS

For **MDD**, we simply replace its cross-entropy loss with an L_2 loss. For **SENTRY**, since it requires confidence scores during training, we include another classification network that predicts whether the average temperature of next 6 months will go up or down compared to the previous 6 months, thereby providing confidence scores.

E   NEW EDGE TYPE FOR PROBABILISTIC GRAPHICAL MODELS

In Fig. 8, we introduce a new edge type, "---", to denote independence. $\boldsymbol{\beta}_k$ --- $\mathbf{z}$ enforces independence between $\mathbf{z}$ and $\boldsymbol{\beta}_k$, i.e, $p(\mathbf{z}|\boldsymbol{\beta}_k) = p(\mathbf{z})$; note that this does *not* contradict $\boldsymbol{\beta}_k \rightarrow \mathbf{z}$, as long as there are multiple paths between $\boldsymbol{\beta}_k$ and $\mathbf{z}$. In this case, we have two paths between $\boldsymbol{\beta}_k$ and $\mathbf{z}$, $\boldsymbol{\beta}_k \rightarrow \mathbf{z}$ and $\boldsymbol{\beta}_k \rightarrow \mathbf{u} \rightarrow \mathbf{z}$.

As a simplified example, consider only a sub-graph in Fig. 8 with only three nodes $\boldsymbol{\beta}_k$, $\mathbf{u}$, and $\mathbf{z}$. Essentially our algorithm tries to learn two conditional dependencies $p(\mathbf{u}|\boldsymbol{\beta}_k)$ and $p(\mathbf{z}|\boldsymbol{\beta}_k, \mathbf{u})$. Adding a dashed edge $\boldsymbol{\beta}_k$ --- $\mathbf{z}$ ensures that $p(\mathbf{z}|\boldsymbol{\beta}_k) = p(\mathbf{z})$, which is equivalent to

$$p(\mathbf{z}|\boldsymbol{\beta}_k) = p(\mathbf{z}|\boldsymbol{\beta}'_k), \ \ \forall \boldsymbol{\beta}_k, \boldsymbol{\beta}'_k,$$

which is equivalent to

$$\int p(\mathbf{u}|\boldsymbol{\beta}_k)p(\mathbf{z}|\boldsymbol{\beta}_k, \mathbf{u})d\mathbf{u} = \int p(\mathbf{u}|\boldsymbol{\beta}'_k)p(\mathbf{z}|\boldsymbol{\beta}'_k, \mathbf{u})d\mathbf{u}, \ \ \forall \boldsymbol{\beta}_k, \boldsymbol{\beta}'_k. \tag{26}$$

It is easy to see that Eqn. 26 only introduces an additional constraint, but does not contradict the learning of conditional dependencies $p(\mathbf{u}|\boldsymbol{\beta}_k)$ and $p(\mathbf{z}|\boldsymbol{\beta}_k, \mathbf{u})$.

Combining the ELBO below

$$\mathcal{L}_{ELBO}(\mathbf{x}, y) = \mathbb{E}_{q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}[p_\theta(\mathbf{u}, \mathbf{x}, \mathbf{z}, y, \boldsymbol{\beta}|\boldsymbol{\alpha})] - \mathbb{E}_{q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})}[q_\phi(\mathbf{u}, \mathbf{z}, \boldsymbol{\beta}|\mathbf{x})], \tag{27}$$

with the additional constraint in Eqn. 26, we have the following objective function

$$\max_{\boldsymbol{\theta},\boldsymbol{\phi}} \ \mathbb{E}_{p(\mathbf{x},y)}\Big[\mathbb{E}_{q_{\phi}(\mathbf{u},\mathbf{z},\boldsymbol{\beta}|\mathbf{x})}[p_{\theta}(\mathbf{u},\mathbf{x},\mathbf{z},y,\boldsymbol{\beta}|\boldsymbol{\alpha})] - \mathbb{E}_{q_{\phi}(\mathbf{u},\mathbf{z},\boldsymbol{\beta}|\mathbf{x})}[q_{\phi}(\mathbf{u},\mathbf{z},\boldsymbol{\beta}|\mathbf{x})]\Big], \quad (28)$$

$$s.t. \ \int p_{\theta}(\mathbf{u}|\boldsymbol{\beta}_k)p_{\theta}(\mathbf{z}|\boldsymbol{\beta}_k,\mathbf{u})d\mathbf{u} = \int p_{\theta}(\mathbf{u}|\boldsymbol{\beta}_k')p_{\theta}(\mathbf{z}|\boldsymbol{\beta}_k',\mathbf{u})d\mathbf{u}, \ \ \forall \boldsymbol{\beta}_k,\boldsymbol{\beta}_k', \quad (29)$$

which is equivalent to Eqn. 14.

F   LARGER FIGURES

In this section, we provide larger versions of figures for domain index visualization in the main paper.

Figure 9: Inferred domain indices for 48 domains in *TPT-48*. We color inferred domain indices according to ground-truth latitude. VDI's inferred indices are correlated with true indices, even though *VDI does not have access to true indices during training*.

Figure 10: Inferred domain indices for 48 domains in *TPT-48*. We color inferred domain indices according to ground-truth longitude. VDI's inferred indices are correlated with true indices, even though *VDI does not have access to true indices during training*.

Figure 11: Inferred domain indices for 30 domains in *CompCars*. We color inferred domain indices according to ground-truth viewpoints. VDI's inferred indices are correlated with true indices, even though *VDI does not have access to true indices during training*.

Figure 12: Inferred domain indices for 30 domains in *CompCars*. We color inferred domain indices according to ground-truth viewpoints. VDI's inferred indices are correlated with true indices, even though *VDI does not have access to true indices during training*.