Understanding Bottlenecks of State Space Models through the Lens of Recency and Over-smoothing

Abstract

Structured State Space Models (SSMs) have emerged as alternatives to transformers, addressing the challenges of processing long sequences. While SSMs are often regarded as effective in capturing long-term dependencies, we theoretically demonstrate that they suffer from a strong recency bias. Our empirical findings reveal that this bias impairs the models' ability to recall distant information and introduces robustness issues. We conducted scaling experiments and discovered that deeper structures in SSMs facilitate the learning of long contexts. However, our theoretical analysis reveals that as SSMs increase in depth, they exhibit a tendency toward over-smoothing, resulting in token representations becoming increasingly indistinguishable. This over-smoothing phenomenon ultimately constrains the scalability of SSMs to achieve improved performance. Collectively, these findings highlight important limitations of SSMs and underscore the need for further research to address these challenges in long-range sequence modeling.

1 Introduction

The evolution of sequence processing architectures has been witnessed over recent decades, progressing from RNNs (Hochreiter & Schmidhuber, 1997; Sutskever et al., 2014; Cho et al., 2014; Cho, 2014) to transformers (Vaswani et al., 2017; Devlin et al., 2019; Radford et al., 2018; 2019; Brown et al., 2020), and more recently proposed State Space Models (SSMs) (Gu et al., 2021a; Gu & Dao, 2023). Each step represents a leap in natural language processing, addressing the limitations of its predecessors and introducing new capabilities.

SSMs (Gu et al., 2021a; Gu & Dao, 2023; Dao & Gu, 2024) have emerged as a compelling alternative to transformers, addressing the challenges associated with processing long sequences. SSMs provide advantages in two key areas. Firstly, they enable more efficient handling of long sequences. SSMs operate in two modes: convolution and recurrence, each tailored for different aspects of language model training and inference (Gu et al., 2021b). In convolutional mode, SSMs assume visibility of the entire sequence and utilize hardware-optimized convolutions to propagate information across all tokens in parallel. This approach circumvents the need for calculating pairwise correlations inherent in attention mechanisms, thereby accelerating training speed. In the recent Mamba model (Gu & Dao, 2023), convolution has been supplanted by a parallel scanning algorithm, facilitating more expressive sequence-level mixing without sacrificing efficiency. Conversely, in recurrent mode, SSMs process one token at a time while maintaining a compact recurrent hidden state that encodes the sequence history. The outputs are sequentially decoded from this hidden state, eliminating the necessity to store all past key-value pairs (Dai et al., 2019), thus reducing memory usage during inference.

Furthermore, SSMs have been meticulously tailored to effectively capture long-range dependencies and filter contextual information. These models are grounded in the HiPPO theory (Gu et al., 2020), which demonstrates that a first-order Ordinary Differential Equation (ODE) can encapsulate long-term memory through a designated state matrix known as the HiPPO matrix. Subsequent research (Gu et al., 2021b;a; Gupta et al., 2022; Gu et al., 2022a) has streamlined this state matrix to a diagonal form, significantly enhancing computational efficiency while retaining the capability to model long-range dependencies. More recently, Mamba (Gu & Dao, 2023) introduced a selection mechanism that selectively aggregates pertinent information from the context into the state, showcasing impressive

performance in language modeling. Concurrently, another class of efficient sequential models, coined as Linear Attention Models, has emerged, derived from streamlined attention mechanisms (Katharopoulos et al., 2020; Sun et al., 2023; Peng et al., 2023; Yang et al., 2023). Collectively, these advancements can be interpreted through a unified lens as more structured SSMs (Dao & Gu, 2024).

However, despite the initial empirical successes of these models, recent findings indicate that SSMs may not match transformers in their ability to recall information from long contexts (Arora et al., 2023; Poli et al., 2024) or in handling more complex retrieval patterns (Park et al., 2024). Additionally, it has been noted that Mamba continues to underperform compared to transformers at larger scales (Waleffe et al., 2024). These shortcomings, however, have yet to be systematically elucidated.

In this paper, we identify two fundamental limitations of SSMs in their ability to model complex long-range dependencies. First, we argue that the long-term memory capabilities of modern SSMs may be misinterpreted. Our analysis reveals that an SSM layer exhibits a strong recency bias, limiting tokens to primarily interact with nearby context. This bias is intrinsic to SSMs and many linear attention models, regardless of the employed content-informing techniques, such as the selection mechanism introduced by Mamba (Gu & Dao, 2023). We further posit that the loss of long-range capabilities may stem from the oversimplification of HiPPO-induced SSMs, trading efficiency off the performance. To substantiate this claim, we perform a long-range retrieval task on an industrial-scale language model (Jiang et al., 2023) based on Mamba. Our test results indicate that Mamba catastrophically forgets distant content once the context length surpasses its memory capacity. Furthermore, we raise a novel robustness concern regarding SSMs with recency bias: our empirical outcomes show that Mamba is more susceptible to perturbations on local tokens, making it vulnerable to adversarial attack, as these local tokens can be easily manipulated to serve as backdoors.

Additionally, we conduct a series of scaling experiments with varying context lengths during the pre-training of SSMs. Our results indicate that increasing the model's depth is crucial for enhancing its ability to utilize long contexts by expanding the receptive field. However, we observe that depth scaling encounters a bottleneck, as performance begins to saturate with continued increases in depth. To investigate this scalability issue theoretically, we analyze the feature dynamics across SSM layers. Our findings reveal that SSMs inherently function as smoothening operators, leading to over-smoothing in deep architectures (NT & Maehara, 2021; Oono & Suzuki, 2019; Cai & Wang, 2020). As a result, token representations become increasingly uniform and indistinguishable with each additional layer.

2 PRELIMINARIES

In this work, we primarily focus on SSMs and their similar models working with discrete-time sequences of tokens. We represent the a sequence of tokens as $\boldsymbol{x} = [x_1 \quad \cdots \quad x_T]^\top \in \mathbb{R}^T$, where T is the total number of tokens. For vector-valued input sequences, SSMs process each channel independently. Therefore, to simplify notation, we focus on scalar-valued sequences without loss of generality. The impact of multi-channel inputs will be addressed in the relevant context.

SSMs learn to represent and forecast the next token by integrating past information. Formally, SSMs can be viewed as a sequence-to-sequence transformation from inputs $\boldsymbol{x} \in \mathbb{R}^T$ to outputs $\boldsymbol{y} \in \mathbb{R}^T$ through a *memory state* $\boldsymbol{h}_t \in \mathbb{R}^N$, which is iteratively updated with a linear recurrence. A general form can be written as:

$$\boldsymbol{h}_t = \boldsymbol{A}_t \boldsymbol{h}_{t-1} + \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t), \quad \boldsymbol{y}_t = c_t(\boldsymbol{h}_t), \quad \boldsymbol{h}_0 = \boldsymbol{0}, \quad \forall t \in [T], \tag{1}$$

where $t \in [T]$ denotes the time step. Intuitively, $\boldsymbol{A}_t \in \mathbb{R}^{N \times N}$ extracts information from the previous state $\boldsymbol{h}_{t-1}$ [1], $\boldsymbol{b}_t : \mathbb{R} \to \mathbb{R}^N$ projects every input token to the hidden space, $\Delta_t \in \mathbb{R}$ controls how much information of the new token will be fused into the hidden memory, and $c_t : \mathbb{R}^N \to \mathbb{R}$ decodes the hidden state at time t to the final prediction. In all SSMs considered in this paper, it is necessary to assume $(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)$ *only depends on the inputs at the time* t. SSMs are trained end-to-end to optimize for parameters $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$, for which different SSMs adopt various types of instantiation. Below we list some representative examples.

---

[1] In most scenarios discussed in this paper, we assume real parameterization by default, as it is the standard approach in the cases of our primary interest, such as language modeling (Gu & Dao, 2023)

S4, DSS, and S4D. The seminal works (Gu et al., 2020; 2021b; 2022b) demonstrate that discretizing time-invariant ODE $\boldsymbol{h}'(t) = \boldsymbol{A}\boldsymbol{h}(t) + \boldsymbol{b}x(t)$ with some special realization of matrix $\boldsymbol{A}$ can yield an efficient recurrent network for long-sequence modeling. The follow-up works Gu et al. (2021a) together with Gupta et al. (2022); Gu et al. (2022a) simplifies $\boldsymbol{A}$ to be a diagonal matrix. Applying the zero-order hold rule for discretization, as suggested by Gupta et al. (2022), we can summarize this series of models in the form of Eq. 1:

$$(\text{S4}) \quad \boldsymbol{A}_t = \exp(\Delta\boldsymbol{A}), \quad \boldsymbol{b}_t(\boldsymbol{x}_t) = \boldsymbol{b}\boldsymbol{x}_t, \quad c(\boldsymbol{h}_t) = \boldsymbol{c}^\top \boldsymbol{h}_t, \quad \Delta_t = \Delta, ^2 \tag{2}$$

where $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c}, \Delta)$ are learnable parameters. In particular, $\boldsymbol{A}$ is restricted to be a diagonal matrix and can be complex valued. However, $\boldsymbol{A}$ must have negative real part (Gu et al., 2022a). $\Delta \in (0, 1]$ is often interpreted as the time interval for discretization. We call this family of SSMs *S4* following the naming convention in Gu & Dao (2023).

Mamba. A recent breakthrough Mamba (Gu & Dao, 2023) introduces the *selection* mechanism to extend S4. Instead of learning $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c}, \Delta)$ in Eq. 2 as free parameters, Mamba conditions $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c}, \Delta)$ on the inputs, which enables each iterative step in Eq. 1 to filter useful token information during the recurrence. Specifically, Mamba computes $(\boldsymbol{A}_t\boldsymbol{b}_t, c_t, \Delta_t)$ as follows:

$$(\text{Mamba}) \quad \boldsymbol{A}_t = \exp(\Delta_t\boldsymbol{A}), \ \boldsymbol{b}_t(\boldsymbol{x}_t) = (\boldsymbol{W}_B\boldsymbol{x}_t)\boldsymbol{x}_t, \ c_t(\boldsymbol{h}) = (\boldsymbol{W}_C\boldsymbol{x}_t)^\top \boldsymbol{h}_t, \ \Delta_t = \sigma(\boldsymbol{W}_\Delta\boldsymbol{x}_t), \tag{3}$$

where $\boldsymbol{W}_\Delta \in \mathbb{R}, \boldsymbol{W}_B \in \mathbb{R}^N, \boldsymbol{W}_C \in \mathbb{R}^N$ are learnable weights in addition to $\boldsymbol{A}$, and $\sigma(\cdot)$ denotes softplus activation. When handling multi-dimensional token embeddings, $\boldsymbol{W}_\Delta, \boldsymbol{W}_B, \boldsymbol{W}_C$ are extended on the input dimension ^{3}. The resultant Δ_t is then specified for each channel, while $\boldsymbol{b}_t, \boldsymbol{c}_t$ are shared across channels. In language modeling, $\boldsymbol{A}$ has strictly negative real-valued diagonal, which ensures $\boldsymbol{A}_t \in (0, 1)^{N \times N}$. Additionally, Mamba is integrated with the H3 architecture (Fu et al., 2022), wherein the selective SSMs is working with a local convolution and sandwiched by two gated connections.

Linear Attention. Concurrent with SSMs, there is another line of work streamlining attention to linear time complexity. With slight abuse of terminology, we name all of them collectively as Linear Attention Models (LAMs). We observe that many of them can be written in the form of Eq. 1 such that in the remainder of this paper, we extend the definition of SSMs to include LAMs without introducing ambiguity, as LAMs and SSMs are dual to each other (Dao & Gu, 2024). We leave a full summary to Appendix A.

3 CAN SSM EFFECTIVELY REPRESENT LONG-RANGE DEPENDENCIES?

3.1 SSMs ARE LOCALLY BIASED

In this section, we investigate the ability of SSMs to learn long-range dependencies. Recent studies find that SSMs seem more effective than transformers on this task (Gu et al., 2020; Tay et al., 2020; Li et al., 2022; Gu & Dao, 2023). However, in Sec. 3.1 we theoretically show a negative result that an SSM layer is inherent to *local bias* and loses long-term memory exponentially. In Sec. 3.2, we empirically justify our claim by showing SSMs struggle to retrieve from distant context. We also demonstrate that the local bias may lead to robustness issues in Sec. 3.3.

To understand how information is propagated and long-range dependencies are modeled in SSMs, we aim to uncover the relationship between the output at time $t \in [T]$ and the input token at time $s \le t$. We define the derivatives $|\partial\boldsymbol{y}_t/\partial\boldsymbol{x}_s|$ as the *influential score* to represent the importance of the s-th input token to the t-th output token. Note that $|\partial\boldsymbol{y}_t/\partial\boldsymbol{x}_s|$ is well-defined for every $s, t \in [T]$ as long as $(\boldsymbol{A}_t.\boldsymbol{b}_t, c_t, \Delta_t)$ are all differentiable in terms of $\boldsymbol{x}$. Intuitively, if $|\partial\boldsymbol{y}_t/\partial\boldsymbol{x}_s|$ is larger, then the s-th input token is more influential on the t-th output token, and vice versa.

Below we present a formal result regarding the influential score.

---

^{2}More rigorously, by zero-order hold, $\boldsymbol{b}$ should be parameterized as $\boldsymbol{b} = (\Delta\boldsymbol{A})^{-1}(\exp(-\Delta\boldsymbol{A}) - \boldsymbol{I})\boldsymbol{b}$. However, the presented form is more commonly used in practice as in Gu & Dao (2023).

^{3}Suppose the embedding dimension is D, then $\boldsymbol{W}_\Delta \in \mathbb{R}^D$, $\boldsymbol{W}_B \in \mathbb{R}^{N \times D}$, and so on.

Theorem 3.1 (Recency of SSMs). *Consider an SSM defined in Eq. 1 with $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$. Assume that (i) the input space $\mathcal{X} \subset \mathbb{R}^T$ is compact, (ii) $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$ are continuous and have continuous derivatives, and (iii) $\boldsymbol{A}_t \in (0, 1)^{N \times N}$ are diagonal matrices for all $t \in [T]$. Let $A_{max} = \max_{t \in [T], n \in [N]}(\boldsymbol{A}_t)_{n,n}$. Then for arbitrary $\boldsymbol{x} \in \mathcal{X}$ and every $s, t \in [T]$ such that $s < t$, $|\partial \boldsymbol{y}_t / \partial \boldsymbol{x}_s| = O(\exp(-\kappa(t - s)))$ for some $\kappa = \Theta(\log(A_{max}^{-1}))$.*

The proof can be found in Appendix C.1. The first two assumptions are standard and always satisfied. The third assumption also holds for most of SSMs discussed in Sec. 2. Therefore, Theorem 3.1 applies to numerous SSMs including but not limited to S4 (Gu et al., 2021a; 2022a), Mamba (Gu & Dao, 2023), RetNet (Sun et al., 2023), RWKV (Peng et al., 2023), GLA (Yang et al., 2023), HGRN2 (Qin et al., 2024), Griffin (De et al., 2024), and Megalodon (Ma et al., 2022; 2024). Theorem 3.1 states that influential scores between two tokens modeled by SSMs are *exponentially* diminishing with respect to their relative distance. The decay rate is determined by the maximal values among all $\boldsymbol{A}_t$'s elements. The closer A_{max} is to zero, the faster the influential scores decay. The practical implication is that SSMs are factually recency-biased models. Tokens farther away are under-reaching and forgotten rapidly while the information of closer tokens dominates the final output. This can significantly limit their ability of fitting complex long-range relationships.

Figure 1: Visualization of influential scores. The y-axis represents the value of $|\partial \boldsymbol{y}_t / \partial \boldsymbol{x}_s|$ and x-axis denotes $(t - s)$.

Empirical Validation. We empirically verify our theory by directly plotting the influential score w.r.t. the relative distances in Fig. 1. The blue and orange curves in Fig. 1 successfully justify our exponentially decaying bound in Theorem 3.1. In contrast, transformer-based architectures is free from the strong recency bias, while demonstrating a well-known "lost-in-the-middle" pattern (Liu et al., 2024b).

Is decay a necessary and desirable design? One key observation from our theory is that the parameterization of $\boldsymbol{A}_t$ within the interval $(0, 1)$ leads to strictly decaying dependencies among tokens based on their relative distances. This design choice appears to be a standard practice, and perhaps intentional, in several recently proposed SSMs (Gu & Dao, 2023; Dao & Gu, 2024; Beck et al., 2024; Yang et al., 2023; Peng et al., 2024; De et al., 2024; Ma et al., 2024; Liu et al., 2024a; Yang et al., 2024). Interestingly, it has been demonstrated that this "intentional" decay of long-range dependencies not only avoids degrading the perplexity of language models but also improves generalization for length extrapolation. This observation aligns with the empirical success of soft gating mechanisms adopted in traditional RNNs (Cho, 2014; Cho et al., 2014; Gu et al., 2021b) and the decaying patterns imposed on transformers (Raffel et al., 2020; Press et al., 2021; Sun et al., 2022). We find the constraint $\boldsymbol{A}_t \in (0, 1)^{N \times N}$ is likely inherent to SSMs as it plays a critical role in ensuring the numerical stability for length generalization during long-context recurrence (Gu et al., 2022a; Yang et al., 2023). Promoting the importance of local tokens could also lead to a nearly correct bias, as natural language generation mostly utilizes recent contexts. However, as we will detail in subsequent sections, this design comes with a significant drawbacks: it result in substantial loss of long-distance information (Sec. 3.2) and may raise potential security concerns (Sec. 3.3). This observation underscores that the validation perplexity may not fully capture all aspects of a model's capabilities and can be an inadequate metric for assessing long-range dependencies.

3.2 LOST IN THE DISTANCE: LONG-CONTEXT RETRIEVAL TEST

To assess the ability of large language models (LLMs) to effectively utilize long-context data, we evaluate open-source SSM using the "Needle in a Haystack" benchmark and compare its performance with that of Transformer. In this benchmark, a randomly generated statement is embedded within the middle of a long document, and the models are tasked with retrieving the statement. By varying the insertion position of the statement, we measure the retrieval accuracy at each location, which reflects

Figure 2: Comparison between SSM and Transformer on the "Needle in a Haystack" benchmark. The left figure shows the retrieval accuracy of the Mamba-Codestral-7B model, while the right figure presents the retrieval accuracy of the Mistral-7B model. We present a heatmap where "full context length" refers to the total length of the document, and "needle position" denotes the relative position of the statement to be retrieved within the context. See more fine-grained visualization in Appendix D.1.

the model's positional bias. To enforce LLMs using the data within context, instead of recalling information memorized by its model weights, we carefully design the statement with factual error. See detailed examples in Appendix D.1.

We compare the retrieval accuracy of the Mamba-Codestral-7B model, a representative SSM capable of handling long-context inputs of up to 256k tokens, with Mistral-7B (Jiang et al., 2023), which utilizes a transformer architecture. As illustrated in Figure 2, the retrieval accuracy of the Transformer remains stable regardless of the needle position. In contrast, the SSM achieves higher accuracy when the needle is placed closer to the end of the context (i.e., larger needle position values), while its accuracy drops when the needle is located near the beginning of the document. This indicates a positional bias towards local tokens in the SSM.

3.3 POTENTIAL RISK ON MODEL ROBUSTNESS

We conduct quantitative experiments to show the recency-biased nature of SSMs will lead to potential hazards. The downstream task in this study is image classification on sequences of pixels (Tay et al., 2020), where $W \times H$ images are flattened to sequences of pixel tokens and fed to sequence models for classification. We test a family of SSMs, including H3 (Fu et al., 2022), RWKV (Peng et al., 2023), and Mamba (Gu & Dao, 2023), and compare them against a transformer baseline (Vaswani et al., 2017) on CIFAR-10 dataset. To adapt SSMs for this task, we append a learnable class token after the last token of the input sequence. The output state of this class token is then mapped to logits using a classifier head. Experiment details are given in Appendix D.2. In the following, two attack patterns on the input data are introduced, which degrade the robustness of SSMs in this task.

Adversarial Attack. To assess the bias of SSMs towards corrupted data, we perturb the leading and trailing tokens of input sequences with random noise. In unbiased models, perturbations in both leading and trailing tokens cause similar performance drops. However, in locally biased models, where the class token is appended after the last input token, the trailing tokens are supposed to have greater impacts on classification outcomes than leading tokens. Table 1 presents our experimental results on the CIFAR-10 dataset under two corruption ratios. For each ratio, the same number of leading and trailing tokens are corrupted with Gaussian noise. Among all the SSM family methods compared, the performance drops caused by trailing token corruption are significantly larger than those caused by leading token corruption. Notably, for Mamba, perturbing the last 32 out of 1024 tokens results in an 81.24% drop in classification accuracy, whereas corrupting the first 32 tokens only reduces accuracy by 2.30%. In contrast, the transformer baseline shows relatively smaller impacts

Table 1: Results of adversarial attack experiments on the CIFAR-10 dataset, evaluated using classification accuracy. Each input sequence contains 1,024 tokens. Two corruption ratios (32/1024 and 96/1024) are applied to perturb the leading and trailing tokens, respectively.

| Models | (no corrupt) | **Corrupted region** (seq. length = 1024) | | | |
		[992:1024]	[0:32]	[928:1024]	[0:96]
H3	0.654	0.569 (↓ 13.04%)	0.654 (↓ 0.03%)	0.477 (↓ 27.07%)	0.650 (↓ 0.72%)
Transformer	0.580	0.535 (↓ 7.81%)	0.447 (↓ 22.95%)	0.431 (↓ 25.76%)	0.370 (↓ 36.32%)
RWKV	0.474	0.150 (↓ 68.35%)	0.466 (↓ 1.58%)	0.138 (↓ 70.88%)	0.460 (↓ 2.91%)
Mamba	0.674	**0.126 (↓ 81.24%)**	0.658 (↓ 2.30%)	**0.098 (↓ 85.46%)**	0.647 (↓ 3.98%)

(a) Attack ratio $= 256/1024$ (25.00%) (b) Attack ratio $= 480/1024$ (46.875%)

Figure 3: Results of target attack experiments on CIFAR-10, where "horse" is the target class. (a) and (b) present target attack success rates under two attack ratios. Lower success rates suggest higher robustness in the corresponding attack regions.

from trailing token corruption. Instead, our experiments indicate that more informative features from transformers tend to sink in the leading tokens, aligning with the observations in Xiao et al. (2023).

Target Attack.   Beyond degrading the performance of SSMs by attacking trailing tokens, we also demonstrate that local bias creates a backdoor for target attacks. In this scenario, a target class is selected, and pixel tokens from that class are used to replace those in images from other classes. The attack succeeds when models mis-classify images from other classes as belonging to the target class. Due to the local bias, trailing tokens are expected to be a more effective attack region for SSMs, leading to a significantly higher attack success rate compared to leading tokens. Fig. 3 shows the success rate comparisons across different attack regions and ratios. When trailing regions are replaced with pixels from the target class, SSMs achieve much higher success rates than when leading regions are attacked. This phenomenon is observed at both 25% and 47% attack ratios. By comparison, the transformer model possesses greater robustness, maintaining similar success rates between attacks on leading and trailing tokens.

Implications for Language Models.   While our adversarial attack experiments are conducted on image datasets, the findings have broader implications for language models. System prompts, which are typically a group of confidential tokens prepended to user inputs, play a critical role in controlling the behavior of language models and preventing undesirable outputs. However, our targeted attack experiments reveal that SSM-based language models are particularly vulnerable to jailbreak attacks (Perez & Ribeiro, 2022; Zou et al., 2023). This is because SSMs prioritize recent information over past tokens, making it easier to bypass system prompts by appending jailbreak instructions at the end of the input. Moreover, our theoretical analysis suggests that fine-tuning LLMs with instructional datasets or human feedback to enforce adherence to system prompts may not resolve this vulnerability, as the recency bias remains inherent to SSM models regardless of weight configurations.

4 Understanding Scalability Bottleneck of SSMs

4.1 Necessity and Limits of Depth Scaling

In Sec. 3.1, we have seen that the dependencies between tokens are exponentially decaying with their relative distances in an SSM layer. Consequently, SSMs resemble localized kernels, similar to those employed in various neural architectures such as Convolutional Neural Networks (CNNs) (LeCun et al., 1998) and Graph Neural Networks (GNNs) (Kipf & Welling, 2016). It is a reasonable postulation that increasing the number of layers can extend the model's receptive field (Goodfellow et al., 2016). We justify this hypothesis via a scaling-up experiment with various context lengths and model architectures.

We pretrain Mamba using causal language modeling with two context lengths, {2048, 8192}. Besides, we fix the number of layers at {16, 24, 32, 48, 64, 72} and vary the hidden dimension. We defer more experiment details in Appendix D.3. The validation loss versus the number of parameters is plotted in Fig. 4. Under the 2048 context length, models of different configurations exhibit similar performance, consistent with the findings of Kaplan et al. (2020). However, as the context length increases, the scaling behavior across depth-width configurations begins to diverge. Notably, deeper models outperform shallower ones, likely because deeper architectures can more effectively utilize

Figure 4: We empirically observe that deeper models become increasingly advantageous as the context length grows. However, beyond a certain depth, the performance of SSMs begins to plateau and eventually declines.

the extended context to meet the training objectives. Nevertheless, we observe that the performance gain starts to saturate when we keep increasing the depth (cf. the 32-layer and 48-layer models). When the depth of the model continues to increase, the validation perplexity starts to rise, indicating a decline in performance (cf. the 64-layer and 72-layer models). In Mamba with a 2048 context length, models with more than 48 layers perform worse than 16-layer models. Longer-context models appear to be more tolerant of increased depth, whereas shorter-context models experience a rapid performance degradation once the depth exceeds a certain threshold.

4.2 UNVEILING OVER-SMOOTHING IN SSMs

To explain the depth scaling bottleneck revealed in the previous section, we conduct a theoretical and empirical investigation of the feature and state dynamics in SSMs. Our key finding is that token embeddings, after being processed by SSM layers, tend to become increasingly similar, which leads to a phenomenon commonly referred to as *over-smoothing* (NT & Maehara, 2021; Cai & Wang, 2020; Oono & Suzuki, 2019). Over-smoothing occurs when token representations become indistinguishable, rendering the state uninformative.

First of all, we warm up by studying continuous-time S4 with constant $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c})$. Recall that a continuous-time S4 layer can be described by a group of ODEs: $\boldsymbol{h}'(t) = \boldsymbol{A}\boldsymbol{h}(t) + \boldsymbol{b}x(t), \boldsymbol{y}(t) = \boldsymbol{c}^\top \boldsymbol{h}(t)$. Our analysis starts with the equivalence between convolution and S4 (Gu et al., 2021b). This is, the analytic solution to the time-invariant ODE can be expressed as $\boldsymbol{y}(t) = \int \boldsymbol{c}^\top \exp(\boldsymbol{A}(t - s))\boldsymbol{b}x(s)ds$. Now we analyze the filtering property of this convolution operator from the Fourier domain perspective. We define a convolutional operator as a low-pass filter if it suppresses high-frequency components (see Definition C.3). We summarize the main finding in the following proposition, whose formal version and proof are provided in Appendix C.2.1:

Proposition 4.1 (Low-pass filtering of continuous S4). *Consider a continuous-time S4 with parameters $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c})$. Assume $\boldsymbol{A}$ is diagonal with all values negative. Then $\boldsymbol{y}(t) = \int \boldsymbol{c}^\top \exp(\boldsymbol{A}(t - s))\boldsymbol{b}x(s)ds$ defines a low-pass filter.*

The assumption therein is always satisfied when real parameterization is adopted (Gu et al., 2022a). Proposition 4.1 states that S4 is inherently a low-pass filter regardless of how $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c})$ are trained. Therefore, the high-frequency components of input signals are being constantly removed at each layer. Presumably, stacking many S4 layers might cause over-smoothing when all high-frequency components are suppressed to zero.

Now we consider a more general scenario when SSMs work on discrete-time regime and $(\boldsymbol{A}_t, \boldsymbol{b}_t, \boldsymbol{c}_t, \Delta_t)$ are time-varying or even data-dependent. Formally, we prove the following result showing the sharpness of input signals will be reduced as well:

Theorem 4.2 (Over-smoothing of SSMs). *Consider an SSM specified in Eq. 1 with $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$. Assume an input space $\mathcal{X} \subset \mathbb{R}^T$ such that for every $\boldsymbol{x} \in \mathcal{X}$, (i) $(\boldsymbol{A}_t)_{n,n} + \Delta_t \leq 1$ for every $n \in [N]$ and $t \in [T]$, (ii) $\min_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)_n \leq 0$ and $\max_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)_n \geq 0$ for every $n \in [N]$. Let $A_{min} = \min_{t \in [T], n \in [N]}(\boldsymbol{A}_t)_{n,n}$. Then for any $\boldsymbol{x} \in \mathcal{X}$ and the memory*

(a) $\boldsymbol{b}_t$ and $\boldsymbol{h}_t$. (b) Mixer output. (c) Block output.

Figure 5: Visualization of feature smoothness across layers in pre-trained Mamba and Pythia. The y-axis represents the average pairwise differences among tokens. Mixer outputs (b) solely consider the Mamba or attention module, while Block outputs (c) include all other components (e.g., MLP).

states $\{\boldsymbol{h}_t : t \in [T]\}$ *generated by the SSM, we have:*

$$\max_{t,s \in [T]} \|\boldsymbol{h}_t - \boldsymbol{h}_s\|_\infty \leq \left(1 - A_{min}^{T-1}\right) \max_{t,s \in [T]} \|\boldsymbol{b}_t(\boldsymbol{x}_t) - \boldsymbol{b}_s(\boldsymbol{x}_s)\|_\infty , \tag{4}$$

Proof can be found in Appendix C.2.2. We first justify our assumptions here. $(\boldsymbol{A}_t)_{n,n} + \Delta_t \leq 1$ is a generic condition to ensure the recurrence of SSMs is non-expansive, which is crucial to guarantee memory states stay numerically stable. The second assumption requires the data to be well-distributed and centered around the origin, which can be easily satisfied by normalization techniques. We find that prevalent SSM models such as (Gu & Dao, 2023; Peng et al., 2023; De et al., 2024; Qin et al., 2024) can easily achieve these two assumptions. Moreover, if $(\boldsymbol{A}_t)_{n,n} + \Delta_t = 1$ is always true letting each recurrent update be conservative (Peng et al., 2023; Ma et al., 2022), then we can remove the second assumption as well (see Theorem C.5). Theorem 4.2 examines the relationship between the pairwise distances of memory states and encoded tokens within the sequence. This result indicates that the pairwise discrepancies among memory states are diminished by a factor less than one, suggesting that the memories undergo smoothing following the application of an SSM in Eq. 1. We infer that if the memory is losing its discriminative capacity, the intermediate hidden feature space will similarly collapse.

Delving deeper, the decay rate is intricately linked to both the context length and the minimal value within $\{\boldsymbol{A}_t, t \in [T]\}$. As the context length increases, it requires more time to effectively mix all tokens. This can be understood from the message-passing perspective (Gilmer et al., 2017): the message of the first token needs to go through the whole sequence to be mixed with the last token. When A_{min} approaches one, the decay rate is maximized, as the entire SSM essentially performs a uniform pooling over the entire sequence, which smoothens the signal via a box-like filter. It is worth noting that the smoothing nature of SSMs is intuitive; one can conceptualize the recurrent operation of SSMs as performing a running average of the encoded token signals.

Empirical Validation. We adopt a pairwise distance between tokens to quantify the sharpness of a signal: $\mathcal{E}(\boldsymbol{x}) = \frac{1}{2(N-1)}\left(\sum_{i \neq j}\|\boldsymbol{x}_i - \boldsymbol{x}_j\|_2^2\right)/\left(\sum_i\|\boldsymbol{x}_i\|_2^2\right)$. $\mathcal{E}(\boldsymbol{x})$ being small means the token representations are close to each other and become less discriminative. We plot the feature smoothness of a 1.4B Mamba in Fig. 5. In Fig. 5a, $\boldsymbol{b}_t$ is above $\boldsymbol{h}_t$ among all Mamba blocks. This suggests the sharpness of input signals is consistently higher than the sharpness of the memory state output from Mamba, verifying our Theorem 4.2. In addition, Fig. 5b and 5c show the sharpness of Mamba mixer and Mamba block output, which tends to decrease rapidly in deeper layers. We also provide a comparison with a transformer (of the same size). Although transformers suffer from over-smoothing in theory (Dong et al., 2021; Shi et al., 2022; Wang et al., 2022), we observe that transformers have a slower decay of feature sharpness. See more discussions in Appendix B.

5 DISCUSSIONS

In this section, we provide further discussions on our results while deferring the remaining parts to Sec. B due to page limit. We also propose initial solutions to enhance SSMs based on our theories.

Revisiting HiPPO theory. HiPPO, introduced in (Gu et al., 2020) and extended by Gu et al. (2021b; 2022b), forms the theoretical basis of SSMs. It optimally reconstructs a signal x up to time t by minimizing $\|x_{\leq t} - y^{(t)}\|_{L_2(\omega^{(t)})}$ with respect to a measure $\omega^{(t)}$ supported on $(-\infty, t]$. The solution projects $x_{\leq t}$ onto N basis functions, producing a coefficient vector $\boldsymbol{h}(t)$, which synthesizes $y^{(t)}$ via linear combinations. Gu et al. (2020) showed $\boldsymbol{h}(t)$ evolves as $\boldsymbol{h}'(t) = \boldsymbol{A}(t)\boldsymbol{h}(t) + \boldsymbol{b}(t)x(t)$, where $\omega^{(t)} = \mathbb{I}[0, t]/t$ yields closed form $\boldsymbol{A}(t) = -\boldsymbol{A}_{hippo}/t$. Subsequent works like S4 (Gu et al., 2021a) and Mamba (Gu & Dao, 2023) utilize this matrix as initialization but omitted $1/t$, resulting in a warped measure $\omega^{(t)}(s) \propto \exp(s - t)\mathbb{I}[s < t]$ (Gu et al., 2022b). This measure emphasizes recent history when approximating $x_{\leq t}$. Hence, findings of Gu et al. (2022b) do not contradict our results but also align with Theorem 3.1. The practical implementations often disconnect from HiPPO theory by neglecting the unitary matrices associated with $\boldsymbol{A}_{hippo}$. Whereas, we focus on discrete-domain SSMs, adhering to practical parameterizations. Additionally, Gu et al. (2021b) demonstrates that SSMs' expressiveness spans all convolutions and RNNs. We contend that the low-pass filtering property also arises from the parameter simplifications of $\boldsymbol{A}_t$ (see Proposition 4.1).

The effect of selection mechanism. Traditional S4 architectures operate as linear time-invariant systems. To introduce more non-linearity, Mamba (Gu & Dao, 2023) proposes modeling $(\boldsymbol{b}_t, c_t, \Delta_t)$ as a function of inputs, a mechanism known as *selection*. This is motivated by the selective copying synthetic task, wherein $\boldsymbol{A}_t$ and $\boldsymbol{b}_t$ need to adapt based on content to filter relevant information for memory updates. Despite this adaptation, Theorem 3.1 still holds in scenarios involving the selection mechanism, meaning selective SSMs like Mamba may continue to suffer from recency bias. In the meantime, Theorem 4.2 also applies to Mamba, suggesting that the selective SSMs do not demonstrate higher expressiveness in filtering signals and perform similarly to linear S4 as low-pass filters (Proposition 4.1). Nevertheless, we note that selection can alleviate these issues by adaptively controlling the values in $\boldsymbol{A}_t$. According to our theory, the selection mechanism can potentially make the upper bound A_{max} closer to one and the lower bound A_{min} closer to zero. However, parameter $\boldsymbol{A}$ in Eq. 3 is initialized with negative integers (Gu et al., 2022a), which exacerbates the bound in Theorem 3.1 by accelerating the decay rate of the influence score.

Importance of context scaling. Theorem 4.2 also highlights the importance of context-length scaling to mitigate the over-smoothing issue. As the smoothing rate decreases with increased context length, lengthening training sequences not only relieves over-smoothing but also maximizes the utility of hardware efficiency of SSMs. This is also evidenced by Fig. 4, where models with longer training contexts have better tolerance of deeper architectures.

6 MITIGATING RECENCY AND OVER-SMOOTHING VIA POLARIZATION

In this section, we propose a simple solution to mitigate recency and over-smoothing simultaneously. First of all, results in Theorem 3.1 and Theorem 4.2 can be interpreted in conjunction. To relieve the smoothening rate, one might aim to minimize the values in $\boldsymbol{A}_t$. However, this could inadvertently enhance the locality of SSMs, as a decrease in A_{max} may occur. A practical implication of this relationship is that the values in $\boldsymbol{A}_t$ should be as diverse as possible to simultaneously mitigate the artifacts of recency and over-smoothing.

Figure 6: Cumulative histogram of $(A_{max} - A_{min})$. The height of each bin represents the cumulative proportion of $(A_{max} - A_{min})$ less than or equal to the corresponding value on the x-axis.

Although $A_{min} \approx 0$ and $A_{max} \approx 1$ could theoretically occur simultaneously, our empirical findings show that these values are largely concentrated within a narrow range. To illustrate this, we visualize the distribution of $(A_{max} - A_{min})$ across different channels in Fig. 6. Each bin represents the proportion of channels whose memory state satisfies $(A_{max} - A_{min})$ being smaller than the corresponding threshold on the x-axis. Notably, over 60% of channels have $(A_{max} - A_{min})$ values smaller than 0.5, indicating that most channels cannot simultaneously achieve $A_{max} \approx 1$ and $A_{max} \approx 0$. Memory representations will inevitably undergo either exponential diminishing or over-smoothing.

To this end, we propose to maintain one component in $\boldsymbol{A}_t$ as a constant 1, another as a constant 0, and others freely learnable. We term this approach as *polarization*. Polarization ensures that the dimension polarized to zero in the state memory consistently focuses on the current token, counteracting over-smoothing by preventing mixing with previous tokens. Simultaneously, another dimension polarized to one exclusively retains information from past tokens, avoiding locality issues by preserving the complete history. In our implementation (see Appendix D.4), we polarize the first state channel to one (*i.e.*, $(\boldsymbol{A}_t)_{1,1} = 1$) and the last state channel to zero (*i.e.*, $(\boldsymbol{A}_t)_{N,N} = 0$).

We empirically validate our polarization technique through the *associative recall* tasks, where Mamba models (Gu & Dao, 2023) are trained over sequences of key-value pairs to retrieve the associated value according to the query from the context. Please refer to Arora et al. (2023) and Appendix D.4 for more details. If an SSM can recall information with higher accuracy from a larger number of key-value pairs, then it has better long-context capability. We test the performance of Mamba with neither, one of, or both zero- and one-polarized channels, across different numbers of layers. The empirical results are reported in Tab. 2 (an extended version in Appendix

Configurations	# Layers	# KV Pairs			Avg.
		64	128	256	
Default $\boldsymbol{A}_t$	2	98.38	81.81	36.00	72.06
Default $\boldsymbol{A}_t$	4	99.23	82.08	33.52	71.61
$(\boldsymbol{A}_t)_{1,1} = 1$	2	99.81	94.70	56.39	83.63
$(\boldsymbol{A}_t)_{N,N} = 0$	2	98.41	81.35	36.55	72.10
$(\boldsymbol{A}_t)_{N,N} = 0$	4	99.74	92.20	52.21	81.38
$(\boldsymbol{A}_t)_{1,1} = 1, (\boldsymbol{A}_t)_{N,N} = 0$	2	99.23	95.54	54.74	83.17
$(\boldsymbol{A}_t)_{1,1} = 1, (\boldsymbol{A}_t)_{N,N} = 0$	4	99.94	98.80	81.56	93.43

Table 2: Results of polarization. Rows 1-2 have no polarization, rows 3-5 only polarize one channel to either one or zero, and rows 6-7 polarize both channels.

D.4). The key observation is that the default parameterization of $\boldsymbol{A}_t$ suffers from information retrieval from long context, and deepening the architecture even harms the performance (potentially due to over-smoothing). However, once we introduce a channel polarized to one, even shallow Mamba could perform high-accuracy associative recall (row 3). We can also gain the performance by deepening Mamba if the over-smoothing issue can be bypassed by adopting the zero-polarized channel (row 5). Furthermore, if we could apply one- and zero-polarized channels, and in the meanwhile deepening the architecture, we find it achieves the best performance over all settings (row 7).

7 OTHER RELATED WORK

Despite the remarkable empirical success of SSMs in various long-range applications (Lieber et al., 2024; Zhu et al., 2024; Zhang et al., 2024), their theoretical properties and limitations remain underexplored. Arora et al. (2023) leverages associative recall tasks to theoretically analyze the expressiveness of convolutional SSMs, while advocating for input-dependent kernels. Jelassi et al. (2024) separates the representation capacity of transformers and SSMs via coping tasks. Recent work by Merrill et al. (2024) identifies failure modes of SSMs in state-tracking problems through circuit complexity theory. Hahn (2020) characterize the expressivity of SSMs using linear controlled differential equations, and Ali et al. (2024) reveal structural similarities between selective SSMs and attention mechanisms. While these works provide valuable insights consistent with our findings, none directly examine the long-range modeling capability of SSMs. Ben-Kish et al. (2024) points out that the product of gating matrices (formalized in our Lemma C.1) exhibits locality issues, potentially hindering their ability to model long-range dependencies. However, their analysis lacks a formal justification. Wang & Xue (2024) presents similar theoretical results revealing exponentially decaying long-range dependencies. Nevertheless, their analysis does not consider *input-dependent parameters* $(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)$, which severs as key to the success of modern SSMs (Gu & Dao, 2023; Yang et al., 2023). We defer more comparison with Wang & Xue (2024) to Appendix B. To our best knowledge, none of any earlier works reveals the smoothening nature of SSM operators.

8 CONCLUSION

In this study, we uncover two critical limitations of SSMs. First, we demonstrate that SSMs exhibit a strong recency bias, which significantly impairs their ability to capture long-range dependencies and recall distant information, and even raises robustness concerns. Furthermore, our findings indicate that increasing the depth of SSMs leads to over-smoothing, causing token representations to become indistinguishable and obstructing potential performance gains. We stress the necessity for future research to tackle these challenges, ultimately enhancing the effectiveness of SSMs in natural language tasks.

REFERENCES

Ameen Ali, Itamar Zimerman, and Lior Wolf. The hidden attention of mamba models. *arXiv preprint arXiv:2403.01590*, 2024.

Uri Alon and Eran Yahav. On the bottleneck of graph neural networks and its practical implications. *arXiv preprint arXiv:2006.05205*, 2020.

Simran Arora, Sabri Eyuboglu, Aman Timalsina, Isys Johnson, Michael Poli, James Zou, Atri Rudra, and Christopher Ré. Zoology: Measuring and improving recall in efficient language models. *arXiv preprint arXiv:2312.04927*, 2023.

Maximilian Beck, Korbinian Pöppel, Markus Spanring, Andreas Auer, Oleksandra Prudnikova, Michael Kopp, Günter Klambauer, Johannes Brandstetter, and Sepp Hochreiter. xlstm: Extended long short-term memory. *arXiv preprint arXiv:2405.04517*, 2024.

Assaf Ben-Kish, Itamar Zimerman, Shady Abu-Hussein, Nadav Cohen, Amir Globerson, Lior Wolf, and Raja Giryes. Decimamba: Exploring the length extrapolation potential of mamba. *arXiv preprint arXiv:2406.14528*, 2024.

Yoshua Bengio, Patrice Simard, and Paolo Frasconi. Learning long-term dependencies with gradient descent is difficult. *IEEE transactions on neural networks*, 5(2):157–166, 1994.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Chen Cai and Yusu Wang. A note on over-smoothing for graph neural networks. In *International Conference on Machine Learning Workshop (ICMLW)*, 2020.

Kyunghyun Cho. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

Kyunghyun Cho, Bart Van Merriënboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-decoder approaches. *arXiv preprint arXiv:1409.1259*, 2014.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint arXiv:1901.02860*, 2019.

Tri Dao and Albert Gu. Transformers are ssms: Generalized models and efficient algorithms through structured state space duality. *arXiv preprint arXiv:2405.21060*, 2024.

Soham De, Samuel L Smith, Anushan Fernando, Aleksandar Botev, George Cristian-Muraru, Albert Gu, Ruba Haroun, Leonard Berrada, Yutian Chen, Srivatsan Srinivasan, et al. Griffin: Mixing gated linear recurrences with local attention for efficient language models. *arXiv preprint arXiv:2402.19427*, 2024.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL*, 2019.

Francesco Di Giovanni, Lorenzo Giusti, Federico Barbero, Giulia Luise, Pietro Lio, and Michael M Bronstein. On over-squashing in message passing neural networks: The impact of width, depth, and topology. In *International Conference on Machine Learning*, pp. 7865–7885. PMLR, 2023.

Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: Pure attention loses rank doubly exponentially with depth. In *International Conference on Machine Learning (ICML)*, 2021.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Daniel Y Fu, Tri Dao, Khaled K Saab, Armin W Thomas, Atri Rudra, and Christopher Ré. Hungry hungry hippos: Towards language modeling with state space models. *arXiv preprint arXiv:2212.14052*, 2022.

Borjan Geshkovski, Cyril Letrouit, Yury Polyanskiy, and Philippe Rigollet. A mathematical perspective on transformers. *arXiv preprint arXiv:2312.10794*, 2023.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pp. 1263–1272. PMLR, 2017.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. *arXiv preprint arXiv:2312.00752*, 2023.

Albert Gu, Tri Dao, Stefano Ermon, Atri Rudra, and Christopher Ré. Hippo: Recurrent memory with optimal polynomial projections. *Advances in neural information processing systems*, 33: 1474–1487, 2020.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. *arXiv preprint arXiv:2111.00396*, 2021a.

Albert Gu, Isys Johnson, Karan Goel, Khaled Saab, Tri Dao, Atri Rudra, and Christopher Ré. Combining recurrent, convolutional, and continuous-time models with linear state space layers. *Advances in neural information processing systems*, 34:572–585, 2021b.

Albert Gu, Karan Goel, Ankit Gupta, and Christopher Ré. On the parameterization and initialization of diagonal state space models. *Advances in Neural Information Processing Systems*, 35:35971–35983, 2022a.

Albert Gu, Isys Johnson, Aman Timalsina, Atri Rudra, and Christopher Ré. How to train your hippo: State space models with generalized orthogonal basis projections. *arXiv preprint arXiv:2206.12037*, 2022b.

Ankit Gupta, Albert Gu, and Jonathan Berant. Diagonal state spaces are as effective as structured state spaces. *Advances in Neural Information Processing Systems*, 35:22982–22994, 2022.

Michael Hahn. Theoretical limitations of self-attention in neural sequence models. *Transactions of the Association for Computational Linguistics*, 8:156–171, 2020.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*, 2022.

Samy Jelassi, David Brandfonbrener, Sham M Kakade, and Eran Malach. Repeat after me: Transformers are better than state space models at copying. *arXiv preprint arXiv:2402.01032*, 2024.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention. In *International conference on machine learning*, pp. 5156–5165. PMLR, 2020.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Jeffrey Li, Alex Fang, Georgios Smyrnis, Maor Ivgi, Matt Jordan, Samir Gadre, Hritik Bansal, Etash Guha, Sedrick Keh, Kushal Arora, et al. Datacomp-lm: In search of the next generation of training sets for language models. *arXiv preprint arXiv:2406.11794*, 2024.

Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

Yuhong Li, Tianle Cai, Yi Zhang, Deming Chen, and Debadeepta Dey. What makes convolutional models great on long sequence modeling? *arXiv preprint arXiv:2210.09298*, 2022.

Opher Lieber, Barak Lenz, Hofit Bata, Gal Cohen, Jhonathan Osin, Itay Dalmedigos, Erez Safahi, Shaked Meirom, Yonatan Belinkov, Shai Shalev-Shwartz, et al. Jamba: A hybrid transformer-mamba language model. *arXiv preprint arXiv:2403.19887*, 2024.

Bo Liu, Rui Wang, Lemeng Wu, Yihao Feng, Peter Stone, and Qiang Liu. Longhorn: State space models are amortized online learners. *arXiv preprint arXiv:2407.14207*, 2024a.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024b.

Xuezhe Ma, Chunting Zhou, Xiang Kong, Junxian He, Liangke Gui, Graham Neubig, Jonathan May, and Luke Zettlemoyer. Mega: moving average equipped gated attention. *arXiv preprint arXiv:2209.10655*, 2022.

Xuezhe Ma, Xiaomeng Yang, Wenhan Xiong, Beidi Chen, Lili Yu, Hao Zhang, Jonathan May, Luke Zettlemoyer, Omer Levy, and Chunting Zhou. Megalodon: Efficient llm pretraining and inference with unlimited context length. *arXiv preprint arXiv:2404.08801*, 2024.

William Merrill, Jackson Petty, and Ashish Sabharwal. The illusion of state in state-space models. *arXiv preprint arXiv:2404.08819*, 2024.

Hoang NT and Takanori Maehara. Revisiting graph neural networks: All we have is low-pass filters. In *International Conference on Pattern Recognition (ICPR)*, 2021.

Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, et al. In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*, 2022.

Kenta Oono and Taiji Suzuki. Graph neural networks exponentially lose expressive power for node classification. In *International Conference on Learning Representations (ICLR)*, 2019.

Jongho Park, Jaeseung Park, Zheyang Xiong, Nayoung Lee, Jaewoong Cho, Samet Oymak, Kangwook Lee, and Dimitris Papailiopoulos. Can mamba learn how to learn? a comparative study on in-context learning tasks. *arXiv preprint arXiv:2402.04248*, 2024.

Bo Peng, Eric Alcaide, Quentin Anthony, Alon Albalak, Samuel Arcadinho, Huanqi Cao, Xin Cheng, Michael Chung, Matteo Grella, Kranthi Kiran GV, et al. Rwkv: Reinventing rnns for the transformer era. *arXiv preprint arXiv:2305.13048*, 2023.

Bo Peng, Daniel Goldstein, Quentin Anthony, Alon Albalak, Eric Alcaide, Stella Biderman, Eugene Cheah, Teddy Ferdinan, Haowen Hou, Przemysław Kazienko, et al. Eagle and finch: Rwkv with matrix-valued states and dynamic recurrence. *arXiv preprint arXiv:2404.05892*, 2024.

Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models. *arXiv preprint arXiv:2211.09527*, 2022.

Michael Poli, Armin W Thomas, Eric Nguyen, Pragaash Ponnusamy, Björn Deiseroth, Kristian Kersting, Taiji Suzuki, Brian Hie, Stefano Ermon, Christopher Ré, et al. Mechanistic design and scaling of hybrid architectures. *arXiv preprint arXiv:2403.17844*, 2024.

Ofir Press, Noah A Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length extrapolation. *arXiv preprint arXiv:2108.12409*, 2021.

Zhen Qin, Songlin Yang, Weixuan Sun, Xuyang Shen, Dong Li, Weigao Sun, and Yiran Zhong. Hgrn2: Gated linear rnns with state expansion. *arXiv preprint arXiv:2404.07904*, 2024.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training. 2018.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

Han Shi, Jiahui Gao, Hang Xu, Xiaodan Liang, Zhenguo Li, Lingpeng Kong, Stephen Lee, and James T Kwok. Revisiting over-smoothing in bert from the perspective of graph. *arXiv preprint arXiv:2202.08625*, 2022.

Yutao Sun, Li Dong, Barun Patra, Shuming Ma, Shaohan Huang, Alon Benhaim, Vishrav Chaudhary, Xia Song, and Furu Wei. A length-extrapolatable transformer. *arXiv preprint arXiv:2212.10554*, 2022.

Yutao Sun, Li Dong, Shaohan Huang, Shuming Ma, Yuqing Xia, Jilong Xue, Jianyong Wang, and Furu Wei. Retentive network: A successor to transformer for large language models. *arXiv preprint arXiv:2307.08621*, 2023.

Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. *Advances in neural information processing systems*, 27, 2014.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena: A benchmark for efficient transformers. *arXiv preprint arXiv:2011.04006*, 2020.

Jake Topping, Francesco Di Giovanni, Benjamin Paul Chamberlain, Xiaowen Dong, and Michael M Bronstein. Understanding over-squashing and bottlenecks on graphs via curvature. *arXiv preprint arXiv:2111.14522*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is All You Need. In *Proceedings of NeurIPS*, 2017.

Aaron Voelker, Ivana Kajić, and Chris Eliasmith. Legendre memory units: Continuous-time representation in recurrent neural networks. *Advances in neural information processing systems*, 32, 2019.

Roger Waleffe, Wonmin Byeon, Duncan Riach, Brandon Norick, Vijay Korthikanti, Tri Dao, Albert Gu, Ali Hatamizadeh, Sudhakar Singh, Deepak Narayanan, et al. An empirical study of mamba-based language models. *arXiv preprint arXiv:2406.07887*, 2024.

Peihao Wang, Wenqing Zheng, Tianlong Chen, and Zhangyang Wang. Anti-oversmoothing in deep vision transformers via the fourier domain analysis: From theory to practice. *arXiv preprint arXiv:2203.05962*, 2022.

Shida Wang and Beichen Xue. State-space models with layer-wise nonlinearity are universal approximators with exponential decaying memory. *Advances in Neural Information Processing Systems*, 36, 2024.

Xinyi Wu, Zhengdao Chen, William Wang, and Ali Jadbabaie. A non-asymptotic analysis of oversmoothing in graph neural networks. *arXiv preprint arXiv:2212.10701*, 2022.

Xinyi Wu, Amir Ajorlou, Yifei Wang, Stefanie Jegelka, and Ali Jadbabaie. On the role of attention masks and layernorm in transformers. *arXiv preprint arXiv:2405.18781*, 2024a.

Xinyi Wu, Amir Ajorlou, Zihui Wu, and Ali Jadbabaie. Demystifying oversmoothing in attention-based graph neural networks. *Advances in Neural Information Processing Systems*, 36, 2024b.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.

Songlin Yang, Bailin Wang, Yikang Shen, Rameswar Panda, and Yoon Kim. Gated linear attention transformers with hardware-efficient training. *arXiv preprint arXiv:2312.06635*, 2023.

Songlin Yang, Bailin Wang, Yu Zhang, Yikang Shen, and Yoon Kim. Parallelizing linear transformers with the delta rule over sequence length. *arXiv preprint arXiv:2406.06484*, 2024.

Tao Zhang, Xiangtai Li, Haobo Yuan, Shunping Ji, and Shuicheng Yan. Point could mamba: Point cloud learning via state space model. *arXiv preprint arXiv:2403.00762*, 2024.

Lianghui Zhu, Bencheng Liao, Qian Zhang, Xinlong Wang, Wenyu Liu, and Xinggang Wang. Vision mamba: Efficient visual representation learning with bidirectional state space model. *arXiv preprint arXiv:2401.09417*, 2024.

Andy Zou, Zifan Wang, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A UNIFIED FORMULATION OF SSMs

Gated Linear Attention. We present GLA (Yang et al., 2023) below, which generalizes several extant LAMs:

$$\text{(GLA)} \quad \boldsymbol{A}_t = \text{diag}(\boldsymbol{\alpha}(\boldsymbol{x}_t)), \quad \boldsymbol{b}_t(\boldsymbol{x}_t) = \boldsymbol{k}(\boldsymbol{x}_t), \quad c_t(\boldsymbol{h}_t) = \boldsymbol{q}(\boldsymbol{x}_t)^\top \boldsymbol{h}_t, \quad \Delta_t = v(\boldsymbol{x}_t), \quad (5)$$

where $\boldsymbol{\alpha} : \mathbb{R} \to (0,1)^N$ converts input to gating logits, $\boldsymbol{k}, \boldsymbol{q} : \mathbb{R} \to \mathbb{R}^N$, $v : \mathbb{R} \to \mathbb{R}$ are linear mappings playing roles similar to key, query, value matrices in transformers (Vaswani et al., 2017). When the inputs are multi-dimensional, we share $\boldsymbol{\alpha}$ across channels while assigning each channel with a separate $\boldsymbol{k}, \boldsymbol{q}, v$ and extending their input dimension accordingly. Linear Attention (LA) (Katharopoulos et al., 2020) can be regarded as GLA with constant $\boldsymbol{A}_t$, while RetNet (Sun et al., 2023) can be formulated as GLA with input-independent $\boldsymbol{A}_t$ (Liu et al., 2024a).

Griffin. The recurrent unit in Griffin (De et al., 2024) can be re-formulated as a kind of SSMs:

$$\boldsymbol{A}_t = \text{diag}\left(\boldsymbol{\alpha}(\boldsymbol{x}_t)\right), \ \ \boldsymbol{b}_t(\boldsymbol{x}_t) = \text{diag}\left(\boldsymbol{i}(\boldsymbol{x}_t)\right), \ \ c_t(\boldsymbol{h}_t) = \boldsymbol{h}_t, \ \ \Delta_t = \text{diag}\left(\sqrt{1 - \boldsymbol{\alpha}(\boldsymbol{x}_t)^2}\right), \quad (6)$$

where $\boldsymbol{i}(\boldsymbol{x}_t) = \text{sigmoid}(\boldsymbol{W}_x \boldsymbol{x}_t + \boldsymbol{b}_x)$ is an input gate, $\boldsymbol{\alpha}$ is computed in log-space: $\log \boldsymbol{\alpha}(\boldsymbol{x}_t) = -\xi \, \text{softplus}(\boldsymbol{\Gamma}) \odot \text{sigmoid}(\boldsymbol{W}_a \boldsymbol{x}_t + \boldsymbol{b}_a)$, $\odot$ is Hadamard product, ξ is a constant, and $\boldsymbol{\Gamma}$, $\boldsymbol{W}_a$, $\boldsymbol{b}_a$, $\boldsymbol{W}_x$, $\boldsymbol{b}_x$ are learnable parameters. In particular, the dimension of $\boldsymbol{h}_t$ in Griffin is equal to the dimension of $\boldsymbol{x}_t$. If we consider single-channel $\boldsymbol{x}_t$, then $\boldsymbol{A}_t$, $\boldsymbol{b}_t$, and Δ_t are all scalar-valued.

RetNet. The SSM formulation of RetNet (Sun et al., 2023) is similar to that of GLA, with the distinction of $\boldsymbol{A}_t$.

$$\boldsymbol{A}_t = \gamma \boldsymbol{I}, \quad \boldsymbol{b}_t(\boldsymbol{x}_t) = \boldsymbol{k}(\boldsymbol{x}_t), \quad c_t(\boldsymbol{h}_t) = \boldsymbol{q}(\boldsymbol{x}_t)^\top \boldsymbol{h}_t, \quad \Delta_t = v(\boldsymbol{x}_t), \quad (7)$$

where $\gamma \in [0, 1]$ is a scalar, and the other symbols retain the same meaning as in GLA.

RWKV. We demonstrate that RWKV (Peng et al., 2023) can also be reformulated into the structure of SSMs:

$$\boldsymbol{A}_t = \frac{\exp(-w_t)\boldsymbol{I}}{\exp(-w_t) + \exp(k(\boldsymbol{x}_t))}, \quad \boldsymbol{b}_t(\boldsymbol{x}_t) = \boldsymbol{v}(\boldsymbol{x}_t), \quad (8)$$

$$c_t(\boldsymbol{h}_t) = \boldsymbol{q}(\boldsymbol{x}_t)^\top \boldsymbol{h}_t, \quad \Delta_t = \frac{\exp(k(\boldsymbol{x}_t))}{\exp(-w_t) + \exp(k(\boldsymbol{x}_t))}. \quad (9)$$

Another view suggests RWKV can be seen as a state of ratio form of two SSMs: $\boldsymbol{h}_t = \frac{\boldsymbol{a}_t}{\boldsymbol{b}_t} = (\exp(-w)\boldsymbol{a}_{t-1} + \exp(k(\boldsymbol{x}_t))v(\boldsymbol{x}_t)) / (\exp(-w)\boldsymbol{b}_{t-1} + \exp(k(\boldsymbol{x}_t)))$.

B DEFERRED DISCUSSIONS

Revisiting HiPPO theory. HiPPO established in (Gu et al., 2020), extended by Gu et al. (2021b; 2022b) is the theoretical foundation of SSMs. Consider a signal x and its reconstruction $y^{(t)}$ up to time t. To optimally memorizes the history of x using $y^{(t)}$, HiPPO minimizes $\|x_{\leq t} - y^{(t)}\|_{L_2(\omega^{(t)})}$ w.r.t. a measure $\omega^{(t)}$ supported on $(-\infty, t]$. The solution is to project the history of x before time t onto N basis functions (e.g. Legendre polynomials), which yields a time-continuous coefficient vector $\boldsymbol{h}(t)$, and $y^{(t)}$ can be synthesized by linearly combining the N basis using $\boldsymbol{h}(t)$. Gu et al. (2020) shows that the evolution of $\boldsymbol{h}(t)$ follows an ODE $\boldsymbol{h}'(t) = \boldsymbol{A}(t)\boldsymbol{h}(t) + \boldsymbol{b}(t)x(t)$. In particular, Gu et al. (2020) chooses a uniform measure over the past history $\omega^{(t)} = \mathbb{I}[0, t]/t$, which places no approximation bias over the time horizon in contrast to an earlier work (Voelker et al., 2019). As a result, $\boldsymbol{A}(t)$ in Eq. 1 can be written in a closed form: $\boldsymbol{A}(t) = -\boldsymbol{A}_{hippo}/t$, where $\boldsymbol{A}_{hippo}$ is a time-independent constant called the HiPPO matrix. Its various forms have been used as initialization in subsequent works including S4 (Gu et al., 2021a) and Mamba (Gu & Dao, 2023). While HiPPO theory seems to guarantee the long-rangeness for SSMs, the actual form of $\boldsymbol{A}(t)$ employed in S4 and Mamba drops the normalizer $1/t$. Gu et al. (2022b) shows that this change causes a warp of measure from uniform to $\omega^{(t)}(s) \propto \exp(s - t)\mathbb{I}(\infty, t]$. We note that this warped measure assigns more importance to recent history, and thus, our Theorem 3.1 does not contradict HiPPO theory but also

matches the findings in Gu et al. (2022b). We also point out that when adopting the diagonalized form of A_{hippo} (Gu et al., 2021a; Gupta et al., 2022; Gu et al., 2022a), the unitary matrices decomposed from A_{hippo} is sometimes not applied to b_t and c_t, which introduces a disconnect between HiPPO theory and its practical implementation. Our paper directly studies the discrete-domain SSMs and aligns with the parameterization used in practice. Another less-discussed property of SSMs is their approximation power for a broad family of operators. In Gu et al. (2021b), SSMs are shown to possess expressiveness that encompasses both convolutions and RNNs. It is worth noting that the original HiPPO-based SSM is not necessarily a low-pass filter. Rather, it is the successive simplifications in the parameterization of A_t that impart the smoothing characteristics of SSMs (see Proposition 4.1).

Does hungry hungry hippos help? The key innovation of Hungry Hungry Hippos (H3) (Fu et al., 2022) lies in the introduction of self-gating connections and locally shifting convolutions to improve in-context recall for state space models (SSMs). This design has quickly become a standard backbone for various SSMs (Gu & Dao, 2023; Beck et al., 2024). However, we question its effectiveness in addressing the local rangeness issue in SSMs. The gating mechanism operates at the token level, which impacts the bound in Theorem 3.1 only by a constant factor. Additionally, the introduced convolutions typically use small kernels, which are insufficient to mitigate the exponentially decaying relevance between tokens. As we empirically show in Fig. 2, while Mamba with H3 performs adequately in associative recall tasks when the state size is sufficiently large, a locality bias begins to emerge as the number of key-value pairs exceeds the model's memory capacity. This highlights the limitations of the architecture in handling long-range dependencies under constrained memory.

Does gradient vanish in SSMs? Vanishing gradients refer to a challenge in RNNs, where backpropagation-based learning is impeded due to gradient magnitudes decaying exponentially over time. The diminishing dependencies among distant tokens are a fundamental cause of this issue (Bengio et al., 1994). SSMs were initially proposed to address this limitation by explicitly modeling long-range dependencies, as highlighted in (Gu et al., 2020; 2021b). Subsequent work, such as Mamba, extends this approach by adopting their initialization alongside newly proposed selection mechanisms, which are widely believed to enhance these capabilities. Our Theorem 3.1 lies in theoretically challenging this assumption. We demonstrate that modern SSMs still suffer from the recency bias, which not only undermines their ability to capture long-term dependencies but also potentially exacerbates the vanishing gradient problem.

Connection with over-squashing theory in GNNs. The influential score defined in Sec. 3.1 is also used for *over-squashing* analysis in Graph Neural Networks (GNNs) to identify information bottleneck (Topping et al., 2021; Di Giovanni et al., 2023). The sensitivity analysis in Topping et al. (2021) demonstrates similar exponentially decaying dependencies among graph nodes, dependent on the underlying graph topology. We postulate that propagating information from long distances remains challenging for SSMs because the model needs to encapsulate all history information into a fixed-dimension hidden vector, which is also observed as one major problem with RNNs (Bengio et al., 1994; Alon & Yahav, 2020; Sutskever et al., 2014; Cho et al., 2014; Cho, 2014).

Connection with over-smoothing theory in GNNs and transformers. Over-smoothing issues were first identified in GNNs (Li et al., 2018; NT & Maehara, 2021; Oono & Suzuki, 2019; Cai & Wang, 2020; Wu et al., 2022; 2024b) and later explored in transformers (Dong et al., 2021; Wang et al., 2022; Shi et al., 2022; Wu et al., 2024a; Geshkovski et al., 2023). In both cases, over-smoothing manifests as feature representations becoming increasingly uniform with greater model depth. To the best of our knowledge, our work is the first to uncover this phenomenon in SSMs. In GNNs, the over-smoothing effect typically follows a linear decay rate governed by the second-largest eigenvalue of the adjacency matrix: $O(\lambda_2^L)$, where L denotes the number of layers (Oono & Suzuki, 2019; Cai & Wang, 2020). More closely related to our setting, Wu et al. (2024a) analyzes the convergence rate of feature smoothness in causal attention, demonstrating a rate of $O((1 - \hat{A}_{min}^T)^{L/T})$, where $\hat{A}_{min}$ is the minimal value in attention maps. In comparison, our result in Theorem 4.2 shows a rate of $O((1 - A_{min}^T)^L)$, indicating that the smoothening speed of SSMs is faster than that of transformers. Our Fig. 5 supports this claim, as the transformer-based architecture exhibits a mild decrease of sharpness at deeper layers, whereas SSMs show a constantly steeper decay slope. Moreover, due to the inherent locality of SSMs (Theorem 3.1), achieving effective long-range interactions necessitates deeper architectures. In contrast, transformers, which allow

arbitrary long-range interactions among tokens, do not have the same requirement. This distinction is partially supported by the observation that modern SSMs often adopt architectures that are roughly twice as deep as transformers. Consequently, depth-scaling limitations are more critical for SSMs than for transformers.

Comparison with Wang & Xue (2024). The most relevant prior work to our study in SSM recency is perhaps Wang & Xue (2024), in which their Theorem 3.13 reveals the exponentially decaying memory for SSMs. Distinct from their findings, our primary contribution lies in analyzing nonlinearity and input-dependent mechanisms widely adopted in modern SSMs (Gu & Dao, 2023; Yang et al., 2023; Arora et al., 2023). To the best of our knowledge, our work presents the first counterargument showing that even with input-dependent SSMs, effective context filtering may not be achieved. Instead, these mechanisms impose a strict recency bias, inheriting the limitations of linear SSMs as previously highlighted by Wang & Xue (2024). Notably, Wang & Xue (2024) only addresses nonlinear activations after performing linear SSMs (*i.e.*, S4), with the state transition matrix $\boldsymbol{A}_t$ being independent of inputs. Our analysis, however, considers both $\boldsymbol{A}_t$ and $\boldsymbol{b}_t$ as input-dependent, aligning with settings in Mamba and other follow-up works. The approach in Wang & Xue (2024) does not naturally extend to this case, as they assume the linearity of the sequence mixer (cf. Eq. 9 in Wang & Xue (2024)). Furthermore, we conduct a finer-grained analysis, quantitatively relating the decay rate to the specific values within the input-dependent gating matrix $\boldsymbol{A}_t$.

C PROOFS

C.1 EXPONENTIALLY DECAYING DEPENDENCY WITH RELATIVE DISTANCE

In this section, we extend and prove Theorem 3.1 in a more general case where inputs and parameters are all complex-valued. Below we by default assume that $\boldsymbol{A}_t \in \mathbb{C}^{N \times N}$, $\boldsymbol{b}_t : \mathbb{C} \to \mathbb{C}^N$, $c_t : \mathbb{C}^N \to \mathbb{C}$, and $\Delta_t \in \mathbb{R}$. First of all, we present the following auxiliary lemma, reformulating SSM recurrence in an explicit parallel form.

Lemma C.1 (Parallel form). *For any $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$ and $\boldsymbol{x} \in \mathbb{C}^T$, $\boldsymbol{y} \in \mathbb{C}^T$ computed via an SSM defined in Eq. 1 is equal to:*

$$\boldsymbol{h}_t = \sum_{s=1}^{t-1} \left(\prod_{r=s+1}^{t} \boldsymbol{A}_r \right) \Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s) + \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t), \quad \boldsymbol{y}_t = c_t(\boldsymbol{h}_t), \quad \forall t \in [T]. \tag{10}$$

Proof. Proof by induction. First let us examine the base case when $t = 1$: $\boldsymbol{h}_1 = \Delta_1 \boldsymbol{b}_1(\boldsymbol{x}_1)$, indicating that Eq. 10 holds trivially. Now we make inductive hypothesis that Eq. 10 holds for some $t \in [T-1]$. Then for time step $t + 1 \in [T]$:

$$\begin{aligned}
\boldsymbol{h}_{t+1} &= \boldsymbol{A}_{t+1} \boldsymbol{h} + \Delta_{t+1} \boldsymbol{b}_{t+1}(\boldsymbol{x}_{t+1}) \\
&= \boldsymbol{A}_{t+1} \left(\sum_{s=1}^{t-1} \left(\prod_{r=s+1}^{t} \boldsymbol{A}_r \right) \Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s) + \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t) \right) + \Delta_{t+1} \boldsymbol{b}_{t+1}(\boldsymbol{x}_{t+1}) \\
&= \sum_{s=1}^{t-1} \left(\boldsymbol{A}_{t+1} \cdot \prod_{r=s+1}^{t} \boldsymbol{A}_r \right) \Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s) + \boldsymbol{A}_{t+1} \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t) + \Delta_{t+1} \boldsymbol{b}_{t+1}(\boldsymbol{x}_{t+1}) \\
&= \sum_{s=1}^{t-1} \left(\prod_{r=s+1}^{t+1} \boldsymbol{A}_r \right) \Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s) + \left(\prod_{r=t+1}^{t+1} \boldsymbol{A}_r \right) \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t) + \Delta_{t+1} \boldsymbol{b}_{t+1}(\boldsymbol{x}_{t+1}) \\
&= \sum_{s=1}^{t} \left(\prod_{r=s+1}^{t+1} \boldsymbol{A}_r \right) \Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s) + \Delta_{t+1} \boldsymbol{b}_{t+1}(\boldsymbol{x}_{t+1}),
\end{aligned}$$

which also satisfies Eq. 10. Then we conclude the proof by induction. $\square$

A remark of Lemma C.1. Lemma C.1 provides an alternative perspective on how SSMs compute the outputs. The predicted value for the t-th token is obtained via decoding a weighted aggregation over representations of all past tokens. The encoding and decoding stage is element-wise independent

of the context. Whereas, the "weight" associated with each past token in the summation reflects the pairwise relationship, playing a similar role to attention weights in transformers (Dao & Gu, 2024; Ali et al., 2024). The weight corresponding to one past token is calculated as the cumulative product $\prod_r \boldsymbol{A}_r$, where $r \in [s+1, t]$ traverses from the past token (at time s) to the target token (at time t). Assume $\boldsymbol{A}_t \in (0,1)^{N \times N}$, which is satisfied by most of SSMs discussed in Sec. 2, we can show that $(\prod_{r=s+1}^{t} \boldsymbol{A}_r)_{n,n} < (\prod_{r=s'+1}^{s} \boldsymbol{A}_r)_{n,n}$ for any $s < s' < t$ and $n \in [N]$. By this interpretation, SSMs assign strictly higher "attention" to the nearer tokens than the further tokens.

Below we formally state and prove the complex version of Theorem 3.1. Theorem 3.1 is a straightforward corollary of Theorem C.2.

Theorem C.2 (Recency of SSMs). *Consider an SSM defined in Eq. 1 with $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$. Assume that:*

   (i) The input space $\mathcal{X} \subset \mathbb{C}^T$ is compact.

   (ii) $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$ and $\left\{ \left(\frac{\partial \boldsymbol{A}_t}{\partial \boldsymbol{x}_t}, \frac{\partial \boldsymbol{b}_t}{\partial \boldsymbol{x}_t}, \frac{\partial c_t}{\partial \boldsymbol{x}_t}, \frac{\partial \Delta_t}{\partial \boldsymbol{x}_t} \right) \right\}_{t \in [T]}$ are continuous.

   (iii) $\boldsymbol{A}_t$ is diagonal and $0 < |(\boldsymbol{A}_t)_{n,n}| < 1$ for all $t \in [T], n \in [N]$.

Let $A_{max} = \max_{t \in [T], n \in [N]} |(\boldsymbol{A}_t)_{n,n}|$. Then for arbitrary $\boldsymbol{x} \in \mathcal{X}$ and every $s, t \in [T]$ such that $s < t$,

$$\left| \frac{\partial \boldsymbol{y}_t}{\partial \boldsymbol{x}_s} \right| \leq C \exp \left(-\kappa(t - s) \right),$$

for some constant $C > 0$ independent of t and s, and $\kappa = \log(A_{max}^{-1})$.

Proof of Theorem 3.1. First of all, we note that by compactness of input space (Assumption (i)) and continuity (Assumption (ii)), $(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)$ and $\left(\frac{\partial \boldsymbol{A}_t}{\partial \boldsymbol{x}_t}, \frac{\partial \boldsymbol{b}_t}{\partial \boldsymbol{x}_t}, \frac{\partial c_t}{\partial \boldsymbol{x}_t}, \frac{\partial \Delta_t}{\partial \boldsymbol{x}_t} \right)$ are all bounded by some constant for every $t \in [T]$.

By Lemma C.1, Eq. 1 can be expressed in the closed form as follows:

$$
\begin{aligned}
\boldsymbol{h}_t &= \sum_{i=1}^{t-1} \left(\prod_{r=i+1}^{t} \boldsymbol{A}_r \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i) + \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t) \\
&= \sum_{i=1}^{t-1} \exp \left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i) + \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t) \\
&= \underbrace{\sum_{i=1}^{s-1} \exp \left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i)}_{\boldsymbol{u}_t} + \underbrace{\sum_{i=s}^{t-1} \exp \left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i)}_{\boldsymbol{v}_t} + \Delta_t \boldsymbol{b}_t(\boldsymbol{x}_t),
\end{aligned}
$$

where the second equality is by simply rewriting the cumulative product as an exponential of cumulative summation of logarithms. The logarithmic terms are well defined and constantly negative due to Assumption (iii). We decompose $\boldsymbol{h}_t$ into three components, where the first term, denoted as $\boldsymbol{u}_t$, depends on $\boldsymbol{x}_s$ only through $\{\boldsymbol{A}_r\}_{r=s}^{t}$, the second term, denoted as $\boldsymbol{v}_t$, only relies on $\boldsymbol{x}_s$ via $\{\Delta_i \boldsymbol{b}_i\}_{i=s}^{t}$, while the remaining part is independent of $\boldsymbol{x}_s$.

Now we tackle each component separately. First, we simplify $\partial \boldsymbol{u}_t / \partial \boldsymbol{x}_s$ as:

$$\frac{\partial \boldsymbol{u}_t}{\partial \boldsymbol{x}_s} = \frac{\partial}{\partial \boldsymbol{x}_s} \left[\sum_{i=1}^{s-1} \exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i) \right]$$

$$= \sum_{i=1}^{s-1} \frac{\partial}{\partial \boldsymbol{x}_s} \left(\exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i)$$

$$= \sum_{i=1}^{s-1} \exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \left(\sum_{r=i+1}^{t} \frac{\partial \log \boldsymbol{A}_r}{\partial \boldsymbol{x}_s} \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i)$$

$$= \sum_{i=1}^{s-1} \exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \left(\boldsymbol{A}_s^{-1} \frac{\partial \boldsymbol{A}_s}{\partial \boldsymbol{x}_s} \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i),$$

where the last steps follow from the basic chain rule. Then we can bound its ℓ_1 norm by:

$$\left\| \frac{\partial \boldsymbol{u}_t}{\partial \boldsymbol{x}_s} \right\|_1 \leq \sum_{n=1}^{N} \sum_{i=1}^{s-1} \left| \exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right)_{n,n} \right| \cdot \left| \left(\frac{1}{\boldsymbol{A}_r} \frac{\partial \boldsymbol{A}_r}{\partial \boldsymbol{x}_s} \right)_{n,n} \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i)_n \right| \tag{11}$$

$$\leq C_1 \sum_{n=1}^{N} \sum_{i=1}^{s-1} \exp\left(\sum_{r=i+1}^{t} \log |(\boldsymbol{A}_r)_{n,n}| \right) \tag{12}$$

$$\leq C_1 N \sum_{i=1}^{s-1} \exp\left(\log A_{max}(t-i) \right) \tag{13}$$

$$= C_1 N \frac{1 - \exp\left(-\log A_{max}(s-1) \right)}{1 - A_{max}^{-1}} \exp\left(\log A_{max}(t-1) \right) \tag{14}$$

$$= C_1 N \frac{\exp\left(\log A_{max}(t-s) \right) - \exp\left(\log A_{max}(t-1) \right)}{A_{max}^{-1} - 1}$$

$$\leq \frac{C_1 N}{A_{max}^{-1} - 1} \exp\left(-\log A_{max}^{-1}(t-s) \right). \tag{15}$$

We elaborate on the derivation step by step. Eq. 11 is due to triangular inequality. To obtain Eq. 12, we note that $\boldsymbol{A}_r^{-1}, \partial \boldsymbol{A}_r / \partial \boldsymbol{x}_s, \Delta_i, \boldsymbol{b}_i$ are all element-wisely bounded, thus, we can extract their uniform upper bound $C_1 > 0$ out of the summation Eq. 13 can be derived by applying the supremum A_{max} over all $\{|(\boldsymbol{A}_t)_{n,n}|\}_{t \in [T], n \in [N]}$. Eq. 14 follows from the summation of geometric series. And finally, inequality in Eq. 15 holds by dropping a negative term.

Similarly, we rewrite $\partial \boldsymbol{v}_t / \partial \boldsymbol{x}_s$ as below:

$$\frac{\partial \boldsymbol{v}_t}{\partial \boldsymbol{x}_s} = \frac{\partial}{\partial \boldsymbol{x}_s} \left[\sum_{i=s}^{t-1} \exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i) \right]$$

$$= \sum_{i=s}^{t-1} \exp\left(\sum_{r=i+1}^{t} \log \boldsymbol{A}_r \right) \frac{\partial(\Delta_i \boldsymbol{b}_i(\boldsymbol{x}_i))}{\partial \boldsymbol{x}_s}$$

$$= \exp\left(\sum_{r=s+1}^{t} \log \boldsymbol{A}_r \right) \frac{\partial(\Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s))}{\partial \boldsymbol{x}_s},$$

by which we can yield the following upper bound on its ℓ_1 norm:

$$\left\| \frac{\partial \boldsymbol{v}_t}{\partial \boldsymbol{x}_s} \right\|_1 \leq \sum_{n=1}^{N} \left| \exp\left(\sum_{r=s+1}^{t} \log \boldsymbol{A}_r \right)_{n,n} \right| \cdot \left| \frac{\partial(\Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s)_n)}{\partial \boldsymbol{x}_s} \right|$$

$$\leq C_2 \sum_{n=1}^{N} \exp\left(\sum_{r=s+1}^{t} \log |(\boldsymbol{A}_r)_{n,n}| \right) \tag{16}$$

$$\leq N C_2 \exp\left(-\log A_{max}^{-1}(t-s) \right), \tag{17}$$

where Eq. 16 is obtained by applying uniform upper bound $C_2 > 0$ over $|\partial(\Delta_s \boldsymbol{b}_s(\boldsymbol{x}_s)_n)/\partial \boldsymbol{x}_s|$. Eq. 17 is induced by leveraging the supremum A_{max} over all $\{|(\boldsymbol{A}_t)_{n,n}|\}_{t \in [T], n \in [N]}$.

Combining Eqs. 15 and 17, we have:

$$\left\| \frac{\partial \boldsymbol{h}_t}{\partial \boldsymbol{x}_s} \right\|_1 \leq \left(\frac{C_1 N}{A_{max}^{-1} - 1} + N C_2 \right) \exp\left(-\log A_{max}^{-1}(t - s) \right). \tag{18}$$

Finally, we conclude the proof based on Eq. 18:

$$\left| \frac{\partial \boldsymbol{y}_t}{\partial \boldsymbol{x}_s} \right| = \left| \frac{\partial c_t(\boldsymbol{h}_t)}{\partial \boldsymbol{h}_t}^\top \frac{\partial \boldsymbol{h}_t}{\partial \boldsymbol{x}_s} \right| \leq \left\| \frac{\partial c_t(\boldsymbol{h}_t)}{\partial \boldsymbol{h}_t} \right\|_\infty \left\| \frac{\partial \boldsymbol{h}_t}{\partial \boldsymbol{x}_s} \right\|_1$$

$$\leq C_3 \left(\frac{C_1 N}{A_{max}^{-1} - 1} + N C_2 \right) \exp\left(-\log A_{max}^{-1}(t - s) \right),$$

$$= C \exp\left(-\kappa(t - s) \right)$$

where we use Hölder inequality in the first equation and upper bound $\|\partial c_t(\boldsymbol{h}_t)/\partial \boldsymbol{h}_t\|_\infty$ again via constant $C_3 > 0$ due to continuity ($c_t(\boldsymbol{h}_t)$ is a composition of a series of continuous functions as in Assumption (ii)). This is as desired after letting $C > 0$ absorb all constants and $\kappa = \log A_{max}^{-1}$. $\quad\square$

C.2 OVER-SMOOTHING IN SSMs

C.2.1 LOW-PASS FILTERING PROPERTIES

In this section, we formally state and prove Proposition 4.1. To begin with, we define low-pass filters as below:

Definition C.3 (Low-pass Filter). *Suppose $z(t) : \mathbb{C} \to \mathbb{C}$ is absolutely integrable. Then the Fourier transform $Z(\omega) : \mathbb{C} \to \mathbb{C}$ exists and $Z(\omega) \triangleq \int z(t) \exp(-i\omega t) dt$. We say $z(t)$ is an (ϵ, Ω)-low-pass filter for some $0 < \epsilon < 1$ and $\Omega > 0$ if $|Z(\omega)| \leq \epsilon$ for every $|\omega| \geq \Omega$. Furthermore, we say $z(t)$ is a low-pass filter if for every $0 < \epsilon < 1$, there exists $\Omega > 0$ such that $z(t)$ is an (ϵ, Ω)-low-pass filter.*

Note that our definition of low-pass filters focuses on its effect on removing high-frequency components. By Definition C.3, it is equivalent to say a system performs low-pass filtering if and only if the responses converge to zero as the frequency increases. Fixing $\epsilon > 0$ small enough, we can say a (ϵ, Ω)-low-pass filter has cut-off frequency at $|\omega| = \Omega$.

Now we present a formal version of Proposition 4.1 as below, which quantifies the cut-off frequency of a filter induced by continuous-time S4. Note that Proposition C.4 holds for complex-valued $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c})$. Below we assume $\boldsymbol{A} \in \mathbb{C}^{N \times N}$, $\boldsymbol{b} \in \mathbb{C}^N$, $\boldsymbol{c} \in \mathbb{C}^N$ by default.

Proposition C.4 (Formal version of Proposition 4.1). *Consider a continuous-time S4 with parameters $(\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c})$. Assume $\boldsymbol{A} \in \mathbb{C}^{N \times N}$ is diagonal and its diagonal values have negative real parts. Then $\boldsymbol{y}(t) = \int \boldsymbol{c}^\top \exp(\boldsymbol{A}(t - s)) \boldsymbol{b} x(s) ds$ is an $(\epsilon, O(1/\epsilon))$-low-pass filter for any $\epsilon > 0$ sufficiently small.*

Proof. First of all, let us rewrite the filter induced by S4 as below:

$$z(t) = \sum_{n=1}^N \boldsymbol{c}_n \boldsymbol{b}_n \exp(\boldsymbol{A}_{n,n} t).$$

Then we apply Fourier transform on $z(t)$:

$$Z(\omega) = \int z(t) e^{-i\omega t} dt = \int \sum_{n=1}^N \boldsymbol{c}_n \boldsymbol{b}_n \exp(\boldsymbol{A}_{n,n} t) \exp(-i\omega t) dt$$

$$= \sum_{n=1}^N \boldsymbol{c}_n \boldsymbol{b}_n \int \exp(\boldsymbol{A}_{n,n} t) \exp(-i\omega t) dt$$

$$= \sum_{n=1}^N \boldsymbol{c}_n \boldsymbol{b}_n \int \exp((\boldsymbol{A}_{n,n} - i\omega) t) dt$$

$$= \sum_{n=1}^N \frac{\boldsymbol{c}_n \boldsymbol{b}_n}{i\omega - \boldsymbol{A}_{n,n}},$$

where the last integral converges due to $\Re(\boldsymbol{A}_{n,n}) < 0$. Then we can upper bound the magnitude of $Z(\omega)$ as:

$$|Z(\omega)| = \left| \sum_{n=1}^{N} \frac{\boldsymbol{c}_n \boldsymbol{b}_n}{\mathrm{i}\omega - \boldsymbol{A}_{n,n}} \right| \leq \sum_{n=1}^{N} \left| \frac{\boldsymbol{c}_n \boldsymbol{b}_n}{\mathrm{i}\omega - \boldsymbol{A}_{n,n}} \right| \leq \sum_{n=1}^{N} \frac{|\boldsymbol{c}_n \boldsymbol{b}_n|}{||\omega| - |\boldsymbol{A}_{n,n}||}.$$

We consider $\epsilon > 0$ small enough, thus, it is sufficient to consider the scenario when $|\omega| > A_{max} \triangleq \max_{n \in [N]} |\boldsymbol{A}_{n,n}|$. In this regime, we have:

$$|Z(\omega)| \leq \left(\sum_{n=1}^{N} |\boldsymbol{c}_n \boldsymbol{b}_n| \right) \frac{1}{|\omega| - A_{max}} \leq \frac{\|\boldsymbol{b}\|_2 \|\boldsymbol{c}\|_2}{|\omega| - A_{max}},$$

where the last two inequalities are due to Hölder's inequality. It is sufficient to set:

$$\Omega = \frac{\|\boldsymbol{b}\|_2 \|\boldsymbol{c}\|_2}{\epsilon} + A_{max},$$

to let $|Z(\omega)| \leq \epsilon$ for every $|\omega| \geq \Omega$ hold. $\qquad\square$

C.2.2 GENERALIZED SMOOTHENING PROPERTIES

In this section, we define generalized smoothening operators as those that narrow distances between token features. We provide the following results that formalize this point. Theorem C.5 below extends the result of Theorem 4.2 to include the case when $(\boldsymbol{A}_t)_{n,n} + \Delta_t = 1$ for every $n \in [N], t \in [T]$, which is more aligned with Ma et al. (2022; 2024); Peng et al. (2023) in practice.

Theorem C.5 (Complete version of Theorem 4.2). *Consider an SSM specified in Eq. 1 with $\{(\boldsymbol{A}_t, \boldsymbol{b}_t, c_t, \Delta_t)\}_{t \in [T]}$. Assume an input space $\mathcal{X} \subset \mathbb{R}^T$ such that for every $\boldsymbol{x} \in \mathcal{X}$, either of the following conditions is satisfied:*

    (i) $(\boldsymbol{A}_t)_{n,n} + \Delta_t = 1$ for every $n \in [N]$ and $t \in [T]$, or

    (ii) $(\boldsymbol{A}_t)_{n,n} + \Delta_t \leq 1$ for every $n \in [N], t \in [T]$, and $\min_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)_n \leq 0$ and $\max_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)_n \geq 0$ for every $n \in [N]$.

Let $A_{min} = \min_{t \in [T], n \in [N]} (\boldsymbol{A}_t)_{n,n}$. Then for any $\boldsymbol{x} \in \mathcal{X}$ and the memory states $\{\boldsymbol{h}_t : t \in [T]\}$ generated by the SSM, we have:

$$\max_{t, s \in [T]} \|\boldsymbol{h}_t - \boldsymbol{h}_s\|_\infty \leq \left(1 - A_{min}^{T-1} \right) \max_{t, s \in [T]} \|\boldsymbol{b}_t(\boldsymbol{x}_t) - \boldsymbol{b}_s(\boldsymbol{x}_s)\|_\infty,$$

Proof. To simplify the proof, we first only consider the dynamics of one channel in the memory state. We denote $\alpha_t = (\boldsymbol{A}_t)_{n,n}$, $z_t = \boldsymbol{b}_t(\boldsymbol{x}_t)_n$, and $s_t = \boldsymbol{h}_{t,n}$ for some $n \in [N]$. Additionally, we define the following two quantities:

$$m = \min_{t \in [T]} z_t, \quad M = \max_{t \in [T]} z_t$$

When Assumption (ii) holds, we know that $m \leq 0$ and $M \geq 0$. Suppose $z_1 = pm + (1-p)M$ for some $p \in [0, 1]$. Furthermore, let $q = 1 - p$. Now we consider the following dynamics with $s_0 = 0$:

$$s_t = \alpha_t s_{t-1} + \Delta_t z_t, \quad t \in [T], \tag{19}$$

Next, we can show the result below (proved later):

Lemma C.6. *We have the following inequality for Eq. 19:*

$$(1 - A_{min}^{t-1} q)m + A_{min}^{t-1} qM \leq s_t \leq A_{min}^{t-1} pm + (1 - A_{min}^{t-1} p)M, \quad \forall t \in [T],$$

if either of the following conditions holds:

    (i) $\alpha_t + \Delta_t = 1$;

    (ii) $\alpha_t + \Delta_t < 1$ and $m \leq 0 \leq M$.

Note that the two conditions in Lemma C.6 corresponds to Assumptions (i) and (ii) in Theorem C.5, respectively. Thus we can upper and lower bound the minimum and maximum of memory states $\{s_t : t \in [T]\}$ through:

$$m' \triangleq \min_{t \in [T]} s_t \geq \min_{t \in [T]} (1 - A_{min}^{t-1}q)m + A_{min}^{t-1}qM$$

$$= (1 - A_{min}^{T-1}q)m + A_{min}^{T-1}qM,$$

as we are moving the convex combination towards the smaller end (i.e., $1 - A_{min}^{T-1}q > 1 - A_{min}^{t-1}q$), and similarly,

$$M' \triangleq \max_{t \in [T]} s_t \leq \max_{t \in [T]} A_{min}^{t-1}pm + (1 - A_{min}^{t-1}p)M$$

$$\leq A_{min}^{T-1}pm + (1 - A_{min}^{T-1}p)M.$$

as we are now relaxing the convex combination towards the larger end (i.e., $1 - A_{min}^{T-1}p > 1 - A_{min}^{t-1}p$) Henceforth, we can upper bound:

$$M' - m' \leq A_{min}^{T-1}pm + (1 - A_{min}^{T-1}p)M - (1 - A_{min}^{n-1}q)m - A_{min}^{n-1}qM$$

$$= (1 - A_{min}^{T-1})(M - m),$$

using the fact that $p + q = 1$.

Now we can apply the above result to all memory channels. Assigning each channel with $m_n = \min_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)_n$, $M_n = \max_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)_n$ and M'_n, m'_n accordingly, where $n \in [N]$. We can yield:

$$\max_{t,s \in [T]} \|\boldsymbol{h}_t - \boldsymbol{h}_s\|_\infty \leq \max_{n \in [N]} (M'_n - m'_n)$$

$$\leq \max_{n \in [N]} \left(1 - A_{min}^{T-1}\right)(M_n - m_n)$$

$$\leq \left(1 - A_{min}^{T-1}\right) \max_{n \in [N]} (M_n - m_n)$$

$$= \left(1 - A_{min}^{T-1}\right) \max_{n \in [N]} \left(\max_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t) - \min_{t \in [T]} \boldsymbol{b}_t(\boldsymbol{x}_t)\right)$$

$$= \left(1 - A_{min}^{T-1}\right) \max_{n \in [N]} \max_{t,s \in [T]} (\boldsymbol{b}_t(\boldsymbol{x}_t) - \boldsymbol{b}_s(\boldsymbol{x}_s))$$

$$\leq \left(1 - A_{min}^{T-1}\right) \max_{t,s \in [T]} \|\boldsymbol{b}_t(\boldsymbol{x}_t) - \boldsymbol{b}_s(\boldsymbol{x}_s)\|_\infty,$$

where we exchange the two maximum in the last step. $\square$

Finally, we prove an auxiliary result we used before. This result generalizes Lemma 3 in Wu et al. (2024a) in the scenario when $\alpha_t + \Delta_t < 1$ and $m \leq 0 \leq M$.

Proof of Lemma C.6. We first prove the side that is "less than". Note that the desired inequality trivially holds for the base case s_1. Then we conduct the following inductive steps. Suppose the desired inequality holds for some $r \in [T-1]$, namely:

$$s_r \leq A_{min}^{r-1}pm + (1 - A_{min}^{r-1}p)M.$$

Then we show that for time step $r + 1 \in [T]$,

$$s_{r+1} = A_{r+1}s_r + \Delta_{r+1}z_{r+1}$$

$$\leq A_{r+1} \left(A_{min}^{r-1}pm + (1 - A_{min}^{r-1}p)M\right) + \Delta_{r+1}M \tag{20}$$

$$\leq A_{r+1} \left(A_{min}^{r-1}pm + (1 - A_{min}^{r-1}p)M\right) + (1 - A_{r+1})M \tag{21}$$

$$\leq A_{min} \left(A_{min}^{r-1}pm + (1 - A_{min}^{r-1}p)M\right) + (1 - A_{min})M \tag{22}$$

$$= A_{min}^r pm + (1 - A_{min}^r p)M,$$

where we substitute the upper bounds of s_t (by the inductive hypothesis) and z_t in Eq. 20, Eq. 21 holds because either $\Delta_{r+1} = 1 - A_{r+1}$ (by Assumption (i)) or $\Delta_{r+1} \leq 1 - A_{r+1}$ and $M \geq 0$ (by

Assumption (ii)), Eq. 22 is satisfied as we are lowering down the coefficient for the smaller end in the convex combination. This concludes the proof by induction.

The proof for the "greater than" side follows from a symmetric argument. We provide a brief proof for completeness. The base case s_1 trivially satisfies the desired inequality. Consider an inductive step where s_r for some $r \in [T-1]$ also satisfies the desired inequality. Then we have:

$$
\begin{aligned}
s_{r+1} &= A_{r+1}s_r + \Delta_{r+1}z_{r+1} \\
&\geq A_{r+1}\left((1 - A_{min}^{r-1})qm + A_{min}^{r-1}qM)\right) + \Delta_{r+1}m \\
&\geq A_{r+1}\left((1 - A_{min}^{r-1})qm + A_{min}^{r-1}qM)\right) + (1 - A_{r+1})m \\
&\geq A_{min}\left((1 - A_{min}^{r-1})qm + A_{min}^{r-1}qM)\right) + (1 - A_{min})m \\
&= (1 - A_{min}^r q)m + A_{min}^r qM,
\end{aligned}
$$

which concludes the proof by induction. $\qquad\square$

D EXPERIMENT DETAILS

D.1 NEEDLE IN A HAYSTACK TEST

Our experiments of testing positional bias for Mamba in Sec. 3.2 are based on an open-source project `LLMTest _NeedleInAHaystack` [4]. To validate the retrieval capability of the models while preventing them from relying on memorized information stored in their model weights, we carefully design the inserted statements to contain factual errors. Several examples of such statements are provided in Figure 7. For instance, we insert the statement, "The capital of France is Madrid." and then test the model's retrieval ability by asking the question, "What is the capital of France?" While the correct answer, Paris, is likely memorized by the LLM, if the model "correctly" outputs Madrid based on the context provided, it demonstrates that the model is successfully using the contextual information rather than relying on pre-existing knowledge. This approach ensures that the evaluation focuses on the model's ability to retrieve and process information from the input context. We also add an instruction "ignore the fact, only use information in the context to answer the questions" to facilitate this behavior. We provide the fine-grained visualization result in Figure 8.

Inserted Statement: The capital of France is Madrid.	***Question:*** What is the capital of France?
Inserted Statement: The telephone was invented by Elon Musk.	***Question:*** Who invented the telephone?
Inserted Statement: The largest planet in our solar system is Earth.	***Question:*** What is the largest planet in our solar system?
Inserted Statement: The country known for the Great Wall is Brazil.	***Question:*** What country is known for the Great Wall?

Figure 7: An illustration of our synthetic data.

D.2 CIFAR-10 IMAGE CLASSIFICATION

Here we present experiment details in Sec. 3.3, where we conduct image classification on the CIFAR-10 dataset to study locality bias in SSMs. Specifically, 32×32 RGB images in the dataset are flattened into sequences with a shape of $(1024, 3)$, where 1024 represents the sequence length and 3 corresponds to the RGB channels of the pixel tokens. These pixel tokens are then projected into H-dimensional features via a linear projection, which are then input into SSM or transformer mixers. In addition to pixel tokens, we insert a class token at the last position of the input sequence. The output state of the class token will be processed by a one-layer classifier head to generate the final logits.

Note that while the ViT architecture (Dosovitskiy et al., 2020) places the class token at the first position of the input sequence, this design is incompatible with SSMs, which rely on causal sequence modeling. In SSMs, the class token must be positioned last to aggregate features from the entire sequence. We position the class token as the last token to establish long-range dependencies between global image features and the leading pixel tokens. Alternative methods for aggregating features

---

[4] https://github.com/gkamradt/LLMTest_NeedleInAHaystack

Figure 8: Detailed comparison between SSM and Transformer on the "Needle in a Haystack" benchmark. The upper figure shows the retrieval accuracy of the Mamba-Codestral-7B model, while the lower figure presents the retrieval accuracy of the Mistral-7B model. We present a heatmap where "full context length" refers to the total length of the document, and "needle position" denotes the relative position of the statement to be retrieved within the context.

across the entire sequence, such as mean pooling (Gu et al., 2021a; Tay et al., 2020) or placing the class token in the middle of the sequence (Zhu et al., 2024), work more robustly in general but do not fit the needs for our arguments on locality.

In addition, our image classification setup differs from Tay et al. (2020), where an 8-bit pixel intensity lookup table is used as the token embedder. Instead, we employ a linear projection to map RGB pixel colors into H-dimensional features.

For a fair comparison, the same hyperparameters are used across all models: learning rate = 0.001, weight decay = 0.1, number of layers = 3, feature dimension $H = 32$, and number of states = 64. Each model is trained for 100 epochs. The models and training pipelines are built on Arora et al. (2023). No perturbations are imposed on the input sequences in the training stage.

Adversarial Attack. To introduce perturbations to test data for adversarial attack, we first define a corruption length K, which is small relative to the entire sequence length. We then replace the leading and trailing K tokens with random Gaussian noise. In our experiments, K is set to 32 and 96, corresponding to one row and three rows of pixels, respectively. Table 3 shows more results under other corruption regions.

Table 3: Extended results of adversarial attack experiments on the CIFAR-10 dataset. Classification accuracy is used as the metric.

Models	(no corrupt)	Corrupted region (seq. length = 1024)					
		[1014:1024]	[0:10]	[768:1024]	[0:256]	[512:544]	[480:576]
H3	0.654	0.629	0.654	0.394	0.639	0.603	0.543
Transformer	0.580	0.571	0.500	0.249	0.263	0.498	0.347
RWKV	0.474	**0.194**	0.470	**0.107**	0.448	0.405	0.392
Mamba	0.674	0.348	0.664	**0.099**	0.597	0.515	0.446

Target Attack. For the target attack experiments, a target class is first selected. For each image from the other classes, an image from the target class is randomly sampled, and its leading and trailing pixels are used to replace the corresponding pixels in the original image. We test two attack ratios: 256/1024 and 480/1024. Replacing fewer than 256 pixels generally does not result in considerable success rates based on our trials. In our main text, we show success rates when "horse" is the target class. Similar patterns are also observed across other classes. Fig. 9 shows the average success rates obtained by setting each class as the target.

Figure 9: Overall success rate of our target attack experiments on CIFAR-10, calculated by averaging the attack success rates obtained when each class is individually set as the target class.

D.3 SCALING LAW WITH VARYING DEPTH

In this section, we elaborate on experiment details for Sec. 4.1. We perform casual language modeling (Radford et al., 2018) with Mamba and report the validation perplexity. For each curve in Fig. 4, we fix the depth of the model and vary the number of parameters from 140M to 550M by adjusting the hidden dimension accordingly. The depth is chosen from {16, 24, 32, 48, 64, 72}. All other model configurations keep the default values: the memory state size $N = 16$, the intermediate SSM dimension is two times the hidden dimension, and the intermediate rank for predicting time step Δ_t is the hidden dimension divided by 16. We adopt `DataComp-LM` (Li et al., 2024) as our training corpus for its high data quality. The evaluation set is created by holding out a subset of 10M tokens from the training data. We follow the training recipe provided in Appendix E.2.1 of Gu & Dao (2023), which roughly follows the Chinchilla scaling laws (Hoffmann et al., 2022) to allocate the number of tokens for each model size. We test two block sizes {2048, 8192}. During training, we fix the number of tokens in one training batch (# sequences × sequence length) as 0.5M. The number of training steps is computed by the total number of tokens divided by batch size (# tokens / # tokens in one batch). We use AdamW as the optimizer with gradient clip value 1.0, weight decay 0.1, and linear learning warmup with cosine decay to 1e-5, following Gu & Dao (2023). The peak learning rate is 5× the GPT3 values (Brown et al., 2020) for different model sizes. We summarize the training hyperparameters for varying-sized models in Tab. 4.

D.4 SSM POLARIZATION AND ASSOCIATIVE RECALL EXPERIMENTS

D.4.1 POLARIZED MAMBA

Recall that we polarize a channel in $\boldsymbol{A}_t$ with constant zero and another with constant one. Note that in the implementation of Mamba, $\boldsymbol{A}_t$ is parameterized by $\boldsymbol{A}_t = \exp(\Delta_t \boldsymbol{A})$, where $\boldsymbol{A}$ is a learnable

# Params	Training steps	Peak LR	Batch Size (in tokens)	# Tokens
100-250M	4800	3e-3	0.5M	2.5B
250-400M	13500	1.5e-3	0.5M	7B
400-550M	20000	1.25e-3	0.5M	10B

Table 4: Summary of training settings for varying-sized Mamba.

parameters. We change the forward pass of Mamba by prepending a zero and appending a number negatively large enough (i.e., -1000). So the pre- and post-exponential $\boldsymbol{A}$ and $\boldsymbol{A}_t$ become:

$$
\boldsymbol{A} \leftarrow \begin{bmatrix} 0 & & \\ & \boldsymbol{A} & \\ & & -1000 \end{bmatrix}, \quad \boldsymbol{A}_t \approx \begin{bmatrix} 1 & & \\ & \exp(\Delta_t \boldsymbol{A}) & \\ & & 0 \end{bmatrix}
$$

We also study two variants: 0-polarized and 1-polarized Mamba by only pretending or appending one or zero to $\boldsymbol{A}_t$ to single out the effects of one and zero gating, respectively.

The gradient flow should also comply with the original one, meaning polarization does not change the optimization dynamics of Mamba.

$$
\frac{\partial \ell}{\partial \Delta_t} = \frac{\partial \ell}{\partial \boldsymbol{b}_t} \frac{\partial \boldsymbol{b}_t}{\partial \Delta_t} + \sum_{n=2}^{N-1} \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{n,n}} \frac{\partial (\boldsymbol{A}_t)_{n,n}}{\partial \Delta_t} + \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{1,1}} \frac{\partial (\boldsymbol{A}_t)_{1,1}}{\partial \Delta_t} + \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{N,N}} \frac{\partial (\boldsymbol{A}_t)_{N,N}}{\partial \Delta_t} \frac{\partial \ell}{\partial \Delta_t}
$$

$$
= \frac{\partial \ell}{\partial \boldsymbol{b}_t} \frac{\partial \boldsymbol{b}_t}{\partial \Delta_t} + \sum_{n=2}^{N-1} \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{n,n}} \frac{\partial (\boldsymbol{A}_t)_{n,n}}{\partial \Delta_t} + \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{1,1}} \exp(\Delta_t (\boldsymbol{A}_t)_{1,1}) \underbrace{(\boldsymbol{A}_t)_{1,1}}_{=0}
$$

$$
+ \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{N,N}} \underbrace{\exp(\Delta_t (\boldsymbol{A}_t)_{N,N})(\boldsymbol{A}_t)_{N,N}}_{\approx 0}
$$

$$
\approx \frac{\partial \ell}{\partial \boldsymbol{b}_t} \frac{\partial \boldsymbol{b}_t}{\partial \Delta_t} + \sum_{n=2}^{N-1} \frac{\partial \ell}{\partial (\boldsymbol{A}_t)_{n,n}} \frac{\partial (\boldsymbol{A}_t)_{n,n}}{\partial \Delta_t},
$$

where the term $\exp(\Delta_t (\boldsymbol{A}_t)_{N,N})(\boldsymbol{A}_t)_{N,N} \to 0$ is achieved by taking $(\boldsymbol{A}_t)_{N,N} \to -\infty$.

D.4.2 ASSOCIATIVE RECALL EXPERIMENTS

Associative Recall (AR) is the task of retrieving a specific value tied to a given key. This ability is particularly important for in-context learning, where a model leverages previously presented information to adapt to new inputs (Olsson et al., 2022; Arora et al., 2023).

In our experiments, we use Mamba as the representative SSM, following the setup described in Arora et al. (2023). The input sequences to the model consist of two parts. The first part is a set of key-value

Configurations	# Layers	Recency	Over-smoothing	# KV Pairs			Avg.
				64	128	256	
Default $\boldsymbol{A}_t$	2	●	◐	98.38	81.81	36.00	72.06
Default $\boldsymbol{A}_t$	4	◐	●	99.23	82.08	33.52	71.61
$(\boldsymbol{A}_t)_{1,1} = 1$	2	○	◐	99.81	94.70	56.39	83.63
$(\boldsymbol{A}_t)_{N,N} = 0$	2	●	○	98.41	81.35	36.55	72.10
$(\boldsymbol{A}_t)_{N,N} = 0$	4	◐	○	99.74	92.20	52.21	81.38
$(\boldsymbol{A}_t)_{1,1} = 1, (\boldsymbol{A}_t)_{N,N} = 0$	2	○	○	99.23	95.54	54.74	83.17
$(\boldsymbol{A}_t)_{1,1} = 1, (\boldsymbol{A}_t)_{N,N} = 0$	4	○	○	99.94	98.80	81.56	93.43

Table 5: Extension to Tab. 5. We note the extent of locality and over-smoothing for each configuration. We consider 1-polarization mitigates locality most significantly, while deepening architecture only relieves recency mildly but deteriorates over-smoothing. 0-polarization alleviates over-smoothening and unleash the benefits by depth scaling.

pairs, randomly sampled from a vocabulary, with keys and values drawn independently. The second part contains random keys, selected from those present in the first part (without repetition), and placed according to a power-law distribution at random. Any remaining slots in the sequence are filled with a zero token. The target sequence contains the values corresponding to the positions of the respective key occurrences, while all other tokens are excluded from loss supervision and accuracy evaluation.

We employ a training strategy with mixed sequence lengths and varying numbers of key-value pairs. Specifically, the total sequence length varies across {64, 128, 256, 512, 1024}, with {12.5%, 25%, 50%} of the sequence allocated to key-value pairs and the remainder to queried keys. Each configuration includes 20,000 examples, resulting in a total of 300,000 training examples. For evaluation, the sequence length is fixed at 1024, while the number of key-value pairs varies among 64, 128, 256. We use a batch size of 128 and a learning rate of 1e-3 throughout the experiments. We provide an extended table for the results in Tab. 5.