Out-of-distribution Prediction with Invariant Risk Minimization: The Limitation and An Effective Fix

Abstract

This work considers the out-of-distribution (OOD) prediction problem where (1) the training data are from multiple domains and (2) the test domain is unseen in the training. DNNs fail in OOD prediction because they are prone to pick up spurious correlations. Recently, Invariant Risk Minimization (IRM) is proposed to address this issue. Its effectiveness has been demonstrated in the colored MNIST experiment. Nevertheless, we find that the performance of IRM can be dramatically degraded under *strong Λ spuriousness* – when the spurious correlation between the spurious features and the class label is strong due to the strong causal influence of their common cause, the domain label, on both of them (see Fig. 1). In this work, we try to answer the questions: why does IRM fail in the aforementioned setting? Why does IRM work for the original colored MNIST dataset? Then, we propose a simple and effective approach to fix the problem of IRM. We combine IRM with conditional distribution matching to avoid a specific type of spurious correlation under strong Λ spuriousness. Empirically, we design a series of semi synthetic datasets – the colored MNIST plus, which exposes the problems of IRM and demonstrates the efficacy of the proposed method.

1 Introduction

Strong empirical results have demonstrated the efficacy of deep neural networks (DNNs) in a variety of areas including computer vision, natural language processing and speech recognition. However, such positive results overwhelmingly rely on the assumption that the training, validation and test data consist of independent identical samples of the same underlying distribution. In contrast, in the setting of out-of-distribution (OOD) prediction where (1) the training data is from multiple domains and (2) the test set has different distribution from the training, the performance of DNNs can be dramatically degraded. This is because DNNs are prone to pick up spurious correlations which do not hold beyond the training data distribution (Beery et al., 2018; Arjovsky et al., 2019). For example, when most camel pictures in a training set have a desert in the background, DNNs will pick up the spurious correlation between a desert and the class label, leading to failures when camel pictures come with different backgrounds in a test set. Therefore, OOD prediction remains an extremely challenging problem for DNNs.

Figure 1: The causal relationships among the causal features X^c, the spurious features X^s, the domain label E and the class label Y in OOD prediction. The causal relationship between X^c and Y, $P(Y|X^c)$, is invariant across domains. The spurious correlation $P(Y|X^s)$ may vary. The thick directed edges show strong Λ spuriousness.

The invariant causal relationships across different domains turns out to be the key to address the challenge of OOD prediction. The causal graph in Fig. 1 describes the relationships of the variables in the OOD prediction problem. Although spurious correlations learned in one domain are unreliable in another, invariant causal relationships enable DNNs that capture causal relationships to generalize to unseen domains. In practice, it is extremely difficult to know whether an input feature is causal or spurious. Thus, a recipe for training DNNs that capture causal relationships is learning causal feature representations that hold invariant causal relationships with the class label.

Thus, the main challenge of OOD prediction becomes learning causal feature representations given training data from multiple domains. Recently, Invariant Risk Minimization (IRM) (Arjovsky et al., 2019) is proposed to learn causal feature representations for OOD prediction. IRM formulates the invariance of causal relationships as a constraint. It requires that causal feature representations must result in the same optimal classifier across all domains. This constraint can be written as the conditional independence, $Y \perp\!\!\!\perp E | F(X)$ (Chang et al., 2020; Zeng et al., 2019) which can be derived from the causal graph in Fig. 1 when $F(X)$ is a mapping of causal features (X^c in Fig. 1) with no information loss.

Despite IRM's success in the colored MNIST dataset (Arjovsky et al., 2019), in this work, we find an important issue of IRM that has not been discussed. Specifically, we consider the situation where strong spurious correlation exists between the spurious features and the class label only in the training set. We name this *strong Λ spuriousness* using the shape of the causal structure among the three variables in the causal graph (Fig. 1). Under strong Λ spuriousness, IRM regularized empirical risk can have low values with spurious feature representations that accurately predict the domain label. This is because, in this setting, picking up spurious features can achieve high accuracy in predicting both domain and class in the training set, but not in the test. However, the colored MNIST dataset cannot expose this issue because the strong similarity between the two training domains makes it difficult to pick up the weak spurious correlation between the domain label and the spurious features. To illustrate this problem, we design a new dataset – the colored MNIST plus. As shown in Fig. 2, in this dataset, under strong Λ spuriousness, the performance of IRM models is significantly degraded.

Moreover, to resolve this issue of IRM, we propose an effective solution, which combines IRM with conditional distribution matching (CDM). The CDM constraint means that the representation distribution of instances from the same class should be invariant across domains. Theoretically, we show that (1) causal feature representations can satisfy CDM and IRM at the same time and (2) CDM can prevent DNNs from learning spurious feature representations that accurately predict the domain label. Empirically, on our newly introduced dataset, the proposed method achieves significant performance improvement over IRM under strong Λ spuriousness.

2 PRELIMINARIES AND IRM

Notations. We use lowercase (e.g., x), uppercase (e.g., X) and calligraphic uppercase (e.g., $\mathcal{X}$) letters for values, random variables and spaces. We let $X \in \mathcal{X}$, $Y \in \mathcal{Y}$ and $E \in \mathcal{E}$ denote raw input, the class label and the domain label where $\mathcal{X}$, $\mathcal{Y}$ and $\mathcal{E}$ are the spaces of input, class labels and domains. A DNN model consists of a feature learning function F and a classifier G. A feature learning function $F : \mathcal{X} \to \mathbb{R}^d$ maps raw input X to its d-dimensional representations $F(X)$. A classifier $G : \mathbb{R}^d \to \mathcal{Y}$ maps a feature representation to a class label. We denote their parameters by $\boldsymbol{\theta}_F$ and $\boldsymbol{\theta}_G$, respectively. Let $\boldsymbol{\theta} = Concat(\boldsymbol{\theta}_F, \boldsymbol{\theta}_G)$ denote the concatenation of them.

A domain e of n_e instances is denoted by $D_e = \{x_i^e, y_i^e\}_{i=1}^{n_e}$. Let $\mathcal{E}_{tr}$ and $\mathcal{E}_{ts}$ denote the set of training and test domains, in OOD prediction, we have (1) $|\mathcal{E}_{tr}| > 1$ and (2) $\mathcal{E}_{tr} \cap \mathcal{E}_{ts} = \emptyset$.

Problem Statement. Given data from multiple training domains $\{D_e\}_{e \in \mathcal{E}_{tr}}$. We aim to predict the label $y_i^{e'}$ of each instance with features $x_i^{e'}$ from a test domain $\{x_i^{e'}, y_i^{e'}\}_{i=1}^{n_{e'}}, e' \in \mathcal{E}_{ts}$.

Invariant Risk Minimization. IRM (Arjovsky et al., 2019) is a recently proposed method to impose the causal inductive bias: the causal relationships between causal features and the label should be invariant across different domains. It not only aims to address the challenging OOD prediction problem, but also is a pioneer work that guides causal machine learning research towards the development of inductive bias imposing causal constraints. The effectiveness of IRM and its variants have been demonstrated across various areas including computer vision (Ahuja et al., 2020), natural language processing (Chang et al., 2020), CTR prediction (Zeng et al., 2019), reinforcement learning (Zhang et al., 2020a) and financial forecasting (Krueger et al., 2020). Arjovsky et al. (2019) propose the original formulation of IRM as a two-stage optimization problem:

$$\underset{\boldsymbol{\theta}_F, \boldsymbol{\theta}_G}{\arg\min} \sum_{e \in \mathcal{E}_{tr}} \mathbb{E}_{(x,y) \sim D_e}[R^e(G(F(x)), y)]$$

$$s.t. \ \boldsymbol{\theta}_G \in \underset{\boldsymbol{\theta}'_G}{\arg\min} \ R^e(G(F(x); \boldsymbol{\theta}'_G), y), \tag{1}$$

where R^e denotes the loss function of domain e. Then, they show that the IRM constraint can be imposed by adding a regularizer into the loss function. It turns out the IRM constraint can be written as the conditional independence $Y \perp\!\!\!\perp E|F(X)$ (Chang et al., 2020; Zeng et al., 2019). This can be derived from the causal graph in Fig. 1. For brevity, we refer to $Y \perp\!\!\!\perp E|F(X)$ as the IRM constraint.

3 THE LIMITATION OF IRM

In this section, we find that IRM fails under strong Λ spuriousness – when the spurious correlations among spurious features, the domain label and the class label are strong. To show it, we design a new dataset – the colored MNIST plus (CMNIST+) to expose this limitation of IRM. Then, we try to answer two crucial research questions: (1) why does IRM fail in CMNIST+? (2) Why does IRM work for the original colored MNIST (CMNIST) dataset?

3.1 WHY DOES IRM FAIL?

(a) IRM (b) IRM with label balancing (c) ERM

Figure 2: Test accuracy of IRM, IRM with balanced classes in each domain, and ERM on CM-NIST+: when the Λ spuriousness is strong ($\rho \geq 0.8$), the performance of IRM drops dramatically because, in this situation, the spurious feature representation $F(X) = E$ satisfies the IRM constraint. The naïve solution, balancing classes in each domain cannot mitigate this problem of IRM.

Despite its previous success, results in Fig. 2 show that IRM fails in our newly designed colored MNIST plus dataset, under strong Λ spuriousness ($\rho \geq 0.8$). Here, we show that, under strong Λ spuriousness, at least two types of feature representations, $F(X) = Y$ and $F(X) = E$, satisfy the IRM constraint. When $F(X) = E$, the feature representations pick up spurious relationships.

Satisfying IRM by Perfectly Predicting the Label. First, we consider a case where there exists a feature representation that perfectly predicts the class label, i.e., $F(X) = Y$. In this case, we know that the feature representation satisfies the IRM constraint because $Y \perp\!\!\!\perp E|F(X) = Y$ always holds. This is reasonable because the causal relationship between Y and itself must be invariant across different domains[1].

Satisfying IRM by Perfectly Predicting the Domain Does Not Lead to OOD Generalizable Feature Representations. However, there is another way to satisfy the IRM constraint. If there exists a feature representation $F(X) = E$[2], then the IRM constraint can be satisfied by $F(X)$. This is due to the fact $Y \perp\!\!\!\perp E|F(X) = E$. However, this is not desired behavior of IRM as $F(X) = E$ is a type of spurious feature representation. This is because $P(Y|E)$ can vary across domains. Using the camel picture example, if domains are the individuals who take the picture, we may find more camel pictures taken by person e than from person e' ($P(Y = camel|E = e) > P(Y = camel|E = e')$). Why is $F(X) = E$ a good solution for the original IRM optimization problem (Eq. 1)? This is because $F(X) = E$ also leads to low values of the loss function R^e since the direct causal influence of the domain label E on the class label Y is also strong when Λ spuriousness is strong. So, with a proper classifier G, we can achieve low values of R^e with $F(X) = E$. Then, we describe the CMNIST+ dataset and show experimental and theoretical results to support our claim.

---

[1] Note that Y is a cause of Y because modifying the value of Y would change the value of Y with all other variables remaining the same (*ceteris paribus*).

[2] $F(X)$ can be any superset of E to satisfy IRM.

The Colored MNIST Plus (CMNIST+) Dataset. We follow CMNIST (Arjovsky et al., 2019) to create CMNIST+ by resampling and adding colors to instances of MNIST. The digits $0 - 4$ $(5 - 9)$ are class $Y = 1$ $(Y = 0)$. We randomly flip 25% of class labels so that spuriousness can be stronger than the causal relationship between the shape S (causal features) and the class label Y. Table 1 describes the dataset. The variable $C \in \{G, B, R\}$ denotes the color, which represents the spurious feature X^s. The parameter $\rho \in (0.5, 1)$ controls the strength of the spurious correlations between the color (spurious features) C and the class label Y through their common cause, the domain label E. The larger the value of ρ, the stronger the spurious correlations. Intuitively, in the two training domains of CMNIST+, in addition to the strong spurious correlation between the class label Y and color C, we set the spurious correlation between the domain label E and color C to be strong, too. Thus, the CMNIST+ dataset can expose the problem of IRM: it would not penalize the models that fit the domain variable as the feature representation ($F(X) = E$). To verify this claim, we show theoretical results to support the experimental results in Fig. 2.

Table 1: Definition of CMNIST+

E	$P(Y = 1|E)$	Y	$P(C = G|Y, E)$	$P(C = B|Y, E)$	$P(C = R|Y, E)$
$E = 1$	0.9	$Y = 1$	ρ	$(1-\rho)/2$	$(1-\rho)/2$
		$Y = 0$	$(1-\rho)/2$	$(1-\rho)/2$	ρ
$E = 2$	0.1	$Y = 1$	$(1-\rho)/2$	ρ	$(1-\rho)/2$
		$Y = 0$	$(1-\rho)/2$	$(1-\rho)/2$	ρ
$E = 3$	0.5	$Y = 1$	0.1	0.1	0.8
		$Y = 0$	0.4	0.4	0.2

Figure 3: We visualize the differences between CMNIST and CMNIST+ ($\rho = 0.9$) in terms of $P(C|Y = 1, E)$. Each large triangle represents the space of $P(C|Y, E)$. Each small triangle shows the values of $P(C = c|Y = 1, E = e), c \in \{R, G, B\}, e \in \{1, 2, 3\}$.

Theoretical Results. Here, we show the theoretical results on the CMNIST+ to answer two questions: what features will be learned by ERM and IRM under under different Λ spuriousness? What is the expected test accuracy of these models? For simplicity, we assume that the classifier is deterministic, which always predicts the majority class given the feature. If the number of instances from each class is the same, then it would predict a random label. We analyze three types of spurious feature representations: (1) those that fit color, (2) those that fit the domain label and (3) those that use a combination of them for prediction. The first case mimics the behavior of ERM that picks up the spurious correlation between color and the class label. The second one represents a model satisfying IRM by $F(X) = E$. The third one stands for a model satisfying IRM by $F(X) = Concat(E, C)$. One may argue that IRM can be fixed if we simply balance the two classes in each domain. Theoretical analysis shows that this is an invalid solution. We summarize the theoretical results in Table 2 where $\hat{E}$ denotes the domain label predicted by a deterministic classifier using color as the feature. This is because in an unseen test domain, we cannot directly use the domain label for prediction. The highlighted numbers show which type of features would be learned by ERM and IRM. We can see as ρ increases, ERM and IRM are more likely to learn spurious feature representations. This explains results in Fig. 2. As a DNN may still pick up some causal features (shape in CMNIST+) even when $\rho = 0.9$, the test accuracy of IRM in practice would be greater than 0.35 without label balancing and 0.2 with label balancing. Similarly, the test accuracy of ERM would be greater than 0.2. From Fig. 2, we can see the test accuracy of IRM, IRM with label balancing and ERM are slightly better than the aforementioned lower bounds. The derivations can be found in Appendix A.1.

Experimental Setup. We use a LeNet-5 (LeCun et al., 1998) instead of a three-layer MLP. To take input with three colors, we modify the first CNN layer to have three channels. LeNet-5 has more predictive power such that it can pick up the three types of spurious correlations (color – domain, color – class, and domain – class) or the causal relationship (shape – class). We randomly split the instances from the training domains into 80% training and 20% validation. The model selection is done by picking the one with the lowest validation loss in each run. We report the average test accuracy of the selected models in 10 runs. It is crucial to ensure only data from training domains are used in model selection, since the test domain should be unseen during training and validation. During training, we begin applying the IRM penalty at iteration K_{IRM}, set to 200, 400, or 600. By varying K_{IRM}, we aim to examine the following hypothesis: IRM works by pushing the spurious features out of the representations learned by the standard ERM training before the IRM penalty is applied (Krueger et al., 2020). More details on the setup can be found in Appendix B.1.

Experimental Results. Fig. 2 shows the performance of IRM and IRM with balanced classes in each domain. We make the following observations: first, the test accuracy of IRM drops dramatically under strong Λ spuriousness. Second, we show that a naïve fix for IRM, balancing the two classes in each domain by oversampling the minority class, does not lead to improvement in performance.

Table 2: Theoretical validation/test accuracy with the three spurious feature representations (C: color, E: domain and E+C) and the causal feature representation (S: shape) on CMNIST+. The ones with the best validation accuracy in each setting are highlighted, which show the type of feature representations would be learned by ERM and IRM.

		Validation/Test Accuracy						
		without label balancing				with label balancing		
ρ	$\hat{P}(Y\|C)$	$\hat{P}(Y\|\hat{E})$	$\hat{P}(Y\|\hat{E},C)$	$\hat{P}(Y\|S)$	$\hat{P}(Y\|C)$	$\hat{P}(Y\|\hat{E})$	$\hat{P}(Y\|\hat{E},C)$	$\hat{P}(Y\|S)$
0.55	0.662/0.2	0.646/0.35	0.662/0.35	**0.75/0.75**	0.662/0.2	0.5/0.5	0.662/0.2	**0.75/0.75**
0.6	0.7/0.2	0.68/0.35	0.7/0.35	**0.75/0.75**	0.7/0.2	0.5/0.5	0.7/0.2	**0.75/0.75**
0.65	0.738/0.2	0.714/0.35	0.738/0.35	**0.75/0.75**	0.738/0.2	0.5/0.5	0.737/0.2	**0.75/0.75**
0.7	**0.775/0.2**	0.748/0.35	**0.775/0.35**	0.75/0.75	**0.775/0.2**	0.5/0.5	**0.775/0.2**	0.75/0.75
0.8	**0.85/0.2**	0.815/0.35	0.815/0.35	0.75/0.75	**0.85/0.2**	0.5/0.5	**0.85/0.2**	0.75/0.75
0.85	**0.888/0.2**	0.849/0.35	0.849/0.2	0.75/0.75	**0.888/0.2**	0.5/0.5	**0.888/0.2**	0.75/0.75
0.9	**0.925/0.2**	0.883/0.35	0.883/0.2	0.75/0.75	**0.925/0.2**	0.5/0.5	**0.925/0.2**	0.75/0.75

3.2 WHY DOES IRM WORK FOR THE ORIGINAL COLORED MNIST?

(a) IRM on CMNIST test set

(b) IRM on CMNIST+ test set

Figure 4: Accuracy of IRM trained on datasets between CMNIST and CMNIST+ and tested on the test sets of CMNIST and CMNIST+ (w_{plus} increases): As the training set becomes more similar to CMNIST+, the performance of IRM gradually drops, on the test sets of both CMNIST and CMNIST+.

The Colored MNIST (CMNIST) dataset cannot expose the limitation of IRM under strong Λ spuriousness. This is because its two training domains are quite similar. As shown in the large triangle on the left in Fig. 3, the values of $P(C|Y,E)$ are similar for $E=1$ and $E=2$. In addition, the values of $P(Y|E)$ are the same for all E. This makes it difficult to satisfy the IRM constraint by learning feature representations $F(X) \approx E$.

Then, we present experiments to show how IRM gradually goes from working on CMNIST to failing on CMNIST+. In Fig. 3 Left and Right, we observe the differences between between CMNIST and CMNIST+ ($\rho = 0.9$). In Fig. 3 Middle, we create various datasets that interpolate between these

two datasets, illustrated by the yellow line in the middle triangle. We use a parameter $w_{plus} \in [0, 1]$ to control $P(C|Y, E)$ of the weights of CMNIST+ ($\rho = 0.9$) in the interpolated dataset:

$$P(C|Y, E) = \frac{P_{\text{cmnist+}}(C|Y, E)w_{plus} + P_{\text{cmnist}}(C|Y, E)(1 - w_{plus})}{\sum_C (P_{\text{cmnist+}}(C|Y, E)w_{plus} + P_{\text{cmnist}}(C|Y, E)(1 - w_{plus}))}, \tag{2}$$

where $P_{\text{cmnist+}}(C|Y, E)$ and $P_{\text{cmnist}}(C|Y, E)$ are the values of $P(C|Y, E)$ in CMNIST+ and CM-NIST. When $w_{plus} = 0$ and $P(Y = 1|E = 1) = P(Y = 0|E = 2) = 0.5$, the dataset is the same with CMNIST. As w_{plus} and $P(Y = 1|E = 1) = P(Y = 0|E = 2)$ increase, the dataset becomes more similar to CMNIST+, and becomes the same with CMNIST+ ($\rho = 0.9$) when $w_{plus} = 1$ and $P(Y = 1|E = 1) = P(Y = 0|E = 2) = 0.9$. For the training sets, we set $P(Y = 1|E = 1) = P(Y = 0|E = 2) \in \{0.5, 0.7, 0.9\}$. Fig. 4 shows results of IRM on the test sets of both CMNIST and CMNIST+. The performance of IRM gradually drops when the values of $P(C|Y, E)$ becomes more similar to CMNIST+ (when the Λ spuriousness becomes stronger).

4 AN EFFECTIVE FIX FOR IRM

In this section, we propose a simple but effective solution to address the limitation of the IRM training. In a series of experiments, we show that the proposed method can improve the performance of IRM even under strong Λ spuriousness.

Since the IRM constraint is too general, we propose an effective solution – combining the conditional distribution matching (CDM) constraint and the IRM constraint. The CDM constraint (Li et al., 2018; Long et al., 2018) requires $P(F(X)|Y, E) = P(F(X)|Y)$, which means the feature representation distribution given the class label should be invariant across different domains. We first explain why this can be a reasonable solution. Then, we propose two types of models that combine the two constraints.

Here, we use the two cases from Section 3.1 to explain why combining IRM with CDM can be an effective fix for IRM.

Perfectly predicting the label satisfies CDM. In this case, $F(X) = Y$ and we already know the IRM constraint is satisfied. The CDM condition also holds as $P(F(X)|Y, E) = P(Y|Y, E) = P(Y|Y) = P(F(X)|Y)$.

Perfectly predicting the domain label violates CDM. In this case, $F(X) = E$ and the IRM constraint can be satisfied, but the CDM constraint does not hold as $P(F(X)|Y, E) = P(E|Y, E) \neq P(E|Y) = P(F(X)|Y)$). This case implies that we can add CDM to IRM to exclude the undesirable solution of learning spurious features that accurately predict the domain label.

One way to enforce the CDM constraint is through adversarial training: a discriminator tries to infer the source domain from the feature representation $F(X)$ and $F(X)$ tries to adjust itself to fool the discriminator. From this perspective, we can find that the CDM constraint exactly prevents $F(X)$ from making use of the domain labels to achieve high training accuracy (i.e., low R_e).

With the idea of combining IRM and CDM, we can formulate the optimization problem as:

$$\underset{\boldsymbol{\theta}_F, \boldsymbol{\theta}_G}{\arg\min} \sum_{e \in \mathcal{E}_{tr}} \mathbb{E}_{(x,y) \sim D_e}[R^e(G(F(x)), y)]$$
$$s.t. \ Y \perp\!\!\!\perp E|F(X), P(F(X)|Y, E = e) = P(F(X)|Y, E = e'), e \neq e', \tag{3}$$

where R^e denotes the loss function in domain e (e.g., cross entropy loss). To impose the CDM constraint, we aim to minimize certain divergence between feature distributions from different domains, denoted as $div(P(F(X)|Y, E = e)||P(F(X)|Y, E = e')), e \neq e'$.

We propose two choices of divergences, i.e., Maximum Mean Discrepancy (MMD) and Kullback-Leibler (KL) divergence (through adversarial training), which result in two algorithms: IRM-MMD and IRM-ACDM (i.e., IRM-Adversarial Conditional Distribution Matching).

IRM-MMD. In IRM-MMD, we adopt Maximum Mean Discrepancy (MMD) (Long et al., 2015; Tolstikhin et al., 2017; Shalit et al., 2017) as the distribution divergence. The MMD between P and Q, two d-dimensional distributions of feature representations, can be defined as:

$$MMD_k(P, Q) = \sup_{f \in \mathcal{H}} |\mathbb{E}_{Z \sim P}[f(Z)] - \mathbb{E}_{Z \sim Q}[f(Z)]|, \tag{4}$$

where $Z \in \mathbb{R}^d$, $f : \mathbb{R}^d \to \mathbb{R}$ maps a feature representation to a real value, $k : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}$ denotes the characteristic kernel of f and $\mathcal{H}$ is the RHKS of k. The MMD in Eq. 4 is not directly computable. So, we use the unbiased estimator of MMD (Gretton et al., 2012a) with N samples $z_1^P, ..., z_N^P$ from P and M samples $z_1^Q, ..., z_M^Q$ from Q:

$$MMD_k(P,Q) = \frac{1}{N(N-1)} \sum_{i \neq j} k(z_i^P, z_j^P) + \frac{1}{M(M-1)} \sum_{i \neq j} k(z_i^Q, z_j^Q) - \frac{2}{MN} \sum_{i=1}^{N} \sum_{j=1}^{M} k(z_i^P, z_j^Q). \tag{5}$$

With MMD defined, we can define the loss function of IRM-MMD as:

$$\arg \min_{\boldsymbol{\theta}} \sum_{e \in \mathcal{E}_{tr}} \mathcal{L}_{IRM}^e + \beta \sum_{y \in \mathcal{Y}} \sum_{e \in \mathcal{E}_{tr}} \sum_{e' \in \mathcal{E}_{tr} \setminus e} MMD_k(P(F(X)|y,e), P(F(X)|y,e')), \tag{6}$$

where $\mathcal{L}_{IRM}^e = \frac{1}{n_e} \sum_{i=1}^{n_e} R^e(G(F(x_i^e)), y_i^e) + \alpha|| \bigtriangledown_{w|w=1.0} wR^e(G(F(x_i^e)))||^2$ denotes the IRM regularized loss (Arjovsky et al., 2019) for domain e, hyperparameters α and β control the trade-off between the main loss, the IRM constraint and the CDM constraint.

IRM-ACDM. In IRM-ACDM, we make $div(P(F(X)|Y, E = e)||P(F(X)|Y, E = e'))$ be the Kullback-Leibler (KL) divergence and use adversarial learning to estimate it (Tolstikhin et al., 2017; Song et al., 2020). More precisely, we define the loss function of IRM-ACDM as:

$$\arg \min_{\boldsymbol{\theta}} \sum_{e \in \mathcal{E}_{tr}} \mathcal{L}_{IRM}^e + \beta \sum_{y \in \mathcal{Y}} \sum_{e \in \mathcal{E}_{tr}} \gamma_e^y KL(P(F(X)|Y = y, E = e)||P(F(X)|Y = y)), \tag{7}$$

where $\gamma_e^y := P(E = e, Y = y)$. In adversarial learning, a conditional discriminator $D : \mathbb{R}^d \times \mathcal{Y} \to \mathcal{E}_{tr}$ with parameters $\boldsymbol{\theta}_D$ is introduced to predict the domain label of an instance, given its feature representation and class label. As proved in Li et al. (2018); Song et al. (2020), the estimation of the KL divergence above can be reformulated as the minimax game below:

$$\min_{\boldsymbol{\theta}} \max_{\boldsymbol{\theta}_D} \sum_{e \in \mathcal{E}_{tr}} \mathcal{L}_{IRM}^e + \beta \sum_{y \in \mathcal{Y}} \sum_{e \in \mathcal{E}_{tr}} \gamma_e^y \mathbb{E}_{F(x) \sim P(F(X)|Y=y, E=e)}[\log D^e(F(x), y)], \tag{8}$$

where $D^e(F(x), y) = \hat{P}(E = e|F(x), y)$ is the predicted probability of the instance for domain e by the discriminator D. In practice, we solve the minimax game above efficiently by the alternative gradient ascent/descent algorithm.

Experimental Results. We evaluate IRM-MMD and IRM-ACDM on CMNIST+ to show their efficacy under strong Λ spuriousness. We let the output of the second last layer of LeNet-5 to be the feature representation $F(X)$. For IRM-MMD, we use the multiple kernel MMD (MKMMD) (Gretton et al., 2012b; Long et al., 2015). For IRM-ACDM, we use a two-layer MLP with $|\mathcal{E}_{tr}|$ outputs as the discriminator D. To show that CDM alone cannot solve OOD prediction under strong Λ spuriousness, we set the weight of the IRM penalty $\alpha = 0$ in IRM-MMD and IRM-ACDM to obtain the models regularized by MMD and ACDM, respectively. We also include ERM and oracle. The oracle uses the original LeNet-5 architecture with a single-channel CNN as the first layer. It is trained and tested with instances transformed into grayscale.

Table. 3 shows the performance of IRM-MMD, IRM-ACDM and the baselines. Under strong Λ spuriousness, compared to IRM (Fig. 2), we can observe the significant and consistent performance improvement over IRM resulting from combining CDM with IRM. IRM-MMD and IRM-ACDM also outperform MMD and ACDM. This verifies that CDM alone cannot solve the OOD prediction problem.

5 RELATED WORK

OOD Prediction. IRM (Arjovsky et al., 2019) formulates causal feature learning as a constraint on the ERM framework (Vapnik, 1992), which imposes the causal inductive bias: causal feature representations lead to the existence of an optimal classifier for all domains. Then it is transformed to a regularizer which can be minimized along with empirical risks. Chang et al. (2020) propose a variant of IRM. They implement IRM by minimizing the difference between two classifiers' outputs, which take $F(X)$ and $Concat(F(X), E)$ as the inputs, respectively. Ahuja et al. (2020)

Table 3: Test accuracy on CMNIST+: by combining CDM with IRM, performance is improved significantly and consistently under strong Λ spuriousness ($\rho \geq 0.8$) compared to IRM.

Method	$\rho = 0.8$	$\rho = 0.85$	$\rho = 0.9$
IRM-MMD (ours)	**52.91%**	**40.83%**	**37.96%**
IRM-ACDM (ours)	**57.23%**	**45.47%**	**42.85%**
IRM	47.01%	37.81%	36.31%
MMD	23.04%	25.22%	24.22%
ACDM	30.41%	29.48%	25.53%
ERM	30.16%	27.83%	24.61%
Oracle	73.10%	73.49%	73.58%

reformulate the optimization problem of IRM from a game theory aspect. IRM is related to robust optimization (Ben-Tal et al., 2009). The goal is to optimize the worst domain specific empirical risk. Krueger et al. (2020) extend robust optimization (Ben-Tal et al., 2009) to minimize the empirical risk of the worst domain and maximize that of other domains. They also propose to minimize the variance of domain specific empirical risks along with the empirical risk. Jin et al. (2020) propose to minimize the domain specific risk between two models, one trained on the same domain, the other trained on the other domains. These methods essentially minimize the differences among domain specific risks. Moreover, data augmentation can also improve the generalizability of DNNs from the data perspective (Ilse et al., 2020; van der Wilk et al., 2018). However, it requires prior knowledge on the differences between training and test domains, which are not be available in OOD prediction. Kuang et al. (2018) and Qiao et al. (2020) aim to handle the case with only one training domain. Zhang et al. (2020b) propose to make DNNs more robust against test data generated by unseen interventions. They model interventions in training data with a generative model and perform test-time inference to catch unseen interventions. Compared to the existing work, this work exposes and fixes the issue of IRM in OOD prediction under strong Λ spuriousness.

Domain Adaptation (DA) assumes that the unlabeled test set can be used during training and validation. From the methodology aspect, distribution matching methods used in DA, such as gradient reversing (Ganin & Lempitsky, 2015) and adversarial CDM (Long et al., 2018) are useful for OOD prediction. Peters et al. (2016) realize the invariance of causal relationships can be used for DA. Zhang et al. (2013) propose reweighting and kernel based distribution matching methods to handle three types of DA problems: target shift, conditional shift and generalized target shift. Gong et al. (2016) work on extracting transferable components $F(X)$ that ensure $P(F(X)|Y)$ to be invariant across domains with location-scale transformation. Their method can identify how $P(Y)$ changes across domains simultaneously. Different from DA, we strictly ensure that the test domain is unseen during training and validation to reflect the scenario of OOD prediction in real-world applications.

6 CONCLUDING REMARKS

This work focuses on the OOD prediction problem under strong Λ spuriousness. Strong Λ spuriousness means the correlations between spurious features and the class label are strong. We find an important limitation of IRM in OOD prediction under strong Λ spuriousness: it can be satisfied by spurious feature representations that are predictive of the domain label. To verify it, we design the CMNIST+ dataset which has strong Λ spuriousness between color (spurious features) the class label through their common cause – the domain variable. On CMNIST+, we observe the performance of IRM dramatically drops when the Λ spuriousness becomes stronger. Based on this observation, we propose a simple but an effective fix to mitigate this issue of IRM. The proposed approach combines CDM and IRM because CDM can also be satisfied by causal feature representations. At the same time, CDM can prevent DNNs from picking up the aforementioned spurious feature representations. Experimental results on CMNIST+ show significant performance improvement of the proposed method, demonstrating its effectiveness. Interesting future work includes (1) extension of the proposed method to OOD prediction tasks in complex data (e.g., graphs and time series) and (2) development of general causal inductive bias that can impose various conditional independence.

REFERENCES

Kartik Ahuja, Karthikeyan Shanmugam, Kush Varshney, and Amit Dhurandhar. Invariant risk minimization games. *arXiv preprint arXiv:2002.04692*, 2020.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 456–473, 2018.

Aharon Ben-Tal, Laurent El Ghaoui, and Arkadi Nemirovski. *Robust optimization*, volume 28. Princeton University Press, 2009.

Shiyu Chang, Yang Zhang, Mo Yu, and Tommi S Jaakkola. Invariant rationalization. In *ICML*, 2020.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pp. 1180–1189, 2015.

Mingming Gong, Kun Zhang, Tongliang Liu, Dacheng Tao, Clark Glymour, and Bernhard Schölkopf. Domain adaptation with conditional transferable components. In *International conference on machine learning*, pp. 2839–2848, 2016.

Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773, 2012a.

Arthur Gretton, Dino Sejdinovic, Heiko Strathmann, Sivaraman Balakrishnan, Massimiliano Pontil, Kenji Fukumizu, and Bharath K Sriperumbudur. Optimal kernel choice for large-scale two-sample tests. In *Advances in neural information processing systems*, pp. 1205–1213, 2012b.

Maximilian Ilse, Jakub M Tomczak, and Patrick Forré. Designing data augmentation for simulating interventions. *arXiv preprint arXiv:2005.01856*, 2020.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Domain extrapolation via regret minimization. *arXiv preprint arXiv:2006.03908*, 2020.

David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Remi Le Priol, and Aaron Courville. Out-of-distribution generalization via risk extrapolation (rex). *arXiv preprint arXiv:2003.00688*, 2020.

Kun Kuang, Peng Cui, Susan Athey, Ruoxuan Xiong, and Bo Li. Stable prediction across unknown environments. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 1617–1626, 2018.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Ya Li, Xinmei Tian, Mingming Gong, Yajing Liu, Tongliang Liu, Kun Zhang, and Dacheng Tao. Deep domain generalization via conditional invariant adversarial networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 624–639, 2018.

Mingsheng Long, Yue Cao, Jianmin Wang, and Michael Jordan. Learning transferable features with deep adaptation networks. In *International conference on machine learning*, pp. 97–105. PMLR, 2015.

Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I Jordan. Conditional adversarial domain adaptation. In *Advances in Neural Information Processing Systems*, pp. 1640–1650, 2018.

Jonas Peters, Peter Bühlmann, and Nicolai Meinshausen. Causal inference by using invariant prediction: identification and confidence intervals. *J. R. Stat. Soc. Series B Stat. Methodol.*, 78(5): 947–1012, 2016.

Fengchun Qiao, Long Zhao, and Xi Peng. Learning to learn single domain generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12556–12565, 2020.

Uri Shalit, Fredrik D Johansson, and David Sontag. Estimating individual treatment effect: generalization bounds and algorithms. In *International Conference on Machine Learning*, pp. 3076–3085. PMLR, 2017.

Yuhang Song, Wenbo Li, Lei Zhang, Jianwei Yang, Emre Kiciman, Hamid Palangi, Jianfeng Gao, C-C Jay Kuo, and Pengchuan Zhang. Novel human-object interaction detection via adversarial domain generalization. *arXiv preprint arXiv:2005.11406*, 2020.

Ilya Tolstikhin, Olivier Bousquet, Sylvain Gelly, and Bernhard Schoelkopf. Wasserstein autoencoders. *arXiv preprint arXiv:1711.01558*, 2017.

Mark van der Wilk, Matthias Bauer, ST John, and James Hensman. Learning invariances using the marginal likelihood. In *Advances in Neural Information Processing Systems*, pp. 9938–9948, 2018.

Vladimir Vapnik. Principles of risk minimization for learning theory. In *Advances in neural information processing systems*, pp. 831–838, 1992.

Shuxi Zeng, Pengchuan Zhang, Denis Charles, Eren Manavoglu, and Emre Kiciman. Robust neural networks for causal invariant features extraction. NeurIPS 2019 Workshop, "Do the right thing": machine learning and causal inference for improved decision making, December 2019.

Amy Zhang, Clare Lyle, Shagun Sodhani, Angelos Filos, Marta Kwiatkowska, Joelle Pineau, Yarin Gal, and Doina Precup. Invariant causal prediction for block mdps. *arXiv preprint arXiv:2003.06016*, 2020a.

Cheng Zhang, Kun Zhang, and Yingzhen Li. A causal view on robustness of neural networks. *arXiv preprint arXiv:2005.01095*, 2020b.

Kun Zhang, Bernhard Schölkopf, Krikamol Muandet, and Zhikun Wang. Domain adaptation under target and conditional shift. In *International Conference on Machine Learning*, pp. 819–827, 2013.