DECLARATIVE NETS THAT ARE EQUILIBRIUM MODELS

ABSTRACT

Implicit layers are computational modules that output the solution to some problem depending on the input and the layer parameters. The deep equilibrium model (DEQ) outputs a solution to a fixed point equation. On the other hand, deep declarative networks (DDNs) solve an optimisation problem in their forward pass, an arguably more intuitive, interpretable problem than finding a fixed point. We show that using a kernelised generalised linear model (kGLM) as an inner problem in a DDN yields a large class of commonly used DEQ architectures with a closed-form expression for the hidden layer parameters in terms of the kernel. The activation functions have interpretations in terms of the derivative of the log partition function and the Bayesian prior or kernel regulariser. Building on existing literature, we interpret DEQs as fine-tuned, unrolled classical algorithms, giving an intuitive justification for why DEQ models are sensible. We use our theoretical result to devise an initialisation scheme for DEQs that allows them to solve kGLMs in their forward pass at initialisation. We empirically show that this initialisation scheme improves training stability and performance over random initialisation.

1 INTRODUCTION

Implicit layers (Pineda, 1987; Almeida, 1990) have recently been subject to renewed attention (Kolter et al., 2020). In contrast with explicitly defined layers, implicit layers define a mapping in terms of a solution to some problem depending on the input and problem parameters. For example, deep equilibrium models (DEQs) consist of layers that output fixed points of parameterised functions (Bai et al., 2019). Deep declarative networks (DDNs) use declarative nodes which output solutions to optimisation problems (Gould et al., 2016; Amos & Kolter, 2017). Neural ordinary differential equations (NODEs) output solutions to ODEs (Chen et al., 2018; Dupont et al., 2019). Traditional explicit layers can always be represented as implicit layers (for example, see Proposition 4.10 of Gould et al. (2021)). Also, solutions to certain convex optimisation problems may be obtained via an iterative optimisation procedure such as Newton's method or gradient descent, and as such, may be represented as fixed points of an iterative scheme. A correspondence between DDNs and DEQs is expected (but undiscovered), given the fundamental connection between fixed points of iterative maps and critical points of optimisation problems (Ryu & Boyd, 2016). This leads to two natural questions: (1) *Do commonly implemented DEQs correspond with any optimisation problem?* (2) *Can this correspondence be exploited for any theoretical, conceptual, or practical benefit?*

Contributions. (1) We prove an equivalence between a DEQ and a DDN with a classical statistical model — a kernelised generalised linear model (kGLM) — as the declarative node, as illustrated in Figure 1 and formally stated in Theorem 3 and Corollary 6. The weights of the DEQ layer have closed-form expressions in terms of the kernel. The surprise in our result is that the feature mapping involved in this correspondence is exactly the class of hidden layers that are most commonly used in practice. (2) We empirically demonstrate that initialising a DEQ as a DDN using the derived expression for the weights improves performance and stability over random parameter initialisation.

Notation and example implication of result. Let $\mathbb{X} \subseteq \mathbb{R}^{d_x}$ and $\mathbb{Y} \subseteq \mathbb{R}$ be coordinate and target spaces. Define a $\mathbb{Y}-$valued stochastic process $\{y(x, \omega)\}_{x \in \mathbb{X}}$ indexed by elements $x \in \mathbb{X}$ with outcome ω from a sample space Ω. Let $X \in \mathbb{R}^{n \times d_x}$ be a matrix such that the ith row of X is some element $x_i \in \mathbb{R}^{d_x}$. Similarly define $\widetilde{X} \in \mathbb{R}^{\widetilde{n} \times d_x}$. Take n evaluations $\{y_i\}_{i=1}^n = \{y(x_i, \omega_0)\}_{i=1}^n$ from a realisation of the stochastic process for every ith row in X, and form a corresponding matrix Y.

Figure 1: Implicit network modules such as DDNs and DEQs output solutions to problems depending on their inputs and parameters (top). We establish a connection between DDNs with an optimisation layer (middle) and DEQs with a fixed point layer (bottom). Under mild conditions, a DDN that solves a kGLM as its inner problem over dataset (X, Y) and forms predictions at $\widetilde{X}$ (middle) is equivalent to a fully connected or convolutional DEQ accepting a data$point$ Y with underlying fixed coordinates X and $\widetilde{X}$ (bottom). In an inpainting task, the inner yellow and outer regions represent pixel coordinates X and $\widetilde{X}$. Y and $\widetilde{Y}$ represent corresponding image values. The DEQ consists of a fixed point/linear layer with known fixed parameters W_1, W_2, W_3, V_1, V_2 determined by the kernel k and coordinates $X, \widetilde{X}$. The activation functions σ, ρ, T are determined by the exponential family and kernel regulariser of the kGLM. Red indicates that gradient signals are blocked for exact equivalence; equivalence is exact under our initialisation scheme.

Using the same realisation of the stochastic process, take $\widetilde{n}$ evaluations $\{\widetilde{y}_i\}_{i=1}^{\widetilde{n}} = \{y(\widetilde{x}_i, \omega_0)\}_{j=1}^{\widetilde{n}}$ for every ith row in $\widetilde{X}$. We call X and Y the inner coordinate and target data, and $\widetilde{X}$ and $\widetilde{Y}$ the outer coordinate and target data. X and $\widetilde{X}$ encode the positions of corresponding elements in Y and $\widetilde{Y}$, and induce kernel matrices whose utility roughly corresponds with infinite dimensional versions of positional embeddings (Gehring et al., 2017) also used in transformers (Vaswani et al., 2017). The exact manner in which the our models use positional information differs from transformers, but their purpose is the same. Consider the example of image inpainting for a single 32×32 colour image. We might take $\mathbb{X} = \{1, \ldots, 32\}^2 \times \{1, 2, 3\}$, and $X \in \mathbb{Z}_{>0}^{n \times 3}$ to be a matrix consisting of (non-repeated) triples, where $n < 32^2$. We take $\widetilde{X} \in \mathbb{Z}_{>0}^{\widetilde{n} \times 3}$ to be the matrix consisting of remaining triples, such that $n + \widetilde{n} = 32^2 \times 3$. An incomplete image $Y \in \mathbb{R}^n$ together with its missing values $\widetilde{Y} \in \mathbb{R}^{\widetilde{n}}$ are jointly sampled from the same distribution from which CIFAR10 images are drawn. The task of image completion might be performed by using kernel ridge regression or a Gaussian process with Gaussian likelihood to regress $\widetilde{Y}$ given X, Y and $\widetilde{X}$. These models represent special cases of regularised or Bayesian kGLMs whose predictor may be computed in closed form. More general kGLMs require an algorithm to compute the predictor, see Appendix A for more information.

We wrap the kGLM with an outer minimisation loop that compares the loss $\mathcal{L}$ between a neural network $\mathcal{F}_\gamma$ output applied to the kGLM predictor and the target $\widetilde{Y}$ to obtain a DDN, as sketched in Figure 1. We show that such a DDN is equivalent to a DEQ with a closed-form expression for the parameters depending on the kernel. When the kGLM has fixed hyperparameters, the DEQ has a fixed set of parameters (made precise in Theorem 3 and Corollary 6). Initialising the DEQ with these parameters improves training stability and performance, as shown in § 4.

Figure 2: Layers (1) on the interval $[-1, 1]$ when $Y = 0$. Shown in orange is the identity. (a) $\tanh(0.9z + 2)$ has derivative ≤ 0.9 so is a contraction, admitting a unique fixed point. (b) $\tanh(z)$ has derivative less than *or equal to* 1. It satisfies the conditions of Proposition 2 on $(-1, 0)$ and $(0, 1)$ and so admits a unique fixed point. (c) $\tanh(-3z)$ is not a contraction but still admits a unique fixed point; contractions are not necessary. (d, e, f) $\tanh(3z)$, ReLU$(z + 0.2)$, ReLU(z) are not contractions and admit three, zero and uncountably many fixed points.

2 DEEP EQUILIBRIUM MODELS

Given some $Y \in \mathbb{R}^{n \times d_y}$ containing row elements $y \in \mathbb{Y}$, **deep equilibrium models** (DEQs) (Bai et al., 2019) compute an *embedding* $z^* \in \overline{\mathcal{Z}} \subset \mathbb{R}^{n \times d_z}$ as a fixed point of some function and then output an affine transformation $f^*(Y)$ of the fixed point. More concretely, letting $g_\theta(\cdot; Y) : \mathbb{R}^{n \times d_z} \to \mathbb{R}^{n \times d_z}$ denote a parameterised function (e.g. a neural network) with parameters $\theta \in \Theta$,

$$f^*(Y) = Vz^*, \qquad z^* = g_\theta(z^*; Y), \quad z^* \in \overline{\mathcal{Z}} \subset \mathbb{R}^{n \times d_z}, \tag{1}$$

where $V \in \mathbb{R}^{d_u \times (n \times d_z)}$ are referred to as readout parameters, and V may be thought of as a $d_u \times nd_z$ matrix acting on a flattened vector with nd_z entries. We will find it more natural to introduce a linear skip connection between Y and the output. We will also choose $d_y = d_z = 1$. That is, we consider

$$f^*(Y) = V_1 z^* + V_2 Y, \qquad z^* = g_\theta(z^*; Y), \quad z^* \in \overline{\mathcal{Z}} \subset \mathbb{R}^n \tag{2}$$

Typically DEQs are trained in a supervised manner by running some iterative algorithm such as gradient descent on a loss that aims to match a neural network involving $f^*(Y)$ to some target $\widetilde{Y}$ with respect to the DEQ and neural network parameters. Given a dataset $\{(Y_s, \widetilde{Y}_s)\}_{s=1}^N$, this procedure may be realised by running an iterative algorithm over the equality constrained optimisation problem

$$\min_{\gamma, \theta, V_1, V_2} \quad \sum_{s=1}^N \mathcal{L}\left(\widetilde{Y}_s, \mathcal{F}_\gamma\left(f^*(Y_s)\right)\right) \tag{3}$$
$$\text{subject to} \quad z_s^* = g_\theta(z_s^*; Y_s), \qquad f^*(Y_s) = V_1 z_s^* + V_2 Y_s, \qquad s = 1, \dots, N$$

as if the algorithm were to solve the problem, even though it may be highly non-convex. A large class of iterative algorithms requires the derivative with respect to the network parameters θ and V_1, V_2; these may be computed under mild conditions without solving the fixed point equation via implicit differentiation. We refer the reader to Bai et al. (2019) for details.

Dealing with existence and uniqueness of fixed points. In order for (1) and (2) to specify useful computational rules, they have to admit at least one fixed point. To avoid having to choose which fixed point should be returned with additional rules, it might be desirable that they admit exactly one fixed point. We give example configurations of fixed points in Figure 2. The classical Banach fixed point theorem (BFPT) gives sufficient conditions for the existence and uniqueness of fixed points.

Theorem 1 (BFPT). *Let $(\overline{\mathcal{Z}}, d)$ be a complete metric space. A function $H : \overline{\mathcal{Z}} \to \overline{\mathcal{Z}}$ is said to be a contraction if there exists some $0 \leq q < 1$ such that for all $z, z' \in \overline{\mathcal{Z}}$, $d\left(H(z), H(z')\right) \leq qd(z, z')$. Every contraction admits a unique fixed point.*

The contraction property is suggestive of a simple algorithm (Hasselblatt & Katok, 2003) for finding the fixed point z^* of a contraction H given an initial guess z_0: While some termination condition is not met, Update the current estimate z_r for the fixed point to be $f(z_{r-1})$. This algorithm allows one to interpret the inner problem of (3) as an infinitely deep neural network with weights shared between each layer. More advanced algorithms are available, which we do not discuss here.

H is a contraction if the induced matrix norm $\|\cdot\|$ of the Jacobian of H is strictly less than 1 on $\overline{\mathcal{Z}}$, providing a useful test for checking whether a unique fixed point of H exists. More generally,

Proposition 2. *Let $\mathcal{Z}$ be an open strictly convex set, $\overline{\mathcal{Z}}$ its closure, $H : \overline{\mathcal{Z}} \to \overline{\mathcal{Z}}$ differentiable on $\mathcal{Z}$ and continuous on $\overline{\mathcal{Z}}$. If $\|DH\| \leq \lambda < 1$ on $\mathcal{Z}$, then H is a contraction on $\overline{\mathcal{Z}}$.*

$\widetilde{Y}_s$ Y_s Random   kGLM $\widetilde{Y}_s$ Y_s Random   kGLM

Figure 3: Grouped in sets of four. (Left to right) Uncorrupted target image $\widetilde{Y}_s$, noisy image Y_s, image output by randomly initialised DEQ, image output by kGLM initialised DEQ. kGLM but not random initialisation preserves some qualitative properties of the input.

We provide a proof in Appendix B. While elegant, contractions are stronger than necessary and using them limits the set of admissible networks. It is therefore desirable to work with tighter conditions, or otherwise sidestep the issue. A consensus on how to deal with existence and uniqueness does not yet appear to have been reached. One may run the algorithm as if a unique fixed point exists (Bai et al., 2019), constrain or monitor the parameters during learning to ensure that a unique fixed point exists, add a penalisation term on an estimate of the spectral norm of the Jacobian (Roosta-Khorasani & Ascher, 2015) to encourage a contractive map (Bai et al., 2021), or design variants of DEQs that explicitly ensure that a unique fixed point exists (Winston & Kolter, 2020). We do not address this problem; we assume (in a precise sense, see Assumption 3) verifiable conditions for the BFPT.

Initialisation. For the vast majority of practical neural network architectures, learning involves applying an optimisation procedure (e.g. stochastic gradient descent or quasi-Newton's method) to an empirical risk minimisation problem in the overparameterised network's parameters outside of conditions that guarantee convergence to a minimum. Debate continues as to why such procedures lead to good generalisation performance (Belkin et al., 2019; Zhang et al., 2021). However, there are intuitive, empirical and theoretical reasons to suggest that appropriate parameter initialisation plays an important role (Glorot & Bengio, 2010; He et al., 2015; Poole et al., 2016; Hu et al., 2020). For DEQs, initialisations have not yet been studied in great detail. By interpreting DEQs as unrolled kGLMs, we find parameter initialisations as a corollary of our main theoretical result. See Figure 3.

3 EXACT FIXED PARAMETER EQUIVALENCE BETWEEN DDNs AND DEQs

We present our main result here and give a special case of a tractable Ising model in Appendix C.2. Our main result is a derivation of a fully connected or convolutional DEQ architecture as a model that is equivalent to a DDN that solves a kGLM as its inner problem.

3.1 SETTING: A KGLM INSIDE A DDN

Inner problem. We work with the exponential family in canonical form (Deisenroth et al., 2020, Section 6.6), with log partition function $A : \mathbb{R} \to \mathbb{R}$ and sufficient statistic $T : \mathbb{R} \to \mathbb{R}$. We choose a strongly log-concave (Saumard & Wellner, 2014) prior $p_{K/\lambda}$ over evaluations $f(X)$ of a kGLM,

$$p_{K/\lambda}\left(f(X)\right) = q\left(f(X)\right)\phi_{K/\lambda}\left(f(X)\right), \qquad \phi_{K/\lambda}(v) \propto e^{-\frac{\lambda}{2}v^\top K^{-1}v}, \tag{4}$$

where q is a log-concave function and $\phi_{K/\lambda}$ is a Gaussian density with covariance K/λ. The MAP f^* of the kGLM with representer coefficients α^* satisfies

$$\alpha^* = \underset{\alpha \in \mathbb{R}^n}{\arg\min} -\alpha^\top KT(Y) + \mathbb{1}^\top A(K\alpha) - \log p_{K/\lambda}(K\alpha), \qquad f^*(\cdot; X, Y) = k(\cdot, X)\alpha^*. \tag{5}$$

For convenience, we define $\rho :\equiv (-\log q)' \circ (A')^{-1}$, whenever it exists. When q is constant, $p_{K/\lambda}$ is Gaussian and $\rho \equiv 0$ if $(A')^{-1}$ exists. Note (5) is strongly convex in α and admits a unique solution.

Deep declarative network. We will use (5) as a declarative node (Gould et al., 2021) by wrapping it with an outer optimisation task in order to learn the parameters of a neural network by empirical risk minimisation. Let $\mathcal{L}$ denote a loss function (for example, mean squared error), and let $\mathcal{F}_\gamma$ define a generic neural network with parameters γ. Form a set of N quartets $\{(X_s, Y_s, \widetilde{X}_s, \widetilde{Y}_s)\}_{s=1}^N$, for example a set of N images. Define $K_s = k(X_s, X_s)$. We consider the optimisation task

$$\min_\gamma \quad \sum_{s=1}^N \mathcal{L}\Big(\widetilde{Y}_s, \mathcal{F}_\gamma\big(f^*(\widetilde{X}_s; X_s, Y_s)\big)\Big)$$

$$\text{subject to} \quad \alpha_s^* = \arg\min_{\alpha \in \mathbb{R}^n} -\alpha^\top K_s T(Y_s) + \mathbb{1}^\top A(K_s \alpha) - \log p_{K/\lambda}(K_s \alpha), \qquad s = 1, \ldots, N,$$

$$f_s^*(\cdot) = k(\cdot, X_s)\alpha_s^*, \qquad s = 1, \ldots, N,$$

$$\tag{6}$$

where we have used the strong convexity of the N inner problems to ensure a unique solution of the N inner problems. The outer problem is in general non-convex and highly nonlinear in γ.

3.2 MAIN RESULT: DERIVING A FIXED-PARAMETER DEQ

Restricting our attention to the exponential family with strictly convex log partition functions or requiring that the prior (4) is Gaussian (i.e. $q \equiv 1$), z^* may be represented as a solution to a fixed point iteration, whose form may be understood to be an embedding produced by a DEQ. Note that the log partition function A is always convex, and is strictly convex for so-called minimal exponential families.

Assumption 1. *The log partition function A is strictly convex or $q \equiv 1$.*

Under only Assumption 1, the equivalence between the *embeddings* z^* of kGLMs and DEQs holds. Under Assumption 2, we may invert the mapping to obtain α^* from the embeddings z^*, so that the DEQ and the kGLM are equivalent *predictive* models.

Assumption 2. *The log partition function A is strictly convex and the kernel matrix K is strictly positive definite.*

We now state our main result, the proof of which is given in Appendix D.

Theorem 3. *Let α^* be the minimiser of one of the inner optimisation tasks (5), inducing a function $f^*(\cdot; X, Y) = k(\cdot, X)\alpha^*$. Define $z^* := A'(K\alpha^*)$. Under Assumption 1, z^* is a fixed point*

$$z^* = \sigma\big(W_1 z^* + W_2 T(Y) + W_3 \rho(z^*)\big), \tag{7}$$

where $W_1 = W_3 = -\lambda^{-1}K$ and $W_2 = \lambda^{-1}K$ are parameter matrices, $\sigma \equiv A'$ and $\rho \equiv (-\log q)' \circ (A')^{-1}$ are monotone non-decreasing. Furthermore, under Assumption 2, for any test index $\widetilde{X} \in \mathbb{R}^{\widetilde{n} \times d_x}$ and for at least one z^* satisfying (7),

$$f^*(\widetilde{X}; X, Y) = V_1(z^* + \rho(z^*)) + V_2 T(Y), \tag{8}$$

where $V_1 = -\lambda^{-1}k(\widetilde{X}, X)$ and $V_2 = \lambda^{-1}k(\widetilde{X}, X)$.

Further conditions (Assumption 3) force the fixed point iteration to have a unique solution.

Assumption 3. *Let $\mathcal{Z}$ be an open strictly convex set and $\overline{\mathcal{Z}}$ its closure. Suppose $A' : \mathbb{R} \to \overline{\mathcal{Z}}$ is continuous on $\overline{\mathcal{Z}}$ and A' is differentiable on $\mathcal{Z}$. Suppose*

$$(A3.1) \sup_{z \in \mathcal{Z}} |A''(z)| < 1 \qquad \text{and} \qquad (A3.2) \|K/\lambda\| \sup_{z \in \mathcal{Z}} \|I + \text{diag}\rho'(z)\| \le 1.$$

Alternatively, swap the $<$ in A3.1 with the $\le$ in A3.2.

Note that when ρ is constant, i.e. p is Gaussian, A3.2 reduces to $\|K/\lambda\| \le 1$.

Proposition 4. *Under Assumptions 1 and 3, (7) admits a unique fixed point on $\overline{\mathcal{Z}}$.*

The outer problem depends on the solution α_s^* to the inner problem only through $f^*(\widetilde{X}_s; X_s, Y_s)$, which under Assumption 2 in turn only depends on z_s^*. We therefore have the following.

Corollary 5. *Under Assumptions 1, 2 and 3, the optimisation problem (6) is equivalent to the constrained optimisation problem*

$$
\min_{\gamma} \qquad \sum_{s=1}^{N} \mathcal{L}\Big(\widetilde{Y}_s, \mathcal{F}_\gamma\big(f^*(\widetilde{X}_s; X_s, Y_s)\big)\Big)
$$

$$
\textit{subject to} \quad z_s^* = \sigma\big(W_{1s} z_s^* + W_{2s} T(Y_s) + W_{3s}\rho(z_s^*)\big), \qquad s = 1,\ldots,N,
$$

$$
f^*(\widetilde{X}_s; X_s, Y_s) = V_{1s}\big(z_s^* + \rho(z_s^*)\big) + V_{2s} T(Y_s), \qquad s = 1,\ldots,N,
$$

(9)

where $V_{1s} = -\lambda^{-1} k(\widetilde{X}_s, X_s)$, $V_{2s} = \lambda^{-1} k(\widetilde{X}_s, X_s)$, $W_{1s} = W_{3s} = -\lambda^{-1} K_s$ and $W_{2s} = \lambda^{-1} K_s$ take the role of DEQ parameters and $\sigma = A'$ and ρ are monotone non-decreasing and take the role of DEQ activation functions. The fixed point condition for z_s^* is met by exactly one element of $\overline{\mathcal{Z}}$.

The model in Corollary 5 allows the parameters W_{1s}, W_{2s}, V_{1s} and V_{2s} to vary with s whereas (3) does not. An additional assumption ensures these parameters are constant in s.

Corollary 6. *In the same setting as Corollary 5, if $X_s = X$ and $\widetilde{X}_s = \widetilde{X}$ are constant in s, the parameters W_1, W_2, W_3, V_1, V_2 are constant in s and we may write $f^*(Y_s) \equiv f_s^*(\widetilde{X}_s; X_s, Y_s)$.*

Note that in (3), the outer problem is with respect to γ, θ, V_1, V_2 whereas in (9) the outer problem is only with respect to γ. The parameters V_1, V_2 and W_1, W_2 (which take the role of θ), are automatically determined according to X, $\widetilde{X}$ and the kGLM kernel k.

Corollary 5 is suggestive of a DEQ model that we are yet to implement whose weights are a dynamic kernel function of the coordinate X_s. One parameterisation of such a model is to have an auxillary network that predicts a finite-dimensional feature mapping of the coordinates X_s.

3.3 REMARKS ON MATCHING DDNS AND DEQS

Special cases. Choosing $p_{K/\lambda}$ to be Gaussian, $\rho \equiv 0$. Additionally, if T is the identity and $\sigma \equiv A' \equiv \tanh$, we obtain a fully connected layer with $\tanh$ activations, as derived in Appendix C.2. Logistic sigmoidal activations are obtained when the kGLM is specialised as kernel logistic regression. When A' and T are the identity, the kGLM becomes kernel ridge regression, with Gaussian process regression as the corresponding Bayesian model. Certain infinitely *wide* (nonlinear) neural networks are Gaussian processes (Neal, 1995). Our result shows that one may also construct Gaussian processes whose posterior predictive mean is an infinitely *deep* neural network with linear activations. The role of the coordinates X and $\widetilde{X}$ differs between the two models.

Symbol matching. Theorem 3 says that an embedding (2) computed by a DEQ given Y is the same as an embedding (7) computed by a kGLM on coordinates X for a training set (X, Y) if the hidden parameters W_1, W_2 and W_3 are scalar multiples of the kernel matrix $k(X, X)$.

Initialisation via optimisation warm-start. In a stronger setting, Corollary 6 shows a connection between the two optimisation tasks (3) and (9). Given a fixed DEQ architecture with a fixed point condition that may be expressed as (7) (and noting that this equation also includes convolutional architectures), we may initialise parameter values that ensure that the prediction is equivalent to a *trained* kGLM and identify the hyperparameters of the kGLM. This initialisation may be naive (i.e. assume a "reasonable" kernel function, coordinates and regularisation parameter for a wide range of tasks) or more informed (i.e. leverage some information about the task to suit the kernel and regularisation to the task being performed). Note that even without Assumptions 2 and 3, we may initialise the DEQ such that the feature embeddings z^* are equivalent for at least one of the fixed points. We demonstrate both naive and informed approaches in § 4.

On augmentation and assumptions. Assumption 3 allows one to compute without concern using (7) since a unique fixed point is guaranteed to exist. DEQs are sometimes implemented *without* checking that a unique fixed point exists. This assumption may be replaced by any other assumption that is sufficient to ensure a unique fixed point. Using the derivative test on the open set $\mathcal{Z}$ instead of $\overline{\mathcal{Z}}$ allows us to handle important edge cases, namely when $A' \equiv \tanh$ (with derivative 1 at the origin) or A' is Leaky ReLU with gradients in $\{0, 1\}$ on both sides of the origin (with undefined

Figure 4: A particular choice of kernel induces a sparse matrix $K = k(X, X)$ with repeated entries. Pre-multiplication by this sparse matrix (left) is equivalent to convolution with reshaping (right). (Left) The kernel matrix applied to a flattened image. (Right) Each row of the kernel matrix is identical (after zero-padding the image), so that each row's action may be thought of as applying one filter centered at a corresponding pixel. See Corollary 11, Appendix E for result on RGB images.

derivative at the origin). Assumption 2 allows one to map the kGLM embedding to the prediction. The skip connection present in (2) but not (1) is not a severe limitation from a practical perspective. The augmented model considers a coordinate X absent from the original DEQ. Note that any DEQ may be written as an augmented model by simply ignoring the coordinate X. *Under only Assumption 1 and no others, the equivalence between the embeddings produced by kGLMs and DEQs is still valid for at least one of their respective fixed points.*

Convolutional layers. The derived network architecture involves only matrix multiplication, however as is well-known, we may represent a convolution through a sparse matrix equation (Figure 4). Conveniently, the local structure expected in images may be encoded by a particular informed kernel choice in order to recover a convolutional architecture. We formally discuss how this may be done in 2D RGB images in Corollary 11, Appendix E through a particular choice of kernel k.

Other priors. One may replace the strongly log-concave prior $p_{K/\lambda}$ with, for example, the conjugate prior of the exponential family (which is only log-concave). Here we focus on the strongly log-concave prior to recover a form more similar to DEQs that are implemented in practice.

Spectral normalisation. Supposing $\| \cdot \|$ is the spectral norm, Assumption 3 is suggestive of a particular weight normalisation scheme. More precisely, if λ is the spectral norm of K, then A3.2 holds automatically. The technique of using layers with unit spectral norm is explored by Miyato et al. (2018) in the context of improving training stability of GANs. Our results indicate that such spectral normalisation also leads to improved stability in DEQs at initialisation, in the sense that it guarantees a unique fixed point by Proposition 4. Abusing terminology, we refer to the spectral norm of the linear transformation corresponding with a convolutional layer as the spectral norm of the convolutional layer. An easy to implement method for calculating the spectral norm of convolutional layers is available (Sedghi et al., 2018), which we use in our implementation and experiments.

4 EXPERIMENTS

DEQ parameters may be partitioned into two sets: the parameters of the layer that defines the fixed point iteration ($\theta = (W_1, W_2, W_3, V_1, V_2)$), and the remainder of the parameters. Leveraging our theoretical result, we give DEQs a warm-start by initialising θ such that the DEQ solves a kGLM.

We empirically demonstrate that such initialisation is superior to random intialisation. We stress that our comparison is between randomly initialised DEQs and kGLM initialised DEQs *only*. We are not interested in demonstrating that DEQs can achieve results competitive with state-of-the-art models, as this has already been demonstrated in previous studies (Bai et al., 2019; 2021). Our limited scope allows us to perform a more definitive empirical study with meaningful statistics examining the differences between random and kGLM initialisation. We give a detailed explanation of two of the tasks in the main text, and refer the reader to Appendix F for more experiments. For random initialisation, we initialise weights from a symmetric uniform distribution (the Pytorch default).

Smooth sequence-to-sequence task. Let $\mathbb{X} = [-2\pi - 2, 2\pi]$ and define a function $h(x) = e^{-x^2/10} \sin(x) + e^{-(x+9)^2}$. Let $X_s = X$ and $\widetilde{X}_s = \widetilde{X}$ be 100 points on a uniform

(a)   (b)

Figure 5: (a) Test error on a smooth sequence-to-sequence task for 100 random seeds for each initialisation scheme. kGLM initialsation offers a better starting point and faster training than random initialisation. (b) Sample model outputs on smooth sequence-to-sequence task. Black curves show mean h and colours represent different samples. (Top left) Ground-truth test data $\widetilde{Y}_s$. (Top right) `Random` and (Bottom left) `Naive GLM` initialisation after 20 epochs. (Bottom right) `Informed kGLM` initialisation without any training (i.e. epoch 0). kGLM initialisation, particularly informed, preserves some of the qualitative properties of the target sequence.

grid in $[-2\pi, 2\pi]$ and $[-2\pi - 2, 2\pi - 2]$ respectively. Define sequences Y_s and $\widetilde{Y}_s$ to be joint evaluations of the sth realisation of a Gaussian process with covariance function $k_{\text{true}}(x, x') = 0.1 \exp \frac{-\|x-x'\|^2}{2} \exp\left(-\sin^2\|x-x'\|\right)$, having means $h(X)$ and $h(\widetilde{X})$ respectively.

For `informed kGLM` initialisation, we pretend that we know the kernel and coordinate space. We choose $k \equiv k_{\text{true}}$ and form the required kernel matrices by taking $X_s = X$ and $\widetilde{X}_s = \widetilde{X}$. For `naive GLM` initialisation, pretending we do not know the true underlying kernel or coordinate space, we default to $k_{\text{naive}} = \exp \frac{-\|x-x'\|^2}{2}$ and choose $X_s = X$ to be a uniform grid over the interval $[-2\pi, 2\pi]$. We initialise the hidden parameters W_1 and W_2 according to Theorem 3 and initialise V_1 and V_2 according to the same rule as `random` initialisation. When training using `naive GLM`, we update only the readout parameters for the first 10 epochs.

We generate a training and test set of size $N = 20,000$ and $2,000$. Each sequence is evaluated on an $n = 100$ dimensional uniform grid. We choose $g_\theta(z^*) = \tanh\left(W_1 z^* + W_2 Y + b\right)$ and train for 400 epochs using Adam with default hyperparameters. We repeat this for 100 trials using seeds 0 to 99 and collect the test error curves for each trial. See Figure 5(a) and (b).

Image denoising. We consider a convolutional architecture as described in Appendix E, with $\sigma \equiv$ ReLU, T the identity, and $\rho \equiv 0$ applied to an image denoising task using the CIFAR10 dataset. The coordinate space $\mathbb{X}$ is the space of all 2D pixel and channel triples $(i, j, c) \in \{1, \ldots, 32\}^2 \times \{1, 2, 3\}$. Elements Y_s are CIFAR10 images corrupted by i.i.d. additive $\mathcal{N}(0, 0.2)$ noise, clipped to take values between 0 and 1. Elements $\widetilde{Y}_s$ are the corresponding uncorrupted CIFAR10 images.

For random initialisation, we sample the filter weights $\overset{i.i.d.}{\sim} \mathcal{N}(0, \text{Var})$. For kGLM initialisation, we let $\lambda = \|K\|/C$, where $\|\cdot\|$ denotes the spectral norm and $C > 0$ (see Assumption 3). Spectral norms are calculated using the fast and exact method described by Sedghi et al. (2018). The kernel is constructed randomly from the squared exponential kernel and described in Appendix F.

We are interested in separating the effects of the choice of scaling and initialisation scheme. For random initialisation, the scale is chosen through the variance, inducing a convolutional layer with *random* spectral norm. For kGLM initialisation, the scale C is *equal to* the spectral norm. We try all variances in logspace($10^{-3}, 1, 25$) and all C in logspace($10^{-2}, 10, 25$), which results in a grid of spectral norms covering roughly the same space for both initialisation schemes. We try 100 different random seeds for each configuration, resulting in $2 \times 100 \times 25 = 5000$ different models.

In Figure 6, we plot individually after training for $0, \ldots, 5$ epochs the test MSE against the spectral norm for both initialisation schemes and all random seeds. kGLM initialisation offers improved test error, training stability and reduced variance in test error. The curves for kGLM initialised models adhere to the shape predicted by classical generalisation theory, where the spectral norm

Figure 6: Test MSE against the average spectral norm of each layer for image denoising task using kGLM initialisation (blue, ours) and random initialisation (red). The vertical axes change between plots. Markers at the edge of the top border indicate that a value greater than the axis limit or NaN was observed. Our initialisation scheme shows superior performance at all epochs.

measures model complexity. For kGLM initialisation, spectral norms of 10^0 appear to represent a critical point; smaller values lead to stable training and larger values lead to unstable training. This contrasts with randomly initialised models, most of which have increasing test error with increasing spectral norm in their later epochs. This means it is easy to select an appropriate scale for kGLM initialisation, but not for random initialisation. In Figure 3, we plot sample targets, inputs and outputs for random and kGLM initialised DEQs without any training, showing that samples using kGLM initialisation are visually more similar to the expected output than random initialisation. Figure 3 and epoch 0 of Figure 6 provide a sanity check of Theorem 3. More plots are given in Appendix F.

5 DISCUSSION AND CONCLUSION

Related work. A review on connections between other optimisation-based iterative procedures and neural networks generally is given by Monga et al. (2021). Repeated applications of weight-tied layers can sometimes be seen as solving model-based problems, if the weights are chosen appropriately. Since the derived network implicitly minimises a conceptually tractable and principled model, it possesses a certain degree of interpretability. However, only the minimisation problems and not the forward pass computations of the network are interpretable, and as such the network does not satisfy the requirements of interpretability in many settings (Rudin, 2019). Monga et al. (2021) also discuss how disabling weight-tying and allowing parameters to be fine-tuned, thereby escaping the optimisation-based iterative procedure, can sometimes lead to improved performance, perhaps at the cost of interpretability, generalisation performance and theoretical guarantees.

Notable models analysed under this framework include ISTA (Beck & Teboulle, 2009) for solving LASSO, which when unrolled and fine-tuned yields LISTA (Gregor & LeCun, 2010), and ADMM for compressive sensing (Boyd et al., 2011) with an unrolled version called ADMM-CSNet (Yang et al., 2018). Our work considers a different class of iterative models to those surveyed by Monga et al. (2021), and recovers exactly the DEQ model. In previous works, the architectures, tasks, model classes and activations are specific to a particular setting. We consider a relatively broad class of kGLMs, inducing a large class of DEQs, tasks, nonparametric model classes and activations.

Conclusion. By inserting a kGLM as an inner problem inside a DDN, we derived a DEQ with a convolutional or fully connected implicit layer and a fixed closed-form expression for the weights. Such a result gives intuitive justification for computing with DEQ models: DEQs can solve classical statistical problems in their forward pass. Using this theoretical connection also allowed us to initialise DEQ parameters and obtain performance improvements over random initialisation.

ETHICS STATEMENT

Our work is mostly theoretical in nature and is unlikely to directly cause harm, discrimination or privacy violations. However, as our work may be used in future in applications, we encourage users of our work to adhere to ICLR's general ethical principles. We welcome open enquiry and scrutiny of the theoretical results presented in this paper.

REPRODUCIBILITY STATEMENT

We have included code and the instructions required to reproduce our results in the supplementary material. The code will be made publically available upon acceptance.

REFERENCES

Luis B Almeida. A learning rule for asynchronous perceptrons with feedback in a combinatorial environment. In *Artificial neural networks: concept learning*, pp. 102–111, 1990.

Brandon Amos and J Zico Kolter. Optnet: Differentiable optimization as a layer in neural networks. In *International Conference on Machine Learning*, pp. 136–145. PMLR, 2017.

Shaojie Bai, J Zico Kolter, and Vladlen Koltun. Deep equilibrium models. *Advances in Neural Information Processing Systems*, 32:690–701, 2019.

Shaojie Bai, Vladlen Koltun, and Zico Kolter. Stabilizing equilibrium models by jacobian regularization. In *International Conference on Machine Learning*, pp. 554–565. PMLR, 2021.

Amir Beck and Marc Teboulle. A fast iterative shrinkage-thresholding algorithm for linear inverse problems. *SIAM journal on imaging sciences*, 2(1):183–202, 2009.

Mikhail Belkin, Daniel Hsu, Siyuan Ma, and Soumik Mandal. Reconciling modern machine-learning practice and the classical bias–variance trade-off. *Proceedings of the National Academy of Sciences*, 116(32):15849–15854, 2019.

Stephen Boyd, Neal Parikh, and Eric Chu. *Distributed optimization and statistical learning via the alternating direction method of multipliers*. Now Publishers Inc, 2011.

Stéphane Canu and Alex Smola. Kernel methods and the exponential family. *Neurocomputing*, 69 (7-9):714–720, 2006.

Gavin C Cawley, Gareth J Janacek, and Nicola LC Talbot. Generalised kernel machines. In *2007 International Joint Conference on Neural Networks*, pp. 1720–1725. IEEE, 2007.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 6572–6583, 2018.

Marc Peter Deisenroth, A Aldo Faisal, and Cheng Soon Ong. *Mathematics for Machine Learning*. Cambridge University Press, 2020.

Emilien Dupont, Arnaud Doucet, and Yee Whye Teh. Augmented neural odes. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pp. 3140–3150, 2019.

Jonas Gehring, Michael Auli, David Grangier, Denis Yarats, and Yann N Dauphin. Convolutional sequence to sequence learning. In *International Conference on Machine Learning*, pp. 1243–1252. PMLR, 2017.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256. JMLR Workshop and Conference Proceedings, 2010.

Stephen Gould, Basura Fernando, Anoop Cherian, Peter Anderson, Rodrigo Santa Cruz, and Edison Guo. On differentiating parameterized argmin and argmax problems with application to bi-level optimization. *arXiv preprint arXiv:1607.05447*, 2016.

Stephen Gould, Richard Hartley, and Dylan John Campbell. Deep declarative networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *Proceedings of the 27th international conference on international conference on machine learning*, pp. 399–406, 2010.

Boris Hasselblatt and Anatole Katok. *A first course in dynamics: with a panorama of recent developments*. Cambridge University Press, 2003.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Wei Hu, Lechao Xiao, and Jeffrey Pennington. Provable benefit of orthogonal initialization in optimizing deep linear networks. In *International Conference on Learning Representations*, 2020.

Z Kolter, D Duvenaud, and M Johnson. Deep implicit layers - neural odes, deep equilibrium models, and beyond. Neural information processing systems tutorial, 2020. URL http://implicit-layers-tutorial.org/.

Jiarou Lu, Huafeng Liu, Yazhou Yao, Shuyin Tao, Zhenmin Tang, and Jianfeng Lu. Hsi road: A hyper spectral image dataset for road segmentation. In *IEEE International Conference on Multimedia and Expo (ICME)*, 2020.

P. McCullagh and J.A. Nelder. *Generalized Linear Models, Second Edition*. Chapman & Hall/CRC Monographs on Statistics & Applied Probability. Taylor & Francis, 1989. ISBN 9780412317606. URL https://books.google.com.au/books?id=h9kFH2_FfBkC.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018.

Vishal Monga, Yuelong Li, and Yonina C Eldar. Algorithm unrolling: Interpretable, efficient deep learning for signal and image processing. *IEEE Signal Processing Magazine*, 38(2):18–44, 2021.

Radford M Neal. *Bayesian learning for neural networks*. PhD thesis, University of Toronto, 1995.

H Chau Nguyen, Riccardo Zecchina, and Johannes Berg. Inverse statistical problems: from the inverse ising problem to data science. *Advances in Physics*, 66(3):197–261, 2017.

Fernando Pineda. Generalization of back propagation to recurrent and higher order neural networks. In *Neural information processing systems*, pp. 602–611, 1987.

Ben Poole, Subhaneil Lahiri, Maithra Raghu, Jascha Sohl-Dickstein, and Surya Ganguli. Exponential expressivity in deep neural networks through transient chaos. *Advances in neural information processing systems*, 29:3360–3368, 2016.

Farbod Roosta-Khorasani and Uri Ascher. Improved bounds on sample size for implicit matrix trace estimators. *Foundations of Computational Mathematics*, 15(5):1187–1212, 2015.

Cynthia Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019.

Ernest K Ryu and Stephen Boyd. Primer on monotone operator methods. *Appl. Comput. Math*, 15 (1):3–43, 2016.

Adrien Saumard and Jon A Wellner. Log-concavity and strong log-concavity: a review. *Statistics surveys*, 8:45, 2014.

Craig Saunders, Alexander Gammerman, and Volodya Vovk. Ridge regression learning algorithm in dual variables. In *Proceedings of the Fifteenth International Conference on Machine Learning*, pp. 515–521, 1998.

Bernhard Schölkopf, Alexander J Smola, et al. Learning with kernels: support vector machines, regularization. *Optimization, and Beyond. MIT press*, 1(2), 2002.

Hanie Sedghi, Vineet Gupta, and Philip M Long. The singular values of convolutional layers. In *International Conference on Learning Representations*, 2018.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

Ezra Winston and J Zico Kolter. Monotone operator equilibrium networks. *Advances in Neural Information Processing Systems*, 33:10718–10728, 2020.

Yan Yang, Jian Sun, Huibin Li, and Zongben Xu. Admm-csnet: A deep learning approach for image compressive sensing. *IEEE transactions on pattern analysis and machine intelligence*, 42 (3):521–538, 2018.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning (still) requires rethinking generalization. *Communications of the ACM*, 64(3):107–115, 2021.

Ji Zhu and Trevor Hastie. Kernel logistic regression and the import vector machine. *Journal of Computational and Graphical Statistics*, 14(1):185–205, 2005.

A   KERNELISED GENERALISED LINEAR MODELS

A.1   KERNEL TRICK AND REPRESENTER THEOREM

The predictions of some classical algorithms depend on the training input data $X \in \mathbb{R}^{n \times d_x}$ only through the matrix product $XX^\top$. A widely exploited technique in machine learning, the kernel trick, replaces X with $\psi(X) \in \mathbb{R}^{n \times d_\psi}$, where d_ψ may be large or in fact infinite. Here $\psi : \mathbb{R}^{d_x} \to \mathbb{R}^{d_\psi}$ and with an abuse of notation, when applied to a matrix it is understood to apply individually to each row so that $\psi(X) \in \mathbb{R}^{n \times d_\psi}$. It is easy to change the resulting predictor since the type of $\psi(X)\psi(X)^\top \in \mathbb{R}^{n \times n}$ matches that of $XX^\top$, and scales with n and not d_ψ. One example is in kernel ridge regression (Saunders et al., 1998). Following our abuse of notation, we will use $k(X, X) \in \mathbb{R}^{n \times n}$ to denote the matrix with ijth entry $k(x_i, x_j) := \psi(x_i)^\top \psi(x_j)$. Any function of the form k together with the matrix X characterises the matrix $\psi(X)\psi(X)^\top$. Such a function is called a kernel function, and is a valid choice if and only if it corresponds with an inner product in feature space or equivalently, if it is positive semi-definite (PSD). The space of functions $\mathcal{H}_k$ that the kernel k characterises is called a reproducing kernel Hilbert space (RKHS).

Let k be a positive semi-definite (PSD) function inducing a reproducing kernel Hilbert space (RKHS) $\mathcal{H}_k$. We will use $K = k(X, X) \in \mathbb{R}^{n \times n}$ to denote the matrix with ijth entry $k(x_i, x_j)$. We will make use of the representer theorem, which for appropriately regularised empirical risk minimisation problems, allows one to solve optimisation problems in nonparametric function space.

Theorem 7 (Representer Theorem (Schölkopf et al., 2002)). *Denote by $R : [0, \infty) \to \mathbb{R}$ a strictly monotonic increasing function, by $\mathbb{X}$ a set and by $L : (\mathbb{X} \times \mathbb{R}^2)^n \to \mathbb{R} \bigcup \{\infty\}$ an arbitrary loss function. Let $\mathcal{H}_k$ be an RKHS with kernel k. Then*

$$f^* \in \underset{f \in \mathcal{H}_k}{\arg\min} \, L\Big(\big\{\big(x_i, y_i, f(x_i)\big)\big\}_{i=1}^n\Big) + R\left(\|f\|_{\mathcal{H}_k}\right) \quad \implies \quad f^*(x) = \sum_{i=1}^n \alpha_i k(x_i, x).$$

A.2   KERNELISED GENERALISED LINEAR MODELS

We work with the exponential family in canonical form (Deisenroth et al., 2020, Section 6.6), as shown in equation 10. As has also been noted by others (Canu & Smola, 2006; Cawley et al., 2007), the representer theorem allows one to extend appropriately regularised GLMs (McCullagh & Nelder, 1989) to kGLMs by replacing the linear predictor with an arbitrary element of an RKHS. Here we demonstrate this fact.

Generalised linear models use an exponential family for the likelihood of observing response y_i. The exponential family in canonical form is

$$p(y_i \mid \eta_i) = h(y_i) \exp\left(\eta_i T(y_i) - A(\eta_i)\right), \tag{10}$$

where $h : \mathbb{R} \to \mathbb{R}$, $A : \mathbb{R} \to \mathbb{R}$, and $T : \mathbb{R} \to \mathbb{R}$ are functions that must be chosen such that the resulting density (mass function) integrates (sums) to 1. The *log-partition function A* is always convex. Here η_i are called the natural parameters of the distribution. We work exclusively with univariate responses y_i and canonical parameters η_i, but GLMs are constructed more generally. For GLMs with a canonical link function, one chooses $\eta_i = x_i^\top \beta = f(x_i)$ to be a linear function of the predictor variables x_i with parameters $\beta \in \mathbb{R}^{d_x}$.

It is possible to extend GLMs to accommodate a non-linear predictor f in an RKHS $\mathcal{H}_k$ with a small modification. This modification can be motivated by either a Bayesian or frequentist perspective by placing a Gaussian prior over the function values or regularising respectively, and then solving the resulting functional optimisation problem over an RKHS using the representer theorem. Following the former philosophy, the *maximum a posteriori* (MAP) estimate f^* of $p\big(f(X) \mid Y\big)$ with a particular prior with parameter λ satisfies

$$f^* = \underset{f \in \mathcal{H}_k}{\arg\min} \sum_{j=1}^n -\log h(y_i) + A\left(f(x_i)\right) - f(x_i)T(y_i) + \frac{\lambda}{2}\|f\|_{\mathcal{H}_k}^2,$$

so that by the representer theorem,

$$f^*(\cdot) = k(\cdot, X)\alpha^* \quad \text{where} \quad \alpha^* = \underset{\alpha \in \mathbb{R}^n}{\arg\min} \, \mathbb{1}^\top A\left(K\alpha\right) - \alpha^\top K T(Y) + \frac{\lambda}{2}\alpha^\top K\alpha, \quad K = k(X, X).$$

As an example, in binary kernel logistic regression, using the representer theorem we seek to minimise

$$-\log p\left(f(X) \mid Y\right) = -Y^\top K\alpha^* + \mathbb{1}^\top \log\left(\mathbb{1} + e^{K\alpha^*}\right) + \frac{\lambda}{2}\alpha^{*\top}K\alpha^*,$$

where $K = K(X, X) \in \mathbb{R}^{n \times n}$ is the kernel matrix with pqth entry $K_{pq} = k(x_p, x_q)$. The solution can be found by applying Newton's method, resulting in an iterative fixed-point numerical scheme for α^*. Details of this method can be found in a number of references (Zhu & Hastie, 2005). A detailed example of the Ising model is given in Appendix C.

B DERIVATIVE TEST

We will require the mean value theorem.

Theorem 8 (Mean value theorem). *Let $S : [a, b] \to \mathbb{R}^n$ be continuous on $[a, b]$ and differentiable on (a, b). Then there exists some $t \in (a, b)$ such that*

$$\|S(b) - S(a)\| \leq \left\| \frac{d}{dt} S(t) \right\| (b - a).$$

We now restate the result to be proven. We follow the approach in theorem 2.2.16 of Hasselblatt & Katok (2003).

Proposition 2. *Let $\mathcal{Z}$ be an open strictly convex set, $\overline{\mathcal{Z}}$ its closure, $H : \overline{\mathcal{Z}} \to \overline{\mathcal{Z}}$ differentiable on $\mathcal{Z}$ and continuous on $\overline{\mathcal{Z}}$. If $\|DH\| \leq \lambda < 1$ on $\mathcal{Z}$, then H is a contraction on $\overline{\mathcal{Z}}$.*

Proof. Let $z_1, z_2 \in \overline{\mathcal{Z}}$ and define $c(t) := z_1 + t(z_2 - z_1)$ for $t \in [0, 1]$ and $S(t) := H\big(S(t)\big)$. Then $S : (0, 1) \to \mathcal{Z}$ by strict convexity. By the mean value theorem, there exists some $t \in (0, 1)$ such that

$$
\begin{aligned}
\|H(z_2) - H(z_1)\| = \|S(1) - S(0)\| \leq \left\| \frac{d}{dt} S(t) \right\| (1 - 0) &= \left\| \frac{d}{dt} S(t) \right\| \\
&= \left\| DH\left(S(t)\right) \frac{d}{dt} c(t) \right\| \\
&= \| DH\left(S(t)\right) (z_2 - z_1) \| \\
&\leq \| DH\left(S(t)\right) \| \, \| z_2 - z_1 \| \\
&\leq \lambda \, \| z_2 - z_1 \| \\
&< \| z_2 - z_1 \|
\end{aligned}
$$

and therefore H is a contraction mapping. $\qquad\square$

C   WARM-UP: A TRACTABLE ISING MODEL

We demonstrate our main result for a special Ising model case. The general case is given in § 3.

C.1   AS A κGLM

Let x and x' be two dimensional indices on the finite lattice, $x \in \{1, \dots, a\} \times \{1, \dots, b\}$ for integers $a, b \in \mathbb{Z}$. The Ising model prescribes that

$$p\left(Y \mid f(X)\right) = Z^{-1} \exp\left(t^{-1}\left(\sum_{pq} J_{pq} y_{ip} y_{iq} + \sum_p f_{x_{ip}} y_{ip}\right)\right),$$

where Z is the partition function, some normalising constant ensuring that $p\left(Y \mid f(X)\right)$ is a valid probability mass function. Here the parameters J_{pq} determine interactions between the spin states y_{ip} and y_{iq}, $f_{x_{ip}}$ controls an interaction between the spin state y_{ip} and an external magnetic field at lattice position x_{ip} and t is a temperature parameter. We let $f_x = f(x)$ belong to an RKHS $\mathcal{H}_k$ with PSD kernel k. With a standard Gaussian prior over f, we have that

$$\log p\left(f(X) \mid Y\right) = t^{-1}\left(\sum_{p,q} J_{p,q} y_{ip} y_{iq} + \sum_p f(x_{ip}) y_{ip}\right) - \log Z - \lambda/2 \|f\|_{\mathcal{H}_k}^2.$$

Supposing no interactions, $J_{pq} = 0$ and $Z = 2\cosh\left(t^{-1} f(x_{ip})\right)$ (Nguyen et al., 2017). By Theorem 7, letting $K = t^{-1} k(X, X)$ denote the matrix with pqth entry $t^{-1} k(x_{ip}, x_{iq})$,

$$\alpha^* = \arg\min_\alpha -Y^\top K \alpha + \mathbb{1}^\top \log\left(2\cosh\left(K\alpha\right)\right) + \frac{t\lambda}{2} \alpha^\top K \alpha.$$

The problem is strictly convex so we may find the solution by applying Newton's method. Using that the derivative of $\log\left(2\cosh(\cdot)\right)$ is $\tanh(\cdot)$, stationarity of the solution implies that

$$\mathbf{0} = -KY + K\tanh\left(K\alpha^*\right) + t\lambda K\alpha^* := F(\alpha^*). \tag{11}$$

The Jacobian $\frac{\partial F}{\partial \alpha^*}$ is given by

$$J(\alpha^*) := \frac{\partial F}{\partial \alpha^*} = K^\top D K + t\lambda K, \qquad \text{where } D := \text{diag}\left(\text{sech}^2(K\alpha^*)\right),$$

so that the cth Newton iteration requires solving a linear system,

$$J(\alpha^*_{(c-1)})\left(\alpha^*_{(c)} - \alpha^*_{(c-1)}\right) = K\left(Y - \tanh\left(K\alpha^*_{(c-1)}\right) - t\lambda\alpha^*_{(c-1)}\right).$$

We employ the shorthand $M(\alpha^*_{(c)}) = M_{(c)}$ for any matrix function of $\alpha^*_{(c)}$. The Newton update is typically rearranged as an Iteratively Re-Weighted Least Squares (IRWLS) form by substituting $\alpha^*_{(c-1)} = J_{(c-1)}^{-1} J_{(c-1)} \alpha^*_{(c-1)}$, yielding

$$J_{(c-1)} \alpha^*_{(c)} = K D_{(c-1)} z_{(c-1)},$$

where $z := K\alpha + D^{-1}(Y - \mu)$ and $\mu = \tanh\left(K\alpha^*\right)$. Once α^* has been approximated to some tolerance using this numerical scheme, the predictor f_* may be evaluated at points $\widetilde{X} \in \mathbb{R}^{\widetilde{n} \times d_x}$ using the representer theorem,

$$f(\widetilde{X}) = t\widetilde{K}\alpha^* \in \mathbb{R}^{n_*}, \quad \widetilde{K} := t^{-1} k(\widetilde{X}, X). \tag{12}$$

C.2   AS A DEQ

Rearranging (11), and applying $\tanh$ to both sides of the equation, we obtain

$$\tanh\left(K\alpha^*\right) = \tanh\left(\frac{1}{t\lambda} K\left(Y - \tanh\left(K\alpha^*\right)\right)\right).$$

Choosing $z_* = \tanh\left(K\alpha^*\right)$, $W_1 = -(t\lambda)^{-1} K$, $W_2 = (t\lambda)^{-1} K$, we have

$$z_* = \tanh\left(W_1 z_* + W_2 Y\right). \tag{13}$$

Note that α^* being a unique fixed point of (11) implies that z_* is a fixed point of (13), but not that the fixed point of (13) is necessarily unique. One condition that guarantees the uniqueness of the fixed point of (13) is that the induced matrix norm of K is less than or equal to 1. Without this assumption, (13) is still true but when used as a computational model, the output will in general depend on the fixed-point solver and initial conditions passed to that solver (and even still, might never return unstable fixed points). Finally by assuming that K is invertible and using (12), we obtain

$$f(Y) = t\widetilde{K}\alpha^* = t\widetilde{K}K^{-1}\tanh^{-1} z_* = \frac{1}{\lambda}\widetilde{K}\left(Y - z_*\right) = V_1 z_* + V_2 Y,$$

where $V_1 = -(\lambda)^{-1}\widetilde{K}$ and $V_2 = (\lambda)^{-1}\widetilde{K}$.

D   PROOF OF MAIN RESULT

Theorem 3. *Let α^* be the minimiser of one of the inner optimisation tasks (5), inducing a function $f^*(\cdot; X, Y) = k(\cdot, X)\alpha^*$. Define $z^* := A'(K\alpha^*)$. Under Assumption 1, z^* is a fixed point*

$$z^* = \sigma\big(W_1 z^* + W_2 T(Y) + W_3 \rho(z^*)\big), \tag{7}$$

where $W_1 = W_3 = -\lambda^{-1}K$ and $W_2 = \lambda^{-1}K$ are parameter matrices, $\sigma \equiv A'$ and $\rho \equiv (-\log q)' \circ (A')^{-1}$ are monotone non-decreasing. Furthermore, under Assumption 2, for any test index $\widetilde{X} \in \mathbb{R}^{\widetilde{n} \times d_x}$ and for at least one z^* satisfying (7),

$$f^*(\widetilde{X}; X, Y) = V_1\left(z^* + \rho(z^*)\right) + V_2 T(Y), \tag{8}$$

where $V_1 = -\lambda^{-1} k(\widetilde{X}, X)$ and $V_2 = \lambda^{-1} k(\widetilde{X}, X)$.

Proof. Suppose A is strictly convex, implying $A' = \sigma$ strictly increasing and invertible. $Q := -\log q(\cdot)$ is a convex function, and its derivative Q' is monotone nondecreasing. Also note that $Q' \circ (A')^{-1}$ is monotone nondecreasing. Let $K = k(X, X)$. From (5), stationarity at the minimum and the representer theorem implies

$$\mathbf{0} = -KT(Y) + KA'(K\alpha^*) + KQ'(K\alpha^*) + \lambda K\alpha^*$$

$$K\alpha^* = \frac{1}{\lambda}\left(KT(Y) - KA'(K\alpha^*) - KQ'(K\alpha^*)\right)$$

$$A'(K\alpha^*) = A'\left(\frac{1}{\lambda}\left(KT(Y) - KA'(K\alpha^*) - KQ'(K\alpha^*)\right)\right)$$

$$A'(K\alpha^*) = A'\left(\frac{1}{\lambda}\left(KT(Y) - KA'(K\alpha^*) - KQ' \circ (A')^{-1} \circ A'(K\alpha^*)\right)\right) \tag{14}$$

$$z_* = \sigma\big(W_1 z_* + W_2 T(Y) + W_3 \rho(z_*)\big). \tag{15}$$

Note a subtlety in moving from (14) to (15). Since A is strictly convex, α^* is the unique fixed point of (14). However, z_* is only a (not necessarily unique) fixed point of (15). If A is not strictly convex but $q \equiv 1$, the above again holds $Q' \equiv 0$ and without the need to invert A'.

Suppose Assumption 2. Since K is invertible, and σ is invertible (since A is strictly convex), then again using the representer theorem, new predictions may be formed as

$$\widetilde{K}\alpha^* = \widetilde{K}K^{-1}\sigma^{-1}z_* = \frac{1}{\lambda}\widetilde{K}\left(T(Y) - z_* - \rho(z_*)\right) = V_1\left(z_* + \rho(z_*)\right) + V_2 T(Y),$$

where $\widetilde{K} = k(\widetilde{X}, X)$.

$\square$

Proposition 4. *Under Assumptions 1 and 3, (7) admits a unique fixed point on $\overline{\mathcal{Z}}$.*

Proof. Let H be the mapping defined by iteration (15),

$$H(z_*) = \sigma\big(W_1 z_* + W_2 T(Y) + W_3 \rho(z_*)\big).$$

H is a contraction since the induced matrix norm of the Jacobian of H satisfies

$$\|DH\| = \left\|\left(W_1 + W_3 \mathrm{diag}\rho'(z_*)\right)\mathrm{diag}\sigma'\big(W_1 z_* + W_2 T(Y)\big)\right\|$$
$$\leq \|K/\lambda\| \sup_{z \in \mathcal{Z}} \|I + \mathrm{diag}\rho'(z)\| \sup_{z \in \mathcal{Z}} |A''(z)|$$
$$< 1.$$

The result follows from Theorem 1.

$\square$

Figure 7: Connections between implicit layer architectures.

E CONVOLUTION AS MATRIX MULTIPLICATION

Let $w, h \in \mathbb{Z}_{>1}$ denote the pixel width and height of a space of images with c channels. Let

$$\mathbb{X}_{wh} = \{1, \ldots, h\} \times \{0, \ldots, w\}, \qquad \mathbb{X}_{whc} = \mathbb{X}_{wh} \times \{1, \ldots, c\} \tag{16}$$

denote the corresponding pixel and pixel-channel spaces. Let $X \in \mathbb{R}^{(whc) \times 1\}}$ denote a matrix, where every row is one of the pixel coordinates $(i, j, c) \in \mathbb{X}_{whc}$. Choose $X_s = X$ for some set of N images $\{Y_s\}_{s=1}^N$. The images Y_s are of size whc, and contain pixel intensities for the corresponding pixel coordinates in X.

Let x_1, x_2 and x_3 denote the first, second and third coordinates of an element $x \in \mathbb{X}_{whc}$. Let

$$h_1(x, x') = \mathbb{1}(|x_1 - x_1'| \leq r_1),$$
$$h_2(x, x') = \mathbb{1}(|x_2 - x_2'| \leq r_2),$$

where $\mathbb{1}$ is the indicator function for some truncating parameters $r_1, r_2 > 0$. Let $\kappa_0 : \mathbb{X}_{whc} \times \mathbb{X}_{whc} \to \mathbb{R}$ denote any stationary PSD kernel, for example $\kappa_0(x, x) = e^{-\frac{1}{2}\|x - x'\|_2^2}$. Note that these functions each define a PSD kernel. Using the fact that kernels are closed under multiplication, define

$$\kappa(x, x') := h_1(x, x')h_2(x, x')\kappa_0(x, x'). \tag{17}$$

Here h_1 and h_2 ensure that only close pixels have non-zero kernel values.

Note that the matrix $\kappa(X, X)$ is sparse when r_1 or r_2 are small and has an off-diagonal structure. More concretely choosing $\kappa(x, x') = e^{-\frac{1}{20}\|[x_1, x_2] - [x_1', x_2']\|_2^2} \mathbb{1}(\|x - x'\|_\infty \leq 5)$ where $\|\cdot\|_\infty$ denotes the supremum norm, we obtain a $whc \times whc$ matrix. Each block of size wh is repeated horizontally.

This matrix represents c convolutional filters of filter length $5 \times 2 + 1 = 11$ in both directions. We plot the induced $32^2 \times 32^2$ kernel matrix when $w = h = 32$ and $c = 1$ in Figure 4, as well as the corresponding operation as a convolution. When $c > 1$, this matrix is simply repeated vertically and horizontally c times. For rows in the middle of the matrix, there are 11^2 non-zero entries, corresponding to the indices included in the convolution operation when centered on the pixel of the corresponding row.

The proof is tedious and mostly centres around the notation of appropriate reshaping of arrays and zero-padding. In order to state our result, we first need to define the neural network convolution operation.

Definition 9 (Single-channel convolution). *Fix $\mathbb{X} = \mathbb{X}_{wh}$ (in the sense of (16)) and let the rows of X be equal to the elements of $\mathbb{X}$. Let $*_1$ denote the single-channel image convolution operation (in the sense of convolutional networks).*

More concretely, $C *_1 Y$ applies a filter $C \in \mathbb{R}^{(2r_1+1) \times (2r_2+1)}$ to a flattened image $Y \in \mathbb{R}^{wh}$ as follows. First flatten C to be an element $\tilde{C}$ of $\mathbb{R}^{(2r_1+1)(2r_2+1)}$ and zero-pad Y to be an element $\widetilde{Y}$ of $\mathbb{R}^{(2r_1+w)(2r_2+h)}$. Then define for each $j \in \{1, wh\}$ a vector $\tilde{C}_j$ with the same dimensionality as $\widetilde{Y}i$, such that $\tilde{C}_{j,[j:j+(2r_1+1)(2r_2+1)]} = \tilde{C}$ and all other elements of $\tilde{C}_j$ are zero. Then for each $j \in \{1, wh\}$, define

$$(C *_1 Y)_j = \tilde{C}_j^\top \widetilde{Y} = (C_{mat}\widetilde{Y})_j$$

so that $C *_1 Y \in \mathbb{R}^{wh}$, where $C_{mat} \in \mathbb{R}^{wh \times (2r_1+w)(2r_2+h)}$ is a matrix with jth row equal to $\tilde{C}_j$.

Definition 10 (Multi-channel convolution). *Let $*$ denote the muti-channel image convolution operation (in the sense of convolutional networks).*

More concretely, $C * Y$ applies a set of filters $C \in \mathbb{R}^{c_1 \times c_2 \times (2r_1+1) \times (2r_2+1)}$ to a flattened image $Y \in \mathbb{R}^{whc_2}$ as

$$(C * Y)_j = \sum_{r=1}^{c_2} C_{j,r,:,:} *_1 Y_r \in \mathbb{R}^{wh},$$

so that $C * Y \in \mathbb{R}^{c_1 wh}$, where $Y_r \in \mathbb{R}^{wh}$ represents the rth channel of Y.

Generally, we have the following corollary of Theorem 3.

Corollary 11. *In the same setting as Theorem 3, under Definition 9, let $k \equiv \kappa$ (in the sense of (17)) and let $f_*(\cdot; Y, X) = \kappa(\cdot, X)\alpha^*$ be a global minimiser of (5). Under Assumption 1,*

$$z_* = \sigma\big(C_1 * z_* + C_2 * T(Y) + C_3 * \rho(z_*)\big), \tag{18}$$

where $z_* = A'(\kappa(X, X)\alpha^*)$. $C_1 = C_3$ and C_2 are convolutional filters with pqth entry $-\lambda^{-1}\kappa_0(X_{i,[r_1+1,r_2+1]}^\top, X_{i,[p,q]})$ and $\lambda^{-1}\kappa_0(X_{i,[r_1+1,r_2+1]}^\top, X_{i,[p,q]})$ respectively. $\sigma = A'$ and $\rho = (-\log q)' \circ (A')^{-1}$ are monotone non-decreasing. Furthermore,

1. *Under Assumption 3, (7) admits a unique fixed point on $\overline{\mathcal{Z}}$.*

2. *Under Assumption 2, for any test index $\widetilde{X} \in \mathbb{R}^{\widetilde{n} \times d_x}$ and for at least one z_* satisfying (7),*

$$f_*(\widetilde{X}; Y, X) = V_1\left(z_* + \rho(z_*)\right) + V_2 T(Y), \tag{19}$$

   where $V_1 = -\lambda^{-1}\kappa(\widetilde{X}, X)$ and $V_2 = \lambda^{-1}\kappa(\widetilde{X}, X)$.

Proof. We begin with the case $c = 1$. By Definition 9, we have that

$$C_1 * z_* = C_{\text{mat}}\tilde{z}_* \in \mathbb{R}^{wh},$$

where $\tilde{z}_* \in \mathbb{R}^{(2r_1+w)(2r_2+h)}$ is a zero-padded z_* and $C_{\text{mat}} \in \mathbb{R}^{wh \times (2r_1+w)(2r_2+h)}$. The jth row of C_{mat} is equal to $\tilde{C}_j$, where $\tilde{C}_{j,[j:j+(2r_1+1)(2r_2+1)]} = \tilde{C}$ and all other elements of $\tilde{C}_j$ are zero. Here $\tilde{C}$ is a flattened version of C_1.

By removing the zero entries from $\tilde{z}_*$ and the corresponding columns from C_{mat}, we may write

$$C_{\text{mat}}\tilde{z}_* = W_{\text{mat}} z_*$$

for some $W_{1\text{mat}} \in \mathbb{R}^{wh \times wh}$. The same holds for W_2 and W_3. We may therefore write

$$\sigma\big(C_1 * z_* + C_2 * T(Y) + C_3 * \rho(z_*)\big) = \sigma\big(W_{1\text{mat}} z_* + W_{2\text{mat}} T(Y) + W_{3\text{mat}} \rho(z_*)\big).$$

On the other hand, Theorem 3 says that

$$\sigma\big(W_1 z_* + W_2 T(Y) + W_3 \rho(z_*)\big) = z_*.$$

Choosing $W_{1\text{mat}} = W_1 = -\lambda^{-1}\kappa(X, X)$ and similarly for W_2, W_3, we obtain (18). This implies that the filter C_1 has pqth entry $-\lambda^{-1}\kappa_0(X_{i,[r_1+1,r_2+1]}^\top, X_{i,[p,q]})$. The rest of the corollary follows from Theorem 3. $\qquad\square$

F DETAILED EXPERIMENTS

Our experiments may be reproduced using the code provided in the supplementary material by following the README.md file.

Choice of kernel for initialisation To intialise a convolutional network, we need to choose r_1, r_2 and κ_0 according to (17). We choose $r_1 = r_2 = 3$ and $\kappa_0(x, x') = \sum_{r=1}^{c(c+1)/2} g_r(x_3, x'_3) e^{-\frac{1}{2\ell_r^2}\|x_{[1,2]} - x'_{[1,2]}\|^2}$, where $g_r(a, b) = 1$ if $a == a_r$ and $b == b_r$ or $a == b_r$ and $b == a_r$ and 0 otherwise. We sample the squared lengthscales from a uniform distribution between 0 and 4.

Scaling up parameter counts The number of rows of the square kernel matrix is equal to the number of rows in X. This means, for example, in the setting of CIFAR10 where $X \in \mathbb{R}^{32*32*3\times 3}$, there are roughly $9.4 * 10^6$ elements in the kernel matrix. Using a convolutional representation, the sparse kernel matrix may be represented as a convolutional layer of size $(3, 3, 32, 32)$. Crucially, the parameter count scales quadratically with the number of input channels, which in this case is 3.

One way to experiment on larger models is to scale up the size of the input data. To this effect, we take a dataset containing 3799 hyperspectral (25 channel) images (HSI) of roads (Lu et al., 2020) of total size $(3799, 25, 192, 384)$. We consider a sequence of denoising tasks when the input data is a subset of the 25 hyperspectral channels. The resulting plots are given in Figures 8, 9, 10 11. The results are summarised in Table 1

Table 1: Summary of experimental results. Shown are average $\log$ test losses $\pm$ one "sample standard deviation" of the logarithm taken at the best performing spectral norm. The spectral norm grid was as described in the main text. If NaNs or Infs were observed, these were replaced by the maximum before the average and variance were recorded. # failed indicates the number of NaNs and Infs observed over the full grid. Due to training instability causing NaN and Infs data points, especially in randomly initialised models, the average and "sample standard deviation" are not true unbiased estimators. kGLM initialisation shows superior performance, both in terms of average performance and number of failed runs.

Model	Parameter (#)	Runs (#)	Epochs (#)	kGLM init		Random init	
				Mean $\pm$ std (MSE)	Failed (#)	Mean $\pm$ std (MSE)	Failed (#)
4 channel	1600	70	0	$\mathbf{-4.80 \pm 0.55}$	**0**	-6.37 ± 0.17	220
			3	$\mathbf{-6.61 \pm 0.03}$	**17**	-6.51 ± 0.01	222
			5	$\mathbf{-6.64 \pm 0.02}$	**21**	-6.57 ± 0.01	222
8 channel	6400	100	0	$\mathbf{-4.87 \pm 0.37}$	**0**	-3.53 ± 0.15	450
			3	$\mathbf{-6.76 \pm 0.01}$	**42**	-6.73 ± 0.01	485
			5	-6.80 ± 0.01	**46**	-6.79 ± 0.01	486
10 channel	10,000	65	0	$\mathbf{-4.95 \pm 0.31}$	**0**	-3.63 ± 0.12	256
			3	$\mathbf{-6.84 \pm 0.01}$	**33**	-6.80 ± 0.02	268
			5	$\mathbf{-6.90 \pm 0.01}$	**35**	-6.87 ± 0.02	268
13 channel	16,900	65	0	$\mathbf{-4.60 \pm 0.37}$	**0**	-3.23 ± 0.15	185
			3	-6.82 ± 0.22	**28**	-6.42 ± 0.40	206
			5	-6.87 ± 0.22	**28**	-6.46 ± 0.42	208

Figure 8: First 4 channels of HSI dataset. Test MSE against the average spectral norm of each layer for image denoising task using kGLM initialisation (blue, ours) and random initialisation (red). The vertical axes change between plots. Markers at the edge of the top border indicate that a value greater than the axis limit or NaN was observed. Our initialisation scheme shows superior performance at all epochs.

Figure 9: First 8 channels of HSI dataset. Test MSE against the average spectral norm of each layer for image denoising task using kGLM initialisation (blue, ours) and random initialisation (red). The vertical axes change between plots. Markers at the edge of the top border indicate that a value greater than the axis limit or NaN was observed. Our initialisation scheme shows superior performance at all epochs.

Figure 10: First 10 channels of HSI dataset. Test MSE against the average spectral norm of each layer for image denoising task using kGLM initialisation (blue, ours) and random initialisation (red). The vertical axes change between plots. Markers at the edge of the top border indicate that a value greater than the axis limit or NaN was observed. Our initialisation scheme shows superior performance at all epochs.

Figure 11: First 10 channels of HSI dataset. Test MSE against the average spectral norm of each layer for image denoising task using kGLM initialisation (blue, ours) and random initialisation (red). The vertical axes change between plots. Markers at the edge of the top border indicate that a value greater than the axis limit or NaN was observed. Our initialisation scheme shows superior performance at all epochs.