Teach Less, Learn More: On the Undistillable Classes in Knowledge Distillation

Abstract

Knowledge distillation (KD) can effectively compress neural networks by training a smaller network (student) to simulate the behavior of a larger one (teacher). A counter-intuitive observation is that a more expansive teacher does not make a better student, but the reasons for this phenomenon remain unclear. In this paper, we demonstrate that this is directly attributed to the presence of *undistillable classes*: when trained with distillation, the teacher's knowledge of some classes is incomprehensible to the student model. We observe that while KD improves the overall accuracy, it is at the cost of the model becoming inaccurate in these undistillable classes. After establishing their widespread existence in state-of-the-art distillation methods, we illustrate their correlation with the capacity gap between teacher and student models. Finally, we present a simple "Teach Less Learn More" (TLLM) framework to identify and discard the undistillable classes during training. We validate the effectiveness of our approach on multiple datasets with varying network architectures. In all settings, our proposed method is able to exceed the performance of competitive state-of-the-art techniques.

1 Introduction

More accurate machine learning models often demand more computation and memory at test time, making them difficult to deploy on computational-constraint devices. Knowledge distillation (KD) alleviates this burden by transferring the knowledge from an expensive teacher model to a cheap student model to improve the performance of this more efficient network. Over the past several years, we have witnessed a huge success in knowledge distillation and a surge of related literature on designing better distillation techniques.

An intuitive thought of knowledge distillation is that better teachers are supposed to make better students since a larger model can learn more visually meaningful and task-related information, and a student model can presumably benefit from learning with more informative knowledge. However, recent works show that such intuition is incorrect. In fact, prior works found that students distilled from a bigger teacher, one with more parameters and higher accuracy, can perform worse than the same students distilled from a smaller teacher [19, 7, 32, 21, 29]. The situation is getting more severe when training on a large-scale, challenging dataset such as ImageNet [3]. More surprisingly, the model with the same architecture [43] or even a model with lower performance [15, 41, 44] can be used as a teacher network to perform knowledge distillation, which plays a role of regularization [28, 20, 46]. Indeed, a large body of researches [49, 31, 47, 14, 30] devoted to solving this problem, but few minimal efforts have been put into understanding this phenomenon.

In this paper, we propose a new data-centric perspective on the phenomenon of "larger teacher, worse student". In contrast to the previous works, we cast the inefficacy of large teachers as a fundamental consequence of the class-dependent bias in KD. Specifically, we claim that:

The undistillable classes are a direct result of the inefficacy of large teachers in distillation.

Recall that prior works attribute the failure of large teachers in KD to the capacity mismatch between the teacher and student model. In other words, the student model cannot learn the teacher's knowledge due to their insufficient expressive power. Indeed, we find that their claim is true for *some* classes that posses bad *distillability*. We posit that these classes cause seemingly mismatched capacity over all samples in the dataset.

The empirical study supports our hypothesis. For samples from the undistillable classes, the feature representation similarity between the teacher and student model is extremely low compared to the regular classes. Furthermore, perhaps less surprisingly, the distilled model could obtain lower accuracy on these undistillable classes than their vanilla-trained counterpart. To further corroborate our theory, we show that the number of undistillable classes increases when the capacity gap between the two models increases.

After verifying our hypothesis, a natural question would be raised: to what extent do these undistillable classes exist? When discussing the property of knowledge distillation, previous literature typically evaluates vanilla knowledge distillation [12]. However, considering the evolution of distillation techniques over the past several years, we believe it is necessary to expand our study. To this end, we investigate the existence of the undistillable classes over three standard datasets (CIFAR100 [18], ImageNet1K [4], CUB-200 [38]) with more than 20 modern distillation techniques. We also include the evaluation of advanced architectures, i.e., vision transformer [35]. Our study shows that the undistillable classes generally exist, usually taking over from 10% to 50% of the total classes, depending on the distillation methods, datasets, and teacher-student pairs.

To resolve this issue, we present a novel distillation framework called "Teach Less, Learn More" distillation (TLLM). It is motivated by the successful teaching strategy in pedagogy[33], where teachers are encouraged to do less rote learning and provide more spaces for students to explore and discover their talents. Our methodology is conceptually similar: we aim to identify the undistillable classes and remove them entirely during distillation, allowing the student model to explore the representations of these classes with their own capacity. Specifically, we record the per-class teaching curve (distillation losses) and calculate its change over a moving window of K epochs. If the teaching curve for some particular classes is stagnated or upward, we consider the knowledge transfer process for these classes is no longer necessary. Then, we remove these classes in distillation (if it is an output-based KD, we replace them with the label smoothing technique to compensate for the regularization effect). Our approach, despite its simplicity, is proven to be effective in preventing the adverse effect brought by the undistillable classes and improving the overall accuracy.

Overall, we emphasize our contributions are the following: 1) we analytically show that the undistillable classes are the cause of inefficacy of the large teacher model; 2) we demonstrate that the accuracy of these undistillable classes drops after distillation, and our extensive experiments showing this is a general phenomenon, irrespective of distillation methods, datasets, or teacher-student pairs; 3) we propose a simple yet effective framework to identify and discard undistillable classes and illustrate the effectiveness our approach with extensive experiments.

2 On the Undistillable Classes in Knowledge Distillation

2.1 Formal Definition

In this section, we formally define the undistillable classes. Considering an multi-class predictor $F : \mathbb{R}^d \to \mathbb{R}^k$ as student and another predictor $G : \mathbb{R}^d \to \mathbb{R}^k$ as teacher. Giving a training sample $S = \{(x_i, y_i)_{i=1}^n\} \sim \mathbb{P}^n$ for distribution $\mathbb{P}$ over a set of instance $\mathcal{X}$ and label $\mathcal{Y} = [L] = [1, 2, \ldots, L]$. In the standard training, the goal is to approximate the risk $R(f; S)$ of functional class $f \in F$ via the

Figure 1: The representation agreement measured by CKA between teacher model and student model. For student network, the samples from undistillable classes clearly fail to match the representation from teacher model.

empirical risk $\hat{R}(\mathbf{f}; S) = \frac{1}{N} \sum_n l(y, \mathbf{f}(x))$, for any bounded loss. For knowledge distillation, we can rewrite the distilled risk as $\tilde{R}(\mathbf{f}; S) = \frac{1}{N} \sum_n l(\mathbf{g}(x), \mathbf{f}(x))$, where the functional class $g \in G$.

The conventional setting consider all classes equally. Without loss of generality, we will consider the $S = S_r \bigcup S_u \sim \mathbb{P}^n$, where we split the data over distribution $\mathbb{P}$ into two categories, each category contains non-overlapping instances $S_u = \{(x_i, y_i^u)_{i=1}^n\}, \mathcal{Y}^u = [L] = \{L_{n+1}, L_{n+2}, \cdots, L\}, S_r = S \setminus S_u$ and $|\cdot|_c$ be a appropriate distillability measurement. We define that S_u are a set of samples from the *undistillable classes* in distillation iff $|\mathbf{f}; S_u|_c \ll |\mathbf{f}; S_r|_c$.

2.2 Mismatched Representation for Undistillable Classes

The previous section formally defines the undistillable classes as classes with bad distillability. In this section, we develop a criterion to measure the distillability of a class quantitatively. Recall that the student is typically encouraged to mimic the behavior of the teacher model. Therefore, a converged student should impeccably match the teacher's behavior in an ideal setting. It implies that their feature representations should be the same as the teachers', given the same input on both models. As a result, we harness the similarity of feature representations between teacher and student to reflect the level of distillability of the student model. Inspired by Zhu et al. [49], we use the Center Kernel Alignment (CKA) [17] to calculate the representation similarity between two neural networks. To create a typical case of capacity mismatch, we follow the previous works [3] to use a ResNet56 as our pre-trained teacher model and a modified ResNet24 as the student model (see Appendix for details). We perform standard feature knowledge distillation [27] on stage four, which contains nine consecutive convolutional blocks. We choose to compare the network representation at convergence. For the CKA score figure, we primarily focus the score on the diagonal, which indicates the representation similarity of the convolutional layer at the same position in the network. In order to compare the representation similarity of samples from different types of classes, we deliberately choose 12 test samples from distinct classes. Note that we use samples from the test set to ensure that the observed behavior is not due to ad-hoc memorization.

In the middle of Figure 1, the feature similarity between teacher and student on each corresponding layer is presented. We can observe that the CKA scores for most layers are less than 0.6, and for some layers are even less than 0.5. These results indicate that despite the student indeed learning to match the teacher's representations, their features are far from perfect alignment. Notably, the representation similarity score is calculated based on the average score over a batch. Therefore, we decouple the matrices and check the CKA score for each sample individually. On the left side and right side of Figure 1, we give the CKA matrices at the last three layers for 12 samples. Each side contains six samples. We notice a clear trend: the CKA scores for samples from the left side are obviously much lower than those on the right side, indicating that the mismatched representations are not uniformly distributed over all samples. Therefore, we name the classes on the left side as *undistillable classes*. Our observation contradicts the conclusion from the prior work, which attributes

Figure 2: The ΔPA versus ΔAcc for three teacher-student pairs on CIFAR100. The Pearson's r is higher than 0.65 for all figures.

the mismatched capacity as a general issue for all data [49, 3, 19]. We later show that at the left top of Figure 4, the accuracy for the undistillable classes drops after training with KD compared to their train-from-scratch counterpart.

2.3   Bad Distillability hurts Accuracy

As aforementioned, a model would contain some classes with bad distillability. But what is the consequence of distilling knowledge to these classes? In this section, we show that the quality of KD (i.e., accuracy) is highly correlated to their distillability. Here we record the difference in accuracy between the vanilla trained model (training without distillation) and the model trained with knowledge distillation. Particularly, we adopt per-class accuracy:

$$\Delta \text{ACC}^m = \text{ACC}_{\text{vanilla}}^m - \text{ACC}_{\text{kd}}^m \tag{1}$$

where $j \in \mathbb{Y}$. The motivation behind this metric is straightforward: if the $\Delta \text{ACC}^m > 0$, then for m^{th} class, the effect of KD is positive; otherwise, the KD hurts the student's performance on m^{th} class. To demonstrate the correlation between per-class accuracy and per-class distillability, a naive approach is to compare the ΔACC with the CKA scores, as shown in the previous section. However, CKA measures per-layer feature representation similarity; simply averaging over the total number of layers may be inaccurate, not to mention that the teacher model usually contains more layers than students. Therefore, we present a new metric based on average prediction agreement:

$$\text{PA} := \frac{1}{n} \sum_{i=1}^{n} \mathbb{1} \, \text{argmax} \, \sigma(z_{t,i}) = \text{argmax} \, \sigma(z_{s,i}) \tag{2}$$

where $\sigma(z_t) = \frac{\exp(z_i)}{\sum_j \exp(z_i)}$ and $\sigma(z_s) = \frac{\exp(z_s)}{\sum_j \exp(z_s)}$ is the output of softmax function for teacher model and student model, respectively. Equation 2 is inspired by the fact that if the feature representations between two models are exactly the same, these two models ought to produce the same top-1 label. Similar to ΔAcc, here we focus on the difference in prediction agreement ΔPA between two models; one is trained from scratch, and another is trained with distillation:

$$\Delta \text{PA}^m := \text{PA}_{\text{vanilla}}^m - \text{PA}_{\text{kd}}^m \tag{3}$$

Specifically, we put these two metrics in a scatter plot chart for three varying teacher-student pairs on CIFAR100. Figure 2 reveals that for most of the classes with $\Delta \text{ACC} \leq 0$, its corresponding $\Delta \text{PA} \leq 0$ as well, indicating that if the student *become* disagrees with the teacher's prediction, the teacher's supervision can hurt student's performance on this particular class. In addition, we can observe that the level of disagreement is linearly correlated to the level of performance change: when measured with the Pearson's r, it obtained over 0.65 with a p-value less than 0.0005 on all three teacher-student combination, showing a statistically significant linear correlation between these two metrics. In conclusion, for any class in the student model, if it is undistillable, it certainly has $\Delta \text{ACC}^m < 0$.

Figure 3: **Left:** Per-class ACC and per-class ΔACC for three teacher-student pairs in CIFAR100. **Right:** Proportion of Undistillable Classes distilling ResNet20 with three teacher models.

2.4 The Larger the Capacity Gap, the More the Undistillable Classes

Now, we redirect our attention to the correlation between the level of capacity gap and the presence of the undistillable classes. We propose to leverage multiple teacher networks with varying capacity to distilled a single, low-capacity student. Specifically, we select the ResNet20 as our student model, and pick ResNet44, ResNet56, and ResNet110 as three individual teacher model. For each set of experiments, we adopt one teacher model from the above to train a student model via vanilla KD [12]. This procedure mirrors that of mismatched capacity experiments in Cho et al. [3], except that our goal is to investigate the relationship of per-class accuracy with the capacity gap. As shown in Figure 3, we observe a clear relation between increase of the number undistillable classes, as increase in the capacity gap between models. Specifically, the number of total undistillable classes for the smallest student model (ResNet44) is almost tripled compare to the largest largest model (ResNet101).

2.5 On the Existence of the Undistillable Classes

The knowledge distillation is well-known for its "free" gain over compact models *on average* on an i.i.d test set. Modern distillation techniques only focus on improving the overall accuracy of the student model, with an intuition that the distillation is beneficial for all classes. Indeed, the overall accuracy is paramount, but the per-class accuracy is also important in many cases. For instance, the engineers may want to avoid their face recognition system mistakenly recognizing a black woman as a man with brown skin. Nevertheless, the distillation method inevitably brings class-dependent bias into the student model. As briefly shown in Figure 4, the distilled student model shows crystal class-dependent bias on all datasets. It is also worth noting that the accuracy drops dramatically for some undistillable classes. For instance, on ImageNet1K, there are 127 classes that lose over 4% accuracy compared to their vanilla trained counterpart, and more than nine classes lose over 10% on the test set.

In recent years, the techniques of distillation have evolved dramatically, i.e., feature-based distillation and self-supervision-based distillation [34]. Therefore, to ensure the undistillable classes are not a unique byproduct of the vanilla KD, we extend our experiments to include 26 state-of-the-art distillation frameworks, each of them evaluated by five different teacher-student pairs on CIFAR100. We categorize them into two groups (output-based KD and feature-based KD). Table 1 give a list of all methods that we used for evaluation. We only present the results for 13 of them due to limited space; the complete analysis and more evaluation of ImageNet-1K can be found in Appendix. Figure 5 shows the number of undistillable classes. It is surprising to show that all of them contain undistillable

Table 1: A summary of all distillation methods that we used for evaluation in Section 2.5

Method	KD [12]	FitNet [27]	AT [42]	SP [37]	CC [25]	VID [1]	RKD [23]	PKT [24]	AB [11]	FT [16]	FSP [40]	NST [13]	CRD [34]
Pub	Arxiv'14	ICLR'15	Arxiv'16	ICCV'19	ICCV'19	CVPR'19	CVPR'19	ECCV'18	AAAI'19	Neurips18	CVPR'17	Arxiv'18	ICLR'19
Output	✓	✗	✗	✗	✓	✗	✗	✓	✗	✗	✗	✓	✗
Feature	✗	✓	✓	✓	✗	✓	✓	✗	✓	✓	✓	✗	✓

Method	SSKD [39]	PAD [45]	WSKD [48]	LST [29]	OH [10]	TA [19]	ESKD [3]	SCKD [49]	KR [2]	SFTN [22]	CID [5]	FKD [9]	DKD [47]
Pub	ECCV'20	ECCV'20	ICLR'20	ICLR'20	ICCV'19	AAAI'20	ICCV'19	ICCV'21	ICCV'21	Neurips'21	Neurips'21	ICLR'22	CVPR'22
Output	✓	✓	✓	✓	✗	✓	✓	✓	✗	✓	✓	✓	✓
Feature	✗	✗	✗	✗	✓	✗	✗	✓	✗	✓	✗	✗	✗

Figure 4: The per-class ΔACC of knowledge distillation on three datasets (CIFAR100 [18]/ImageNet1K [4]/CUB-200 [38]) with vanilla KD [12]. We only show the first 500 class in ImageNet1K and the first 100 classes in CUB-200.

classes. For instance, the Resnet32x4:Resnet8x4 with vanilla KD has 52 undistillable classes, more the half of the total classes. Despite so many undistillable classes, all distillation methods improve the vanilla student model, some by a large margin. Such a phenomenon indicates that the effect of knowledge distillation is non-uniform at the class level. Moreover, the proportion of the undistillable classes is taking over from 10% to 50% over the total number of classes. Therefore, it is critical and necessary to control and reduce the number of undistillable classes in the student network.

3 Teach Less, Learn More (TLLM): Identifying and Discarding the Undistillable Classes

We have stressed the adverse effect and characterized the properties of the undistillable classes from the previous section. To this end, we give a simple framework, named "Teach Less, Learn More" distillation (TLLM), which analogy to a successful teaching principal in the pedagogy, to build better KD algorithms. Our idea is conceptually similar to the TLLM in the pedagogy, where the student is encouraged to have more autonomy and devise their own solutions to problems. In practice, the student model is supervised by both teacher's knowledge and the ground truth labels. Training with

Figure 5: **Top**: the number of undistillable classes for diverse teacher-student pair evaluated by various distillation methods. More can be found in the Appendix. **Bottom left**: Three types of distillation approaches. **Bottom middle**: Definition of undistillable classes. **Bottom right**: Each size of circle represent a range of undistillable class number.

the model's task-oriented objectives is critical to the eventual performance [12], and provably to correct the wrong gradient directions that are brought by the teacher's mistaken knowledge [15]. Therefore, what we do is simple: identify the undistillable classes and then remove them from the distillation process. As a result, the student can learn these classes directly from the ground truth labels without interference. The critical challenge of TLLM is how to find the undistillable classes during training. A naive yet computational expansive approach is first to train the model to convergence with distillation and then retrain it by manually eliminating the undistillable classes according to the performance on the test set. Instead, we propose to monitor the teaching curves (distillation losses) and set up a criterion to find the undistillable classes during training that are more computationally efficient.

Figure 6: Teaching curve for regular class and undistillable class.

Specifically, we pay attention to the per-class teaching curve, i.e., teaching curve $l(y_m, \mathbf{f}(x))$ on m^{th} class, instead of the averaged distillation loss over the entire datasets. The teaching curve is calculated on the validation set. Then, we set a moving window over K epochs, which is started at S^{th} epoch and end at $(S + K)^{th}$ epoch. During the distillation process, we record and update the per-class teaching curve $[l_S(y_m, \mathbf{f}(x)), l_{S+K}(y_m, \mathbf{f}(x))]$. If $l_S(y_m, \mathbf{f}(x)) - l_{S+K}(y_m, \mathbf{f}(x)) \leq \eta, 0 \leq \eta$, meaning that the loss is moving upward in the K epochs moving window. Figure 3 gives an example of the teaching curve for an undistillable class. After training with approximately 50 epochs, the loss for this particular class suddenly jumps. Therefore, our method can capture such behavior, then identify and remove these undistillable classes during training. It is worth noting that these classes remain in the task-oriented objective for the

Table 2: Experimental results on CIFAR100 with CNN architectures. We observe that our approach improves overall accuracy and significantly reduces the number of undistillable classes.

T-S Pair	ResNet32x4/ResNet8x4 (%)			ResNet50/MobileNetV2 (%)			ResNet32x4/ShuffleNetV1 (%)		
Method	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ
Teacher	79.42	-	-	79.34	-	-	79.42	-	-
Student	72.50	-	-	64.60	-	-	70.50	-	-
KD [12]	73.08	**75.53**	+2.54	67.28	**69.54**	+2.26	74.07	**76.67**	+2.60
FitNet [27]	73.50	**75.52**	+2.02	63.06	**66.33**	+3.27	73.59	**75.82**	+2.23
AT [42]	73.44	**75.21**	+1.77	58.58	**61.70**	+3.12	71.73	**75.10**	+3.37
OH [10]	74.98	**76.82**	+1.84	67.69	**69.21**	+1.52	77.43	**79.05**	+1.62
KR [2]	75.63	**76.84**	+1.21	69.89	**71.84**	+1.95	77.14	**78.87**	+1.73
SFTN [22]	76.64	**77.83**	+1.19	70.01	**70.94**	+0.93	79.58	**80.04**	+0.46

student, making sure that the student can still learn from these data. Our approach is very efficient since the extra computational cost is linearly correlated with the number of classes, usually not a big number.

4 Experiment

4.1 Main Results

In this section, we evaluate our proposed method on CIFAR100 [18] and ImageNet [4] under various distillation settings. We refer reader to the Appendix for the implementation details.

CIFAR100. As aforementioned, our approach is orthogonal to other distillation techniques. Therefore, we investigate the performance of TLLM when combined with other methods. We report the experimental results on CIFAR100, which average over five trials. Specifically, we compare six distillation methods, and for each of them, we add our method to theirs. As shown in Table 2, our method consistently improve the overall accuracy for baseline. For instance, we improve the vanilla KD [12] by 2.54%. The performance gain mostly comes from the increased accuracy on undistillable classes. Later, we will show that our approach also reduces the number of undistillable classes. It is also surprising to find that some methods that were once inferior to other approaches, i.e., the accuracy of OH [10] is 0.65% lower than KR [2] on ResNet32x4/ResNet8x4, obtain higher accuracy after applying TLLM, showing that many "outdated" algorithms have the potential to be quality methods. Moreover, our approach is practical for both output-based (i.e., KD [12])and feature-based distillation [27, 2, 42] algorithms.

ImageNet. ImageNet is a large-scale classification dataset that contains 1.28 million images for training and 50k images for validation. Unlike conventional papers that only report the performance of CNN models, we also consider vision transformer (ViT), an advanced network architecture that has drawn increasing attention lately.

For CNN-based architectures, we evaluate two teacher-student pairs: 1) ResNet32 as a pretrained teacher and ResNet18 as a student model, a widely adopted setting follows CRD [34], 2) ResNet50 as a pretrained teacher, and MobileNetV2 as a student model, a less conventional setting that some papers have used. The experimental results are reported in Table 3. Our TLLM, which is built based on KR [8], achieves a considerable improvement over its baseline. It is also worth mentioning that the performance of TLLM outperforms other state-of-the-art distillation methods.

For ViT architectures, we evaluate two types of teacher-student pairs: 1) the RegNetY [26] and ViT-Tiny/ViT-Small [6] pairs are the popular setting in DeiT [35] which apply a CNN model as a teacher network to distill a vision transformer, 2) the CaiT-S23 [36] and ViT-Tiny pairs adopt an advanced ViT model as a teacher, whose performance is slightly inferior to RegNetY. We compare

Table 3: Experimental results on ImageNet1K with CNN architectures.

Teacher	Baseline	Distillation Framework (%)									
ResNet32	ResNet18	KD [12]	AT [42]	OFD [10]	CRD [34]	SRRL	KR [2]	SFTN [22]	CID [10]	DKD [47]	**TLLM**
73.3	69.8	70.7	70.7	71.2	71.2	71.7	71.6	71.1	71.9	71.7	**72.6**
ResNet50	MobileNetV2	KD	AT	OFD	CRD	SRRL	KR	SFTN	CID	DKD	**TLLM**
76.2	68.9	70.5	69.6	71.3	71.4	71.7	72.6	71.5	72.3	72.1	**73.2**

Table 4: Experimental results on ImageNet1K with vision transformer architectures.

T-S Pair	RegNetY/ViT-Tiny (%)		RegNetY/ViT-Small (%)		CaiT-S24/ViT-Tiny (%)		CaiT-S24/ViT-Small (%)	
Method	Vanilla	TLLM	Vanilla	TLLM	Vanilla	TLLM	Vanilla	TLLM
Teacher	82.9	-	82.7	-	82.7	-	82.7	-
Student	72.2	-	79.9	-	72.2	-	79.9	-
KD/DeiT [35]	74.5	$\mathbf{76.3}_{+1.8}$	81.2	$\mathbf{81.9}_{+0.7}$	74.4	$\mathbf{76.1}_{+1.7}$	81.3	$\mathbf{82.0}_{+0.7}$

with DeiT [35], a benchmark that uses teachers' hard labels as dark knowledge to supervise the student network. We notice that in Table 4, we achieve higher accuracy than DeiT on all teacher-student pairs. Particularly, when the capacity gap between teacher and student is large, i.e., RegNetY/ViT-Tiny and CaiT-S24/ViT-Small, the improvement in the validation set is more notable.

4.2 Ablation Study

Number of the Undistillable classes. Our method specifically identified the undistillable classes and then discarded them during distillation. Therefore, we conduct experiments to check whether our approach reduces the number of undistillable classes. In the Appendix, we show that our proposed TLLM significantly reduces the number of undistillable classes in the student models, allowing balanced performance improvement.

Does TLLM allow larger teacher to make better student? Our approach is motivated to resolve the "larger teacher, worse student problem"; thus, it is natural to verify whether our approach can solve this issue. In the Appendix, we show that our approach allows the larger teacher to distill students with higher accuracy.

Are undistillable classes consistent across multiple experiments? Yes and no. Yes, since we find some classes consistently hurt by knowledge distillation over several repeated experiments. No, because some classes are undistillable at one experiment and then become distillable in the second round. We provide more evidences in the Appendix.

5 Conclusion

This paper studies the "larger teacher, worse student" phenomena in knowledge distillation. Unlike prior works, which attribute the inefficacy of large teachers as a capacity mismatch issue on samples, we consider the presence of undistillable classes as the direct cause of mismatched capacity. Our paper verified that these classes lower the ability of the student model to match the teacher's feature representation and predictive distribution, making the accuracy drops considerably in some arbitrary classes, therefore, hurting the overall performance. We further demonstrate that the existence of undistillable classes is universal, irrespective of distillation methods, datasets, and student-teacher configurations. Finally, we propose a "teacher less, learn more" (TLLM) method to alleviate this issue by targeting and removing samples from the undistillable classes. Our experiments have shown that our TLLM can greatly eliminate the adverse effect of undistillable classes to improve the overall performance significantly. Overall, we believe that our analysis and proposed method provides an interesting and practical new perspective on designing distillation algorithms.

References

[1] Sungsoo Ahn, Shell Xu Hu, Andreas Damianou, Neil D Lawrence, and Zhenwen Dai. Variational information distillation for knowledge transfer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9163–9171, 2019.

[2] Pengguang Chen, Shu Liu, Hengshuang Zhao, and Jiaya Jia. Distilling knowledge via knowledge review. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5008–5017, 2021.

[3] Jang Hyun Cho and Bharath Hariharan. On the efficacy of knowledge distillation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 4794–4802, 2019.

[4] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[5] Xiang Deng and Zhongfei Zhang. Comprehensive knowledge distillation with causal intervention. *Advances in Neural Information Processing Systems*, 34, 2021.

[6] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[7] Tommaso Furlanello, Zachary Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born again neural networks. In *International Conference on Machine Learning*, pages 1607–1616. PMLR, 2018.

[8] Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. Knowledge distillation: A survey. *International Journal of Computer Vision*, 129(6):1789–1819, 2021.

[9] Bobby He and Mete Ozay. Feature kernel distillation. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=tBIQEvApZK5`.

[10] Byeongho Heo, Jeesoo Kim, Sangdoo Yun, Hyojin Park, Nojun Kwak, and Jin Young Choi. A comprehensive overhaul of feature distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1921–1930, 2019.

[11] Byeongho Heo, Minsik Lee, Sangdoo Yun, and Jin Young Choi. Knowledge transfer via distillation of activation boundaries formed by hidden neurons. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3779–3787, 2019.

[12] Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

[13] Zehao Huang and Naiyan Wang. Like what you like: Knowledge distill via neuron selectivity transfer. *arXiv preprint arXiv:1707.01219*, 2017.

[14] Aref Jafari, Mehdi Rezagholizadeh, Pranav Sharma, and Ali Ghodsi. Annealing knowledge distillation. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2493–2504, 2021.

[15] Guangda Ji and Zhanxing Zhu. Knowledge distillation in wide neural networks: Risk bound, data efficiency and imperfect teacher. *Advances in Neural Information Processing Systems*, 33: 20823–20833, 2020.

[16] Jangho Kim, SeongUk Park, and Nojun Kwak. Paraphrasing complex network: Network compression via factor transfer. *Advances in neural information processing systems*, 31, 2018.

[17] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International Conference on Machine Learning*, pages 3519–3529. PMLR, 2019.

[18] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[19] Seyed Iman Mirzadeh, Mehrdad Farajtabar, Ang Li, Nir Levine, Akihiro Matsukawa, and Hassan Ghasemzadeh. Improved knowledge distillation via teacher assistant. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5191–5198, 2020.

[20] Hossein Mobahi, Mehrdad Farajtabar, and Peter Bartlett. Self-distillation amplifies regularization in hilbert space. *Advances in Neural Information Processing Systems*, 33:3351–3361, 2020.

[21] Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? *Advances in neural information processing systems*, 32, 2019.

[22] Dae Young Park, Moon-Hyun Cha, Daesin Kim, Bohyung Han, et al. Learning student-friendly teacher networks for knowledge distillation. *Advances in Neural Information Processing Systems*, 34, 2021.

[23] Wonpyo Park, Dongju Kim, Yan Lu, and Minsu Cho. Relational knowledge distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3967–3976, 2019.

[24] Nikolaos Passalis and Anastasios Tefas. Learning deep representations with probabilistic knowledge transfer. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 268–284, 2018.

[25] Baoyun Peng, Xiao Jin, Jiaheng Liu, Dongsheng Li, Yichao Wu, Yu Liu, Shunfeng Zhou, and Zhaoning Zhang. Correlation congruence for knowledge distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 5007–5016, 2019.

[26] Ilija Radosavovic, Raj Prateek Kosaraju, Ross Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10428–10436, 2020.

[27] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014.

[28] Zhiqiang Shen, Zhankui He, and Xiangyang Xue. Meal: Multi-model ensemble via adversarial learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4886–4893, 2019.

[29] Zhiqiang Shen, Zechun Liu, Dejia Xu, Zitian Chen, Kwang-Ting Cheng, and Marios Savvides. Is label smoothing truly incompatible with knowledge distillation: An empirical study. *arXiv preprint arXiv:2104.00676*, 2021.

[30] Wenxian Shi, Yuxuan Song, Hao Zhou, Bohan Li, and Lei Li. Follow your path: a progressive method for knowledge distillation. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 596–611. Springer, 2021.

[31] Wonchul Son, Jaemin Na, Junyong Choi, and Wonjun Hwang. Densely guided knowledge distillation using multiple teacher assistants. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9395–9404, 2021.

[32] Samuel Stanton, Pavel Izmailov, Polina Kirichenko, Alexander A Alemi, and Andrew G Wilson. Does knowledge distillation really work? *Advances in Neural Information Processing Systems*, 34, 2021.

[33] KH Tan, Charlene Tan, and JS Chua. The "teach less, learn more" initiative in singapore schools. *Innovation in education*, pages 153–171, 2008.

[34] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. In *International Conference on Learning Representations*, 2019.

[35] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pages 10347–10357. PMLR, 2021.

[36] Hugo Touvron, Matthieu Cord, Alexandre Sablayrolles, Gabriel Synnaeve, and Hervé Jégou. Going deeper with image transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 32–42, 2021.

[37] Frederick Tung and Greg Mori. Similarity-preserving knowledge distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1365–1374, 2019.

[38] Peter Welinder, Steve Branson, Takeshi Mita, Catherine Wah, Florian Schroff, Serge Belongie, and Pietro Perona. Caltech-ucsd birds 200. 2010.

[39] Guodong Xu, Ziwei Liu, Xiaoxiao Li, and Chen Change Loy. Knowledge distillation meets self-supervision. In *European Conference on Computer Vision*, pages 588–604. Springer, 2020.

[40] Junho Yim, Donggyu Joo, Jihoon Bae, and Junmo Kim. A gift from knowledge distillation: Fast optimization, network minimization and transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4133–4141, 2017.

[41] Li Yuan, Francis EH Tay, Guilin Li, Tao Wang, and Jiashi Feng. Revisiting knowledge distillation via label smoothing regularization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3903–3911, 2020.

[42] Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. *arXiv preprint arXiv:1612.03928*, 2016.

[43] Linfeng Zhang and Kaisheng Ma. Improve object detection with feature-based knowledge distillation: Towards accurate and efficient detectors. In *International Conference on Learning Representations*, 2020.

[44] Linfeng Zhang, Zhanhong Tan, Jiebo Song, Jingwei Chen, Chenglong Bao, and Kaisheng Ma. Scan: A scalable neural networks framework towards compact and efficient models. *Advances in Neural Information Processing Systems*, 32, 2019.

[45] Youcai Zhang, Zhonghao Lan, Yuchen Dai, Fangao Zeng, Yan Bai, Jie Chang, and Yichen Wei. Prime-aware adaptive distillation. In *European Conference on Computer Vision*, pages 658–674. Springer, 2020.

[46] Zhilu Zhang and Mert Sabuncu. Self-distillation as instance-specific label smoothing. *Advances in Neural Information Processing Systems*, 33:2184–2195, 2020.

[47] Borui Zhao, Quan Cui, Renjie Song, Yiyu Qiu, and Jiajun Liang. Decoupled knowledge distillation. 2022.

[48] Helong Zhou, Liangchen Song, Jiajie Chen, Ye Zhou, Guoli Wang, Junsong Yuan, and Qian Zhang. Rethinking soft labels for knowledge distillation: A bias-variance tradeoff perspective. *arXiv preprint arXiv:2102.00650*, 2021.

[49] Yichen Zhu and Yi Wang. Student customized knowledge distillation: Bridging the gap between student and teacher. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 5057–5066, 2021.