Teach Less, Learn More: On the Undistillable Classes in Knowledge Distillation

Yichen Zhu,
Midea Group

Ning Liu
Midea Group

Zhiyuan Xu
Midea Group

Xin Liu
East China Normal University

Weibing Meng
Tsinghua University

Yi Wang
Midea Group

Zhicai Ou
Midea Group

Jian Tang[*]
Midea Group

Abstract

Knowledge distillation (KD) can effectively compress neural networks by training a smaller network (student) to simulate the behavior of a larger one (teacher). A counter-intuitive observation is that a more expansive teacher does not make a better student, but the reasons for this phenomenon remain unclear. In this paper, we demonstrate that this is directly attributed to the presence of *undistillable classes*: when trained with distillation, the teacher's knowledge of some classes is incomprehensible to the student model. We observe that while KD improves the overall accuracy, it is at the cost of the model becoming inaccurate in these undistillable classes. After establishing their widespread existence in state-of-the-art distillation methods, we illustrate their correlation with the capacity gap between teacher and student models. Finally, we present a simple "Teach Less Learn More" (TLLM) framework to identify and discard the undistillable classes during training. We validate the effectiveness of our approach on multiple datasets with varying network architectures. In all settings, our proposed method is able to exceed the performance of competitive state-of-the-art techniques.

1 Introduction

More accurate machine learning models often demand more computation and memory at test time, making them difficult to deploy on computational-constraint devices. Knowledge distillation (KD) alleviates this burden by transferring the knowledge from an expensive teacher model to a cheap student model to improve the performance of this more efficient network. Over the past several years, we have witnessed a huge success in knowledge distillation and a surge of related literature on designing better distillation techniques.

An intuitive thought of knowledge distillation is that better teachers are supposed to make better students since a larger model can learn more visually meaningful and task-related information, and a student model can presumably benefit from learning with more informative knowledge. However, recent works show that such intuition is incorrect. In fact, prior works found that students distilled from a bigger teacher, one with more parameters and higher accuracy, can perform worse than the same students distilled from a smaller teacher [20, 8, 33, 22, 30]. The situation is getting more severe when training on a large-scale, challenging dataset such as ImageNet [4]. More surprisingly, the model with the same architecture [46] or even a model with lower performance [16, 43, 47] can be used as a teacher network to perform knowledge distillation, which plays a role of regularization [29, 21, 49]. Indeed, a large body of researches [52, 32, 50, 15, 31] devoted to solving this problem, but few minimal efforts have been put into understanding this phenomenon.

---

[*]Corresponding Author

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

In this paper, we propose a new data-centric perspective on the phenomenon of "larger teacher, worse student". In contrast to the previous works, we cast the inefficacy of large teachers as a fundamental consequence of the class-dependent bias in KD. Specifically, we claim that:

The undistillable classes are a direct result of the inefficacy of large teachers in distillation.

Recall that prior works attribute the failure of large teachers in KD to the capacity mismatch between the teacher and student model. In other words, the student model cannot learn the teacher's knowledge due to their insufficient expressive power. Indeed, we find that their claim is true for *some* classes that posses bad *distillability*. We posit that these classes cause seemingly mismatched capacity over all samples in the dataset.

The empirical study supports our hypothesis. For samples from the undistillable classes, the feature representation similarity between the teacher and student model is extremely low compared to the regular classes. Furthermore, perhaps less surprisingly, the distilled model could obtain lower accuracy on these undistillable classes than their vanilla-trained counterpart. To further corroborate our theory, we show that the number of undistillable classes increases when the capacity gap between the two models increases.

After verifying our hypothesis, a natural question would be raised: to what extent do these undistillable classes exist? When discussing the property of knowledge distillation, previous literature typically evaluates vanilla knowledge distillation [13]. However, considering the evolution of distillation techniques over the past several years, we believe it is necessary to expand our study. To this end, we investigate the existence of the undistillable classes over three standard datasets (CIFAR100 [19], ImageNet1K [5], CUB-200 [39]) with more than 20 modern distillation techniques. We also include the evaluation of advanced architectures, i.e., vision transformer [36]. Our study shows that the undistillable classes generally exist, usually taking over from 10% to 50% of the total classes, depending on the distillation methods, datasets, and teacher-student pairs.

To resolve this issue, we present a novel distillation framework called "Teach Less, Learn More" distillation (TLLM). It is motivated by the successful teaching strategy in pedagogy[34], where teachers are encouraged to do less rote learning and provide more spaces for students to explore and discover their talents. Our methodology is conceptually similar: we aim to identify the undistillable classes and remove them entirely during distillation, allowing the student model to explore the representations of these classes with their own capacity. Specifically, we record the per-class teaching curve (distillation losses) and calculate its change over a moving window of K epochs. If the teaching curve for some particular classes is stagnated or upward, we consider the knowledge transfer process for these classes is no longer necessary. Then, we remove these classes in distillation (if it is an output-based KD, we replace them with the label smoothing technique to compensate for the regularization effect). Our approach, despite its simplicity, is proven to be effective in preventing the adverse effect brought by the undistillable classes and improving the overall accuracy.

Overall, we emphasize our contributions are the following: 1) we analytically show that the undistillable classes are the cause of inefficacy of the large teacher model; 2) we demonstrate that the accuracy of these undistillable classes drops after distillation, and our extensive experiments showing this is a general phenomenon, irrespective of distillation methods, datasets, or teacher-student pairs; 3) we propose a simple yet effective framework to identify and discard undistillable classes and illustrate the effectiveness our approach with extensive experiments.

2 On the Undistillable Classes in Knowledge Distillation

2.1 Formal Definition

In this section, we formally define the undistillable classes. Considering an multi-class predictor $F : \mathbb{R}^d \to \mathbb{R}^k$ as student and another predictor $G : \mathbb{R}^d \to \mathbb{R}^k$ as teacher. Giving a traing dataset $S = \{(x_i, y_i)_{i=1}^n\} \sim \mathbb{P}^n$ for distribution $\mathbb{P}$ over a set of instance $\mathcal{X}$ and label $\mathcal{Y} = [L] = [1, 2, \ldots, L]$. In the standard training, the goal is to approximate the risk $R(f; S)$ of functional class $f \in F$ via the empirical risk $\hat{R}(\mathbf{f}; S) = \frac{1}{N} \sum_n l(y, \mathbf{f}(x))$, for any bounded loss. For knowledge distillation, we can rewrite the distilled risk as $\tilde{R}(\mathbf{f}; S) = \frac{1}{N} \sum_n l(\mathbf{g}(x), \mathbf{f}(x))$, where the functional class $g \in G$.

The conventional setting consider all classes equally. Without loss of generality, we will consider the $S = S_r \bigcup S_u \sim \mathbb{P}^n$, where we split the data over distribution $\mathbb{P}$ into two categories, each category

Figure 1: The representation agreement measured by CKA between teacher model and student model. For student network, the samples from undistillable classes clearly fail to match the representation from teacher model.

contains non-overlapping instances $S_u = \{(x_i, y_i^u)_{i=1}^n\}, \mathcal{Y}^u = [L] = \{L_{n+1}, L_{n+2}, \cdots, L\}, S_r = S \setminus S_u$ and $|\cdot|_c$ be a appropriate distillability measurement. In our context, we define the distillability function $|\cdot|_c$ as the difference in performance between the distilled student model with the train-from-scratch counterpart under certain evaluation metrics. Let $E(\cdot)$ be an evaluation metric that measures the performance of a particular multi-class predictor on S. Then, formally, we define $|\cdot|_c = E(F_{kd}) - E(F_{vanilla})$. Finally, we define that S_u are a set of samples from the *undistillable classes* in distillation iff $|\mathbf{f}; S_u|_c \ll |\mathbf{f}; S_r|_c$.

2.2 Mismatched Representation for Undistillable Classes

The previous section formally defines the undistillable classes as classes with bad distillability. In this section, we develop a criterion to measure the distillability of a class quantitatively. Recall that the student is typically encouraged to mimic the behavior of the teacher model. Therefore, a converged student should impeccably match the teacher's behavior in an ideal setting. It implies that their feature representations should be the same as the teachers', given the same input on both models. As a result, we harness the similarity of feature representations between teacher and student to reflect the level of distillability of the student model. Inspired by Zhu et al. [52], we use the Center Kernel Alignment (CKA) [18] to calculate the representation similarity between two neural networks. To create a typical case of capacity mismatch, we follow the previous works [4] to use a ResNet56 as our pre-trained teacher model and a modified ResNet24 as the student model (see Appendix for details). We perform standard feature knowledge distillation [28] on stage four, which contains nine consecutive convolutional blocks. We choose to compare the network representation at convergence. For the CKA score figure, we primarily focus the score on the diagonal, which indicates the representation similarity of the convolutional layer at the same position in the network. In order to compare the representation similarity of samples from different types of classes, we deliberately choose 12 test samples from distinct classes. Note that we use samples from the test set to ensure that the observed behavior is not due to ad-hoc memorization.

In the middle of Figure 1, the feature similarity between teacher and student on each corresponding layer is presented. We can observe that the CKA scores for most layers are less than 0.6, and for some layers are even less than 0.5. These results indicate that despite the student indeed learning to match the teacher's representations, their features are far from perfect alignment. Notably, the representation similarity score is calculated based on the average score over a batch. Therefore, we decouple the matrices and check the CKA score for each sample individually. On the left side and right side of Figure 1, we give the CKA matrices at the last three layers for 12 samples. Each side contains six samples. We notice a clear trend: the CKA scores for samples from the left side are obviously much lower than those on the right side, indicating that the mismatched representations are not uniformly distributed over all samples. Therefore, we name the classes on the left side as *undistillable classes*. Our observation contradicts the conclusion from the prior work, which attributes the mismatched capacity as a general issue for all data [52, 4, 20]. We later show that at the left top of Figure 4, the accuracy for the undistillable classes drops after training with KD compared to their train-from-scratch counterpart.

Figure 2: The ΔPA versus ΔAcc for three teacher-student pairs on CIFAR100. The Pearson's r is higher than 0.65 for all figures.

2.3 Bad Distillability hurts Accuracy

As aforementioned, a model would contain some classes with bad distillability. But what is the consequence of distilling knowledge to these classes? In this section, we show that the quality of KD (i.e., accuracy) is highly correlated to their distillability. Here we record the difference in accuracy between the vanilla trained model (training without distillation) and the model trained with knowledge distillation. Particularly, we adopt per-class accuracy:

$$\Delta \mathrm{ACC}^m = \mathrm{ACC}^m_{\mathrm{vanilla}} - \mathrm{ACC}^m_{\mathrm{kd}} \tag{1}$$

where $m \in \mathbb{Y}$. The motivation behind this metric is straightforward: if the $\Delta \mathrm{ACC}^m > 0$, then for m^{th} class, the effect of KD is positive; otherwise, the KD hurts the student's performance on m^{th} class. To demonstrate the correlation between per-class accuracy and per-class distillability, a naive approach is to compare the ΔACC with the CKA scores, as shown in the previous section. However, CKA measures per-layer feature representation similarity; simply averaging over the total number of layers may be inaccurate, not to mention that the teacher model usually contains more layers than students. Therefore, we present a new metric based on average prediction agreement:

$$\mathrm{PA} := \frac{1}{n} \sum_{i=1}^{n} \mathbb{1} \operatorname{argmax} \sigma(z_{t,i}) = \operatorname{argmax} \sigma(z_{s,i}) \tag{2}$$

where $\sigma(z_t) = \frac{\exp(z_i)}{\sum_j \exp(z_i)}$ and $\sigma(z_s) = \frac{\exp(z_s)}{\sum_j \exp(z_s)}$ is the output of softmax function for teacher model and student model, respectively. Equation 2 is inspired by the fact that if the feature representations between two models are exactly the same, these two models ought to produce the same top-1 label. Similar to ΔAcc, here we focus on the difference in prediction agreement ΔPA between two models; one is trained from scratch, and another is trained with distillation:

$$\Delta \mathrm{PA}^m := \mathrm{PA}^m_{\mathrm{vanilla}} - \mathrm{PA}^m_{\mathrm{kd}} \tag{3}$$

Specifically, we put these two metrics in a scatter plot chart for three varying teacher-student pairs on CIFAR100. Figure 2 reveals that for most of the classes with $\Delta \mathrm{ACC} \leq 0$, its corresponding $\Delta \mathrm{PA} \leq 0$ as well, indicating that if the student *become* disagrees with the teacher's prediction, the teacher's supervision can hurt student's performance on this particular class. In addition, we can observe that the level of disagreement is linearly correlated to the level of performance change: when measured with the Pearson's r, it obtained over 0.65 with a p-value less than 0.0005 on all three teacher-student combination, showing a statistically significant linear correlation between these two metrics. In conclusion, for any class in the student model, if it is undistillable, it certainly has $\Delta \mathrm{ACC}^m < 0$.

2.4 The Larger the Capacity Gap, the More the Undistillable Classes

Now, we redirect our attention to the correlation between the level of capacity gap and the presence of the undistillable classes. We propose to leverage multiple teacher networks with varying capacity to distilled a single, low-capacity student. Specifically, we select the ResNet20 as our student model,

Figure 3: **Left:** Per-class ACC and per-class ΔACC for three teacher-student pairs in CIFAR100. **Right:** Proportion of Undistillable Classes distilling ResNet20 with three teacher models.

and pick ResNet44, ResNet56, and ResNet110 as three individual teacher model. For each set of experiments, we adopt one teacher model from the above to train a student model via vanilla KD [13]. This procedure mirrors that of mismatched capacity experiments in Cho et al. [4], except that our goal is to investigate the relationship of per-class accuracy with the capacity gap. As shown in Figure 3, we observe a clear relation between increase of the number undistillable classes, as increase in the capacity gap between models. Specifically, the number of total undistillable classes for the smallest student model (ResNet44) is almost tripled compare to the largest largest model (ResNet101).

2.5 On the Existence of the Undistillable Classes

The knowledge distillation is well-known for its "free" gain over compact models *on average* on an i.i.d test set. Modern distillation techniques only focus on improving the overall accuracy of the student model, with an intuition that the distillation is beneficial for all classes. Indeed, the overall accuracy is paramount, but the per-class accuracy is also important in many cases. Nevertheless, the distillation method inevitably brings class-dependent bias into the student model. As briefly shown in Figure 4, the distilled student model shows obvious class-dependent bias on all datasets. It is also worth noting that the accuracy drops dramatically for some undistillable classes. For instance, on ImageNet1K, there are 127 classes that lose over 4% accuracy compared to their vanilla trained counterpart, and more than nine classes lose over 10% on the test set.

In recent years, the techniques of distillation have evolved dramatically, i.e., feature-based distillation and self-supervision-based distillation [35]. Therefore, to ensure the undistillable classes are not a unique byproduct of the vanilla KD, we extend our experiments to include 26 state-of-the-art distillation frameworks, each of them evaluated by five different teacher-student pairs on CIFAR100. We categorize them into two groups (output-based KD and feature-based KD). Table 1 give a list of all methods that we used for evaluation. We only present the results for 13 of them due to limited space; the complete analysis and more evaluation of ImageNet-1K can be found in Appendix. Figure 5 shows the number of undistillable classes. It is surprising to show that all of them contain undistillable classes. For instance, the Resnet32x4:Resnet8x4 with vanilla KD has 52 undistillable classes, more the half of the total classes. Despite so many undistillable classes, all distillation methods improve the vanilla student model, some by a large margin. Such a phenomenon indicates that the effect of knowledge distillation is non-uniform at the class level. Moreover, the proportion of the undistillable classes is taking over from 10% to 50% over the total number of classes. Therefore, it is critical and necessary to control and reduce the number of undistillable classes in the student network.

Table 1: A summary of all distillation methods that we used for evaluation in Section 2.5

Method	KD [13]	FitNet [28]	AT [44]	SP [38]	CC [26]	VID [1]	RKD [24]	PKT [25]	AB [12]	FT [17]	FSP [42]	NST [14]	CRD [35]
Pub	Arxiv'14	ICLR'15	Arxiv'16	ICCV'19	ICCV'19	CVPR'19	CVPR'19	ECCV'18	AAAI'19	Neurips18	CVPR'17	Arxiv'18	ICLR'19
Output	✓	✗	✗	✗	✓	✗	✗	✓	✗	✗	✗	✓	✗
Feature	✗	✓	✓	✓	✗	✓	✓	✓	✓	✓	✓	✗	✓

Method	SSKD [40]	PAD [48]	WSKD [51]	LST [30]	OH [11]	TA [20]	ESKD [4]	SCKD [52]	KR [2]	SFTN [23]	CID [6]	FKD [10]	DKD [50]
Pub	ECCV'20	ECCV'20	ICLR'20	ICLR'20	ICCV'19	AAAI'20	ICCV'19	ICCV'21	ICCV'21	Neurips'21	Neurips'21	ICLR'22	CVPR'22
Output	✓	✓	✓	✓	✗	✓	✓	✓	✗	✓	✓	✓	✓
Feature	✗	✗	✗	✗	✓	✗	✗	✓	✗	✓	✗	✗	✗

Figure 4: The per-class ΔACC of knowledge distillation on three datasets (CIFAR100 [19]/ImageNet1K [5]/CUB-200 [39]) with vanilla KD [13]. We only show the first 500 class in ImageNet1K and the first 100 classes in CUB-200. The dashed line denotes the improvement of average accuracy using KD.

3 Teach Less, Learn More (TLLM): Identifying and Discarding the Undistillable Classes

We have stressed the adverse effect and characterized the properties of the undistillable classes from the previous section. To this end, we give a simple framework, named "Teach Less, Learn More" distillation (TLLM), which analogy to a successful teaching principal in the pedagogy, to build better KD algorithms. Our idea is conceptually similar to the TLLM in the pedagogy, where the student is encouraged to have more autonomy and devise their own solutions to problems. In practice, the student model is supervised by both teacher's knowledge and the ground truth labels. Training with the model's task-oriented objectives is critical to the eventual performance [13], and provably to correct the wrong gradient directions that are brought by the teacher's mistaken knowledge [16]. Therefore, what we do is simple: identify the undistillable classes and then remove them from the distillation process. As a result, the student can learn these classes directly from the ground truth labels without interference.

The critical challenge of TLLM is how to find the undistillable classes during training. A naive yet computational expansive approach is first to train the model to convergence with distillation and then

Figure 5: **Top**: the number of undistillable classes for diverse teacher-student pair evaluated by various distillation methods. More can be found in the Appendix. **Bottom left**: Three types of distillation approaches. **Bottom middle**: Definition of undistillable classes. **Bottom right**: Each size of circle represent a range of undistillable class number.

retrain it by manually eliminating the undistillable classes according to the performance on the test set. Instead, we propose to monitor the teaching curves (distillation losses) and set up a criterion to find the undistillable classes during training that are more computationally efficient.

Specifically, we pay attention to the per-class teaching curve, i.e., teaching curve $l(y_m, \mathbf{f}(x))$ on m^{th} class, instead of the averaged distillation loss over the entire datasets. The teaching curve is calculated on the validation set. Then, we set a moving window over K epochs, which is started at S^{th} epoch and end at $(S + K)^{th}$ epoch. During the distillation process, we record and update the per-class teaching curve $[l_S(y_m, \mathbf{f}(x)), l_{S+K}(y_m, \mathbf{f}(x))]$. If $l_S(y_m, \mathbf{f}(x)) - l_{S+K}(y_m, \mathbf{f}(x)) \leq \eta$, $0 \leq \eta$, meaning that the loss is moving upward in the K epochs moving window. Figure 3 gives an example of the teaching curve for an undistillable class. After training with approximately 50 epochs, the loss for this particular class suddenly jumps. Therefore, our method can capture such behavior, then identify and remove these undistillable classes during training. It is worth noting that these classes remain in the task-oriented objective for the student, making sure that the student can still learn from these data. Our approach is very efficient since the extra computational cost is linearly correlated with the number of classes, usually not a big number.

4 Experiment

4.1 Main Results

In this section, we evaluate our proposed method on CIFAR100 [19] and ImageNet [5] under various distillation settings. We refer reader to the Appendix for the implementation details.

CIFAR100. As aforementioned, our approach is orthogonal to other distillation techniques. Therefore, we investigate the performance of TLLM when combined with other methods. We report the experimental results on CIFAR100, which average over five trials. Specifically, we compare six distillation methods, and for each of them, we add our method to theirs. As shown in Table 2, our method consistently improve the overall accuracy for baseline. For instance, we improve the vanilla KD [13] by 2.54%. The performance gain mostly comes from the increased accuracy on undistillable

Table 2: Experimental results on CIFAR100 with CNN architectures. We observe that our approach improves overall accuracy and significantly reduces the number of undistillable classes.

T-S Pair	ResNet32x4/ResNet8x4 (%)			ResNet50/MobileNetV2 (%)			ResNet32x4/ShuffleNetV1 (%)		
Method	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ
Teacher	79.42	-	-	79.34	-	-	79.42	-	-
Student	72.50	-	-	64.60	-	-	70.50	-	-
KD [13]	73.08	**75.53**	+2.54	67.28	**69.54**	+2.26	74.07	**76.67**	+2.60
FitNet [28]	73.50	**75.52**	+2.02	63.06	**66.33**	+3.27	73.59	**75.82**	+2.23
AT [44]	73.44	**75.21**	+1.77	58.58	**61.70**	+3.12	71.73	**75.10**	+3.37
OH [11]	74.98	**76.82**	+1.84	67.69	**69.21**	+1.52	77.43	**79.05**	+1.62
KR [2]	75.63	**76.84**	+1.21	69.89	**71.84**	+1.95	77.14	**78.87**	+1.73
SFTN [23]	76.64	**77.83**	+1.19	70.01	**70.94**	+0.93	79.58	**80.04**	+0.46

classes. Later, we will show that our approach also reduces the number of undistillable classes. It is also surprising to find that some methods that were once inferior to other approaches, i.e., the accuracy of OH [11] is 0.65% lower than KR [2] on ResNet32x4/ResNet8x4, obtain higher accuracy after applying TLLM, showing that many "outdated" algorithms have the potential to be quality methods. Moreover, our approach is practical for both output-based (i.e., KD [13])and feature-based distillation [28, 2, 44] algorithms.

ImageNet. ImageNet is a large-scale classification dataset that contains 1.28 million images for training and 50k images for validation. Unlike conventional papers that only report the performance of CNN models, we also consider vision transformer (ViT), an advanced network architecture that has drawn increasing attention lately.

For CNN-based architectures, we evaluate two teacher-student pairs: 1) ResNet32 as a pretrained teacher and ResNet18 as a student model, a widely adopted setting follows CRD [35], 2) ResNet50 as a pretrained teacher, and MobileNetV1 as a student model, a less conventional setting that some papers have used. The experimental results are reported in Table 7. Our

Figure 6: Teaching curve for regular class and undistillable class.

TLLM, which is built based on KR [9], achieves a considerable improvement over its baseline. It is also worth mentioning that the performance of TLLM outperforms other state-of-the-art distillation methods.

For ViT architectures, we evaluate two types of teacher-student pairs: 1) the RegNetY [27] and ViT-Tiny/ViT-Small [7] pairs are the popular setting in DeiT [36] which apply a CNN model as a teacher network to distill a vision transformer, 2) the CaiT-S23 [37] and ViT-Tiny pairs adopt an advanced ViT model as a teacher, whose performance is slightly inferior to RegNetY. We compare with DeiT [36], a benchmark that uses teachers' hard labels as dark knowledge to supervise the student network. We notice that in Table 4, we achieve higher accuracy than DeiT on all teacher-student pairs. Particularly, when the capacity gap between teacher and student is large, i.e., RegNetY/ViT-Tiny and CaiT-S24/ViT-Small, the improvement in the validation set is more notable.

4.2 Ablation Study

Number of the Undistillable classes. Our method specifically identified the undistillable classes and then discarded them during distillation. Therefore, we conduct experiments to check whether our approach reduces the number of undistillable classes. In the Appendix, we show that our proposed TLLM significantly reduces the number of undistillable classes in the student models, allowing balanced performance improvement.

Table 3: Experimental results on ImageNet1K with CNN architectures.

Teacher	Baseline	Distillation Framework (%)									
ResNet32	ResNet18	KD [13]	AT [44]	OFD [11]	CRD [35]	SRRL [41]	KR [2]	SFTN [23]	CID [11]	DKD [50]	**TLLM**
73.3	69.8	70.7	70.7	71.2	71.2	71.7	71.6	71.1	71.9	71.7	**72.6**
ResNet50	MobileNetV1	KD	AT	OFD	CRD	SRRL	KR	SFTN	CID	DKD	**TLLM**
76.2	68.9	70.5	69.6	71.3	71.4	71.7	72.6	71.5	72.3	72.1	**73.2**

Table 4: Experimental results on ImageNet1K with vision transformer architectures.

T-S Pair	RegNetY/ViT-Tiny (%)		RegNetY/ViT-Small (%)		CaiT-S24/ViT-Tiny (%)		CaiT-S24/ViT-Small (%)	
Method	Vanilla	TLLM	Vanilla	TLLM	Vanilla	TLLM	Vanilla	TLLM
Teacher	82.9	-	82.7	-	82.7	-	82.7	-
Student	72.2	-	79.9	-	72.2	-	79.9	-
KD/DeiT [36]	74.5	$\mathbf{76.3}_{+1.8}$	81.2	$\mathbf{81.9}_{+0.7}$	74.4	$\mathbf{76.1}_{+1.7}$	81.3	$\mathbf{82.0}_{+0.7}$

Does TLLM allow larger teacher to make better student? Our approach is motivated to resolve the "larger teacher, worse student problem"; thus, it is natural to verify whether our approach can solve this issue. In the Appendix, we show that our approach allows the larger teacher to distill students with higher accuracy.

5   Analysis of the Undistillable Classes

This section will thoroughly analyze the undistillable classes we observed in the previous empirical study.

5.1   Hard Classes of *Student* $\neq$ Undistillable Classes

One may wonder whether the undistillable classes can be represented by the hard classes in the student model (classes with relatively low accuracy). This is a reasonable hypothesis since challenging classes of student networks (trained without distillation) can be hard to gain more knowledge from the teacher. Nevertheless, we show that undistillable classes are not the hard class in the student model. Specifically, we consider three varying teacher-student pairs: ResNet32x4/ResNet18, WRN-40-2/WRN-16-1, and ResNet56/ResNet20 on CIFAR100 dataset that is trained with vanilla KD [13]. We compare the test accuracy of the student model with the improvement in test accuracy with the student model train with and without KD. Figure 7 present the results.

Figure 7: Hard classes of student model are not undistillable classes

We can observe that the correlation between students' accuracy and the improvement of KD is almost random, showing that the hard classes of a student are not equivalent to undistillable classes.

5.2   Hard Classes of *Teacher* $\neq$ Undistillable Classes

Another reasonable hypothesis is that the challenging classes in teacher model can be undistillable classes because teacher model is normally imperfect. For instance, ResNet-50 can only achieve 76.2% on ImageNet dataset. Can we find undistillable classes by looking at the hard classes of the teacher model? To answer this question, we conduct similar experiments as in the previous section. The only difference is that we record the teacher's test accuracy instead of recording the student's test

Figure 8: Hard classes of teacher model are not undistillable classes

Figure 9: Visualizing of the penultimate layer representation of ResNet8x4 on CIFAR-100 training set using t-SNE. Left: training with ground truth label. Right: training with knowledge distillation. The purple color represents undistillable classes, and the yellow color denotes the rest of the classes.

accuracy. Also, we conduct experiments on three teacher-student pairs. Figure 8 presents the results, which lead to the same conclusion that hard classes of teacher model are not undistillable classes.

5.3 Visualization of Undistillable Classes versus Distillable Classes

To give a more intuitive understanding of undistillable classes, we utilize t-SNE to visualize the penultimate layer representations of ResNet8x4 on CIFAR-100 trained with ground truth labels and distillation. Figure 9 presents the visualization. We can observe that those clusters with clean boundaries (meaning that their prediction is accurate) can be either distillable or undistillable classes. It again verifies our previous conclusion that we can not tell whether a class is distillable or not based on their relative accuracy on the student model.

6 Conclusion

This paper studies the "larger teacher, worse student" phenomena in knowledge distillation. Unlike prior works, which attribute the inefficacy of large teachers as a capacity mismatch issue on samples, we consider the presence of undistillable classes as the direct cause of mismatched capacity. Our paper verified that these classes lower the ability of the student model to match the teacher's feature representation and predictive distribution, making the accuracy drops considerably in some arbitrary classes, therefore, hurting the overall performance. We further demonstrate that the existence of undistillable classes is universal, irrespective of distillation methods, datasets, and student-teacher configurations. Finally, we propose a "teacher less, learn more" (TLLM) method to alleviate this issue by targeting and removing samples from the undistillable classes. Our experiments have shown that our TLLM can greatly eliminate the adverse effect of undistillable classes to improve the overall performance significantly. Overall, we believe that our analysis and proposed method provides an interesting and practical new perspective on designing distillation algorithms.

References

[1] Sungsoo Ahn, Shell Xu Hu, Andreas Damianou, Neil D Lawrence, and Zhenwen Dai. Variational information distillation for knowledge transfer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9163–9171, 2019.

[2] Pengguang Chen, Shu Liu, Hengshuang Zhao, and Jiaya Jia. Distilling knowledge via knowledge review. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5008–5017, 2021.

[3] Tianqi Chen, Mu Li, Yutian Li, Min Lin, Naiyan Wang, Minjie Wang, Tianjun Xiao, Bing Xu, Chiyuan Zhang, and Zheng Zhang. Mxnet: A flexible and efficient machine learning library for heterogeneous distributed systems. *arXiv preprint arXiv:1512.01274*, 2015.

[4] Jang Hyun Cho and Bharath Hariharan. On the efficacy of knowledge distillation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 4794–4802, 2019.

[5] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[6] Xiang Deng and Zhongfei Zhang. Comprehensive knowledge distillation with causal intervention. *Advances in Neural Information Processing Systems*, 34, 2021.

[7] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[8] Tommaso Furlanello, Zachary Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born again neural networks. In *International Conference on Machine Learning*, pages 1607–1616. PMLR, 2018.

[9] Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. Knowledge distillation: A survey. *International Journal of Computer Vision*, 129(6):1789–1819, 2021.

[10] Bobby He and Mete Ozay. Feature kernel distillation. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=tBIQEvApZK5`.

[11] Byeongho Heo, Jeesoo Kim, Sangdoo Yun, Hyojin Park, Nojun Kwak, and Jin Young Choi. A comprehensive overhaul of feature distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1921–1930, 2019.

[12] Byeongho Heo, Minsik Lee, Sangdoo Yun, and Jin Young Choi. Knowledge transfer via distillation of activation boundaries formed by hidden neurons. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3779–3787, 2019.

[13] Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

[14] Zehao Huang and Naiyan Wang. Like what you like: Knowledge distill via neuron selectivity transfer. *arXiv preprint arXiv:1707.01219*, 2017.

[15] Aref Jafari, Mehdi Rezagholizadeh, Pranav Sharma, and Ali Ghodsi. Annealing knowledge distillation. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2493–2504, 2021.

[16] Guangda Ji and Zhanxing Zhu. Knowledge distillation in wide neural networks: Risk bound, data efficiency and imperfect teacher. *Advances in Neural Information Processing Systems*, 33:20823–20833, 2020.

[17] Jangho Kim, SeongUk Park, and Nojun Kwak. Paraphrasing complex network: Network compression via factor transfer. *Advances in neural information processing systems*, 31, 2018.

[18] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International Conference on Machine Learning*, pages 3519–3529. PMLR, 2019.

[19] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[20] Seyed Iman Mirzadeh, Mehrdad Farajtabar, Ang Li, Nir Levine, Akihiro Matsukawa, and Hassan Ghasemzadeh. Improved knowledge distillation via teacher assistant. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5191–5198, 2020.

[21] Hossein Mobahi, Mehrdad Farajtabar, and Peter Bartlett. Self-distillation amplifies regularization in hilbert space. *Advances in Neural Information Processing Systems*, 33:3351–3361, 2020.

[22] Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? *Advances in neural information processing systems*, 32, 2019.

[23] Dae Young Park, Moon-Hyun Cha, Daesin Kim, Bohyung Han, et al. Learning student-friendly teacher networks for knowledge distillation. *Advances in Neural Information Processing Systems*, 34, 2021.

[24] Wonpyo Park, Dongju Kim, Yan Lu, and Minsu Cho. Relational knowledge distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3967–3976, 2019.

[25] Nikolaos Passalis and Anastasios Tefas. Learning deep representations with probabilistic knowledge transfer. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 268–284, 2018.

[26] Baoyun Peng, Xiao Jin, Jiaheng Liu, Dongsheng Li, Yichao Wu, Yu Liu, Shunfeng Zhou, and Zhaoning Zhang. Correlation congruence for knowledge distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 5007–5016, 2019.

[27] Ilija Radosavovic, Raj Prateek Kosaraju, Ross Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10428–10436, 2020.

[28] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014.

[29] Zhiqiang Shen, Zhankui He, and Xiangyang Xue. Meal: Multi-model ensemble via adversarial learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4886–4893, 2019.

[30] Zhiqiang Shen, Zechun Liu, Dejia Xu, Zitian Chen, Kwang-Ting Cheng, and Marios Savvides. Is label smoothing truly incompatible with knowledge distillation: An empirical study. *arXiv preprint arXiv:2104.00676*, 2021.

[31] Wenxian Shi, Yuxuan Song, Hao Zhou, Bohan Li, and Lei Li. Follow your path: a progressive method for knowledge distillation. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 596–611. Springer, 2021.

[32] Wonchul Son, Jaemin Na, Junyong Choi, and Wonjun Hwang. Densely guided knowledge distillation using multiple teacher assistants. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9395–9404, 2021.

[33] Samuel Stanton, Pavel Izmailov, Polina Kirichenko, Alexander A Alemi, and Andrew G Wilson. Does knowledge distillation really work? *Advances in Neural Information Processing Systems*, 34, 2021.

[34] KH Tan, Charlene Tan, and JS Chua. The "teach less, learn more" initiative in singapore schools. *Innovation in education*, pages 153–171, 2008.

[35] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. In *International Conference on Learning Representations*, 2019.

[36] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pages 10347–10357. PMLR, 2021.

[37] Hugo Touvron, Matthieu Cord, Alexandre Sablayrolles, Gabriel Synnaeve, and Hervé Jégou. Going deeper with image transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 32–42, 2021.

[38] Frederick Tung and Greg Mori. Similarity-preserving knowledge distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1365–1374, 2019.

[39] Peter Welinder, Steve Branson, Takeshi Mita, Catherine Wah, Florian Schroff, Serge Belongie, and Pietro Perona. Caltech-ucsd birds 200. 2010.

[40] Guodong Xu, Ziwei Liu, Xiaoxiao Li, and Chen Change Loy. Knowledge distillation meets self-supervision. In *European Conference on Computer Vision*, pages 588–604. Springer, 2020.

[41] Jing Yang, Brais Martinez, Adrian Bulat, Georgios Tzimiropoulos, et al. Knowledge distillation via softmax regression representation learning. International Conference on Learning Representations (ICLR), 2021.

[42] Junho Yim, Donggyu Joo, Jihoon Bae, and Junmo Kim. A gift from knowledge distillation: Fast optimization, network minimization and transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4133–4141, 2017.

[43] Li Yuan, Francis EH Tay, Guilin Li, Tao Wang, and Jiashi Feng. Revisiting knowledge distillation via label smoothing regularization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3903–3911, 2020.

[44] Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. *arXiv preprint arXiv:1612.03928*, 2016.

[45] Chang-Bin Zhang, Peng-Tao Jiang, Qibin Hou, Yunchao Wei, Qi Han, Zhen Li, and Ming-Ming Cheng. Delving deep into label smoothing. *IEEE Transactions on Image Processing*, 30: 5984–5996, 2021.

[46] Linfeng Zhang and Kaisheng Ma. Improve object detection with feature-based knowledge distillation: Towards accurate and efficient detectors. In *International Conference on Learning Representations*, 2020.

[47] Linfeng Zhang, Zhanhong Tan, Jiebo Song, Jingwei Chen, Chenglong Bao, and Kaisheng Ma. Scan: A scalable neural networks framework towards compact and efficient models. *Advances in Neural Information Processing Systems*, 32, 2019.

[48] Youcai Zhang, Zhonghao Lan, Yuchen Dai, Fangao Zeng, Yan Bai, Jie Chang, and Yichen Wei. Prime-aware adaptive distillation. In *European Conference on Computer Vision*, pages 658–674. Springer, 2020.

[49] Zhilu Zhang and Mert Sabuncu. Self-distillation as instance-specific label smoothing. *Advances in Neural Information Processing Systems*, 33:2184–2195, 2020.

[50] Borui Zhao, Quan Cui, Renjie Song, Yiyu Qiu, and Jiajun Liang. Decoupled knowledge distillation. 2022.

[51] Helong Zhou, Liangchen Song, Jiajie Chen, Ye Zhou, Guoli Wang, Junsong Yuan, and Qian Zhang. Rethinking soft labels for knowledge distillation: A bias-variance tradeoff perspective. *arXiv preprint arXiv:2102.00650*, 2021.

[52] Yichen Zhu and Yi Wang. Student customized knowledge distillation: Bridging the gap between student and teacher. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 5057–5066, 2021.

A   Limitations and Potential Negative Social Impacts.

Limitation. Our work investigates the "larger teacher, worse student" phenomena in knowledge distillation through the lens of the undistillable classes. However, we only discuss image classification. Therefore, we do not guarantee the validity of our observation on other tasks, i.e., object detection, and cannot guarantee our approach's effectiveness on these tasks. We propose a method to resolve this issue in Section 4. We have extensively verified our approach's effectiveness in the experimental section but may still fail in other untested scenarios. Also, both our phenomenon and solutions lack theoretical justification and may leave to the future work to solve.

Potential Negative Social Impacts This paper presents the concept of undistillable classes, which can cause potential negative social impacts. Specifically, we found that knowledge distillation can hurt the performance of arbitrary classes. In addition, these classes can be sensitive, i.e., gender or race, which can negatively impact society. In Section 3, we propose a solution to mitigate this problem but cannot fully address them. We hope future work can completely resolve this issue.

Figure 10: The number of undistillable classes for five teacher-student pair evaluated by additional 13 distillation methods.

B   Implementation Details

Implementation Details. For all experiments in CIFAR100 [19], we follows the implementation in CRD [35] (https://github.com/HobbitLong/RepDistiller). For those methods that are not implemented in CRD, we follow the implementation in the open-sourced codes and transplant their approach to CRD. Since most of these method provides hyper-parameters for CIFAR100, we do not modify them. For experiments on CUB200 [39], because few KD methods open-sourced their implementations on this dataset, we leverage the same hyper-parameters as in CIFAR100. For all η in the experiments, we conduct a hyper-parameter search on the validation dataset. During training, we randomly select 5% of the original training data as validation data to find the undistillable classes. We ensure the same number of samples are selected for each class. The best η is obtained through hyper-parameter search, where we split another 5% of the pruned training data as validation data. The test data is not involved during neither training or hyper-parameter search stage. The experiments on ImageNet is similar, except that we only select 2% of them since ImageNet contains more training data than CIFAR100.

For all experiments in ImageNet1K [5], we use different implementations. For vision transformer architectures, we follows the DeiT [36] and CaiT [37] (https://github.com/facebookresearch/deit) to conduct our analysis. For other experiments with CNN architectures, we follows the implementation of mdistiller (https://github.com/megvii-research/mdistiller), we transplant some of the open-sourced methods, i.e., SRRL [41], SFTN [23], CID [6], to this platform for fair comparison.

Details in Section 2.2.   In Section 2.2 we use modified ResNet24 as student to perform KD on a ResNet56 teacher model. Specifically, we ensure that the last stage in ResNet24 has the same number of layers as ResNet56 for fair comparison, since the resolution of the image are the same.

Figure 11: The per-class ΔACC of knowledge distillation on ImageNet1K.

C The Undistillable Classes: More Evidences

We have mentioned the existence of the undistillable classes in general to various methods, and Table 1 gives a comprehensive list of methods for which we studied. To complete the analysis, Figure 10 presents the number of undistillable classes on CIFAR100 with five teacher-student pairs on another thirteen methods. We notice that for most approaches, there are more than 30 classes that are undistillable. We observe no clear advantage in feature-based distillation (OH and KR) compared to output-based distillation. Prior works that have proven capably bridge the capacity gap between teacher and student also demonstrate no superiority on this metric. We think existing methods need

Table 5: Experimental results on CIFAR100 which demonstrate that TLLM reduced number of undistillable classes of the baseline

T-S Pair	ResNet32x4/ResNet8x4 (%)			ResNet50/MobileNetV2 (%)			ResNet32x4/ShuffleNetV1 (%)		
Method	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ
KD [13]	52	16	-36	48	14	-34	54	15	-39
FitNet [28]	39	14	-25	46	17	-29	45	19	-26
AT [44]	37	17	-20	39	13	-26	43	17	-26

Table 6: Larger teacher makes better student with TLLM.

Student	Teacher			
WRN16-2	W-28-2	W-40-2	W-16-4	W-28-4
73.43	75.40	75.72	77.31	78.56
KD	75.21	74.97	75.38	75.21
TLLM	76.02	76.54	77.11	77.35

to take account of this phenomenon more explicitly and carefully. Another observation is that the capacity gap indeed plays a vital role in the KD. We notice that the capacity gap between ResNet50: MobileNetV2 pair and the ResNet32x4: ShuffleNetV1 pair is larger than in other pairs. Thus for some methods, there are more undistillable classes in these pairs.

We further showcase of vision transformer on ImageNet1K. Besides the DeiT-small, as we showed in Figure 4 (bottom), we further provide the ΔACC on the first 500 classes on ImageNet1K for DeiT-tiny, DeiT-base, and DeiT-base with 384 resolution on testing. For CNNs, we provide ResNet50-ResNet18 as teacher-student pairs. As shown in Figure 11, we consistently observe the class-dependent phenomenon.

D   Ablation Study

TLLM reduce the Number of the Undistillable classes. Table 5 shows that our TLLM indeed reduce the undistillable classes.

Does TLLM allow larger teacher to make better student Table 6 presents experiments to verify that our proposed TLLM can indeed improve the student's accuracy when using a large teacher. We see that the vanilla KD achieves lower accuracy for WRN-16-2 on a larger teacher than a smaller teacher, yet our approach can let large teachers make better students.

E   More Analysis of the Undistillable Classes

This section will thoroughly analyze the undistillable classes we observed in the previous empirical study.

E.1   Are Undistillable Classes Network-Independent?

In this section, we study whether undistillable classes are network-independent. We define the network-independent here as different teacher-student pairs. We consider three teacher-student pairs in our experiments, WRN-40-2/WRN-16-2, ResNet56/ResNet20, and ResNet32x4/ResNet8x4. We find out the undistillable classes are network-dependent, as shown in Figure 12

E.2   Are Undistillable Classes Capacity-Gap-Independent?

Given the same teacher model, will the student model have different undistillable classes? In Figure 7 we present five classes that are undistillable classes in four different student architectures, where each of these models is distilled by a RegNet-Y model. Note that these are the only five classes

Table 7: Five classes in DeiT based student that consistently hurt by KD.

ID	Name	ΔACC (%)				
		DeiT-Tiny	DeiT-Small	DeiT-Base	DeiT-Base-384	Avgerage
212	English Setter	-4	-2	-8	-2	-4
356	Weasel	-2	-4	-2	-4	-3
638	Maillot	-8	-24	-10	-14	-14
744	Missile	-12	-18	-18	-8	-14
876	Tub	-4	-8	-6	-8	-6.5

Figure 12: Hard classes of teacher model are not undistillable classes

that are undistillable across four teacher-student pairs. It is perhaps not surprising that most of the undistillable classes are dependent on the capacity gap between the teacher model and the student model

E.3 Are Undistillable Classes Distillation-Independent?

We further explore whether undistillable classes depend on the distillation method. In Figure 13, we compare four different distillation method on the same teacher-student pair (ResNet32x4/ResNet8x4) on CIFAR100. We observe no clear trend that some classes are consistently undistillable across different distillation methods.

Figure 13: Undistillable classes are distillation dependent

F More Experiments of TLLM

F.1 More Experiments on ImageNet

In Table 2, we test our approach on CIFAR100 based on multiple baseline. In this section, we conduct a similar experiments to show that our proposed TLLM can consistently improve the baseline method on large-scale dataset. We conduct three experiments based on KD, AT, and SFTN on ImageNet with two different teacher-student pairs. Our results are presented in Table 8, which indicates the TLLM is effective on these KD methods.

F.2 Comparison with Label Smoothing Baseline

In TLLM, the label smoothing techniques are used when the undistillable classes are discarded during distillation process, in order to compensate for the regularization effect that was brought by the

Table 8: Experimental results on ImageNet with CNN architectures. The TLLM is performed on multiple baseline. Our approach consistently improve the state-of-the-art KD approaches.

T-S Pair	ResNet32/ResNet18 (%)			ResNet50/MobileNetV1 (%)		
Method	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ
Teacher	73.3	-	-	76.2	-	-
Student	69.8	-	-	68.9	-	-
KD [13]	70.7	**72.1**	+1.4	70.5	**72.0**	+1.5
AT [44]	70.7	**71.5**	+0.8	69.6	**70.6**	+1.0
SFTN [23]	71.1	**72.0**	+0.9	71.5	**72.8**	+1.3

KD. Therefore, we compare our approach to the baseline that is trained with label smoothing for fair comparison. We adopt the same hyper-parameter for all experiments (including TLLM), which set $\alpha = 0.1$. Table 9 present the results of comparing TLLM with label smoothing baseline. For fair comparison, our TLLM is ran based on KD [13]. We observe that the label smoothing indeed improve the baseline method. Nevertheless, it is much less effective than KD, which is consistent with the observation in OLS [45]. For instance, on ResNet50/ShuffleNetV1, the label smoothing only improve the student model by 0.28%, while our method increase the top-1 accuracy by 6.17%. In conclusion, we believe this experiment is sufficient to show that the improvement of TLLM cannot solely attribute to the label smoothing techniques.

Table 9: Comparison with label smoothing baseline on CIFAR-100. The LS denotes the label smoothing technique. We also compare with KD [13]. Our TLLM is developed based on KD [13]. All LS experiments use hyper-parameter with 0.1, including TLLM.

T-S Pair	ResNet32x4/ResNet8x4				ResNet50/MobileNetV2				ResNet50/ShuffleNetV1			
Method	Student	KD	LS	TLLM	Student	KD	LS	TLLM	Student	KD	LS	TLLM
Acc (%)	72.50	73.08	73.86	75.53	64.60	67.28	65.11	69.54	70.50	74.07	70.78	76.67

F.3   TLLM on CUB-200-2011

Experimental setting. We set batch size to 64 with initial learning rate of 0.05, the learning rate scheduler is set with decay factor of 0.1 after every 30 epochs to train each model for 120 epochs. We use random cropping, brightness jitter and random flip data augmentations, a standard training setting by MXNet [3]. For KD [13] baseline, we set $\alpha = 0.5$ and temperature $T = 3$. Table 10 gives the experimental results. We can observe a clear advantage of our method over vanilla KD [13]. For example, we improve the KD by 1.19% on ResNet50/ResNet18 teacher-student pairs.

Table 10: Experimental results on CUB-200-2011.

Dataset	CUB-200-2011					
T-S Pair	ResNet50/ResNet18 (%)			ResNet50/MobileNetV2 (%)		
Method	Vanilla	TLLM	Δ	Vanilla	TLLM	Δ
Teacher	82.17	-	-	82.17	-	-
Student	76.89	-	-	79.20	-	-
KD [13]	79.96	**81.15**	+1.19	81.18	**82.26**	+1.08

F.4   Comparison with ESKD

We stress that there are two early-stopping based KD algorithms in ESKD. The first one is the adopt early-stopping *during distillation*, and the second one is the use early-stopping to *train teacher model*. Despite that the latter was emphasis by the ESKD and it is also the commonly referred method, the former was more correlated to our method. Therefore, we compare our approach to the prior

training strategy instead of the latter for fair comparison. Notice that ESKD require hard threshold to stop the distillation process during student's training stage. We conduct a hyper-parameter search which stopped the distillation process at 70%, 80%, 90%, and 95% of the total training epochs and report the best results. Table 11 present the experiments on CIFAR100 and ImageNet1K datasets. On CIFAR100, we use ResNet50 as teacher model and MobileNetV2 as student model. On ImageNet, we use ResNet34 as teacher model and ResNet18 as student model. It is clear that ESKD can improve the baseline method, nevertheless, it is much less effective than our proposed TLLM. We think the reason behind such huge performance gap between TLLM and ESKD is because the class-wise KD perspective.

Table 11: Direct Comparison with ESKD [4].

Dataset	CIFAR100			ImageNet1K		
Teacher-Student Pair	ResNet50/MobileNetV2 (%)			ResNet34/ResNet18 (%)		
Method	Vanilla	ESKD	TLLM	Vanilla	ESKD	TLLM
Top-1 Accuracy (%)	64.6	66.4	**69.5**	69.8	70.7	**72.1**