Preserved central model for faster bidirectional compression in distributed settings

Abstract

We develop a new approach to tackle communication constraints in a distributed learning problem with a central server. We propose and analyze a new algorithm that performs bidirectional compression and achieves the same convergence rate as algorithms using only uplink (from the local workers to the central server) compression. To obtain this improvement, we design MCM, an algorithm such that the downlink compression *only impacts local models*, while the global model is preserved. As a result, and contrary to previous works, the gradients on local servers are computed on *perturbed models*. Consequently, convergence proofs are more challenging and require a precise control of this perturbation. To ensure it, MCM additionally combines model compression with a memory mechanism. This analysis opens new doors, e.g. incorporating worker dependent randomized-models and partial participation.

1 Introduction

Large scale distributed machine learning is widely used in many modern applications [1, 6, 32]. The training is distributed over a potentially large number N of workers that communicate either with a central server [see 17, 25, on federated learning], or using peer-to-peer communication [8, 37, 35].

In this work, we consider a setting using a central server that aggregates updates from remote nodes. Formally, we have a number of features $d \in \mathbb{N}^*$, and a convex cost function $F : \mathbb{R}^d \to \mathbb{R}$. We want to solve the following distributed convex optimization problem using stochastic gradient algorithms [28, 5]: $\min_{w \in \mathbb{R}^d} F(w)$ with $F(w) = \frac{1}{N} \sum_{i=1}^{N} F_i(w)$, where $(F_i)_{i=1}^{N}$ is a *local* risk function (empirical risk or expected risk in a streaming framework). This applies to both instances of *distributed* and *federated* learning.

An important issue of those frameworks is the high communication cost between the workers and the central server [16, Sec. 3.5]. This cost is a concern from several points of view. First, exchanging information can be the bottleneck in terms of speed. Second, the data consumption and the bandwidth usage of training large distributed models can be problematic; and furthermore, the energetic and environmental impact of those exchanges is a growing concern. Over the last few years, new algorithms were introduced, compressing messages in the *upload communications* (i.e., from remote devices to the central server) in order to reduce the size of those exchanges [31, 3, 39, 2, 38, 34, 33, 26, 21]. More recently, a new trend has emerged to also compress the *downlink communication*: this is *bidirectional compression*.

The necessity for bidirectional compression can depend on the situation. For example, a single uplink compression could be sufficient in *asymmetric* regimes in which broadcasting a message to N workers ("one to N") is faster than aggregating the information coming from each node ("N to one"). However, in other regimes, e.g. with few machines, where the bottleneck is the transfer time of a heavy model (up to several GB in modern Deep Learning architectures) the downlink communication cannot be disregarded, as the upload and download speed are of the same order [27].

Furthermore, in a situation in which participants have to systematically download an update (e.g., on their smartphones) to participate in the training, participants would prefer to receive a small size update (compressed) rather than a heavier one. To encompass all situations, we consider algorithms for which the information exchanged is compressed in both directions.

To perform downlink communication, existing bidirectional algorithms [36, 41, 29, 22, 27, 13, 40, 10] first aggregate all the information they have received, compress them and then carry out the broadcast. Both the main "global" model and the "local" ones perform the *same* update with this compressed information. Consequently, the model hold on the central server and the one used on the local workers (to query the gradient oracle) are identical. However, this means that the model on the central server has been artificially *degraded*: instead of using all the information it has received, it is updated with the compressed information.

Here, we focus on *preserving* (instead of *degrading*) the central model: the update made on its side does not depend on the downlink compression. This implies that the local models are *different* from the central model. The local gradients are thus measured on a *"perturbed model"* (or *"perturbed iterate"*): such an approach requires a more involved analysis and the algorithm must be carefully designed to control the deviation between the local and global models [24]. For example, algorithms directly compressing the model or the update would simply not converge.

We propose MCM - *Model Compression with Memory* - a new algorithm that 1) preserves the central model, and 2) uses a memory scheme to reduce the variance of the local model. We prove that the convergence of this method is similar to the one of algorithms using only unidirectional compression.

Potential Impact. Proposing an analysis that handles perturbed iterates is the key to unlock three major challenges of distributed learning run with bidirectionally compressed gradients. First, we show that it is possible to improve the convergence rate by sending *different **randomized** models* to the different workers, this is Rand-MCM. Secondly, this analysis also paves the way to deal with partially participating machines: the adaptation of Rand-MCM to this framework is straightforward; while adapting existing algorithms [29] to partial participation is not practical. Thirdly, this framework is also promising in terms of business applications, e.g., in the situation of learning with privacy guarantees and *with a trusted central server*. We detail those three possible extensions in Subsection 4.1.

Broader impact. This work is aligned with a global effort to make the usage of large scale Federated Learning sustainable by minimizing its environmental impact. Though the impact of such algorithms is expected to be positive, at least on environmental concerns, cautiousness is still required, as a rebound effect may be observed [11]: having energetically cheaper and faster algorithms may result in an increase of such applications, annihilating the gain made by algorithmic progress.

Contributions. We make the following contributions:
1. We propose a new algorithm MCM, combining a memory process to the "preserved" update. To convey the key steps of the proof, we also introduce an auxiliary hypothetical algorithm, Ghost.
2. For those algorithms, we carefully control the variance of the local models w.r.t. the global one. We provide a *contraction equation* involving the control on the local model's variance and show that MCM achieves the same rate of convergence as single compression in strongly-convex, convex and non-convex regimes. We give a comparisons of MCM's rates with existing algorithms in Table 2.
3. We propose a variant, Rand-MCM incorporating diversity into models shared with the local workers and show that it improves convergence for quadratic functions.

The rest of the paper is organized as follows: in Section 2 we present the problem statement and introduce MCM and Rand-MCM. Theoretical results on these algorithms are successively presented in Sections 3 and 4. Finally, we present experiments supporting the theory in Section 5.

2 Problem statement

We consider the minimization problem described in Section 1. In the convex case, we assume there exists an optimal parameter w_*, and denote $F_* = F(w_*)$. We use $\|\cdot\|$ to denote the Euclidean norm. To solve this problem, we rely on a stochastic gradient descent (SGD) algorithm. A stochastic gradient g_{k+1}^i is provided at iteration k in $\mathbb{N}$ to the device i in $[\![1, N]\!]$. This gradient oracle can be computed on a mini-batch of size b. This function is then evaluated at point w_k. In the classical centralized framework (without compression), for a learning rate γ, SGD corresponds to:

$$w_{k+1} = w_k - \gamma \frac{1}{N} \sum_{i=1}^{N} g_{k+1}^i(w_k). \tag{1}$$

Table 1: Features of the main existing algorithms performing compression. e_k^i (resp. E_k) denotes the use of error-feedback at uplink (resp. downlink). h_k^i (resp. H_k) denotes the use of a memory at uplink (resp. downlink). Note that `Dist-EF-SGD` is identical to `Double-Squeeze` but has been developed simultaneously and independently.

	Compr.	e_k^i	h_k^i	E_k	H_k	Rand.	update point
`Qsgd` [3]	one-way						
`ECQ-sgd` [39]	one-way	✓					
`Diana` [26]	one-way		✓				
`Dore` [22]	two-way		✓	✓			degraded
`Double-Squeeze` [36], `Dist-EF-SGD` [41]	two-way	✓		✓			degraded
`Artemis` [27]	two-way		✓				degraded
`MCM`	two-way		✓		✓		non-degraded
`Rand-MCM`	two-way		✓		✓	✓	non-degraded

90 We now describe the framework used for compression.

91 ## 2.1 Bidirectional compression framework

92 Bidirectional compression consists in compressing communications in both directions between the
93 central server and remote devices. We use two different compression operators, respectively $\mathcal{C}_{\mathrm{up}}$ and
94 $\mathcal{C}_{\mathrm{dwn}}$ to compress the message in each direction. Roughly speaking, the update in eq. (1) becomes:

$$ w_{k+1} = w_k - \gamma \mathcal{C}_{\mathrm{dwn}} \left(\frac{1}{N} \sum_{i=1}^{N} \mathcal{C}_{\mathrm{up}}(g_{k+1}^i(w_k)) \right). $$

95 However, this approach has a major drawback. The central server receives and aggregates information
96 $\frac{1}{N} \sum_{i=1}^{N} \mathcal{C}_{\mathrm{up}}(g_{k+1}^i(w_k))$. But in order to be able to broadcast it back, it compresses it, *before*
97 applying the update. We refer to this strategy as the "degraded update" approach. Its major advantage
98 is simplicity, and it was used in all previous papers performing double compression. Yet, it appears to
99 be a waste of valuable information. In this paper, we update the global model w_{k+1} independently of
100 the downlink compression:

$$ \begin{cases} w_{k+1} = w_k - \gamma \frac{1}{N} \sum_{i=1}^{N} \mathcal{C}_{\mathrm{up}}\left(g_{k+1}^i(\hat{w}_k)\right) . \\ \hat{w}_{k+1} = C_{\mathrm{dwn}}(w_{k+1}) \end{cases} \tag{2} $$

101 However, bluntly compressing w_{k+1} in eq. (2) hinders convergence, thus the second part of the update
102 needs to be refined by adding a memory mechanism. **We now describe both communication stages**
103 **of the real `MCM`, which is entirely defined by the following uplink and downlink equations.**

Downlink
$$ \begin{cases} \Omega_{k+1} = w_{k+1} - H_k , \\ \widehat{w}_{k+1} = H_k + \mathcal{C}_{\mathrm{dwn}}(\Omega_{k+1}) \\ H_{k+1} = H_k + \alpha_{\mathrm{dwn}}\mathcal{C}_{\mathrm{dwn}}(\Omega_{k+1}). \end{cases} $$

Uplink
$$ \begin{cases} \forall i \in [\![1, N]\!], \Delta_k^i = g_{k+1}^i(\widehat{w}_k) - h_k^i \\ w_{k+1} = w_k - \frac{\gamma}{N} \sum_{i=1}^{N} \mathcal{C}_{\mathrm{up}}(\Delta_k^i) + h_k^i \\ h_{k+1}^i = h_k^i + \alpha_{\mathrm{up}}\mathcal{C}_{\mathrm{up}}(\Delta_k^i). \end{cases} \tag{3} $$

104 **Downlink Communication.** We introduce a *downlink memory term* $(H_k)_k$, which is available
105 on both workers and central server. The difference Ω_{k+1} between the model and this memory is
106 compressed and exchanged, then the local model is reconstructed from this information. The memory
107 is then updated as defined on left part of eq. (3), with a learning rate α_{dwn}.

108 Introducing this memory mechanism is crucial to control the variance of the local model $\widehat{w}_{k+1}$. To
109 the best of our knowledge `MCM` is the first algorithm that uses such a memory mechanism for downlink
110 compression. This mechanism was introduced by Mishchenko et al. [26] for the uplink compression.

111 **Uplink Communication.** The motivation to introduce an uplink memory term h_k^i for each device
112 $i \in [\![1, N]\!]$ is different, and better understood. Indeed, for the uplink direction, this mechanism is only
113 necessary (and then crucial) to handle heterogeneous workers [i.e., with different data distributions,
114 see e.g. 27]. Here, the difference Δ_k^i between the stochastic gradient g_{k+1}^i at the local model $\widehat{w}_k$ (as
115 defined in eq. (3)) and the memory term is compressed and exchanged. The memory is then updated
116 as defined on right part of eq. (3) with a rate α_{dwn}.

117 **Remark 1** (Rate α_{dwn})**.** *It is necessary to use $\alpha_{\mathrm{dwn}} < 1$. Otherwise, the compression noise tends to*
118 *propagate and is amplified, because of the multiplicative nature of the compression. In Figure 1 we*

119 *compare* `MCM`, *with 3 other strategies: compressing only the update, compressing $w_k - \widehat{w}_{k-1}$, (i.e.,*
120 $\alpha_{\text{dwn}} = 1$*), and compressing the model (i.e., $H_k = 0$), showing that only* `MCM` *converges.*

121 **Remark 2** (Memory vs Error Feedback). *Error feedback is another technique, introduced by Seide*
122 *et al. [31]. In the context of double compression, it has been shown to improve convergence for a*
123 *restrictive class of* contracting *compression operators (which are generally biased) by Zheng et al.*
124 *[41], Tang et al. [36]. However, we note several differences to our approach: (1) for unbiased*
125 *operators - as considered in* `Dore`*, it did not lead to any theoretical improvement [Remark 2 in Sec.*
126 *4.1., 22], (2) moreover, only a fraction (namely $(1 + \omega_{\text{dwn}})^{-1}$) of the "error" $w_{k+1} - \hat{w}_{k+1}$ can be*
127 *preserved in the EF term (see line 18 in algo 1 in Liu et al.). It is thus impossible to recover the*
128 *central preserved model as a function of the degraded model and the EF term.*

129 In Table 1 we summarize the main algorithms for compression in distributed training. As downlink
130 communication can be more efficient than uplink, we consider distinct operators $\mathcal{C}_{\text{dwn}}, \mathcal{C}_{\text{up}}$ and allow
131 the corresponding compressions levels to be distinct: those quantities are defined in Assumption 1.

132 **Assumption 1.** *There exists constants $\omega_{\text{up}}, \omega_{\text{dwn}} \in \mathbb{R}_+^*$, such that the compression operators*
133 $\mathcal{C}_{\text{up}}$ *and* $\mathcal{C}_{\text{dwn}}$ *satisfy the two following properties for all w in $\mathbb{R}^d$: $\mathbb{E}[\mathcal{C}_{\text{up/dwn}}(w)] = w$, and*
134 $\mathbb{E}[\|\mathcal{C}_{\text{up/dwn}}(w) - w\|^2] \leq \omega_{\text{up/dwn}}\|w\|^2$. *The higher is ω, the more aggressive the compression is.*

135 We only consider unbiased operators, that encompass sparsification, quantization and sketching.
136 References and a discussion on those operators, and possible extensions of our results to biased
137 operators are provided in Appendix A.1.

138 **Remark 3** (Related work on Perturbed iterate analysis). *The theory of perturbed iterate analysis was*
139 *introduced by Mania et al. [24] to deal with asynchronous SGD. More recently, it was used by Stich*
140 *and Karimireddy [33], Gorbunov et al. [10] to analyze the convergence of algorithms with uplink*
141 *compressions, error feedback and asynchrony. Using gradients at randomly perturbed points can*
142 *also be seen as a form of randomized smoothing [30], a point we discuss in Appendix A.2.*

2.2 The randomization mechanism, `Rand-MCM`

144 In this subsection, we describe the key feature introduced in `Rand-MCM`: *randomization*. It consists
145 in performing an independent compression for each device instead of performing a single one for
146 all of them. As a consequence, each worker holds a different model centered around the global one.
147 This introduces some supplementary randomness that stabilizes the algorithm. Formally, we will
148 consider N mutually independent compression operators $\mathcal{C}_{\text{dwn},i}$ instead of a single one $\mathcal{C}_{\text{dwn}}$, and the
149 central server will send to the device i at iteration $k + 1$ the compression of the difference between
150 its model and the local memory on worker i: $\mathcal{C}_{\text{dwn},i}(w_{k+1} - H_k^i)$. The tradeoffs associated with this
151 modification are discussed in Section 4.

152 The pseudocode of `Rand-MCM` is given in Algorithm 1 in Appendix A. It incorporates all components
153 described above: 1) the bidirectional compression, 2) the model update using the non-degraded point,
154 3) the two memories, 4) the up and down compression operators, 5) the randomization mechanism.

3 Assumptions and Theoretical analysis

156 We make standard assumptions on $F : \mathbb{R}^d \rightarrow \mathbb{R}$. We first assume that the loss function F is smooth.

157 **Assumption 2** (Smoothness). *F is twice continuously differentiable, and is L-smooth, that is for all*
158 *vectors w_1, w_2 in $\mathbb{R}^d$: $\|\nabla F(w_1) - \nabla F(w_2)\| \leq L\|w_1 - w_2\|$.*

159 Results in Section 3 are provided in a convex, strongly-convex and non-convex setting.

160 **Assumption 3** (Strong convexity). *F is μ-strongly convex (or convex if $\mu = 0$), that is for all vectors*
161 *w_1, w_2 in $\mathbb{R}^d$: $F(w_2) \geq F(w_1) + (w_2 - w_1)^T \nabla F(w_1) + \frac{\mu}{2}\|w_2 - w_1\|_2^2$.*

162 Next, we present the assumption on the stochastic gradients.

163 **Assumption 4** (Noise over stochastic gradients computation). *The noise over stochastic gradients*
164 *for a mini-batch of size b, is uniformly bounded: there exists a constant $\sigma \in \mathbb{R}_+$, such that for all k*
165 *in $\mathbb{N}$, for all i in $[\![1, N]\!]$ and for all w in $\mathbb{R}^d$ we have: $E[\|g_k^i(w) - \nabla F(w)\|^2] \leq \sigma^2/b$.*

166 We here provide guarantees of convergence for `MCM`. `MCM` incorporates an uplink memory term,
167 designed to handle heterogeneous workers. To highlight our main contributions, that concerns the
168 downlink compression, we present the results in the homogeneous setting, that is with $F_i = F_j$ and
169 $\alpha_{\text{up}} = 0$. Similar results (almost identical, up to constant numerical factors) in to the heterogeneous

setting are described in Appendix G. Experiments are also performed on heterogeneous workers. We provide here convergence results in the strongly-convex, then convex case.

Notations and settings. For k in $\mathbb{N}$, we denote $\Upsilon_k = \|w_k - H_{k-1}\|^2$, and define $V_k = \mathbb{E}[\|w_k - w_*\|^2] + 32\gamma L\omega_{\mathrm{dwn}}^2\mathbb{E}[\Upsilon_k]$, which serves as Lyapunov function. V_k is composed of two terms: the first one controls the quadratic distance to the optimal model, and the second controls the variance of the local models $\hat{w}_k$. For both theorems, we choose $\alpha_{\mathrm{dwn}} = (8\omega_{\mathrm{dwn}})^{-1}$. We denote $\Phi(\gamma) := (1 + \omega_{\mathrm{up}})\left(1 + 64\gamma L\omega_{\mathrm{dwn}}^2\right)$.

Limit learning rate: There exists a maximal learning rate to ensure convergence. More specifically, we define $\gamma_{\max} := \min(\gamma_{\max}^{\mathrm{up}}, \gamma_{\max}^{\mathrm{dwn}}, \gamma_{\max}^{\Upsilon})$, where $\gamma_{\max}^{\mathrm{up}} := (2L(1 + \omega_{\mathrm{up}}/N))^{-1}$ corresponds to the classical constraint on the learning rate in the unidirectional regime [see 26, 27], $\gamma_{\max}^{\mathrm{dwn}} := (8L\omega_{\mathrm{dwn}})^{-1}$ is a similar constraint coming from the downlink compression, and $\gamma_{\max}^{\Upsilon} := \left(8L\omega_{\mathrm{dwn}}\sqrt{8\omega_{\mathrm{dwn}} + \omega_{\mathrm{up}}/N}\right)^{-1}$ is a combined constraint that arises when controlling the variance term Υ.[1] Overall, this constraints are weaker than in the "degraded" framework [22, 27], in which $\gamma_{\max}^{\mathrm{Dore}} \leq \left(8L(1 + \omega_{\mathrm{dwn}})(1 + \omega_{\mathrm{up}}/N)\right)^{-1}$. Especially, in the regime in which $\omega_{\mathrm{up,dwn}} \to \infty$ and $\omega_{\mathrm{dwn}} \simeq \omega_{\mathrm{up}} \simeq: \omega$, the maximal learning rate for MCM is $(L\omega^{3/2})^{-1}$, while it is $(L\omega^2)^{-1}$ in [22, 27]. Our $\gamma_{\max}$ is thus larger by a factor $\sqrt{\omega}$, see Table 2. We define $\widetilde{L}$ such that $\gamma_{\max} = (2\widetilde{L})^{-1}$.

Theorem 1 (Convergence of MCM in the homogeneous and strongly-convex case). *Under Assumptions 1 to 4 with $\mu > 0$, for k in $\mathbb{N}$, for any sequence $(\gamma_k)_{k\geq 0} \leq \gamma_{\max}$ we have:*

$$V_k \leq (1 - \gamma_k\mu)V_{k-1} - \gamma_k\mathbb{E}\left[F(\widehat{w}_{k-1}) - F(w_*)\right] + \frac{\gamma_k^2\sigma^2\Phi(\gamma_k)}{Nb}, \tag{4}$$

Consequently, (1) if $\sigma^2 = 0$ (noiseless case), for $\gamma_k \equiv \gamma_{\max}$ we recover a linear convergence rate: $\mathbb{E}[\|w_k - w_*\|^2] \leq (1 - \gamma_{\max}\mu)^k V_0$; (2) if $\sigma^2 > 0$, taking for all K in $\mathbb{N}$, $\gamma_K = 2/(\mu(K+1) + \widetilde{L})$, for the weighted Polyak-Ruppert average $\bar{w}_K = \sum_{k=1}^{K}\lambda_k w_{k-1}/\sum_{k=1}^{K}\lambda_k$, with $\lambda_k := (\gamma_{k-1})^{-1}$,

$$\mathbb{E}\left[F(\bar{w}_K) - F(w_*)\right] \leq \frac{\mu + 2\widetilde{L}}{4\mu K^2}\|w_0 - w_*\|^2 + \frac{\sigma^2(1 + \omega_{\mathrm{up}})}{\mu KNb}\left(1 + \frac{64L\omega_{\mathrm{dwn}}^2}{\mu K}\ln(\mu K + \widetilde{L})\right). \tag{5}$$

Limit Variance (Equation (4)). For a constant γ, the variance term (i.e., term proportional to σ^2) in Equation (4) is upper bounded by $\frac{\gamma^2\sigma^2}{Nb}(1 + \omega_{\mathrm{up}})(1 + 64\gamma L\omega_{\mathrm{dwn}}^2)$. The impact of the downlink compression is attenuated by a factor γ. As γ decreases, this makes the limit variance similar to the one of Diana, i.e., without downlink compression [26, Eq. 16 in Th. 2] and much lower than the variance for previous algorithms using double compression for which the variance scales quadratically with the compression constants as $\gamma^2\sigma^2(1 + \omega_{\mathrm{up}})(1 + \omega_{\mathrm{dwn}})/N$: (1) for Dore, see Corollary 1 in Liu et al. [22] (who indicate $(1 - \rho)^{-1} \geq (1 + \omega_{\mathrm{up}}/N)(1 + \omega_{\mathrm{dwn}})$), (2) for Artemis see Table 2 and Th. 3 point 2 in [27], (3) for [10], see Theorem I.1. (with $\gamma D_1' \propto \gamma^2\sigma^2(1 + \omega_{\mathrm{up}})(1 + \omega_{\mathrm{dwn}})/N$).

Convergence and complexity: With a decaying sequence of steps, we obtain a convergence rate scaling as $O(K^{-1})$ in Equation (5), without dependency on the ω_{dwn} in the dominating term, which only appears in faster decaying terms scaling as K^{-2}. The iteration complexity (i.e., number of iterations to achieve ϵ expected error) is thus at first order $O_{\epsilon\to0}(\frac{\sigma^2(1+\omega_{\mathrm{up}})}{\mu\epsilon Nb})$. Again, this matches the complexity of Diana [14, see Theorem 1 and Corollary 1] and is smaller by a factor $1 + \omega_{\mathrm{dwn}}$ than the one of Artemis, Dore, DIANAsr-DQ (see Corollary I.1. in [10]). Next, we give a convergence result in the convex case.

Theorem 2 (Convergence of MCM, convex case). *Under Assumptions 1 to 4 with $\mu = 0$. For all $k > 0$, for any $\gamma \leq \gamma_{\max}$, we have, for $\bar{w}_k = \frac{1}{k}\sum_{i=0}^{k-1} w_i$,*

$$\gamma\mathbb{E}\left[F(w_{k-1}) - F(w_*)\right] \leq V_{k-1} - V_k + \frac{\gamma^2\sigma^2\Phi(\gamma)}{Nb} \implies \mathbb{E}[F(\bar{w}_k) - F_*] \leq \frac{V_0}{\gamma k} + \frac{\gamma\sigma^2\Phi(\gamma)}{Nb}. \tag{6}$$

Consequently, for K in $\mathbb{N}$ large enough, a step-size $\gamma = \sqrt{\frac{\|w_0 - w_*\|^2 Nb}{(1+\omega_{\mathrm{up}})\sigma^2 K}}$, we have:

$$\mathbb{E}[F(\bar{w}_K) - F_*] \leq 2\sqrt{\frac{\|w_0 - w_*\|^2(1 + \omega_{\mathrm{up}})\sigma^2}{NbK}} + O(K^{-1}). \tag{7}$$

---

[1]The dependency in $\omega^{3/2}$ is similar to the one obtained by Horváth et al. [14] in unidirectional compression in the non-convex case (Theorem 4).

209 *Moreover if $\sigma^2 = 0$ (noiseless case), we recover a faster convergence: $\mathbb{E}[F(\bar{w}_K) - F_*] = O(K^{-1})$.*

210 **Limit Variance (Eq. (6)).** The variance term is identical to the strongly-convex case.

211 **Convergence and complexity (Equation (7)).** The downlink compression constant only appears
212 in the second-order term, scaling as $1/K$. In other words, the convergence rate is equivalent to the
213 convergence rate of `Diana`, in the non-strongly-convex. As K increases, this complexity scales as
214 $\frac{(1+\omega_{\mathrm{up}})}{n\epsilon^2}$ independently of the downlink compression. Again, for previous algorithms with double
215 compression the complexity is at least $O\left(\frac{(1+\omega_{\mathrm{up}})(1+\omega_{\mathrm{dwn}})}{n\epsilon^2}\right)$ (see Corollary I.2 in [10]).

216 **Control of the variance of the local model.**

217 We here present the backbone Lemma of MCM's
218 proof. It allows to control the variance of the
219 local model $\mathbb{E}[\|\hat{w}_k - w_k\|^2 \,|\, w_k]$ (which is upper-
220 bounded by $\omega_{\mathrm{dwn}}\mathbb{E}[\|\Upsilon_k\|^2 \,|\, w_k]$) and to build the
221 Lyapunov function defined in Theorems 1 and 2.

222 This result highlights the impact of the downlink
223 memory term. Without memory, i.e., with $\alpha_{\mathrm{dwn}} =$
224 0, the variance of the local model $\|\hat{w}_k - w_k\|^2$
225 increases with the number of iterations. On the
226 other hand, if α_{dwn} is too large (close to 1), this
227 variance diverges. This behavior is illustrated on

Figure 1: Comparing MCM on two datasets with three other algorithms using a non-degraded update, $\gamma = 1/L$. `Artemis-ND` stands for `Artemis` with a non-degraded update.

228 two real datasets on Figure 1. This phenomenon is similar to the divergence observed in frameworks
229 involving error feedback, when the compression operator is not contractive.

230 **Theorem 3.** *Consider the `MCM` update as in eq. (2). Under Assumptions 1, 2 and 4 with $\mu = 0$, if*
231 $\gamma \leq (8\omega_{\mathrm{dwn}}L)^{-1}$ *and $\alpha \leq (4\omega_{\mathrm{dwn}})-1$, then for all k in $\mathbb{N}$:*

$$\mathbb{E}\left[\Upsilon_k\right] \leq \left(1 - \frac{\alpha_{\mathrm{dwn}}}{2}\right)\mathbb{E}\left[\Upsilon_{k-1}\right] + 2\gamma^2\left(\frac{1}{\alpha_{\mathrm{dwn}}} + \frac{\omega_{\mathrm{up}}}{N}\right)\mathbb{E}\left[\|\nabla F(\hat{w}_{k-1})\|^2\right] + \frac{2\gamma^2\sigma^2(1 + \omega_{\mathrm{up}})}{Nb}.$$

232 This bound provides a recursive control on Υ_k. Beyond the $(1 - \alpha_{\mathrm{dwn}})$ contraction, the bound
233 comprises the squared-norm of the gradient at the previous perturbed iterate, and a noise term.

234 **Summary of rates.** In Table 2, we summarize the rates and complexities, and maximal learning
235 rate for `Diana`, `Artemis`, `Dore` and `MCM`. For simplicity, we ignore absolute constants, and provide
asymptotic values for large $\omega_{\mathrm{up}}, \omega_{\mathrm{dwn}}$, and complexities for $\epsilon \to 0$.

Table 2: Summary of rates on the initial condition, limit variance, asympt. complexities and $\gamma_{\max}$.

Problem		Diana	Artemis, Dore	MCM, Rand-MCM
	$L\gamma_{\max} \propto$	$1/(1 + \omega_{\mathrm{up}})$	$1/(1 + \omega_{\mathrm{up}})(1 + \omega_{\mathrm{dwn}})$	$1/(1 + \omega_{\mathrm{dwn}})\sqrt{1 + \omega_{\mathrm{up}}} \wedge 1/(1 + \omega_{\mathrm{up}})$
	Lim. var. $\propto \gamma^2\sigma^2/n\times$	$(1 + \omega_{\mathrm{up}})$	$(1 + \omega_{\mathrm{up}})(1 + \omega_{\mathrm{dwn}})$	$(1 + \omega_{\mathrm{up}})(1 + \gamma L\omega_{\mathrm{dwn}}^2)$
Str.-convex	Rate on init. cond. (SC)	$(1 - \gamma\mu)^k$	$(1 - \gamma\mu)^k$	$(1 - \gamma\mu)^k$
	Complexity	$(1 + \omega_{\mathrm{up}})/\mu\epsilon N$	$(1 + \omega_{\mathrm{dwn}})(1 + \omega_{\mathrm{up}})/\mu\epsilon N$	$(1 + \omega_{\mathrm{up}})/\mu\epsilon N$
Convex	Complexity	$(\omega_{\mathrm{up}} + 1)/\epsilon^2$	$(1 + \omega_{\mathrm{up}})(1 + \omega_{\mathrm{dwn}})/\epsilon^2$	$(\omega_{\mathrm{up}} + 1)/\epsilon^2$

236

237 **Proof in the heterogeneous case.** To extend Theorems 1 to 3 in the heterogeneous setting
238 for a convex objective (Appendix G), we assume that there exists a constant B in $\mathbb{R}_+$, s.t.:
239 $\frac{1}{N}\sum_{i=0}^{N}\|\nabla F_i(w_*)\|^2 = B^2$. We further define $\Xi_k = \frac{1}{N^2}\sum_{i=1}^{N}\|h_k^i - \nabla F_i(w_*)\|^2$, where for
240 all i in $[\![1, N]\!]$. This term is recursively controled [26, 27] and combined into the Lyapunov function.

241 **Proofs.** To convey the best understanding of the theorems and the spirit of the proof, we introduce a
242 `Ghost` algorithm (impossible to implement) in Appendix D.1. A sketch of the proof describes the
243 main steps in the case of `Ghost`, those steps are similar for `MCM`. Fundamentally, our proof relies on
244 a tight analysis, related to perturbed iterate analysis [24]. Proofs of Theorems 1 to 3 are given in
245 Appendix E. Th. S10 in Appendix E.4 ensures convergence for a non-convex F. Note that the proof
246 for non-convex follows a different approach than the one in Theorems 1 and 2.

247 As mentioned in the introduction, our analysis of perturbed iterate in the context of double com-
248 pression opens new directions: in particular, it opens the door to handling a different model for

each worker. In the next section, we detail those possibilities, and provide theoretical guarantees for `Rand-MCM`, the variant of `MCM` in which instead of sending the same model to all workers, the compression noises are mutually *independent*.

4 Extension to `Rand-MCM`

4.1 Communication and convergence trade-offs

In `Rand-MCM`, we leverage the fact that the compressions used for each worker need not be identical. On the contrary, it is possible to consider *independent* compressions. By doing so, we reduce the impact of the downlink compression.

The relevance of such a modification depends on the framework: while the convergence rate will be improved, the computational time can be slightly increased. Indeed, N compressions need to be computed instead of one: however, this computational time is typically not a bottleneck w.r.t. the communication time. A more important aspect is the communication cost. While the size of each message will remain identical, a different message needs to be sent to each worker. That is, we go from a "one to N" configuration to N "one to one" communications. While this is a drawback, it is not an issue when the bandwidth/transfer time are the bottlenecks, as `Rand-MCM` will result in a better convergence with almost no cost. Furthermore, we argue that handling worker dependent models is essential for several major applications. `Rand-MCM` can directly be adapted to those frameworks.

1. Worker dependent compression. A first simple situation is the case in which workers are allowed to choose the size (or equivalently the compression level) of their updates.

2. Partial participation (PP). Similarly, having N different messages to send to each worker may be unavoidable in the case of *partial participation* of the workers. This is a key feature in Federated Learning frameworks [25]. In the classical distributed framework (without downlink constraints) it is easy to deal with it, as each available worker just queries the global model to compute its gradient on it [see for example 13]. On the other hand, for bidirectional compression, to ensure that all the local models match the central model, the adaptation to partial participation relies on a *synchronization step*. During this step, each worker that has not participated in the last S steps receives the last S corresponding messages as long as it costs less to send this sequence than a full uncompressed model. This is described in the description of the adaptation to partial participation in [27], in the remark preceding Eq. (20) in [29] and by Tang et al. [36, v2 on arxiv for the distributed case], who use a buffer. On the contrary, `Rand-MCM` naturally handles a different model, memory and update per worker. The adaptation to partial participation is thus straightforward. Though theoretical results are out of the scope of this paper, we provide experiments on PP in Appendix B.1 and fig. 4.

One drawback is the necessity to store the N memories $(H_k^i)_{i \in [N]}$ instead of one, which results in an additional memory cost. To circumvent this issue we propose two independent solutions. 1) Keep and use a single memory $\bar{H}_k = N^{-1} \sum_{i=1}^{N} H_k^i$ (as suggested in [27]). It is then necessary to periodically reset the local memories H_k^i on all workers to the averaged value $\bar{H}_k$ (rarely enough not to impact the communication budget). This is illustrated in fig. 4. 2) Use `Rand-MCM` with an arbitrary number of groups $G \ll N$ of workers. In each group $\mathcal{G}_g$, $g \in [G]$, all workers share the same memory (H_k^g) and receive the same update $\mathcal{C}_{\mathrm{dwn},g}(w_{k+1} - H_k^g)$. We call this algorithm `Rand-MCM-G`.

Remark 4 (Protecting the global model from honest-but-curious clients). *Another business advantage of `MCM` and `Rand-MCM` is that providing degraded models to the participants can be used to guarantee privacy, or to ensure the workers participate in good faith, and not only to obtain the model. This issue of detecting ill-intentioned clients (free-riders) that want to obtain the model without actually contributing has been studied by Fraboni et al. [9].*

4.2 Theoretical results

In this Section, we provide two main theoretical results for `Rand-MCM`. First Theorem 4 ensures that the theoretical guarantees are at least as good for `Rand-MCM` as for `MCM`. Then, in Theorem 5, we provide convergence result for both `MCM` and `Rand-MCM` in the case of quadratic functions.

Theorem 4. *Theorems 1 to 3 are valid for `Rand-MCM` and `Rand-MCM-G`.*

The improvement in `Rand-MCM` comes from the fact that we are ultimately averaging the gradients at several random points, reducing the variance coming from this aspect. The goal is obviously to reduce the impact of ω_{dwn}. Keeping in mind that the dominating term in the rate is independent of ω_{dwn}, *we can thus only expect to reduce the second-order term.* Next, the uplink compression noise increases

with the variance of the randomized model, which will not be directly reduced by `Rand-MCM`. As a consequence, we only expect the improvement to be visible in the part of the second-order term that does not depend on ω_{up} (that is, the effect would be the most significant if ω_{up} is small or 0).

This intuition is corroborated by the following result, in which we show that the convergence is improved when adding the randomization process for a quadratic function. Extending the proof beyond quadratic functions is possible, though it requires an assumption on third or higher order derivatives of F (e.g., using self-concordance [4]) to control of $\mathbb{E}\left[||\nabla F(\widehat{w}_{k-1}) - \mathbb{E}[\nabla F(\widehat{w}_{k-1})]||^2 \,\big|\, w_{k-1}\right]$.

Theorem 5 (Convergence in the quadratic case)**.** *Under Assumptions 1 to 4 with $\mu = 0$, if the function is quadratic, after running $K > 0$ iterations, for any $\gamma \leq \gamma_{\mathrm{max}}$, and we have*

$$\mathbb{E}[F(\bar{w}_K) - F_*] \leq \frac{V_0}{\gamma K} + \frac{\gamma\sigma^2\Phi^{\mathrm{Rd}}(\gamma)}{Nb}\,,$$

with $\Phi^{\mathrm{Rd}}(\gamma) = (1 + \omega_{\mathrm{up}})\left(1 + \frac{4\gamma^2 L^2 \omega_{\mathrm{dwn}}}{K}(\frac{1}{\mathbf{C}} + \frac{\omega_{\mathrm{up}}}{N})\right)$ *and* $\mathbf{C} = N$ *for* `Rand-MCM`, $\mathbf{C} = G$ `Rand-MCM-G`, *and* $\mathbf{C} = 1$ *for* `MCM`.

This result is derived in Appendix F. We can make the following comments: (1) The convergence rate for quadratic functions is slightly better than for smooth functions. More specifically, the right hand term in Φ is multiplied by an additional $\gamma\left(\frac{1}{\mathbf{C}} + \frac{\omega_{\mathrm{up}}}{N}\right)$ (w.r.t. Theorem 2), which is decaying at the same rate as γ. Besides, the proof for `Rand-MCM` is substantially modified, as $\mathbb{E}[\nabla F(\widehat{w}_{k-1})]$ is an unbiased estimator of $\nabla F(w_{k-1})$. (2) Moreover, the randomization in `Rand-MCM` (resp. `Rand-MCM-G`) further reduces by a factor N (resp. G) this term. Depending on the relative sizes of ω_{up} and N, this can lead to a significant improvement up to a factor of N. In practice the impact of `Rand-MCM` is noticeable, as illustrated in the following experiments.

5 Experiments

In this section, we illustrate the validity of the theoretical results given in the previous section on both synthetic and real datasets, on (1) least-squares linear regression (LSR), (2) logistic regression (LR), and (3) non-convex deep learning. We compare `MCM` with classical algorithms used in distributed settings: `Diana`, `Artemis`, `Dore` and of course the simplest setting - `SGD`, which is the baseline.

In these experiments, we provide results on the log of the excess loss $F(w_k) - F_*$, averaged on 5 runs, with errors bars displayed on each figure (but not in the "zoom square"), corresponding to the standard deviation of $\log_{10}(F(w_k) - F_*)$. On Figure 3, the X-axis is respectively the number of iterations and the number of bits exchanged. Figure 2 is only displayed w.r.t. the number of exchanged bits, corresponding figures w.r.t. to the number of iterations k are given in Appendix B.

Each experiment has been run with $N = 20$ workers using stochastic scalar quantization [3], w.r.t. 2-norm. To maximize compression, we always quantize on a single level ($s = 1$), unless stated otherwise (for PP and neural network, we use $s = 2$, i.e. 3 levels, and $s = 4$ i.e. 5 levels). We built one toy dataset devoted to linear regression in an homogeneous setting. This toy dataset allows to illustrate `MCM` properties in a simple framework. We also ran experiments with two real datasets commonly used in optimization: *quantum* (defined by Caruana et al. [7], 66 features, 50.000 points, logistic regression) and *superconduct* (analyzed by Hamidieh [12], 82 features, 21.200 points, LSR). Experiments on *quantum* and *superconduct* were conducted with heterogeneous workers obtained by clustering (using *TSNE* [23]) the input points. Finally, we carried out experiments on MNIST [see 20] using a CNN (Figure 2c, $\gamma = 0.1$, quantization with $s = 1$ and infinity norm) and on CIFAR10 [see 18] using LeNet model defined by Lecun et al. [19] (Figure 2d, $\gamma = 0.01$, quantization with $s = 4$ and infinity norm). More details can be found in Appendix B.

Saturation level. All experiments are performed with a constant learning rate γ to observe the bias (initial reduction) and the variance (saturation level) independently. Stochastic gradient descent results in a fast convergence during the first iterations, and then reaches a saturation at a given level proportional to σ^2. Theorem 2 states that the variance of `MCM` is proportional to ω_{up}, this is experimentally observed on Figures 2 and 3: `MCM` meets `Diana` while `Artemis` and `Dore` saturate at a higher level (scaling as $\omega_{\mathrm{up}} \times \omega_{\mathrm{dwn}}$). These trade-offs are preserved with optimized learning rates.

Linear convergence when $\sigma^2 = 0$. The six algorithms present a linear convergence when $\sigma^2 = 0$. This is illustrated by Figure 2b: we ran experiments with a full gradient descent. Note that in

(a) $\sigma^2 \neq 0, \gamma = (L\sqrt{k})^{-1}$ (b) $\sigma^2 = 0, \gamma = L^{-1}$ (c) MNIST with a CNN   (d) CIFAR10 with LeNet

Figure 2: Convergence on toy dataset on LSR (a,b) and on neural networks (c, d).

(a) Quantum in #iter.   (b) Quantum in #bits   (c) Superconduct in #iter.   (d) Superconduct in #bits

Figure 3: Experiments on real dataset with $\gamma = 1/L$, quantization with $s = 1$, LSR (a,b), LR (c,d).

these settings `MCM` has a slightly worse performance than other methods; however, this slow-down is compensated by `Rand-MCM`.

Impact of randomization. The impact of randomization is noticeable on Figures 2b, 3c and 3d. Randomization helps to stabilise convergence of `MCM`: it reduces the variance of the runs and when $\sigma^2 = 0$, it performs identically to `SGD`. Figure 4 illustrates the impact of using a single memory, instead of N, to alleviate the memory cost in the PP setting (Subsection 4.1), with or without periodic reset. Without reset, performance are slightly degraded, but with it, we recover previous results.

Deep learning. Figures 2c and 2d illustrates experiments with neural networks on MNIST and CIFAR10, details on settings are given in Appendix B.3. Again, `MCM` meets `Diana` rates as stated by Theorem S10 (theorem in the non-convex case). On the MNIST dataset, we even observe an interesting smoothing effect: the train loss reaches *smaller* values with `MCM` (that actually corresponds to using stochastic gradients of a *smoothed loss* and can thus avoid some local minima, see [15]).

Figure 4: `Rand-MCM` (PP) on *quantum* with a *single memory* ($s = 2$).

Overall, these experiments show the benefits of `MCM` and `Rand-MCM`, that reach the saturation level of `Diana` while exchanging at 10x to 100x fewer bits. More experiments with partial participation for `Rand-MCM` are given in Appendix B.1. All the code is provided as SM.

6 Conclusion

In this work, we propose a new algorithm to perform bidirectional compression while achieving the convergence rate of algorithms using compression in a single direction. One of the main application of this framework is Federated Learning. With `MCM` we stress the importance of not degrading the global model. In addition, we add the concept of randomization which allows to reduce the variance associated with the downlink compression. The analysis of `MCM` is challenging as the algorithm involves perturbed iterates. Proposing such an analysis is the key to unlocking numerous challenges in distributed learning, e.g., proposing practical algorithms for partial participation, incorporating privacy-preserving schemes *after* the global update is performed, dealing with local steps, etc. This approach could also be pivotal in non-smooth frameworks, as it can be considered as a weak form of randomized smoothing.

References

[1] Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek G. Murray, Benoit Steiner, Paul Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: a system for large-scale machine learning. In *Proceedings of the 12th USENIX conference on Operating Systems Design and Implementation*, OSDI'16, pages 265–283, USA, November 2016. USENIX Association. ISBN 978-1-931971-33-1.

[2] Naman Agarwal, Ananda Theertha Suresh, Felix Xinnan X Yu, Sanjiv Kumar, and Brendan McMahan. cpSGD: Communication-efficient and differentially-private distributed SGD. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems 31*, pages 7564–7575. Curran Associates, Inc., 2018.

[3] Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. QSGD: Communication-Efficient SGD via Gradient Quantization and Encoding. *Advances in Neural Information Processing Systems*, 30:1709–1720, 2017.

[4] Francis Bach. Self-concordant analysis for logistic regression. *Electronic Journal of Statistics*, 4(none):384–414, January 2010. ISSN 1935-7524, 1935-7524. doi: 10.1214/09-EJS521. Publisher: Institute of Mathematical Statistics and Bernoulli Society.

[5] Léon Bottou. Large-Scale Machine Learning with Stochastic Gradient Descent. In Yves Lechevallier and Gilbert Saporta, editors, *Proceedings of COMPSTAT'2010*, pages 177–186, Heidelberg, 2010. Physica-Verlag HD. ISBN 978-3-7908-2604-3. doi: 10.1007/978-3-7908-2604-3_16.

[6] Sebastian Caldas, Sai Meher Karthik Duddu, Peter Wu, Tian Li, Jakub Konečný, H. Brendan McMahan, Virginia Smith, and Ameet Talwalkar. LEAF: A Benchmark for Federated Settings. *arXiv:1812.01097 [cs, stat]*, December 2019. arXiv: 1812.01097.

[7] Rich Caruana, Thorsten Joachims, and Lars Backstrom. KDD-Cup 2004: results and analysis. *ACM SIGKDD Explorations Newsletter*, 6(2):95–108, December 2004. ISSN 1931-0145. doi: 10.1145/1046456.1046470.

[8] Igor Colin, Aurelien Bellet, Joseph Salmon, and Stéphan Clémençon. Gossip Dual Averaging for Decentralized Optimization of Pairwise Functions. In *International Conference on Machine Learning*, pages 1388–1396. PMLR, June 2016. ISSN: 1938-7228.

[9] Yann Fraboni, Richard Vidal, and Marco Lorenzi. Free-rider Attacks on Model Aggregation in Federated Learning. *arXiv:2006.11901 [cs, stat]*, June 2020. arXiv: 2006.11901.

[10] Eduard Gorbunov, Dmitry Kovalev, Dmitry Makarenko, and Peter Richtárik. Linearly Converging Error Compensated SGD. *arXiv:2010.12292 [cs, math]*, October 2020. arXiv: 2010.12292.

[11] M. J. Grubb. Communication Energy efficiency and economic fallacies. *Energy Policy*, 18(8): 783–785, October 1990. ISSN 0301-4215. doi: 10.1016/0301-4215(90)90031-X.

[12] Kam Hamidieh. A data-driven statistical model for predicting the critical temperature of a superconductor. *Computational Materials Science*, 154:346–354, November 2018. ISSN 0927-0256. doi: 10.1016/j.commatsci.2018.07.052.

[13] Samuel Horváth and Peter Richtárik. A Better Alternative to Error Feedback for Communication-Efficient Distributed Learning. *arXiv:2006.11077 [cs, stat]*, June 2020. arXiv: 2006.11077.

[14] Samuel Horváth, Dmitry Kovalev, Konstantin Mishchenko, Sebastian Stich, and Peter Richtárik. Stochastic Distributed Learning with Gradient Quantization and Variance Reduction. *arXiv:1904.05115 [math]*, April 2019. arXiv: 1904.05115.

[15] Chi Jin, Lydia T. Liu, Rong Ge, and Michael I Jordan. On the local minima of the empirical risk. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/da4902cb0bc38210839714ebdcf0efc3-Paper.pdf.

[16] Peter Kairouz, H. Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Keith Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, Rafael G. L. D'Oliveira, Salim El Rouayheb, David Evans, Josh Gardner, Zachary Garrett, Adrià Gascón, Badih Ghazi, Phillip B. Gibbons, Marco Gruteser, Zaid Harchaoui, Chaoyang He, Lie He, Zhouyuan Huo, Ben Hutchinson, Justin Hsu, Martin Jaggi, Tara Javidi, Gauri Joshi, Mikhail Khodak, Jakub Konečný, Aleksandra Korolova, Farinaz Koushanfar, Sanmi Koyejo, Tancrède Lepoint, Yang Liu, Prateek Mittal, Mehryar Mohri, Richard Nock, Ayfer Özgür, Rasmus Pagh, Mariana Raykova, Hang Qi, Daniel Ramage, Ramesh Raskar, Dawn Song, Weikang Song, Sebastian U. Stich, Ziteng Sun, Ananda Theertha Suresh, Florian Tramèr, Praneeth Vepakomma, Jianyu Wang, Li Xiong, Zheng Xu, Qiang Yang, Felix X. Yu, Han Yu, and Sen Zhao. Advances and Open Problems in Federated Learning. *arXiv:1912.04977 [cs, stat]*, December 2019. arXiv: 1912.04977.

[17] Jakub Konečný, H. Brendan McMahan, Daniel Ramage, and Peter Richtárik. Federated Optimization: Distributed Machine Learning for On-Device Intelligence. *arXiv:1610.02527 [cs]*, October 2016. arXiv: 1610.02527.

[18] Alex Krizhevsky, Geoffrey Hinton, and others. Learning multiple layers of features from tiny images. 2009. Publisher: Citeseer.

[19] Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, November 1998. ISSN 1558-2256. doi: 10.1109/5.726791. Conference Name: Proceedings of the IEEE.

[20] Yann LeCun, Corinna Cortes, and CJ Burges. MNIST handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

[21] Zhize Li, Dmitry Kovalev, Xun Qian, and Peter Richtarik. Acceleration for Compressed Gradient Descent in Distributed and Federated Optimization. In *International Conference on Machine Learning*, pages 5895–5904. PMLR, November 2020. ISSN: 2640-3498.

[22] Xiaorui Liu, Yao Li, Jiliang Tang, and Ming Yan. A Double Residual Compression Algorithm for Efficient Distributed Learning. In *International Conference on Artificial Intelligence and Statistics*, pages 133–143, June 2020. ISSN: 1938-7228 Section: Machine Learning.

[23] Laurens van der Maaten and Geoffrey Hinton. Visualizing Data using t-SNE. *Journal of Machine Learning Research*, 9(Nov):2579–2605, 2008. ISSN ISSN 1533-7928.

[24] Horia Mania, Xinghao Pan, Dimitris Papailiopoulos, Benjamin Recht, Kannan Ramchandran, and Michael I. Jordan. Perturbed Iterate Analysis for Asynchronous Stochastic Optimization. *arXiv:1507.06970 [cs, math, stat]*, March 2016. arXiv: 1507.06970.

[25] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-Efficient Learning of Deep Networks from Decentralized Data. In *Artificial Intelligence and Statistics*, pages 1273–1282. PMLR, April 2017. ISSN: 2640-3498.

[26] Konstantin Mishchenko, Eduard Gorbunov, Martin Takáč, and Peter Richtárik. Distributed Learning with Compressed Gradient Differences. *arXiv:1901.09269 [cs, math, stat]*, June 2019. arXiv: 1901.09269.

[27] Constantin Philippenko and Aymeric Dieuleveut. Artemis: tight convergence guarantees for bidirectional compression in Federated Learning. *arXiv:2006.14591 [cs, stat]*, November 2020. arXiv: 2006.14591.

[28] Herbert Robbins and Sutton Monro. A Stochastic Approximation Method. *Annals of Mathematical Statistics*, 22(3):400–407, September 1951. ISSN 0003-4851, 2168-8990. doi: 10.1214/aoms/1177729586. Number: 3 Publisher: Institute of Mathematical Statistics.

[29] Felix Sattler, Simon Wiedemann, Klaus-Robert Müller, and Wojciech Samek. Robust and Communication-Efficient Federated Learning From Non-i.i.d. Data. *IEEE Transactions on Neural Networks and Learning Systems*, pages 1–14, 2019. ISSN 2162-2388. doi: 10.1109/TNNLS.2019.2944481. Conference Name: IEEE Transactions on Neural Networks and Learning Systems.

[30] Kevin Scaman, Francis Bach, Sebastien Bubeck, Laurent Massoulié, and Yin Tat Lee. Optimal Algorithms for Non-Smooth Distributed Optimization in Networks. *Advances in Neural Information Processing Systems*, 31:2740–2749, 2018.

[31] F. Seide, H. Fu, Jasha Droppo, G. Li, and D. Yu. 1-bit stochastic gradient descent and its application to data-parallel distributed training of speech DNNs. pages 1058–1062, January 2014.

[32] Frank Seide and Amit Agarwal. CNTK: Microsoft's Open-Source Deep-Learning Toolkit. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, page 2135, New York, NY, USA, August 2016. Association for Computing Machinery. ISBN 978-1-4503-4232-2. doi: 10.1145/2939672.2945397.

[33] Sebastian U. Stich and Sai Praneeth Karimireddy. The Error-Feedback Framework: Better Rates for SGD with Delayed Gradients and Compressed Communication. *arXiv:1909.05350 [cs, math, stat]*, September 2019. arXiv: 1909.05350.

[34] Sebastian U Stich, Jean-Baptiste Cordonnier, and Martin Jaggi. Sparsified SGD with Memory. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems 31*, pages 4447–4458. Curran Associates, Inc., 2018.

[35] Hanlin Tang, Xiangru Lian, Ming Yan, Ce Zhang, and Ji Liu. D^2: Decentralized Training over Decentralized Data. In *International Conference on Machine Learning*, pages 4848–4856. PMLR, July 2018. ISSN: 2640-3498.

[36] Hanlin Tang, Chen Yu, Xiangru Lian, Tong Zhang, and Ji Liu. DoubleSqueeze: Parallel Stochastic Gradient Descent with Double-pass Error-Compensated Compression. In *International Conference on Machine Learning*, pages 6155–6165. PMLR, May 2019. ISSN: 2640-3498.

[37] Paul Vanhaesebrouck, Aurélien Bellet, and Marc Tommasi. Decentralized Collaborative Learning of Personalized Models over Networks. In *Artificial Intelligence and Statistics*, pages 509–517. PMLR, April 2017. ISSN: 2640-3498.

[38] Jianqiao Wangni, Jialei Wang, Ji Liu, and Tong Zhang. Gradient Sparsification for Communication-Efficient Distributed Optimization. *Advances in Neural Information Processing Systems*, 31:1299–1309, 2018.

[39] Jiaxiang Wu, Weidong Huang, Junzhou Huang, and Tong Zhang. Error Compensated Quantized SGD and its Applications to Large-scale Distributed Optimization. In *International Conference on Machine Learning*, pages 5325–5333. PMLR, July 2018. ISSN: 2640-3498.

[40] An Xu, Zhouyuan Huo, and Heng Huang. Training Faster with Compressed Gradient. *arXiv:2008.05823 [cs, stat]*, August 2020. arXiv: 2008.05823.

[41] Shuai Zheng, Ziyue Huang, and James Kwok. Communication-Efficient Distributed Blockwise Momentum SGD with Error-Feedback. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 11450–11460. Curran Associates, Inc., 2019.