The Impact of Symbolic Representations on In-context Learning for Few-shot Reasoning

Abstract

Pre-trained language models (LMs) have shown remarkable reasoning performance using explanations for in-context learning. On the other hand, those reasoning tasks are usually presumed to be more approachable for symbolic programming. To make progress towards understanding in-context learning, we revisit neuro-symbolic approaches and design a model LMLP that learns from demonstrations containing logic rules and corresponding examples to iteratively reason over knowledge bases (KBs). Such a procedure makes explicit correspondence between LMs' outputs and predicates in the KBs to recover Prolog's backward chaining algorithm. Comprehensive experiments are included to systematically compare LMLP with their natural language counterparts like "chain-of-thought" (CoT) [48] in deductive and inductive reasoning settings, which demonstrates that LMLP enjoys much better efficiency and length generalization in various settings.

1 Introduction

Large LMs pre-trained on open-domain text corpora have achieved impressive advances in natural language generation and understanding tasks [18, 6]. By self-supervised imitation on human-generated texts, LMs contain rich factual knowledge [34, 5, 40] and linguistic structures [27], serving as a versatile inference regime for various downstream tasks [6, 25]. Among them, GPT-3 stands out by its few-shot generalization to unseen cases without further fine-tuning given in-context samples as demonstrations [6]. However, it is a common belief that LMs have not yet enjoyed a comparable success in tasks that require extensive planning and grounding [12, 2, 3] as well as symbolic reasoning [17, 14, 38].

Therefore, there are emerging interests to leverage language models to enable planning [23, 15], heuristic search [11] and symbolic inference [48, 54]. Among them, *chain of thought* prompting [48] show that taking (input, explanation, output) as in-context examples for LMs can lead to significant performance gain in reasoning tasks. However, like most fine-tuned LMs, they fail to generalize compositionally [56], which means that they can not reuse knowledge to solve harder problems with unseen combinations [22, 1, 19]. One notable case is that LMs would suffer from catastrophic performance degradation when tested on sequences longer than training ones (Figure 1) even if we scale up the parameters. *least-to-most prompting* [56] takes inspirations from neuro-symbolic programs and proposes to tackle the challenge by modularized prompting on the reduced problem. This divide-and-conquer strategy provides powerful tools to improve LMs' reasoning, but also poses an additional challenge:

Figure 1: Relational reasoning performance (accuracy) comparisons on the CLUTRR-LP dataset given training data with story length 2, 3, 4.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

what is the right representations for in-context samples? How does natural language explanation compared with symbolic provenance when acting as prompts?

Our goal is to answer these questions by comparing those two paradigms closely. To provide insights into in-context learning for reasoning tasks from a symbolic perspective, we study relational reasoning over natural language or KBs. This is because of its reliability[1] and controllability: given a query, it is easy to find a reasoning path in KBs as provenance without hand-crafting rationales [48] serving as part of the prompts. To few-shot learn from symbolic demonstrations and plan simultaneously in an explainable and scalable manner, we propose LMLP. LMLP uses logic rule templates and examples combined with pre-trained knowledge to do in-context learning iteratively for answering a relational query. Specifically, given a goal query as the in-context example that can be interpreted as a question-answering task, we search or retrieve a related task example with a corresponding logic rule (Figure 2). Then we concatenate the context and task description as the input of the Planning LM like GPT. At each step of generation, we use a

Figure 2: A deductive reasoning example for LMLP.

Translation LM such as Sentence BERT [39] to compare the similarity between the generated natural language sentences and encoded top-k similar `(subject, relation, object)` predicates in the KB. Such that each generated sentences is transformed into a predicate and the generated reasoning path is confined within the KB. Then the process is iterated until a predefined maximum iteration or the target of interest is reached (Figure 3).

We curate two datasets and design a series of experiments, intended to compare two recent in-context learning paradigms and explore both symbolic and naturalistic scenarios. Specifically, we adopt semi-synthetic datasets containing (natural, symbolic) data pairs which can be well-suited for investigating the role of symbolic representations for few-shot reasoning. Moreover, we create experimental settings that are infavorable for LMLP since i) we use GPT-2 and SentenceBERT as its backbones, which is known to be of much smaller scale compared to CoT which is usually based on GPT-3 or PaLM; ii) LMs are pre-trained over natual language sentences as opposed to KBs, which creates substantial gaps in semantics and representations, thus poses a grounding challenge where LMs are known to be ineffective [3]. Our results on relational reasoning show that CoT prompting still fails to solve compositionality challenge. On the other hand, LMLP takes symbolic inputs (predicates) to explicitly separate logic and control for improved problem-solving [21], can work much more reliably. It is a common belief that large pre-trained LMs learned via imitation are not grounded in contexts that required learning with rich experiences. However, experimental results show that eliciting LMs with logic rules and examples using in-context learning is sufficient for solving some challenging reasoning tasks over KBs. This is also complementary to evidence in in-context examples which are poorly understood and manifest many intricate design choices [55, 24, 28, 7].

2   Related Works

Neuro-symbolic Reasoning. Neuro-symbolic approaches are proposed for logic programming in statistical relational learning (SRL) but they usually have several key limitations. General ILP (Inductive Logic Programming) problem involves several steps that are NP-hard: (i) the rule search space grows exponentially in the length of the rule; (ii) assigning the logic variables to be shared by predicates grows exponentially in the number of arguments, which we refer as variable binding problem; (iii) the number of rule instantiations needed for formula evaluation grows exponentially in the size of data. A fundamental challenge in logic programming is to separate logic and control for improved efficient problem-solving [21]: with a determined control or theorem-proving strategy, the remaining process is to specify what is to be done via logic programming. Following the principle, traditional neuro-symbolic algorithms like backward chaining [42] and its continuous relaxation [41, 29, 30] are proposed, where unification between terms is replaced by the similarity between their embedding representations. We refer readers to Appendix A for more details and emphasize that those hybrid approaches are inefficient and ineffective. Instead, with LMs, one can model the

---

[1]KBs are mostly constructed with clear pipelines and strong supervisions.

distribution of the optimal decisions, and generate suitable candidate steps to proceed. Therefore, LMs offer a generic way of modeling the output space as a sequence.

In-context Learning concerns feeding input texts describing a task with some examples to the black-box model for learning the task [6]. Many works show that there are intricate design choices like prompt formats [16, 24, 55, 28], example choices and their ordering [55, 26], pre-training data distribution [51, 43, 7] and model architectures [7] to improve the LMs' powerful and versatile in-context learning ability. There are recent works focusing on bootstrapping LMs with natural language explanations, intermediate steps, or rationales for reasoning [57, 48, 32, 54]. There are works concerning grounding or reasoning using in-context learning [33]. However, they typically *finetune* the model using rationales or explanations [57, 54, 48] focus on natural language-based reasoning such as commonsense reasoning, arithmetic reasoning, open-domain question answering [54, 48], concept grounding [33] etc. Therefore, they are fundamentally different from our goal of probing the representations of prompts in-context learning.

Figure 3: Illustration of step-wise prompting of LMLP.

3 Methodology Overview

We consider the reasoning task with an SRL query as the question we are interested in based on some background knowledge as the context. The relational information in the query and context can be expressed either using natural language or a `(subject, relation, object)` predicate. There is a KB with facts $\mathcal{F}$ and rules $\mathcal{R}$ to support the above question answering. There are two ways of representing the problem - symbolic or natural language, which leads to the model designs below.

Datasets construction. As shown in Table 1, for LMLP, we need to curate new symbolic datasets from the original ones into (i) *A query subset* that contains triplets needed for proving. (ii) *A set of facts $\mathcal{F}$* that contains all the available facts/triplets, which composes a KB, and (iii) *A set of rules $\mathcal{R}$* that contains examples (A task and its proofs) extracted from the training set using backward chaining based neuro-symbolic reasoner [41]. See appendix C.2 for the details.

Table 1: Examples of data processing and curation.

Dataset	Natural Language Samples	Query	Facts $\mathcal{F}$	Logic rules $\mathcal{R}$
CLUTRR	Task: What's the relationship between Ashley and Nicholas? Story: Ashley told her daughter Lillian to wash up. Dinner was ready. Lillian called her brother, Nicholas up to see how he was doing after surgery.	(Ashley, son, Nicholas)	(Ashley, daughter, Lillian) (Lillian, brother, Nicholas) ...	Task: Ashley's son is Nicholas Step 1: Ashley's daughter is Lillian Step 2: Lillian's brother is Nicholas
Countries	Task: Is palau located in oceania?	(palau, locatedIn, oceania)	(palau, locatedIn, oceania) ...	Task: palau locatedIn oceania Step 1: palau locatedIn micronesia Step 2: micronesia locatedIn oceania

Language Models as Logic Programmers. In LMLP, given a query, we first select examples in logical rules $\mathcal{R}$ as the initial prompt. The most simple way is to random sample an example in $\mathcal{R}$ as the initial prompt, which cannot attain superior performance. We compare many other strategies in the experimental section. In Figure 3, we select one example as the initial prompt, which is concatenated with the query `Task: Joseph's sister is Katherine` and feed into the planning LM.

We then repeatedly generate contents by prompting an autoregressive planning LM $\mathcal{P}_\theta$ (Figure 3): For every hop in the deductive reasoning, we prompt $\mathcal{P}_\theta$ using the input. The generated output is

converted to particular triplets in the KB using the similarity of the embedding using a translation LM $\mathcal{T}_\phi$, implemented as a sentence-specific Masked LMs. By constraining the output space of $\mathcal{P}_\theta$ with an external KB in this way, LMLP is expected to produce more plausible provenance for explaining the reasoning process of final prediction. To improve the coherency, we enforce the chain rule transition constraints: the tail entity of the previous predicate should be the same as the head entity of the next predicate on each output step. Moreover, we concatenate the intermediate results into the prompt for every next step as shown in Figure 3. Essentially, LMLP leverages an abstract logic rule `Sister(A,C) ← Brother(A,B) ∧ Sister(B,C)` and its grounded example `Sister(George, Nancy) ← Brother(George, Dale) ∧ Sister(Dale, Nancy)` to derive the answer for the query `Sister(Joseph, Katherine)`. The model terminates when predefined maximum iterations or the target of interest is reached. When LMLP can arrive at the tail entity under a given amount of iterations, the query is treated as correct and can be proven. In other words, the prediction is true for the question if there is a reasoning provenance from the subject to the object by prompting LMs. The faithfulness of the explanation is governed by post-hoc human evaluations. The overall algorithm is described in Figure 4(a) and Appendix B Algorithm 1.

Using prompting, we bootstrap the reasoning process from LMs in a few-shot manner (Figure 3): If we retrieve a set of different rules as prompts, we can prove all the test samples in the Countries dataset by deriving a relational path that leads from the subject to the object (Table 5). This is in stark contrast to popular methods that need expensive human annotations and retraining [47, 15, 48, 54] or uncontrollable using only pre-trained knowledge [20].

Figure 4: (a) Schematic overview of LMLP. (b) Schematic overview of CoT.

Chain-of-Thought Prompting. CoT [48] proposes to solve complicated multi-step reasoning tasks such as math word problems by decomposing them into intermediate reasoning steps, which is also intuitive for our multi-hop SRL tasks.

Figure 4(b) shows an example of applying CoT to solve an SRL task from the CLUTRR dataset [44]: given an in-context sample in the form of <input, explanation, output>, LMs are expected to imitate the reasoning process of the given explanation to generalize to a new query. The explanation of each question is generated just the same as the rules set $\mathcal{R}$, which extracted from the training set based on neuro-symbolic reasoners. Specifically, the in-context exemplar adapts LMs to another sample containing multiple relations and a query for the relation between two entities *"What is the relation between Theodore and Frances?"*, CoT first generates a reasoning path from *Frances* to *Theodore*, namely *"France's grandson is Charles, . . . , Chris's brother is Theodore."*, and finally answer the query: *"The relation of Frances between Theodore is grandson"*. With such a prompt, LMs are expected to generate both the reasoning paths and the resulting queried relation.

4   Experiments

We now describe the experimental setups, empirically evaluate LMLP and compare it with existing methods. See Appendix C for full details of data preprocessing and performance evaluation.

Settings. We curate two datasets for evaluating the in-context learning capability of LMs for reasoning: CLUTRR-LP and Countries-LP, which are based on CLUTRR [44] and **Countries** [4] datasets respectively. CLUTRR [44] contains a group of KBs, where each node denotes a family member and edges are family relations. The target of **CLUTRR** dataset is to infer a two-family members' relationship that is not explicitly mentioned. The training set of CLUTRR consists of

graphs that the target relation can be inferred by traversing a limited number of edges while the relation in the test set needs more traversing steps for inference, which allows us to controllably study the compositionality of Machine Learning models. Another intriguing property of CLUTRR is that there are ground truth **one-to-one correspondances** between KBs and natural language stories, which exactly suits our needs. **Countries** [4] concerns link prediction, where countries, regions, and sub-regions are entities and relations containing *LocatedIn* and *NeighborOf*. Countries has three tasks, *R1,R2*, and *R3* based on three different data partitions strategies, which is detailed in [41].

Table 2: Numerical results and ablation on the length of test samples on CLUTRR-LP.

Planner	No Prompt	Only Rule	Random	Entity-based	CoT	LMLP-reverse	LMLP
0.0973	0.1514	0.1622	0.2919	0.2000	0.173	**0.3730**	0.3297
0.1810	0.1238	0.1524	0.2095	0.1429	0.1365	**0.3048**	0.2476
0.2258	0.2000	0.2129	0.2323	0.1742	0.1032	**0.3742**	0.2581
0.1037	0.2222	0.2000	0.3111	0.2370	0.1506	**0.3556**	**0.3556**
0.1048	0.1935	0.2177	0.1613	0.1855	0.0914	**0.3548**	0.2984
0.1230	0.2869	0.2131	0.3934	0.2705	0.123	**0.5246**	0.4754

Table 3: Qualitative comparison of CoT and LMLP over the same example on CLUTRR-LP.

CoT Prompting	LMLP
Question: Wilhelmina took her uncle Hugh to the grocery store. Francisco and his brother Wesley were wrestling. Wilhelmina, Francisco's daughter, was cheering on the competition. What is the relation between Hugh and Wesley? Answer: Wesley's brother is Francisco, Francisco's daughter is Wilhelmina, Wilhelmina's uncle is Hugh. The relation of Hugh between Wesley is brother.	Task: A's aunt is B
Step 1: A's sister is C
Step 2: C's mother is D
Step 3: D's sister is B
Task: Carrie's aunt is Lynn
Step 1: Carrie's sister is Natasha
Step 2: Natasha's mother is Cindy
Step 3: Cindy's sister is Lynn
Question: Constance went shoe shopping with her sister Ellen. Elsie had a daughter named Constance. Elsie had picked her daughter Margaret out the cutest new dress to wear on her birthday. Charles and his sister Kathleen have been best friends ever since childhood. Nadia and her father, James, went to the marina. James's daughter, Mabel, had purchased a boat, and they were eager to see it. Mabel bought her mother, Ellen, a puppy for her birthday. James hung his son Charles's finger paintings on the refrigerator. The paintings were right next to the paintings of Nadia, Charles's sister. Kathleen was n't old enough to make any paintings for her father, James. What is the relation between Margaret and Charles? Answer: charles' mother is nancy, nancy's daughter is elizabeth, elizabeth's husband is john, john's wife is mary, mary's brother is george, david's nephews are william, william's nephews are robert.✗	Task: Charles's aunt is Margaret
Step 1: Charles's sister is Nadia
Step 2: Nadia's aunt is Margaret ✓

Table 4: Ablation of LMLP on CLUTRR-LP.

Test Reasoning Length	K=1	K=3	K=5	K=10	Avg
5 Hops	0.3946	0.6865	0.7838	1.0000	0.7162
6 Hops	0.5048	0.7143	0.7619	1.0000	0.7452
7 Hops	0.4323	0.8065	0.8774	1.0000	0.7790
8 Hops	0.5037	0.8000	0.8593	1.0000	0.7907
9 Hops	0.3710	0.6452	0.7500	1.0000	0.6915
10 Hops	0.5328	0.8279	0.8525	0.9180	0.7828

5 Concluding Remarks

We probes in-context learning of LMs through a symbolic reasoning perspective, showing that LMs can be prompted with demonstrations to generate plausible provenance for reasoning tasks over KBs. The empirical superiority of LMLP provides fresh insights towards understanding in-context learning ans suggests a way to ground GPT that types language to non-linguistic symbols in the KB. Moreover, few-shot in-context learning with LMs provides a convenient way to incorporate background knowledge without re-training. As its implications, it supports interpretable multi-hop reasoning and easy integration of domain knowledge that are key desiderata of neuro-symbolic approaches. We hope our empirical study can inspire more explorations on the trade-off between natural language and computer languages for effective adaptation of LMs.

References

[1] Dzmitry Bahdanau, Shikhar Murty, Michael Noukhovitch, Thien Huu Nguyen, Harm de Vries, and Aaron Courville. Systematic generalization: What is required and can it be learned? In *ICLR*, 2018.

[2] Emily M Bender and Alexander Koller. Climbing towards nlu: On meaning, form, and understanding in the age of data. In *ACL*, 2020.

[3] Yonatan Bisk, Ari Holtzman, Jesse Thomason, Jacob Andreas, Yoshua Bengio, Joyce Chai, Mirella Lapata, Angeliki Lazaridou, Jonathan May, Aleksandr Nisnevich, et al. Experience grounds language. In *EMNLP*, 2020.

[4] Guillaume Bouchard, Sameer Singh, and Theo Trouillon. On approximate reasoning capabilities of low-rank vector spaces. In *AAAI*, 2015.

[5] Zied Bouraoui, Jose Camacho-Collados, and Steven Schockaert. Inducing relational knowledge from bert. In *AAAI*, 2020.

[6] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *NeurIPS*, 2020.

[7] Stephanie CY Chan, Adam Santoro, Andrew K Lampinen, Jane X Wang, Aaditya Singh, Pierre H Richemond, Jay McClelland, and Felix Hill. Data distributional properties drive emergent few-shot learning in transformers. *arXiv preprint arXiv:2205.05055*, 2022.

[8] Swarat Chaudhuri, Kevin Ellis, Oleksandr Polozov, Rishabh Singh, Armando Solar-Lezama, Yisong Yue, et al. *Neurosymbolic Programming*. Now Publishers, 2021.

[9] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

[10] Peter Clark, Oyvind Tafjord, and Kyle Richardson. Transformers as soft reasoners over language. In *IJCAI*, 2021.

[11] Adam Dahlgren, Johanna Björklund, and Frank Drewes. Perception, memory, and inference: The trinity of machine learning. In *Is Neuro-Symbolic SOTA still a myth for Natural Language Inference? The first workshop*, 2021.

[12] Arthur M Glenberg and Michael P Kaschak. Grounding language in action. *Psychonomic bulletin & review*, 2002.

[13] Nicolas Gontier, Koustuv Sinha, Siva Reddy, and Chris Pal. Measuring systematic generalization in neural proof generation with transformers. *NeurIPS*, 2020.

[14] Chadi Helwe, Chloé Clavel, and Fabian M. Suchanek. Reasoning with transformer-based models: Deep learning, but shallow reasoning. In *AKBC*, 2021.

[15] Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. *arXiv preprint arXiv:2201.07207*, 2022.

[16] Zhengbao Jiang, Frank F Xu, Jun Araki, and Graham Neubig. How can we know what language models know? *TACL*, 2020.

[17] Nora Kassner, Benno Krojer, and Hinrich Schütze. Are pretrained language models symbolic reasoners over knowledge? *arXiv preprint arXiv:2006.10413*, 2020.

[18] Jacob Devlin Ming-Wei Chang Kenton and Lee Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *NAACL-HLT*, 2019.

[19] Daniel Keysers, Nathanael Schärli, Nathan Scales, Hylke Buisman, Daniel Furrer, Sergii Kashubin, Nikola Momchev, Danila Sinopalnikov, Lukasz Stafiniak, Tibor Tihon, et al. Measuring compositional generalization: A comprehensive method on realistic data. In *ICLR*, 2019.

[20] Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners, 2022.

[21] Robert Kowalski. Algorithm= logic+ control. *Communications of the ACM*, 1979.

[22] Brenden Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *ICML*. PMLR, 2018.

[23] Shuang Li, Xavier Puig, Yilun Du, Clinton Wang, Ekin Akyurek, Antonio Torralba, Jacob Andreas, and Igor Mordatch. Pre-trained language models for interactive decision-making. *arXiv preprint arXiv:2202.01771*, 2022.

[24] Jiachang Liu, Dinghan Shen, Yizhe Zhang, Bill Dolan, Lawrence Carin, and Weizhu Chen. What makes good in-context examples for gpt-3? *arXiv preprint arXiv:2101.06804*, 2021.

[25] Kevin Lu, Aditya Grover, Pieter Abbeel, and Igor Mordatch. Pretrained transformers as universal computation engines. *arXiv preprint arXiv:2103.05247*, 2021.

[26] Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. *arXiv preprint arXiv:2104.08786*, 2021.

[27] Christopher D Manning, Kevin Clark, John Hewitt, Urvashi Khandelwal, and Omer Levy. Emergent linguistic structure in artificial neural networks trained by self-supervision. *PNAS*, 2020.

[28] Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. Rethinking the role of demonstrations: What makes in-context learning work? *arXiv preprint arXiv:2202.12837*, 2022.

[29] Pasquale Minervini, Matko Bosnjak, Tim Rocktäschel, and Sebastian Riedel. Towards neural theorem proving at scale. *arXiv preprint arXiv:1807.08204*, 2018.

[30] Pasquale Minervini, Sebastian Riedel, Pontus Stenetorp, Edward Grefenstette, and Tim Rocktäschel. Learning reasoning strategies in end-to-end differentiable proving. In *ICML*, 2020.

[31] Stephen Muggleton and Luc De Raedt. Inductive logic programming: Theory and methods. *The Journal of Logic Programming*, 1994.

[32] Maxwell Nye, Anders Johan Andreassen, Guy Gur-Ari, Henryk Michalewski, Jacob Austin, David Bieber, David Dohan, Aitor Lewkowycz, Maarten Bosma, David Luan, et al. Show your work: Scratchpads for intermediate computation with language models. *arXiv preprint arXiv:2112.00114*, 2021.

[33] Roma Patel and Ellie Pavlick. Mapping language models to grounded conceptual spaces. In *ICLR*, 2021.

[34] Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. Language models as knowledge bases? In *EMNLP-IJCNLP*, 2019.

[35] Stanislas Polu and Ilya Sutskever. Generative language modeling for automated theorem proving. *arXiv preprint arXiv:2009.03393*, 2020.

[36] Meng Qu, Junkun Chen, Louis-Pascal Xhonneux, Yoshua Bengio, and Jian Tang. Rnnlogic: Learning logic rules for reasoning on knowledge graphs. In *ICLR*, 2020.

[37] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 2019.

[38] Yasaman Razeghi, Robert L Logan IV, Matt Gardner, and Sameer Singh. Impact of pretraining term frequencies on few-shot reasoning. *arXiv preprint arXiv:2202.07206*, 2022.

[39] Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *EMNLP-IJCNLP*, 2019.

[40] Adam Roberts, Colin Raffel, and Noam Shazeer. How much knowledge can you pack into the parameters of a language model? In *EMNLP*, 2020.

[41] Tim Rocktäschel and Sebastian Riedel. End-to-end differentiable proving. *NeurIPS*, 2017.

[42] Stuart Russell and Peter Norvig. Artificial intelligence: a modern approach. 2002.

[43] Seongjin Shin, Sang-Woo Lee, Hwijeen Ahn, Sungdong Kim, HyoungSeok Kim, Boseop Kim, Kyunghyun Cho, Gichang Lee, Woomyoung Park, Jung-Woo Ha, et al. On the effect of pretraining corpora on in-context learning by a large-scale language model. *arXiv preprint arXiv:2204.13509*, 2022.

[44] Koustuv Sinha, Shagun Sodhani, Jin Dong, Joelle Pineau, and William L. Hamilton. Clutrr: A diagnostic benchmark for inductive reasoning from text. *EMNLP*, 2019.

[45] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In *ICLR*, 2018.

[46] Alon Talmor, Yanai Elazar, Yoav Goldberg, and Jonathan Berant. olmpics-on what language model pre-training captures. *TACL*, 2020.

[47] Maria Tsimpoukelli, Jacob Menick, Serkan Cabi, SM Eslami, Oriol Vinyals, and Felix Hill. Multimodal few-shot learning with frozen language models. *NeurIPS*, 2021.

[48] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. *arXiv preprint arXiv:2201.11903*, 2022.

[49] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

[50] Yuhuai Wu, Markus N Rabe, Wenda Li, Jimmy Ba, Roger B Grosse, and Christian Szegedy. Lime: Learning inductive bias for primitives of mathematical reasoning. In *ICML*, 2021.

[51] Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. An explanation of in-context learning as implicit bayesian inference. *ICLR*, 2021.

[52] Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. *NeurIPS*, 2017.

[53] Yuan Yang and Le Song. Learn to explain efficiently via neural logic inductive learning. In *ICLR*, 2020.

[54] Eric Zelikman, Yuhuai Wu, and Noah D Goodman. Star: Bootstrapping reasoning with reasoning. *arXiv preprint arXiv:2203.14465*, 2022.

[55] Zihao Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. Calibrate before use: Improving few-shot performance of language models. In *ICML*, 2021.

[56] Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Olivier Bousquet, Quoc Le, and Ed Chi. Least-to-most prompting enables complex reasoning in large language models. *arXiv preprint arXiv:2205.10625*, 2022.

[57] Wangchunshu Zhou, Jinyi Hu, Hanlin Zhang, Xiaodan Liang, Maosong Sun, Chenyan Xiong, and Jian Tang. Towards interpretable natural language understanding with explanations as latent variables. *NeurIPS*, 2020.

Appendix

A   Extended Related Work

Neuro-Symbolic Reasoning. ILP [31] and its neural version [53] are unable to reason about disjoint relations in confront of missing links when KBs are noisy like in FreeBase, which means ILP only synthesizes rules based on existing relations. Methods like Neural-LP [52] and RNNLogic [36] require enumeration of all possible rules given a max rule length T. Thus, the complexity of these models grows exponentially as max rule length increases, which is an significant disadvantage for systematicity problems. For deductive reasoning, NTP [41] and its improved versions [29, 30] require hand-crafted templates to imitate backward chaining for deductive reasoning. This belies the considerable user burden of authoring the templates which then fundamentally biases the tool toward a specific subset of programs that the author has in mind. Moreover, the performance and efficiency of NTP is far from satisfactory: the performance usually lags far behind its neural counterparts like knowledge graph embedding methods [45]; during both training and inference, NTPs need to compute all possible proof trees needed for proving a query, relying on the continuous unification of the query with all the rules and facts in the KB. However, the search space of existing works is exponentially large, which makes them hard to scale up in general [29, 8].

LMs for Theorem Proving. Most works focus on proving formal mathematical theorems: GPT-f [35] shows promising results by generative language modeling over mathematical formulas. Systematicity of LMs when training on proofs is evaluated in [13] but shows negative results in generalizing to unseen proof steps in extrapolation and complex language. Three synthetic tasks inspired by three reasoning primitives of deduction, induction, and abduction are demonstrated in [50]. The above works provide insights into understanding LMs' reasoning capabilities. Though they share similar problem structures like compositionality with ours, they fundamentally require large-scale pre-training and fine-tuning due to the mismatch between Wikipedia pre-training corpora and mathematical formulas. Such a re-training requirement not only results in computational inefficiency but lacking in compositional generalization to longer proof steps unseen during training [13].

Symbolic Reasoning with LMs. Recent works showcase both some positive [10] and negative results [17, 14, 46] in adapting LMs for symbolic or logical reasoning. Though there are some encouraging progress [10, 48, 9, 54], they require a significant amount of computation for re-training and human annotations about reasoning paths or so-called chain of thoughts [48]. Moreover, their entangled nature with natural language make them hard to make robust inference over symbolic factual knowledge. However, our goal is fundamentally different from theirs in investigating the few-shot reasoning in over KBs using in-context learning.

B   Algorithm Description

Algorithm 1 describes the procedure or LMLP. It can also be illustrated in Figure 4(a).

C   Additional Experimental Setups and Results

Implementation details. For LMLP, we implement the planning LM $\mathcal{P}_\theta$ as GPT-2 [37], the translation LM $\mathcal{T}_\phi$ as Sentence BERT (Sent-BERT) [39] based on Hugging Face Transformers [49]. The default model for Translation LM is Sentence-RoBERTa-Large and for Planning LM is GPT2-Large [37] pretrained on large corpora. For CoT, we follow the original paper [48] to sample in-context samples and use GPT-3 (text-davinci-002) which is accessed using OpenAI API for implementation. We conduct all the experiments on a machine with four Nvidia TITAN XP (10GB) GPU cards.

Since prompt formats lead to significant performance variations [24], we propose to explore two simple design choices for LMLP and find that they can further boost the reasoning capacity. (i) Multiple examples for prompting. Denote N the number of examples we used in one proof task. Table 9 shows two examples with $N = 1$ and $N = 2$ are supplied respectively. The intuition is that, getting more examples in the prompt can make LMs better recognize the proof task and thus produce more reliable reasoning paths. See the experimental section for empirical verification. (ii) Prompts Ensembling. Table 8 shows the results of different prompts for the same task. We can see

---

Algorithm 1 Generate proof path from Pre-Trained Language Models.

Require: Planning LM $\mathcal{P}_\theta$, Translation LM $\mathcal{T}_\phi$, Query set $\mathcal{Q}$ that contains all query triplets, $\mathcal{F}$ that contains all available facts, $\mathcal{R}$ that contains all the available rules or proof examples.

   for $(s, r, o) \in \mathcal{Q}$ **do** // *s, r, o denote subject entity, relation and object entity respectively.*

      Find $e \in \mathcal{F}$, whose task relation is r. Convert e to the prompt e'.

      while Max step is not reached **do**

         Sample 10 sentences $\{x_i\}_{i=1}^{10}$ from $\mathcal{P}_\theta$ with current prompt.

         Set $\mathcal{F}' \in \mathcal{F}$ whose first entity is s.

         if $|\mathcal{F}'| == 0$ **then**

            Break   // *No available facts in the $\mathcal{F}$ start with entity s.*

         for $x \in \{x_i\}_{i=1}^{10}$ **do**

            $score_i = \max cosine(\mathcal{T}_\phi(x, r)); \forall r \in \mathcal{F}'$// *Calculate cosine similarities of s to facts in $\mathcal{F}'$.*

            $idx = \arg\max cosine(\mathcal{T}_\phi(x, r)); \forall r \in \mathcal{F}'$// *Select $r \in \mathcal{F}'$ with the highest similarity to x.*

            $x' = \mathcal{F}'[idx]$

         Choose the highest score rule $x' = (s, r', o')$ as the next proof step and append it to the prompt.

         if $o' == o$ **then**

            Break   // *The object entity converges to the target entity o.*

---

the influence of prompts on the generated proof path. The first few proof steps are largely similar to the provided example. If the provided example supplies a wrong direction, the proof is likely to be wrong. To study and exploit the benefit brought by different prompts, during experiments, we propose to use K prompts alternatively for one task, where one task is marked to be successfully proved if any of these K prompts gets the right result. Namely, a larger K means that we have a higher probability of picking a good prompt. The default hyper-parameters N, K are set to one.

Evaluation metrics used in this work is the **proven accuracy or success rate**. For example, for the target "Task: palau locatedIn oceania", we begin with entity "palau" and select facts from the $\mathcal{F}$. If the chosen triplet ends with entity "oceania", the proven path is correct, e.g., "micronesia locatedIn oceania" in Table 1. For LMLP, if there is no chosen triplet ends with entity "oceania", the prediction is incorrect. For CoT, we can easily compare the final answer with the ground truth.

For every query set, we calculate the average proven success rate (Number of correct proven paths/number of test samples). For the CLUTRR dataset, there are a large number of noisy triplets. For example, the target in Table 1 is "Ashley's son is Nicholas" while "Ashley's husband is Nicholas" is in $\mathcal{F}$. Once the latter rule is chosen as one proof step, the proving process will terminate because "Ashley's husband is Nicholas" ends with the entity "Nicholas", however, the proof path is wrong and cannot induce the relation "son" between "Ashley" and "Nicholas". To evaluate the correctness of generated proof path, **human evaluations** are conducted. For each proof path, we ask annotators to answer "Yes" or "No" to whether the target relation can be induced from the proof path.

C.1 Comparisons of LMLP and CoT

The goal of this part is to systematically compare LMLP with CoT both quantitatively and qualitatively on SRL tasks to better understand the reasoning of LMs using in-context learning.

In Figure 1, we compare LMLP to CoT and the reported performances are all human evaluation results. Qualitatively, CoT can get positive results on some query examples, for example, in Table 11, we showcase two examples where CoT can generate a correct proof path and predict the target relation at the same time. However, compared to LMLP, CoT attains inferior results on all query sets with test reasoning length $5, 6, 7, 8, 9, 10$ even using GPT-3 for text generation. Besides, as the reasoning length increases, the performance of CoT shows a clear downward trend. Table 11 shows two negative examples, where the story contains sophisticated relations and the model cannot get the right reasoning path or just generate a wrong relation. In contrast, LMLP can consistently achieves a high proven success rate (Table 2) and human evaluation score (Table 6 in Appendix), which again verifies the systematic generalization capability of LMLP. Table 3 shows examples with the same task but processed by the two methods respectively, where CoT cannot get deduce a right relation

path from *Margaret* to *Charles* but LMLP can extract a simple yet right relation path. The reason why LMLP is better than CoT can be that, although CoT decomposes complex multi-hop relation reasoning tasks into a multi-step reasoning process and then predict the final results, the proof path is all generated by LMs at once. The decomposition of LMLP to multi-hop reasoning tasks is more thorough, where the generation of a proof path is divided into multi-steps and each step will be projected into the KB, which is a much stronger inductive bias. Therefore, the decomposed tasks in each step are easier to solve and the knowledge in the KB can be well exploited.

C.2 Data Generation.

CLUTRR-LP. CLUTRR has 9 subsets with difference story length, named $l_2, l_3, \ldots, l_{10}$. Following [30], we convert l_2, l_3, l_4 to the $\mathcal{R}$ and use $l_5, \ldots, l_{10}$ to the **query sets**. As illustrated in Table. 1, data samples in CLUTRR consist of a story and a target, where the target contains two entities and the relation that is needed to be inferred, the story contains available triplets. Each sample in the l_2, l_3, l_4 will be converted to the format "Task: ..., Step i: ..." and added to the $\mathcal{R}$. Note that all examples in the $\mathcal{R}$ have a story length of less than five, which enables us to test the systematic generalization ability of LMLP. For CLUTRR, the story triplets in the $\mathcal{R}$ are not useful for test target proving, because they are all from different relation graphs. For example, story triplets in the l_2, l_3, l_4 contain "(William's brother is Steve)" while one test story on l_5 contains "(William's uncle is Steve)". During the evaluation, if the model chooses "(William's brother is Steve)", the proof path will be wrong. However, the similarity of these two triplets is high, the model is then easy to make errors and these noisy facts increase proof difficulties. We hence evaluate our methods in two settings considering the number of noisy facts. The simplest setting (**Test Facts Setting**) is that, when queries are from $l_i, i \in [5, \ldots, 10]$, the $\mathcal{F}$ only contains facts in l_i. In this case, the $\mathcal{F}_{5 \sim 10}$ have $251, 222, 275, 279, 285, 304$ facts respectively. The most difficult setting is termed **All Facts Setting**. We first extract facts in the $\mathcal{F}$ with length l_2, l_3, l_4 and get totally $5, 210$ facts. When queries are from $l_i, i \in [5, \ldots, 10]$, the $\mathcal{F}$ contains triplets in l_i, l_2, l_3, l_4, where the additional $5, 210$ facts are not useful for the proof path and are noisy facts. The All Facts Setting is set as our default setting and experimental results of the Test Facts Setting are mainly in the Appendix. For CoT, the $\mathcal{F}$ is needless and the construction of prompt examples is slightly different from the procedure above. Specifically, as shown in Figure 4(b), for each target in the training samples, we need to preserve the story and extract a proof path for the target.

Countries-LP. Training samples in Countries are triplets that describe the *neighbor of* relation or *located in* relation of two regions/subregions/countries and can thus be directly used as $\mathcal{F}$. Because the three tasks (*S1, S2, S3*) [30] have different training sets and thus have different $\mathcal{F}$. Test samples in Countries are also triplets with specific entities and relations, hence the **query set** is just the test set of the original Countries dataset. One main difficulty in applying the proposed method to Countries is the lack of off-the-shelf proof paths ($\mathcal{R}$). The CTP [30] model is trained and used for proving each triplet in the training set. CTP returns the scores of the possible proof path and the proof with the maximum score is iteratively searched as added into the $\mathcal{R}$. After that, $924, 906, 705$ available examples are found for *S1, S2, S3* tasks respectively.

C.3 Additional results.

C.4 Analysis of LMLP

Given the above observations that LMLP outperforms CoT by a large margin, we systematically analyze LMLP with extensive experiments below.

Ablation Studies on prompting strategies. As illustrated in Table 2, **No Prompt** means that we only feed the target directly and generate each step, prompts in the **Only Rule** baseline is one proof example with entities replaced by some symbols. We also compare LMLP to Language Planner [15], which first finds the most similar target in the $\mathcal{R}$ and uses such an example as the prompt. **LMLP-reverse** swaps the position of the abstract logic rule and its grounded example in the prompt of LMLP. For example, in Figure 3, the in-context prompt of LMLP-reverse will place `Sister(George, Nancy) ← Brother(George, Dale) ∧ Sister(Dale, Nancy)` before its abstract logic rule `Sister(A,C) ← Brother(A,B) ∧ Sister(B,C)`. Examples for all baselines are shown in Appendix Table 9.

(a) Results on Test Facts.   (b) Results on Test Facts.

Figure 5: Ablation about the scaling of Planning LMs (a) and Translation LMs (b) for LMLP on the Test Facts Setting of the CLUTRR-LP dataset..

Table 2 shows that directly applying Language Planner for relational reasoning does not work and using only facts or no prompt attain inferior performance. The possible reason for the inferior performance of Planner can be that it finds the example from $\mathcal{R}$ with the most similar task as the prompt, which usually retrieves rules with the same entities of the goal task. However, for reasoning tasks over KBs, relation contains much more information of the task than the entity. As shown in Table 9, for the task "Patricia's uncle is Donald", Planner finds the example with task "David's nephew is Don", whose following proofs do not make sense for the relation "uncle". LMLP in contrast finds an example whose task has the same relation as the goal predicate, which is more informative.

Table 5: Results of LMLP on Countries-LP. *S1, S2, S3* [30] are three different tasks with different $\mathcal{F}$ (See experimental setting for the details).

	K=1	K=3	K=5	K=10	A Long Example
S1	0.7083	0.9583	1.0000	1.0000	Task: A locatedIn C
Step 1: A neighborOf B
Step 2: B locatedIn C
S2	0.5000	0.8750	0.9583	1.0000	Task: uruguay locatedIn south_america
Step 1: uruguay neighborOf argentina
Step 2: argentina locatedIn south_america
S3	0.7500	0.9167	0.9167	1.0000	Task: sudan locatedIn africa
Step 1: sudan neighborOf central african republic
Step 2: central african republic neighborOf chad
Step 3: chad neighborOf south sudan
Step 4: south sudan neighborOf dr congo
Step 5: dr congo neighborOf republic of the congo
Step 6: republic of the congo locatedIn middle africa
Step 7: middle africa locatedIn africa

Effects of K. We show evaluation results on CLUTRR-LP in Table 4 and the proposed method can generate realistic and correct proof paths. A large K can further boost the performance, which also verifies the importance of prompts ensembling: Table 5 in the Appendix shows the performance on Countries-LP where almost all the query samples can be proved correctly with a large K. One interesting phenomenon is that LMLP can generate a much longer proof path even though the proof path length in the rule set $\mathcal{R}$ is less than 3. This manifests a potential improvement with respect to the significant weakness in systematic generalization of fine-tuning or re-training of LMs [44]. The $\mathcal{R}$ of CLUTRR-LP contains only examples whose proof paths are less than five. However, during testing, our model can produce proof paths much longer than five steps and perform well on all query sets. **Effects of N.** Recall that N denotes the amount of in-context examples used in one proof task.

Table 7 shows an example when $N = 2$. Figure 6(a) gives ablation results, where a larger N can bring consistent performance gains. However, longer prompts require larger GPU memory and there is a trade-off between memory and performance.

Robustness to noisy facts. As elaborated in Appendix C.2, we have 5210 noisy facts in total. Figure 6(b) shows the results when we vary the number of noisy facts, where the noisy rate is 0.5 means that we add $5210 * 0.5$ facts to the $\mathcal{F}$ during evaluation. Even though when all the 5,210 noisy facts are added to the $\mathcal{F}$ (251, 222, 275, 279, 285, 304 facts for the six sets of facts $\mathcal{F}_{5\sim10}$), namely more than 95% facts are noisy, the performance is still favorable.

Effects of model size. Figure 6 (a) show the effects of **Model size of Planning LM.** Larger GPT models always attain better performance especially when there is a large number of noisy facts. Besides, compared to results on the Test Facts Setting (Figure 5 (a) in Appendix), Figure 6 (a) verifies that GPT2-Large is always more robust to noisy facts than GPT2 and GPT2-medium. Considering the effects of **Model size of Translation LM**, we compare four models in Figure 6(b), e.g., Sentence BERT (base), Sentence BERT (large), Sentence RoBERTa (base), and Sentence RoBERTa (large), which have 110M, 340M, 125M, 325M parameters respectively. No significant differences are observed in the All Facts setting across different variants of BERT and RoBERTa models. See Appendix C.3 for more comparison and discussion.

Figure 6: (a) Effect of the number of templates for LMLP on CLUTRR-LP. (b) The effects of noisy facts for LMLP on CLUTRR-LP. Ablation on the scaling of (c) Planning LMs and (d) Translation LMs for LMLP on CLUTRR-LP.

C.5 Analysis of Demonstrations of In-context Learning

Besides results in Table 3, we conduct additional qualitative analysis of demonstrations of in-context learning.

Failure cases analysis of baselines. Since the generated sentences are closely related to the prompt, Table 10 in Appendix shows that if we randomly choose prompts, the generated proof path has relations similar to the prompt but is wrong for the given task. For entity-based prompts, since the task has the same start entity as the in-context exemplar, hence the generated step 1 in this setting are very similar, leading to many wrong proof paths. Language Planner, without chain rule constraint, the generated triplets are chaos, e.g., in Example 1, the generated proof does even not contain the subject "Jon" and thus exactly wrong. Although the proposed LMLP attains a high success rate, there are also some failure cases. As shown in Appendix Table 8, an appropriate prompt needs to be chosen for the right proof paths.

Human evaluation results are shown in Appendix Table 6. When the $\mathcal{F}$ is small and without many noisy facts, almost all ablations attain high accuracy besides the language planner. Namely, the language planner either fails to prove the target task or the proof path is wrong. As we increase the number of noisy facts, the proposed LMLP shows high robustness and attains higher accuracy than other ablations.

Effects of model size. Compared to Figure 6(a), where models are evaluated on the All Facts Setting, Figure 5 (a) shows again that Larger GPT models always attain better performance. Considering the effects of **Model size of Translation LM**, we compare four models, e.g., Sentence BERT (base), Sentence BERT (large), Sentence RoBERTa (base), and Sentence RoBERTa (large), which have

110M, 340M, 125M, 325M parameters respectively. In the Test Facts setting, Figure 5 (b) shows that RoBERTa models attains superior results compared to BERT models. We hypothesize that this is because RoBERTa models pre-trained with larger corpora and a greater amount of parameters produce more expressive sentence embeddings and thus benefit the translation process. However, when there is a large number of noisy facts, this advantage gradually disappears.

Takeaways. Similar to previous works [24, 28], we find that in-context learning performance varies greatly with choices of exemplars (Table 4). One of the key findings in [28] is that even without any labeled data, LMs can achieve k-shot performance by simply prompting with demonstrations containing unlabeled inputs. Our findings are generally in-line is in line with the importance of input-label formats highlighted in the work. However, we show in Table 7 and 9 that the correct mapping of rule-example pairs are important since given only rules with symbols like X, Y, Z rather than concrete entities like $China$ makes LMLP fail catastrophically. We leave explorations about zero-shot baselines of symbolic reasoning over KBs as future work.

Table 6: Human evaluation of the proposed technique. A 0.9 accuracy during human evaluation means that 90% of the model's successful proof paths in Table 2 are correct and others give incorrect reasoning paths even if they converge to the target entity. Hence the true proven success rate of LMLP in the query set with Test Reasoning Length 5 is $0.3946{\times}0.8356$.

Test Reasoning Length	Planner	No Prompt	Only Rule	Random	Entity-based	LMLP-reverse	LMLP
5	0.4615	0.7368	0.7143	0.7941	0.7872	**0.9200**	0.8356
6	0.6129	0.5417	0.5926	0.5366	0.5000	**0.6531**	0.4906
7	0.7292	0.6458	0.6471	0.5217	0.5625	**0.8406**	0.5970
8	0.4375	0.6977	0.6923	0.7368	0.7442	**0.7619**	0.7059
9	0.5417	0.7500	0.8182	0.7407	0.7419	**0.8462**	0.8043
10	0.5556	0.8750	0.7647	0.8421	0.8684	**0.9846**	0.8923

Table 7: Sensitivity analysis of prompt formats using LMLP in the Countries dataset [41].

Method	Prompt	Output
Facts w/o Provenance	Task: Kazakhstan locatedIn Asia	Step 1: Kazakhstan locatedIn CentralAsia
Step 2: CentralAsia locatedIn Asia
Facts w/ Provenance	Task: Kazakhstan locatedIn CentralAsia
Step 1: Kazakhstan neighborOf Uzbekistan
Step 2: Uzbekistan locatedIn CentralAsia
Task: Kazakhstan locatedIn Asia	Step 1: Kazakhstan neighborOf China
Step 2: China neighborOf India
Step 3: India locatedIn SouthernAsia
Step 4: SouthernAsia locatedIn Asia
LMLP (N=1)	Task: X is located in Z
Step 1: X is located in Y
Step 2: Y is located in M
Step 3: M is located in Z
Task: Kazakhstan locatedIn Asia	Step 1: Kazakhstan neighborOf kyrgyzstan
Step 2: Kyrgyzstan neighborOf Uzbekistan
Step 3: Uzbekistan neighborOf Afghanistan
Step 4: Afghanistan neighborOf china
Step 5: China neighborOf India
Step 6: India neighborOf Nepal
Step 7: Nepal locatedIn Asia
	Task: X locatedIn Y
Step 1: X neighborOf M
Step 2: M neighborOf N
Step 3: N locatedIn Y
Task: Kazakhstan locatedIn Asia	Step 1: Kazakhstan locatedIn CentralAsia
Step 2: CentralAsia locatedIn Asia
	Task: X locatedIn Y
Step 1: X neighborOf M
Step 2: M locatedIn N
Step 3: N locatedIn Y
Task: Kazakhstan locatedIn Asia	Step 1: Kazakhstan locatedIn CentralAsia
Step 2: CentralAsia locatedIn Asia
	Task: X locatedIn Y
Step 1: X neighborOf Z
Step 2: Z locatedIn Y
Task: Kazakhstan locatedIn Asia	Step 1: Kazakhstan neighborOf kyrgyzstan
Step 2: Kyrgyzstan neighborOf Uzbekistan
Step 3: Uzbekistan neighborOf Afghanistan
Step 4: Afghanistan neighborOf Tajikistan
Step 5: Tajikistan neighborOf China
Step 6: China neighborOf India
Step 7: India neighborOf Nepal
Step 8: Nepal locatedIn Asia

Table 8: Failure cases analysis - the results of different prompts for the same task.

Method	Prompt	Output
No Prompt	Task: Richard's father is Donald	Step 1: Richard's grandmother is Elizabeth
Step 2: Elizabeth's son is Donald
Random Prompt	Task: C's father is B
Step 1: C's brother is A
Step 2: A's father is B
Task: Janet's father is George
Step 1: Janet's brother is John
Step 2: John's father is George
Task: Pat's grandfather is Jose	Step 1: Pat's uncle is Samuel
Step 2: Samuel's father is Jose
Rule Only	Task: B's father is C
Step 1: B's mother is D
Step 2: D's son is A
Step 3: A's father is C
Task: Richard's father is Donald	Step 1: Richard's grandmother is Elizabeth
Step 2: Elizabeth's son is Donald
Entity-based Prompt	Task: C's brother is A
Step 1: C's brother is B
Step 2: B's brother is A
Task: Milton's brother is Glen
Step 1: Milton's brother is Michael
Step 2: Michael's brother is Glen
Task: Milton's mother is Antonia	Step 1: Milton's daughter is Margaretta
Step 2: Margaretta's grandmother is Antonia
Language Planner	Task: David's nephew is Don ✗
Step 1: David's mother is Frances
Step 2: Frances's daughter is Lynn
Step 3: Lynn's son is Don
Task: Patricia's uncle is Donald	Step 1: Richard's father is Donald
LMLP (N=1)	Task: B's father is C
Step 1: B's mother is D
Step 2: D's daughter is A
Step 3: A's father is C
Task: Bobby's father is Hugh
Step 1: Bobby's mother is David
Step 2: David's daughter is Marie
Step 3: Marie's father is Hugh
Task: Richard's father is Donald	Step 1: Richard's mother is Maria
Step 2: Maria's husband is Donald
LMLP (N=2)	Task: E's father is B
Step 1: E's daughter is A
Step 2: A's sister is D
Step 3: D's brother is C
Step 4: C's grandfather is B
Task: Louis's father is Harold
Step 1: Louis's daughter is Jennifer
Step 2: Jennifer's sister is Nettie
Step 3: Nettie's brother is Samuel
Step 4: Samuel's grandfather is Harold
Task: D's father is C
Step 1: D's husband is A
Step 2: A's son is B
Step 3: B's grandfather is C
Task: Lena's father is James
Step 1: Lena's husband is Wesley
Step 2: Wesley's son is Theodore
Step 3: Theodore's grandfather is James
Task: Richard's father is Donald	Step 1: Richard's grandmother is Elizabeth
Step 2: Elizabeth's son is Donald

Table 9: The comparison of different demonstrations on results.

Table 10: Failure cases analysis of different baselines. Examples for each method are all from the same setting.

Method	Example 1	Example 2
Random Prompt	Task: D's mother is B
Step 1: D's father is E
Step 2: E's daughter is C
Step 3: C's brother is A
Step 4: A's mother is B
Task: Allan's mother is Marie
Step 1: Allan's father is Robert
Step 2: Robert's daughter is Michelle
Step 3: Michelle's brother is Ronald
Step 4: Ronald's mother is Marie
Task: Jose's granddaughter is Margaretta
Step 1: Jose's father is William ✗
Step 2: William's niece is Margaretta	Task: A's grandson is B
Step 1: A's granddaughter is C
Step 2:C's brother is B
Task: Clarence's grandson is James
Step 1: Clarence's granddaughter is Charlotte
Step 2: Charlotte's brother is James
Task: Samuel's nephew is Charles
Step 1: Samuel's aunt is Marie ✗
Step 2: Marie's grandfather is Charles
Entity-based Prompt	Task: B's granddaughter is A
Step 1: B's daughter is D
Step 2: D's brother is C
Step 3: C's daughter is A
Task: James's granddaughter is Juanita
Step 1: James's daughter is David
Step 2: David's brother is Joshua
Step 3: Joshua's daughter is Juanita
Task: James's niece is Mary ✗
Step 1: James's daughter is Mary	Task: B's granddaughter is D
Step 1: B's grandson is C
Step 2: C's brother is A
Step 3: A's sister is D
Task: James's granddaughter is Andrea
Step 1: James's grandson is Thomas ✗
Step 2: Thomas's brother is Don
Step 3: Don's sister is Andrea
Task: James's nephew is Don
Step 1: James's grandson is Thomas
Step 2: Thomas's brother is Don
Language Planner	Task: James's father is Dale
Step 1: James's sister is Charlotte
Step 2:Charlotte's father is Dale
Task: Jon's grandfather is Daniel
Step 1: James's grandmother is Mary
Step 2: Dorothy's mother is Mary
Step 3: Mary's husband is Daniel ✗	Task: Lynn's nephew is Michael
Step 1: Lynn's brother is Hugh
Step 2:Hugh's son is Johnson
Step 3:Johnson's brother is Michael
Task: Bonnie's nephew is Michael
Step 1: Ross's brother is Michael ✗
LMLP (N=1)	Task: B's father is C
Step 1: B's son is D
Step 2: D's mother is A
Step 3: A's father is C
Task: Hugh's father is James
Step 1: Hugh's son is Bobby
Step 2: Bobby's mother is David
Step 3: David's father is James
Task: Irene's father is Milton
Step 1: Irene's grandfather is Jose
Step 2: Jose's mother is Mary ✗
Step 3: Mary's husband is Milton	Task: Task: D's nephew is A
Step 1: D's brother is B
Step 2: B's son is C
Step 3: C's brother is A
Task: Francisco's nephew is Clarence
Step 1: Francisco's brother is Joshua
Step 2: Joshua's son is Joseph
Step 3: Joseph's brother is Clarence
Task: Melanie's nephew is Charles
Step 1: Melanie's husband is William
Step 2: William's nephew is Kyle
Step 3: Kyle's father is Charles ✗

Table 11: Showcase of results and failure cases analysis of CoT.

Right

Question: Nettie's brother Paul took her to the fair when she was little. Paul also brought his brother Samuel. Shantel and husband Harold are trying to get custody of Shantel's granddaughter Nettie before she gets placed in foster care. What is the relation between Samuel and Harold?
Answer: Harold's wife is Shantel, Shantel's granddaughter is Nettie, Nettie's brother is Paul, Paul's brother is Samuel. The relation of Samuel between Harold is grandson.

Question: Chris wants to throw a surprise party for his brother Theodore. Chris's brother Charles helps pick the decorations. Frances combed her grandson Charles's hair. She wanted him to look good for his first day of school. What is the relation between Theodore and Frances?
Answer: Frances's grandson is Charles, Charles's brother is Chris, Chris's brother is Theodore. The relation of Theodore with Frances is grandson. ✔

Question: Kevin went to the park with his sister, Heidi, and his father, Wayne. The three of them had a wonderful time there. What is the relation between Wayne and Heidi?
Answer: Heidi's brother is Kevin, Kevin's father is Wayne. The relation of Wayne between Heidi is father.

Question: Harold was so excited to surprise his son, Louis, with the tickets to the playoffs. Shantel enjoyed a homemade dinner with her son Louis Tracy was making dinner for her son, Kevin. Shantel, Kevin's grandmother, stopped by, so Shantel made a bit more so they all had enough to eat. What is the relation between Harold and Tracy?
Answer: tracy's mother is shantel, tracy's father is harold. the relation of harold and tracy is father. ✔

Wrong

Question: Wilhelmina took her uncle Hugh to the grocery store. Francisco and his brother Wesley were wrestling. Wilhelmina, Francisco's daughter, was cheering on the competition. What is the relation between Hugh and Wesley?
Answer: Wesley's brother is Francisco, Francisco's daughter is Wilhelmina, Wilhelmina's uncle is Hugh. The relation of Hugh between Wesley is brother.

Question: Constance went shoe shopping with her sister Ellen. Elsie had a daughter named Constance. Elsie had picked her daughter Margaret out the cutest new dress to wear on her birthday. Charles and his sister Kathleen have been best friends ever since childhood. Nadia and her father, James, went to the marina. James's daughter, Mabel, had purchased a boat, and they were eager to see it. Mabel bought her mother, Ellen, a puppy for her birthday. James hung his son Charles's finger paintings on the refrigerator. The paintings were right next to the paintings of Nadia, Charles's sister. Kathleen was n't old enough to make any paintings for her father, James. What is the relation between Margaret and Charles?
Answer: charles' mother is nancy, nancy's daughter is elizabeth, elizabeth's husband is john, john's wife is mary, mary's brother is george, george's nephews are david, david's nephews are william, william's nephews are robert. ✘

Question: Nicholas bought his brother Wayne a present. It was to congratulate him on becoming a father to his new son, Lorraine. What is the relation between Nicholas and Lorraine?
Answer: Lorraine's father is Wayne, Wayne's brother is Nicholas. The relation of Nicholas between Lorraine is uncle.

Question: William wanted to have a family cookout so he invited his brother James. James wanted to invite his other brother Cesar. Darryl's mother, Patrice, waited impatiently for him at the diner. Dan played basketball with his brother Eric. Darryl took his brother Eric to the baseball game with Nora's father Cesar. Cesar took his son Eric to go get nachos during the game. Patrice fixed her husband Cesar dinner and then they watched a movie they rented. Cesar rushed to the hospital to find out that his wife and already given birth to a boy and had named him Dan. Cesar was so excited to surprise his son, Eric, with the tickets to the playoffs. What is the relation between William and Nora?
Answer: nora has two brothers, one of them being william. william is the only one who knows about nora's pregnancy. he is also the only one who knew about nora's pregnancy. ✘