AriEL: volume coding for sentence generation comparisons

Abstract

Saving sequences of data to a point in a continuous space makes it difficult to retrieve them via random sampling. Mapping the input to a volume makes it easier, which is the strategy followed by Variational Autoencoders. However optimizing for prediction and for smoothness, forces them to trade-off between the two. We analyze the ability of standard deep learning techniques to generate sentences through latent space sampling. We compare to AriEL, an entropic coding method to construct volumes without the need for extra loss terms. We benchmark on a toy grammar, to automatically evaluate the language learned and generated, and find where it is stored in the latent space. Then, we benchmark on a dataset of human dialogues and using GPT-2 inside AriEL. Our results indicate that the random access to stored information can be improved, since AriEL is able to generate a wider variety of correct language by randomly sampling the latent space. This supports the hypothesis that encoding information into volumes, leads to improved retrieval of learned information with random sampling.

1 Introduction

It is standard for neural networks to map an input to a point in $\mathbb{R}^d$ (Hochreiter and Schmidhuber, 1997; Vaswani et al., 2017; LeCun et al., 1989). However, that makes it difficult to find a specific point when the real space is sampled randomly. That can limit the applicability of pre-trained models to their initial scope. The family of approaches that stems out of the Variational Autoencoders idea (Kingma and Welling, 2014; Bowman et al., 2016; Rezende and Mohamed, 2015; Chen et al., 2018) are trained to encourage such type of representations. By encoding an input into a probability distribution that is sampled before decoding, several neighbouring points in $\mathbb{R}^d$ can end up representing the same input. However, it requires two summands in the loss, a log-prior and a log-likelihood term (Kingma and Welling, 2014; Bowman et al., 2016), that fight for two different causes. In fact, a smooth and volumetric representation, encouraged by the log-prior, might come at the cost of worse reconstruction or classification, encouraged by the log-likelihood.

By giving partially up on smoothness, we propose a method to explicitly construct volumes, without a loss to implicitly encourage them. We propose AriEL, a method to map sentences to volumes in $\mathbb{R}^d$ for efficient retrieval with either random sampling, or a network that operates in its continuous space. It fuses arithmetic coding (AC) (Elias and Abramson, 1963) and k-d trees (KdT) (Bentley, 1975), and we name it after them *Arithmetic coding and k-d trEes for Language* (AriEL). For simplicity we choose to focus on dialogue language, even if AriEL is applicable for the coding of any variable length sequence of discrete symbols.

AriEL can be used as an objective benchmark to understand how other methods use their latent space. It attempts to fill completely the latent space with the language learned on the training set, using information theory notions. AriEL uses a language model to split the latent space in volumes, guided by the probability assigned to the next symbol in a sentence. Therefore, it can simplify as well the reuse of pretrained language models for new tasks and in larger architectures. In fact, it can provide an agent with a simpler interface with a language model, e.g. a GPT-2 (Radford et al., 2019; Wolf et al., 2020), where the agent could choose the optimal dimensionality of the interface. We prove how such a

volume representation eases the retrieval of stored learned patterns and how to use it to set references for other models.

Our contributions are therefore:

- AriEL, a volume coding technique based on arithmetic coding and k-d trees (Section 3.1), to improve the retrieval of learned patterns with random sampling;
- the use of a context-free grammar and a random bias (Section 3.3), to automatically evaluate the generated language and find where it is stored in the latent space;
- the notion that explicit volume coding (Section 4) can be a useful technique in tasks that involve the generation of sequences of discrete symbols, such as sentences;
- the observation that conventional learned codes like AE, VAE or Transformer, do not use the latent space effectively (Section 4), in the AriEL entropic coding sense.

2 Related Work

Volume codes: We define a *volume code* as a pair of functions, an encoder and a decoder functions, where the encoder maps an input x into a set that contains compact and connected sets of $\mathbb{R}^d$ (Munkres, 2018), and the decoder maps every point within that set back to x. It is a form of distributed representations (Hinton et al., 1984) since that only implies that the input x will be represented as an $\mathbb{R}^d$ point. We define *point codes* as the distributed representations that are not volume codes. Volume codes differ from coarse coding (Hinton et al., 1984) since in this case the code is represented by a list of zeros and ones that identifies in which overlapping sets x falls into. We call the volume code *implicit*, when the volumes are encouraged through a term in the loss (Bengio et al., 2013; Ng and Jordan, 2002; Kingma and Welling, 2014; Jebara, 2012) and *explicit*, when the volumes are constructed through the architecture's operations, independently from any loss and optimizer choice.

Sentence generation through random sampling: Generative Adversarial Networks (GAN) (Goodfellow et al., 2014) map random samples to a learned generation through a 2-players game training procedure. Several advances have significantly improved their performance in text generation (Yu et al., 2017; Xu et al., 2018; Kusner and Hernández-Lobato, 2016). Random sampling the latent space is used as well by Variational Autoencoders (VAE) (Kingma and Welling, 2014), to smooth their representations. Training VAE for text has been refined in several works (Bowman et al., 2016; Severyn et al., 2017; Yang et al., 2017). Several works explore how VAE and GAN can be combined (Makhzani et al., 2015; Tolstikhin et al., 2017; Mescheder et al., 2017). AriEL can be used as a generator or a discriminator in a GAN, or as an encoder or a decoder in an autoencoder. However it differs from them in the explicit procedure to construct volumes in the latent space that correspond to different inputs. The intention is to fill the entire latent space with the learned patterns, to ease the retrieval by uniform random sampling.

Arithmetic coding and neural networks: AC is one of the most efficient lossless data compression techniques (Witten et al., 1987; Elias and Abramson, 1963). AC assigns a sequence to a segment in $[0, 1]$ whose length is proportional to its frequency in the dataset. AC is used for neural network compression (Wiedemann et al., 2019) and neural networks are used in AC as the model of the data distribution, to perform prediction based compression (Pasero and Montuori, 2003; Triantafyllidis and Strintzis, 2002; Jiang et al., 1993; Ma et al., 2019; Tatwawadi, 2018). We turn AC into a compression algorithm in $\mathbb{R}^d$, to combine its properties with the properties of high-dimensional spaces, neural networks domain.

K-d trees and neural networks: KdT (Bentley, 1975) is a data structure for storage that can handle different types of queries efficiently. It is typically used as a fast approximation to k-nearest neighbours in low dimensions (Friedman et al., 1977). It gives a binary label to the data with respect to its median. It moves through the k dimensions of the data and repeats the process. Neural networks are typically used in conjuction with KdT to reduce the dimensionality of the search space, for KdT to be able to perform queries efficiently (Woodbridge et al., 2018; Yin et al., 2017; Vasudevan et al., 2009). We use KdT to make sure that the multidimensional AC uses all the space available.

3 METHODOLOGY

3.1 ARIEL: VOLUME CODING OF LANGUAGE IN CONTINUOUS SPACES

Figure 1: **Arithmetic coding and AriEL.** In this example, the generating context-free grammar (CFG) is $S \rightarrow A|B|AA|AB|AC|BC|ABC|BCC$, and the bar plot on top indicates the frequency of those sentences in the dataset, as an extra bias to the language. Arithmetic Coding (middle) encodes any sequence of this CFG over a single dimension within $[0, 1]$, and the frequency of the sentence determines the length assigned on that segment. AriEL (bottom) is a multidimensional extension of AC (here in 2D), where the frequency information is preserved in the volumes. The Language Model provides the boundaries where the next symbols are to be found. For a 2D latent space, $d = 2$, the axis to split to find symbol s_i is $d_i = i \mod d$. $d_i = 0, 1$ represent the horizontal and vertical axis.

AriEL maps the sentence $(s_1, \cdots, s_n)$ to a d-dimensional volume of size $P((s_1, \cdots, s_n)) = \Pi_{i=1}^n P(s_i|(s_j)_{j<i})$. The sentence is encoded as the center of that volume for simplicity, and any point within it is decoded to the same sentence. AriEL loops through each axis of a d-dimensional hypercube, and constructs volume boundaries using probabilities provided by a language model (algorithm 1). The extension to a larger $[0, x]^d$ hypercube is straightforward, and could provide higher precision, but here we restrict ourselves to $[0, 1]^d$.

To adapt KdT to more splits than binary, we assign a segment on d_i to each possible next symbol s, proportional to its probability. Then we turn to the following axis and continue the process of splitting and turning (figure 1 and algorithm 1). We select the next axis in $\mathbb{R}^d$ to split to be $d_i = i \mod d$, where $i \in \{1, 2, \ldots, n\}$ and n is the length of the sequence. If n is larger than the dimension d, then the segment previously assigned in d_i is split again. We use a neural network to estimate the statistics of the data $P(s_i|(s_j)_{j<i})$, the Language Model (LM) of AriEL, $P_{LM}(s_i|(s_j)_{j<i})$. This will approximate the frequency information that makes AC entropically efficient since after a successful training, P_{LM} will converge to P. AriEL conserves then the arithmetic coding property of assigning larger volumes to frequent sentences. We prove AriEL is an *explicit volume code* in the Supplementary Material (SM) 8.

AriEL with a RNN-based language model has a computational complexity of $O(nD^2)$ for encoding and decoding (algorithm 1), where n is the length of the sequence and D is the dimensionality of the RNN hidden state. We use capital D for the length of the longest hidden layer among the recurrent layers in the encoder or in the decoder, while d refers to the latent space size. AriEL has a minimum number of sequential operations of $O(n)$ for both encoding and decoding, which is on par with conventional recurrent networks for seq2seq learning.

3.2 NEURAL NETWORKS: MODELS AND EXPERIMENTAL CONDITIONS

We compare AriEL to some classical approaches that map variable length discrete spaces to fixed length continuous spaces. These are the sequence to sequence recurrent autoencoders (AE) (Sutskever et al., 2014), their variational version (VAE) (Bowman et al., 2016) and

Algorithm 1 Algorithms for AriEL encoder and decoder B stands for bound, and B_{up} and B_{low} for the upper and lower bounds that define AriEL volumes, major differences between encoder and decoder are in blue and P_{LM} is AriEL's Language Model. Its cumulative distributions (c_{up}, c_{low}) define the limits of the volumes and its size (a). s and s' represent the vector of words in the vocabulary of choice, or equivalently their indices, and s_i the particular value taken at position i in the sentence. (Left) AriEL Encoding: from sentence to continuous space. Finally the volumes are represented by their central point $\mathbf{z}$ for simplicity. (Right) AriEL decoding: from continuous space to sentence. $\mathbf{z}$ is used to identify which volume has to be picked next. The $find$ operation is defined in SM10.

AriEL Encoding

Input: sentence: $S = (s_j)_{j=1}^n$
Output: $\mathbf{z}$ represents S in $[0,1]^d$

1: **function** AriEL_ENCODE(S)
2: $\quad d = $ latent space dimension
3: $\quad B_{low} = zeros(d)$
4: $\quad B_{up} = ones(d)$
5: $\quad n = length(S)$

6: $\quad$ **for** $i = 0, \cdots, n-1$ **do**
$\qquad\qquad \triangleright$ *choose dimension to split*
7: $\qquad d_i = i \mod d$
8: $\qquad P_{next}(s) = P_{LM}(s|(s_j)_{j<i})$
9: $\qquad c_{low}(s) = \sum_{s>s'} P_{next}(s')$
10: $\qquad c_{up}(s) = \sum_{s>s'-1} P_{next}(s')$
11: $\qquad a = B_{up}(d_i) - B_{low}(d_i)$
$\qquad\qquad \triangleright$ *update volume bounds*
12: $\qquad B_{up}(d_i) = B_{low}(d_i) + a \cdot c_{up}(s_i)$
13: $\qquad B_{low}(d_i) = B_{low}(d_i) + a \cdot c_{low}(s_i)$
14: $\quad$ **end for**
$\qquad \triangleright$ *represent the volume by its center*
15: $\quad \mathbf{z} = (B_{low} + B_{up})/2$
16: $\quad$ **return** $\mathbf{z}$
17: **end function**

AriEL Decoding

Input: $\mathbf{z}$ represents S in $[0,1]^d$
Output: sentence: $S = (s_j)_{j=1}^n$

1: **function** AriEL_DECODE($\mathbf{z}$)
2: $\quad d = dimension(\mathbf{z})$
3: $\quad B_{low} = zeros(d)$
4: $\quad B_{up} = ones(d)$

5: $\quad S = \langle START \rangle$
6: $\quad$ **for** $i = 0, \cdots, n_{max}-1$ **do**
$\qquad\qquad \triangleright$ *choose dimension to unsplit*
7: $\qquad d_i = i \mod d$
8: $\qquad P_{next}(s) = P_{LM}(s|S)$
9: $\qquad c_{low}(s) = \sum_{s>s'} P_{next}(s')$
10: $\qquad c_{up}(s) = \sum_{s>s'-1} P_{next}(s')$
11: $\qquad a = B_{up}(d_i) - B_{low}(d_i)$
$\qquad\qquad \triangleright$ *update volume bounds*
12: $\qquad Bs_{up}(s) = B_{up}(d_i) + a \cdot c_{up}(s)$
13: $\qquad Bs_{low}(s) = B_{low}(d_i) + a \cdot c_{low}(s)$
$\qquad \triangleright$ *any point in the volume is assigned the symbol s_i*
14: $\qquad s_i = find_s\Big(Bs_{low}(s) < \mathbf{z}(d_i) < Bs_{up}(s) \Big)$
15: $\qquad B_{up}(d_i) = Bs_{up}(s_i)$
16: $\qquad B_{low}(d_i) = Bs_{low}(s_i)$
17: $\qquad S = S.append(s_i)$
18: $\quad$ **end for**
19: $\quad$ **return** S
20: **end function**

Tranformer (Vaswani et al., 2017). We trained them for next word prediction of word s_i, when all the previous words are given as input, and they are trained over the biased train set, defined in section 3.3. All of them can be split into an encoder that maps the sentences at the input into $\mathbb{R}^d$, and a decoder that maps back from $\mathbb{R}^d$ into a sentence. More training details can be found in the SM7.

In this work, AriEL's language model neural network P_{LM} consists of a word embedding of size 64, a 140-unit LSTM, a feedforward layer and a softmax. At test time the argmax is not applied directly to the softmax, but the latent space representation is used as the deterministic pointer that chooses the position in the softmax probabilities, as shown in the definition of the $find$ function in SM10. However the language model is trained for next time step prediction through cross-entropy. For both AE and VAE, we stack two GRU layers (Cho et al., 2014) with 128 units at both, the encoder and the decoder. Other recurrent networks gave similar results (Hochreiter and Schmidhuber, 1997; Li et al., 2018). The last

encoder layer has either $d = 16$ units or $d = 512$ for all methods. The decoder outputs a softmax over the entire vocabulary.

Tranformer (Vaswani et al., 2017) is the state-of-the-art in many S2S problems (Dai et al., 2019; Radford et al., 2018). Since at the word level it is a fixed-length representation and it is variable-length at the sentence level, we padded all sentences to the maximum length in the dataset to be able to compare its latent space capacity to the other models. We take as its latent dimension the connection between the encoder and decoder, with d_{model} size, that will take a value of 16 or 512. We choose most parameters as in the original work: the number of attention heads $n_{head} = 8$, the key and value dimension $d_{key} = d_{value} = 64$, a dropout regularization of 0.1. We change the stack of identical decoders and encoders to $n_{layers} = 2$, and the dimension of the inner feed-forward network to $d_{ff} = 256$ to have a number of parameters similar to the other methods. On the GuessWhat?! dataset (De Vries et al., 2017) we tested $n_{layers} = 20$ to have an amount of parameters comparable for $d = 16$ to the other methods, but performed worse than $n_{layers} = 2$, so we report the smaller one.

3.3 DATASETS: TOY AND HUMAN SENTENCES

We perform our analysis on two datasets. A toy dataset of sentences generated from a context-free grammar (CFG) and a realistic dataset of sentences written by humans playing a cooperative game.

The toy dataset: we generate questions about objects with a CFG (Supplementary Material 1). To stress the learning methods we choose a CFG with a large vocabulary and numerous grammar rules, rather than more classic alternatives (e.g. REBER (Hochreiter and Schmidhuber, 1997)). All sentences are framed as questions about objects.

We distinguish between *unbiased* sentences, simply sampled from the CFG, and *biased* sentences, selected according to an additional structural constraint after being sampled from the CFG. To do so we generate an adjacency matrix of words that can occur together in the same sentence, and we use that as the filter to bias the sentences. Once a sentence is produced from the CFG, if all its words can be together in a sentence judged by the adjacency matrix, the sentence is considered as biased, and unbiased otherwise. For simplicity the adjacency matrix is a random matrix of zeros and ones, generated only once for all the experiments, making sure that some symbols such as *the*, *it* or *?*, can be found in both types of sentences. The intention is to emulate a CFG constrained by realistic scenes, where not all the grammatically correct sentences are semantically correct: e.g. 'Is it the wooden shower in the kitchen ?' could be grammatical, but semantically incorrect since it is unusual in a realistic scene. We use it to detect how each learning method extracts the grammar and the roles of each word, despite a bias that makes it harder.

The vocabulary consists of 840 words. The maximal and mean length of the sentences is of 19 and 9.9 symbols. We split the biased dataset into 1M train, 10k test and 512 validation sentences, with no overlap between them. We created a set of 10k unbiased test sentences with the same CFG, only with sentences that do not follow the adjacency matrix. We train on the biased sentences and we test if they grasped the grammar behind, with the unbiased.

The real dataset: we choose the GuessWhat?! dataset (De Vries et al., 2017), a dataset of questions asked by humans to solve a cooperative game. It has a vocabulary of 10,469 words. The maximal and mean length of the sentences are of 57 and 5.9 symbols.

3.4 EVALUATION METRICS

3.4.1 QUANTITATIVE EVALUATIONS ON THE TOY GRAMMAR, CFG

We measure the quality of generation, prediction and generalization. We study networks with a latent dimension of 16 units, to understand their compression limits, and for 512 units, often taken as the default size (Kingma and Welling, 2014; Vaswani et al., 2017).

Generation/Decoding Quality is evaluated with sentences produced by the decoder when the latent space of each model is sampled randomly. The sampling is done uniformly in the continuous latent space, within the maximal hyper-cube defined by the encoded test

sentences. We sample 10k sentences and evaluate: *i) vocabulary coverage (VC)* as the ratio of sampled words, over the size of the complete vocabulary; *ii) uniqueness (U)* as a ratio of unique sampled sentences; and *iii) validity (V)* as a ratio of valid sampled sentences, defined as the unique and grammatically correct sentences.

Prediction Quality is evaluated by encoding and decoding the 10k *biased* test sentences as follows: *i) prediction accuracy biased (PAB)* as a ratio of correctly reconstructed sentences (i.e. all words must match); *ii) grammar accuracy (GA)* as a ratio of grammatically correct reconstructions (i.e. can be parsed by the CFG, even if the reconstruction is not accurate). and *iii) bias accuracy (BA)* as the ratio of inaccurate reconstructions that are still grammatical and keep the bias of the training set.

Generalization Quality is evaluated using the 10k *unbiased* test sentences while the embeddings were trained on the *biased* training set. The *prediction accuracy unbiased (PAU)*, as *PAB*, is the ratio of correctly reconstructed unbiased sentences. It measures how well the latent space generalizes to grammatically correct sentences outside the training bias.

3.4.2 Quantitative evaluations on the real dataset, GuessWhat?!

Humans use spontaneously ungrammatical constructions. We therefore quantify the quality of the language learned with two measures: *memorization* and *subjective interpretability*. *Memorization* is the percentage of sentences that are unique and can be found in the training data, indicating how easy it is to retrieve the learned information. To measure *subjective interpretability*, we completed a survey of 5 participants that were asked to evaluate the interpretability of the generated sentences. They were assigned 5 sentences for each method and d, and each sentence was from a different training seed. Samples shown to the surveyees can be seen in SM12.

3.4.3 Interpolations within AriEL

AriEL organization of language in volumes changes with d, using the same Language Model. In figure 2 we show how many valid sentences can be found on a straight line between two random points in $[0, 1]^d$, AriEL's latent space. Valid refers to unique and grammatically correct, as in the toy dataset case. Since the average is taken over the segment and over the random pairs of points, we call this metric *interpolation diversity*. For each d the average is taken over 15 different random sentence pairs, and over 100 interpolation steps on the line that connects them. The Language Model tested is the one trained on the toy grammar.

3.4.4 Qualitative evaluations

We show (1) samples of reconstruction via next word prediction of unbiased sentences, to understand the generalization capabilities of different models ($d = 16$, table 3 and S2), (2) generated sentences by uniformly sampling the latent space, after training on the toy dataset, to understand the generation capabilities ($d = 16$, table 4 and S3) (3) samples generated by AriEL with a pretrained GPT2 as its language model, for small latent spaces ($d = 1, 5$, table 5 and S4) and long sentences (100 symbols), to see if the folding process and the floating point precision represent a limitation for AriEL. To avoid cherry picking, we display the first samples produced.

4 Results

4.1 Quantitative Evaluations

AriEL improves over the rest for all the 7 measures on the toy data (table 1 and figure S2), outperforming them by a large margin for validity, i.e. unique and grammatical sentences generated, the most important of the metrics. Transformer performs remarkably well at not overfitting and it is able to reconstruct biased and unbiased sentences better than the other non-AriEL methods, even under-parameterized ($d = 16$). However, it performs very poorly at generating diverse valid sentences by random sampling. VAE 16 despite the poor generalization to the biased and the unbiased test set, results in the best non-AriEL generator,

		Generation			Prediction			Generalization
	param	vocabulary coverage	validity	uniqueness	bias accuracy	grammar accuracy	prediction accuracy biased	prediction accuracy unbiased
d = 16								
AriEL	237K	**70.4** ± 0.2%	**97.6** ± 0.2%	**99.7** ± 0.1%	**100.0** ± 0.0%	**100.0** ± 0.0%	**100.0** ± 0.0%	**53.1** ± 0.4%
Transformer	258K	**70.1** ± 0.8%	4.7 ± 2.7%	99.1 ± 0.5%	99.98 ± 0.01%	99.95 ± 0.02%	99.92 ± 0.02%	49.0 ± 0.1%
AE	258K	6.89 ± 0.7%	11.5 ± 4.2%	13.9 ± 5.1%	89.5 ± 2.3%	98.0 ± 1.7%	0.0 ± 0.1%	0.0 ± 0.1%
VAE	258K	11.5 ± 2.6%	16.0 ± 9.2%	24.3 ± 14.8%	85.4 ± 5.2%	85.1 ± 8.8%	0.0 ± 0.1%	0.0 ± 0.1%
d = 512								
AriEL	237K	**70.2** ± 0.3%	**97.9** ± 0.2%	**99.8** ± 0.1%	**100.0** ± 0.0%	**100.0** ± 0.0%	**100.0** ± 0.0%	**53.2** ± 0.3%
Transformer	9M	67.3 ± 0.9%	17.2 ± 6.3%	87.2 ± 7.5%	99.99 ± 0.01%	99.91 ± 0.03%	99.86 ± 0.05%	49.0 ± 0.1%
AE	120M	39.3 ± 6.0%	21.0 ± 11.8%	71.8 ± 5.6%	82.2 ± 3.5%	86.8 ± 1.3%	34.7 ± 11.4%	24.4 ± 6.0%
VAE	120M	28.9 ± 2.4%	26.5 ± 2.4%	95.2 ± 3.8%	73.8 ± 2.2%	89.5 ± 2.8%	4.3 ± 3.7%	4.9 ± 3.6%

Table 1: **Evaluation of continuous sentence embeddings on the toy dataset (d = 16, 512).** Each experiment is run 5 times. AriEL, achieves almost perfect performance in most metrics, especially in validity, which quantifies how many random samples were decoded into a unique and grammatical sentence. Transformer performed exceptionally, except for validity. All methods improved their performance increasing *d*, particularly in validity, but still achieved less than one third the performance of AriEL. VAE is the second best in validity, supporting the hypothesis, that volume coding facilitates retrieval of information by random sampling.

	param	prediction accuracy	memorization	subjective interpretability
d = 16				
AriEL	2,901K	97.2 ± 0.2%	**21.9** ± 0.4%	**100.0** ± 0.0%
Transformer	588K	88.4 ± 0.4%	0.5 ± 0.4%	17.6 ± 15.3%
AE	2,787K	11.9 ± 0.6%	2.4 ± 0.6%	75.6 ± 31.4%
VAE	2,787K	14.0 ± 1.6%	2.8 ± 1.4%	68.8 ± 17.1%
d = 512				
AriEL	2,901K	97.3 ± 0.2%	**20.9** ± 0.4%	**92.0** ± 15.0%
Transformer	18,809K	88.7 ± 1.7%	3.46 ± 1.7%	45.2 ± 17.4%
AE	4,900K	15.9 ± 2.3%	3.4 ± 0.9%	77.6 ± 16,1%
VAE	5,425K	27.2 ± 2.1%	0.4 ± 0.1%	41.6 ± 16.7%

Figure 2: **Interpolations between random points in AriEL's latent space, and amount of valid sentences generated in between.** For a low latent dimension all sentences are very densely packed, and in the extreme of *d* = 1, all sentences are found on the same axis. As *d* increases, the sentences are redistributed in $[0, 1]^d$ and less sentences are found in a given direction. The lower bound at 0.746 is related to the language complexity.

Table 2: **Performance on the Guess-What?! Questioner data.** For the real dataset the pattern is repeated: AriEL shows that a larger value of valid sentences is possible. Transformer 16 gave better results when $n_{layers} = 2$ than $n_{layers} = 20$, that was tested to increase its learnable parameters from 588K to 2,666K.

measured by validity. The conflict between log-prior and log-likelihood, encouraged VAE to look for sentences outside the bias, since it was able to produce more grammatically correct sentences, albeit unbiased, than AE. Increasing the learned parameters (*d* = 512), had no effect on Transformer, that was already excellent in several of the metrics, apart from a significant improvement in validity. However, a larger latent space and the increase in number of parameters that followed, prevented AE and VAE from overfitting (better PAU and PAB). When trained on human sentences, on the GuessWhat?! dataset, AriEL sets again a large memorization and interpretability margin compared to the other approaches. Generated samples can be found in table S5.

In the interpolation diversity study (figure 2) we see that for low *d*, we have to pass through many sentences in between two random points in the latent space, while as we augment the dimensionality, we distribute the sentences in different directions. Therefore we find less sentences when we move on a straight line between two random points.

Input Sentences
is it huge and teal ?
is the thing transparent , huge and slightly heavy ?
AriEL
is it huge and teachable ?
is the thing transparent , huge and slightly heavy ?
Transformer
is it huge and magenta ?
is the thing transparent , huge and slightly heavy ?
AE
is it this average-sized and average-sized laminate ?
is the thing very heavy , heavy and very heavy ?
VAE
is it the light deep bedroom ?
is the thing textured , textured and moderately heavy ?

Table 3: **Generalization: next word prediction of unbiased sentences at test time.** Blue means that the incorrect reconstruction complies with the bias and purple means that it is still unbiased. Most reconstructions seem grammatically correct. In practice AriEL also made errors. Some failed reconstructions comply with the training bias, some do not. Interestingly the errors made by Transformer tend to turn the unbiased input sentence into a biased version. AE produced only biased sentences whose structure resembled the unbiased ones. VAE behaved similarly, producing more unbiased sentences.

AriEL
is the object that tiny very light set ?
is the thing a tiny destroyable abstraction ?
Transformer
is it an tomato slot box made of decoration facing stone ?
is the thing short and spring heavy slightly heavy potang ?
AE
is the object that light light laminate ?
is the thing a light , small and small laminate ?
VAE
is the thing a light and deep office ?
is it light , light and light and pink ?

Table 4: **Generation: output of the decoder when sampled uniformly in the latent space.** Red defines grammatically incorrect generations according to the CFG the models are trained on. AriEL produces an extremely varied set of grammatically correct sentences, most of which keep the bias of the training set. Transformer reveals itself to be hard to control via random sampling of the latent space, since it almost never produces correct sentences with this method. AE and VAE manage to produce several different sentences, the latter producing more non grammatical, but as well more varied grammatical ones.

4.2 QUALITATIVE EVALUATIONS

Table 3 and S2 show the generalization study. AE and VAE fail to generalize to the unbiased language, but both keep the structure of the input sentence. Their behavior improved with $d = 512$, and its increase of parameters. In theory, AriEL can reconstruct any sequence by design. In practice, it failed slightly less often than Transformer. Both produce reconstructions of the unbiased input at a similar rate (table 3, 1 and figure S2). This means that codes for data not seen during training are available for AriEL and Transformer. Instead, the latent space seems to be taken exclusively by the training set for AE and VAE, since sentences that are not seen during training (e.g. unbiased) cannot be reconstructed.

Almost all AriEL generations are *valid* (table 4). AE and VAE perform well despite the small latent space. VAE triples AE in *validity* when $d = 16$ (table 1). Transformer struggles to generate grammatical sentences sampling the latent space. However, increasing d, Transformer, AE and VAE improve in validity, remaining at one third AriEL's reference.

Samples generated with GPT-2 as AriEL's LM can be seen in table 5 and S4, for $d = 1, 5, 10, 50, 100$. Despite the large vocabulary of GPT-2, 50K subwords, and the long sentences, 100 symbols, the floating point precision and the unit hypercube latent space of AriEL, seem to still be able to generate high quality language.

5 DISCUSSION

AriEL latent space d is a free parameter. The size d of the latent space of AriEL can be defined at any time, for a fixed Language Model. It could therefore be controlled with a learnable parameter or with the activity of another neuron. As we increase d, the volumes will have more neighbouring volumes that represent different sentences (figure 2).

$d = 1$

Where to go from here?$\backslash n \backslash n$We're looking for special interests and fans to pay much more attention to when they come in to another site. If you're looking for good stuff to read on other sites, then get on your site and read their stories. If you're looking for things that work for your community, then look up what their leaderboard is and where they're based. If you're looking for things that make me love them, then say hey. You're really doing your

Saul Niguez is not going to let go of his dream of playing for Hillary Clinton.$\backslash n \backslash n$The Florida native will plan to accept the Democratic presidential nomination for president on November 8.$\backslash n \backslash n$The 38-year-old machinist has called Trump$\backslash$'s presidential nominee a "post-modern bull - " on social media.$\backslash n \backslash n$In an interview with DailyMail.com, Niguez told her you could still name her after Trump.$\backslash n \backslash n$"This is my father$\backslash$'s

$d = 5$

Utility Shells are just as dependent on human labor as steel, yet they had been enormously more efficient than nuclear power in incongruity's late 70s. US clients – including the nation's largest retiree retirement fund – already manufactured many of their own carbon-free cars. But what about non-node Americans? How could they simply cool down at home for work for years at a time? Inventing these subs would seem like a smart thing to do. But there's one

Out featured: on Alcoholism, Marriage and Dating: I'am No Timber [Decision note: 19th August 2013] with Runnymede Colman and producer Dan Patrick$\backslash n \backslash n$Partial transcript as follows:$\backslash n \backslash n$DAVID WEISES: After 20 years of marriage to my Malcastian partner, we've lost our lives to drugs. And so it's our hope that by allowing my Malcastian partner to become an alcoholic and grow up to be a successful husband and

Table 5: **AriEL samples using GPT-2 as Language Model.** Even for a large language model such as the small GPT-2, 117M parameters, over 50K subwords, and 100 symbols sentences, AriEL results in high quality samples for a wide range of latent dimensions (SM 11). Floating point precision does not seem to be of concern up to this limit.

Evidence for volume codes. The results suggest that AriEL volumes are responsible of its success. We provided evidence on how volume codes improve the retrieval of information composed of discrete, variable length sequences, by random sampling, compared to other codes. AriEL generates more valid sentences, an explicit volume code. VAE is the second on the toy dataset, an implicit volume code, but it is worse than AE on the real dataset.

Transformers are hard to sample from the latent space. The Transformer has been used in this work in an uncommon way: by sampling its latent space instead of its output space. Its low validity score in this work reflects it. Our aim was to understand the latent organization of language, so, we do not suggest this is the most effective way to use Transformer. Transformer is excellent when sampled in the output space, but it's difficult to sample from the latent space. This is so because Transformer represents each word in d dimensions while the other approaches represent a sentence in d dimensions. Transformer needs a very high dimensional vector to represent a sentence, $n \cdot d$, where n is the number of words in it. This makes it hard to find sentences by uniform sampling the latent space.

6   CONCLUSIONS

We proposed AriEL, a mapping of language into volumes, that we used as a reference system for language generation. AriEL fuses arithmetic coding and k-d trees to construct volumes that preserve the statistics of a dataset. On the one hand, this study helps to realize how much of the latent space lies unused by standard architectures. On the other hand, when compared to standard techniques it highlights room for improvement in their capacity for generation, prediction and generalization. AriEL allows us to sample/generate in theory the training set probability distribution and in practice a diverse set of sentences, as demonstrated on the toy, on the human dataset and using GPT-2 as its language model.

References

Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., Levenberg, J., Mané, D., Monga, R., Moore, S., Murray, D., Olah, C., Schuster, M., Shlens, J., Steiner, B., Sutskever, I., Talwar, K., Tucker, P., Vanhoucke, V., Vasudevan, V., Viégas, F., Vinyals, O., Warden, P., Wattenberg, M., Wicke, M., Yu, Y. and Zheng, X. (2015), 'TensorFlow: Large-scale machine learning on heterogeneous systems'. Software available from tensorflow.org.

Bengio, Y., Courville, A. and Vincent, P. (2013), 'Representation learning: A review and new perspectives', *IEEE transactions on pattern analysis and machine intelligence* **35**(8), 1798–1828.

Bentley, J. L. (1975), 'Multidimensional binary search trees used for associative searching', *Communications of the ACM* **18**(9), 509–517.

Bowman, S. R., Vilnis, L., Vinyals, O., Dai, A., Jozefowicz, R. and Bengio, S. (2016), Generating sentences from a continuous space, *in* '20th SIGNLL CoNLL', Association for Computational Linguistics, pp. 10–21.

Chen, T. Q., Rubanova, Y., Bettencourt, J. and Duvenaud, D. K. (2018), Neural ordinary differential equations, *in* 'NeurIPS', pp. 6571–6583.

Cho, K., van Merrienboer, B., Gulcehre, C., Bahdanau, D., Bougares, F., Schwenk, H. and Bengio, Y. (2014), Learning phrase representations using rnn encoder–decoder for statistical machine translation, *in* 'EMNLP', Association for Computational Linguistics, pp. 1724–1734.

Dai, Z., Yang, Z., Yang, Y., Carbonell, J., Le, Q. and Salakhutdinov, R. (2019), Transformer-XL: Attentive language models beyond a fixed-length context, *in* 'Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics', Association for Computational Linguistics, Florence, Italy, pp. 2978–2988.

De Vries, H., Strub, F., Chandar, S., Pietquin, O., Larochelle, H. and Courville, A. C. (2017), Guesswhat?! visual object discovery through multi-modal dialogue., *in* 'IEEE CPVR', Vol. 1.

Edelsbrunner, H., Kirkpatrick, D. and Seidel, R. (1983), 'On the shape of a set of points in the plane', *IEEE Transactions on Information Theory* **29**(4), 551–559.

Elias, P. and Abramson, N. (1963), *Information Theory and Coding*, Electronic Science, 1st edn, McGraw-Hill Inc.,US, pp. 72–89.

Friedman, J. H., Bentley, J. L. and Finkel, R. A. (1977), 'An algorithm for finding best matches in logarithmic expected time', *ACM TOMS* **3**(3), 209–226.

Glorot, X. and Bengio, Y. (2010), Understanding the difficulty of training deep feedforward neural networks, *in* 'JMLR W&CP: 13th AISTATS', Vol. 9, pp. 249–256.

Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A. and Bengio, Y. (2014), Generative adversarial nets, *in* Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence and K. Q. Weinberger, eds, 'NeurIPS 27', Curran Associates, Inc., pp. 2672–2680.

Hinton, G. E., McClelland, J. L. and Rumelhart, D. E. (1984), *Distributed representations*, Carnegie-Mellon University Pittsburgh, PA.

Hochreiter, S. and Schmidhuber, J. (1997), 'Long short-term memory', *Neural computation* **9**(8), 1735–1780.

Jebara, T. (2012), *Machine learning: discriminative and generative*, Vol. 755, Springer Science & Business Media.

Jiang, W., Kiang, S., Hakim, N. and Meadows, H. E. (1993), Lossless compression for medical imaging systems using linear/nonlinear prediction and arithmetic coding, *in* 'ISCAS', IEEE, pp. 283–286.

Johnson, N. W. (2018), *Geometries and transformations*, Cambridge University Press.

Kingma, D. P. and Ba, J. (2015), Adam: A method for stochastic optimization, *in* 'ICLR'.

Kingma, D. P. and Welling, M. (2014), Auto-encoding variational bayes., *in* 'ICLR'.

Kusner, M. J. and Hernández-Lobato, J. M. (2016), 'Gans for sequences of discrete elements with the gumbel-softmax distribution', *arXiv preprint arXiv:1611.04051* .

LeCun, Y., Boser, B., Denker, J. S., Henderson, D., Howard, R. E., Hubbard, W. and Jackel, L. D. (1989), 'Backpropagation applied to handwritten zip code recognition', *Neural computation* **1**(4), 541–551.

Li, S., Li, W., Cook, C., Zhu, C. and Gao, Y. (2018), Independently recurrent neural network (indrnn): Building A longer and deeper RNN, *in* 'IEEE CPVR'.

Ma, C., Liu, D., Peng, X., Zha, Z.-J. and Wu, F. (2019), Neural network-based arithmetic coding for inter prediction information in hevc, *in* 'ISCAS', IEEE, pp. 1–5.

Makhzani, A., Shlens, J., Jaitly, N., Goodfellow, I. and Frey, B. (2015), 'Adversarial autoencoders', *arXiv preprint arXiv:1511.05644* .

Mescheder, L., Nowozin, S. and Geiger, A. (2017), Adversarial variational bayes: Unifying variational autoencoders and generative adversarial networks, *in* 'Proceedings of the 34th International Conference on Machine Learning-Volume 70', JMLR. org, pp. 2391–2400.

Miller, G. A. (1995), 'Wordnet: A lexical database for english', *Commun. ACM* **38**(11), 39–41.

Munkres, J. R. (2018), *Elements of algebraic topology*, CRC Press.

Ng, A. Y. and Jordan, M. I. (2002), On discriminative vs. generative classifiers: A comparison of logistic regression and naive bayes, *in* 'NeurIPS', pp. 841–848.

Pasero, E. and Montuori, A. (2003), Neural network based arithmetic coding for real-time audio transmission on the tms320c6000 dsp platform, *in* 'ICASSP', Vol. 2, IEEE, pp. II–761.

Radford, A., Narasimhan, K., Salimans, T. and Sutskever, I. (2018), 'Improving language understanding by generative pre-training', *Technical report, OpenAI* .

Radford, A., Wu, J., Child, R., Luan, D., Amodei, D. and Sutskever, I. (2019), 'Language models are unsupervised multitask learners', *OpenAI Blog* **1**(8), 9.

Rezende, D. J. and Mohamed, S. (2015), 'Variational inference with normalizing flows', *arXiv preprint arXiv:1505.05770* .

Saxe, A. M., McClelland, J. L. and Ganguli, S. (2014), Exact solutions to the nonlinear dynamics of learning in deep linear neural networks, *in* 'ICLR'.

Severyn, A., Barth, E. and Semeniuta, S. (2017), A hybrid convolutional variational autoencoder for text generation, *in* 'EMNLP'.

Sutskever, I., Vinyals, O. and Le, Q. V. (2014), Sequence to sequence learning with neural networks, *in* 'NeurIPS', MIT Press, Cambridge, MA, USA, pp. 3104–3112.

Tatwawadi, K. (2018), 'Deepzip: Lossless compression using recurrent networks', *URL https://web. stanford. edu/class/cs224n/reports/2761006. pdf* .

Tolstikhin, I., Bousquet, O., Gelly, S. and Schoelkopf, B. (2017), 'Wasserstein autoencoders', *arXiv preprint arXiv:1711.01558* .

Triantafyllidis, G. and Strintzis, M. (2002), A neural network for context-based arithmetic coding in lossless image compression, *in* 'WSES ICNNA'.

Vasudevan, S., Ramos, F., Nettleton, E. and Durrant-Whyte, H. (2009), 'Gaussian process modeling of large-scale terrain', *Journal of Field Robotics* **26**(10), 812–840.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł. and Polosukhin, I. (2017), Attention is all you need, *in* 'NeurIPS', pp. 5998–6008.

Wiedemann, S., Kirchhoffer, H., Matlage, S., Haase, P., Marban, A., Marinc, T., Neumann, D., Osman, A., Marpe, D., Schwarz, H. et al. (2019), 'Deepcabac: Context-adaptive binary arithmetic coding for deep neural network compression', *arXiv preprint arXiv:1905.08318* .

Williams, R. J. and Zipser, D. (1989), 'A learning algorithm for continually running fully recurrent neural networks', *Neural Computation* **1**(2), 270–280.

Witten, I. H., Neal, R. M. and Cleary, J. G. (1987), 'Arithmetic coding for data compression', *Communications of the ACM* **30**(6), 520–540.

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Scao, T. L., Gugger, S., Drame, M., Lhoest, Q. and Rush, A. M. (2020), Transformers: State-of-the-art natural language processing, *in* 'Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations', Association for Computational Linguistics, Online, pp. 38–45.

Woodbridge, J., Anderson, H. S., Ahuja, A. and Grant, D. (2018), Detecting homoglyph attacks with a siamese neural network, *in* 'SPW', IEEE, pp. 22–28.

Xu, J., Ren, X., Lin, J. and Sun, X. (2018), Diversity-promoting gan: A cross-entropy based generative adversarial network for diversified text generation, *in* 'EMNLP', pp. 3940–3949.

Yang, Z., Hu, Z., Salakhutdinov, R. and Berg-Kirkpatrick, T. (2017), Improved variational autoencoders for text modeling using dilated convolutions, *in* 'Proceedings of the 34th International Conference on Machine Learning-Volume 70', JMLR. org, pp. 3881–3890.

Yin, H., Ding, X., Tang, L., Wang, Y. and Xiong, R. (2017), Efficient 3d lidar based loop closing using deep neural network, *in* 'ROBIO', IEEE, pp. 481–486.

Yu, L., Zhang, W., Wang, J. and Yu, Y. (2017), Seqgan: Sequence generative adversarial nets with policy gradient, *in* 'Thirty-First AAAI Conference on Artificial Intelligence'.