CORE-Bench: A Comprehensive Benchmark for Code Retrieval in the Era of Agentic Coding

Abstract

Code retrieval is becoming central to coding agents, but agentic coding requires more than matching a natural-language query to an isolated snippet. Given a user request, a coding agent needs to navigate a concrete repository state, locate relevant files and functions, gather supporting context, and filter similar in-repository distractors. Existing code retrieval benchmarks mainly evaluate docstring-to-function or snippet-level matching, thereby missing this requirement-driven repository search problem. To address this gap, we introduce **CORE-Bench**, a comprehensive benchmark for code retrieval in the era of agentic coding. CORE-Bench evaluates code retrieval ability at three levels: code understanding, issue-to-edit localization, and broader context retrieval. Built from curated code-search tasks and SWE-bench-series instances, CORE-Bench contains over 180K queries and 106K broader-context relevance labels. Experiments with representative embedding models show a sharp drop from traditional code search to code retrieval in agentic coding settings. Simple supervised fine-tuning of existing embedding models significantly improves performance in this setting, suggesting substantial room for further progress.

1 Introduction

Code retrieval has long served as a bridge between natural language and code. In agentic coding and vibe-coding settings, retrieval becomes part of the coding-agent workflow: given a bug report, feature request, refactoring request, or other user request, an agent must decide which files, functions, and documents are worth inspecting before editing. Current coding-agent harnesses, such as Open-Hands (Wang et al., 2025a) and SWE-agent (Yang et al., 2024), usually do not reduce these decisions to a single embedding lookup. Instead, they rely heavily on command-line repository exploration, including `ls`, `grep`, `find`, file reading, and iterative narrowing. These steps show that retrieval remains central in practice, but the retrieval problem shifts toward interactive, requirement-driven repository search. This raises a concrete question: why are retrieval models that perform well on standard code-search benchmarks often less useful for this search process?

This mismatch suggests that code retrieval in agentic coding settings may be better understood as *requirement-driven repository search*, rather than isolated code-snippet matching. Existing benchmarks are not fully aligned with this setting. CodeSearchNet (Husain et al., 2019) and many code tasks in MTEB (Muennighoff et al., 2023) and CoIR (Li et al., 2025) mainly evaluate decontextualized snippet retrieval under fixed corpora and simplified query-document mappings. These benchmarks measure basic natural-language/code alignment but miss several properties that matter for code retrieval in agentic coding: (1) realistic development requests often have a large intent-to-implementation gap; (2) relevant evidence is heterogeneous and scattered across code, configuration files, dependencies, and other repository artifacts; (3) candidate documents are often long function-level chunks or documentation snippets, which can dilute the evidence captured by a single embedding; (4) a single request may require multiple edit snippets and related context; and (5) real repositories contain dense local distractors, such as similar wrappers, adapters, and configuration snippets. Strong performance on existing benchmarks may therefore overstate a model's usefulness for coding agents.

To address this gap, we introduce **CORE-Bench**, a comprehensive code retrieval benchmark for evaluating retrieval ability in agentic coding settings. **CORE-Bench** has three levels. **Level-1: Code Understanding** retains challenging traditional retrieval tasks to evaluate foundational code-

understanding ability. **Level-2: Issue-to-Edit Localization** tests whether a model can retrieve the files or code chunks that must be modified for a requested change. **Level-3: Broader Context Retrieval** further evaluates whether a model can retrieve auxiliary code, documents, and other information needed to understand and complete the change.

To align with existing agentic coding evaluation settings, CORE-Bench further annotates datasets from the SWE-bench series. Patch information provides direct labels for issue-to-edit localization, while the corresponding repository snapshots preserve the pre-resolution code state and simulate the actual programming environment. For broader context retrieval, we build an automated pipeline that combines coarse annotation, relevance filtering, and quality validation to identify additional context useful for completing the requested change. The resulting data contain realistic requirements, temporally grounded repository corpora, and multi targets over edited code and broader context. We evaluate general and code-oriented embedding models of different scales on **CORE-Bench**. In addition, in-domain supervised fine-tuning (SFT) with supervision constructed from pull requests in open-source GitHub repositories substantially improves embedding models. Here are our contributions:

- We find existing code retrieval methods fall short in agentic coding, and revisit code retrieval for agentic coding as requirement-driven repository search and summarize key challenges missed by existing benchmarks.
- We introduce **CORE-Bench**, a three-level benchmark for evaluating sparse and dense retrievers in requirement-driven repository search for agentic coding, covering code understanding, issue-to-edit localization, and broader context retrieval.
- We show that current embedding retrievers suffer large performance drops on code retrieval in agentic coding settings, while in-domain SFT with supervision from GitHub pull requests improves performance but still leaves a clear gap.

2 Related Work

2.1 Code Search Benchmarks

Existing code retrieval benchmarks mostly ask a query to retrieve an "answer" artifact, rather than agent-useful repository context. CodeSearch-Net (Husain et al., 2019), CodeXGLUE (Lu et al., 2021), CoSQA (Huang et al., 2021), APPS (Hendrycks et al., 2021), HumanEval (Chen et al., 2021; Muennighoff et al., 2023), MBPP (Austin et al., 2021; Muennighoff et al., 2023), and DS-1000 (Lai et al., 2023; Muennighoff et al., 2023) cover docstrings, web queries, programming problems, algorithms, and data science. Code-TransOcean (Yan et al., 2023), CodeEditSearch (Muennighoff et al., 2023), StackOverflowQA (Muennighoff et al., 2023), FreshStack (Thakur et al., 2025; Muennighoff et al., 2023), and CodeRAG-Bench (Wang et al., 2025b) broaden the surface to multilingual code-to-code retrieval, version-history edits, developer text, mixed code–natural-language artifacts, and repositories with external knowledge sources.

Umbrella benchmarks such as MTEB (Muennighoff et al., 2023), CoIR (Li et al., 2025), CLARC (Wang et al., 2026), and CPRet (Deng et al., 2025) unify task formats and domains. SWELoc (Reddy et al., 2025), LOC-BENCH (Chen et al., 2025), and ContextBench (Li et al., 2026) approach agentic coding, but mainly study process analysis or edit-location finding, leaving standalone retrievers for multi-location context retrieval under concrete repository states and local distractors underexplored.

2.2 Code Search Models

Code search models span lexical, sparse, dense, late-interaction, and hybrid retrieval. BM25 (Robertson and Zaragoza, 2009), bag-of-words analyses (Zhang et al., 2021), and SPLADE-style sparse expansion (Formal et al., 2021) remain useful for exact identifiers, APIs, file names, stack traces, and configuration keys.

Dense methods such as DPR (Karpukhin et al., 2020) and ANCE (Xiong et al., 2021) introduced dual encoders and hard-negative mining; general embedding families multilingual-E5 (Wang et al., 2024b), BGE (Xiao et al., 2024), BGE-M3 (Chen et al., 2024), GTE (Zhang et al., 2024), GTE-Qwen (Li et al., 2023), Qwen3-Embedding (Zhang et al., 2025), E5-Mistral (Wang et al., 2024a), pplx-embed (Eslami et al., 2026), Jina Embeddings (Günther et al., 2025; Akram et al., 2026), and F2LLM-v2 (Zhang et al., 2026) provide strong transfer baselines. Code-oriented models CodeBERT (Feng et al., 2020), GraphCode-BERT (Guo et al., 2021), UniXcoder (Guo et al., 2022), CodeXEmbed (Liu et al., 2025), CodeR-

Language	LEVEL-2	LEVEL-3	Language	LEVEL-2	LEVEL-3
Python	48.7%	16.5%	C++	3.8%	6.2%
Java	12.0%	13.4%	C	0.9%	6.2%
Go	11.9%	12.4%	Ruby	0.9%	6.2%
JS	7.6%	11.3%	PHP	0.6%	4.1%
TS	7.4%	8.2%	Swift	0.2%	1.0%
Rust	5.9%	14.4%			

(a) Repository language coverage. (b) Repository-level retrieval difficulty.

Figure 1: Analysis of CORE-Bench(Level-2 and Level-3), including language coverage and difficulty.

Table 1: Statistics of CORE-Bench. Rels/Q denotes number of relevance documents per query. Avg.Q/Avg.C denote mean query/corpus lens.

Setting	Task	#Repos	#Queries	#Corpus	#Qrels	Rels/Q	Avg.Q Len	Avg.C Len
Level-1	Code Understanding	–	172,961	2,412,296	823,345	4.8	676	412
Level-2	Issue-to-Edit Localization	632	5,061	9,377,120	52,712	10.42	1,558.5	1,004.9
Level-3	Broader Context Retrieval	97	2,580	2,609,581	106,479	41.27	1,074.4	1,154.8

Table 2: Query intent distribution for Level-2/3.

Intent	Level-2	Level-3
Bug report	3,047 (60.2%)	1,468 (56.9%)
Feature request	1,659 (32.8%)	927 (35.9%)
Refactoring	187 (3.7%)	121 (4.7%)
Question	91 (1.8%)	11 (0.4%)
Other	59 (1.2%)	44 (1.7%)
Documentation	18 (0.4%)	9 (0.3%)
Total	**5,061**	**2,580**

ankEmbed (Suresh et al., 2025), Jina Code Embeddings (Kryvosheieva et al., 2025), C2LLM (Qin et al., 2025), and SweRankEmbed (Reddy et al., 2025) add programming-language or issue-localization supervision, while ColBERT (Khattab and Zaharia, 2020) and BEIR (Thakur et al., 2021) motivate late-interaction or hybrid matching. Yet these models are not designed for requirement-driven, repository-state-aware code-agent retrieval.

Overall, modern agents such as OpenHands (Wang et al., 2025a) and SWE-agent (Yang et al., 2024) need retrieval over concrete repository states, multiple edit- and reasoning-relevant locations, and plausible in-repository distractors. CORE-Bench targets this missing code-agent retrieval setting.

3 Benchmark

3.1 Overview of CORE-Bench

CORE-Bench uses a three-level evaluation:

- **Level-1: Code Understanding.** We retain challenging traditional retrieval tasks across Code-to-Text, Text-to-Code, Code-to-Code, and hybrid settings, excluding datasets with weak alignment with realistic retrieval.
- **Level-2: Issue-to-Edit Localization.** We evaluate whether a model can retrieve files or chunks that must be modified for a requested change, using patch-aligned edit snippets from SWE-bench-series and SWE-bench-style software-change datasets.
- **Level-3: Broader Context Retrieval.** We evaluate whether retrieval can recover auxiliary code, documentation, and tests that help an agent reason about and complete the change, using an automated annotation pipeline because such context is rarely recorded by developers.

Table 1 summarizes the aggregate scale of CORE-Bench. Level-1 contains 172K queries over 2.4M corpus items for foundational code understanding. Level-2 covers 632 repositories, 5,061 queries, and 9.38M repository chunks for issue-to-edit localization, while Level-3 contains 2,580 queries and 106K relevance labels for

Figure 2: Overall pipeline of CORE-Bench (LEVEL-2 and LEVEL-3) benchmark construction.

broader context retrieval. Detailed sub-dataset statistics are provided in Appendix A. Although Level-3 has fewer queries than Level-2, it contains roughly twice as many qrels and nearly four times as many relevant chunks per query, reflecting its denser broader-context annotation target. We also provide rewrite variants for Level-2 and Level-3 by converting raw pull request (PR) or issue descriptions into concise developer-facing queries that resemble what users would ask an AI coding assistant, while keeping the corpus and qrels unchanged.

Figure 1 and Table 2 further characterize the agentic levels. Across Level-2 and Level-3, CORE-Bench spans 11 programming languages, as shown in Figure 1(a); bug reports and feature requests account for over 92% of queries. Figure 1(b) groups repositories by retrieval corpus size and relevant chunks per query, yielding four regimes that test both precise edit localization and large-scale contextual retrieval.

3.2 Benchmark Construction

3.2.1 LEVEL-1: Code Understanding

For Level-1, we curate existing code-retrieval datasets into a unified retrieval setting (Li et al., 2025; Muennighoff et al., 2023). The retained benchmark covers Text-to-Code, Code-to-Text, Code-to-Code, hybrid retrieval, and competitive-programming retrieval through APPS, CoSQA, SyntheticText2SQL, CLARC, Code-SearchNet, CodeTransOcean-DL, CodeFeedback-ST, and CPRet (Hendrycks et al., 2021; Huang et al., 2021; Muennighoff et al., 2023; Wang et al., 2026; Husain et al., 2019; Yan et al., 2023; Zheng et al., 2024; Deng et al., 2025). We exclude saturated or weakly aligned tasks, including StackOverflowQA, CodeEditSearchRetrieval, and CodeFeedback-MT.

3.2.2 LEVEL-2: Issue-to-Edit Localization

LEVEL-2 is built from existing end-to-end agent benchmarks in the SWE-bench family, such as SWE-bench_Verified, SWE-bench_Pro, and related SWE-bench-style datasets. The LLM-based query-filtering stage uses Qwen3.5-397B-A17B (Qwen Team, 2026) to remove answer-leaking, low-quality, underspecified, or non-actionable PR and issue descriptions before patch alignment.

As shown in Figure 2, the construction proceeds in five steps. First, we collect PR or issue metadata from SWE-bench-derived sources. Second, we checkout each repository to the commit immediately before the PR, so the retrieval corpus matches the code state seen by the corresponding request. Third, we chunk source and documentation files with AST and LangChain-based splitters, filtering irrelevant file types while preserving file paths and line spans. Fourth, we align the PR patch back to these pre-PR chunks by matching modified files and edited line ranges. Finally, we treat the PR or issue description as the query and the patch-aligned chunks as relevant documents. This turns historical software changes into issue-to-edit localization instances without using post-hoc diffs as retrievable answers.

3.2.3 LEVEL-3: Broader Context Retrieval

Level-3 extends Level-2 beyond edited chunks. In real development tasks, a developer or agent often reads tests, helper functions, configuration files, documentation, and neighboring call sites before deciding how to edit the code. Such supporting context is rarely preserved in PR metadata, so we construct it with an automated pipeline that re-

runs resolution attempts and extracts useful context from the resulting agent execution traces. The pipeline has three phases: **1) Precise Context Annotation; 2) Quality Verification; and 3) Feedback Iteration.**

Phase 1: Precise Context Annotation We combine a Code Agent with LLM-based relevance assessment. Mini-SWE-Agent reruns the corresponding development tasks with Qwen3.5-397B-A17B. From the execution traces, we extract browse actions, including files opened by commands such as cat, grep, head, and sed. These browsed snippets are aligned to the Level-2 chunking schema, so overlapping Level-2/3 instances use comparable chunk units. The resulting query–chunk pairs are still noisy because agents may inspect irrelevant files. We therefore apply a three-vote LLM relevance ensemble: Qwen3.5-397B-A17B casts two independent votes, and Claude Sonnet 4.6 (Anthropic, 2026) casts one additional vote for each pair.

Phase 2: Quality Evaluation We validate annotations by modifying mini-swe-agent to run in a closed allowlist setting. For each task, the agent can only read files covered by the annotation-derived allowlist. We build one allowlist from Level-2 edit labels and another from Level-3 broader-context labels, then rerun the annotated dataset under both settings. A higher resolution rate under the Level-3 allowlist indicates that the added context is not merely textually related, but functionally useful for completing the requested change.

Phase 3: Feedback Iteration For cases whose annotations remain insufficient, we perform feedback iteration. Unresolved or weakly supported cases are rerun, and newly browsed contextual snippets are aligned, judged, and added as supplementary labels. We do not require every retained trajectory to end in a solved patch, because resolved runs tend to favor easier tasks with smaller edits. Instead, useful trajectory-derived context can be kept after relevance judging when it helps understand or localize the requested change.

3.3 Rewrite Version of CORE-Bench

Original PR and issue descriptions are often detailed and often include issue-template boilerplate, whereas practical agentic or vibe-coding queries are usually shorter, more casual, and directly addressed to an AI coding assistant. For the retained Level-2 and Level-3 queries, we therefore provide rewritten variants that preserve key technical terms, error messages, and code clues while removing irrelevant template noise and redundant context. The separate query-filtering stage handles unsuitable inputs before benchmark construction; rewriting only changes the retained query style. Both stages use Qwen3.5-397B-A17B, and the prompt templates are provided in Appendix H.

3.4 Training Data Construction

To evaluate whether LLM embedding models can benefit from task-specific supervision, we construct an in-domain SFT set from PRs outside the SWE-bench family. PR descriptions serve as queries, while patch-aligned chunks provide positive supervision and repository-local chunks provide hard negatives. The full data scale, sampling strategy, and contrastive training objective are provided in Appendix B.

4 Experiments and Evaluation

4.1 Experimental Setup

Baselines. We select a representative subset of embedding models for the main-paper comparison, including BGE-M3 (Chen et al., 2024), GTE-Qwen2-1.5B-instruct (Li et al., 2023), Qwen3-Embedding (Zhang et al., 2025), E5-Mistral (Wang et al., 2024a), F2LLM-v2 (Zhang et al., 2026), CodeRankEmbed (Suresh et al., 2025), Jina Code Embeddings (Kryvosheieva et al., 2025), C2LLM-7B (Qin et al., 2025), SweRankEmbed-Large (Reddy et al., 2025), and our in-domain fine-tuned Qwen3-Embedding variants. All in-domain SFT rows report checkpoints after three supervised fine-tuning epochs. A more complete list of evaluated baselines and their model descriptions is provided in Appendix C.

Evaluation Details. We evaluate all embedding models with a modified MTEB framework (Muennighoff et al., 2023). Instead of materializing one corpus for each query, we build a repository-level corpus by merging and deduplicating chunks from different temporal snapshots, while preserving repository and commit metadata for each chunk. During scoring, the evaluator filters this merged corpus separately for each query, so metrics are computed only over the documents visible at the corresponding PR or issue state. For instruction-tuned models, we follow each model family's official query and document instructions, and use raw text when no template is available. We

Table 3: **CORE-Bench results on a model subset (NDCG@10/Recall@100). L1** = Level-1 Code Understanding; **L2** = Level-2 Issue-to-Edit Localization; **L3** = Level-3 Broader Context Retrieval; **Rw** = query-rewrite variant.

Model	#Param	L1	L2	L3	L2-Rw	L3-Rw	L1–L3 Avg.	Rewrite Avg.
Small Embedding Models (<1B)								
CodeRankEmbed	137M	47.4/78.6	12.1/32.9	22.5/28.6	13.8/37.9	26.2/31.4	27.3/46.7	20.0/34.6
bge-m3	568M	23.8/53.8	4.6/18.3	8.7/12.5	3.9/15.3	7.8/11.4	12.4/28.2	5.8/13.3
Qwen3-Embedding-0.6B	0.6B	66.9/94.7	17.0/45.5	32.6/40.2	16.5/45.5	31.1/39.2	38.8/60.1	23.8/42.3
Medium Embedding Models (1B–2B)								
gte-Qwen2-1.5B-instruct	1.5B	31.3/63.0	3.5/15.9	8.1/14.9	4.3/18.2	9.5/15.7	14.3/31.3	6.9/16.9
jina-code-embeddings-1.5b	1.5B	56.2/88.7	17.0/48.5	31.6/42.7	14.9/46.4	28.9/39.2	34.9/60.0	21.9/42.8
Large Embedding Models (≥4B)								
Qwen3-Embedding-4B	4B	72.7/96.9	18.3/46.9	32.8/40.8	17.3/46.2	31.1/39.3	41.3/61.5	24.2/42.8
C2LLM-7B	7B	72.4/96.7	16.7/44.9	32.9/41.0	14.5/41.4	28.4/37.8	40.7/60.9	21.5/39.6
e5-mistral-7b-instruct	7B	54.7/86.4	18.3/51.7	33.9/44.4	17.4/49.9	31.8/42.0	35.6/60.9	24.6/45.9
SweRankEmbed-Large	7B	45.4/79.1	22.4/52.1	34.4/42.4	21.7/49.7	33.6/41.5	34.0/57.9	27.7/45.6
F2LLM-v2-8B	8B	63.8/91.9	19.0/45.8	33.8/37.2	17.8/43.3	30.8/34.9	38.9/58.3	24.3/39.1
Qwen3-Embedding-8B	8B	71.7/96.9	20.3/48.0	34.4/41.5	17.2/45.1	30.8/38.4	42.2/62.1	24.0/41.7
In-domain SFT Models (0.6B–8B)								
Qwen3-0.6B-SFT	0.6B	58.1/90.3	26.5/59.4	44.5/54.4	25.5/58.6	40.2/52.0	43.0/68.1	32.8/55.3
Qwen3-4B-SFT	4B	59.8/90.5	30.3/66.0	49.2/61.6	27.3/64.3	44.1/58.1	46.4/72.7	35.7/61.2
Qwen3-8B-SFT	8B	63.0/92.5	32.8/66.4	50.2/61.4	29.2/64.0	44.4/57.4	48.7/73.4	36.8/60.7

report NDCG@10 and Recall@100, with metric definitions provided in Appendix D. NDCG@10 measures top-rank precision for LEVEL-2 edit localization, while Recall@100 measures whether LEVEL-3 retrieves the broader context needed by the agent.

4.2 Evaluation of Retrieval Models

Table 3 summarizes representative results across the three CORE-Bench levels and their query-rewrite variants; complete results are provided in Appendix G. We observe a large gap between traditional code understanding and repository-level retrieval for agentic coding. Many strong code-search models collapse to a similar low range on LEVEL-2/3, as shown in Figure 3. For example, Qwen3-Embedding-8B reaches 71.7/96.9 on LEVEL-1, but drops to 20.3/48.0 on LEVEL-2 and 34.4/41.5 on LEVEL-3, indicating that LEVEL-2/3 are not simply scaled-up versions of traditional code search.

LEVEL-2 has lower NDCG@10, whereas LEVEL-3 has lower Recall@100, reflecting their different focus on edit-location precision and broader context coverage. Rewritten queries often fail to improve retrieval and can even reduce performance, suggesting that realistic repository retrieval depends on request-specific context that may be lost during rewriting.

Figure 3: Detailed performance comparison of top models.

Figure 4: Spearman correlation of NDCG@10 between LEVEL-1 tasks and LEVEL-2/3 averages.

4.3 In-domain SFT Performance

The last group of Table 3 reports the results of embedding models trained with in-domain supervision. We find that simple SFT substantially improves retrieval performance on LEVEL-2/3.

Table 4: **CORE-Bench per-language results for a subset of models on LEVEL-2 and LEVEL-3 (NDCG@10).**

	LEVEL-2											LEVEL-3										
Model	Python	Go	JS	Rust	TS	Java	C++	C	Ruby	PHP	Swift	Python	Go	JS	Rust	TS	Java	C++	C	Ruby	PHP	Swift
Small Embedding Models (<1B)																						
CodeRankEmbed	10.7	15.3	8.8	12.5	10.2	8.7	14.1	12.4	5.4	6.4	0.0	26.4	33.5	12.3	26.5	17.6	21.7	28.6	26.3	13.6	10.6	0.0
bge-m3	5.1	4.5	4.0	4.7	2.2	3.0	3.8	3.0	2.6	2.1	0.0	8.1	10.6	5.0	10.9	4.1	8.3	10.0	8.9	3.7	2.0	0.0
Qwen3-0.6B	18.4	16.5	18.1	14.3	17.0	10.2	17.7	11.8	8.0	4.5	17.7	38.2	37.7	27.5	34.8	34.1	30.4	37.4	28.8	26.0	12.0	7.1
Medium Embedding Models (1B–2B)																						
gte-Qwen2-1.5B	2.0	4.0	3.5	4.1	3.3	3.1	1.8	2.1	0.0	0.9	0.0	5.9	9.1	5.8	6.5	4.1	8.2	7.8	8.7	3.2	3.7	0.0
jina-code-1.5b	18.3	23.1	14.1	18.2	15.9	14.6	16.2	10.5	12.2	9.6	0.0	33.1	46.0	23.8	37.1	31.0	31.4	35.5	27.2	21.1	19.6	0.0
Large Embedding Models (≥4B)																						
Qwen3-4B	19.3	15.1	16.0	15.6	19.3	10.0	18.4	12.5	4.2	4.4	0.0	38.8	33.4	25.4	33.5	32.2	28.0	37.8	30.7	17.9	11.3	0.0
C2LLM-7B	16.6	24.1	20.1	19.4	19.1	12.1	17.3	10.3	11.3	2.2	38.9	33.7	46.1	32.5	40.4	30.8	35.9	40.8	28.1	27.3	14.6	23.6
e5-mistral-7b	20.1	25.5	15.2	16.3	19.0	11.3	16.2	14.5	9.6	6.6	0.0	38.7	45.6	20.6	31.3	29.1	27.2	34.3	31.6	33.2	18.2	0.0
SweRankEmbed-L	25.9	26.8	21.2	18.0	25.0	10.6	17.9	8.7	9.2	_18.7_	0.0	42.6	44.3	24.0	35.0	34.9	25.9	33.9	23.5	23.2	19.4	0.0
F2LLM-v2-8B	20.5	17.1	14.7	19.0	17.6	13.2	16.4	13.4	10.6	10.6	38.7	36.9	38.2	21.3	34.3	32.3	35.8	36.2	33.0	29.1	24.2	14.8
Qwen3-8B	21.9	14.6	18.6	22.1	22.6	12.5	21.0	17.0	13.4	4.2	45.6	39.4	32.2	23.5	40.6	33.4	32.1	45.6	35.9	31.9	13.9	_32.3_
In-domain SFT Models (0.6B–8B)																						
Qwen3-0.6B-SFT	27.5	33.3	31.8	28.1	32.3	17.6	25.4	19.0	12.2	15.5	48.2	48.8	56.7	43.3	46.8	46.4	44.7	48.6	40.4	38.7	25.3	18.5
Qwen3-4B-SFT	_30.6_	_36.3_	_36.6_	_33.4_	36.0	19.7	26.5	22.7	26.5	14.9	**92.0**	51.6	61.6	50.7	50.4	_53.4_	45.7	50.3	47.1	50.3	_30.2_	**38.3**
Qwen3-8B-SFT	**33.7**	**38.8**	**39.8**	**33.6**	**36.8**	**21.8**	**29.1**	**27.8**	**27.7**	**19.4**	_60.5_	**53.7**	**64.3**	**51.9**	**52.2**	_51.5_	**48.1**	**52.6**	**48.3**	**53.1**	**30.4**	23.2

Table 5: **CORE-Bench LEVEL-2 results for a subset of models by repository difficulty (NDCG@10/Recall@100). F/D** denote focused/dense relevance regimes, and **S/L** denote small/large corpus regimes. Full LEVEL-2/3 difficulty results are provided in Table 22 in Appendix G.

Model	F-S	F-L	D-S	D-L
Small Embedding Models (<1B)				
CodeRankEmbed	13.4/43.7	9.5/28.8	14.5/39.7	12.6/28.4
bge-m3	4.7/25.8	3.5/13.5	6.9/26.2	5.3/12.9
Qwen3-0.6B	17.4/54.3	16.1/45.6	18.6/46.6	17.8/40.9
Medium Embedding Models (1B–2B)				
gte-Qwen2-1.5B	2.9/21.5	1.7/8.6	6.5/25.1	3.4/12.1
jina-code-1.5b	16.0/58.0	17.6/49.8	19.2/48.9	18.9/43.0
Large Embedding Models (≥4B)				
Qwen3-4B	16.9/55.2	16.0/45.3	19.9/48.8	18.6/41.2
C2LLM-7B	18.4/53.0	16.6/46.0	20.6/47.4	19.4/41.0
e5-mistral-7b	19.8/60.6	18.4/51.3	21.4/52.1	19.9/44.1
SweRankEmbed-L	24.1/61.7	23.1/50.8	22.5/51.7	24.0/43.8
F2LLM-v2-8B	14.2/49.1	17.9/44.5	21.3/47.3	20.2/37.9
Qwen3-8B	18.8/55.9	19.0/48.2	21.8/48.3	20.6/41.7
In-domain SFT Models (0.6B–8B)				
Qwen3-0.6B-SFT	28.2/67.9	28.0/62.1	26.0/55.4	29.2/54.2
Qwen3-4B-SFT	_30.9_/**74.7**	31.8/69.2	_29.1_/**61.2**	32.3/_59.4_
Qwen3-8B-SFT	**34.0**/_73.2_	**35.0**/69.7	**32.7**/60.5	**33.7**/**60.4**

Qwen3-0.6B-SFT already outperforms larger embedding models on both LEVEL-2 and LEVEL-3, and Qwen3-8B-SFT achieves the best overall performance on code retrieval in agentic coding settings. Nevertheless, there remains a clear gap between its LEVEL-2/3 performance and its LEVEL-1 performance. This indicates that supervision from pull requests helps the model learn repository-level relevance signals, but it still does not fully solve the difficulty of multi-target change localization.

4.4 Cross-level Correlation Analysis

Figure 4 gives the cross-level correlation analysis. The LEVEL-1 average only moderately predicts LEVEL-2 performance. Code-to-text retrieval is a relatively weak proxy for both agentic levels, while the hybrid task has the strongest correlation. Together with the absolute performance drop in Table 3, this shows that LEVEL-2 and LEVEL-3 preserve part of the model-ranking signal from traditional retrieval tasks, but also introduce additional challenges related to repository-local structure and requirement-conditioned context.

4.5 Performance on Different Languages

Table 4 reports results by programming language. The benefit of in-domain SFT is not limited to Python. On LEVEL-2, Qwen3-8B-SFT obtains the best NDCG@10 on most languages and substantially improves over the non-adapted Qwen3-8B baseline. The improvement is especially clear on JavaScript, TypeScript, and Go. This suggests that repository-local naming conventions, framework structure, and engineering patterns matter for requirement-conditioned retrieval beyond generic semantic similarity. Language difficulty cannot be explained only by popularity. Even after SFT, Java remains one of the harder LEVEL-2

Table 6: LEVEL-2/3 target expansion examples.

Instance	Signal and Targets
django-15499	**Request:** optimize CreateModel + AlterModelManagers into CreateModel.
L2: 1 qrel for the migration operation-reduction branch.
L3: 58 qrels covering the migration graph, duplicate-object validation, model-state objects, and helper operations.
grpc-go-3201	**Request:** do not call NewServiceConfig when DNS lookups are disabled.
L2: 2 qrels for DNS resolver and resolver-wrapper callers.
L3: 121 qrels over the resolver stack, ClientConn state updates, default service-config behavior, and wrapper logic.

Table 7: Query rewrite examples.

Instance	Rewrite Effect
streamlink-5926	**Raw:** 1,904-character bug report with checklist text, Kuwaiti channel URLs, and debug logs.
Rewrite: keeps the "No plugin can handle URL" failure and concrete media.gov.kw URLs as retrieval anchors.
fmt-3729	**Raw:** verbose discussion of generic versus native formatting for filesystem paths.
Rewrite: requests generic and native format specifiers while preserving slash-direction behavior.
camunda-27226	**Raw:** change the state field from string to enum in ProcessInstance and ProcessInstanceFilter.
Rewrite: keeps class names, state, and OpenAPI enum values while turning the note into a developer question.

tasks. Overall, task-specific adaptation improves cross-language robustness, but repository-local requirement-conditioned retrieval remains uneven across ecosystems.

4.6 Performance across Difficulty Levels

Table 5 reports LEVEL-2 performance under different repository difficulties. We draw two conclusions: (1) In-domain SFT improves performance in all difficulty settings, including the hardest dense-large setting. (2) Even for the strongest SFT model, Recall@100 still drops when moving from focused or smaller settings to dense repositories. This indicates that when the candidate pool becomes larger and the repository contains many similar distractors, relevant edit chunks can still be pushed out of the retrieved set. Besides, SFT models maintain relatively stable NDCG@10 across difficulty settings, suggesting that the adapted models learn useful repository-local ranking signals once relevant candidates are retrieved. Therefore, dense-large repositories form an important stress test for future retrievers.

4.7 Qualitative Case Studies

Tables 6 and 7 highlight representative cases of CORE-Bench. LEVEL-3 needs broader recall because useful context can be spread across state-management, validation, and helper paths rather than concentrated at the final edit site. Query rewriting removes boilerplate and changes the lexical and structural signals available to retrievers. These examples clarify why the two agen-

tic levels reward different retrieval behavior. In django-15499, the direct edit target is narrow, but the agent also needs migration-graph and model-state context to judge whether the optimization is valid. In grpc-go-3201, the useful context expands from resolver call sites to ClientConn state and service-configuration propagation. Thus, LEVEL-3 is a context-coverage setting rather than a looser version of edit localization. The rewrite cases further show that cleaner queries are useful only when they preserve repository anchors, such as concrete URLs, error strings, API names, fields, and enum values; otherwise, rewriting can remove exactly the lexical cues that help retrieve local code amid cross-file distractors during realistic agent runs. Full cases are provided in Tables 10 and 15 in Appendix F.

5 Conclusion

In this paper, we presented **CORE-Bench**, a comprehensive benchmark for code retrieval in agentic coding. By organizing evaluation from traditional code understanding to issue-to-edit localization and broader context retrieval, CORE-Bench exposes the gap between snippet-level code search and requirement-driven repository search. Our experiments show that current general embedding models and code-oriented embedding models degrade sharply in this setting. Besides, in-domain SFT with pull request data across different open-source repositories substantially improves LEVEL-2/3 retrieval of CORE-Bench.

Limitations

CORE-Bench is mainly built from SWE-bench-series and SWE-bench-style software-change data. It may therefore not fully capture retrieval on newly created or rapidly evolving repositories, and it does not yet include freshness-oriented metrics for such settings. Its diversity is also uneven: popular ecosystems contribute more examples, while long-tail languages and uncommon project structures remain underrepresented.

References

Mohammad Kalim Akram, Saba Sturua, Nastia Havriushenko, Quentin Herreros, Michael Günther, Maximilian Werk, and Han Xiao. 2026. jina-embeddings-v5-text: Task-targeted embedding distillation. *arXiv preprint arXiv:2602.15547*.

Anthropic. 2026. Claude Sonnet 4.6. Accessed: 2026-05-24.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and 1 others. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Jianlyu Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2024. M3-embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. In *Findings of the association for computational linguistics: ACL 2024*, pages 2318–2335.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Zhaoling Chen, Robert Tang, Gangda Deng, Fang Wu, Jialong Wu, Zhiwei Jiang, Viktor Prasanna, Arman Cohan, and Xingyao Wang. 2025. Locagent: Graph-guided llm agents for code localization. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8697–8727.

Han Deng, Yuan Meng, Shixiang Tang, Wanli Ouyang, and Xinzhu Ma. 2025. Cpret: A dataset, benchmark, and model for retrieval in competitive programming. In *Advances in Neural Information Processing Systems*, volume 38. Datasets and Benchmarks Track.

Sedigheh Eslami, Maksim Gaiduk, Markus Krimmel, Louis Milliken, Bo Wang, and Denis Bykov. 2026. Diffusion-pretrained dense and contextual embeddings. *arXiv preprint arXiv:2602.11151*.

Zhangyin Feng, Daya Guo, Duyu Tang, Nan Duan, Xiaocheng Feng, Ming Gong, Linjun Shou, Bing Qin, Ting Liu, Daxin Jiang, and 1 others. 2020. Codebert: A pre-trained model for programming and natural languages. In *Findings of the association for computational linguistics: EMNLP 2020*, pages 1536–1547.

Thibault Formal, Benjamin Piwowarski, and Stéphane Clinchant. 2021. Splade: Sparse lexical and expansion model for first stage ranking. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2288–2292.

Michael Günther, Saba Sturua, Mohammad Kalim Akram, Isabelle Mohr, Andrei Ungureanu, Bo Wang, Sedigheh Eslami, Scott Martens, Maximilian Werk, Nan Wang, and 1 others. 2025. jina-embeddings-v4: Universal embeddings for multimodal multilingual retrieval. In *Proceedings of the 5th Workshop on Multilingual Representation Learning (MRL 2025)*, pages 531–550.

Daya Guo, Shuai Lu, Nan Duan, Yanlin Wang, Ming Zhou, and Jian Yin. 2022. Unixcoder: Unified cross-modal pre-training for code representation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7212–7225.

Daya Guo, Shuo Ren, Shuai Lu, Zhangyin Feng, Duyu Tang, Shujie LIU, Long Zhou, Nan Duan, Alexey Svyatkovskiy, Shengyu Fu, and 1 others. 2021. Graphcodebert: Pre-training code representations with data flow. In *International Conference on Learning Representations*.

Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, and 1 others. 2021. Measuring coding challenge competence with apps. *arXiv preprint arXiv:2105.09938*.

Junjie Huang, Duyu Tang, Linjun Shou, Ming Gong, Ke Xu, Daxin Jiang, Ming Zhou, and Nan Duan. 2021. Cosqa: 20,000+ web queries for code search and question answering. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 5690–5700.

Hamel Husain, Ho-Hsiang Wu, Tiferet Gazit, Miltiadis Allamanis, and Marc Brockschmidt. 2019. Codesearchnet challenge: Evaluating the state of semantic code search. arxiv 2019. *arXiv preprint arXiv:1909.09436*.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP)*, pages 6769–6781.

Omar Khattab and Matei Zaharia. 2020. Colbert: Efficient and effective passage search via contextualized late interaction over bert. In *Proceedings of the 43rd International ACM SIGIR conference on research and development in Information Retrieval*, pages 39–48.

Daria Kryvosheieva, Saba Sturua, Michael Günther, Scott Martens, and Han Xiao. 2025. Efficient code embeddings from code generation models. *arXiv preprint arXiv:2508.21290*.

Yuhang Lai, Chengxi Li, Yiming Wang, Tianyi Zhang, Ruiqi Zhong, Luke Zettlemoyer, Wen-tau Yih, Daniel Fried, Sida Wang, and Tao Yu. 2023. Ds-1000: A natural and reliable benchmark for data science code generation. In *International Conference on Machine Learning*, pages 18319–18345. PMLR.

Han Li, Letian Zhu, Bohan Zhang, Rili Feng, Jiaming Wang, Yue Pan, Earl T Barr, Federica Sarro, Zhaoyang Chu, and He Ye. 2026. Contextbench: A benchmark for context retrieval in coding agents. *arXiv preprint arXiv:2602.05892*.

Xiangyang Li, Kuicai Dong, Yi Quan Lee, Wei Xia, Hao Zhang, Xinyi Dai, Yasheng Wang, and Ruiming Tang. 2025. Coir: A comprehensive benchmark for code information retrieval models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 22074–22091.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. 2023. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*.

Ye Liu, Rui Meng, Shafiq Joty, Silvio Savarese, Caiming Xiong, Yingbo Zhou, and Semih Yavuz. 2025. Codexembed: A generalist embedding model family for multilingual and multi-task code retrieval. In *Proceedings of the Conference on Language Modeling*. COLM 2025.

Shuai Lu, Daya Guo, Shuo Ren, Junjie Huang, Alexey Svyatkovskiy, Ambrosio Blanco, Colin Clement, Dawn Drain, Daxin Jiang, Duyu Tang, and 1 others. 2021. Codexglue: A machine learning benchmark dataset for code understanding and generation. *arXiv preprint arXiv:2102.04664*.

Niklas Muennighoff, Nouamane Tazi, Loïc Magne, and Nils Reimers. 2023. Mteb: Massive text embedding benchmark. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 2014–2037.

Jin Qin, Zihan Liao, Ziyin Zhang, Hang Yu, Peng Di, and Rui Wang. 2025. C2llm technical report: A new frontier in code retrieval via adaptive cross-attention pooling. *arXiv preprint arXiv:2512.21332*.

Qwen Team. 2026. Qwen3.5: Accelerating productivity with native multimodal agents.

Revanth Gangi Reddy, Tarun Suresh, JaeHyeok Doo, Ye Liu, Xuan Phi Nguyen, Yingbo Zhou, Semih Yavuz, Caiming Xiong, Heng Ji, and Shafiq Joty. 2025. Swerank: Software issue localization with code ranking. *arXiv preprint arXiv:2505.07849*.

Stephen Robertson and Hugo Zaragoza. 2009. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389.

Tarun Suresh, Revanth Gangi Reddy, Yifei Xu, Zach Nussbaum, Andriy Mulyar, Brandon Duderstadt, and Heng Ji. 2025. Cornstack: High-quality contrastive data for better code retrieval and reranking. In *International Conference on Learning Representations*.

Nandan Thakur, Jimmy Lin, Samuel Havens, Michael Carbin, Omar Khattab, and Andrew Drozdov. 2025. Freshstack: Building realistic benchmarks for evaluating retrieval on technical documents. In *Advances in Neural Information Processing Systems*, volume 38. Datasets and Benchmarks Track.

Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. Beir: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Kaicheng Wang, Liyan Huang, Weike Fang, and Weihang Wang. 2026. Clarc: C/c++ benchmark for robust code search. In *The Fourteenth International Conference on Learning Representations*. Poster.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2024a. Improving text embeddings with large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11897–11916.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2024b. Multilingual e5 text embeddings: A technical report. *arXiv preprint arXiv:2402.05672*.

Xingyao Wang, Boxuan Li, Yufan Song, Frank F Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, and 1 others. 2025a. Openhands: An open platform for ai software developers as generalist agents. In *International Conference on Learning Representations*.

Zora Zhiruo Wang, Akari Asai, Frank F Xu, Yiqing Xie, Graham Neubig, Daniel Fried, and 1 others. 2025b. Coderag-bench: Can retrieval augment code generation? In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 3199–3214.

Shitao Xiao, Zheng Liu, Peitian Zhang, Niklas Muennighoff, Defu Lian, and Jian-Yun Nie. 2024. C-pack: Packed resources for general chinese embeddings.

In *Proceedings of the 47th international ACM SIGIR conference on research and development in information retrieval*, pages 641–649.

Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul N. Bennett, Junaid Ahmed, and Arnold Overwijk. 2021. Approximate nearest neighbor negative contrastive learning for dense text retrieval. In *International Conference on Learning Representations*.

Weixiang Yan, Yuchen Tian, Yunzhe Li, Qian Chen, and Wen Wang. 2023. Codetransocean: A comprehensive multilingual benchmark for code translation. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 5067–5089.

John Yang, Carlos E Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. 2024. Swe-agent: Agent-computer interfaces enable automated software engineering. *Advances in Neural Information Processing Systems*, 37:50528–50652.

Xin Zhang, Yanzhao Zhang, Dingkun Long, Wen Xie, Ziqi Dai, Jialong Tang, Huan Lin, Baosong Yang, Pengjun Xie, Fei Huang, and 1 others. 2024. mgte: Generalized long-context text representation and reranking models for multilingual text retrieval. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 1393–1412.

Xinyu Zhang, Ji Xin, Andrew Yates, and Jimmy Lin. 2021. Bag-of-words baselines for semantic code search. In *Proceedings of the 1st Workshop on Natural Language Processing for Programming (NLP4Prog 2021)*, pages 88–94.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, and 1 others. 2025. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*.

Ziyin Zhang, Zihan Liao, Hang Yu, Peng Di, and Rui Wang. 2026. F2llm-v2: Inclusive, performant, and efficient embeddings for a multilingual world. *arXiv preprint arXiv:2603.19223*.

Tianyu Zheng, Ge Zhang, Tianhao Shen, Xueling Liu, Bill Yuchen Lin, Jie Fu, Wenhu Chen, and Xiang Yue. 2024. Opencodeinterpreter: Integrating code generation with execution and refinement. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 12834–12859.

A Detailed Dataset Statistics

Table 8 reports the sub-dataset-level statistics for all three CORE-Bench levels behind the aggregate summary in Table 1.

LEVEL-1. LEVEL-1 brings together standard code-understanding retrieval tasks rather than repository-local requirement data. The rows differ noticeably in query style and relevance density: CodeSearchNet-style tasks dominate the corpus scale, CLARC uses much denser relevance labels, and CosQA or Text2SQL-style tasks contain shorter natural-language queries. This level is mainly a reference point for general code-semantic matching.

LEVEL-2. LEVEL-2 moves to issue-to-edit localization inside concrete repository snapshots. The corpus is much larger, while each request is linked to a relatively small set of edit-bearing chunks. Different SWE-bench-derived sources vary in repository coverage and target density, but the common difficulty is the same: the retriever must find the code that is likely to be edited, not just broadly related code.

LEVEL-3. LEVEL-3 keeps the requirement-centered setting but expands the target from edit locations to useful surrounding context. Its relevance sets are therefore denser than LEVEL-2, especially for cases where completing the change requires nearby helpers, tests, state definitions, or related implementation paths. This level is intended to evaluate whether retrieval can support an agent's broader context gathering, not only the first edit location.

CORE-Bench is constructed from publicly released code-retrieval datasets, SWE-bench-series benchmarks, and open-source GitHub repositories. We use only data sources that are available for research or benchmark use, follow the corresponding upstream licenses and terms, and do not include private or proprietary repositories. This construction avoids introducing additional license risk beyond the original open-source data sources.

B SFT Training Details

Table 9 reports the scale of the in-domain training data used for continued embedding-model fine-tuning. The training set covers 628 repositories and 53,301 queries collected from pull requests, yielding 1,218,875 relevance labels over a corpus of 29,171,451 chunks. On average, each query has 22.87 relevant chunks, indicating that the supervision is not limited to single-location matching but often contains multiple patch-aligned code targets. The average query length is 375.1 characters,

Table 8: Detailed CORE-Bench dataset statistics. Rewrite variants share the same corpus and qrels with their non-rewrite counterparts. Total-row averages are weighted by the corresponding total query or corpus counts.

Sub-dataset	#Repos	#Queries	#Corpus	#Qrels	Rels/Q	Avg.Q Len	Avg.Rw.Q Len	Avg.C Len
LEVEL-1: Code Understanding								
CPRet	–	19,806	102,259	91,558	4.6	1,464	–	2,641
CLARC	–	6,210	7,228	584,842	94.2	431	–	971
AppsRetrieval	–	3,765	8,765	3,765	1.0	1,670	–	575
CodeFeedbackST	–	31,306	156,526	31,306	1.0	724	–	1,521
CodeSearchNetCCRetrieval	–	52,561	1,005,474	52,561	1.0	388	–	267
COIRCodeSearchNetRetrieval	–	52,561	1,003,765	52,561	1.0	663	–	183
CodeTransOceanContest	–	221	1,008	221	1.0	1,012	–	1,508
CodeTransOceanDL	–	180	816	180	1.0	1,868	–	1,479
CosQA	–	500	20,604	500	1.0	37	–	276
SyntheticText2SQL	–	5,851	105,851	5,851	1.0	83	–	127
LEVEL-1 Total	**–**	**172,961**	**2,412,296**	**823,345**	**4.8**	**676**	**–**	**412**
LEVEL-2: Issue-to-Edit Localization								
SWE-bench Verified	12	432	398,397	1,173	2.72	1,685.9	772.5	1,339.8
SWE-bench Pro	10	632	586,719	8,088	12.80	1,292.9	528.2	1,316.1
SWE-bench Live	209	1,623	1,229,695	14,028	8.64	2,237.3	811.1	1,388.3
SWE-bench++	319	442	5,365,829	6,197	14.02	1,564.8	756.1	830.5
SWE-bench+	6	207	57,320	1,483	7.16	2,027.4	849.8	1,576.9
Multi-SWE-bench	35	1,449	858,042	20,384	14.07	724.6	418.2	1,406.2
SWE-bench Multilingual	41	276	881,118	1,359	4.92	1,991.5	884.9	745.1
LEVEL-2 Total	**632**	**5,061**	**9,377,120**	**52,712**	**10.42**	**1,558.5**	**660.8**	**1,004.9**
LEVEL-3: Broader Context Retrieval								
SWE-bench Verified	12	302	372,258	8,928	29.56	1,562.7	799.1	1,319.4
SWE-bench Pro	10	585	509,200	14,987	25.62	1,292.1	614.1	1,319.8
Multi-SWE-bench	35	1,445	857,861	77,293	53.49	724.3	416.7	1,406.2
SWE-bench Multilingual	40	248	870,262	5,271	21.25	2,006.4	845.6	740.1
LEVEL-3 Total	**97**	**2,580**	**2,609,581**	**106,479**	**41.27**	**1,074.4**	**547.4**	**1,154.8**

Table 9: Training data scale.

Metric	Value
# Repos	628
# Queries	53,301
# Qrels	1,218,875
# Corpus	29,171,451
Avg. query length	375.1
Avg. corpus length	2,188.4
Qrels / Query	22.87

while the average corpus chunk length is 2,188.4 characters, giving the model relatively concise PR descriptions paired with substantially longer repository-local code contexts.

We fine-tune the Qwen3-Embedding family with in-domain supervision derived from LEVEL-2-style PR data. The repositories are disjoint from the SWE-bench family. For each PR, we use the PR description as the query and patch-aligned chunks as positives. For each query, 64 non-positive chunks are sampled from the same repository to form a repository-local negative pool. During training, examples are drawn with a 1:8 positive-to-negative ratio, so the model must separate true edit targets from plausible distractors in the same codebase. All in-domain SFT rows in the experiments report checkpoints after three supervised fine-tuning epochs.

For each query q with positive chunks $\mathcal{P}$ and repository-local negatives $\mathcal{N}$, we optimize a multi-positive InfoNCE loss:

$$\mathcal{L}(q) = -\log \frac{\sum_{d \in \mathcal{P}} \exp(s_\theta(q, d)/\tau)}{\sum_{d \in \mathcal{P} \cup \mathcal{N}} \exp(s_\theta(q, d)/\tau)}. \quad (1)$$

where $s_\theta(q, d)$ is the query–document embedding similarity and τ is the temperature.

C Details of All Baselines

Table 3 intentionally includes both general embedding models and code-oriented retrieval models.

General-purpose models are used to test whether broad semantic representations transfer to agentic code retrieval, whereas code-specific models are used to test whether supervision from code search, code understanding, or issue localization better matches the task structure of CORE-Bench. When a table row is a fine-tuned variant, the citation points to the public base model family; the fine-tuning itself is the in-domain adaptation described in Appendix B. All in-domain SFT rows use checkpoints after three supervised fine-tuning epochs.

Lexical baseline.
- **BM25** (Robertson and Zaragoza, 2009) is a sparse lexical retrieval baseline based on exact term matching, inverse document frequency, and document-length normalization.

General embedding models.
- **multilingual-e5-small/base/large** (Wang et al., 2024b) are encoder-only multilingual-E5 checkpoints trained as general text embedding models over multilingual contrastive data.
- **bge-large-en-v1.5** (Xiao et al., 2024) is a model from the BGE embedding family.
- **bge-m3** (Chen et al., 2024) extends BGE toward multilingual, multifunctional, and multigranularity retrieval. It is still a general embedding model, but its long-input and hybrid-retrieval design makes it relevant for large code-context evaluation.
- **gte-multilingual-base** (Zhang et al., 2024) is an encoder-only multilingual GTE model with long-context support and dense/sparse representation capability.
- **jina-emb-v5-small** (Akram et al., 2026) refers to `jina-embeddings-v5-text-small`, a compact task-targeted text embedding model distilled for efficient general-purpose retrieval.
- **gte-Qwen2-1.5B-instruct** (Li et al., 2023) is an LLM-based GTE model built on Qwen2-1.5B and instruction-tuned for retrieval.
- **F2LLM-v2-1.7B/4B/8B** (Zhang et al., 2026) are general-purpose multilingual embedding LLMs from the F2LLM-v2 family.
- **e5-mistral-7b-instruct** (Wang et al., 2024a) fine-tunes a Mistral-7B backbone for text embedding with synthetic and labeled retrieval data. It is a strong general-purpose LLM-based embedding baseline.
- **pplx-embed-v1-4b** (Eslami et al., 2026) is a Per-

plexity embedding model trained for web-scale multilingual retrieval on a diffusion-pretrained backbone.
- **Qwen3-Embedding-0.6B/4B/8B** (Zhang et al., 2025) are public Qwen3-Embedding models. They provide a controlled general-embedding family for testing how model scale affects zero-shot transfer to agentic code retrieval before any in-domain adaptation.

Code-oriented models.
- **CodeRankEmbed** (Suresh et al., 2025) is a 137M bi-encoder trained for code retrieval using contrastive data from CoRNStack. It is a compact code-specialized baseline for aligning natural-language queries with code.
- **jina-code-emb-0.5b/1.5b** (Kryvosheieva et al., 2025) are Jina Code Embeddings checkpoints built from Qwen2.5-Coder backbones. They support multiple code retrieval directions, including natural-language-to-code and code-to-code.
- **C2LLM-7B** (Qin et al., 2025) is a code contrastive LLM for code retrieval with adaptive cross-attention pooling.
- **SweRankEmbed-Large** (Reddy et al., 2025) is a 7B issue-localization retriever trained to map GitHub issues and code snippets into a shared retrieval space.
- **Qwen3-Embedding-0.6B/4B/8B-ft** (Zhang et al., 2025) are our in-domain fine-tuned Qwen3 Embedding variants. They keep the base model family fixed while adapting different model scales to CORE-Bench-style request-to-code retrieval data under the same benchmark protocol.

D   Evaluation Metrics

CORE-Bench reports NDCG@10 and Recall@100 for retrieval evaluation. Unless otherwise specified, result tables report each cell as NDCG@10/Recall@100.

NDCG@10. NDCG@10 measures whether highly relevant chunks appear near the top of the retrieved list. For a query q, let rel_i be the relevance score of the chunk ranked at position i. We compute

$$\mathrm{DCG}@10(q) = \sum_{i=1}^{10} \frac{2^{rel_i} - 1}{\log_2(i+1)}.$$

$$\text{NDCG@10}(q) = \frac{\text{DCG@10}(q)}{\text{IDCG@10}(q)}.$$

This metric is especially important for LEVEL-2, where the retriever should place edit-bearing chunks among the first results an agent is likely to inspect.

Recall@100. Recall@100 measures coverage of the relevant context. Let R_q be the set of positive-relevance chunks for query q, and let $T_{100}(q)$ be the top-100 retrieved chunks. We compute

$$\text{Recall@100}(q) = \frac{|R_q \cap T_{100}(q)|}{|R_q|}.$$

This metric is especially important for LEVEL-3, where useful information may be spread across edit locations, helper code, tests, configuration, and documentation.

E LEVEL-3 Annotation Pipeline

Algorithm 1 summarizes the automated annotation procedure used to construct LEVEL-3. The pipeline is designed to recover context that helps an agent understand and localize a requested change, rather than only the chunks eventually edited by a patch. The allowlist rerun is therefore used as a functional validation signal, while final qrels are still determined by trajectory extraction and relevance judging.

Notation. Here, $\mathcal{I}$ denotes the issue set, $\mathcal{C}_i$ is the chunked repository corpus for issue i, and $\mathcal{Q}_i^{(2)}$ and $\mathcal{Q}_i^{(3)}$ are the LEVEL-2 edit-location qrels and LEVEL-3 broader-context qrels, respectively. The agent is $\mathcal{A}$, the LLM judges are $\mathcal{M}$, and $\mathcal{U}$ is the set of browse commands parsed from trajectories. During annotation, τ_i is an agent trajectory, $\mathcal{B}_i$ is the browsed text extracted from it, $\mathcal{S}_i$ is the aligned candidate chunk set, and $\mathcal{R}_i$ contains chunks accepted by relevance judging. The allowlists $\mathcal{W}_i^{(2)}$ and $\mathcal{W}_i^{(3)}$ are built from LEVEL-2 and LEVEL-3 qrels, and $(v_i^{(2)}, v_i^{(3)})$ record the corresponding validation outcomes.

Algorithm 1 LEVEL-3 annotation pipeline.

Input: $\mathcal{I}, \{\mathcal{C}_i\}, \{\mathcal{Q}_i^{(2)}\}$, agent $\mathcal{A}$, judges $\mathcal{M}$, commands $\mathcal{U} = \{\text{cat}, \text{grep}, \text{head}, \text{sed}\}$, budget B.
Output: $\{\mathcal{Q}_i^{(3)}\}$ and validation rates $\{(v_i^{(2)}, v_i^{(3)})\}$.

1 **for** each issue $i \in \mathcal{I}$ **do**
2      $\mathcal{Q}_i^{(3)} \leftarrow \mathcal{Q}_i^{(2)}; \mathcal{S}_i \leftarrow \varnothing; t \leftarrow 0$
3   **repeat**
4          $(\hat{p}_i, r_i, \tau_i) \leftarrow \text{RUNAGENT}(\mathcal{A}, i)$
5          $\mathcal{B}_i \leftarrow \text{EXTRACTBROWSE}(\tau_i, \mathcal{U})$
6          $\mathcal{S}_i \leftarrow \mathcal{S}_i \cup \text{ALIGNTOCHUNKS}(\mathcal{B}_i, \mathcal{C}_i)$
7          $\mathcal{R}_i \leftarrow \text{VOTEJUDGE}(\mathcal{M}, q_i, \mathcal{S}_i)$
8          $\mathcal{Q}_i^{(3)} \leftarrow \mathcal{Q}_i^{(3)} \cup \{c \in \mathcal{R}_i \mid \text{score}(c) > 0\}$
9          $t \leftarrow t + 1$
10   **until** $r_i = 1$ **or** $\text{NONEWCONTEXT}(\mathcal{Q}_i^{(3)})$ **or** $t = B$
11     $\mathcal{W}_i^{(2)} \leftarrow \text{BUILDALLOWLIST}(\mathcal{Q}_i^{(2)})$;
12     $\mathcal{W}_i^{(3)} \leftarrow \text{BUILDALLOWLIST}(\mathcal{Q}_i^{(3)})$
13     $(v_i^{(2)}, v_i^{(3)}) \leftarrow \text{ALLOWLISTEVAL}(\mathcal{A}, \mathcal{W}_i^{(2)}, \mathcal{W}_i^{(3)})$
14 **end for**
15 **return** $\{\mathcal{Q}_i^{(3)}\}_{i \in \mathcal{I}}$ and aggregate validation statistics over $\{(v_i^{(2)}, v_i^{(3)})\}$.

F Case Studies

The following cases illustrate how CORE-Bench cleans raw SWE-bench-style instances and reshapes them into agentic-code-search queries. We use compact tables to show the source signal, filtering decision, query type, and rewrite effect side by side.

F.1 Level-2 and Level-3 Target Expansion

For overlapping instances, LEVEL-2 focuses on edit-bearing chunks, whereas LEVEL-3 expands the target into surrounding implementation, data-flow, and test context that can help a coding agent reason about the fix. Table 10 shows that this expansion is not a small formatting change: one or two direct edit chunks can become dozens of context chunks once tests, helper paths, resolver state, or migration state need to be retrieved. This is why LEVEL-3 is treated as a broader context-retrieval task rather than only a relaxed version of LEVEL-2.

F.2 Level-3 Annotation Quality

The allowlist evaluation in Section 3.2.3 checks whether the added LEVEL-3 context is useful for completing requested changes, rather than only textually related to the query. Table 11 reports the resolve rate under three settings. The Full Agent column is the original mini-swe-agent run used during annotation, with normal repository access. The LEVEL-2 and LEVEL-3 columns rerun the agent in our allowlist environment, where readable files are restricted to the corresponding qrels.

Across all sources, the LEVEL-3 allowlist consistently solves more instances than the LEVEL-2 allowlist, showing that the additional context labels recover information needed by the agent beyond the final edit locations.

These rates should be read as a relative validation signal. Our allowlist environment restricts file reading and file operations more strongly than the standard mini-swe-agent setting, and these restrictions can also affect the agent's testing step. As a result, the allowlisted resolve rates can be lower than the original full-agent resolve rate even when the annotation contains useful context. The key comparison is therefore between the LEVEL-3 and LEVEL-2 allowlists.

We also do not remove every unresolved trajectory when constructing LEVEL-3. Keeping only resolved runs would bias the dataset toward simpler tasks with fewer edits, because those are the cases agents solve more easily. For harder tasks, the trajectory may still reveal files, tests, helpers, or data-flow paths that are useful for understanding and localizing the fix. After trajectory extraction and LLM relevance judging, we retain such useful snippets as qrels even when the end-to-end agent run does not fully complete the requested change.

F.3 Filtered Raw Queries

Some raw SWE-bench-style requests are unsuitable for retrieval evaluation. We filter queries that leak the answer location or fix, and queries that contain almost no problem description beyond an issue number or boilerplate.

Table 12 summarizes the filtering results for the SWE-bench-derived sources used in CORE-Bench. Overall, 489 of 5,550 raw queries are removed. Most filtered queries leak the answer location or patch recipe, while Multi-SWE-bench contributes most of the meaningless-query cases. SWE-bench Verified has the highest filtering rate, and SWE-bench Pro has the lowest. The examples in Table 13 show typical cases behind these counts.

F.4 Agentic Coding Query Types

Agentic coding queries are not only bug reports. They also include feature requests, refactoring requests, documentation fixes, and open-ended questions where the desired code change must be inferred from user intent. Table 14 gives representative cases. The examples show that even short requests can carry different localization signals: bug reports often name failures or inconsistent behavior, feature requests name the desired API behavior, and documentation or question-style queries require the retriever to infer which implementation or documentation paths are relevant.

F.5 Original Query and Rewrite Contrast

The rewrite variant keeps the same corpus and qrels but converts retained issue or PR text into a natural developer query. Because this split is built after the query-quality filtering stage, rewriting focuses on removing boilerplate and redundant context while preserving concrete failures, API names, and desired changes. Table 15 illustrates the intended tradeoff. Rewriting makes the query closer to what a developer would type into an assistant, but it also compresses context; this is why the rewritten split is reported separately rather than replacing the original raw-query setting.

G Detailed CORE-Bench Results

These tables give the detailed results behind the main comparison. The appendix includes BM25 as the sparse-retrieval baseline, while all embedding-model groups are marked as dense retrieval. Each cell reports NDCG@10/Recall@100. Cell shading follows NDCG@10, while best/second-best marks are computed separately for NDCG@10 and Recall@100. LEVEL-1 abbreviations are: Apps = AppsRetrieval, COIR-CSN = COIRCodeSearchNetRetrieval, CFB-ST = CodeFeedbackST, CSN-CC = CodeSearchNetCCRetrieval, CSN = CodeSearchNetRetrieval, CTO-C = CodeTransOceanContest, CTO-DL = CodeTransOceanDL, and Text2SQL = SyntheticText2SQL.

Table 16 is mainly a calibration point. It shows that strong performance on conventional code-understanding retrieval does not reliably carry over to requirement-conditioned retrieval: some zero-shot and code-specialized models remain competitive on LEVEL-1, while the in-domain SFT models are not uniformly dominant there. Interestingly, after in-domain SFT, the largest LEVEL-1 drops are concentrated in task formats that are superficially close to natural-language-to-code retrieval, suggesting that PR-based supervision shifts the model toward change-target relevance rather than simply strengthening generic code search.

Table 10: Level-2 versus Level-3 target expansion cases.

Instance	Raw Query Signal	Level-2 Target	Level-3 Expansion
django-15499 SWE-bench Verified	Optimize `CreateModel` + `AlterModelManagers` into `CreateModel`; the request asks whether this should mirror the existing `AlterModelOptions` optimization.	**1 qrel**. The direct target is the migration operation-reduction branch that checks model-operation types, model names, and proxy options before returning an empty operation list.	**58 qrels**. The target set expands to the migration-operation graph, duplicate-object validation, model state objects, and helper operations needed to judge whether the optimization is safe.
zstd-983 Multi-SWE-bench	Increase `windowLog` from a `CDict` when source size is known, so dictionary compression can fit both the dictionary and source under a smaller limit.	**1 qrel**. The direct target is the CDict compression entry point that reads applied compression parameters from the reference context.	**79 qrels**. The expanded set covers pledged-source-size handling, compression-level-to-parameter conversion, and CDict internals such as dictionary buffer, content size, and reference context.
grpc-go-3201 Multi-SWE-bench	Do not call `NewServiceConfig` when DNS lookups are disabled; also ignore related resolver-wrapper calls and improve resolver service-config tests.	**2 qrels**. The direct targets are DNS resolver and resolver-wrapper callers that parse and apply service-config updates.	**121 qrels**. The target set expands to the resolver stack, `ClientConn` resolver-state updates, default service-config behavior, and wrapper behavior around disabled lookups.

Table 11: LEVEL-3 annotation validation.

Source	Full	L3	L2
SWE-bench Verified	73.0%	69.0%	62.0%
SWE-bench Multilingual	65.0%	59.0%	43.0%
SWE-bench Pro	46.1%	43.2%	36.9%
Multi-SWE-bench	42.0%	39.5%	23.3%

The central comparison is in Tables 17 and 18. Moving to repository-local development requests changes the ranking more than it simply lowers the scores. In-domain SFT becomes the most stable signal on both LEVEL-2 and LEVEL-3, whereas rewriting the query is not a guaranteed simplification; for several models, compression removes useful request-specific clues.

The remaining breakdowns show where this pattern is more fragile. Tables 19 and 20 indicate that the gains are broad but not uniform across languages. Table 21 shows that underspecified question and documentation queries remain difficult, and Table 22 shows that dense or large repositories are where Recall@100 is most easily lost.

H Prompt Templates

The following boxes show the prompt templates used by the data construction pipeline. For compactness, each box merges the system message and user-message template. Variables in angle brackets are filled by the pipeline. Table 23 gives the rewrite prompt used to turn retained PR or issue text into developer-style queries while keeping failure messages and technical clues faithful to the original request. Table 24 shows the separate filtering prompt, which removes answer-leaking, underspecified, or nearly empty queries before benchmark construction. Table 25 lists the relevance-judging prompt used to turn trajectory-derived candidate chunks into LEVEL-3 labels.

I Usage of AI Assistant

For manuscript preparation, we used LLM-based assistance for language polishing and grammar refinement.

Table 12: Filtered-query statistics for SWE-bench-derived sources.

Source	Raw	Kept	Filtered	Leak	Meaningless	Rate
Multi-SWE-bench	1,615	1,449	166	61	105	10.3%
SWE-bench++	475	442	33	32	1	6.9%
SWE-bench Live	1,784	1,623	161	160	1	9.0%
SWE-bench+	223	207	16	15	1	7.2%
SWE-bench Multilingual	300	276	24	23	1	8.0%
SWE-bench Pro	653	632	21	21	0	3.2%
SWE-bench Verified	500	432	68	68	0	13.6%
Total	**5,550**	**5,061**	**489**	**380**	**109**	**8.8%**

Table 13: Raw queries filtered before benchmark construction.

Query	Verdict	Why Filtered	Raw Signal
django-11179 SWE-bench Verified	Answer leak	The raw request names the exact module and line range, then states the required update. Retrieval would be nearly solved before the model reads the repository.	"delete() on instances of models without dependencies does not clear PKs" followed by an explicit pointer to the deletion module, lines 276–281, and the exact line to update.
textual-5795 SWE-bench Live	Answer leak	The raw request gives both the root cause and the patch recipe rather than only describing the observed failure.	Options added after mount are not displayed because the OptionList line-update routine exits early when the scroll region has zero height; the query states the fix is to refresh layout first.
cli-2251 Multi-SWE-bench	Meaningless	The query contains only an issue reference and gives no observable behavior, expected behavior, error message, API name, or implementation clue.	"Fix issue #2216. This fixes #2216."
svelte-13151 Multi-SWE-bench	Meaningless	The only task signal is a short PR title. Most of the body is submission checklist text and branch guidance, which adds noise but not localization signal.	"fix: visit expression for svelte:component references" plus Svelte 5 rewrite boilerplate, close-reference text, and checkbox instructions for PR submission.

Table 14: Agentic coding query type examples.

Type	Instance	Query Signal
Bug report	gson-1093	The Number overload of JsonWriter can write pseudo-numeric values such as NaN and Infinity in lenient mode, but the double overload rejects them, making semi-numeric double output impossible without boxing.
Feature request	fmt-3729	Support both generic and native formatting for filesystem paths, so callers can control slash direction in cross-platform output.
Refactoring	sqlfluff-3904	Standardize the underscored progress-bar option, the only command-line option using underscores instead of dashes; the request asks whether to rename, defer, or accept both forms.
Question	Pillow-9083	Ask whether Pillow can delete only GPS EXIF data rather than all EXIF data; the docs explain deleting from IFD0 but not from GPS IFDs.
Documentation	pylint-10045	The -colorized option for pyreverse is missing from 3.2.0-dev0 documentation even though downstream tools have started integrating it.

Table 15: Original raw queries and rewritten developer queries.

Instance	Original Query Signal	Rewritten Query	Rewrite Effect
streamlink-5926 bug report	A 1,904-character raw report contains checklist boilerplate, contribution-guideline confirmations, sample Kuwaiti channel URLs, and a debug log ending with "No plugin can handle URL".	"I'm trying to stream Kuwaiti channels with Streamlink, but it fails with a 'No plugin can handle URL' error for the media.gov.kw LiveTV page. I also tried the Drama channel URL. How do I fix this?"	Reduces checklist and debug boilerplate while preserving the concrete failure, affected site URL, and developer-facing repair request.
fmt-3729 feature request	The original describes generic versus native formatting for filesystem paths, including Windows-style examples and generic-path output.	"Add support for generic and native format specifiers for filesystem paths to allow cross-platform control over slash direction in output."	Converts a verbose feature discussion into a concise search-style request while keeping the target API and desired behavior.
camunda-27226 refactoring	The original asks to change the state field from string to enum in ProcessInstance and ProcessInstanceFilter, aligned with OpenAPI values ACTIVE, COMPLETED, and CANCELED.	"I'm working with the Camunda Java client and noticed the state field in ProcessInstance and ProcessInstanceFilter is currently just a string. The OpenAPI spec defines it as an enum. How do I update the client code to use an enum type instead?"	Preserves class names, field name, and enum motivation while turning a specification note into a developer question.

Table 16: CORE-Bench LEVEL-1 results.

Model	Apps	CLARC	COIR-CSN	CPRet	CFB-ST	CSN-CC	CSN	CTO-C	CTO-DL	CosQA	Text2SQL	Avg.
Sparse Retrieval												
BM25	4.8/14.8	9.5/49.6	40.9/66.1	18.6/31.0	68.1/89.5	54.0/80.4	60.0/90.3	47.8/84.2	34.4/**100.0**	18.8/63.8	24.9/67.6	34.7/67.0
Small Dense Retrieval Models (<1B)												
CodeRankEmbed	13.5/40.1	25.6/59.9	73.0/90.8	16.8/28.8	65.4/91.5	64.9/88.8	83.8/96.5	51.9/81.9	34.6/**100.0**	30.6/86.6	61.7/99.2	47.4/78.6
mE5-small	12.7/39.5	15.0/54.8	56.4/81.1	19.7/30.0	66.1/93.1	53.0/80.7	71.6/94.5	55.7/86.0	31.5/97.8	22.8/74.4	42.4/93.5	40.6/75.0
mE5-base	5.9/19.7	9.7/45.9	37.4/64.4	12.3/20.9	36.8/67.2	26.8/52.4	60.6/89.7	15.3/44.8	30.8/97.8	12.7/62.0	21.2/54.1	24.5/56.3
mE5-large	19.6/50.8	15.8/52.5	61.7/84.2	24.2/36.6	67.5/94.0	49.2/77.7	78.3/96.0	56.6/88.7	34.8/**100.0**	22.8/78.8	48.9/94.3	43.6/77.6
bge-large-v1.5	5.0/17.7	14.9/51.5	53.5/81.0	14.3/24.1	64.8/93.6	46.2/75.7	81.2/96.2	45.1/84.2	22.2/88.9	30.3/88.2	38.5/88.5	37.8/71.8
bge-m3	1.6/8.6	8.4/43.8	17.1/29.4	13.2/23.0	30.4/53.1	32.3/57.2	41.1/71.0	28.4/67.4	34.7/**100.0**	10.8/47.8	43.4/90.1	23.8/53.8
gte-multi-base	7.9/27.3	20.9/56.9	75.0/90.3	21.3/33.8	74.3/96.3	45.4/71.8	87.7/97.2	63.0/92.8	35.0/**100.0**	33.0/89.0	39.5/92.3	45.7/77.1
jina-emb-v5-small	46.4/85.6	29.9/72.6	74.8/93.9	40.7/60.1	82.9/98.6	59.1/83.9	88.1/97.2	79.6/96.4	28.2/98.9	38.6/95.4	66.3/_99.9_	57.7/89.3
jina-code-0.5b	81.6/98.8	22.4/67.6	75.5/94.3	57.0/80.8	83.3/99.1	63.1/89.3	87.7/97.4	88.1/_99.1_	36.6/**100.0**	38.4/_97.0_	65.1/99.9	63.5/93.0
Qwen3-0.6B	75.0/98.3	35.2/77.2	82.8/96.5	57.6/81.0	86.4/99.3	86.5/97.9	90.5/97.7	85.7/_99.1_	31.9/98.9	39.2/96.0	64.8/99.7	66.9/94.7
Medium Dense Retrieval Models (1B–2B)												
gte-Qwen2-1.5B	4.9/19.0	22.1/60.6	26.6/51.2	12.5/23.4	45.7/77.4	41.7/71.3	64.9/92.8	65.7/95.0	29.2/**100.0**	8.5/46.4	23.0/55.8	31.3/63.0
jina-code-1.5b	63.6/93.1	18.9/73.0	51.8/76.9	48.8/62.7	79.1/96.4	59.6/86.4	85.6/97.1	70.9/95.5	**40.1**/**100.0**	33.0/94.6	66.2/**100.0**	56.2/88.7
F2LLM-v2-1.7B	71.7/95.3	14.2/57.3	28.9/43.1	41.3/60.1	72.8/93.0	30.6/49.1	38.8/62.9	64.6/87.8	29.9/93.3	15.1/53.6	66.2/98.9	43.1/72.2
Large Dense Retrieval Models (≥4B)												
F2LLM-v2-4B	76.9/94.8	30.4/71.8	80.3/95.4	**80.6**/**94.0**	88.2/99.5	**90.0**/98.2	84.2/96.1	92.2/98.2	32.5/**100.0**	30.9/86.6	**69.3**/**100.0**	68.7/94.0
Qwen3-4B	_89.1_/99.7	**48.1**/**87.4**	86.3/_97.7_	73.1/89.3	89.5/_99.7_	87.0/98.6	_92.1_/98.0	_93.7_/**99.5**	34.9/**100.0**	_39.6_/96.6	66.5/99.9	**72.7**/**96.9**
pplx-embed-4b	84.8/**99.9**	27.2/64.8	74.8/93.7	52.4/72.5	73.6/98.3	84.7/97.3	87.3/96.8	85.1/97.7	36.4/**100.0**	36.1/95.2	67.1/99.8	64.5/92.4
C2LLM-7B	86.0/99.1	43.9/85.1	_88.3_/97.6	_73.6_/_91.8_	**90.1**/**99.7**	**93.7**/**99.2**	91.6/_98.2_	91.6/**99.5**	35.1/98.9	37.3/95.0	65.4/**100.0**	_72.4_/96.7
e5-mistral-7b	26.2/60.0	38.1/78.9	55.8/81.0	41.1/61.7	75.8/97.7	64.4/90.0	84.7/96.9	88.0/97.3	35.1/**100.0**	29.5/87.4	63.0/99.5	54.7/86.4
SweRankEmbed-L	15.8/45.2	25.9/68.5	48.6/72.9	26.0/41.7	77.1/97.1	56.2/84.3	77.7/96.3	74.9/97.3	29.8/**100.0**	23.8/77.0	43.5/90.4	45.4/79.1
F2LLM-v2-8B	76.1/92.8	27.5/75.3	66.9/85.6	72.1/84.8	89.5/99.6	77.1/93.1	67.4/89.9	92.5/98.6	32.0/**100.0**	33.6/91.6	_67.7_/**100.0**	63.8/91.9
Qwen3-8B	**91.0**/_99.8_	_48.0_/_87.2_	**88.5**/**98.2**	73.2/89.9	_89.9_/99.7	72.9/95.5	**92.4**/**98.3**	**94.1**/**99.5**	33.2/**100.0**	**39.8**/**97.6**	65.8/_99.9_	71.7/_96.9_
In-domain SFT Dense Retrieval Models (0.6B–8B)												
Qwen3-0.6B-SFT	65.8/96.0	27.6/65.7	63.4/88.2	54.0/77.2	79.5/98.4	62.6/89.9	83.2/97.4	82.7/98.6	33.3/98.9	30.5/85.6	56.8/97.9	58.1/90.3
Qwen3-4B-SFT	82.2/99.1	30.4/69.9	61.0/87.2	63.7/82.8	81.3/98.9	65.5/91.9	82.0/97.6	85.6/98.2	31.1/98.9	22.5/73.4	52.2/97.8	59.8/90.5
Qwen3-8B-SFT	82.9/99.4	35.6/75.7	68.2/91.1	66.6/84.9	83.6/99.3	69.9/93.8	85.1/97.6	89.5/98.6	31.1/_99.4_	24.4/79.4	55.6/98.6	63.0/92.5

Table 17: CORE-Bench LEVEL-2 and LEVEL-3 results. Abbrev.: Pro/Verf/Live/++/+/Multi/Mling = Pro/Verified/Live/++/+/Multi-SWE/Multilingual.

Model	LEVEL-2								LEVEL-3				
	Pro	Verf	Live	++	+	Multi	Mling	Avg.	Pro	Verf	Multi	Mling	Avg.
Sparse Retrieval													
BM25	19.5/38.0	11.9/46.7	14.8/44.4	12.6/32.2	15.0/48.4	12.3/37.0	5.0/24.8	13.0/38.8	29.3/36.1	22.2/33.9	19.7/28.1	10.9/22.2	20.5/30.1
Small Dense Retrieval Models (<1B)													
CodeRankEmbed	16.9/34.4	12.0/37.7	12.2/37.9	11.6/29.5	11.3/33.9	14.7/38.1	5.7/18.7	12.1/32.9	27.0/32.8	20.6/30.6	28.3/30.6	14.2/20.3	22.5/28.6
mE5-small	21.2/41.1	7.7/43.4	11.0/39.6	11.7/31.5	9.8/38.3	12.4/33.6	4.6/18.6	11.2/35.2	30.3/38.4	17.6/31.0	23.9/29.3	9.1/19.0	20.2/29.4
mE5-base	6.0/14.8	1.9/11.7	5.2/25.2	4.7/17.7	4.1/19.0	2.9/13.2	2.2/8.8	3.9/15.8	8.8/13.9	8.1/15.6	7.9/13.1	3.2/9.3	7.0/13.0
mE5-large	17.0/35.8	9.0/45.5	11.0/39.2	11.1/29.8	10.1/38.6	10.5/34.5	3.6/21.6	10.3/35.0	24.2/32.2	21.3/26.8	20.4/26.8	10.7/20.0	19.2/26.5
bge-large-v1.5	19.1/35.1	11.9/47.1	13.9/45.7	14.0/33.1	16.7/44.0	11.9/41.0	4.6/24.2	13.1/38.6	26.4/33.1	25.0/34.6	24.5/30.5	10.8/21.5	21.7/29.9
bge-m3	6.3/15.1	2.5/18.0	4.5/22.8	5.0/18.9	6.5/28.2	5.1/14.6	2.4/10.5	4.6/18.3	8.9/12.9	7.2/11.8	13.1/14.9	5.5/10.2	8.7/12.5
gte-multi-base	15.2/30.2	9.4/34.4	13.7/44.6	12.6/31.5	16.8/38.1	12.9/37.1	5.0/24.1	12.2/34.3	22.5/29.0	22.2/25.4	23.9/28.8	12.9/23.0	20.4/26.6
jina-emb-v5-small	28.8/52.1	19.0/53.4	18.2/51.8	18.2/40.7	19.1/48.4	18.7/47.4	11.4/33.5	19.1/46.7	42.1/50.3	34.0/39.3	33.8/39.7	22.0/34.3	33.0/41.1
jina-code-0.5b	29.8/51.7	17.9/63.7	20.7/56.3	19.8/43.9	22.6/52.0	22.0/54.1	12.8/41.6	20.8/51.9	42.0/50.2	37.6/48.6	41.0/42.9	26.1/40.2	36.7/45.5
Qwen3-0.6B	24.0/48.9	15.7/57.2	17.2/50.4	15.9/37.4	22.9/49.4	16.3/48.2	7.1/27.2	17.0/45.5	37.3/46.7	37.2/45.4	35.5/38.3	20.2/30.2	32.6/40.2
Medium Dense Retrieval Models (1B–2B)													
gte-Qwen2-1.5B	6.4/19.6	0.7/13.9	3.4/17.8	4.8/18.7	2.3/10.1	4.3/21.0	2.5/10.3	3.5/15.9	10.0/18.3	8.2/12.9	8.3/17.5	5.9/10.8	8.1/14.9
jina-code-1.5b	25.5/50.4	11.0/55.4	17.8/55.7	17.0/41.0	20.5/52.9	17.1/47.1	10.0/37.0	17.0/48.5	39.0/49.0	32.3/45.6	34.1/40.4	21.2/35.7	31.6/42.7
F2LLM-v2-1.7B	4.5/11.9	8.6/28.5	7.3/32.1	6.5/20.4	7.3/25.1	5.4/18.8	1.4/8.3	5.8/20.7	7.1/11.0	8.0/17.1	12.2/15.5	1.8/6.4	7.3/12.5
Large Dense Retrieval Models (≥4B)													
F2LLM-v2-4B	27.1/50.4	20.5/57.4	19.7/56.9	17.3/38.7	21.0/56.1	21.6/49.6	10.9/40.0	19.7/49.9	40.3/47.8	37.6/43.3	39.3/38.9	24.2/36.2	35.3/41.6
Qwen3-4B	24.7/49.8	22.3/59.1	18.2/51.1	17.2/38.4	21.7/52.9	16.9/46.3	7.3/30.8	18.3/46.9	36.5/48.2	40.9/47.0	36.2/38.9	17.5/29.1	32.8/40.8
pplx-embed-4b	19.4/39.3	10.7/45.4	13.4/41.5	12.0/31.9	16.0/42.8	13.1/35.2	5.4/22.1	12.9/36.9	30.1/38.4	30.4/37.6	27.5/30.3	12.3/21.8	25.0/32.1
C2LLM-7B	25.9/51.2	13.0/52.9	17.4/48.8	18.1/39.6	15.5/44.1	17.7/45.4	9.2/32.2	16.7/44.9	40.7/50.1	31.3/40.1	38.5/38.5	21.3/35.3	32.9/41.0
e5-mistral-7b	24.9/50.7	16.1/61.9	19.9/54.3	18.2/43.9	21.2/56.8	17.9/51.6	10.1/42.6	18.3/51.7	37.8/48.6	39.1/48.0	33.7/40.6	24.9/40.6	33.9/44.4
SweRankEmbed-L	31.3/52.9	25.1/66.1	25.0/57.6	19.5/42.6	24.5/57.5	20.0/47.8	11.2/40.2	22.4/52.1	44.3/50.9	37.0/46.9	35.9/37.4	20.4/34.3	34.4/42.4
F2LLM-v2-8B	21.6/37.9	24.7/57.5	18.9/53.3	17.0/37.0	24.8/55.7	15.6/42.4	10.6/36.9	19.0/45.8	34.2/38.1	42.4/46.2	33.1/32.2	25.5/32.3	33.8/37.2
Qwen3-8B	23.5/44.7	21.4/59.2	19.8/51.4	18.6/40.0	27.6/52.7	20.2/49.6	11.1/38.3	20.3/48.0	34.0/43.0	42.6/48.1	37.6/39.5	23.6/35.5	34.4/41.5
In-domain SFT Dense Retrieval Models (0.6B–8B)													
Qwen3-0.6B-SFT	36.7/61.2	25.0/68.9	25.7/62.8	23.7/49.2	29.2/60.0	28.5/63.7	16.6/50.1	26.5/59.4	52.6/59.3	44.3/57.7	46.9/51.6	34.3/49.0	44.5/54.4
Qwen3-4B-SFT	37.9/**65.2**	31.1/**79.5**	28.3/66.3	27.7/56.2	32.7/65.0	30.5/65.7	**24.0**/64.1	30.3/66.0	54.8/64.8	49.6/**66.2**	51.6/54.2	41.0/61.0	49.2/**61.6**
Qwen3-8B-SFT	**39.3**/64.9	**33.9**/76.1	**33.1/68.0**	**29.6/57.1**	**36.0/66.0**	**34.0/67.5**	23.7/**65.2**	**32.8/66.4**	**56.2/64.9**	**51.1**/63.3	**52.1/55.3**	**41.5/62.0**	**50.2**/61.4

Table 18: CORE-Bench rewritten-query results. Abbrev.: Pro/Verf/Live/++/+/Multi/Mling = Pro/Verified/Live/++/+/Multi-SWE/Multilingual.

Model	LEVEL-2-Rw								LEVEL-3-Rw				
	Pro	*Verf*	*Live*	*++*	*+*	*Multi*	*Mling*	*Avg.*	*Pro*	*Verf*	*Multi*	*Mling*	*Avg.*
Sparse Retrieval													
BM25	18.2/35.9	13.6/47.9	18.0/47.6	14.0/33.9	17.3/50.8	12.0/39.7	3.3/19.3	13.8/39.3	26.3/34.7	23.6/33.6	22.0/28.3	7.2/18.0	19.8/28.7
Small Dense Retrieval Models (<1B)													
CodeRankEmbed	20.4/40.3	13.7/50.0	14.2/42.2	12.4/32.3	15.6/38.9	15.9/41.5	4.0/20.2	13.8/37.9	30.7/37.5	30.1/36.5	33.2/32.9	11.0/18.5	26.2/31.4
mE5-small	18.8/38.2	10.0/42.9	12.2/40.1	11.5/32.0	11.7/39.8	13.3/40.2	2.6/15.1	11.4/35.5	28.5/36.6	19.5/32.1	25.6/31.2	6.0/14.1	19.9/28.5
mE5-base	3.5/11.3	1.4/12.9	4.7/25.6	4.1/17.4	2.9/18.9	1.6/10.3	0.2/3.1	2.6/14.2	6.3/12.4	7.3/14.0	5.9/12.2	1.3/4.3	5.2/10.7
mE5-large	14.8/33.0	11.3/46.0	9.7/38.6	10.3/29.9	10.5/39.4	13.2/37.4	1.7/13.7	10.2/34.0	22.4/30.5	21.5/28.8	22.1/28.1	5.9/13.5	18.0/25.2
bge-large-v1.5	18.7/35.4	10.0/44.7	14.2/45.8	12.3/31.5	13.8/40.3	13.0/43.0	1.9/15.2	12.0/36.6	26.1/33.1	20.1/32.2	28.1/31.3	5.3/12.8	19.9/27.4
bge-m3	4.8/11.1	2.9/17.6	3.9/18.9	4.4/15.5	5.2/20.8	5.0/14.9	1.0/8.0	3.9/15.3	7.6/10.6	9.6/14.0	10.9/14.3	3.1/6.7	7.8/11.4
gte-multi-base	18.2/32.8	10.9/41.2	16.6/48.6	13.8/33.1	16.7/38.9	14.7/40.4	3.7/26.1	13.5/37.3	27.1/32.2	29.1/30.7	28.4/30.9	9.3/21.4	23.5/28.8
jina-emb-v5-small	28.3/50.8	12.5/57.8	17.9/51.6	17.0/39.6	16.9/47.5	20.4/51.1	6.3/25.7	16.7/46.3	39.3/49.5	35.7/42.4	38.2/41.8	11.1/23.7	31.1/39.3
jina-code-0.5b	30.4/52.5	11.8/55.9	18.7/52.6	19.6/43.5	18.1/46.7	21.1/54.1	7.1/27.0	18.1/47.5	43.2/51.9	35.1/44.0	39.5/44.0	13.8/29.0	32.9/42.2
Qwen3-0.6B	25.0/49.0	14.4/61.8	17.7/52.4	16.3/38.3	21.2/48.0	17.5/49.3	3.5/19.3	16.5/45.5	38.5/47.0	36.7/46.3	37.0/40.6	12.4/23.1	31.1/39.2
Medium Dense Retrieval Models (1B–2B)													
gte-Qwen2-1.5B	7.7/21.4	0.4/14.5	3.6/19.5	6.2/22.3	2.4/13.6	9.2/26.8	0.8/9.2	4.3/18.2	11.4/20.1	6.6/13.2	16.8/21.9	3.3/7.7	9.5/15.7
jina-code-1.5b	24.4/50.6	9.1/52.9	15.7/53.4	16.2/41.2	17.6/49.2	17.4/51.2	3.5/26.6	14.9/46.4	38.5/48.9	31.3/43.3	36.2/41.4	9.6/23.1	28.9/39.2
F2LLM-v2-1.7B	5.7/14.9	6.7/23.7	7.3/32.9	6.2/20.6	6.4/23.4	5.7/18.9	0.6/3.9	5.5/19.8	10.1/14.1	8.5/14.6	11.2/14.5	0.7/2.0	7.6/11.3
Large Dense Retrieval Models (≥4B)													
F2LLM-v2-4B	26.0/50.0	19.9/58.0	18.7/56.4	17.0/38.8	19.0/52.7	21.7/50.2	5.4/25.3	18.3/47.4	39.5/47.6	37.6/43.5	39.0/37.9	13.2/25.2	32.3/38.6
Qwen3-4B	24.0/48.2	19.9/59.4	17.9/52.6	16.7/40.3	18.9/52.3	19.2/48.1	4.2/22.5	17.3/46.2	36.1/47.4	39.7/47.4	38.6/40.7	10.1/22.0	31.1/39.3
pplx-embed-4b	19.5/39.7	8.7/48.6	12.5/41.6	11.3/32.5	14.1/43.2	12.0/33.8	2.1/16.4	11.5/36.5	30.0/38.2	28.1/36.5	25.9/28.3	6.8/15.8	22.7/29.7
C2LLM-7B	25.0/48.7	11.7/50.4	15.2/48.3	17.1/38.6	14.2/40.7	14.1/39.6	4.2/23.4	14.5/41.4	36.7/47.7	30.7/40.4	34.3/36.9	11.9/26.0	28.4/37.8
e5-mistral-7b	24.8/50.8	15.3/61.2	19.3/53.6	17.7/43.7	20.7/53.4	20.0/52.8	3.9/33.6	17.4/49.9	38.3/49.3	39.1/46.2	38.1/42.9	11.6/29.3	31.8/42.0
SweRankEmbed-L	29.9/51.2	25.6/65.2	23.4/57.0	20.3/41.8	26.1/52.2	21.0/50.3	5.8/30.2	21.7/49.7	43.8/50.3	41.9/51.8	36.3/38.7	12.5/25.4	33.6/41.5
F2LLM-v2-8B	20.5/37.0	24.6/53.0	18.6/53.6	16.6/36.9	22.2/54.7	15.7/43.3	6.1/24.8	17.8/43.3	33.6/37.3	40.8/47.1	33.6/33.0	15.3/22.2	30.8/34.9
Qwen3-8B	23.8/45.0	16.0/57.9	17.7/50.0	16.1/39.5	22.2/49.4	19.3/49.6	5.1/24.2	17.2/45.1	33.8/42.1	39.1/49.3	37.7/39.6	12.8/22.4	30.8/38.4
In-domain SFT Dense Retrieval Models (0.6B–8B)													
Qwen3-0.6B-SFT	35.6/59.1	28.0/73.4	25.0/60.9	23.0/49.6	28.0/61.0	30.2/63.4	8.6/43.0	25.5/58.6	51.2/58.3	43.2/60.5	47.0/50.1	19.5/39.2	40.2/52.0
Qwen3-4B-SFT	37.0/**63.8**	30.0/**78.8**	27.9/66.5	25.8/56.5	28.2/65.2	29.3/64.9	12.7/54.1	27.3/**64.3**	54.3/63.9	48.5/**66.1**	**50.9**/53.7	22.4/48.5	44.1/**58.1**
Qwen3-8B-SFT	**39.6**/63.8	**30.4**/75.2	**31.3**/**66.8**	**27.8**/**56.7**	**31.1**/65.4	**31.0**/65.8	**13.4**/54.7	**29.2**/64.0	**56.1**/64.3	**48.6**/62.7	50.8/53.5	22.2/**49.3**	**44.4**/57.4

Table 19: LEVEL-2 per-language results.

	Python	Go	JS	Rust	TS	Java	C++	C	Ruby	PHP	Swift
LEVEL-2											
Model											
Sparse Retrieval											
BM25	15.3/41.2	16.0/38.2	8.7/32.4	11.5/36.3	7.4/24.3	8.1/20.6	9.7/22.5	11.9/24.3	6.4/23.8	5.8/17.3	0.0/0.0
Small Dense Retrieval Models (<1B)											
CodeRankEmbed	10.7/32.0	15.3/37.6	8.8/27.2	12.5/35.9	10.2/28.4	8.7/22.8	14.1/28.0	12.4/32.2	5.4/14.0	6.4/14.1	0.0/0.0
mE5-small	11.6/36.3	14.1/33.6	9.4/31.7	10.5/31.4	9.3/23.8	7.4/19.6	11.7/26.0	7.4/21.8	5.5/14.9	7.1/21.6	0.0/0.0
mE5-base	4.2/18.2	3.4/9.8	2.9/14.9	3.5/12.7	2.9/9.6	3.0/9.0	3.6/7.1	1.3/7.1	0.6/4.4	2.3/6.0	0.0/0.0
mE5-large	11.3/36.5	12.1/30.8	8.9/33.2	8.7/26.7	9.4/27.2	7.8/18.2	9.1/18.8	6.1/21.5	4.6/18.1	5.4/19.1	0.0/0.0
bge-large-v1.5	15.5/42.1	11.5/26.7	12.0/39.5	10.2/33.1	9.1/28.7	9.1/21.6	13.5/28.6	9.8/31.2	4.4/17.0	3.6/19.6	0.0/**100.0**
bge-m3	5.1/19.1	4.5/13.9	4.0/17.7	4.7/13.3	2.2/7.8	3.0/8.1	3.8/11.2	3.0/11.9	2.6/5.7	2.1/11.4	0.0/0.0
gte-multi-base	13.9/37.9	10.8/25.7	9.1/29.1	11.6/36.0	13.3/35.2	10.2/26.1	12.5/29.7	7.8/25.3	5.2/17.0	6.5/22.9	0.0/0.0
jina-emb-v5-small	18.5/49.1	24.5/51.3	16.0/45.8	17.8/45.0	15.3/45.5	11.6/28.7	17.9/34.3	10.8/33.7	7.1/29.0	12.8/24.0	85.0/**100.0**
jina-code-0.5b	22.0/54.2	26.0/54.4	21.1/54.1	22.2/50.3	24.3/55.0	14.7/35.7	20.9/41.1	13.2/35.9	10.2/39.1	11.4/34.7	21.8/50.0
Qwen3-0.6B	18.4/49.3	16.5/43.7	18.1/50.0	14.3/37.7	17.0/50.7	10.2/27.2	17.7/33.8	11.8/34.7	8.0/24.9	4.5/15.8	17.7/**100.0**
Medium Dense Retrieval Models (1B–2B)											
gte-Qwen2-1.5B	2.0/10.8	4.0/15.2	3.5/17.0	4.1/17.3	3.3/12.2	3.1/11.9	1.8/10.5	2.1/14.4	0.0/3.7	0.9/3.1	0.0/0.0
jina-code-1.5b	18.3/53.0	23.1/53.4	14.1/46.1	18.2/45.5	15.9/47.0	14.6/30.5	16.2/31.3	10.5/30.7	12.2/38.6	9.6/30.5	0.0/0.0
F2LLM-v2-1.7B	6.3/24.6	3.1/8.6	3.7/14.1	3.3/14.0	2.2/7.7	4.9/13.2	3.6/10.6	2.2/9.7	0.0/3.3	0.5/4.7	0.0/0.0
Large Dense Retrieval Models (≥4B)											
F2LLM-v2-4B	20.9/52.2	21.5/50.1	23.4/54.3	20.0/45.1	22.7/50.1	12.6/32.6	17.8/36.3	11.9/35.8	8.7/44.3	7.5/23.8	17.7/**100.0**
Qwen3-4B	19.3/49.8	15.1/42.4	16.0/49.4	15.6/42.5	19.3/49.0	10.0/25.2	18.4/37.5	12.5/37.0	4.2/20.6	4.4/14.1	0.0/**100.0**
pplx-embed-4b	14.2/40.6	16.3/37.2	11.7/36.8	13.0/35.3	12.2/34.3	8.2/19.2	12.5/27.7	7.4/23.5	3.2/12.9	1.7/14.9	0.0/50.0
C2LLM-7B	16.6/45.8	24.1/52.4	20.1/50.7	19.4/41.8	19.1/48.2	12.1/28.4	17.3/36.0	10.3/33.7	11.3/38.3	2.2/23.8	38.9/**100.0**
e5-mistral-7b	20.1/54.0	25.5/53.5	15.2/47.5	16.3/44.0	19.0/53.5	11.3/31.7	16.2/39.8	14.5/40.1	9.6/44.2	6.6/38.4	0.0/**100.0**
SweRankEmbed-L	25.9/54.8	26.8/51.0	21.2/49.9	18.0/47.4	25.0/52.6	10.6/27.0	17.9/39.6	8.7/30.5	9.2/28.5	18.7/38.8	0.0/**100.0**
F2LLM-v2-8B	20.5/50.4	17.1/35.7	14.7/37.3	19.0/41.4	17.6/35.9	13.2/34.2	16.4/37.1	13.4/36.9	10.6/21.1	10.6/39.5	38.7/50.0
Qwen3-8B	21.9/50.9	14.6/42.6	18.6/48.8	22.1/52.2	22.6/48.7	12.5/26.9	21.0/43.0	17.0/40.3	13.4/40.3	4.2/24.5	45.6/**100.0**
In-domain SFT Dense Retrieval Models (0.6B–8B)											
Qwen3-0.6B-SFT	27.5/61.3	33.3/62.2	31.8/67.8	28.1/56.6	32.3/66.6	17.6/41.3	25.4/47.6	19.0/44.7	12.2/47.3	15.5/50.2	48.2/**100.0**
Qwen3-4B-SFT	30.6/**67.8**	36.3/67.4	36.6/**75.2**	33.4/64.1	36.0/**72.9**	19.7/46.0	26.5/51.4	22.7/51.8	26.5/**65.9**	14.9/55.1	**92.0**/100.0
Qwen3-8B-SFT	33.7/67.4	**38.8**/**69.6**	**39.8**/74.6	**33.6**/65.5	36.8/67.7	**21.8**/**49.5**	**29.1**/**53.0**	**27.8**/**55.3**	**27.7**/64.1	**19.4**/**70.3**	60.5/**100.0**

Table 20: LEVEL-3 per-language results.

						LEVEL-3					
Model	Python	Go	JS	Rust	TS	Java	C++	C	Ruby	PHP	Swift
Sparse Retrieval											
BM25	26.2/32.5	29.2/30.3	10.6/25.9	17.9/25.0	9.4/14.2	17.9/12.4	16.8/15.6	19.1/15.2	11.3/21.4	7.4/12.7	0.0/0.0
Small Dense Retrieval Models (<1B)											
CodeRankEmbed	26.4/30.7	33.5/31.6	12.3/23.2	26.5/28.6	17.6/23.8	21.7/13.8	28.6/21.9	26.3/20.4	13.6/19.1	10.6/13.6	0.0/11.1
mE5-small	24.2/31.2	27.9/28.2	13.3/27.6	21.9/25.3	14.3/20.3	18.7/12.2	26.7/20.5	18.8/15.8	10.8/21.0	7.9/21.2	0.0/0.0
mE5-base	8.2/12.2	8.0/9.7	3.6/13.7	8.9/11.7	3.7/7.6	6.3/4.4	8.8/6.4	5.9/6.2	3.7/7.7	4.3/5.8	0.0/0.0
mE5-large	21.9/28.2	23.7/24.1	11.0/26.6	18.6/22.6	12.5/20.6	19.0/11.5	17.4/14.9	15.6/14.2	15.0/20.8	7.5/17.5	0.0/0.0
bge-large-v1.5	26.8/32.6	23.0/21.5	16.4/34.4	24.9/27.5	13.8/21.7	18.3/11.8	26.8/22.1	21.9/19.8	12.9/21.5	6.0/18.0	0.0/22.2
bge-m3	8.1/11.9	10.6/12.2	5.0/15.1	10.9/12.0	4.1/7.0	8.3/5.2	10.0/8.0	8.9/7.9	3.7/8.7	2.0/4.8	0.0/0.0
gte-multi-base	25.9/29.7	23.3/20.3	12.2/24.9	25.3/27.5	18.3/27.3	22.8/15.8	24.7/20.7	18.0/16.9	19.5/23.4	8.1/19.9	0.0/0.0
jina-emb-v5-small	36.8/45.1	43.3/42.5	22.7/39.1	35.9/37.6	26.1/41.1	27.0/18.2	38.6/26.6	26.3/24.4	21.1/30.6	16.9/28.6	**42.0**/44.4
jina-code-0.5b	37.4/46.4	46.2/46.1	26.3/44.7	41.6/41.0	34.7/47.0	37.7/24.7	43.0/30.5	32.3/27.8	28.7/40.4	19.7/34.3	8.4/22.2
Qwen3-0.6B	38.2/46.1	37.7/37.2	27.5/43.8	34.8/33.5	34.1/44.7	30.4/19.5	37.4/26.2	28.8/25.6	26.0/31.3	12.0/23.2	7.1/55.6
Medium Dense Retrieval Models (1B–2B)											
gte-Qwen2-1.5B	5.9/10.1	9.1/14.6	5.8/15.8	6.5/13.5	4.1/8.0	8.2/7.1	7.8/8.1	8.7/11.0	3.2/7.2	3.7/7.0	0.0/0.0
jina-code-1.5b	33.1/46.0	46.0/46.5	23.8/40.3	37.1/37.9	31.0/44.1	31.4/19.8	35.5/24.6	27.2/25.2	21.1/33.1	19.6/32.4	0.0/11.1
F2LLM-v2-1.7B	9.1/14.1	9.9/9.5	4.6/11.4	5.7/10.1	4.8/6.2	13.1/8.0	6.6/7.0	7.6/9.8	0.7/4.9	0.9/3.4	0.0/0.0
Large Dense Retrieval Models (≥4B)											
F2LLM-v2-4B	38.5/45.1	45.2/41.5	34.8/46.5	40.3/37.2	38.5/43.8	35.4/20.7	40.6/27.3	28.1/25.4	30.0/38.3	21.5/33.2	0.0/55.6
Qwen3-4B	38.8/46.5	33.4/36.6	25.4/42.5	33.5/35.2	32.2/43.3	28.0/14.3	37.8/28.5	30.7/27.8	17.9/25.5	11.3/22.7	0.0/33.3
pplx-embed-4b	30.4/38.4	34.0/30.3	18.6/33.0	29.2/28.8	20.6/29.4	21.5/11.4	31.9/21.3	17.0/15.5	16.7/24.5	8.9/18.1	0.0/11.1
C2LLM-7B	33.7/43.2	46.1/44.2	32.5/49.4	40.4/37.6	30.8/43.9	35.9/19.7	40.8/29.5	28.1/27.0	27.3/41.7	14.6/31.3	23.6/**66.7**
e5-mistral-7b	38.7/46.6	45.6/42.8	20.6/41.6	31.3/35.0	29.1/44.5	27.2/19.0	34.3/28.7	31.6/28.1	33.2/42.7	18.2/38.9	0.0/22.2
SweRankEmbed-L	42.6/47.9	44.3/39.1	24.0/39.3	35.0/36.0	34.9/42.4	25.9/17.2	33.9/28.2	23.5/22.0	23.2/28.0	19.4/33.2	0.0/44.4
F2LLM-v2-8B	36.9/44.4	38.2/30.4	21.3/29.6	34.3/30.8	32.3/29.0	35.8/23.0	36.2/26.6	33.0/27.5	29.1/29.7	24.2/38.2	14.8/22.2
Qwen3-8B	39.4/46.4	32.2/36.0	23.5/40.0	40.6/41.5	33.4/38.3	32.1/17.3	45.6/33.7	35.9/30.1	31.9/40.0	13.9/27.1	32.3/44.4
In-domain SFT Dense Retrieval Models (0.6B–8B)											
Qwen3-0.6B-SFT	48.8/57.1	56.7/51.8	43.3/60.9	46.8/45.9	46.4/59.5	44.7/30.7	48.6/36.8	40.4/34.0	38.7/50.3	25.3/44.3	18.5/55.6
Qwen3-4B-SFT	51.6/**63.1**	61.6/57.6	50.7/**69.5**	50.4/51.6	**53.4**/**66.7**	45.7/35.7	50.3/41.4	47.1/40.2	50.3/**68.8**	30.2/51.9	38.3/44.4
Qwen3-8B-SFT	**53.7**/62.1	**64.3**/59.1	**51.9**/67.0	**52.2**/53.0	51.5/58.7	**48.1**/37.5	52.6/42.7	**48.3**/42.5	**53.1**/67.1	**30.4**/58.5	23.2/55.6

Table 21: Query-intent results.

Model	LEVEL-2						LEVEL-3					
	Bug	Feature	Refactor	Question	Docs	Other	Bug	Feature	Refactor	Question	Docs	Other
Sparse Retrieval												
BM25	11.7/35.8	15.3/37.6	20.3/33.6	16.2/36.1	7.0/36.3	13.3/29.9	17.5/24.0	24.2/27.4	25.9/27.0	12.5/18.4	20.0/23.0	21.1/18.1
Small Dense Retrieval Models (<1B)												
CodeRankEmbed	8.9/28.6	14.3/36.6	23.1/36.0	15.4/35.0	9.3/30.3	10.3/24.4	21.0/24.7	28.7/29.6	36.9/29.3	17.9/17.9	28.5/27.5	29.6/22.3
mE5-small	8.8/31.1	13.8/35.0	24.3/36.4	14.8/37.9	19.5/23.6	10.0/23.1	18.1/24.4	25.1/27.4	35.4/30.5	12.7/13.6	17.6/18.9	19.0/20.0
mE5-base	2.8/13.8	4.7/15.7	7.5/11.4	5.6/18.6	1.4/15.4	5.2/12.4	5.4/9.3	8.2/11.6	11.3/10.1	2.3/4.7	9.6/9.5	8.3/8.7
mE5-large	8.9/31.9	12.0/32.5	19.6/30.8	11.7/34.2	21.5/26.4	11.3/26.4	15.7/22.5	21.4/24.1	26.9/24.7	15.4/21.3	19.8/17.2	24.5/20.3
bge-large-v1.5	11.3/36.5	15.3/35.7	21.4/33.0	17.7/41.3	11.5/35.7	14.2/28.0	18.5/25.8	24.9/25.8	33.5/28.5	13.7/20.0	29.7/21.4	22.1/24.3
bge-m3	4.0/16.5	4.8/15.1	8.3/14.8	5.6/20.7	3.1/9.7	4.6/14.8	6.7/10.8	9.6/11.7	13.2/10.8	6.2/7.0	11.7/10.3	11.8/10.2
gte-multi-base	10.9/32.6	13.7/34.9	20.9/30.6	15.7/37.3	8.5/28.8	9.8/29.2	19.0/23.6	24.1/24.9	30.1/24.6	11.2/11.3	21.3/22.7	22.1/20.0
jina-emb-v5-small	15.0/43.8	23.1/51.7	31.1/46.6	17.6/47.8	19.9/43.2	13.6/36.8	28.5/36.7	40.2/41.6	47.6/40.7	20.8/25.1	30.9/33.7	38.1/32.1
jina-code-0.5b	19.9/52.4	24.5/52.4	31.3/48.7	22.1/50.9	27.7/44.0	17.4/34.9	33.7/42.2	42.2/43.3	51.8/42.6	27.4/30.9	39.0/35.0	43.2/34.4
Qwen3-0.6B	15.0/44.6	19.9/47.9	27.5/44.9	14.8/43.3	15.4/41.3	9.9/33.8	30.8/37.7	37.9/38.9	45.4/39.4	27.8/29.5	39.2/31.9	37.7/31.3
Medium Dense Retrieval Models (1B–2B)												
gte-Qwen2-1.5B	1.8/10.3	4.0/17.0	6.2/13.6	2.5/14.2	2.5/10.1	3.6/10.4	5.6/10.5	8.8/14.5	8.0/11.5	9.9/9.8	4.6/6.5	4.9/11.1
jina-code-1.5b	16.0/48.8	20.6/50.4	26.2/45.0	17.1/48.1	18.1/32.7	13.0/35.4	30.5/39.5	39.7/42.3	43.4/39.5	27.2/28.9	23.7/31.3	39.0/30.5
F2LLM-v2-1.7B	3.8/16.8	6.1/19.4	7.2/14.1	6.8/24.4	0.0/11.1	4.8/16.8	6.5/9.7	9.1/11.2	10.4/9.4	6.2/3.6	0.0/5.4	8.3/8.2
Large Dense Retrieval Models (≥4B)												
F2LLM-v2-4B	18.7/49.7	22.7/50.0	30.2/45.8	17.5/46.1	17.8/40.5	15.8/38.9	35.5/40.2	43.6/40.3	46.9/39.3	29.0/27.4	24.9/30.6	36.1/33.2
Qwen3-4B	15.0/44.8	20.4/48.4	26.1/42.3	17.9/44.1	16.8/40.7	11.9/34.7	28.9/37.0	36.8/39.3	43.2/37.2	19.4/28.9	26.7/29.4	32.5/30.0
pplx-embed-4b	11.7/35.6	15.6/38.7	24.0/40.9	12.7/40.0	13.7/25.5	8.6/22.8	23.3/29.2	30.8/30.3	39.2/33.7	17.2/22.6	28.3/25.5	30.8/23.4
C2LLM-7B	15.0/43.6	22.5/49.9	27.7/45.5	15.5/43.6	21.0/42.2	12.9/34.7	32.5/40.6	42.4/42.2	49.4/40.6	28.9/32.6	37.6/32.6	38.5/31.9
e5-mistral-7b	16.6/50.0	23.4/52.9	26.5/44.7	21.7/51.2	23.1/47.0	14.1/36.9	30.7/39.7	39.7/41.2	40.4/37.9	28.1/30.1	38.5/34.6	31.1/30.6
SweRankEmbed-L	22.1/50.9	25.1/50.5	34.1/46.8	20.9/46.8	24.9/43.9	15.6/36.8	32.7/38.2	39.5/38.6	45.5/39.0	23.5/23.4	37.4/31.1	32.5/28.4
F2LLM-v2-8B	16.5/44.7	20.5/42.5	28.2/37.8	20.4/43.0	23.3/35.3	14.7/29.2	30.5/33.2	37.8/32.4	38.0/29.5	27.4/23.6	35.5/29.6	32.7/23.7
Qwen3-8B	17.8/47.2	22.3/48.9	28.2/41.8	17.8/43.8	21.2/47.5	16.1/37.3	30.5/38.1	37.8/38.9	44.6/36.5	26.6/28.3	36.6/29.6	36.3/30.6
In-domain SFT Dense Retrieval Models (0.6B–8B)												
Qwen3-0.6B-SFT	26.1/60.7	31.1/60.3	38.5/55.5	28.1/55.7	31.0/58.9	23.6/48.8	44.7/52.4	53.2/51.0	59.7/49.2	44.3/48.2	36.0/44.2	44.4/41.7
Qwen3-4B-SFT	29.7/**68.1**	34.3/65.4	41.5/58.4	27.7/61.0	35.7/**60.9**	30.4/56.9	50.0/**59.8**	57.0/56.6	**63.9**/54.2	**49.3**/52.9	32.1/**46.8**	**52.1**/44.3
Qwen3-8B-SFT	**32.4**/68.1	**36.9/66.2**	**43.1**/57.4	**28.9/63.0**	**36.1**/57.2	**39.4/58.3**	**51.4**/59.0	**59.7/56.7**	62.7/53.5	48.3/52.4	**47.1**/46.3	48.8/**44.6**

Table 22: Repository-difficulty results.

Model	LEVEL-2				LEVEL-3			
	F-S	*F-L*	*D-S*	*D-L*	*F-S*	*F-L*	*D-S*	*D-L*
Sparse Retrieval								
BM25	12.2/50.0	12.4/34.6	16.4/42.3	14.4/30.9	–	5.0/32.9	15.2/43.8	20.9/23.4
Small Dense Retrieval Models (<1B)								
CodeRankEmbed	13.4/43.7	9.5/28.8	14.5/39.7	12.6/28.4	–	12.4/11.1	24.4/44.2	24.7/25.0
mE5-small	10.3/45.0	9.6/30.2	15.0/39.8	13.3/29.0	–	3.2/11.1	19.2/43.5	21.7/23.9
mE5-base	4.3/25.4	2.6/11.1	6.6/26.9	4.4/11.6	–	0.0/5.6	6.2/24.8	6.8/8.7
mE5-large	9.9/43.9	9.6/31.3	12.7/37.2	11.6/26.2	–	17.1/36.4	15.5/39.4	18.8/21.5
bge-large-v1.5	13.5/51.8	12.4/35.2	16.8/43.4	13.1/28.2	–	0.0/2.8	21.0/48.5	21.7/23.7
bge-m3	4.7/25.8	3.5/13.5	6.9/26.2	5.3/12.9	–	9.4/11.1	9.9/28.4	8.0/9.4
gte-multi-base	12.8/46.6	11.7/31.5	15.4/41.8	12.1/27.8	–	14.7/41.7	22.3/43.3	21.3/22.1
jina-emb-v5-small	17.9/56.9	17.2/45.5	21.6/50.9	19.5/41.9	–	6.4/30.2	31.1/54.6	34.0/36.9
jina-code-0.5b	21.8/62.1	21.1/53.1	21.8/51.3	23.3/45.5	–	**37.3**/71.1	34.3/57.4	38.1/40.8
Qwen3-0.6B	17.4/54.3	16.1/45.6	18.6/46.6	17.8/40.9	–	12.8/47.1	35.2/52.3	34.1/36.6
Medium Dense Retrieval Models (1B–2B)								
gte-Qwen2-1.5B	2.9/21.5	1.7/8.6	6.5/25.1	3.4/12.1	–	0.0/1.0	8.9/26.1	6.7/10.6
jina-code-1.5b	16.0/58.0	17.6/49.8	19.2/48.9	18.9/43.0	–	16.7/63.8	32.0/55.9	34.8/38.7
F2LLM-v2-1.7B	6.3/30.7	3.7/14.4	9.5/33.2	4.4/13.1	–	0.0/8.3	9.1/24.6	7.5/8.8
Large Dense Retrieval Models (≥4B)								
F2LLM-v2-4B	19.1/58.0	20.1/50.9	21.4/50.1	21.2/42.6	–	36.7/62.6	37.6/51.8	39.0/38.8
Qwen3-4B	16.9/55.2	16.0/45.3	19.9/48.8	18.6/41.2	–	10.1/38.0	33.2/55.1	32.4/36.0
pplx-embed-4b	13.3/45.3	12.7/36.1	14.6/42.1	14.4/32.3	–	5.7/26.0	23.4/44.6	27.2/28.3
C2LLM-7B	18.4/53.0	16.6/46.0	20.6/47.4	19.4/41.0	–	8.2/22.5	37.0/56.7	37.0/39.5
e5-mistral-7b	19.8/60.6	18.4/51.3	21.4/52.1	19.9/44.1	–	10.2/59.0	33.8/61.1	34.6/37.9
SweRankEmbed-L	24.1/61.7	23.1/50.8	22.5/51.7	24.0/43.8	–	24.6/64.1	32.6/54.8	36.1/36.4
F2LLM-v2-8B	14.2/49.1	17.9/44.5	21.3/47.3	20.2/37.9	–	26.0/26.7	25.6/38.3	34.3/32.0
Qwen3-8B	18.8/55.9	19.0/48.2	21.8/48.3	20.6/41.7	–	12.8/33.5	29.6/50.9	34.4/36.9
In-domain SFT Dense Retrieval Models (0.6B–8B)								
Qwen3-0.6B-SFT	28.2/67.9	28.0/62.1	26.0/55.4	29.2/54.2	–	30.0/**72.1**	45.5/68.7	48.8/49.8
Qwen3-4B-SFT	30.9/**74.7**	31.8/69.2	29.1/**61.2**	32.3/**59.4**	–	29.7/69.2	**50.4/75.7**	53.5/56.3
Qwen3-8B-SFT	**34.0**/73.2	**35.0/69.7**	**32.7**/60.5	**33.7/60.4**	–	16.8/53.3	49.5/69.5	**55.4/56.5**

Table 23: Query rewriting prompt.

Query rewriting prompt

```
[System prompt]
You are an expert at analyzing and rewriting GitHub issue texts for a code-retrieval benchmark.
You have two tasks: (1) classify the issue, (2) rewrite it as a realistic vibe-coding query a developer would type into an AI
    ↪ coding assistant.
Output only a valid JSON object and nothing else.

[User prompt template]
Analyze the following GitHub issue and perform TWO tasks:

## Task 1: Classify the issue on three dimensions

- **description_style**: "natural_language" if the issue is primarily prose description; "error_traceback" if it is primarily
    ↪ structured around a stack trace, error output, or log messages.
- **intent_type**: Choose the single best fit from: "bug_report", "feature_request", "question", "refactoring", "documentation
    ↪ ", "other".
- **content_type**: "text_heavy" if the content is mostly prose with little or no code/paths; "code_heavy" if the dominant
    ↪ content is code blocks or snippets; "file_path_heavy" if the dominant non-prose content is file paths or module names;
    ↪ "mixed" otherwise.

## Task 2: Rewrite the issue as a vibe-coding developer query

Imagine a developer encounters this exact problem while coding and pastes it into an AI coding assistant. Rewrite the issue as
    ↪ the raw, unpolished query they would type.

### What vibe-coding queries look like
- The developer describes symptoms, not root causes: "my X is broken when I do Y" not "the internal state machine fails to
    ↪ transition".
- They paste error messages and stack traces directly without editing them.
- They may include a short code snippet showing what they tried.
- Tone is casual and direct: "why does this crash?", "how do I fix this?", "getting a weird error".
- They do NOT write structured reports: no headers, no "Expected behavior:" labels, no checklists.

### Rewriting rules

Preserve verbatim:
- All error messages, exception types, and stack traces.
- Code snippets that directly show the failing code or minimal reproducer.

Rewrite or compress:
- Translate formal issue prose into casual first-person phrasing.
- Remove GitHub issue template noise, such as HTML comments, section headers, checkboxes, and version tables.
- Drop unrelated environment details unless they are clearly relevant.
- Remove duplicate information.

Per description_style guidance:
- If `error_traceback`: lead with one casual sentence describing what the user was doing, paste the full traceback/error
    ↪ output as-is, then end with a short question.
- If `natural_language`: rewrite as a concise first-person question of about 50--200 words. Keep key technical terms, library
    ↪ names, and short code snippets that illustrate the problem.

Length:
- Target 50--300 words for the rewritten query.
- Never reproduce the entire issue verbatim.
- Never reduce to a single vague sentence that loses technical specifics.

Language: Keep the same language as the original issue.
Faithfulness: Do NOT add information, suggestions, or context not present in the original issue.

Output format:
{
  "description_style": "<natural_language|error_traceback>",
  "intent_type": "<bug_report|feature_request|question|refactoring|documentation|other>",
  "content_type": "<text_heavy|code_heavy|file_path_heavy|mixed>",
  "rewritten_query": "<the rewritten vibe-coding query>",
  "reason": "<one sentence explaining your classification choices, under 40 words>"
}

Rules:
- Output ONLY the JSON object, no markdown fences, no extra text.
- All field values must exactly match the allowed values above.

<issue_text>
<raw_issue_text>
</issue_text>
```

Table 24: Query filtering prompt.

Query filtering prompt

```
[System prompt]
You are a query quality judge for a code retrieval benchmark. Each query is a GitHub PR/Issue description used as a search
    ↪ query to find relevant code files.

Classify the query into one of three categories:

1. FILTER_MEANINGLESS: The query is meaningless, underspecified, non-actionable,
or has no substantive problem content.
Examples:
- Only contains an issue/PR number, such as "Fix #1234" or "Closes #567".
- Contains only boilerplate template text with no filled content.
- Is extremely short with no actionable information, such as "update", "fix", or "bug".
- Contains only links or references without describing the problem.
- Describes a broad maintenance task without symptoms, expected behavior, error
messages, APIs, or repository-specific clues.

2. FILTER_ANSWER_LEAK: The query already reveals the solution, making code retrieval trivial.
Examples:
- Explicitly mentions which file(s) to modify.
- Describes exact code changes or diffs.
- Provides the fix implementation in the description.
- Names specific functions/methods/classes to change AND describes the exact change.
Note: Simply mentioning a module name or function as part of describing a problem is NOT an answer leak. Only classify as leak
    ↪ when the query tells you where and how to fix it.
File paths from tracebacks, logs, or error messages are also not answer leaks
unless the query instructs the developer to edit those files or gives the patch recipe.

3. KEEP: The query is a valid, meaningful problem description with enough
issue-specific signal for retrieval and does not reveal the answer.

Respond with ONLY a JSON object in this exact format:
{"verdict": "FILTER_MEANINGLESS" | "FILTER_ANSWER_LEAK" | "KEEP", "reason": "<brief reason in English>"}

[User prompt template]
Query ID: <query_id>
Query text:
<query_text>
```

Table 25: LLM relevance judge prompt.

LLM relevance judge prompt

```
[System prompt]
You are a strict code-retrieval relevance judge for software issue resolution.

Your task is to decide how useful a trajectory-derived candidate code chunk is for understanding, localizing, or fixing the
    ↪ issue.
Return a single JSON object and nothing else.

[User prompt template]
Evaluate the relevance of the candidate code chunk for the issue below.

Issue instance: <instance_id>
Query id: <query_id>

Relevance labels:
- high: the chunk is directly about the buggy logic, the likely fix location, a closely related serializer/parser/data-flow
    ↪ path, or a key failing test.
- partial: the chunk is adjacent context that would help understand or localize the fix, but is not itself a strong candidate
    ↪ for the main fix.
- irrelevant: the chunk is unrelated, too generic, or unlikely to help understand/localize/fix the issue.

Output schema:
{
  "label": "high" | "partial" | "irrelevant",
  "score": 2 | 1 | 0,
  "confidence": 0.0 to 1.0,
  "reason": "short justification"
}

Rules:
- `score` must match `label` exactly: high=2, partial=1, irrelevant=0.
- Keep `reason` under 60 words.
- Use only the issue text and chunk content below.
- A chunk can be relevant even if it is not an edit location, as long as it helps
understand or localize the issue.
- Do not explain the schema.
- Do not use markdown fences.

<truncation_note>

<issue_text>
<raw_issue_text>
</issue_text>

<chunk_metadata>
file_path: <file_path>
start_line: <start_line>
end_line: <end_line>
language: <language>
chunk_index: <chunk_index>
</chunk_metadata>

<code_chunk>
<code_chunk_text>
</code_chunk>
```