Avoidance Learning of Failure Modes Produces Robust Tool Planners

Abstract

Multi-step tool planning fails through structural errors that cascade silently through dependent steps; parameter typos, missing dependencies, and mis-ordered operations are particularly damaging because each is locally well-formed yet derails the overall trajectory. We introduce FORTE, a framework that trains tool planners to recognize and avoid these failure modes directly. We construct two augmented contrastive datasets for ToolHop and NESTFUL by injecting minimally edited negative plans into gold trajectories under a 9-error taxonomy, train a lightweight judge to score plan structure against a deductive rubric over the taxonomy, and use this frozen judge as both a dense reward signal for GRPO planner training and a verifier for temperature-diversity Best-of-N inference. On ToolHop and NESTFUL, FORTE achieves the highest Judge Success Rate (JSR) across all six backbone and dataset configurations, beating established baselines by 2.5 to 13.2 JSR points using only 3B to 7B open-source models; even our smallest backbone outperforms GPT-5.5 by 33.9 ToolHop JSR points. Ablations confirm that contrastive negatives are the critical ingredient: removing them collapses Best-of-N selection below the single-sample baseline.

1 Introduction

Multi-step tool planning requires LLMs to simultaneously select correct tools, bind arguments with valid types, route intermediate outputs as inputs to downstream calls, and sequence operations correctly. A single local mistake, whether a near-miss tool, a mis-typed argument, or a mis-threaded reference, silently propagates through dependent steps and breaks the entire trajectory. Even frontier models exhibit this brittleness on multi-step tool calling datasets: GPT-4o reaches only 49% accuracy on ToolHop (Ye et al., 2025) and 28% full-sequence match on NESTFUL (Basu et al., 2025). In multi-step tool plans no constraint is independent; a single error cascades forward, producing trajectories that appear syntactically well-formed but are deductively broken.

The community has responded along two axes. The first is *test-time search*: ReAct (Yao et al., 2022), Reflexion (Shinn et al., 2023), LATS (Zhou et al., 2023), and ToolTree (Yang et al., 2026) explore reasoning trajectories more carefully through reactive loops or tree search. The second is *structural scaffolding*: GTool (Chen et al., 2025), GNN4Plan (Wu et al., 2024c), and ToolPlanner (Wu et al., 2024a) inject dependency-graph priors at inference time. RL-based methods that fine-tune tool policies on coarse execution outcomes (Yu et al., 2025; Li et al., 2025; Wu et al., 2024b) provide a third alternative. All share an assumption that improved inference-time guidance or scalar success signals suffice; none directly trains models to recognize and avoid the specific structural failure modes that derail multi-step plans. Recent diagnostic work has begun characterizing these failure modes systematically: CriticTool (Huang et al., 2025) defines a five-type error taxonomy, while ToolScan (Kokane et al., 2024) and FAIL-TALMS (Treviño et al., 2025) catalog recurring failure patterns. However, these taxonomies remain post-hoc diagnostic instruments rather than training targets, leaving a clear opportunity: train planners and judges to be error-aware by construction.

We introduce FORTE (Figure 1), a framework that trains tool planners through failure avoidance. FORTE starts from a 9-error taxonomy for multi-step plans (Table 1) and uses it to drive a contrastive data augmentation pipeline: for each gold trajectory we generate nine minimally edited negative plans, each instantiating one taxonomy error while preserving task context. This produces a dense, taxonomy-grounded supervision signal at scale without manual annotation. A lightweight

Figure 1: FORTE trains tool-planning models in three steps. We first build an error-aware corpus by injecting nine taxonomy-grounded error types into correct plans. We then annotate plans with GPT-5.4, fine-tune a judge model on the nine-error rubric, and train the planner with GRPO using the frozen judge as a dense reward signal. At inference, we sample five candidates with Best-of-N selection.

judge is fine-tuned on a deductive rubric over these plan pairs, learning to score plan structure and localize specific error types. The planner is then trained with GRPO using this frozen judge as a structured reward signal, and at test time the same judge selects from a temperature-diverse Best-of-N candidate pool (Cobbe et al., 2021; Lightman et al., 2023).

FORTE differs from prior judge-planner (Wu et al., 2024a; Yu et al., 2025) and RL methods in three ways. First, the judge is grounded in a human-interpretable error taxonomy rather than in scalar end-task scores, making its judgments more precise and more interpretable. Second, contrastive negative plans densely cover the error space, rather than relying on sparse environment failures or oracle trajectory pairs. Third, the architecture is decoupled in a specific sense that prior methods are not: prior training-based approaches conflate plan-level correctness with tool execution outcomes, whereas FORTE's judge scores plan structure alone, so the planner is reusable across benchmarks and requires no ensemble components, graph-search modules, or multi-agent decompositions at inference time.

Across ToolHop and NESTFUL, FORTE achieves the highest Judge Success Rate (JSR) on all six backbone and dataset configurations using only 3B to 7B open-source models, beating established baselines (ReAct, α-UMi, GNN4TaskPlan, ToolPlanner) by 2.5 to 13.2 JSR points and ex-

ceeding frontier closed-source models: even our smallest backbone outperforms GPT-5.5 by 33.9 ToolHop JSR points. Ablations confirm that the contrastive negatives are the critical ingredient; removing them drops JSR by 14.3 points and collapses Best-of-N selection below the single-sample baseline. Our main contributions are:

- A 9-error taxonomy for multi-step tool plans organized into argument-level, multi-step dependency, and plan-structure failure modes, with three categories that are absent from prior diagnostic frameworks (Table 1).

- Two augmented contrastive datasets (ToolHop and NESTFUL) constructed via a scalable annotation pipeline that, for each gold trajectory, instantiates all nine taxonomy errors as minimally edited negatives and annotates the resulting plan pairs against a deductive rubric, supporting the training of error-aware planners and judges.

- A decoupled judge-planner architecture in which a lightweight judge supplies dense GRPO reward and also serves as a verifier for temperature-diversity Best-of-N inference, without requiring tool execution at any stage of training or selection.

- Comprehensive experiments showing FORTE achieves the highest JSR across all six back-

bone and dataset configurations, with FORTE-Qwen2.5-7B reaching 96.6 / 98.6 JSR on Tool-Hop / NESTFUL and outperforming GPT-5.5 by 33.9 ToolHop JSR points using only open-source 3B to 7B backbones.

2 Related Work

Multi-step tool planning and benchmarks. Tool-augmented LLMs have advanced from single-step function calling (Schick et al., 2023) to multi-step orchestration at scale (Qin et al., 2023). Two recent benchmarks specifically stress multi-step structure: ToolHop (Ye et al., 2025) requires multi-hop chaining across 995 queries and 3,912 tools (GPT-4o: 49% accuracy), and NESTFUL (Basu et al., 2025) targets nested API sequences where one call's output seeds the next (full-sequence match: 28%). These results establish that multi-step dependency failures are qualitatively different from single-call errors and persist even in frontier models, motivating methods that act on multi-step structure at training time.

Test-time search and structural scaffolding. Test-time methods improve robustness either by searching harder or by imposing structure. Search-based approaches range from the canonical Thought–Action–Observation loop of ReAct (Yao et al., 2022) to the recent ToolTree (Yang et al., 2026), which combines pre- and post-execution LLM evaluation inside MCTS with bidirectional pruning. Structural scaffolding methods instead inject dependency priors via GNNs or graph navigation (Wu et al., 2024c). We compare directly against representatives of both families (ReAct and GNN4TaskPlan) in our experiments. All of these methods constrain or guide the planner at inference time but leave its underlying error tendencies unchanged, treating brittleness as an inference problem rather than a training deficiency.

RL and contrastive training for tool use. Several works apply RL or contrastive optimization to tool-use policies. StepTool (Yu et al., 2025) introduces step-grained reward shaping that assigns credit to each tool call based on invocation success and task contribution. Tool-Planner (Wu et al., 2024a) constructs pairwise SFT+RL preference data from task-completion and instruction-following scores. On the contrastive side, AvaTaR (Wu et al., 2024b) learns a comparator module that performs contrastive reasoning over

positive and negative trajectories to generate holistic steering prompts. The supervision in all of these frameworks reduces to coarse execution outcomes, such as binary success, task recall, or completion scores, rather than structured error labels. None trains against a taxonomized error space, so the agent receives no signal distinguishing a dependency threading failure from a parameter-key error. FORTE addresses this directly, training its judge on a deductive rubric over a 9-error taxonomy and making the contrastive signal causally grounded in specific failure types.

Failure taxonomies and diagnostic benchmarks. Substantial recent work characterizes tool-use failures empirically. CriticTool (Huang et al., 2025) is the closest prior work, defining a five-type taxonomy covering tool selection, tool hallucination, parameter-key, parameter-value, and environment errors, and introducing the first benchmark for evaluating LLM self-critique in tool-calling; it finds that GPT-4o achieves only 22% error recovery on NESTFUL. ToolScan and FAIL-TALMS each catalog seven or more recurring error patterns and provide diagnostic protocols (Kokane et al., 2024; Treviño et al., 2025). The consistent pattern across this line of work, including additional studies surveyed in Appendix A, is that error taxonomies serve as diagnostic instruments rather than training targets. FORTE closes this loop: the taxonomy is designed to be labeled over individual plan steps, the contrastive pipeline populates that label space at scale, and the judge is trained to reason within it, transforming error characterization from a post-hoc diagnostic into the primary driver of training.

3 Method

Here, we present the methodology of FORTE.

3.1 Problem Formulation

Let q denote a natural-language query and $\mathcal{T} = \{t_1, \ldots, t_K\}$ a set of available tools, each described by its name, parameter schema, and return type. A *tool plan* is a sequence $\pi = \langle s_0, \ldots, s_L \rangle$ where each $s_i = (v_i, t_i, \mathbf{p}_i)$ specifies an output variable, a tool invocation, and parameter bindings that may reference earlier outputs via $\{\{j\}\}$ syntax; π^* denotes the gold reference plan. The planner f_θ maps $(q, \mathcal{T})$ to a distribution over plans, and the judge g_ϕ maps $(q, \mathcal{T}, \pi)$ to a quality score $\rho \in [0, 100]$ and a predicted error label e drawn from the 9-type taxonomy defined below.

Table 1: FORTE's 9-error taxonomy vs. prior error-characterization and training frameworks (Huang et al., 2025; Kokane et al., 2024; Treviño et al., 2025; Yu et al., 2025; Wu et al., 2024a,b). ✓/✗ indicate whether the error type is explicitly characterized or the methodology property is present. Rows are grouped into argument-level errors (rows 1–3), multi-step dependency errors (rows 4–6), and multi-step plan structure errors (rows 7–9); all three dependency and ordering error types are absent from prior frameworks.

Error Type	Diagnostic Benchmarks			Training Methods			
	Critic Tool	Tool Scan	FAIL-TALMS	Step Tool	Tool Planner	Ava TaR	FORTE (Ours)
Type Mismatch	✗	✓	✗	✗	✗	✗	✓
Parameter Typo	✓	✓	✗	✗	✗	✗	✓
Wrong Tool	✓	✓	✗	✗	✗	✗	✓
Missing Dependency	✗	✗	✗	✗	✗	✗	✓
Circular Dependency	✗	✗	✗	✗	✗	✗	✓
Forward Reference	✗	✗	✗	✗	✗	✗	✓
Inefficient Order	✗	✗	✗	✗	✗	✗	✓
Incomplete Plan	✗	✓	✓	✗	✗	✗	✓
Unnecessary Steps	✗	✓	✗	✗	✗	✗	✓
Errors Covered	2/9	5/9	1/9	0/9	0/9	0/9	**9/9**
Taxonomy Defined	✓	✓	✗	✗	✗	✗	✓
Used as Training Signal	✗	✗	✗	✓	✓	✓	✓
Contrastive Training Data	✗	✗	✗	✗	✗	✓	✓
Judge Trained on Taxonomy	✗	✗	✗	✗	✗	✗	✓

3.2 Error Taxonomy

We define nine concrete failure modes in three categories.

Argument-level errors occur within individual tool invocations. *Parameter Typo* distorts one parameter value while preserving syntactic validity. *Type Mismatch* replaces a parameter with one of an incompatible type, for example an integer where a string is required. *Wrong Tool* substitutes the correct tool with a semantically adjacent but functionally incompatible alternative.

Multi-step dependency errors arise from incorrect data flow. *Missing Dependency* replaces an inter-step reference $\{\{j\}\}$ with a hardcoded literal. *Circular Dependency* introduces a reference cycle. *Forward Reference* lets an earlier step reference a step not yet executed.

Multi-step plan structure errors affect global plan organization. *Inefficient Order* permutes steps so the logical sequence is broken while individual invocations remain correct. *Incomplete Plan* truncates the plan before the final sub-question is resolved. *Unnecessary Steps* inserts a redundant tool call.

These nine types cover the recurring patterns identified in prior diagnostic work (Huang et al., 2025; Kokane et al., 2024; Treviño et al., 2025), extending coverage to the three dependency and ordering errors unique to multi-step plans (Table 1).

3.3 Contrastive Data Augmentation

Given a gold plan π^* for query q, we construct nine taxonomy-grounded negative plans $\{\pi_e^-\}_{e\in\mathcal{E}}$, one per error type, via deterministic, minimally invasive edits to π^*. Each edit targets a single step and preserves all other steps verbatim, so the negative differs from the gold in exactly the way prescribed by e.

Argument-level negatives apply a character-level perturbation (typo), substitute a type-incompatible constant from the schema (type mismatch), or swap the tool name for the most-similar alternative in $\mathcal{T}$ (wrong tool). Dependency negatives replace $\{\{j\}\}$ with a hardcoded string (missing dependency), introduce a back-edge that closes a cycle (circular dependency), or advance a reference past the current step (forward reference). Structural negatives swap two steps with a data-flow dependency (inefficient order), drop the final step (incomplete plan), or duplicate an intermediate step (unnecessary steps).

This yields plan pairs $(q, \mathcal{T}, \pi^*, \pi_e^-, e)$ without manual annotation. Applied independently to the training splits of ToolHop and NESTFUL, the pipeline produces two dataset-specific augmented corpora that systematically cover the full error space.

3.4 Judge Training

We fine-tune a judge model g_ϕ to score plans on a deductive rubric aligned with the taxonomy. Given the query, tool schemas, and proposed plan, the

judge outputs a JSON object containing a quality score $\rho \in [0, 100]$, a categorical success prediction, a natural-language reasoning trace, and a list of detected issues with their predicted error types (inference prompt in Appendix B.2).

Reference annotations. For each pair $(q, \mathcal{T}, \pi^*, \pi_e^-, e)$ we query GPT-5.4 with the inference-time rubric prompt (Appendix B.1). Starting from a base score of 100, the rubric deducts on a four-tier severity schedule: critical (-30) for circular dependencies, forward references, missing required parameters, and non-existent tools; high (-20) for hardcoded values where $\{\{j\}\}$ references are expected; medium (-10) for ordering and redundancy issues; and low (-5) for stylistic issues. The injected error type e is *not* revealed to GPT-5.4: the annotator identifies issues independently and applies the rubric, so each negative's score reflects errors GPT-5.4 actually detects rather than a deterministic mapping from the injection label. Empirically, gold plans score 95 to 100 and negatives score 70 to 95.

Syntactic-only scoring. The rubric scores syntactic plan correctness rather than semantic task success, and the judge is instructed never to type-check parameter values containing $\{\{j\}\}$, since these are dependency references whose runtime type is determined upstream. This decoupling enables training the judge on plan structure alone, with no tool execution environment required.

The judge is LoRA fine-tuned (Hu et al., 2022) from Qwen2.5-7B-Instruct on the reference annotations and used identically across all planner experiments. At inference it is served via batched vLLM as both the GRPO reward model and the Best-of-N scorer.

3.5 Planner Training

Supervised fine-tuning. We initialize the planner from a pretrained instruction-tuned base model and perform SFT on the gold plans of the relevant corpus with the prompt template in Appendix B.3. The objective is token-level cross-entropy on response tokens only. The SFT checkpoint serves as both the RL initialization and the KL reference policy.

RL with GRPO. We use Group Relative Policy Optimization (Shao et al., 2024), which removes the value network and computes advantages via group-normalized rewards: for each query we sample G candidate plans, score each with the frozen judge, and normalize the group's rewards by their mean and standard deviation. The judge weights are frozen throughout RL, so the planner's reward signal is determined entirely by plan structure.

3.6 Inference: Temperature-Diversity Best-of-N

At test time we generate $N = 5$ candidate plans per query and return the highest-scoring candidate. To maximize candidate diversity without sacrificing per-sample quality, we draw exactly one candidate at each temperature in $\tau \in \{0.2, 0.4, 0.6, 0.8, 1.0\}$. Each candidate is scored by the judge with the same rubric used during RL training (Appendix B.2), and we return $\hat{\pi} = \arg\max_{i \in [N]} g_\phi(q, \mathcal{T}, \pi_i)$.

4 Experiments

Here, we expand upon our experimental setup to conduct the experiments and analyze the results.

4.1 Datasets and Evaluation

We evaluate FORTE on two complementary multi-step tool-planning benchmarks.

ToolHop (Ye et al., 2025) contains 995 multi-hop queries each requiring a 2-to-6-step tool plan over a per-query tool set of 3-to-8 tools. The benchmark stresses cross-step reasoning where each query is explicitly decomposed into sub-questions whose answers feed downstream tool calls. We hold out 100 queries for evaluation and apply the augmentation pipeline of Section 3.3 independently to each split: for every query we instantiate one error-free reference plan and nine taxonomy-grounded negatives, one per error type, yielding 1000 annotated evaluation plans that cover the full error space.

NESTFUL (Basu et al., 2025) contains 1861 multi-step instances designed to evaluate nested function calling, where outputs of one tool call are used as arguments of subsequent calls via labeled references such as `$var_1.result$`. The benchmark spans two domains: a mathematical-reasoning subset (1,415 examples drawn from MathQA covering 40 tools with an average of 5.1 tool calls per sample) and a coding subset (446 examples synthesized from StarCoder2-Instruct covering 881 distinct tools with an average of 2.1 tool calls per sample). We apply a similar augmentation pipeline as ToolHop to create our training and test sets.

Metrics. We report four metrics, all expressed as

Table 2: Main results on ToolHop and NESTFUL. **Best** (green shading) and second best are marked within each backbone group. JSR: Judge Success Rate (%, score ≥80). FM: Functional Match (%). PA: Mean Parameter Accuracy (%). DA: Mean Dependency Accuracy (%).

Backbone LLM	Method	ToolHop				NESTFUL			
		JSR	FM	PA	DA	JSR	FM	PA	DA
Llama3.2-3B	ReAct	75.5	74.4	69.8	88.2	88.9	30.8	53.2	83.8
	α-UMi	0.0	0.0	20.0	11.5	17.3	0.0	26.1	9.2
	GNN4TaskPlan	14.0	12.0	25.1	51.8	12.6	2.8	29.4	58.6
	ToolPlanner	83.2	**91.7**	**74.4**	96.5	95.0	31.4	59.1	**85.1**
	FORTE (ours)	**92.9**	80.2	63.6	**98.9**	**98.9**	**37.2**	**60.2**	84.0
Qwen2.5-3B	ReAct	92.7	84.7	**70.0**	93.1	83.3	27.5	45.6	67.7
	α-UMi	18.0	5.0	26.3	52.6	46.7	3.9	30.3	49.5
	GNN4TaskPlan	2.0	2.0	8.9	13.9	4.7	1.7	4.7	20.4
	ToolPlanner	60.1	82.7	66.7	85.4	84.5	29.1	52.3	79.7
	FORTE (ours)	**96.6**	**89.2**	69.5	**98.8**	**97.7**	**33.6**	**56.2**	**87.8**
Qwen2.5-7B	ReAct	74.9	80.0	74.6	91.6	89.4	32.6	52.6	80.6
	α-UMi	29.0	21.3	29.8	49.6	67.3	15.7	42.1	51.1
	GNN4TaskPlan	23.0	25.0	30.9	59.9	24.4	5.3	28.7	57.2
	ToolPlanner	87.7	85.4	67.6	86.2	96.1	41.6	59.0	85.9
	FORTE (ours)	**96.6**	**97.3**	**77.1**	**98.9**	**98.6**	**44.3**	**61.6**	**89.0**

percentages averaged over the test set. *Judge Success Rate* (JSR) is the fraction of generated plans for which the judge assigns a score of at least 80, the threshold calibrated to the rubric's "likely to succeed" band. The remaining three are deterministic structural metrics computed against gold plans. *Functional Match* (FM) requires three conditions to hold jointly on a single example: step-count agreement with the gold plan, at least 50% Jaccard keyword overlap on tool names, and at least 50% parameter accuracy. *Mean Parameter Accuracy* (PA) is the fraction of ground-truth parameters reproduced correctly. *Mean Dependency Accuracy* (DA) is the fraction of $\{\{N\}\}$ output-variable references correctly threaded through the plan.

4.2 Implementation Details

Models. We use three planner backbones: Qwen2.5-3B-Instruct, Qwen2.5-7B-Instruct, and Llama3.2-3B-Instruct. The judge is always Qwen2.5-7B-Instruct fine-tuned on GPT-5.4 reference annotations, regardless of the planner.

Training. SFT runs for 4 epochs with AdamW (peak learning rate 5×10^{-5}, cosine schedule). GRPO uses group size $G = 5$, learning rate 1×10^{-6}, PPO clip $\varepsilon = 0.2$, and KL coefficient $\beta = 0.01$. We train for 4 epochs and report the checkpoint that maximizes joint performance on judge success and structural metrics on a held-out validation split. All training runs use 8×NVIDIA RTX 6000 Ada GPUs with bfloat16 mixed precision.

Inference. Best-of-N uses $N = 5$ with temperatures $\tau \in \{0.2, 0.4, 0.6, 0.8, 1.0\}$ as described in Section 3.6. Top-p is fixed at 0.9 for all candidates. The judge runs as a vLLM server with batch size 64 and is queried in parallel for the five candidates per query.

4.3 Baselines

We compare FORTE against four established multi-step tool-planning baselines. All baselines use our SFT-trained planner as their underlying generation model unless stated otherwise. **ReAct** (Yao et al., 2022) runs a 3-shot Thought-Action loop with a single generation per query. α**-UMi** (Shen et al., 2024a) uses the multi-model Planner-Caller decomposition, with both roles filled by separate instances of the non-fine-tuned instruction-tuned backbone. **GNN4TaskPlan** (Wu et al., 2024c) is a three-stage pipeline (sub-action decomposition → GraphSAGE retriever → parameter filling); we train the retriever on the training-set co-occurrence graph with BPR loss, two hard negatives per positive, for 20 epochs. **Tool-Planner** (Wu et al., 2024a) performs reward-guided beam search with a width of 3, using task-completion and instruction-following scores. This protocol grants the strongest baselines (ReAct, Tool-Planner, GNN4TaskPlan) the same SFT initialization as FORTE, so any remaining gap isolates the contribution of contrastive

judge training and GRPO from that of supervised fine-tuning alone. We also compare against closed-source models GPT-5.5 and GPT-5-Nano.

4.4 Main Results

FORTE achieves the highest judge success in every setting Table 2 shows that FORTE obtains the best JSR across all six backbone-dataset configurations. On ToolHop, FORTE improves over the next-best method by 9.7, 3.9, and 8.9 points for Llama3.2-3B, Qwen2.5-3B, and Qwen2.5-7B, respectively. On NESTFUL, the corresponding gains are 3.9, 13.2, and 2.5 points. This consistent improvement suggests that failure-avoidance training improves overall plan quality across both benchmarks and model families. Qualitative examples of generated plans are presented in Appendix C.

FORTE is strongest on the harder NESTFUL benchmark. NESTFUL is more structurally challenging, with substantially lower FM scores than ToolHop across methods. Despite this, FORTE achieves the best NESTFUL FM for all three backbones, reaching 37.2, 33.6, and 44.3. It also obtains the best PA for all three backbones and the best DA for both Qwen models. These results indicate that FORTE is especially effective when tool planning requires stronger structural generalization.

FORTE nearly saturates dependency accuracy on ToolHop. On ToolHop, FORTE achieves the best DA for every backbone, with scores of 98.9, 98.8, and 98.9. This shows that the generated plans correctly preserve dependencies across multi-step tool calls. Since dependency errors can make otherwise plausible plans non-executable, these gains are important for reliable tool-use planning.

Prior planning baselines are less robust. Tool-Planner and ReAct are competitive in isolated cases, but their performance varies across backbones and datasets. For example, ToolPlanner achieves strong FM on Llama3.2-3B ToolHop, but FORTE dominates JSR across all settings and wins most structural metrics on NESTFUL. Meanwhile, α-UMi and GNN4TaskPlan perform poorly in most configurations, suggesting that methods relying on online execution feedback do not transfer well to offline plan generation.

FORTE benefits from stronger backbone models. The strongest structural results are obtained with Qwen2.5-7B, where FORTE wins all four met-

Table 3: Closed-source frontier reference. Models evaluated on 100 examples per benchmark with identical prompts, judge, and eval as our trained planners; greedy single-shot. **Best** (green shading) per column.

Method	ToolHop				NESTFUL			
	JSR	FM	PA	DA	JSR	FM	PA	DA
GPT-5-Nano	17.0	44.0	50.3	78.0	56.0	17.0	36.6	59.1
GPT-5.5	59.0	50.0	56.9	82.5	89.0	43.0	55.0	73.0
FORTE-Llama3B	92.9	80.2	63.6	98.9	**98.9**	37.2	60.2	84.0
FORTE-Qwen3B	96.6	89.2	69.5	98.8	97.7	33.6	56.2	87.8
FORTE-Qwen7B	**96.6**	**97.3**	**77.1**	**98.9**	98.6	**44.3**	**61.6**	**89.0**

rics within its backbone group on both ToolHop and NESTFUL. On ToolHop, it reaches 96.6 JSR, 97.3 FM, 77.1 PA, and 98.9 DA; on NESTFUL, it reaches 98.6 JSR, 44.3 FM, 61.6 PA, and 89.0 DA. This indicates that FORTE scales positively with backbone capacity rather than saturating at the 3B scale.

Closed models approach FORTE on NESTFUL but miss the strict format bar. GPT-5.5 reaches NESTFUL FM=43.0, within 1.3 points of FORTE-Qwen2.5-7B (44.3) and ahead of our smaller backbones as seen in Table 3. JSR however remains 9.6 points behind: GPT-5.5 produces semantically reasonable plans but consistently misses format, hallucinating parameter values absent from the tool signature and occasionally compressing multi-step plans (Appendix C, Example 5). Training on a curated failure taxonomy beats raw capacity where structural compliance matters most.

5 Discussion

In this section, we provide a discussion of the components of the FORTE pipeline and elaborate on key design choices and ablation studies conducted as part of our experiments.

Contrastive negatives are critical for judge training. Ablating the contrastive component of FORTE's judge by retraining on only perfect plans (quality_score=100) severely degrades the full system on Qwen2.5-3B / ToolHop: JSR drops 14.3 points, FM drops 20.9, and PA drops 12.8 Figure 2. The BoN gain inverts to -2.6 points, meaning the ablated judge's top-1 selection is on average 2.6 quality points worse than simply taking the lowest-temperature sample, and the judge labels 100% of its picks as successful. Without exposure to flawed plans, the judge loses discriminative ability and provides neither useful reward during GRPO nor

Figure 2: Comparison between training with FORTE's contrastive negatives error taxonomy versus not.

useful selection at inference. Damage is concentrated at the argument level, while DA is essentially unchanged (-0.3 points) since SFT already establishes that capability. The contrastive signal is therefore load-bearing rather than incidental: the same negatives that supply the judge's reward also supply the discriminative ability required at inference.

Best-of-N saturates quickly, justifying $N = 5$. Averaged across the three backbones on ToolHop, JSR rises from 93.15% at $N = 1$ to 95.36% at $N = 5$ and 95.87% at $N = 10$. The bulk of the achievable gain (+2.21 points) is captured by $N = 5$, with five further candidates contributing only +0.51 points. $N = 5$ thus realises roughly 80% of the $N = 10$ improvement at half the inference cost, keeping FORTE's per-query budget comparable to non-search baselines without sacrificing the candidate diversity the judge needs to discriminate.

Residual failures are bounded by FM's step-count requirement. We measure the fraction of judge-passing plans (judge ≥ 80) that also satisfy FM (FM=1: step-count match, $\geq 50\%$ tool-name Jaccard, and $\geq 50\%$ parameter accuracy jointly). On ToolHop, agreement is high and rises monotonically with backbone capacity: 80.4%, 89.5%, and 97.2% for Llama3.2-3B, Qwen2.5-3B, and Qwen2.5-7B. On NESTFUL the conditional drops to 37.1%, 33.6%, and 44.0%, but 79.2%, 75.4%, and 72.8% of NESTFUL FM failures across the three backbones are pure step-count mismatches with otherwise correct tool selection, parameter binding, and dependency threading (Appendix C, Example 4): the planner emits compressed plans that the rubric scores as valid but FM rejects for departing from the gold's exact step decomposi-

tion. The 97.2% ToolHop agreement of our largest backbone, where step-count compression is rarely viable, is consistent with this interpretation. The remaining 21–27% of NESTFUL FM failures involve true structural errors, motivating plan-length calibration as the natural next step rather than further work on the structural primitives FORTE already learns reliably.

Inference cost is comparable to baselines and dominated by open-source compute. FORTE's Best-of-N inference issues five planner forward passes and five parallel judge calls per query, matching ReAct (3–5 iterations) and TOOL-PLANNER (beam width 3 plus scoring) and well below tree-search methods like LATS or ToolTree (20–50 LLM calls). Running on local 3B–7B open-source backbones, per-query cost is dominated by GPU compute on commodity hardware, placing FORTE roughly an order of magnitude below closed-source frontier baselines while matching or beating them on plan quality (Table 3). Frontier-grade structural compliance is therefore achievable through targeted failure-mode training rather than scale.

6 Conclusion

We presented FORTE, a framework that trains multi-step tool planners by exposing them to a systematic taxonomy of failure modes during training. By grounding judge training in deductive structural scoring over a 9-error rubric and using contrastive negatives drawn from minimally edited gold plans, FORTE produces planners that achieve the highest Judge Success Rate across all six backbone and dataset configurations on ToolHop and NESTFUL, beating established baselines by 2.5 to 13.2 JSR points and exceeding GPT-5.5 by up to 33.9 points using only 3B to 7B open-source models. Our ablations show that contrastive exposure is the critical ingredient: without it, the judge loses discriminative ability and Best-of-N selection becomes counterproductive. FORTE's decoupled judge-planner architecture, together with the augmented contrastive datasets we construct for ToolHop and NESTFUL, transforms error taxonomies from post-hoc diagnostic instruments into the primary driver of training, suggesting a broader pattern: targeted exposure to failure modes during training is a simple and effective alternative to inference-time search and structural scaffolding for tool-augmented agents.

Limitations

We note several limitations. Firstly, FORTE trains a separate planner per benchmark: the augmented corpus, judge training, and RL fine-tuning are all dataset-specific. Secondly, our error taxonomy is derived from observed failure patterns in Tool-Hop and NESTFUL; additional error categories may exist in domains we do not evaluate, such as long-horizon GUI agents or browser-based tool use. Thirdly, the judge's deductive rubric scores syntactic plan correctness rather than semantic task success; this decoupling is what enables training stability without a tool execution environment, but it means FORTE does not directly optimize for end-task reward, and may miss failure modes that are only visible at execution time. Finally, the 9-error taxonomy treats each failure mode as independent; in practice plan errors can co-occur, and the judge is trained to detect but not necessarily to disentangle compound failures.

References

Kinjal Basu, Ibrahim Abdelaziz, Kiran Kate, Mayank Agarwal, Maxwell Crouse, Yara Rizk, Kelsey Bradford, Asim Munawar, Sadhana Kumaravel, Saurabh Goyal, and 1 others. 2025. Nestful: A benchmark for evaluating llms on nested sequences of api calls. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 33526–33535.

Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, and 1 others. 2025. Why do multi-agent llm systems fail? *arXiv preprint arXiv:2503.13657*.

Jinpeng Chen, Cheng Gong, Hanbo Li, Ziru Liu, Zichen Tian, Xinyu Fu, Shi Wu, Chenyang Zhang, Wu Zhang, Suiyun Zhang, and 1 others. 2026. Cove: Training interactive tool-use agents via constraint-guided verification. *arXiv preprint arXiv:2603.01940*.

Wenjie Chen, Wenbin Li, Di Yao, Xuying Meng, Chang Gong, and Jingping Bi. 2025. Gtool: Graph enhanced tool planning with large language model. *arXiv preprint arXiv:2508.12725*.

Zehui Chen, Weihua Du, Wenwei Zhang, Kuikun Liu, Jiangning Liu, Miao Zheng, Jingming Zhuo, Songyang Zhang, Dahua Lin, Kai Chen, and Feng Zhao. 2024. T-eval: Evaluating the tool utilization capability of large language models step by step. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9510–9529, Bangkok, Thailand. Association for Computational Linguistics.

Jae-Woo Choi, Hyungmin Kim, Hyobin Ong, Minsu Jang, Dohyung Kim, Jaehong Kim, and Youngwoo Yoon. 2025. Reactree: Hierarchical llm agent trees with control flow for long-horizon task planning. *arXiv preprint arXiv:2511.02424*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

Guanting Dong, Yifei Chen, Xiaoxi Li, Jiajie Jin, Hongjin Qian, Yutao Zhu, Hangyu Mao, Guorui Zhou, Zhicheng Dou, and Ji-Rong Wen. 2025. Tool-star: Empowering llm-brained multi-tool reasoner via reinforcement learning. *arXiv preprint arXiv:2505.16410*.

Han Han, Tong Zhu, Xiang Zhang, Mengsong Wu, Xiong Hao, and Wenliang Chen. 2025. Nestools: A dataset for evaluating nested tool learning abilities of large language models. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 9824–9844.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3.

Shiting Huang, Zhen Fang, Zehui Chen, Siyu Yuan, Junjie Ye, Yu Zeng, Lin Chen, Qi Mao, and Feng Zhao. 2025. Critictool: Evaluating self-critique capabilities of large language models in tool-calling error scenarios. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 26683–26692.

Tenghao Huang, Dongwon Jung, Vaibhav Kumar, Mohammad Kachuee, Xiang Li, Puyang Xu, and Muhao Chen. 2024. Planning and editing what you retrieve for enhanced tool learning. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 975–988, Mexico City, Mexico. Association for Computational Linguistics.

Shirley Kokane, Ming Zhu, Tulika Awalgaonkar, Jianguo Zhang, Thai Hoang, Akshara Prabhakar, Zuxin Liu, Tian Lan, Liangwei Yang, Juntao Tan, and 1 others. 2024. Toolscan: A benchmark for characterizing errors in tool-use llms. *arXiv preprint arXiv:2411.13547*.

Minghao Li, Yingxiu Zhao, Bowen Yu, Feifan Song, Hangyu Li, Haiyang Yu, Zhoujun Li, Fei Huang, and Yongbin Li. 2023. API-bank: A comprehensive benchmark for tool-augmented LLMs. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 3102–3116, Singapore. Association for Computational Linguistics.

Zhiwei Li, Yong Hu, and Wenqing Wang. 2025. Encouraging good processes without the need for good answers: Reinforcement learning for llm agent planning. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 1654–1666.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*.

Xukun Liu, Zhiyuan Peng, Xiaoyuan Yi, Xing Xie, Lirong Xiang, Yuchen Liu, and Dongkuan Xu. 2024. Toolnet: Connecting large language models with massive tools via tool graph. *arXiv preprint arXiv:2403.00839*.

Elias Lumer, Pradeep Honaganahalli Basavaraju, Myles Mason, James A Burke, and Vamse Kumar Subbiah. 2025. Graph rag-tool fusion. *arXiv preprint arXiv:2502.07223*.

Zixian Ma, Weikai Huang, Jieyu Zhang, Tanmay Gupta, and Ranjay Krishna. 2024. m & m's: A benchmark to evaluate tool-use for m ulti-step m ulti-modal tasks. In *European Conference on Computer Vision*, pages 18–34. Springer.

Shishir G Patil, Tianjun Zhang, Xin Wang, and Joseph E Gonzalez. 2024. Gorilla: Large language model connected with massive apis. *Advances in Neural Information Processing Systems*, 37:126544–126565.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, and 1 others. 2023. Toolllm: Facilitating large language models to master 16000+ real-world apis. *arXiv preprint arXiv:2307.16789*.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. *Advances in neural information processing systems*, 36:68539–68551.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Weizhou Shen, Chenliang Li, Hongzhan Chen, Ming Yan, Xiaojun Quan, Hehong Chen, Ji Zhang, and Fei Huang. 2024a. Small LLMs are weak tool learners: A multi-LLM agent. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 16658–16680, Miami, Florida, USA. Association for Computational Linguistics.

Yongliang Shen, Kaitao Song, Xu Tan, Dongsheng Li, Weiming Lu, and Yueting Zhuang. 2023. Hugginggpt: Solving ai tasks with chatgpt and its friends in hugging face. *Advances in Neural Information Processing Systems*, 36:38154–38180.

Yongliang Shen, Kaitao Song, Xu Tan, Wenqi Zhang, Kan Ren, Siyu Yuan, Weiming Lu, Dongsheng Li, and Yueting Zhuang. 2024b. Taskbench: Benchmarking large language models for task automation. *Advances in Neural Information Processing Systems*, 37:4540–4574.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652.

Jimin Sun, So Yeon Min, Yingshan Chang, and Yonatan Bisk. 2024. Tools fail: Detecting silent errors in faulty tools. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 14272–14289, Miami, Florida, USA. Association for Computational Linguistics.

Eduardo Treviño, Hugo Contant, James Ngai, Graham Neubig, and Zora Zhiruo Wang. 2025. Benchmarking failures in tool-augmented language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 2916–2934.

Cailin Winston and René Just. 2025. A taxonomy of failures in tool-augmented llms. In *2025 IEEE/ACM International Conference on Automation of Software Test (AST)*, pages 125–135. IEEE.

Qinzhuo Wu, Wei Liu, Jian Luan, and Bin Wang. 2024a. Toolplanner: A tool augmented llm for multi granularity instructions with path planning and feedback. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 18315–18339.

Shirley Wu, Shiyu Zhao, Qian Huang, Kexin Huang, Michihiro Yasunaga, Kaidi Cao, Vassilis N Ioannidis, Karthik Subbian, Jure Leskovec, and James Zou. 2024b. Avatar: Optimizing llm agents for tool usage via contrastive reasoning. *Advances in Neural Information Processing Systems*, 37:25981–26010.

Xixi Wu, Yifei Shen, Caihua Shan, Kaitao Song, Siwei Wang, Bohang Zhang, Jiarui Feng, Hong Cheng, Wei Chen, Yun Xiong, and 1 others. 2024c. Can graph learning improve planning in llm-based agents? *Advances in Neural Information Processing Systems*, 37:5338–5383.

Shuo Yang, Soyeon Caren Han, Yihao Ding, Shuhe Wang, and Eduard Hoy. 2026. Tooltree: Efficient llm agent tool planning via dual-feedback monte carlo tree search and bidirectional pruning. *Preprint*, arXiv:2603.12740.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*.

Junjie Ye, Zhengyin Du, Xuesong Yao, Weijian Lin, Yufei Xu, Zehui Chen, Zaiyuan Wang, Sining Zhu, Zhiheng Xi, Siyu Yuan, and 1 others. 2025. Toolhop: A query-driven benchmark for evaluating large language models in multi-hop tool use. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2995–3021.

Yuanqing Yu, Zhefan Wang, Weizhi Ma, Shuai Wang, Chuhan Wu, Zhiqiang Guo, and Min Zhang. 2025. Steptool: Enhancing multi-step tool usage in llms via step-grained reinforcement learning. In *Proceedings of the 34th ACM International Conference on Information and Knowledge Management*, pages 3952–3962.

Shiqi Zhang, Xinbei Ma, Zouying Cao, Zhuosheng Zhang, and Hai Zhao. 2025. Plan-over-graph: Towards parallelable llm agent schedule. *arXiv preprint arXiv:2502.14563*.

Andy Zhou, Kai Yan, Michal Shlapentokh-Rothman, Haohan Wang, and Yu-Xiong Wang. 2023. Language agent tree search unifies reasoning acting and planning in language models. *arXiv preprint arXiv:2310.04406*.

Yuchen Zhuang, Xiang Chen, Tong Yu, Saayan Mitra, Victor Bursztyn, Ryan A Rossi, Somdeb Sarkhel, and Chao Zhang. 2023. Toolchain*: Efficient action space navigation in large language models with a* search. *arXiv preprint arXiv:2310.13227*.

Appendix

A   Extended Related Work

We elaborate here on the four families of work surveyed in Section 2, covering papers omitted from the main text for space.

Additional multi-step tool planning benchmarks. The broader single-step function-calling literature includes Gorilla (Patil et al., 2024) and Huang et al. (2024). Beyond ToolBench/ToolLLM, API-Bank (Li et al., 2023) established large-scale training and evaluation settings, while Hugging-GPT (Shen et al., 2023) and TaskBench (Shen et al., 2024b) demonstrated tool selection over structured dependency graphs. NesTools (Han et al., 2025) complements NESTFUL with four fine-grained evaluation dimensions including nested parameter filling; m&m (Ma et al., 2024) introduces 4K+ multi-step multimodal tasks across 33 tools; and T-Eval (Chen et al., 2024) decomposes multi-step performance into planning, retrieval, and review sub-scores.

Additional test-time search and structural scaffolding methods. Beyond ReAct and ToolTree, Reflexion (Shinn et al., 2023) added iterative verbal self-refinement, ToT (Yao et al., 2023) introduced tree-of-thought reasoning, and ToolChain* (Zhuang et al., 2023) applied A* search over tool sequences. ReAcTree (Choi et al., 2025) further extends search-based methods by replacing flat trajectories with a dynamically expanding agent tree, using behavior-tree control flow to coordinate subgoal-specialized agents and extending ReAct and least-to-most prompting into hierarchical planning. On the structural scaffolding side, GTool (Chen et al., 2025) and ToolNet (Liu et al., 2024) encode inter-tool dependency graphs via GNNs or directed graph navigation; Graph RAG-Tool Fusion (Lumer et al., 2025) combines retrieval with depth-first graph traversal; and Plan-over-Graph (Zhang et al., 2025) enables parallelizable agent scheduling.

Additional RL and contrastive training methods. RLTR (Li et al., 2025) uses tool-use completeness rewards with distillation-based cold-start. Tool-Star (Dong et al., 2025) combines cold-start fine-tuning with hierarchical multi-level RL across six tool types. CoVe (Chen et al., 2026) uses deterministic task-specific constraints as verifiable reward signals for SFT and RL. As with the meth-

ods discussed in the main text, supervision in each of these frameworks ultimately reduces to coarse execution outcomes rather than structured error labels.

Additional failure taxonomies and diagnostic benchmarks. A taxonomy of failures in tool-augmented LLMs (Winston and Just, 2025) surfaces dependency, specification, and state-desynchronization errors across Gorilla and Chameleon deployments. Sun et al. (2024) specifically study silent errors from malformed tool outputs. At the multi-agent level, MASFT (Cemri et al., 2025) identifies 14 failure modes across five open-source systems, finding that prompt-engineering interventions yield only modest gains, reinforcing the case for training-time solutions.

B Prompts

This appendix collects the prompts used by FORTE verbatim from the released codebase. There are three distinct prompts: the *annotation prompt* (§B.1) used by GPT-5.4 to generate training labels for the judge; the *judge inference prompt* (§B.2) sent to the trained judge during GRPO reward computation and Best-of-N selection; and the *planner prompt* (§B.3) used identically for SFT, GRPO, and BoN inference.

B.1 Annotation Prompt

GPT-5.4 is prompted with the deductive rubric below, which assigns a base score of 100 and subtracts points per identified syntactic error according to a four-tier severity scale (critical -30, high -20, medium -10, low -5). The rubric explicitly forbids the judge from flagging semantic issues or type-checking parameters containing dependency references {{N}}.

System message : annotation judge

```
You are an expert at evaluating multi-step tool execution
plans. You only check syntactic correctness, not semantic
correctness. NEVER type-check parameters containing {{N}}
- they are dependency references and are always type-valid.
```

User message : annotation judge

```
You are evaluating a multi-step tool execution plan using
an OBJECTIVE ERROR-BASED RUBRIC.

**USER QUERY:** {query}
**AVAILABLE TOOLS:** {tools_desc}
**PROPOSED PLAN:** {plan_desc}
**GROUND TRUTH PLAN (for reference):** {ground_truth_desc}
```

```
================================================================
OBJECTIVE SCORING RUBRIC
================================================================

SCORING FORMULA:
1. Start with a base score of 100.
2. Identify ALL errors in the plan.
3. For EACH error, deduct points based on severity:
   - CRITICAL error: -30 points
   - HIGH error:     -20 points
   - MEDIUM error:   -10 points
   - LOW error:       -5 points
4. Final score = max(0, 100 - total_deductions)

================================================================
SYNTAX-ONLY EVALUATION
================================================================

Check ONLY syntactic correctness:
 - Are all required parameters provided?
 - Are LITERAL parameter types correct (skip values
containing {{N}})?
 - Are dependencies valid (no forward refs, no circular
deps)?
 - Are all steps present to complete the task?
 - Is the tool name spelled correctly?

Do NOT check semantics:
 - Whether tool outputs will work together
 - Whether the plan produces the correct final answer
 - Whether tool choice "makes sense" for the task
 - Whether parameter VALUES produce the right result

ABSOLUTE RULE: any parameter value containing {{N}} is a
dependency
reference and is ALWAYS type-valid. Skip type checking
entirely.
Quotes around {{N}} do NOT make it a literal string.

================================================================
ERROR SEVERITY DEFINITIONS
================================================================

CRITICAL (-30): missing required param; circular
dependency; non-existent
   tool; forward reference; literal-value type mismatch;
missing critical step.
HIGH (-20):     hardcoded value where {{N}} expected;
incorrect parameter
   value changing output significantly; missing non-
critical step.
MEDIUM (-10):   inefficient ordering (works but suboptimal
); typo in
   parameter value; unnecessary step that doesn't break the
plan.
LOW (-5):       minor formatting; non-standard but
functional format;
   trivial inefficiency; style issues.

SUCCESS PREDICTION MAPPING:
  90-100 -> "yes"       75-89 -> "likely_yes"
  50-74  -> "uncertain"  25-49 -> "likely_no"   0-24 -> "
no"

================================================================
YOUR TASK
================================================================

1. IDENTIFY ALL ERRORS step by step.
2. CLASSIFY SEVERITY using the rubric above.
3. CALCULATE SCORE: start at 100, deduct per error.
4. SHOW YOUR WORK in the "reasoning" field.

RESPONSE FORMAT (JSON only, no markdown):
{
  "quality_score": <0-100>,
  "success_prediction": "<yes|likely_yes|uncertain|
likely_no|no>",
  "confidence": <0.0-1.0>,
  "reasoning": "Base score: 100\nError 1: [severity]
description (-X)\n...\nFinal score: Z",
  "issues": [
```

```
        {
            "type": "type_mismatch|missing_dependency|wrong_tool
    |parameter_typo|
                        circular_dependency|inefficient_order|
    incomplete_plan|
                        unnecessary_steps|forward_reference|other",
            "severity": "critical|high|medium|low",
            "step": <step_number or null>,
            "description": "Specific description of the error",
            "suggestion": "How to fix this error",
            "points_deducted": <30|20|10|5>
        }
    ]
}
```

B.2 Judge Inference Prompt

At RL training time, the trained judge receives the prompt below to produce a reward signal for GRPO; at inference time, the same prompt is used to score each of the N candidate plans for Best-of-N selection. The system message and JSON output schema match the annotation prompt above so the judge can be trained end-to-end on the GPT-5.4 annotations.

> **System message : inference judge**
>
> ```
> You are an expert judge for evaluating tool execution
> plans. Your task is to:
> 1. Analyze the plan's correctness and efficiency
> 2. Assign a quality score (0-100)
> 3. Predict success likelihood (yes/likely_yes/uncertain/
> likely_no/no)
> 4. Identify specific issues with severity levels
> 5. Provide detailed reasoning
>
> Scoring guidelines:
> - 100:   Perfect execution, no errors
> - 80-99: Minor issues, likely to succeed
> - 60-79: Moderate issues, uncertain outcome
> - 40-59: Major issues, likely to fail
> - 0-39:  Critical errors, will fail
> ```

> **User message : inference judge**
>
> ```
> Query: {query}
>
> {tools_desc}
>
> Plan to Evaluate:
> {plan_str}
>
> Please evaluate this plan and provide:
> 1. Quality score (0-100)
> 2. Success prediction (yes/likely_yes/uncertain/likely_no/
> no)
> 3. Detailed reasoning
> 4. List of issues (if any)
> 5. Confidence (0.0-1.0)
>
> Format your response as JSON:
> {
>     "quality_score":      <int>,
>     "success_prediction": "<string>",
>     "reasoning":          "<string>",
>     "issues":             [...],
>     "confidence":         <float>
> }
> ```

B.3 Planner Prompt

The same prompt template is used for SFT, GRPO, and inference, ensuring that no distribution shift is introduced between training and deployment. The user message instructs the planner to use {{N}} variables for dependency threading and the exact parameter names from the tool signatures.

> **System message : planner**
>
> ```
> You are an expert at creating multi-step tool execution
> plans. Given a query and available tools, generate a
> correct sequence of tool calls to answer the query.
> ```

> **User message : planner**
>
> ```
> Generate a tool execution plan to answer this query.
>
> Query: {question}
>
> {tools_desc}
>
> Generate a step-by-step plan using the available tools.
> Each step should:
> 1. Call exactly one tool
> 2. Use output variables {{0}}, {{1}}, {{2}}, etc. for
> results
> 3. Reference previous step outputs using {{N}} - never
> substitute a hardcoded
>     value for an output that comes from a prior step
> 4. Use the exact parameter names shown in the tool
> signatures above
> 5. Provide all required parameters
>
> Generate only the steps the query requires - no redundant
> steps, no missing steps.
>
> Format each step as: Step N: {{N}} = tool_name(param1=
> value1, param2=value2, ...)
> ```

C   Qualitative Examples

We present five qualitative examples drawn from our held-out evaluation: two perfect plans (one per benchmark), one example of FORTE producing a correct plan despite the reference being seeded with a wrong-tool error, one residual failure that exposes a secondary failure mode, and one closed-source comparison illustrating GPT-5.5's hallucinated parameters and compressed step counts.

Example 1: ToolHop : complete multi-hop plan with full dependency threading (judge=100).

> **ToolHop query 1 : FORTE-Qwen2.5-7B, $T=1.0$**
>
> ```
> QUERY:
> What is the sum of the (unique) prime factors of the year
> when the
> actress that plays Kaylee Frye in the series "Firefly"
> also stars with
> Alan Dale in a sci-fi tv film released in?
>
> GENERATED PLAN:
> Step 0: {{0}} = character_actor_lookup(character_name='
> Kaylee Frye',
> ```

```
        series_name='Firefly', exact_match=True,
case_sensitive=False)
Step 1: {{1}} = film_release_year_finder(actors=['{{0}}',
'Alan Dale'],
        genre='sci-fi')
Step 2: {{2}} = prime_factorization(number={{1}},
        output_format='unique_list', algorithm='
general_purpose')
Step 3: {{3}} = sum_digits(number={{2}}, output_format='
number')

JUDGE: score=100, prediction="yes", confidence=0.98.
```

All three intra-plan references ($\{\{0\}\}, \{\{1\}\}, \{\{2\}\}$) are correctly threaded; step count, tool selection, and dependency accuracy all reach 1.0 against the perfect reference.

Example 2: NESTFUL : exact match to the gold plan (judge=100).

> **NESTFUL query 5 : FORTE-Qwen2.5-7B, T=0.2**
>
> ```
> QUERY:
> Find the unique common values in two lists [1, 2, 3, 4, 5]
>  and
> [4, 5, 6, 7, 8]. Then, swap the values at index 0 and 1 in
>  the
> resulting list.
>
> GENERATED PLAN:
> Step 0: {{0}} = unique_common_values(list1=[1, 2, 3, 4,
> 5],
>        list2=[4, 5, 6, 7, 8])
> Step 1: {{1}} = swap_by_index(values={{0}}, i=0, j=1)
>
> JUDGE: score=100, prediction="yes", confidence=0.99.
> ```

The lowest-temperature candidate suffices; all four structural metrics (exact match, functional match, parameter accuracy, dependency accuracy) equal 1.0.

Example 3: Wrong-tool robustness (NESTFUL).

> **NESTFUL query 5 : reference seeded with wrong_tool**
>
> ```
> QUERY: (same as Example 2)
>
> REFERENCE PLAN (deliberately flawed : wrong_tool):
> Step 0: {{0}} = unique_common_values(list1=[1, 2, 3, 4,
> 5],
>        list2=[4, 5, 6, 7, 8])
> Step 1: {{1}} = non_whitespace_substrings(values={{0}}, i
> =0, j=1)
>
> \textsc{Forte} GENERATED PLAN ($T{=}0.2$):
> Step 0: {{0}} = unique_common_values(list1=[1, 2, 3, 4,
> 5],
>        list2=[4, 5, 6, 7, 8])
> Step 1: {{1}} = swap_by_index(values={{0}}, i=0, j=1)
>
> JUDGE: score=100, prediction="yes", confidence=0.99.
> ```

Although the dataset's reference for this query was seeded with the wrong tool (non_whitespace_substrings), FORTE generates the correct swap_by_index call directly from the query, demonstrating that exposure to wrong-tool negatives during training does not bias the planner toward reproducing them.

Example 4: Residual failure : step-count compression on NESTFUL (judge=100, FM fails).

> **NESTFUL query 34 : FORTE-Qwen2.5-7B, T=0.4**
>
> ```
> QUERY:
> If n is a prime number greater than 5, what is the
> remainder when n^2
> is divided by 12?
>
> GOLD PLAN (4 steps):
> Step 0: {{0}} = add(arg_0=5, arg_1=2)
> Step 1: {{1}} = power(arg_0={{0}}, arg_1=2)
> Step 2: {{2}} = multiply(arg_0=12, arg_1=4)
> Step 3: {{3}} = subtract(arg_0={{1}}, arg_1={{2}})
>
> \textsc{Forte} GENERATED PLAN (3 steps, all 5 candidates
> scored 100):
> Step 0: {{0}} = multiply(arg_0=4, arg_1=3)
> Step 1: {{1}} = divide(arg_0={{0}}, arg_1=2)
> Step 2: {{2}} = power(arg_0={{1}}, arg_1=2)
>
> JUDGE: score=100, prediction="yes", confidence=0.99.
> STRUCTURAL EVAL: step_count_match=False (3 vs 4),
>            exact_tool_accuracy=0.0, functional_match
> =False.
> ```

This is the dominant NESTFUL FM failure mode: the planner compresses the 4-step gold decomposition into a 3-step solution composed of compound arithmetic calls, which the rubric-based judge correctly scores as syntactically valid but which the structural evaluator marks as a functional-match failure due to the step-count mismatch. The judge's deductive rubric does not verify that the compressed plan computes the same intermediate values as the gold, exposing the syntactic-only scoring limitation discussed in the Limitations section.

Example 5: FORTE vs GPT-5.5 on the same ToolHop query.

> **ToolHop query 1 : GPT-5.5 (closed-source frontier, T=0.0)**
>
> ```
> QUERY: (same as Example 1)
>
> GPT-5.5 GENERATED PLAN:
> Step 0: {{0}} = character_actor_lookup(character_name="
> Kaylee Frye",
>        series_name="Firefly", exact_match=true)
> Step 1: {{1}} = film_release_year_finder(actors=[{{0}}, "
> Alan Dale"],
>        genre="sci-fi", additional_filters={"format": "tv
> film"})
> Step 2: {{2}} = prime_factorization(number={{1}},
>        output_format="sum_unique_prime_factors")
>
> JUDGE: score=70, prediction="uncertain", confidence=0.78.
> Step count: 3 vs gold's 4 (step_count_match=False).
> ```

GPT-5.5 exhibits two of the failure modes FORTE's training data systematically penalises: (i) it hallucinates an additional_filters

parameter that does not appear in the `film_release_year_finder` signature, and an `output_format="sum_unique_prime_factors"` enum value that does not exist; (ii) it compresses the plan from four steps to three, folding the final `sum_digits` call into a non-existent `prime_factorization` output format. FORTE's plan for the same query (Example 1) issues four schema-compliant steps and scores 100.