OFFLINE REINFORCEMENT LEARNING FOR LARGE SCALE LANGUAGE ACTION SPACES

ABSTRACT

Training a task-oriented dialogue agent can be naturally formulated as offline reinforcement learning (RL) problem, where the agent aims to learn a conversational strategy to achieve user goals, only from a dialogue corpus. It is very challenging in terms of RL since the natural language action space is infinitely large, while feasible (syntactically and semantically correct) actions are very sparse. Thus, standard RL methods easily fail and generate responses diverging from human language, even when fine-tuning a powerful pre-trained language model. In this paper, we introduce GPT-Critic, an offline RL method for task-oriented dialogue. GPT-Critic is built upon GPT-2, fine-tuning the language model through behavior cloning of the critic-guided self-generated sentences. GPT-Critic is essentially free from the issue of diverging from human language since it learns from the sentences sampled from the pre-trained language model. In the experiments, we demonstrate that our algorithm outperforms the state-of-the-art in task-oriented dialogue benchmarks including MultiWOZ and ConvLab.

1 INTRODUCTION

Building an end-to-end task-oriented dialogue agent is one of the promising applications of natural language processing (NLP) tasks, yet challenging due to large language action spaces and limited availability of human-annotated data. Recently, large-scale pre-trained language models (LM) have achieved remarkable successes in various NLP tasks with prohibitively large vocabulary (Devlin et al., 2019; Radford et al., 2019; Brown et al., 2020; Raffel et al., 2019). The current best performing end-to-end conversational agents for a task-oriented dialogue system utilize a pre-training on large-scale corpus and fine-tuning on downstream tasks (Ham et al., 2020; Yang et al., 2021; Lin et al., 2020; Peng et al., 2021). This combination of pre-training and fine-tuning significantly improves overall performance in task-oriented dialogues. However, supervised fine-tuning (i.e. imitation learning of the dialogue corpus) alone may not be sufficient to learn an optimal dialogue strategy since the corpus often contains suboptimal dialogues collected from human participants of diverse expertise levels. Thus, in order to optimize the task performance of the conversational agent, goal-oriented training (i.e. reinforcement learning) is an essential and promising direction to pursue.

Training a task-oriented conversational agent from a dialogue corpus can be naturally formulated as offline reinforcement learning (RL) problem (Levine et al., 2020; Fujimoto et al., 2019; Jaques et al., 2020), which offers the prospect to optimize the policy solely from the fixed dataset without online environment interaction. Most of the existing offline RL methods are built on the off-policy Actor-Critic framework, which performs iterative optimization of the policy (i.e. actor) and the action-value function (i.e. critic) (Fujimoto et al., 2019; Janner et al., 2019; Kumar et al., 2020). Yet, a naive application of these offline RL methods generally results in poor dialogue strategies which generate responses in no way similar to human language (Lewis et al., 2017; Zhao et al., 2019; Jang et al., 2020).

To mitigate the aforementioned problem, discrete latent representation models for language actions have been proposed to disentangle the semantics of the utterance and the natural language generation (Zhao et al., 2019; Yarats & Lewis, 2018). In that framework, goal-based training was performed in the space of the discrete latent variables instead of directly optimizing utterances. While these approaches can prevent degenerate responses in principle, they cannot be straightforwardly applied to widely used large-scale LMs since most of them are not trained to for discrete latent variables. One

Figure 1: Overall architecture of GPT-Critic.

could make modifications to the LM to work with discrete latent variables but it would need to be pre-trained from scratch with a tremendous amount of data and time, which is undesirable.

In this paper, we present an offline RL algorithm for task-oriented dialogue, which can be adopted for any generative pre-trained language model. Our algorithm, GPT-Critic, does not rely on policy gradient unlike actor-critic methods and is essentially free from the issue of diverging from human language. It starts with fine-tuning the GPT-2 and learning the action-value function (critic) using the dialogue corpus. Then, GPT-Critic generates strategically promising action that is selected based on the value estimated by the critic. GPT-Critic updates the policy through behavior cloning of the critic-guided self-generated responses. This is in contrast to the previous methods that perform weighted behavior cloning on the dialogue corpus, where the action choice is restricted to the support in the dataset (Wang et al., 2020). Since GPT-Critic does not rely on policy gradient and updates the policy within the support of generated actions from the GPT-2, it thus inherits GPT-2's ability to generate human-like responses. In the experiments, we demonstrate that GPT-Critic outperforms the state-of-the-art end-to-end dialogue agent in task-oriented dialogue benchmarks including MultiWOZ (Budzianowski et al., 2018) and ConvLab (Zhu et al., 2020).

2 BACKGROUND

2.1 OFFLINE REINFORCEMENT LEARNING

We consider the task-oriented dialogue system that can be modeled as a partially observable Markov decision process (POMDP) defined by tuple $\langle S, A, O, T, Z, R, \gamma \rangle$ where $\mathcal{S}$ is the set of environment states s (underlying state that consists of user goal and dialogue state), A is the set of actions a (system action and response), O is the set of observations o (user utterance), $T(s'|s, a) = \Pr(s_{t+1} = s'|s_t = s, a_t = a)$ is the transition function, $Z(o|s', a) = Pr(o_{t+1} = o|s_{t+1} = s', a_t = a)$ is the observation probability, $R(h, a, g)$ is the reward function indicating the utility of executing action a in history h and user goal g, and $\gamma \in (0, 1)$ is a discount factor. The history at time step t, $h_t = \{o_0, a_0, \ldots o_{t-1}, a_{t-1}, o_t\}$, is a sequence of all previous observations and actions. The policy $\pi(a_t|h_t)$ is mapping from history h_t to a probability distribution over A. The goal is to find an optimal policy π^* that maximizes the expected cumulative rewards, i.e. $\pi^* = \arg\max_\pi \mathbb{E}_\pi \left[\sum_{t=0}^\infty \gamma^t R(h_t, a_t, g) \right]$. The action-value function of policy π is defined as $Q^\pi(h, a) := \mathbb{E}_\pi \left[\sum_{t=0}^\infty \gamma^t R(h_t, a_t, g)|h_0 = h, a_0 = a \right]$, where Q^π is a unique solution of the Bellman equation:

$$Q^\pi(h, a) = R(h, a, g) + \gamma \mathbb{E}_\pi \left[Q^\pi(h', a') \right] \tag{1}$$

Figure 2: Architecture of policy and critic network based on GPT-2.

In offline RL, the agent optimizes the policy from the pre-collected dataset $\mathcal{D} = \{(h_i, a_i, r_i, h_i')\}_{i=1}^N$ without online environment interaction during the intermediate stages of training. We focus on the MultiWOZ dataset (Budzianowski et al., 2018), which is a representative benchmark for task-oriented dialogue. The MultiWOZ dataset is a fully-annotated corpus of human-human task-oriented conversations, which is collected via the Wizard-of-Oz setting (Kelley, 1984).

2.2 END-TO-END TASK-ORIENTED DIALOGUE SYSTEM

The traditional approach to building a task-oriented dialogue system adopts a modular pipeline, which consists of the following four modules: 1) A natural language understanding (NLU) module (Kim et al., 2017; Zhu et al., 2020) identifies the user's intent and extracts the information of slots and their values, 2) A Dialogue state tracking (DST) module (Williams et al., 2013) infers the belief state, 3) A dialogue policy (POL) module decides the system action, 4) A natural language generation (NLG) module (Wen et al., 2015) generates the system response corresponding to the system action. Recently, end-to-end task-oriented dialogue methods leveraging the pre-trained language model have been proposed (Yang et al., 2021; Ham et al., 2020; Lin et al., 2020; Peng et al., 2021; Hosseini-Asl et al., 2020), and significantly improves overall performance in task-oriented dialogues. In this paper, our algorithm is built upon UBAR (Yang et al., 2021), which is based on GPT-2 (Radford et al., 2019) and currently the state-of-the-art end-to-end dialogue agent for the MultiWOZ domain.

3 OFFLINE REINFORCEMENT LEARNING FOR TASK-ORIENTED DIALOGUES

The corpus collected from human-human conversations inevitably contains unsuccessful dialogues in terms of task completion. For example, approximately 20% dialogues of the MultiWOZ dataset fail to meet the user goal. Therefore, a naive behavior cloning of the whole dataset would limit the performance of the conversational agent since the dataset includes a lot of unsuccessful dialogues: an agent that imitates failure would be inevitably suboptimal. Yet, dropping the unsuccessful dialogues from the corpus is also undesirable, since they may contain some task-specific information that is useful to properly respond to user requests. We thus aim to *revise* unsuccessful dialogues into successful ones in order to prevent repeating the past failure while improving the task performance. In this section, we present GPT-Crtic, an offline RL algorithm for task-oriented dialogue that performs behavior cloning of the critic-guided self-generated responses. Our algorithm is built upon the GPT-2 but it can be adopted for any generative pre-trained language model.

3.1 POLICY EVALUATION

The GPT-Critic starts by training action-value function (i.e. critic), which can evaluate the candidates for the response. The architecture of critic network basically follows GPT-2 with employing different last layers to compute the Q-value. The parameterization of critic network Q_ϕ is designed to share the parameters of the Transformer (Vaswani et al., 2017) layers of GPT-2, where the parameters of

---

Algorithm 1 GPT-Critic

Input: Training dataset $\mathcal{D}_0 = \{(h_i, a_i, r_i, h'_i)\}_{i=1}^N$, policy network π_θ, critic network Q_ϕ

for each iteration i **do**

  Update critic by minimizing the temporal difference error until convergence:

$$\arg\min_\phi \mathbb{E}_{(h_t, a_t, h_{t+1}, r_t) \sim \mathcal{D}_i} \left[\left(r_t + \gamma \mathbb{E}_{a_{t+1} \sim \pi(h_{t+1})} \left[Q_{\bar\phi}(h_{t+1}, a_{t+1}) \right] - Q_\phi(h_t, a_t) \right)^2 \right]$$

  Update dataset by critic-guided self-generation:

$$\mathcal{D}_{i+1} = \{(h_t, a_t^*, r_t^*, h_{t+1}^*) \mid a_t^* = \arg\max_{\substack{a \in \{a_i\}^N \\ \{a_i\}^N \sim \pi(h_t)}} Q_\phi(h_t, a) \text{ where } h_t \in \mathcal{D}_i\}$$

  Update policy by behavior cloning of critic-guided self-generated dataset until convergence:

$$\arg\min_\theta \mathbb{E}_{(h_t, a_t) \sim \mathcal{D}_{i+1}} \left[-\log \pi_\theta(a_t | h_t) \right]$$

end for

---

the Transformer layers are only updated during the policy improvement step. The critic network is trained by minimizing the temporal difference error:

$$\arg\min_\phi \mathbb{E}_{(h_t, a_t, h_{t+1}, r_t) \sim \mathcal{D}_i} \left[\left(r_t + \gamma \mathbb{E}_{a_{t+1} \sim \pi_i(h_{t+1})} \left[Q_{\bar\phi}(h_{t+1}, a_{t+1}) \right] - Q_\phi(h_t, a_t) \right)^2 \right] \quad (2)$$

where $\mathcal{D}_i$ is a dataset for i-th iteration and $\bar\phi$ is the parameters of the target network.

As discussed in the prior work on offline RL, optimizing this loss can be problematic in an offline RL setting due to the overestimation issue in the bootstrapping process by taking out-of-distribution (OOD) actions to evaluate the value of the next state (Fujimoto et al., 2019; Kumar et al., 2020). However, we avoid this OOD problem by generating a new dataset based on offline automatic evaluation in task-oriented dialogue setting. The agent can generate a new dataset that is revised by generated system response and evaluated reward using offline automatic evaluation.

3.2 POLICY IMPROVEMENT

For the policy improvement step, we adopt the RL setup from (Zhao et al., 2019) that generates the response on every system turn and computes the reward without alteration of the original dialogue at every turn. More formally, the GPT-Critic generates a new dataset containing *revised* responses by:

$$\mathcal{D}_{i+1} = \{(h_t, a_t^*, r_t^*, h_{t+1}^*) \mid a_t^* = \arg\max_{\substack{a \in \{a_k\}^N \\ \{a_k\}^N \sim \pi_i(h_t)}} Q_\phi(h_t, a) \text{ where } h_t \in \mathcal{D}_i\} \quad (3)$$

where $\{a_k\}^N$ is a set of N response candidates generated from the policy π (i.e. fine-tuned GPT-2), and $\mathcal{D}_i$ is the dataset at the current iteration. In order to address the prohibitory large language action spaces, we explicitly consider the set of response candidates that are generated from the fine-tuned GPT-2. The GPT-Critic selects the most promising response by calculating the Q-values over response candidates. GPT-Critic then performs behavior cloning of critic-guided self-generated dialogues:

$$\arg\min_\theta \mathbb{E}_{(h_t, a_t) \sim \mathcal{D}_{i+1}} \left[-\log \pi_\theta(a_t | h_t) \right] \quad (4)$$

where θ is the parameters of GPT-2. The policy improvement of GPT-Critic is performed by behavior cloning of generated dialogues from the GPT-2, thus GPT-Critic inherits GPT-2's ability to generate human-like responses.

We can theoretically show that updated policy by above policy improvement step has a higher value than the old policy. We formalize this result in Theorem 1.

	Inform	Success
TRAINING DATA	92.10	80.45
UPDATED DATA (1)	94.60	84.47
UPDATED DATA (2)	95.35	86.04
UPDATED DATA (3)	**95.85**	**87.05**

Table 1: The performance of training dataset and self-generated dialogues being used for each iteration of policy improvement step.

	Inform	Success	BLEU	Combined Score
POLICY ITERATION (1)	87.23	74.73	17.43	98.42
POLICY ITERATION (2)	89.30	76.20	17.58	100.33
POLICY ITERATION (3)	89.83	**77.33**	17.36	100.95
POLICY ITERATION (4)	**90.07**	76.63	**17.78**	**101.13**

Table 2: Experimental results for the policy improvement with GPT-Critic on MultiWOZ dataset.

Theorem 1. *(Policy Improvement) Given a policy π and the number of sampling actions N, If we update the new policy π^{new} by*

$$\forall s, a, \pi^{new}(s, a) = \underset{\substack{a \in \{a_k\}^N \\ \{a_k\}^N \sim \pi(s)}}{\arg\max} \; Q^{\pi}(s, a)$$

then $Q^{\pi^{new}}(s, a) \geq Q^{\pi}(s, a)$ holds for all s, a. (Proof in Appendix A.)

We describe our algorithm, GPT-Critic, in Algorithm 1, that alternates between policy evaluation and policy improvement steps via iterative generation of revised dataset until the policy performance converges.

4 EXPERIMENTS

In this section, we show the experimental results of GPT-critic on both dataset-based and simulator-based automatic evaluations. First, we evaluate the performances of GPT-Critic on MultiWOZ domain (Budzianowski et al., 2018) as dataset-based automatic evaluation, compared with baseline methods including offline RL algorithms. Second, for more realistic evaluation, we conduct a simulator-based evaluation on ConvLab framework (Zhu et al., 2020). Finally, we give a qualitative analysis of our method using generated dialogue examples on the training dataset of MultiWOZ, which shows how GPT-Critic improves the performance through the behavior cloning of self-generated dialogues.

4.1 IMPLEMENTATION DETAILS

We implement GPT-Critic based on HuggingFace Transformers library (Wolf et al., 2019) and codebase of UBAR (Yang et al., 2021), which is a GPT-2-based current state-of-the-art end-to-end task-oriented dialogue agent for the MultiWOZ domain. For the generative pre-trained language model, we use DistilGPT2 (Sanh et al., 2019), a distilled version of GPT-2. Figure 2 shows the architecture of our policy and critic network based on GPT-2. We design the parameterization of critic network to share the parameters of the Transformer layers of GPT-2, where the parameters of the Transformer layers are only updated during the policy improvement step. For the hyperparameters of fine-tuning the GPT-2, we follow the setting in the public code of UBAR (Yang et al., 2021).

4.2 EVALUATION ON MULTIWOZ DATASET

We evaluate our algorithm on the MultiWOZ dataset, which is one of the representative task-oriented dialogue benchmarks. The MultiWOZ is a large-scale multi-domain Wizard-of-Oz dataset, where a tourist (i.e. user) converses with a clerk (i.e. system) at the information center in a touristic city.

Algorithms	Inform	Success	BLEU	Combined Score
SFN+RL* (Mehri et al., 2019)	73.80	53.60	16.90	83.10
DAMD* (Zhang et al., 2020)	76.40	60.40	16.60	85.00
SIMPLETOD* (Hosseini-Asl et al., 2020)	84.40	70.10	15.01	92.26
SOLOIST* (Peng et al., 2021)	85.50	72.90	16.54	95.74
MINTL* (Lin et al., 2020)	84.88	74.91	**17.89**	97.78
UBAR (Yang et al., 2021)	87.23	74.73	17.43	98.42
CRR (Wang et al., 2020)	87.00	74.23	16.52	97.14
DECISION TRANSFORMER (Chen et al., 2021)	87.53	74.33	17.64	98.57
GPT-CRITIC	**90.07**	**76.63**	17.83	**101.13**

Table 3: End-to-end response generation results on MultiWOZ. The results with * are from original papers. All other results are averaged over three independent runs.

Algorithms	Complete	Success	Book	Inform (P / R / F1)	Turn (succ / all)
DAMD	49.40	44.40	50.78	0.55 / 0.60 / 0.55	13.72 / 26.82
MINTL	71.40	68.10	65.38	0.65 / 0.80 / 0.69	15.67 / 20.72
UBAR	79.80	74.30	80.82	**0.74** / 0.86 / 0.76	14.22 / 18.08
CRR	78.20	72.60	82.21	**0.74** / 0.84 / 0.76	**13.61 / 17.96**
DECISION TRANSFORMER	81.30	75.30	83.54	0.73 / 0.87 / 0.77	14.81 / 18.05
GPT-CRITIC	**84.30**	**77.70**	**85.42**	**0.74 / 0.90 / 0.79**	16.27 / 19.42

Table 4: Experimental results of simulator-based evaluation on ConvLab. All results are averaged over 1000 dialogues.

It consists of 8438/1000/1000 dialogues for training/validation/testing. For end-to-end evaluation on MultiWOZ dataset, we use the following automatic evaluation metrics: 1) **Inform**: evaluates whether the system provides an appropriate entity, 2) **Success**: evaluates whether the system answers all the requested information, 3) **BLEU**: measures the fluency of the generated response (Papineni et al., 2002). We also report the **Combined Score** as an overall quality measure (Combined = $(\text{Inform} + \text{Success}) \times 0.5 + \text{BLEU}$).

We compare the performance of GPT-Critic with the following algorithms: 1) SFN+RL (Mehri et al., 2019), a seq2seq network that incorporates several pre-trained dialogue modules into a neural dialogue model, 2) DAMD (Zhang et al., 2020), the domain-aware multi-decoder network with multi-action data augmentation method, 3) SimpleTOD (Hosseini-Asl et al., 2020), a GPT-2-based end-to-end dialogue agent that all sub-tasks recast as a single sequence prediction problem, 4) SOLOIST (Peng et al., 2021), a GPT-2-based end-to-end dialogue agent with transfer learning and machine teaching, 5) MinTL (Lin et al., 2020), an efficient dialogue state tracking method with a minimal generation length by predicting the difference between old and new states, 6) UBAR (Yang et al., 2021), a GPT-2-based end-to-end dialogue agent that leverages the entire dialogue session of every dialogue turn. We implement our algorithm into the codebase of UBAR (Yang et al., 2021), and the result of UBAR is reproduced by adapting its code to the same evaluation settings as other papers.

In addition, we also compare with recent offline RL algorithms that are free from the issue of diverging from human language: 1) CRR (Wang et al., 2020), a value-filtered regression method that performs weighted behavior cloning of offline dataset, 2) Decision Transformer (Chen et al., 2021), a Transformer-based architecture that casts the problem of RL as conditional sequence modeling. For a fair comparison, we use the same pre-trained GPT-2 model as a policy network to train the CRR and the Decision Transformer.

Table 1 and Table 2 show the results of policy iteration. Table 1 shows the performance of training dataset and critic-guided self-generated dialogues being used for each policy improvement step. Table 2 reports the intermediate performance of behavior cloning of training dataset and critic-guided self-generated dialogues in each of the policy iteration. As shown in Table 1 and Table 2, the performance of critic-guided self-generated dialogues is improved gradually; the performance of GPT-Critic is also consistently improved through the behavior cloning of improved dataset.

WOZ20322	Original Dialogue / Self-generated Dialogue
User Utterance	i would like a moderately prices restaurant in the east part of town.
	i would like the phone number and postcode, please.
Dialogue State	[restaurant] pricerange moderate area east
Dialogue Act	[restaurant] [select] food [inform] choice area
System Response	we have [value_choice] matching your request in the [value_area] part of town.
	do you prefer [value_food] or [value_food]?
Dialogue Act *	[restaurant] [inform] food price area phone name postcode
System Response *	[value_name] is a [value_price] [value_food] restaurant in the [value_area] part of
	town. their phone number is [value_phone] and their postcode is [value_postcode].

SNG01237	Original Dialogue / Self-generated Dialogue
User Utterance	i am looking for the nearest police station
Dialogue State	-
Dialogue Act	[police] [inform] phone
System Response	the nearest police station is in parkside cambridge, the telephone number
	is [value_phone].
Dialogue Act *	[police] [inform] name phone address postcode
System Response *	the nearest police station is [value_name], located in [value_address] [value_postcode].
	their phone number is [value_phone]. is there anything else i can help you with?

PMUL2640	Original Dialogue / Self-generated Dialogue
User Utterance	i heard cityroomz is a good hotel. can you give me some information on this hotel?
Dialogue State	[hotel] name cityroomz
Dialogue Act	[hotel] [inform] area price
System Response	it is located in the [value_area] and is priced in the [value_price] range.
Dialogue Act *	[hotel] [inform] area name internet price parking type stars [offerbook]
System Response *	[value_name] is a [value_type] in the [value_area]. it is [value_price], has [value_stars]
	stars, and offers free wifi and parking. would you like me to book it for you?

MUL2024	Original Dialogue / Self-generated Dialogue
User Utterance	i am looking for a hotel called the a and b guest house. can you help me out?
Dialogue State	[hotel] name a and b guest house
Dialogue Act	-
System Response	yes, what would you like to know about it?
Dialogue Act *	[hotel] [inform] area address name price
System Response *	[value_name] is located in the [value_area] at [value_address]. it is [value_price].

Table 5: Examples of the original dialogue and the critic-guided self-generated dialogue on the training dataset of MultiWOZ. The dialogue act and system response with * denote the self-generated dialogue act and response by GPT-Critic. All system responses represent delexicalized responses.

Table 3 summarizes the overall performance of GPT-Critic and baseline algorithms on MultiWOZ dataset. The results show that GPT-Critic achieved the best performance in terms of inform rate, success rate, and combined score. Moreover, the performance of GPT-Critic on the BLEU score matches those of other pre-trained LM-based methods, since GPT-Critic inherits GPT-2's ability to generate human-like responses through the behavior cloning of responses generated by GPT-2. The results show that GPT-Critic improves the task performance of the agent without the issue of diverging from human language.

For the results of offline RL baselines, CRR and Decision Transformer show the results that do not diverge from human-language, since their policy is also trained by behavior cloning. However, both

algorithms show limited performance because they perform behavior cloning on a fixed dataset. CRR has achieved remarkable success in continuous control tasks by performing weighted behavior cloning of training dataset filtered by critic, but it does not effectively perform in task-oriented dialogues because of data scarcity. Furthermore, to evaluate the Decision Transformer, we adopt a delayed return where the agent receives the cumulative reward at the end of dialogue, since the agent cannot observe user goal. Therefore, without observing the user goal at test time, Decision Transformer reduces to the behavior cloning of successful dialogues.

4.3 Evaluation on ConvLab Evaluator

In order to evaluate the performance of dialogue agents in an end-to-end fashion, we conduct simulator-based evaluation on ConvLab (Zhu et al., 2020). ConvLab is an open-source toolkit that enables to build task-oriented dialogue systems and perform an end-to-end evaluation. The simulator-based evaluation is more reliable than dataset-based automatic evaluation because it evaluates the performance while interacting with the user simulator. To interact with dialogue systems, ConvLab provides an agenda-based user simulator (Schatzmann et al., 2007) that consists of a BERT (Devlin et al., 2019) for NLU, a rule-based policy, and a template-based NLG. We compare the performance of GPT-Critic with baseline algorithms interacting with the same user simulator and user goals. We report the results with following metrics: 1) **Complete**: evaluates whether the system completes the goal, 2) **Success**: evaluates whether the all user requests have been informed and the booked entities satisfy the constraints, 3) **Book**: evaluates how many booked entities satisfy the user constraints, 4) **Inform (Precision / Recall / F1)**: evaluates how many user requests have been informed, 5) **Turn (success / all)**: evaluates the average turn number for successful/all dialogues.

We describe the performance of GPT-Critic and baselines in Table 4. Each algorithm is tested for 1000 runs with randomly sampled user goal. The results show that GPT-Critic achieves the best performance in all metrics related to task accomplishment. However, they also show that GPT-Critic takes longer dialogue turn for the task accomplishment because GPT-Critic is trained by maximizing the success rate without considering the dialogue turn.

4.4 Qualitative Analysis of Self-generated Dialogues

In this section, we provide a qualitative analysis on the critic-guided self-generated responses in GPT-Critic. We show the critic-guided self-generated dialogue examples in Table 5 that illustrates how GPT-Critic improves the performance through the behavior cloning of self-generated dialogues, compared with unsuccessful dialogues on the training dataset of MultiWOZ. Each example demonstrates the critic-guided self-generated dialogue act and delexicalized system response, compared with the original dialogue. The generated responses contain all the requests of user with abundant information, whereas original responses of unsuccessful dialogues do not contain all the requested information. GPT-Critic improves the performance through the behavior cloning of these revised responses. Moreover, Table 5 shows that the generated dialogues do not diverge from human language. Since GPT-Critic updates the policy through behavior cloning of the self-generated human-like responses, GPT-Critic is essentially free from the issue of diverging from human language.

5 Related Work

End-to-End Task-Oriented Dialogue System. The traditional approach to building a task-oriented dialogue system adopts a modular pipeline, which consists of natural language understanding, dialogue state tracking, dialogue policy, and natural language generation. Recently, pre-trained LM-based end-to-end task-oriented dialogue agents that all sub-tasks recast as a single sequence prediction problem have been proposed (Ham et al., 2020; Hosseini-Asl et al., 2020), and significantly improved overall performance in task-oriented dialogues. There are a number of variants of GPT-2-based end-to-end task-oriented dialogue agents. Yang et al. (2021) leverage the entire dialogue session of every dialogue turn. Peng et al. (2021) adopt transfer learning and machine teaching for training a GPT-2-based dialogue agent. Lin et al. (2020) present efficient dialogue state tracking with a minimal generation length, and then leverage pre-trained language models for task-oriented dialogues.

Reinforcement Learning for Task-Oriented Dialogues. Applying the standard RL methods straightforward to optimize a task-oriented dialogue agent causes the issue of diverging from human language. To address this problem, interleaving reinforcement learning with supervised learning has been proposed but it is still not free from the issue of diverging from human language (Lewis et al., 2017). Recently, the latent representation models for language actions have been introduced to address the aforementioned problem (Zhao et al., 2019; Yarats & Lewis, 2018). They disentangle the semantics of the utterance and the natural language generation, and then perform goal-based training in the space of the latent variables instead of directly optimizing utterances. However, they cannot be directly applied to large scale pre-trained language models that are not designed in a way that works inherently with discrete latent variables. Jaques et al. (2020) use KL-control to restrict the policy to stay close to its prior policy, but it still suffers from divergence from human language even with carefully chosen hyper-parameters. Furthermore, Jang et al. (2020) adopt Bayes-adaptive Monte-Carlo planning to negotiation dialogue then use it as a policy improvement operator. This approach can prevent the issue of diverging from human language through the policy improvement based on behavior cloning of self-generated dialogues. However, they assume a user model that is difficult enough to be considered another problem.

Offline Reinforcement Learning. There have been extensive studies on offline RL (Fujimoto et al., 2019; Levine et al., 2020; Kumar et al., 2020; Wang et al., 2020). Most of prior works are built on the off-policy actor-critic framework, and they focus on the overestimation issue by taking the OOD actions (Kumar et al., 2019; Lee et al., 2020; Fujimoto et al., 2019; Jaques et al., 2020; Kumar et al., 2020). However, a naive application of these offline RL methods suffer from the issue of diverging from human language in the task-oriented dialogues (Lewis et al., 2017; Zhao et al., 2019; Jang et al., 2020). On the other hand, there are a number of recent works on weighted behavior cloning, where a policy is trained by a variant of supervised learning loss (Wang et al., 2020; Peng et al., 2019; Siegel et al., 2020). More recently, Chen et al. (2021) introduce Decision Transformer, a Transformer-based architecture that casts the problem of RL as conditional sequence modeling. These offline RL methods based on behavior cloning are directly applied to the task-oriented dialogues without aforementioned issue, but their results are similar to that of behavior cloning in task-oriented dialogues.

6 CONCLUSION

We presented GPT-Critic, an offline RL algorithm for task-oriented dialogue system, which can be adopted for any generative pre-trained language model. GPT-Critic aims to learn an end-to-end task-oriented dialogue agent without the issue of diverging from human language. GPT-Critic starts with fine-tuning the GPT-2 and learning the critic using the dialogue corpus. Then, GPT-Critic updates the policy through the behavior cloning of the critic-guided self-generated responses, thus it is essentially free from the issue of diverging from human language. In the experiments, we demonstrated that GPT-Critic outperforms the state-of-the-art algorithms in task-oriented dialogue benchmarks including MultiWOZ and ConvLab.

REFERENCES

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Paweł Budzianowski, Tsung-Hsien Wen, Bo-Hsiang Tseng, Inigo Casanueva, Stefan Ultes, Osman Ramadan, and Milica Gašić. Multiwoz–a large-scale multi-domain wizard-of-oz dataset for task-oriented dialogue modelling. *arXiv preprint arXiv:1810.00278*, 2018.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *arXiv preprint arXiv:2106.01345*, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://aclanthology.org/N19-1423`.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pp. 2052–2062. PMLR, 2019.

Donghoon Ham, Jeong-Gwan Lee, Youngsoo Jang, and Kee-Eung Kim. End-to-end neural pipeline for goal-oriented dialogue systems using gpt-2. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 583–592, 2020.

Ehsan Hosseini-Asl, Bryan McCann, Chien-Sheng Wu, Semih Yavuz, and Richard Socher. A simple language model for task-oriented dialogue. *arXiv preprint arXiv:2005.00796*, 2020.

Youngsoo Jang, Jongmin Lee, and Kee-Eung Kim. Bayes-adaptive monte-carlo planning and learning for goal-oriented dialogues. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2020.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. *arXiv preprint arXiv:1906.08253*, 2019.

Natasha Jaques, Judy Hanwen Shen, Asma Ghandeharioun, Craig Ferguson, Agata Lapedriza, Noah Jones, Shixiang Shane Gu, and Rosalind Picard. Human-centric dialog training via offline reinforcement learning. *arXiv preprint arXiv:2010.05848*, 2020.

John F Kelley. An iterative design methodology for user-friendly natural language office information applications. *ACM Transactions on Information Systems (TOIS)*, 2(1):26–41, 1984.

Young-Bum Kim, Sungjin Lee, and Karl Stratos. OneNet: Joint Domain, Intent, Slot Prediction for Spoken Language Understanding. In *2017 IEEE Automatic Speech Recognition and Understanding Workshop*, 2017.

Aviral Kumar, Justin Fu, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. *arXiv preprint arXiv:1906.00949*, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *arXiv preprint arXiv:2006.04779*, 2020.

Byungjun Lee, Jongmin Lee, Peter Vrancx, Dongho Kim, and Kee-Eung Kim. Batch reinforcement learning with hyperparameter gradients. In *International Conference on Machine Learning*, pp. 5725–5735. PMLR, 2020.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Mike Lewis, Denis Yarats, Yann Dauphin, Devi Parikh, and Dhruv Batra. Deal or no deal? end-to-end learning of negotiation dialogues. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, 2017.

Zhaojiang Lin, Andrea Madotto, Genta Indra Winata, and Pascale Fung. Mintl: Minimalist transfer learning for task-oriented dialogue systems. *arXiv preprint arXiv:2009.12005*, 2020.

Shikib Mehri, Tejas Srinivasan, and Maxine Eskenazi. Structured fusion networks for dialog. *arXiv preprint arXiv:1907.10016*, 2019.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pp. 311–318, 2002.

Baolin Peng, Chunyuan Li, Jinchao Li, Shahin Shayandeh, Lars Liden, and Jianfeng Gao. Soloist: Buildingtask bots at scale with transfer learning and machine teaching. *Transactions of the Association for Computational Linguistics*, 9:807–824, 2021.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*, 2019.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Jost Schatzmann, Blaise Thomson, Karl Weilhammer, Hui Ye, and Steve Young. Agenda-based user simulation for bootstrapping a pomdp dialogue system. In *Human Language Technologies 2007: The Conference of the North American Chapter of the Association for Computational Linguistics; Companion Volume, Short Papers*, pp. 149–152, 2007.

Noah Y Siegel, Jost Tobias Springenberg, Felix Berkenkamp, Abbas Abdolmaleki, Michael Neunert, Thomas Lampe, Roland Hafner, Nicolas Heess, and Martin Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. *arXiv preprint arXiv:2002.08396*, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Ziyu Wang, Alexander Novikov, Konrad Zolna, Jost Tobias Springenberg, Scott Reed, Bobak Shahriari, Noah Siegel, Josh Merel, Caglar Gulcehre, Nicolas Heess, et al. Critic regularized regression. *arXiv preprint arXiv:2006.15134*, 2020.

Tsung-Hsien Wen, Milica Gašić, Nikola Mrkšić, Pei-Hao Su, David Vandyke, and Steve Young. Semantically Conditioned LSTM-based Natural Language Generation for Spoken Dialogue Systems. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, 2015.

Jason Williams, Antoine Raux, Deepak Ramachandran, and Alan Black. The Dialog State Tracking Challenge. In *Proceedings of the SIGDIAL 2013 Conference*, 2013.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

Yunyi Yang, Yunhao Li, and Xiaojun Quan. Ubar: Towards fully end-to-end task-oriented dialog systems with gpt-2. In *AAAI*, 2021.

Denis Yarats and Mike Lewis. Hierarchical text generation and planning for strategic dialogue. In *Proceedings of the 35th International Conference on Machine Learning*, 2018.

Yichi Zhang, Zhijian Ou, and Zhou Yu. Task-oriented dialog systems that consider multiple appropriate responses under the same context. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 9604–9611, 2020.

Tiancheng Zhao, Kaige Xie, and Maxine Eskénazi. Rethinking action spaces for reinforcement learning in end-to-end dialog agents with latent variable models. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics*, 2019.

Qi Zhu, Zheng Zhang, Yan Fang, Xiang Li, Ryuichi Takanobu, Jinchao Li, Baolin Peng, Jianfeng Gao, Xiaoyan Zhu, and Minlie Huang. Convlab-2: An open-source toolkit for building, evaluating, and diagnosing dialogue systems. *arXiv preprint arXiv:2002.04793*, 2020.

A   POLICY IMPROVEMENT THEOREM

Theorem 1. *(Policy Improvement) Given a policy π and the number of sampling actions N, If we update the new policy π^{new} by*

$$\forall s, a, \pi^{new}(s, a) = \underset{\substack{a \in \{a_k\}^N \\ \{a_k\}^N \sim \pi(s)}}{\arg\max} \ Q^\pi(s, a)$$

then $Q^{\pi^{new}}(s, a) \geq Q^\pi(s, a)$ holds for all s, a.

Proof. For any s, a,

$$Q^\pi(s, a) = \mathbb{E}_P\Big[R(s_t, a_t) + \gamma \mathbb{E}_{a_{t+1} \sim \pi(s_{t+1})}[Q^\pi(s_{t+1}, a_{t+1})] | s_t = s, a_t = a\Big]$$

$$\leq \mathbb{E}_P\Big[R(s_t, a_t) + \gamma \mathbb{E}_{\{a_i\}^N \sim \pi(s_{t+1})}[\max_{a' \in \{a_i\}^N} Q^\pi(s_{t+1}, a')] | s_t = s, a_t = a\Big]$$

$$= \mathbb{E}_P\Big[R(s_t, a_t) + \gamma \mathbb{E}_{a_{t+1}^{new} \sim \pi^{new}(s_{t+1})}[Q^\pi(s_{t+1}, a_{t+1}^{new})] | s_t = s, a_t = a\Big]$$

$$= \mathbb{E}_P\Big[R(s_t, a_t) + \gamma \Big(\mathbb{E}_{a_{t+1}^{new} \sim \pi^{new}(s_{t+1})}[R(s_{t+1}, a_{t+1}^{new})] + \gamma \mathbb{E}_{a_{t+2} \sim \pi(s_{t+2})}[Q^\pi(s_{t+2}, a_{t+2})]\Big) | s_t = s, a_t = a\Big]$$

$$= \mathbb{E}_P\Big[\sum_{\tau=t}^{t+1} \mathbb{E}_{a_{\tau+1} \sim \pi^{new}(s_{\tau+1})}[\gamma^{\tau-t} R(s_\tau, a_\tau)] + \gamma^2 \mathbb{E}_{a_{t+2} \sim \pi(s_{t+2})}[Q^\pi(s_{t+2}, a_{t+2})] | s_t = s, a_t = a\Big]$$

$$\leq \mathbb{E}_P\Big[\sum_{\tau=t}^{t+1} \mathbb{E}_{a_{\tau+1} \sim \pi^{new}(s_{\tau+1})}[\gamma^{\tau-t} R(s_\tau, a_\tau)] + \gamma^2 \mathbb{E}_{a_{t+2}^{new} \sim \pi^{new}(s_{t+2})}[Q^\pi(s_{t+2}, a_{t+2}^{new})] | s_t = s, a_t = a\Big]$$

$$= \mathbb{E}_P\Big[\sum_{\tau=t}^{t+2} \mathbb{E}_{a_{\tau+1} \sim \pi^{new}(s_{\tau+1})}[\gamma^{\tau-t} R(s_\tau, a_\tau)] + \gamma^3 \mathbb{E}_{a_{t+3} \sim \pi(s_{t+3})}[Q^\pi(s_{t+3}, a_{t+3})] | s_t = s, a_t = a\Big]$$

$$\vdots$$

$$\leq \mathbb{E}_P\Big[\sum_{\tau=t}^{\infty} \mathbb{E}_{a_{\tau+1} \sim \pi^{new}(s_{\tau+1})}[\gamma^{\tau-t} R(s_\tau, a_\tau)] | s_t = s, a_t = a\Big]$$

$$= Q^{\pi^{new}}(s, a)$$

$\square$