ONLINE BOUNDARY-FREE CONTINUAL LEARNING BY SCHEDULED DATA PRIOR

ABSTRACT

Typical continual learning setup assumes that the dataset is split into multiple discrete tasks. We argue that it is less realistic as the streamed data would have no notion of task boundary in real-world data. Here, we take a step forward to investigate more realistic online continual learning – learning continuously changing data distribution without explicit task boundary, which we call *boundary-free* setup. Due to the lack of boundary, it is not obvious when and what information in the past to be preserved for a better remedy for the stability-plasticity dilemma. To this end, we propose a *scheduled* transfer of previously learned knowledge. In addition, we further propose a data-driven balancing between the knowledge in the past and the present in learning objective. Moreover, since it is not straightforward to use the previously proposed forgetting measure without task boundaries, we further propose a novel forgetting and knowledge gain measure based on information theory. We empirically evaluate our method on a Gaussian data stream and its periodic extension, which is frequently observed in real-life data, as well as the conventional disjoint task-split. Our method outperforms prior arts by large margins in various setups, using four benchmark datasets in continual learning literature – CIFAR-10, CIFAR-100, TinyImageNet and ImageNet.

1 INTRODUCTION

In real-world continual learning (CL) scenarios (He et al., 2020), data arrive in a streamed manner (Aljundi et al., 2019a; Cai et al., 2021) whereas typical continual learning setups split the data into multiple discrete *tasks* whose data distributions differ from each other. Moreover, most CL algorithms are studied in an *offline* CL setup (Kirkpatrick et al., 2017; Rebuffi et al., 2017; Saha et al., 2021), where the model can access data multiple times. While being prevalent in the literature, this setup has a number of issues far from the realistic scenario. Although the task setup have been partly addressed by (Prabhu et al., 2020; Koh et al., 2021; Bang et al., 2022), the revised setups still have the notion of *task boundary* whereas real-world data may not have the explicit task boundaries as the data distribution changes continuously. Despite that many methods update the model in a boundary-agnostic manner, called *task-free* CL (Aljundi et al., 2019b; Koh et al., 2021), they still leverage the notion of task boundary for knowledge transfer and evaluation, *e.g.*, leveraging the fact that distribution shift in data stream occurs only at task boundaries. In addition, the definition of forgetting depends on the notion of 'old' and 'new' tasks, which are defined by the task boundary.

We argue to address an online CL setup where data are learned online (allowing only a single access to data) with continuous distribution shift without explicit task boundaries. We refer to the setup as *online boundary-free continual learning*. In this setup, a small set of data is streamed to the model one by one, and the model only has access to the current data batch only (Aljundi et al., 2019c;a) with the notion of task boundary. Note that this setup can be considered as a large number of small sized task configuration while the previous setup is a small number of large sized task configuration.

For the distribution of continuous data stream, following (Shanahan et al., 2021; Wang et al., 2022), we consider Gaussian distribution as an instance of data streaming distributions. The Gaussian online data stream models the frequency of each class as Gaussian distribution over time. Note that classes do not recur after their initial Gaussian mode in this setup. However, in real-world data, the frequency of a class may have multiple recurring modalities over time, rather than a single mode, as depicted in Fig. 1. To further address such a scenario, we investigate a *periodic*-Gaussian online

stream, where each class would recur and the recurrence is periodic. To the best of our knowledge, this is the first work to study CL in continuous data distributions either in periods or not.

The boundary-free setup poses several challenges as follows. In the CL setup with explicit task boundary definition, methods using both episodic memory and distillation (*i.e.*, using data prior (Buzzega et al., 2020; Wu et al., 2019; Hou et al., 2019)) show compelling performance (Masana et al., 2020). They store the model weights at each task boundary and use the stored model as a distillation teacher for mitigating catastrophic forgetting. However, in the continuous data stream, it is challenging to determine which past models should be stored to be used as a data prior. To determine which data prior to transfer the knowledge from, we propose to combine different exponential moving average (EMA) distributions to have a particular schedule of transferring past knowledge.

In addition, as the past knowledge is now from diverse contexts, it is not trivial to balance the supervisory signal from the past and the present. Instead of using a fixed balancing hyperparameter, we propose to learn to balance them for better generalization in multiple scenarios, *i.e.*, datasets. In our empirical studies, we observe that our method outperforms comparable prior arts in Gaussian, periodic-Gaussian, and disjoint task-split data stream on 4 popular benchmarks in CL literature.

Moreover, conventional performance metrics for CL methods including forgetting is not trivially applicable to our setup as they are defined on the task boundary. Here, we propose a new metric for measuring forgetting using information theory. In contrast to the conventional forgetting metric, it captures loss and gain of intra-class knowledge, appropriate for periodic data distribution where the model has to accumulate different knowledge about the same class over multiple periods.

We summarize our contributions as follows:

- Extensively studying online CL with continuous data stream setup without explicit task boundary, including newly proposed periodic CL setup.
- Proposing an online boundary-free CL method that uses scheduled transfer of past knowledge.
- Proposing to learn to balance amount of using past and present knowledge.
- Proposing new metrics that can measure loss of past knowledge (*i.e.*, forgetting) and gain of new knowledge (*i.e.*, the opposite of intransigience) based on information theory.

2 RELATED WORK

Setups for Continual Learning. With the increasing popularity of CL, there have been several proposals on learning configurations to be realistic. As the first task setup to mimic a real-world data stream that continuously changes over time, prior arts have employed the notion of *task-split*, where the entire data is split into multiple subsets for different continuous tasks (Rebuffi et al., 2017; Castro et al., 2018; Wu et al., 2019). When each subset arrives, it is stored and provided as a set of examples to learn a model. They use multiple epochs to learn a model (Kirkpatrick et al., 2017; Rebuffi et al., 2017; Saha et al., 2021), which is referred as *offline* setup, while a small batch sample of the subset is streamed and used only once in *online* setup (Rolnick et al., 2019; Chaudhry et al., 2019; Aljundi et al., 2019a). In the task-split setup, task boundaries are available and well exploited in various offline/online CL methods (Lopez-Paz & Ranzato, 2017; Rebuffi et al., 2017).

In recent literature, however, there has been efforts to question whether the task-split setup is realistic. To enforce the class distribution of each split differently, *disjoint task-split* confines each class to be assigned to only a single task (Castro et al., 2018). As the disjoint setup is rather artificial as the data stream arrives in class agnostic manner. *Blurry* task-split allows every task shares all classes but with different dominance (Aljundi et al., 2019c; Bang et al., 2021). The *i-Blurry* task-split further guarantee some classes to be added incremental to the blurry task-split (Koh et al., 2021). However, these task configurations have explicit task boundary, which is still artificial. For a more realistic setup, a number of effort has been put into not using boundary information, but they still rely on the notion of task boundary for learning and evaluating the models (Aljundi et al., 2019b).

In contrast to the prior work, we propose a *boundary-free* task setup. It removes the notion of artificial task boundary, rather, the data arrival follows a certain distribution. (Shanahan et al., 2021; Wang et al., 2022) investigate data stream following Gaussian distribution, they neglect a periodic property of real-world data, which we study further here.

Figure 1: Search interest trends of three items (*i.e.*, swimsuit, coat, Christmas gift) from 2009 to the present in Google Trends. Each item follows a periodic distribution with its own mode and duration.

Online Continual Learning Methods. One of the goals of successful CL learners is not to forget knowledge obtained from the preceding tasks; here, catastrophic forgetting has become the main challenge with deep neural networks for CL (French, 1999). To mitigate the issue, there are four main directions in the recent literature, namely distillation, memory replay, parameter isolation, and regularization. For a more comprehensive review, we refer the reader to surveys (De Lange et al., 2021; Mai et al., 2022).

The key difference between online and offline CL is the accessibility of streaming inputs; the model can only see the entire stream once except for the samples in the episodic memory. To tackle this online constraint, several methods have been developed based on the similar ways in offline CL. GEM (Lopez-Paz & Ranzato, 2017) leverages the gradient of samples in the available memory so that they alleviate forgetting the knowledge of the previous tasks. A-GEM (Chaudhry et al., 2018b) proposes to utilize the average of gradients for each task instead of using the projection of all the gradients. It further saves memory usage and reduces the computational cost. GDumb (Prabhu et al., 2020) proposes greedy balance selection which randomly selects the samples while balancing the number of selected samples per class. GSS (Aljundi et al., 2019c) and RM (Bang et al., 2021) utilize the gradient and uncertainty of each sample, respectively, to increase diversity of selected samples. CLIB (Koh et al., 2021) makes up informative samples in the memory by discarding the least informative samples in the memory for further training.

Unlike offline CL, however, online CL understudied the methods which utilize knowledge distillation. DER (Buzzega et al., 2020) utilized the knowledge distillation between logits of an original image and augmented image from origin, which is well-known and widely used. In our proposed setup, which is *boundary-free*, it is not trivial to determine when and what knowledge should be transferred to mitigate the forgetting. Here, we propose a new knowledge distillation method which is suitable for online boundary-free CL by using scheduled data prior.

3   ONLINE TASK BOUNDARY-FREE CONTINUAL LEARNING SETUP

Motivated by a real data stream that changes continuously (*e.g.*, Google search trend of 'swimsuit', 'coat', and 'Christmas gift' during 13 years, depicted in Fig. 1[1]), we propose a new CL setup called *online boundary-free*. We argue that our setup is more realistic than the task-split setup for the following considerations: (1) an ever-changing distribution with (periodic) Gaussian online stream, (2) no notion of explicit task boundaries, and (3) any-time inference for online continual learning.

3.1   GAUSSIAN ONLINE STREAM

For easeness of modeling, here we assume that a real data stream for each class follows Gaussian distribution. First, we consider a single mode stream, then extend it to a multi-modal periodic stream. Gaussian-distributed task modeling has been addressed by Shanahan et al. (2021); Wang et al. (2022). However, they differ from ours since their distribution change is not fully continuous as they still split data into multiple micro-tasks and overlook the periodicity of the online stream.

---

[1] https://trends.google.com/trends/explore?date=all&geo=US&q=christmas%20gift,coat,swimsuit

Specifically, we consider the 'arrival time' of samples to be modeled by the Gaussian distribution. In order to create an online stream without task boundary; samples are streamed in an increasing order of their arrival time. Formally, let us assume that the distribution of arrival time for a class i follows the Gaussian distribution $\mathcal{N}(\mu_i, \sigma^2)$. For each class i, the mean μ_i (=mode) of the distribution is exclusively chosen from $\left\{0, \frac{1}{N}, \ldots, \frac{N-1}{N}\right\}$ where N is the number of classes, and the standard deviation σ is the same for all classes for simplicity (we use $\sigma = 0.1$ for our empirical validations and provide analysis on different values in the appendix).

Periodic Gaussian Online Stream. By a simple modification, we can extend the Gaussian stream to a *periodic* one. Now, the distribution of arrival time of a class i not only follows the Gaussian distribution but also is repeated multiple times:

$$\frac{1}{R} \sum_{r=0}^{R-1} \mathcal{N}(\mu_i + r, \sigma^2), \tag{1}$$

where R is the number of repetition (*i.e.*, periods, we use $R = 5$ in our experiments). The mean μ_i and standard deviation σ are the same as the ones in the non-periodic Gaussian online stream.

4 EVALUATION METRICS FOR CONTINUAL LEARNERS IN THE BOUNDARY-FREE DATA STREAM

Conventional Forgetting and Intransigence metrics (Chaudhry et al., 2018a) require to measure the accuracy of the previous task. However, in the boundary-free setup, they are not readily measurable due to lack of task boundary. Here, we propose new metrics of measuring forgetting and ability to learn new knowledge by computing loss and gain of knowledge based on information theory.

Knowledge Loss Ratio. Specifically, we want to measure loss and gain of knowledge between arbitrary two points in the training, t_1 and t_2. Let Y_{GT} be ground truth label for a randomly selected sample from a data distribution and Y_t be the model's prediction for that sample at time t. We define the Total Knowledge ($TK(t)$) at time t as:

$$TK(t) := I(Y_t; Y_{\text{GT}}), \tag{2}$$

where $I(X; Y) = \sum_{y \in \mathcal{Y}} \sum_{x \in \mathcal{X}} P(x, y) \log\left(\frac{P(x, y)}{P(x)P(y)}\right)$ is a mutual information that measures the quantity of information one variable has about the other. In other words, it measures how much information about ground truth we can obtain by observing the model's prediction at time t.

To measure the loss of knowledge between t_1 and t_2, we quantify the knowledge in Y_{t_1} but not in Y_{t_2}. The knowledge loss can be measured by the knowledge difference between having both output (Y_{t_1}, Y_{t_2}) and having only Y_{t_2}. Thus, we define Knowledge Loss ($KL(t_1, t_2)$) between t_1 and t_2 as:

$$KL(t_1, t_2) := I(Y_{t_1}, Y_{t_2}; Y_{\text{GT}}) - I(Y_{t_2}; Y_{\text{GT}}) = I(Y_{t_1}; Y_{\text{GT}}|Y_{t_2}), \tag{3}$$

where $I(X; Y|Z) = I(X, Z; Y) - I(Z; Y)$ is the conditional mutual information. By dividing the knowledge loss by the total knowledge at t_1, we obtain Knowledge Loss Ratio ($KLR(t_1, t_2)$) as:

$$KLR(t_1, t_2) := \frac{KL(t_1, t_2)}{TK(t_1)} = \frac{I(Y_{t_1}; Y_{\text{GT}}|Y_{t_2})}{I(Y_{t_1}; Y_{\text{GT}})}. \tag{4}$$

KLR measures the ratio of the past knowledge that was lost between t_1 and t_2, which we will use an equivalent measure for forgetting in continuous data stream..

Knowledge Gain Ratio. Similarly, we can define the Knowledge Gain (KG) between t_1 and t_2 as:

$$KG(t_1, t_2) = I(Y_{t_1}, Y_{t_2}; Y_{\text{GT}}) - I(Y_{t_1}; Y_{\text{GT}}) = I(Y_{t_2}; Y_{\text{GT}}|Y_{t_1}). \tag{5}$$

Similar to KLR, we define Knowledge Gain Ratio (KGR) to measure the ratio of the potentially obtainable knowledge obtained between t_1 and t_2. The amount of information in GT label is $H(Y_{\text{GT}})$, so the potentially obtainable knowledge at time t_1 is $H(Y_{\text{GT}}) - I(Y_{t_1}; Y_{\text{GT}})$. Thus, $KGR(t_1, t_2)$ is defined as:

$$KGR(t_1, t_2) := \frac{KG(t_1, t_2)}{H(Y_{\text{GT}}) - I(Y_{t_1}; Y_{\text{GT}})} = \frac{I(Y_{t_2}; Y_{\text{GT}}|Y_{t_1})}{H(Y_{\text{GT}}) - I(Y_{t_1}; Y_{\text{GT}})}. \tag{6}$$

Implications. We illustrate the implication of the defined KL and KG in a Venn-Diagram of Fig. 2. Upper circle, lower left circle, lower right circle represent Y_{GT}, Y_{t_1}, and Y_{t_2}, respectively. KL is knowledge about GT that is in model at t_1 but not in t_2. KG is the knowledge about GT that is in model at t_2 but not in t_1. The triple intersection $I(Y_{t_1}; Y_{t_2}; Y_{\text{GT}})$ represents retained knowledge about GT that is in model at both t_1 and t_2. Finally, the lower intersection, $I(Y_{t_1}; Y_{t_2}|Y_{\text{GT}})$, represents useless information shared in both models that are not relevant to GT labels, such as bias in the model.

Figure 2: Relation of knowledge learned by model to the Knowledge Loss (KL) and Knowledge Gain (KG).

One advantage of KL is that it can be interpreted as intra-class forgetting. Since conventional 'forgetting' is measured using task-wise or class-wise accuracy, if forgetting and knowledge gain simultaneously happens within a task or a class, its net effect is zero, thus its effect will not be measured. For example, if we assume there is class A with features a and b and the model forgot about feature a and learned about feature b so that overall accuracy for class A is the same, it counts as zero forgetting in the conventional measure. In contrast, when using the proposed Knowledge Loss (KL), the current model only has information about feature b, but past and current models combined have information about both a and b, so it captures loss of information about feature a.

5 APPROACH

The existing task-split setup partitions the data stream into multiple discrete tasks. Prior arts in CL literature that have been developed in this setup focus on extracting information from prior models learned in the previous tasks. However, in the online boundary-free setup whose data stream is not partitioned into explicit tasks, it is necessary to consider information at which previous moment we have to transfer to the current time step for better stability and plasiticity trade-off. Although there is no task boundary, a model learned in the past can be stored when each sample arrives and used as a data prior, *i.e.*, a teacher in distillation framework. However, it is not clear which previous models to be used to transfer knowledge to the current time step. We consider various weighting functions to transfer information from the previous data stream in online and continuous fashion, and summarize the empirical results in Table 1.

5.1 SCHEDULED DATA PRIOR

To determine the amount of past knowledge to be transferred in a continuous fashion, we consider a schedule of transfer of past knowledge by a composite function of exponential moving average (EMA) as the EMA combines knowledge from multiple timestamps and can be updated in an online manner. In particular, the EMA update emphasizes the recent knowledge more than the past knowledge by a exponentially decreasing weight distribution, as shown in Fig. 3-(a). However, we argue that recently learned information is well maintained in the model being currently trained (*i.e.*, not yet forgotten) and need to shift the focus to a slightly farther past (as depicted in Fig. 3-(b)).

To implement a such weighting scheme, we propose a hypo-exponential distribution, which has a skewed-bell curve shape to transfer the knowledge from the past. We configure the hypo-exponential distribution by weighted average of two EMA curves with different hyperparameters. The resulting distribution has a mode in the distant past while the vanilla EMA has the mode at the nearest past then the weight monotonically decreases.

Specifically, to construct the scheduled data prior (SDP), we take a weighted sum of two EMA models M_α and M_β with the ratios of α and β where $\alpha > \beta$. Using the coefficient for the hypo-exponential distribution, the proposed distribution $M_{\text{SDP}(\alpha,\beta)}$ is defined as:

$$M_{\text{SDP}(\alpha,\beta)} = \frac{\alpha}{\alpha - \beta} M_\beta - \frac{\beta}{\alpha - \beta} M_\alpha. \qquad (7)$$

Its weight are non-negative and summed up to 1, and form a skewed-bell curve as depicted in Fig. 3-(b). Instead of using α and β, we define SDP with mean μ and coefficient of variation $c^2 = \frac{\sigma^2}{\mu^2}$

(a) EMA weights with $\alpha = 0.0001$ (b) SDP weights with $\mu = 10,000$ and $c^2 = 0.75$

Figure 3: Comparison between weight distribution of EMA and SDP.

of weight distributions, where σ^2 is the variance of the distribution, so that hyperparameters are interpretable. The values of α and β can be calculated from μ and σ as:

$$\alpha = \frac{1 + \sqrt{2c^2 + \frac{2}{\mu} - 1}}{\mu(1 - c^2) - 1}, \quad \beta = \frac{1 - \sqrt{2c^2 + \frac{2}{\mu} - 1}}{\mu(1 - c^2) - 1}, \tag{8}$$

where α and β are positive real values when $\frac{1}{2} - \frac{1}{\mu} < c^2 < 1 - \frac{1}{\mu}$. The derivation for these can be found in appendix.

We empirically validate our hypothesis by a comparative study of using different scheduling distribution of past knowledge transfer in Tab. 1. As shown in the table, the proposed weight distribution (SDP) outperform other scheduling functions by a noticeable margin.

Teacher Model	$A_{\text{AUC}} \uparrow$	$A_{last} \uparrow$
None (Baseline)	62.37±0.52	64.22±0.97
Periodically Saving Model (Offline)	63.44±0.10	65.67±1.38
Saved Logits (DER)	59.82±0.30	58.92±2.36
Saved Features (DER)	61.55±0.22	58.78±2.38
EMA Model	63.75±0.22	66.55±3.32
SDP Model (Ours)	**64.04±0.25**	**69.47±1.79**

Table 1: Comparison of past knowledge transfer functions for continual learners on CIFAR-10. The proposed method outperforms other functions including EMA Model.

5.2 LEARNING TO BALANCE PAST AND PRESENT KNOWLEDGE IN LEARNING

While we transfer the knowledge from the past experience by the SDP distribution, balancing the amount of information from the past and the current time step is a remaining challenge for continual learners (Mai et al., 2022). The balancing hyperparameter is usually tuned by a hand-crafted manner and is dataset specific. Moreover, fixed parameter is not always optimal, as importance of classification and distillation may vary over the course of training. Thus, we propose to learn to balance them for better generalization to different data context and adapting in different phases of training.

With the learnable balancing parameter λ_t, we can write the final objective as:

$$\mathcal{L}(x, y) = \lambda_t \cdot \mathcal{L}_{\text{CE}}(x, y) + (1 - \lambda_t) \cdot \eta_k \cdot \mathcal{L}_{\text{KD}}(x), \tag{9}$$

where $\mathcal{L}_{\text{CE}}(x, y)$ is the cross-entropy loss for current time step's knowledge and $\mathcal{L}_{\text{KD}}(x) = \| f(x) - f_{\text{SDP}}(x) \|_2^2$ is the distillation loss for the past knowledge transfer. Before balancing the two terms for each task, since model parameter update is proportional to gradient, we normalize the scale of the two terms by η_k:

$$\eta_k = \frac{|\nabla_f \mathcal{L}_{\text{CE}}|}{|\nabla_f \mathcal{L}_{\text{KD}}|}, \tag{10}$$

where f is the feature layer of the model and k is a batch index. Note that we use the gradient norm at the feature layer since that of the earlier layers will be proportional to it thanks to the chain rule.

λ_t is typically defined as $\frac{|C_{\text{new}}|}{|C_{\text{new}}| + |C_{\text{old}}|}$ (Wu et al., 2019), where C_{new} is the new classes, *i.e.*, classes in the current task and C_{old} is old classes, *i.e.*, classes from the previous tasks. In the online boundary-free setup, unfortunately, as task is not defined, the notion of new or old is not available for each class. Instead of hard assignment of new and old classes, we measure $0 \leq \gamma_i \leq 1$ that represents how new class i is. The γ_i is measured by the inverse of past model's average confidence over samples

in class i, since the model will have low confidence for new classes. If a past model predicts class i with $p(i) = 1$, we consider that the model has completely learned class i, so $\gamma_i = 0$. If it predicts class i with $p(i) \leq \frac{1}{N}$ where N is the total number of classes, *i.e.*, no better than a random model, we consider that the model has learned nothing about class c, so $\gamma_i = 1$. To compute γ_i, we use the samples' confidence on currently learned model at the current time step before using them for training, as a proxy of validation accuracy.

Finally, we define the online balancing parameter λ_t by averaging confidence for all the samples for each class in the current time step as:

$$\lambda_t = \frac{\sum_{i=0}^{N-1} \gamma_i}{N}, \quad \text{where} \;\; \gamma_i = \begin{cases} 1, & \text{if } p(i) < 1/N, \\ \frac{N}{N-1}\left(1 - p(i)\right), & \text{otherwise.} \end{cases} \tag{11}$$

6 EXPERIMENTS

Experimental Setup. For empirical validations, following (Koh et al., 2021; Guo et al., 2022), we use four benchmark datasets; CIFAR-10, CIFAR-100, TinyImageNet, and ImageNet. Most of our experiments are on Gaussian and Periodic-Gaussian online stream defined in Sec. 3.1 for boundary-free setup except in Sec. 6.3 where we evaluate methods on disjoint stream using 5-split-CIFAR. We use $\sigma = 0.1$ for Gaussian setup, and $\sigma = 0.1$, $R = 5$ for Periodic-Gaussian setup.

For evaluation metrics, we use the area under the curve of accuracy (A_{AUC}) proposed in (Koh et al., 2021) for measuring area under the curve of accuracy-to-(# samples) curve, and last accuracy (A_{last}) that measures the final accuracy after learning all samples. We cannot measure A_{avg} metric since there is no task boundary. We also measure knowledge loss ratio (KLR) and knowledge gain ratio (KGR), defined in section 4. KLR and KGR are measured every $10,000$ samples for CIFAR-10 and CIFAR-100, every $20,000$ samples for TinyImageNet, every $100,000$ samples for ImageNet. All results are averaged over 3 different random seeds, except ImageNet (Bang et al., 2021; Koh et al., 2021) for computational cost. We will publicly release the implementation of our method and the continually learned models.

Baselines. We compare our method with other baselines that can be used in task-free setup: ER (Rolnick et al., 2019), DER++ (Buzzega et al., 2020), ER-MIR (Aljundi et al., 2019a), Gdumb (Prabhu et al., 2020), and CLIB (Koh et al., 2021). Note that since our setup is boundary-free, only the task-free methods can be applied.

Implementation Detail. We use ResNet-18 (He et al., 2016) as the network architecture for all experiments. We set training hyperparameters following (Koh et al., 2021; Bang et al., 2021; Prabhu et al., 2020). For CIFAR-10, CIFAR-100, TinyImageNet and ImageNet, we use batch size of 16, 16, 32, 256, number of updates per sample of 1, 3, 3, 0.25, memory size of 500, 2000, 4000, 20000, respectively. We use Adam optimizer with LR of 0.0003 for all datasets and setup. Constant LR schedule is applied unless the method specifies the LR schedule (Koh et al., 2021; Prabhu et al., 2020). For data augmentation, some prior works (Koh et al., 2021; Bang et al., 2021) use AutoAugment (Cubuk et al., 2019a). However, AutoAugment requires searching the augmentation policy using the dataset, so it is not applicable for our setup. Instead, we use CutMix (Yun et al., 2019) and RandAugment (Cubuk et al., 2019b) with fixed hyperparameters for requiring no policy search.

6.1 RESULTS ON NON-PERIODIC GAUSSIAN DATA STREAM

As shown in Table 2, our method outperforms the other baselines on all benchmark datasets. Especially, we can observe that the last accuracy (A_{last}) is better than the other baselines by large margins, which verifies that our method can quickly adapt to the current task in online boundary-free setup. In addition, the lower KLR score shows that our method is more robust to forgetting.

6.2 RESULTS ON PERIODIC GAUSSIAN DATA STREAM

The results of our method and other baselines on periodic-gaussian online stream is displayed in Table 3. It is observed that our method is superior to other baselines on various datasets with higher accuracies (A_{AUC}, A_{last}). It is noteworthy that our forgetting scores (KLR) is considerably lower

Methods	CIFAR-10				CIFAR-100			
	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$
ER	55.97±0.85	58.59±2.56	23.36±1.39	21.52±0.92	36.93±0.77	40.93±0.35	51.77±0.87	17.42±0.50
DER++	56.12±0.14	60.54±2.37	23.60±2.12	22.57±0.98	28.77±0.67	34.48±0.62	48.83±1.49	17.35±0.16
ER-MIR	56.48±0.18	59.38±2.83	25.04±1.67	21.72±0.16	34.76±1.20	37.20±2.06	57.23±1.14	16.46±0.68
GDumb	46.45±0.68	42.62±0.64	35.47±0.51	11.69±0.32	28.81±0.74	25.38±0.26	86.75±2.07	8.54±0.34
CLIB	63.01±0.31	65.24±2.10	20.79±1.64	22.52±1.92	42.79±0.65	43.81±0.58	48.59±1.78	15.96±0.26
SDP (Ours)	**66.51±0.42**	**76.29±0.50**	**10.75±1.48**	**23.19±1.16**	**46.34±0.64**	**54.93±0.56**	**36.56±0.92**	**18.77±0.27**

Methods	TinyImageNet				ImageNet			
	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$
ER	21.78±0.76	22.64±0.44	66.39±1.36	9.04±0.88	24.16	26.64	39.43	6.19
DER++	17.13±0.88	16.85±0.63	69.65±4.21	7.51±0.64	19.34	21.17	40.64	5.71
ER-MIR	21.64±0.77	22.55±0.66	66.51±1.18	**9.43±0.46**	12.86	24.70	54.53	8.23
GDumb	18.81±0.64	15.08±0.25	91.58±2.15	3.60±0.10	13.74	10.24	64.23	2.95
CLIB	27.53±0.94	26.10±0.93	63.97±2.18	6.16±0.39	34.11	31.60	**36.45**	6.20
SDP (Ours)	**30.49±0.69**	**32.59±0.20**	54.85±0.30	8.30±0.10	**35.52**	33.94	39.37	**8.25**

Table 2: Accuracy of continually learned model in **Non-Periodic Gaussian** data stream in CIFAR-10, CIFAR-100, TinyImageNet and ImageNet. The results except ImageNet are the average values of the three random seeds.

Methods	CIFAR-10				CIFAR-100			
	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$	A_{AUC}	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$
ER	61.17±0.97	67.29±2.58	17.87±0.48	22.44±1.05	37.90±0.31	46.45±0.42	48.83±1.49	17.35±0.16
DER++	60.70±1.07	70.41±1.83	16.47±0.53	23.45±0.49	23.07±1.22	37.88±1.42	48.72±1.49	15.56±0.50
ER-MIR	60.16±1.70	67.86±1.06	18.49±1.01	22.37±0.91	35.87±0.28	45.08±0.35	51.26±0.60	16.73±0.12
GDumb	43.01±0.45	42.97±0.91	39.88±1.90	12.87±0.83	25.01±0.13	25.37±1.91	88.84±1.91	7.82±0.11
CLIB	66.18±0.64	73.86±1.38	16.52±0.43	**24.99±0.69**	42.48±0.54	50.91±1.01	46.94±0.82	17.08±0.27
SDP (Ours)	**69.68±0.33**	**78.66±0.91**	**5.54±0.22**	18.54±1.28	**46.90±0.32**	**55.62±0.16**	**33.30±0.41**	**21.41±0.08**

Methods	TinyImageNet				ImageNet			
	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$
ER	20.67±0.25	24.84±0.49	66.65±1.17	7.14±0.12	25.25	34.93	43.04	9.39
DER++	16.67±0.34	21.67±0.86	66.39±1.36	7.63±0.13	20.57	27.85	44.96	9.87
ER-MIR	20.74±0.36	24.57±1.00	68.40±1.72	7.10±0.06	19.52	31.85	44.73	8.65
GDumb	15.75±0.12	15.40±0.76	95.73±3.75	3.15±0.17	11.22	11.38	67.32	2.59
CLIB	25.45±0.39	30.77±1.40	61.24±1.37	7.47±0.16	32.90	38.96	39.37	8.25
SDP (Ours)	**30.14±0.32**	**37.55±0.43**	**49.95±0.30**	**10.68±0.09**	**34.21**	**39.35**	**33.38**	**10.34**

Table 3: Accuracy of continually learned model in **Periodic Gaussian** data stream. The results except ImageNet are the average values of the three random seeds.

compared to other baselines. We believe that our method can transfer information from the appropriate past, and thus be adventageous when the data distribution repeats periodically.

6.3 RESULTS ON DISJOINT TASK SPLIT

As our method is not specifically designed for the boundary-free task setup, we also compare our method to prior arts in the disjoint setup. We summarize the results on 5-split-CIFAR-10 (*i.e.*, partitions 10 classes into 5 tasks) and 5-split-CIFAR-100 in Table 4 on the conventional task-split setup. As shown in the table, the proposed SDP outperforms other methods even in the setups with clear task boundaries.

Methods	CIFAR-10				CIFAR-100			
	$A_{AUC}\uparrow$	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$	A_{AUC}	$A_{last}\uparrow$	$KLR_{avg}\downarrow$	$KGR_{avg}\uparrow$
ER	73.52±0.87	58.95±2.11	24.95±1.41	25.37±1.21	49.21±1.05	39.86±0.52	58.02±0.97	13.83±0.45
DER++	71.01±1.26	55.37±2.47	30.02±3.22	23.62±1.68	46.03±1.29	37.60±0.75	59.95±1.18	13.79±0.63
ER-MIR	71.69±0.91	56.01±2.06	28.68±4.43	23.69±0.52	48.48±1.19	37.60±0.34	62.95±1.31	12.88±0.32
GDumb	62.23±0.70	44.69±1.11	25.64±1.45	11.44±0.83	37.80±0.31	24.77±0.68	79.33±3.13	9.04±0.14
CLIB	73.62±0.87	56.21±3.30	28.68±4.43	23.69±0.52	50.26±1.06	40.05±0.71	59.48±2.00	12.23±0.46
SDP (Ours)	**76.89±1.22**	**66.19±3.48**	**15.86±1.74**	**25.68±2.61**	**55.94±1.55**	**50.26±1.41**	**46.35±2.44**	**16.04±0.80**

Table 4: Results of disjoint task split on CIFAR-10 / 100. Each of datasets are split into 5 tasks

6.4 ABLATION STUDY

We now ablate the model for the two components, and summarize the results in Table 5. We observe that both the scheduling function and adaptive loss balancing contribute in improving the

Figure 4: Comparison of different values of mean and coefficient of variation, evaluated on CIFAR-10 non-periodic Gaussian data stream.

performance. Baseline is a simple episodic-memory based method using Greedy Balancing Sampler (Prabhu et al., 2020) and memory-only training (Koh et al., 2021). By using SDP distillation, we have 1.7~5.6% improved A_{AUC} and 5.2~8.4% improved A_{last} compared to baseline. Since we didn't apply adaptive loss balancing, we use a fixed balancing parameter optimized by grid search on CIFAR-10 non-periodic Gaussian stream. By applying adaptive loss balancing, we have further improved performance, except for A_{last} in CIFAR-100 periodic-Gaussian setup. It still outperforms baseline and other methods by large margins.

Methods	CIFAR-10				CIFAR-100			
	Gaussian		Periodic-Gaussian		Gaussian		Periodic-Gaussian	
	$A_{\text{AUC}} \uparrow$	$A_{last} \uparrow$	$A_{\text{AUC}} \uparrow$	$A_{last} \uparrow$	$A_{\text{AUC}} \uparrow$	$A_{last} \uparrow$	$A_{\text{AUC}} \uparrow$	$A_{last} \uparrow$
Baseline	62.37±0.52	64.22±0.97	64.95±0.60	72.55±0.71	42.02±0.58	43.19±0.32	40.54±0.23	48.15±0.39
+ Scheduling Function	64.04±0.21	69.47±1.79	67.79±0.21	77.87±0.24	45.73±0.40	50.53±0.18	46.14±0.05	**56.56±0.36**
+ Data-driven Balancing	**66.51±0.42**	**76.29±0.50**	**69.68±0.33**	**78.66±0.91**	**46.34±0.64**	**54.93±0.56**	**46.90±0.32**	55.62±0.16

Table 5: Ablation Study

Next, we study the effect of two hyperparameters of SDP, mean μ and coefficient of variation c^2, by grid search on CIFAR-10 non-periodic Gaussian setup, and summarize the results in Fig. 4. We observe some dependence on SDP mean, but not much on coefficient of variation. Note that the valid range for coefficient of variation is $0.5 - \frac{1}{\mu} < c^2 < 1 - \frac{1}{\mu}$. Since it is not much relevant to performance, we choose the value in the middle of valid range, $c^2 = 0.75$ for all experiments. SDP mean has some impact on the performance, so we choose the optimal value found on CIFAR-10 non-periodic Gaussian setup, $\mu = 10,000$. Since dataset or setup-specific hyperparameter search is not desirable in CL scenario, we use the same value, $\mu = 10,000$, for all datasets and setups.

7 CONCLUSION

For working in a better realistic continual learning scenario, we propose a continual learning setup of a continuous data stream without explicity task boundary defined, called *boundary-free* continual learning, with the constraint of learning the data in online manner. We also investigate the periodicity of the data distribution. As the existing evaluation metrics for continual learning setup assumes the explicit task boundaries, they are not readily applicable in the boundary-free setup. Thus, we propose two new information theoretic evaluation metrics to quantify the amount of information loss and gain over the data stream, named knowledge loss and knowledge gain. To address the continuous data stream to incrementally update the model, we propose a method to leverage the previously learned knowledge by a skewed bell shaped weighting function in a distillation framework, named *scheduled data prior*. For further generalization to different benchmarks, we propose to balance the pace of learning of knowledge in the past and the present in a data-driven manner. In our empirical evaluations, the proposed method outperforms comparable prior arts that update the weights per each data batch in a stream in the proposed boundary-free setup as well as the conventional disjoint task-split setup.

Limitations. Since our method does not leverage any notion of periodicity, it is expected to improve the method by considering the fact that the data stream has a periodic, though we may not know the duration of the period.

ETHICS STATEMENT

Continual learning (CL) including our approach aims to address real-world scenarios where data distributions continuously change in a non-stationary manner. Therefore, it can alleviate some ethical limitation of models resulting from lack of latest knowledge by continuous training and evaluation on newly observed data. This effort can be more effective to handle recent large language models (Brown et al., 2020; Kim et al., 2021; Chowdhery et al., 2022) or foundational vision models (Bommasani et al., 2021). On the other hand, CL methods might be vulnerable to model bias (Rae et al., 2021) caused by various bias inherent in the changing data due to its continuous tracking. This ethical issue is a future research topic. This may expose the public to discrimination by the deployed deep models due to unsolved issues in deep learning such.

REPRODUCIBILITY STATEMENT

We take the reproducibility in deep learning very seriously and highlight some of the contents in the manuscript that might help in reproducing our work. We will definitely release our implementations, learned models and newly derived datasets used in our experiments as mentioned in Sec. 6. Also, we have included relevant implementation details in Sec. 6. Finally, we present our final optimization objective (Eq. 9) with necessary details to reproduce the methodology.

REFERENCES

Rahaf Aljundi, Eugene Belilovsky, Tinne Tuytelaars, Laurent Charlin, Massimo Caccia, Min Lin, and Lucas Page-Caccia. Online continual learning with maximal interfered retrieval. *NeurIPS*, 32:11849–11860, 2019a. 1, 2, 7

Rahaf Aljundi, Klaas Kelchtermans, and Tinne Tuytelaars. Task-free continual learning. In *CVPR*, pp. 11254–11263, 2019b. 1, 2

Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning. In *NeurIPS*, pp. 11816–11825, 2019c. 1, 2, 3

Jihwan Bang, Heesu Kim, YoungJoon Yoo, Jung-Woo Ha, and Jonghyun Choi. Rainbow memory: Continual learning with a memory of diverse samples. In *CVPR*, pp. 8218–8227, 2021. 2, 3, 7

Jihwan Bang, Hyunseo Koh, Seulki Park, Hwanjun Song, Jung-Woo Ha, and Jonghyun Choi. Online continual learning on a contaminated data stream with blurry task boundaries. In *CVPR*, June 2022. 1

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021. 10

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *NeurIPS*, 33:1877–1901, 2020. 10

Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline. *NeurIPS*, 33:15920–15930, 2020. 2, 3, 7

Zhipeng Cai, Ozan Sener, and Vladlen Koltun. Online continual learning with natural distribution shifts: An empirical study with visual data. In *ICCV*, pp. 8281–8290, 2021. 1

Francisco M. Castro, Manuel J. Marin-Jimenez, Nicolas Guil, Cordelia Schmid, and Karteek Alahari. End-to-end incremental learning. In *ECCV*, 2018. 2

Arslan Chaudhry, Puneet K. Dokania, Thalaiyasingam Ajanthan, and Philip H. S. Torr. Riemannian walk for incremental learning: Understanding forgetting and intransigence. In *ECCV*, 2018a. 4

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem. In *ICLR*, 2018b. 3

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with A-GEM. In *ICLR*, 2019. 2

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022. 10

Ekin D. Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V. Le. AutoAugment: Learning augmentation strategies from data. In *CVPR*, June 2019a. 7

Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical data augmentation with no separate search. *arXiv preprint arXiv:1909.13719*, 2(4):7, 2019b. 7

Matthias De Lange, Rahaf Aljundi, Marc Masana, Sarah Parisot, Xu Jia, Aleš Leonardis, Gregory Slabaugh, and Tinne Tuytelaars. A continual learning survey: Defying forgetting in classification tasks. *TPAMI*, 2021. 3

R French. Catastrophic forgetting in connectionist networks. *Trends in Cognitive Sciences*, 1999. 3

Yiduo Guo, Bing Liu, and Dongyan Zhao. Online continual learning through mutual information maximization. In *International Conference on Machine Learning*, pp. 8109–8126. PMLR, 2022. 7

J. He, R. Mao, Z. Shao, and F. Zhu. Incremental Learning In Online Scenario. In *CVPR*, 2020. 1

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016. 7

Saihui Hou, Xinyu Pan, Chen Change Loy, Zilei Wang, and Dahua Lin. Learning a unified classifier incrementally via rebalancing. In *CVPR*, pp. 831–839, 2019. 2

Boseop Kim, HyoungSeok Kim, Sang-Woo Lee, Gichang Lee, Donghyun Kwak, Dong Hyeon Jeon, Sunghyun Park, Sungju Kim, Seonhoon Kim, Dongpil Seo, et al. What changes can large-scale language models bring? intensive study on hyperclova: Billions-scale korean generative pre-trained transformers. *arXiv preprint arXiv:2109.04650*, 2021. 10

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *PNAS*, 114(13):3521–3526, 2017. 1, 2

Hyunseo Koh, Dahyun Kim, Jung-Woo Ha, and Jonghyun Choi. Online continual learning on class incremental blurry task configuration with anytime inference. In *ICLR*, 2021. 1, 2, 3, 7, 9

David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *NeurIPS*, 2017. 2, 3

Zheda Mai, Ruiwen Li, Jihwan Jeong, David Quispe, Hyunwoo Kim, and Scott Sanner. Online continual learning in image classification: An empirical survey. *Neurocomputing*, 2022. 3, 6

Marc Masana, Xialei Liu, Bartlomiej Twardowski, Mikel Menta, Andrew D Bagdanov, and Joost van de Weijer. Class-incremental learning: survey and performance evaluation on image classification. *arXiv preprint arXiv:2010.15277*, 2020. 2

Ameya Prabhu, P. Torr, and Puneet K. Dokania. GDumb: A simple approach that questions our progress in continual learning. In *ECCV*, 2020. 1, 3, 7, 9

Jack W Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, et al. Scaling language models: Methods, analysis & insights from training gopher. *arXiv preprint arXiv:2112.11446*, 2021. 10

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H. Lampert. iCaRL: Incremental classifier and representation learning. In *CVPR*, 2017. 1, 2

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P Lillicrap, and Greg Wayne. Experience replay for continual learning. In *NeurIPS*, 2019. 2, 7

Gobinda Saha, Isha Garg, and Kaushik Roy. Gradient projection memory for continual learning. In *ICLR*, 2021. 1, 2

Murray Shanahan, Christos Kaplanis, and Jovana Mitrovic. Encoders and ensembles for task-free continual learning. *arXiv preprint arXiv:2105.13327*, 2021. 1, 2, 3

Zifeng Wang, Zizhao Zhang, Chen-Yu Lee, Han Zhang, Ruoxi Sun, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, and Tomas Pfister. Learning to prompt for continual learning. In *CVPR*, 2022. 1, 2, 3

Yue Wu, Yan-Jia Chen, Lijuan Wang, Yuancheng Ye, Zicheng Liu, Yandong Guo, and Yun Fu. Large scale incremental learning. In *CVPR*, 2019. 2, 6

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *ICCV*, pp. 6023–6032, 2019. 7

A APPENDIX

A.1 DETAILS ABOUT GAUSSIAN AND PERIODIC GAUSSIAN DATA STREAM SETUP

(a) Gaussian data stream   (b) Periodic-Gaussian data stream

Figure 5: Distribution for (a) Gaussian and (b) Periodic Gaussian data streams

The resulting distribution with $N = 4$ is depicted in Fig. 5-(a). The periodic Gaussian distributions with $N = 4$ and $R = 5$ are illustrated in Fig. 5-(b).

A.2 DERIVATION OF SDP RATIOS FROM MEAN AND VARIANCE

The weights of EMA is same as the pmf of geometric distribution, with k-th weight $w_\alpha(k)$ obtained as:

$$w_\alpha(k) = \alpha(1 - \alpha)^{k-1} \tag{12}$$

when α is the EMA ratio. Using the known mean and variance of geometric distribution, Thus, mean μ_α of EMA is obtained as:

$$\mu_\alpha = \sum_k^\infty k w_\alpha(k) = \frac{1}{\alpha} \tag{13}$$

The variance σ_α^2 is:

$$\sigma_\alpha^2 = \sum_k^\infty k^2 w_\alpha(k) - \mu_\alpha^2 = \frac{1 - \alpha}{\alpha^2} \tag{14}$$

Thus,

$$\sum_k^\infty k^2 w_\alpha(k) = \frac{1 - \alpha}{\alpha^2} + \frac{1}{\alpha^2} = \frac{2 - \alpha}{\alpha^2} \tag{15}$$

Using the definition of SDP . 7, we obtain $w_{(\alpha,\beta)}(k)$, the k-th weights of SDP with two ratios α and β as:

$$w_{(\alpha,\beta)}(k) = \frac{\alpha}{\alpha - \beta} w_\beta(k) - \frac{\beta}{\alpha - \beta} w_\alpha(k) \tag{16}$$

The mean $\mu_{(\alpha,\beta)}$ of SDP is calculated as:

$$
\begin{aligned}
\mu_{(\alpha,\beta)} &= \sum_k^\infty k w_{(\alpha,\beta)}(k) \\
&= \frac{\alpha}{\alpha - \beta} \sum_k^\infty k w_\beta(k) - \frac{\beta}{\alpha - \beta} \sum_k^\infty k w_\alpha(k) \\
&= \frac{\alpha}{\beta(\alpha - \beta)} - \frac{\beta}{\alpha(\alpha - \beta)} \\
&= \frac{\alpha + \beta}{\alpha\beta} = \frac{1}{\alpha} + \frac{1}{\beta}
\end{aligned}
\tag{17}
$$

Also, the variance $\sigma^2_{(\alpha,\beta)}$ of SDP is calculated as:

$$\sigma^2_{(\alpha,\beta)} = \sum_k^\infty k^2 w_{(\alpha,\beta)}(k) - \mu^2_{(\alpha,\beta)}$$

$$= \frac{\alpha}{\alpha - \beta} \sum_k^\infty k^2 w_\beta(k) - \frac{\beta}{\alpha - \beta} \sum_k^\infty k^2 w_\alpha(k) - \mu^2_{(\alpha,\beta)}$$

$$= \frac{\alpha(2 - \beta)}{\beta^2(\alpha - \beta)} - \frac{\beta(2 - \alpha)}{\alpha^2(\alpha - \beta)} - \frac{(\alpha + \beta)^2}{\alpha^2\beta^2}$$

$$= \frac{\alpha^2 + \beta^2 - \alpha\beta(\alpha + \beta)}{\alpha^2\beta^2} \tag{18}$$

Thus, the squared coefficient of variation $c^2 = \frac{\sigma^2}{\mu^2}$ is:

$$c^2 = \frac{(\alpha + \beta)^2 - \alpha\beta(\alpha + \beta + 2)}{(\alpha + \beta)^2} \tag{19}$$

Recall

$$\mu_{(\alpha,\beta)} = \frac{\alpha + \beta}{\alpha\beta} \tag{20}$$

Solving these equations for $\alpha + \beta$ and $\alpha\beta$ by substitution, we get

$$\alpha\beta = \frac{2}{c^2 - \mu^2 + 1} \tag{21}$$

$$\alpha + \beta = \frac{2\mu}{c^2 - \mu^2 + 1} \tag{22}$$

Solving this equations for α and β using quadratic formula, we get:

$$\alpha = \frac{1 + \sqrt{2c^2 + \frac{2}{\mu} - 1}}{\mu(1 - c^2) - 1}, \quad \beta = \frac{1 - \sqrt{2c^2 + \frac{2}{\mu} - 1}}{\mu(1 - c^2) - 1}. \tag{23}$$

A.3 ANALYSIS ON STANDARD DEVIATION OF GAUSSIAN DISTRIBUTION

We test CL methods on 4 different values of standard deviation for Gaussian data stream in CIFAR-10 and CIFAR-100. SDP outperform other methods in all tested values of $sigma$, showing that our model is robust to how spread out the distribution is.

Methods	Sigma=0				Sigma=10			
	$A_{\text{AUC}} \uparrow$	$A_{\text{last}} \uparrow$	$KLR_{\text{avg}} \downarrow$	$KGR_{\text{avg}} \uparrow$	$A_{\text{AUC}} \uparrow$	$A_{\text{last}} \uparrow$	$KRL_{\text{avg}} \downarrow$	$KGR_{\text{avg}} \uparrow$
ER	73.52±0.87	58.95±2.11	24.95±1.41	25.37±1.21	55.97±0.85	58.59±2.56	23.36±1.39	21.52±0.92
DER++	71.01±1.26	55.37±2.47	30.02±3.22	23.62±1.68	56.12±0.14	60.54±2.37	23.60±2.12	22.57±0.98
ER-MIR	71.69±0.91	56.01±2.06	28.68±4.43	23.69±0.52	56.48±0.18	59.38±2.83	25.04±1.67	21.72±0.16
GDumb	62.23±0.70	44.69±1.11	25.64±1.45	11.44±0.83	46.45±0.68	42.62±0.64	35.47±0.51	11.69±0.32
CLIB	73.62±0.87	56.21±3.30	28.68±4.43	23.69±0.52	63.01±0.31	65.24±2.10	20.79±1.64	22.52±1.92
SDP (Ours)	**76.89±1.22**	**66.19±3.48**	**15.86±1.74**	**25.68±2.61**	**66.51±0.42**	**76.29±0.50**	**10.75±1.48**	**23.19±1.16**

Methods	Sigma=25				Sigma=50			
	$A_{\text{AUC}} \uparrow$	$A_{\text{last}} \uparrow$	$KLR_{\text{avg}} \downarrow$	$KGR_{\text{avg}} \uparrow$	$A_{\text{AUC}} \uparrow$	$A_{\text{last}} \uparrow$	$KLR_{\text{avg}} \downarrow$	$KGR_{\text{avg}} \uparrow$
ER	60.42±0.80	68.74±2.45	18.32±1.42	26.89±1.81	58.25±0.85	58.59±2.56	23.36±1.39	21.52±0.92
DER++	58.25±0.73	68.58±0.79	16.96±1.67	**27.49±2.10**	64.39±0.91	75.82±1.38	12.56±0.88	**26.39±0.49**
ER-MIR	60.94±0.92	69.21±0.49	17.94±0.99	25.67±0.93	66.82±0.44	76.38±0.31	13.84±0.11	25.20±0.69
GDumb	41.19±0.18	41.79±0.82	43.04±2.11	12.45±0.24	41.65±0.16	42.62±0.59	39.20±2.20	12.98±0.75
CLIB	66.39±0.09	71.41±1.32	19.74±0.97	26.94±0.69	69.62±0.42	72.31±1.21	7.42±1.12	12.87±1.51
SDP (Ours)	**69.97±0.37**	**81.95±0.89**	**4.23±0.64**	20.67±2.30	**73.44±0.26**	**82.33±0.26**	**3.57±0.26**	16.24±0.59

Table 6: Comparison of Accuracy for different values of standard deviation for Gaussian data Stream in CIFAR-10

Methods	Sigma=0				Sigma=10			
	$A_{\mathrm{AUC}}\uparrow$	$A_{\mathrm{last}}\uparrow$	$KLR_{\mathrm{avg}}\downarrow$	$KGR_{\mathrm{avg}}\uparrow$	$A_{\mathrm{AUC}}\uparrow$	$A_{\mathrm{last}}\uparrow$	$KLR_{\mathrm{avg}}\downarrow$	$KGR_{\mathrm{avg}}\uparrow$
ER	49.21±1.05	39.86±0.52	58.02±0.97	13.83±0.45	36.93±0.77	40.93±0.35	51.77±0.87	17.42±0.50
DER++	46.03±1.29	37.60±0.75	59.95±1.18	13.79±0.63	28.77±0.67	34.48±0.62	48.83±1.49	17.35±0.16
ER-MIR	48.48±1.19	37.60±0.34	62.95±1.31	12.88±0.32	34.76±1.20	37.20±2.06	57.23±1.14	16.46±0.68
GDumb	37.80±0.31	24.77±0.68	79.33±3.13	9.04±0.14	28.81±0.74	25.38±0.26	86.75±2.07	8.54±0.34
CLIB	50.26±1.06	40.05±0.71	59.48±2.00	12.23±0.46	42.79±0.65	43.81±0.58	48.59±1.78	15.96±0.26
SDP (Ours)	**55.94±1.55**	**50.26±1.41**	**46.35±2.44**	**16.04±0.80**	**46.34±0.64**	**54.93±0.56**	**36.56±0.92**	**18.77±0.27**

Methods	Sigma=25				Sigma=50			
	$A_{\mathrm{AUC}}\uparrow$	$A_{\mathrm{last}}\uparrow$	$KLR_{\mathrm{avg}}\downarrow$	$KGR_{\mathrm{avg}}\uparrow$	$A_{\mathrm{AUC}}\uparrow$	$A_{\mathrm{last}}\uparrow$	$KLR_{\mathrm{avg}}\downarrow$	$KGR_{\mathrm{avg}}\uparrow$
ER	49.21±1.05	39.86±0.52	58.02±0.97	13.83±0.45	32.86±0.39	45.11±1.11	50.75±1.05	17.38±0.43
DER++	46.03±1.29	37.60±0.75	59.95±1.18	13.79±0.63	31.25±1.59	46.00±1.65	47.76±0.64	17.57±0.06
ER-MIR	48.48±1.19	37.60±0.34	62.95±1.31	12.88±0.32	31.85±0.17	44.60±0.17	53.32±0.98	16.40±0.30
GDumb	37.80±0.31	24.77±0.68	79.33±3.13	9.04±0.14	23.98±0.13	24.30±0.54	90.32±1.50	7.66±0.17
CLIB	40.06±0.20	46.90±0.87	49.71±0.60	16.51±0.09	50.26±1.06	40.05±0.71	59.48±2.00	12.23±0.46
SDP (Ours)	**43.88±0.57**	**55.32±0.50**	**32.92±0.68**	**20.00±0.24**	**46.50±0.42**	**55.97±0.33**	**32.89±0.25**	**21.57±0.10**

Table 7: Comparison of Accuracy for different values of standard deviation for Gaussian data Stream in CIFAR-100