PIVEN: A Deep Neural Network for Prediction Intervals with Specific Value Prediction

Abstract

Improving the robustness of neural nets in regression tasks is key to their application in multiple domains. Deep learning-based approaches aim to achieve this goal either by improving their prediction of specific values (i.e., point prediction), or by producing prediction intervals (PIs) that quantify uncertainty. We present PIVEN, a deep neural network for producing both a PI and a prediction of specific values. Unlike previous studies, PIVEN makes no assumptions regarding data distribution inside the PI, making its point prediction more effective for various read-world problems. Benchmark experiments show that our approach produces tighter uncertainty bounds than the current state-of-the-art approach for producing PIs, while maintaining comparable performance to the state-of-the-art approach for specific value-prediction. Additional evaluation on large image datasets further support our conclusions.

1 Introduction

Deep neural networks (DNNs) have been achieving state-of-the-art results in a large variety of complex problems. These include automated decision making and recommendation systems in the medical domain (Razzak et al., 2018), autonomous control of drones (Kaufmann et al., 2018) and self driving cars (Bojarski et al., 2016). In many of these domains, it is crucial not only that the prediction made by the DNN is accurate, but rather that its uncertainty is quantified. Quantifying uncertainty has many benefits, including risk reduction and more reliable planning (Khosravi et al., 2010).

In regression, uncertainty is quantified using prediction intervals (PIs), which offer upper and lower bounds on the value of a data point for a given probability (e.g., 95%). Existing non-Bayesian PI generation methods can be roughly divided into two groups: *a)* performing multiple runs of the regression problem, as in dropout (Gal & Ghahramani, 2016) or ensemble-based methods (Lakshminarayanan et al., 2017), then deriving post-hoc the PI from prediction variance, and; *b)* dedicated architectures for the PI generation (Pearce et al., 2018; Tagasovska & Lopez-Paz, 2019).

While effective, both approaches have shortcomings. On the one hand, the former group is not optimized for PIs generation, having to convert a set of sampled values into a distribution. This lack of PI optimization makes using these approaches difficult in domains such as financial risk mitigation or scheduling. For example, providing a PI for the number of days a machine can function without malfunctioning (e.g., 30-45 days with 99% certainty) is more valuable than a prediction for the specific time of failure. On the other hand, the latter group—PI-dedicated architectures —provides accurate upper and lower bounds for the prediction, but lacks in the accuracy of its value predictions. Consequently, these approaches select the middle of the interval as their value prediction, which is (as we later demonstrate) a sub-optimal strategy that makes assumptions regarding the value distribution within the interval. The shortcomings of PI-dedicated architectures with regard to value prediction are supported both by Pearce et al. (2018) and by our experiments in Section 5.

We propose PIVEN (**p**rediction **i**ntervals with specific **v**alue pr**e**dictio**n**), a novel approach for simultaneous PI generation and value prediction using DNNs. Our approach combines the benefits of both above-mentioned groups by producing *both* a PI and a value prediction, while ensuring that the latter is within the former. We follow the experimental procedure of recent works, and compare our approach to current best-performing methods: Quality-Driven PI (QD) by Pearce et al. (2018) (a dedicated PI generation method), and Deep Ensembles (DE) by DeepMind (Lakshminarayanan et al., 2017). Our results show that PIVEN outperforms QD by producing narrower PIs, while

simultaneously achieving comparable results to DE in terms of value prediction. Additional analysis on large image datasets and synthetic data shows that PIVEN performs well on skewed value distributions and can be effectively combined with pre-trained DNN architectures.

2 RELATED WORK

Modeling uncertainty in deep learning has been an active area of research in recent years (Pearce et al., 2018; Qiu et al., 2019; Gal & Ghahramani, 2016; Lakshminarayanan et al., 2017; Keren et al., 2018; Kendall & Gal, 2017; Geifman et al., 2018; Snoek et al., 2019). Studies in uncertainty modeling and regression can be generally divided into two groups: *PI-based* and *non-PI-based*.

Non-PI approaches utilize both Bayesian (MacKay, 1992) and non-Bayesian approaches. The former methods define a prior distribution on the weights and biases of a neural net (NN), while inferring a posterior distribution from the training data. Non-Bayesian methods (Gal & Ghahramani, 2016; Lakshminarayanan et al., 2017; Qiu et al., 2019) do not use initial prior distributions. In (Gal & Ghahramani, 2016), Monte Carlo sampling was used to estimate the predictive uncertainty of NNs through the use of dropout over multiple runs. A later study (Lakshminarayanan et al., 2017) employed a combination of ensemble learning and adversarial training to quantify model uncertainty. In an expansion of a previously-proposed approach (Nix & Weigend, 1994), each NN was optimized to learn the mean and variance of the data, assuming a Gaussian distribution. Recently, Qiu et al. (2019) proposed a post-hoc procedure using Gaussian processes to measure uncertainty.

PI-based approaches are designed to produce a PI for each sample. In Keren et al. (2018), the authors propose a post-processing approach that considers the regression problem as one of classification, and uses the output of the final softmax layer to produce PIs. The authors of Tagasovska & Lopez-Paz (2019) propose the use of a loss function designed to learn all conditional quantiles of a given target variable. LUBE (Khosravi et al., 2010) consists of a loss function optimized for the creation of PIs, but has the caveat of not being able to use stochastic gradient descent (SGD) for its optimization. A recent study (Pearce et al., 2018) inspired by LUBE, proposed a loss function that is both optimized for the generation of PIs and can be optimized using SGD.

Each of the two groups presented above tends to under-perform when applied to tasks for which its loss function was not optimized: Non-PI approaches produce more accurate value predictions, but are not optimized to produce PI and therefore produce bounds that are less tight. PI-based methods produce tight bounds, but tend to underperform when producing value predictions. Recent studies (Kivaranovic et al., 2019; Romano et al., 2019) attempted to produce both value predictions and PIs by using conformal prediction with quantile regression. While effective, these methods use a complex splitting strategy, where one part of the data is used to produce value predictions and PIs, while the the other part is to further adjust the PIs. Contrary to these approaches, PIVEN produces PIs with value predictions in an end-to-end manner by relying on a novel loss function.

3 PROBLEM FORMULATION

In this work we consider a neural network regressor that processes an input $x \in \mathcal{X}$ with an associated label $y \in \mathbb{R}$, where $\mathcal{X}$ can be any feature space (e.g., tabular data, age prediction from images). Let $(x_i, y_i) \in \mathcal{X} \times \mathbb{R}$ be a data point along with its target value. Let U_i and L_i be the upper and lower bounds of PIs corresponding to the ith sample. Our goal is to construct (L_i, U_i, y_i) so that $\Pr(L_i \leq y_i \leq U_i) \geq 1 - \alpha$. We refer to $1 - \alpha$ as the confidence level of the PI.

We define two quantitative measures for the evaluation of PIs, as defined in Khosravi et al. (2010). First, we define *coverage* as the ratio of dataset samples that fall within their respective PIs. We measure coverage using the *prediction interval coverage probability* (PICP) metric:

$$PICP := \frac{1}{n} \sum_{i=1}^{n} k_i \tag{1}$$

where n denotes the number of samples and $k_i = 1$ if $y_i \in (L_i, U_i)$, otherwise $k_i = 0$. Next, we define a quality metric for the generated PIs with the goal of producing as tight a bound as possible

while maintaining adequate coverage. We define the *mean prediction interval width* (MPIW) as,

$$MPIW := \frac{1}{n} \sum_{i=1}^{n} U_i - L_i \tag{2}$$

When combined, these metrics enable us to comprehensively evaluate the quality of generated PIs.

4 METHOD

4.1 SYSTEM ARCHITECTURE

The proposed architecture is presented in Figure 1. It consists of three components:

Backbone block. The main body block, consisting of a varying number of DNN layers or sub-blocks. The goal of this component is to transform the input into a latent representation that is then provided as input to the other components. It is important to note that PIVEN supports any architecture type (e.g., dense, convolutions) that can be applied to a regression problem. Moreover, pre-trained architectures can also be used seamlessly. For example, we use pre-trained VGG-16 and DenseNet architectures in our experiments.

Upper & lower-bound heads. $L(x)$ and $U(x)$ produce the lower and upper bounds of the PI respectively, such that $\mathrm{Pr}(L(x) \leq y(x) \leq U(x)) \geq 1 - \alpha$ where $y(x)$ is the value prediction and $1 - \alpha$ is the predefined confidence level.

Auxiliary head. The auxiliary prediction head, $v(x)$, enables us to produce a value prediction. $v(x)$ does not produce the value prediction directly, but rather produces the *relative weight that should be given to each of the two bounds*. We define the value prediction using,

$$y = v \cdot U + (1 - v) \cdot L \tag{3}$$

where $v \in (0, 1)$. By expressing y as a function of U and L, we *(a)* bound them together and improve their performance (see Section 4.3), and; *(b)* ensure that the value prediction falls within the PI.

Figure 1: The PIVEN schematic architecture

4.2 NETWORK OPTIMIZATION

Our goal is to generate narrow PIs, measured by *MPIW*, while maintaining the desired level of coverage $PICP = 1 - \alpha$. However, PIs that fail to capture their respective data point should not be encouraged to shrink further. We follow the derivation presented in Pearce et al. (2018) and define *captured MPIW* ($MPIW_{capt}$) as the $MPIW$ of only those points for which $L_i \leq y_i \leq U_i$,

$$MPIW_{capt} := \frac{1}{c} \sum_{i=1}^{n} (U_i - L_i) \cdot k_i \tag{4}$$

where $c = \sum_{i=1}^{n} k_i$. Hence, we seek to minimize $MPIW_{capt}$ subject to $PICP \geq 1 - \alpha$:

$$\theta^* = \arg\min_{\theta}(MPIW_{capt,\theta}) \ \ s.t \ \ PICP_\theta \geq 1 - \alpha$$

where θ is the parameters of the neural net. To enforce the coverage constraint, we utilize a variant of the well-known Interior Point Method (Potra & Wright, 2000), resulting in an unconstrained loss:

$$\mathcal{L}_{PI} = MPIW_{capt,\theta} + \sqrt{n} \cdot \lambda \Psi(1 - \alpha - PICP_\theta)$$
$$\Psi(x) := \max(0, x)^2$$

where λ is a hyperparameter controlling the relative importance of width vs. coverage, Ψ is a quadratic penalty function, and n is the batch size. We include dependency on batch size in the loss since a larger sample size increases confidence in the value of PICP, thus increasing the loss. In practice, optimizing the loss with a discrete version of $\mathbf{k}$ (see eq. 4) fails to converge, because the gradient is always positive for all possible values. We therefore define a continuous version of $\mathbf{k}$, denoted as $\mathbf{k}_{soft} = \sigma(s \cdot (\mathbf{y} - \mathbf{L})) \odot \sigma(s \cdot (\mathbf{U} - \mathbf{y}))$, where σ is the sigmoid function, and $s > 0$ is a softening factor. The final version of $\mathcal{L}_{PI}$ uses the continuous and discrete versions of $\mathbf{k}$ in its calculations of the $PICP$ and $MPIW_{capt}$ metrics, respectively. The discrete $\mathbf{k}$ enables us to assign a score of zero to points outside the interval, while $\mathbf{k}_{soft}$ produces continuous values that enable gradient calculations.

Neural networks optimized by the abovementioned objective are able to generate well-calibrated PIs. However, they have two significant drawbacks—*overfitting*, and *lack of value prediction capabilities*.

Overfitting. The $MPIW_{capt}$ term in $\mathcal{L}_{PI}$ focuses only on the fraction c of the training set where the data points are successfully captured by the PI. As a result, the network is likely to overfit to a subset of the data on which it was able to perform well in the first place. Our reasoning is supported by our experiments in sections 5 and 6.

Lack of value prediction capabilities. In its current form, $\mathcal{L}_{PI}$ is not able to perform value prediction, i.e., returning accurate prediction for the regression problem. To overcome this limitation, one can return the middle of the PI, as done in Pearce et al. (2018) and Tagasovska & Lopez-Paz (2019). This approach performs well only if the dataset value distribution is uniform or Gaussian (i.e., where choosing the mean minimizes prediction loss). For skewed distributions, as is often the case in the real world, this approach leads to sub-optimal results, as we show in Section 5.4.

We propose a novel loss function that combines the generation of both PIs and value predictions. To optimize the output of $v(x)$ (the auxiliary head), we minimize the standard regression loss,

$$\mathcal{L}_v = \frac{1}{n} \sum_{i=1}^{n} \ell(v_i \cdot U_i + (1 - v_i) \cdot L_i, \; y_i) \tag{5}$$

where ℓ is a regression objective against the ground-truth. Our final loss function is a convex combination of $\mathcal{L}_{PI}$, and the auxiliary loss $\mathcal{L}_v$. Thus, the overall training objective is:

$$\mathcal{L}_{PIVEN} = \beta \mathcal{L}_{PI} + (1 - \beta) \mathcal{L}_v \tag{6}$$

where β is a hyperparameter that balances the two goals of our approach: producing narrow PIs and accurate value predictions.

While PIs produced by a single PIVEN architecture could be used to capture data uncertainty, an ensemble of PIVEN architectures can capture the uncertainty of the PI itself. Given an ensemble of m NNs trained with $\mathcal{L}_{PIVEN}$, let $\tilde{U}$, $\tilde{L}$ represent the PI, and $\tilde{v}$, $\tilde{y}$ represent the ensemble's auxiliary and value prediction. We calculate the PI uncertainty and use the ensemble to generate the PIs and value predictions as follows:

$$\bar{U}_i = \frac{1}{m} \sum_{j=1}^{m} U_{ij} \tag{7} \qquad \sigma_{PI}^2 = \sigma_{U_i}^2 = \frac{1}{m-1} \sum_{j=1}^{m} (U_{ij} - \bar{U}_i)^2 \tag{9}$$

$$\tilde{U}_i = \bar{U}_i + z_{\alpha/2} \cdot \sigma_{U_i} \tag{8} \qquad \tilde{y}_i = \frac{1}{m} \sum_{j=1}^{m} v_{ij} \cdot U_{ij} + (1 - v_{ij}) \cdot L_{ij} \tag{10}$$

where $(U_{ij} \; L_{ij})$ and v_{ij} represents the PI and the auxiliary prediction for data point i, for NN j. A similar procedure is followed for $\tilde{L}_i$, subtracting $z_{\alpha/2} \cdot \sigma_{L_i}$, where $z_{\alpha/2}$ is the Z score for a confidence level $1 - \alpha$.

4.3 DISCUSSION OF CONTRIBUTIONS

PIVEN differs from previous studies in two important aspects. First, our approach is the first to propose an integrated architecture capable of producing both PIs and exact value predictions. Moreover, since the auxiliary head produces predictions for all training set samples, it prevents PIVEN from overfitting to data points which were contained in their respective PIs, which is a possible problem for studies such as Pearce et al. (2018). This ability improves PIVEN's performance, as shown in Section 5.

PIVEN's second differentiating aspect is its method for producing the value prediction. While previous studies either provided the middle of the PI (Pearce et al., 2018; Tagasovska & Lopez-Paz, 2019) or the mean-variance (Lakshminarayanan et al., 2017) as their value predictions, PIVEN's auxiliary head can produce any value within the PI as its prediction. By expressing the value prediction as a function of the upper and lower bounds, we ensure that the three heads are synchronized and that the prediction *always* falls within the PI. Our use of a *non-Gaussian observation model* enables us to produce predictions that are not in the middle of the interval and create representations that are more characteristic of many real-world cases, where the points within the PI is not necessarily uniformly distributed. Our experiments, presented in Sections 5.4 and 5.5 support our conclusions.

5 EVALUATION

5.1 DATASETS

UCI Datasets. We conduct our experiments on a set of benchmark datasets used by several state-of-the-art studies (Gal & Ghahramani, 2016; Hernández-Lobato & Adams, 2015; Lakshminarayanan et al., 2017; Pearce et al., 2018). This benchmark includes ten datasets (Asuncion & Newman, 2007).

IMDB age estimation dataset. The IMDB-WIKI dataset (Rothe et al., 2018) is currently the largest age-labeled facial dataset available. Our dataset consists of 460,723 images from 20,284 celebrities, and the regression goal is to predict the age of the person in the image. It is important to note that this dataset is known to contain noise (i.e., aleatoric uncertainty), thus making it highly relevant to this study (despite usually being used for pre-training).

RSNA pediatric bone age dataset. This dataset is a popular medical imaging dataset consisting of X-ray images of children's hands (Halabi et al., 2019). The regression task is predicting one's age from one's bone image. The dataset contains 12,611 training images and 200 test set images.

While the first group of datasets enables us to compare PIVEN's performance to recent state-of-the-art studies in the field, the two latter datasets enable us to demonstrate that our approach is both scalable and effective on multiple types of input.

5.2 BASELINES

We compare our performance to two top-performing NN-based baselines from recent years:

Quality driven PI (QD) (Pearce et al., 2018). This approach produces PIs that minimize a smooth combination of the PICP/MPIW metrics without considering the value prediction task in its objective function. Its reported results make this approach state-of-the-art in terms of PI width and coverage.

Deep Ensembles (DE) (Lakshminarayanan et al., 2017). This work combines individual conditional Gaussian distribution with adversarial training, and uses the models' variance to compute prediction intervals. Because DE outputs distributions instead of PIs, we first convert it to PIs, and then compute PICP and MPIW. Its reported results make this method one of the top performers with respect to the RMSE metric (i.e., value prediction).

By comparing PIVEN to these two baselines, we are able to evaluate its ability to simultaneously satisfy the two main requirements for regression problems in domains with high certainty.

5.3 EXPERIMENTAL SETUP

Throughout our experiments, we evaluate our two baselines using their reported deep architectures and hyperparmeters. For full experimental details, please see Appendix A. We ran our experiments using a GPU server with two NVIDIA Tesla P100. Our code is implemented using TensorFlow and Keras (Abadi et al., 2016; Chollet et al., 2015), and made available online[1].

UCI datasets. We use the experimental setup proposed by Hernández-Lobato & Adams (2015), which was also used by our baselines. Results are averaged on 20 random 90%/10% splits of the data, except for the "Year Prediction MSD" and "Protein", which were split once and five times respectively. Our network architecture is identical to that of our two baselines: one hidden layer with ReLU activation function (Nair & Hinton, 2010), and the Adam optimizer (Kingma & Ba, 2014). Input and target variables are normalized to zero mean and unit variance.

IMDB age estimation dataset. We use the DenseNet architecture (Huang et al., 2017) as the backbone block, then add two dense layers. We apply the data preprocessing used in (Yang et al., 2018). We report the results for 5-fold cross validation.

RSNA bone age dataset. We use the VGG-16 architecture (Simonyan & Zisserman, 2014) as the backbone block, with weights pre-trained on ImageNet. We then add two convolutional layers followed by a dense layer. This dataset has a predefined test set of 200 images.

5.4 UCI DATASETS EVALUATION RESULTS AND ANALYSIS

We use two evaluation metrics: MPIW and RMSE, with results presented in Table 1. The desired coverage, measured by PICP, was set to 95%. In terms of PI-quality, PIVEN outperforms QD in nine out of ten datasets (although no method reached the required PICP in the "Boston" and "Concrete" datasets), while achieving equal performance in the remaining dataset. DE trails behind PIVEN and QD in most datasets, which is to be expected since this approach does not attempt to optimize MPIW. For the RMSE metric, it is clear that PIVEN and DE are the top performers, with the former achieving the best results in five datasets, and the latter in four. The QD baseline trails behind the other methods in all datasets but one. QD's performance is not surprising given that the focus of this approach is PI generation rather than value prediction.

The results of our experiments clearly show that PIVEN is capable of providing accurate value predictions for regression problems (i.e., achieving competitive results with the top-performing DE baseline) while achieving state-of-the-art results in uncertainty modeling by the use of PIs.

Analysis. In Section 4.3 we describe our rationale in expressing the value prediction as a function of the upper and lower bounds of the interval. To further explore the benefits of our auxiliary head v, we evaluate two variants of PIVEN. In the first variant, denoted as POO (point-only optimization), we decouple the value prediction from the PI. The loss function of this variant is $\mathcal{L}_{PI} + \ell(v, y_{true})$ where ℓ is set to be MSE loss. In the second variant, denoted MOI (middle of interval), the value prediction produced by the model is always the middle of the PI (in other words, v is set to 0.5).

The results of our analysis are presented in Table 2, which contains the results of the MPIW and RMSE metrics (the PICP values are identical for all variants and are therefore omitted—see full results in Appendix B). The full PIVEN significantly outperforms the two other variants. This leads us to conclude that both novel aspects of our approach—the simultaneous optimization of PI-width and RMSE, and the ability to select any value on the PI as the value prediction—contribute to PIVEN's performance. Finally, it is important to note that while inferior to PIVEN, both the POO and MOI variants outperform the QD baseline in terms of MPIW, while being equal or better for RMSE.

5.5 LARGE-SCALE IMAGE DATASETS

We now evaluate PIVEN on two large and noisy image datasets: bone age and age estimation. Since training the DE approach on datasets of this size is computationally prohibitive, we instead use a dense layer on top of the used architecture (DenseNet/VGG, see Section 5.3) that outputs value prediction using the MSE metric. In doing so, we follow the approach used in Qiu et al. (2019) for similar evaluation. We refer to this architecture as *NN*, because of the dense layer we add.

---

[1]https://github.com/anonymous/anonymous

Table 1: Regression results on UCI datasets comparing PICP, MPIW and RMSE with desired coverage of 95%. Approach with PICP ≥ 0.95 was defined as best for PICP. For MPIW, lower is better.

Datasets	PICP			MPIW			RMSE		
	DE	QD	PIVEN	DE	QD	PIVEN	DE	QD	PIVEN
Boston	0.87 ± 0.01	$\mathbf{0.93 \pm 0.01}$	$\mathbf{0.93 \pm 0.01}$	0.87 ± 0.03	1.15 ± 0.02	1.09 ± 0.01	$\mathbf{2.87 \pm 0.19}$	3.39 ± 0.26	3.13 ± 0.21
Concrete	0.92 ± 0.01	$\mathbf{0.93 \pm 0.01}$	$\mathbf{0.93 \pm 0.01}$	1.01 ± 0.02	1.08 ± 0.01	1.02 ± 0.01	$\mathbf{5.21 \pm 0.09}$	5.88 ± 0.10	5.43 ± 0.13
Energy	$\mathbf{0.99 \pm 0.01}$	0.97 ± 0.01	$\mathbf{0.97 \pm 0.01}$	0.49 ± 0.01	0.45 ± 0.01	0.42 ± 0.01	1.68 ± 0.06	2.28 ± 0.04	$\mathbf{1.65 \pm 0.03}$
Kin8nm	$\mathbf{0.97 \pm 0.00}$	0.96 ± 0.00	0.96 ± 0.00	1.14 ± 0.00	1.18 ± 0.00	1.10 ± 0.00	0.08 ± 0.00	0.08 ± 0.00	$\mathbf{0.07 \pm 0.00}$
Naval	$\mathbf{0.98 \pm 0.00}$	0.97 ± 0.00	$\mathbf{0.98 \pm 0.00}$	0.31 ± 0.01	0.27 ± 0.00	0.24 ± 0.00	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00
Power	$\mathbf{0.96 \pm 0.00}$	0.96 ± 0.00	0.96 ± 0.00	0.91 ± 0.00	0.86 ± 0.00	0.86 ± 0.00	3.99 ± 0.04	4.14 ± 0.04	4.08 ± 0.04
Protein	$\mathbf{0.96 \pm 0.00}$	0.95 ± 0.00	0.95 ± 0.00	2.68 ± 0.01	2.27 ± 0.01	2.26 ± 0.01	$\mathbf{4.36 \pm 0.02}$	4.99 ± 0.02	4.35 ± 0.02
Wine	0.90 ± 0.01	$\mathbf{0.91 \pm 0.01}$	$\mathbf{0.91 \pm 0.01}$	2.50 ± 0.02	2.24 ± 0.02	2.22 ± 0.01	0.62 ± 0.01	0.67 ± 0.01	0.63 ± 0.01
Yacht	$\mathbf{0.98 \pm 0.01}$	0.95 ± 0.01	$\mathbf{0.95 \pm 0.01}$	0.33 ± 0.02	0.18 ± 0.00	0.17 ± 0.00	1.38 ± 0.07	1.10 ± 0.06	$\mathbf{0.98 \pm 0.07}$
MSD	$\mathbf{0.95 \pm NA}$	$\mathbf{0.95 \pm NA}$	$\mathbf{0.95 \pm NA}$	$2.91 \pm NA$	$2.45 \pm NA$	$\mathbf{2.42 \pm NA}$	$8.95 \pm NA$	$9.30 \pm NA$	$\mathbf{8.93 \pm NA}$

Table 2: Analysis comparing MPIW and RMSE. Results were analyzed as in Table 1.

Datasets	MPIW			RMSE		
	POO	MOI	PIVEN	POO	MOI	PIVEN
Boston	$\mathbf{1.09 \pm 0.02}$	1.15 ± 0.02	$\mathbf{1.09 \pm 0.01}$	3.21 ± 0.24	3.39 ± 0.27	$\mathbf{3.13 \pm 0.21}$
Concrete	$\mathbf{1.02 \pm 0.01}$	1.07 ± 0.01	$\mathbf{1.02 \pm 0.01}$	5.55 ± 0.11	5.73 ± 0.10	$\mathbf{5.43 \pm 0.13}$
Energy	$\mathbf{0.42 \pm 0.01}$	0.45 ± 0.01	$\mathbf{0.42 \pm 0.01}$	2.16 ± 0.04	2.27 ± 0.04	$\mathbf{1.65 \pm 0.03}$
Kin8nm	1.13 ± 0.00	1.17 ± 0.00	$\mathbf{1.10 \pm 0.00}$	0.08 ± 0.00	0.08 ± 0.00	$\mathbf{0.07 \pm 0.00}$
Naval	$\mathbf{0.24 \pm 0.00}$	0.30 ± 0.02	$\mathbf{0.24 \pm 0.00}$	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00
Power	$\mathbf{0.86 \pm 0.00}$	$\mathbf{0.86 \pm 0.00}$	$\mathbf{0.86 \pm 0.00}$	4.13 ± 0.04	4.15 ± 0.04	$\mathbf{4.08 \pm 0.04}$
Protein	$\mathbf{2.25 \pm 0.01}$	2.27 ± 0.01	2.26 ± 0.01	4.78 ± 0.02	4.99 ± 0.02	$\mathbf{4.35 \pm 0.02}$
Wine	2.24 ± 0.01	2.23 ± 0.01	$\mathbf{2.22 \pm 0.01}$	0.64 ± 0.01	0.67 ± 0.01	0.63 ± 0.01
Yacht	0.18 ± 0.00	0.19 ± 0.01	$\mathbf{0.17 \pm 0.00}$	0.99 ± 0.07	1.15 ± 0.08	$\mathbf{0.98 \pm 0.07}$
MSD	$\mathbf{2.42 \pm NA}$	$2.43 \pm NA$	$\mathbf{2.42 \pm NA}$	$9.10 \pm NA$	$9.25 \pm NA$	$\mathbf{8.93 \pm NA}$

Our results are presented in Table 3. We use *mean absolute error* (MAE), which was the datasets' chosen metric. For the IMDB age prediction dataset, results show that PIVEN outperforms both baselines across all metrics. It is particularly noteworthy that our approach achieves *both* higher coverage and tighter PIs compared to QD. We attribute the significant improvement in MPIW – 17% – to the fact that this dataset has relatively high degrees of noise (Yang et al., 2018). In the bone age dataset, PIVEN outperforms both baselines in terms of MAE. Our approach fares slightly worse compared to QD on the MPIW metric, but that is likely due to its higher coverage (i.e., PICP).

Our results support our hypothesis that for large and high-dimensional data (and in particular those with high degrees of noise), PIVEN is likely to outperform previous work due to its ability to combine value predictions with PI generation. PIVEN produces tighter PIs and place the value prediction more accurately within the PI. A detailed analysis of the training process – in terms of training/validation loss, MAE, PICP and MPIW – is presented in Appendix D and further supports our conclusions.

Table 3: Results on the RSNA bone age and IMDB age estimation datasets.

Datasets	Method	PICP	MPIW	MAE
Bone age	NN	NA	NA	18.68
	PIVEN	$\mathbf{0.93}$	2.09	$\mathbf{18.13}$
	QD	0.9	$\mathbf{1.99}$	20.24
IMDB age	NN	NA	NA	7.08 ± 0.03
	PIVEN	$\mathbf{0.95 \pm 0.01}$	$\mathbf{2.87 \pm 0.04}$	$\mathbf{7.03 \pm 0.04}$
	QD	0.92 ± 0.01	3.47 ± 0.03	10.23 ± 0.12

6 DISCUSSION

6.1 VALUE PREDICTION IN NON-UNIFORM PI DISTRIBUTIONS

As noted in Pearce et al. (2018), the QD baseline's approach of producing value predictions inside the PI "breaks the distribution-free assumption". This means that for value distributions that are neither uniform nor Gaussian, QD's approach of returning the middle of the interval as the value is likely sub-optimal. To test this hypothesis, we evaluate PIVEN and QD on the Sine and skewed-normal distributions. The results, presented in Figure 2 (for skewed-normal) and Appendix A.1 (for Sine), clearly illustrate PIVEN's superior ability to adapt to multiple value distributions.

Figure 2: Value prediction comparison, where y is sampled from skewed-normal distribution.

6.2 PI Performance as a Function of Coverage

In Section 4.3 we argue that PIVEN's auxiliary head has the secondary effect of enabling it to train on the entire training set rather than only on the data points captured within their PIs. We argue that this property makes PIVEN more robust compared to current SOTA benchmarks. We explore the effects of capturing a smaller percentage of data points (i.e., smaller coverage) on the performance of both PIVEN and QD. Given that QD ignores such data points, it will optimize its performance for a smaller training set. A summary of the MPIW results is presented in Table 4 and full results are in Appendix C. As the coverage decreases, PIVEN's relative performance to QD continually improves. Interestingly, PIVEN's RMSE performance remains unchanged (Figure 3). The results clearly support our hypothesis regarding PIVEN's training robustness to points outside the PI.

Datasets	alpha					
	0.05	0.10	0.15	0.20	0.25	0.30
Boston	7%	7%	6%	7%	8%	8%
Concrete	7%	7%	8%	7%	12%	13%
Energy	6%	12%	8%	17%	19%	27%
Kin8nm	5%	7%	9%	19%	13%	15%
Naval	10%	16%	16%	14%	17%	23%
Power	0%	0%	1%	1%	1%	1%
Protein	1%	1%	2%	3%	2%	2%
Wine	0%	1%	2%	2%	4%	4%
Yacht	8%	12%	14%	20%	20%	21%
MSD	1%	-3%	-3%	1%	-5%	-2%
Mean	**4.5%**	**6.0%**	**6.3%**	**9.1%**	**9.1%**	**11.2%**

Table 4: MPIW improvement in percentages (PIVEN relative to QD) as the coverage decreases (i.e, alpha increases).

Figure 3: RMSE as function of α on two of the UCI datasets. See Appendix C for full results.

7 Conclusions

We present PIVEN, a novel deep architecture which is the first to combine the generation of prediction intervals together with specific value predictions in an end-to-end manner. By optimizing for these two goals simultaneously we are able to produce tighter intervals while at the same time achieving greater quality in our value predictions. PIVEN's performance is enhanced by two factors. First, its value-prediction and PI-prediction are connected, making it better able to model non-uniform value distributions in the PI, making it different from previous approaches. Secondly, PIVEN does not ignore but rather trains on data points that are not captured by the PI. Extensive evaluation on known benchmarks, large image datasets and synthetic data support our conclusions and show PIVEN's superior performance.

REFERENCES

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning. In *12th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 16)*, pp. 265–283, 2016.

Arthur Asuncion and David Newman. Uci machine learning repository, 2007.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, et al. End to end learning for self-driving cars. *arXiv preprint arXiv:1604.07316*, 2016.

François Chollet et al. Keras. `https://keras.io`, 2015.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059, 2016.

Yonatan Geifman, Guy Uziel, and Ran El-Yaniv. Bias-reduced uncertainty estimation for deep neural classifiers. *arXiv preprint arXiv:1805.08206*, 2018.

Safwan S Halabi, Luciano M Prevedello, Jayashree Kalpathy-Cramer, Artem B Mamonov, Alexander Bilbily, Mark Cicero, Ian Pan, Lucas Araújo Pereira, Rafael Teixeira Sousa, Nitamar Abdala, et al. The rsna pediatric bone age machine learning challenge. *Radiology*, 290(2):498–503, 2019.

José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of bayesian neural networks. In *International Conference on Machine Learning*, pp. 1861–1869, 2015.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Elia Kaufmann, Antonio Loquercio, Rene Ranftl, Alexey Dosovitskiy, Vladlen Koltun, and Davide Scaramuzza. Deep drone racing: Learning agile flight in dynamic environments. *arXiv preprint arXiv:1806.08548*, 2018.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In *Advances in neural information processing systems*, pp. 5574–5584, 2017.

Gil Keren, Nicholas Cummins, and Björn Schuller. Calibrated prediction intervals for neural network regressors. *IEEE Access*, 6:54033–54041, 2018.

Abbas Khosravi, Saeid Nahavandi, Doug Creighton, and Amir F Atiya. Lower upper bound estimation method for construction of neural network-based prediction intervals. *IEEE transactions on neural networks*, 22(3):337–346, 2010.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Danijel Kivaranovic, Kory D Johnson, and Hannes Leeb. Adaptive, distribution-free prediction intervals for deep neural networks. *arXiv preprint arXiv:1905.10634*, 2019.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in neural information processing systems*, pp. 6402–6413, 2017.

David JC MacKay. A practical bayesian framework for backpropagation networks. *Neural computation*, 4(3):448–472, 1992.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th international conference on machine learning (ICML-10)*, pp. 807–814, 2010.

David A Nix and Andreas S Weigend. Estimating the mean and variance of the target probability distribution. In *Proceedings of 1994 ieee international conference on neural networks (ICNN'94)*, volume 1, pp. 55–60. IEEE, 1994.

Tim Pearce, Mohamed Zaki, Alexandra Brintrup, and Andy Neely. High-quality prediction intervals for deep learning: A distribution-free, ensembled approach. *arXiv preprint arXiv:1802.07167*, 2018.

Florian A Potra and Stephen J Wright. Interior-point methods. *Journal of Computational and Applied Mathematics*, 124(1-2):281–302, 2000.

Xin Qiu, Elliot Meyerson, and Risto Miikkulainen. Quantifying point-prediction uncertainty in neural networks via residual estimation with an i/o kernel. *arXiv preprint arXiv:1906.00588*, 2019.

Muhammad Imran Razzak, Saeeda Naz, and Ahmad Zaib. Deep learning for medical image processing: Overview, challenges and the future. In *Classification in BioApps*, pp. 323–350. Springer, 2018.

Yaniv Romano, Evan Patterson, and Emmanuel Candes. Conformalized quantile regression. In *Advances in Neural Information Processing Systems*, pp. 3538–3548, 2019.

Rasmus Rothe, Radu Timofte, and Luc Van Gool. Deep expectation of real and apparent age from a single image without facial landmarks. *International Journal of Computer Vision*, 126(2-4): 144–157, 2018.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Jasper Snoek, Yaniv Ovadia, Emily Fertig, Balaji Lakshminarayanan, Sebastian Nowozin, D Sculley, Joshua Dillon, Jie Ren, and Zachary Nado. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, pp. 13969–13980, 2019.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Natasa Tagasovska and David Lopez-Paz. Single-model uncertainties for deep learning. In *Advances in Neural Information Processing Systems*, pp. 6414–6425, 2019.

Tsun-Yi Yang, Yi-Hsuan Huang, Yen-Yu Lin, Pi-Cheng Hsiu, and Yung-Yu Chuang. Ssr-net: A compact soft stagewise regression network for age estimation. In *IJCAI*, volume 5, pp. 7, 2018.

Yunxuan Zhang, Li Liu, Cheng Li, et al. Quantifying facial age by posterior of age comparisons. *arXiv preprint arXiv:1708.09687*, 2017.