EXPLOITING CLASS ACTIVATION VALUE FOR PARTIAL-LABEL LEARNING

ABSTRACT

Partial-label learning (PLL) solves the multi-class classification problem, where each training instance is assigned a set of candidate labels that include the true label. Recent advances showed that PLL can be compatible with deep neural networks, which achieved state-of-the-art performance. However, most of the existing deep PLL methods focus on designing proper training objectives under various assumptions on the collected data, which may limit their performance when the collected data cannot satisfy the adopted assumptions. In this paper, we propose to exploit the learned intrinsic representation of the model to identify the true label in the training process, which does not rely on any assumptions on the collected data. We make two key contributions. As the first contribution, we empirically show that the *class activation map* (CAM), a simple technique for discriminating the learning patterns of each class in images, is surprisingly better at making accurate predictions than the model itself on selecting the true label from candidate labels. Unfortunately, as CAM is confined to image inputs with convolutional neural networks, we are yet unable to directly leverage CAM to address the PLL problem with general inputs and models. Thus, as the second contribution, we propose the *class activation value* (CAV), which owns similar properties of CAM, while CAV is versatile in various types of inputs and models. Building upon CAV, we propose a novel method named CAV Learning (CAVL) that selects the true label by the class with the maximum CAV for model training. Extensive experiments on various datasets demonstrate that our proposed CAVL method achieves state-of-the-art performance.

1 INTRODUCTION

To liberate humans from exhaustive label annotation work, numerous researchers have dedicated themselves to investigating various *weakly supervised learning* (WSL) (Zhou, 2017) problems, including but not limited to noisy-label learning (Natarajan et al., 2013; Liu & Tao, 2015; Lukasik et al., 2020), semi-supervised learning (Zhu & Goldberg, 2009; Miyato et al., 2018; Luo et al., 2018), and multiple-instance learning (Zhou et al., 2012). This paper focuses on another popular WSL problem called *partial-label learning* (PLL) (Jin & Ghahramani, 2002; Cour et al., 2011), which aims to learn a model from training examples equipped with a set of candidate labels that include the true label. Due to the cost and difficulty of annotating every example exactly with the true label in huge datasets, PLL has been widely applied to various tasks such as multimedia context analysis (Zeng et al., 2013) and web mining (Luo & Orabona, 2010).

To solve the PLL problem, there are two mainstream strategies to discriminate the unknown true label from candidate labels, including the *average-based strategy* (ABS) and the *identification-based strategy* (IBS). ABS always treats each candidate label equally and averages the model outputs of all candidate labels for prediction (Hüllermeier & Beringer, 2006; Cour et al., 2011; Feng et al., 2020; Yao et al., 2020; Wen et al., 2021). IBS concentrates on iteratively selecting one label from the candidate label set as the true label to exclude the uncertainty, forming PLL into an ordinary classification problem (Jin & Ghahramani, 2002; Liu & Dietterich, 2014; Zhang & Yu, 2015; Zhang et al., 2016). Among these methods, only several of them (Yao et al., 2020; Wen et al., 2021) can be compatible with deep neural networks, which achieved state-of-the-art performance.

Most of the existing PLL methods aim at designing proper training objectives under various assumptions on the collected data. For example, the consistent methods proposed by Feng et al. (2020) are based on a specific data generation assumption. The derivation of the PRODEN method (Lv et al., 2020) stems from the assumption that the true label achieves the minimal loss among the candidate labels. Yan & Guo (2021) proposed the MGPLL method based on the assumption of non-random label noise. Although these methods have achieved generally great empirical performance, their performance could be degraded when the collected data cannot meet the adopted assumptions.

In this paper, we aim to investigate a novel PLL method by exploiting the learned intrinsic representation of the model to identify the ground truth in the training process without relying on any assumptions on the collected data. We focus on the *class activation map* (CAM) (Zhou et al., 2016), which is a prevailing tool for visualizing the representation information of *convolutional neural network* (CNN)-based models and could be easily obtained by the weighted linear sum of the feature maps. As CAM is able to discriminate the learning patterns of each class for the model, we conjecture that CAM could be used to guide the model to spot the true label. To verify this assumption, we conducted a pilot experiment on CIFAR-10 (Krizhevsky et al., 2009) by treating all the labels from the candidate set as the true label, where the candidate label sets were generated in two different ways. As shown in Figure 1 (please refer to Section 2.2), it is surprising to find that CAM can recognize more true labels than the model outputs, and such capacity of CAM synchronously changes with the classifier during the whole training phase. Based on the experimental results, it can be conjectured that the model could learn the intrinsic representations, which can be useful to distinguish the true label from candidate labels for PLL.

Motivated by the above observations, we naturally consider leveraging CAM to solve the PLL problem. However, CAM was only proposed for addressing image datasets with using deep models built on CNN, revealing two limitations on its application. Firstly, CAM cannot be adopted to the classifier based on shallow models such as the linear model and *multilayer perceptron* (MLP). Secondly, CAM is unable to deal with any inputs other than the image. To overcome these shortcomings, we for the first time propose a simple but effective tool—the *class activation value* (CAV) to capture the learned representation information in a more general way, which is essentially the weighted outputs of the classifier. Differently from CAM, where the weight parameters for the feature maps are the weights of the final linear layer, we take advantage of the gradient of the output entropy with respect to the logit as the weight for the class-related output. Figure 1 also shows that our CAV works similarly as CAM during the training phase.

Building upon CAV, we propose a simple yet effective PLL method called CAV Learning (CAVL) that guides the model to differentiate the true label from the candidate set during the training process. Specifically, we first train the model by treating all candidate labels equally and obtain CAVs of given training examples, and then regard the class with the maximum CAV as the true label for each instance during the training process. In this way, CAVL transforms PLL into supervised learning, thereby making the model reliable to recognize the true label with learned representation information by CAV. Extensive experiments on benchmark-simulated and real-world datasets show that our proposed CAVL method achieves state-of-the-art performance.

2 DISCOVERING CLASS ACTIVATION MAP FOR PARTIAL-LABEL LEARNING

In this section, we provide a detailed discussion about our motivation and empirically show that the class activation map could be more helpful than the model output for PLL.

2.1 CLASS ACTIVATION MAP

The *class activation map* (CAM) (Zhou et al., 2016) is a popular and elementary mechanism in computer vision to represent the discriminative part of an input image captured by the classifier to identify each class. In other words, CAM manifests the learning patterns of the classifier, denoted as f, to the specific class in the image. Let us denote an input image as $\boldsymbol{x} \in \mathbb{R}^{d=c \times h \times w}$ (with c channels, height h and width w) and CAM of $\boldsymbol{x} \in \mathbb{R}^{d=c \times h \times w}$ as $\boldsymbol{m} \in \mathbb{R}^{k \times h \times w}$ where k is the number of classes. We note that $\boldsymbol{m}$ could be generated by training a specific classification model f_c, which normally comprises of an encoder function $e : \mathbb{X} \to \mathbb{R}^{c_f \times h \times w}$ for feature map extraction, a Global Average-Pooling layer $gap : \mathbb{R}^{c_f \times h \times w} \to \mathbb{R}^{c_f \times 1}$, and a linear layer with weight $\boldsymbol{\theta} \in \mathbb{R}^{k \times C_f}$,

(a) IM with ResNet   (b) IM with DenseNet

IM in (a) is implemented by ResNet with using USS to generate the candidate set. IM in (b) is conducted in DenseNet with the candidate label sets produced by FPS. For three lines representing accuracy performance, the training accuracy of "CAM (CAV)" drawn by the blue (red) line is obtained by regarding the class with the most number of activated seeds in its CAM (the maximum CAV score) as the true label. "Model Output" drawn by the orange dashed line refers to the training accuracy of the classifier. The paired circle indicates the similar accuracy fluctuation between the classifier and the CAM (or our CAV), which shows the `dynamic` attribute. The double arrow marks the performance gap between the CAM (or our CAV) and the basic output, which represents the `power` attribute.

Figure 1: Comparison of accuracy performance obtained by the model output, CAM and CAV.

where c_f is the number of channels in the feature maps. Therefore, CAM of $\boldsymbol{x}$ related to the j-th class could be obtained by

$$\boldsymbol{m}^j = \sum_{i=1}^{C_f} (\boldsymbol{\theta}^j)_i e^i(\boldsymbol{x}), j \in \{1, \ldots, k\}, \tag{1}$$

where $\boldsymbol{\theta}^j \in \mathbb{R}^{1 \times C_f}$ is the corresponding linear weight related to the j-th object. CAM is a weighted linear sum of feature maps and the linear weights. The weakness of CAM is the limited applications, since not all classification network architectures follow the model f_c mentioned above. To improve its generalization for any CNN-based model f, *Gradient-weighted CAM* (Grad-CAM) (Selvaraju et al., 2017) was proposed to implement such an internal representation by reasonably leveraging class-specific gradient information. Concretely, let us denote by $\boldsymbol{g}^j \in \mathbb{R}^{d=c \times h \times w}$ the Grad-CAM of $\boldsymbol{x}$ related to the j-th object, and $\boldsymbol{g}^j$ could be expressed as

$$\boldsymbol{g}^j = \frac{1}{h \times w} \sum_{z=1}^{c_f} \sum_{m=1}^{h} \sum_{n=1}^{w} \frac{\partial f^j(\boldsymbol{x})}{\partial e^z(\boldsymbol{x})_{m,n}} e^z(\boldsymbol{x}). \tag{2}$$

Intuitively, the derivative of logit $f(\boldsymbol{x})$ with respect to feature map $e(\boldsymbol{x})$ is used as the weights for calculating $\boldsymbol{g}$. Note that both Grad-CAM and CAM are generated by weighted sums of the feature maps, and Grad-CAM is equivalent to CAM when f follows the same architecture as f_c. Based on Grad-CAM, Grad-CAM++ (Chattopadhay et al., 2018) aims to provide better visual explanations of CNN and occurrences of multiple foreground objects. Thanks to such a simple technique, numerous problems in computer vision such as *interpretation* (Xu et al., 2019a) and *weakly supervised semantic segmentation* (Wei et al., 2016) have achieved marvelous progress. In this paper, we aim to extract and improve the knowledge from CAM to address the PLL problem, leading the classifier to identify the ground truth.

2.2 PILOT EXPERIMENT ON CAM

Generally, Grad-CAM or CAM is treated as the internal knowledge of f. We believe that such a mechanism could guide f to differentiate the true label from the candidate set because it is constructed by taking advantage of internal elements in f. To validate our conjecture, we conducted a pilot experiment using an *intuitive method* (IM) to solve the PLL problem, which simply regards all

the labels from the candidate sets as the true label with using cross entropy loss. The label candidate label sets were generated by two different approaches: *(I) Uniformly Sampling Strategy* (USS). Uniformly sampling the candidate label set for each training instance from all the possible candidate label sets (Feng et al., 2020). *(II) Flipping Probability Strategy* (FPS). By setting a flipping probability q to any false label, the false label could be selected as a candidate label with a probability q (Feng & An, 2019a; Yan & Guo, 2020; Lv et al., 2020; Wen et al., 2021). Here the detailed training settings of the experiments are similar to the experiment part (please refer to Section 4.1.1 for details). ResNet (He et al., 2016) and DenseNet (Huang et al., 2017) were chosen as the backbones to train a classifier on CIFAR-10 (Krizhevsky et al., 2009). During each training epoch, we calculated the number of the positive elements in CAM of every class, i.e., foreground seeds, from each candidate label set. Finally, we checked whether CAM with the most foreground seeds belongs to the true label.

Figure 1 shows the average results of 5-time trials and we can find that CAM demonstrates two helpful features during the training phase. Firstly, it is clear that CAM is better at recognizing the true labels than the classifier itself on the training dataset. Secondly, the training process of IM is somewhat unstable, which is caused by the false positive labels. Surprisingly, we can also find that the accuracy of identifying true labels by CAM is synchronously changed with that by the classifier. Several fluctuations (marked by the paired circle) of the classifier accuracy and CAM accuracy are similar to a large extent. Here we name these two observed features of CAM the `power` and `dynamic` attributes. The `power` and `dynamic` attributes disclose the fact that the model may *learn more than we thought*, hence it would be reasonable and meaningful to explore an internal sign like CAM or Grad-CAM as guidance for solving the PLL problem.

3 PROPOSING CLASS ACTIVATION VALUE FOR PARTIAL-LABEL LEARNING

3.1 CLASS ACTIVATION VALUE—SIMPLE AND GENERAL KNOWLEDGE

In this paper, we aim to propose a CAM-like tool as guidance for f to identify the true label from candidate labels. CAM or Grad-CAM is specially designed for *convolutional neural network* (CNN)-based models, which mainly deals with image datasets with retaining spatial information. However, to the best of our knowledge, most PLL methods are implemented in datasets with various forms, including the image datasets such as MNIST (LeCun et al., 1998) and CIFAR-10 (Krizhevsky et al., 2009), and feature vectors such as Lost (Cour et al., 2011) and BirdSong (Briggs et al., 2012). The networks on these datasets could be directly adapted to elementary models such as the linear or *multilayer perceptron* (MLP) for f to deal with the inputting flattened-dimension vectors. Without spatial information or CNN-based architectures, CAM-based tools are invalid to represent the internal knowledge. To make such a concept versatile, we aim to propose another novel CAM-like tool with simple implementation that could be adopted in a wider range of backbones and problems. We note that the outputs can replace the feature map $e(\boldsymbol{x})$ since the encoder e could be directly regarded as f. Therefore, it is fundamental to formulate an internal component for a value-based framework. To this end, we propose the *class activation value* (CAV) of the j-th class as

$$v^j = |\frac{\partial(-\log(\psi^j(f(\boldsymbol{x}))))}{\partial f^j(\boldsymbol{x})}|\psi^j(f^j(\boldsymbol{x})), \tag{3}$$

where $\psi : \mathbb{R}^k \to \mathbb{R}^k$ is the activation function to model the logit $f(\boldsymbol{x})$ to approximate the $P(y|\boldsymbol{x})$. Besides, ψ is mostly implemented by the *SoftMax* function, thus Eq. (3) can be simplified as

$$v^j = |\psi^j(f^j(\boldsymbol{x})) - 1|\psi^j(f^j(\boldsymbol{x})). \tag{4}$$

The derivation process is provided in Appendix A. In Eq. (2), Grad-CAM regards the gradient information flow to the last convolution layer as the importance of each neuron for the interest to the j-th class. Inspired by this, we propose to use the derivative of the absolute information entropy of $P(y|\boldsymbol{x})$, modeled by $\psi(f(\boldsymbol{x}))$, with respect to $f(\boldsymbol{x})$ related to the same class as the weight parameters. Specifically, the self-information of $P(y|\boldsymbol{x}_i)$ represents the amount of information to the event that $\boldsymbol{x}_i$ belongs to the class y, which could served as the "logit" for calculating the weights as in Eq. (2). Compared with CAM, we directly treat $\psi(f(\boldsymbol{x}))$ as the "feature map" so that v can be obtained by the weighted operation on the outputs of the model. According to the simplified version in Eq. (4), we can calculate v by directly using the model outputs.

Algorithm 1 CAVL Algorithm

Input: Model f, epoch $T_{\max}$, iteration $Z_{\max}$, partial labeled training set $\mathbb{D} = \{(\boldsymbol{x}_i, S_i)\}_{i=1}^m$.
   for $t = 1, 2, ..., T_{\max}$ **do**
      Shuffle $\mathbb{D}$;
      for $z = 1, 2, ..., I_{\max}$ **do**
         Sample mini-batch $\mathbb{D}_z = \{(\boldsymbol{x}_j, S_j)\}_{j=1}^u$ from $\mathbb{D}$;
         if $t = 1$ **then**
            Update f by minimizing the cross entropy loss function $\hat{\mathcal{R}}_1$ in Eq. (6) with treating all the candidate labels from S_j equally;
         else
            Obtain the CAV v for each $\boldsymbol{x}_j$ by Eq. (4);
            Generate y'_j for $\boldsymbol{x}_j$ by selecting the maximum v from S_j by Eq. (7);
            Update f by minimizing the cross entropy loss function $\hat{\mathcal{R}}_{\text{cavl}}$ in Eq. (8) with treating y'_j as the sole true label for each $\boldsymbol{x}_j$;
         end if
      end for
   end for
Output: f.

Here we give a discussion about the comparison between CAM and CAV. In all, both CAV and CAM are the weighted operation to the feature maps (or outputs in the classifier). Differently from CAM, CAV is essentially a *value* so that it could be easily obtained and applied to different backbones. Besides, our CAV could also be generated with less time complexity since there is no need to process the weighted sum of the feature maps. Figure 1 shows the accuracy of recognizing the true label by using the maximum CAV from the candidate label set, and it can be seen that CAV not only possesses two attributes (i.e., `power` and `dynamic`) as CAM, but also shows better gap performance than CAM and presents better consistency with the classifier performance variation. Therefore, we believe that CAV could work effectively as the guidance for f.

3.2 Partial-Label Learning with Class Activation Value

In this section, we introduce how to effectively address PLL by using CAV in detail. Firstly, we give a formal introduction to PLL. For a k-class classification problem, let $\mathbb{X} \in \mathbb{R}^d$ be the feature (input) space and $\{\boldsymbol{x}_i\}_{i=1}^m \in \mathbb{X}$ be the input data, where m refers to the number of training examples. Let $\mathbb{Y} = \{1, 2, ..., k\}$ be the label space. Let us denote $\mathbb{C} = \{2^{\mathbb{Y}} \backslash \emptyset \backslash \mathbb{Y}\}$ as the candidate label space where $2^{\mathbb{Y}}$ is the power set of $\mathbb{Y}$, and $|\mathbb{C}| = 2^k - 2$ shows that the candidate label set is not supposed to be the empty set nor the whole label set. For each training instance $\boldsymbol{x}_i$, let $y_i \in \mathbb{Y}$ be the ground truth label and $S_i \in \mathbb{C}$ be the candidate label set. We denote $P(\boldsymbol{x}, y)$ and $P(\boldsymbol{x}, S)$ as the probability densities of fully labeled examples and partially labeled examples respectively. Based on the crucial assumption of PLL that the candidate label set of each instance must include the correct label, we have $y_i \in S_i$, i.e.,

$$P(y_i \in S_i | y = y_i, \boldsymbol{x} = \boldsymbol{x}_i) = 1, \forall y_i \in \mathbb{Y}, \forall S_i \in \mathbb{C}. \tag{5}$$

PLL aims to learn a classifier $f : \mathbb{X} \to \mathbb{R}^k$ with training examples independently and identically sampled from $P(\boldsymbol{x}, S)$ to make correct predictions for test examples. To the best of our knowledge, most methods focus on designing the loss by considering all candidate labels or iteratively extracting the true label from the theoretical aspect. Differently from them, we concentrate on how to solve PLL by efficiently utilizing the learned representation by CAV, which could be potential and effective guidance for helping f recognize the true label.

Note that the learned representation could be directly obtained by using CAV after firstly training f in one epoch. For training f in the first epoch, here we directly utilize the IM strategy, i.e., treating every candidate label equally by cross entropy loss $\mathcal{L}(f(\boldsymbol{x}), s), s \in S$. Hence the empirical risk function $\hat{\mathcal{R}}_1$ for the first epoch could be defined as

$$\hat{\mathcal{R}}_1(\mathcal{L}, f) = \frac{1}{m} \sum_{i=1}^m \sum_{j \in S_i} \mathcal{L}(f(\boldsymbol{x}_i), s_j). \tag{6}$$

After training f in one epoch, v of every candidate label could be gained for each $\boldsymbol{x}$ by Eq. (3). To keep the classifier away from the negative effect by the false positive labels from the candidate set, we use the knowledge by CAV to guide the following learning process after the first training epoch, and the potential true label for $\boldsymbol{x}_i$ is selected by

$$y_i' = \arg\max_{j \in S_i} v_i^j, \tag{7}$$

where y_i' is the selected true label from the candidate label set for $\boldsymbol{x}_i$. In this way, y_i' could be straightly treated as the ground truth so that PLL could be transferred to classical supervised learning. Finally, the risk function $\hat{\mathcal{R}}_{\text{cavl}}$ for the following epochs could be expressed as

$$\hat{\mathcal{R}}_{\text{cavl}}(\mathcal{L}, f) = \frac{1}{m} \sum_{i=1}^{m} \mathcal{L}(f(\boldsymbol{x}_i), y_i'). \tag{8}$$

As f gradually learns to approximate $P(y'|\boldsymbol{x})$, CAV would also be updated to identify the true label due to its `dynamic` attribute, which means that $P(y|y', \boldsymbol{x}) = 1$ in an ideal way. Based on such progressive label selection on S, our Class Activation Value Learning (CAVL) is supposed to be a better sign for indicating the true label. The pseudo-code of CAVL is showed in Algorithm 1.

4 EXPERIMENTS

In this section, extensive experiments on various datasets are implemented to verify the effectiveness and rightness of our proposed CAV and CAVL method.

4.1 CAVL PERFORMANCE

4.1.1 BENCHMARK DATASET COMPARISONS

Datasets and backbones. We use four popular benchmark datasets to test the performance of our CAVL, which are MNIST (LeCun et al., 1998), Fashion-MNIST (Xiao et al., 2017), Kuzushiji-MNIST (Clanuwat et al., 2018) and CIFAR-10 (Krizhevsky et al., 2009). Note that it is necessary to manually generate the candidate label sets since they are supposed to be used for single-classification problems. Recall that we introduce two different candidate label generation process (please refer to Section 2.2 for details) (Feng & An, 2019a;b; Feng et al., 2020; Lv et al., 2020; Wen et al., 2021), i.e., USS and FPS. The former one is implemented by uniformly sampling a label set from all the partial label space $\mathbb{C}$ for each instance, and the latter one sets a flipping probability q to any irrelevant label so that it could become one item in the candidate label set with probability q. In this section we set $q \in \{0.3, 0.5, 0.7\}$ to represent different ambiguity degrees. For MNIST, Kuzushiji-MNIST and Fashion-MNIST, we adopt 3-layer MLP and 5-layer LeNet as the backbones. For CIFAR-10, we choose 34-layer ResNet (He et al., 2016) and 22-layer DenseNet (Huang et al., 2017) as the base models.

Compared methods and training settings. We compare our CAVL with three state-of-the-art approaches including Leveraged Weighted (LW) Loss (Wen et al., 2021), RC and CC (Feng et al., 2020). For all methods we search the initial learning rate from $\{0.0001, 0.001, 0.01, 0.05, 0.1, 0.5\}$, and weight decay from $\{10^{-6}, 10^{-5}, ..., 10^{-1}\}$. We take a mini-batch size of $\{64, 256\}$ images and train all the methods using Adam (Kingma & Ba, 2015) optimizer for 250 epochs. Hyper-parameters are selected to exploit the best performance on the validation set containing 10% of the training examples. The overall methods implemented by Pytorch are trained on 1 RTX3090 GPU with 24 GB memory. To guarantee the fairness of comparisons, we repeatedly conduct all experiments 5 times and record the average accuracy with the standard deviation following the conventions in Feng et al. (2020); Lv et al. (2020); Wen et al. (2021).

Experiment results. As shown in Table 1 and 2, our CAVL shows its superiority on four benchmark datasets with various backbones. Additionally, our CAVL outperforms nearly all state-of-the-art methods using the candidate labels generated by both USS and FPS, which shows that our CAVL does not rely on any data generation assumption. Specifically, it is worth mentioning that CAVL is able to show competitive performance with RC, which is theoretically proved to be possess optimal performance in data distribution generated by USS. Therefore, the results reasonably verify the generalization and effectiveness of our CAV and CAVL.

Table 1: Test performance of CAVL and other methods on benchmark datasets using data generation by USS. The best results among all methods with the same backbone are marked in **bold**.

Dataset (Backbones)	Method	Accuracy
MNIST (MLP/LeNet)	CC	$97.77 \pm 0.12\%$ / $98.77 \pm 0.06\%$
	RC	$98.05 \pm 0.15\%$ / $99.03 \pm 0.04\%$
	LW	$97.99 \pm 0.06\%$ / $98.74 \pm 0.05\%$
	CAVL	$\mathbf{98.17 \pm 0.08}\%$ / $\mathbf{99.11 \pm 0.04}\%$
Kuzushiji-MNIST (MLP/LeNet)	CC	$88.87 \pm 0.32\%$ / $93.83 \pm 0.20\%$
	RC	$\mathbf{89.36 \pm 0.30}\%$ / $94.01 \pm 0.15\%$
	LW	$87.98 \pm 0.39\%$ / $91.52 \pm 0.65\%$
	CAVL	$88.73 \pm 0.18\%$ / $\mathbf{94.29 \pm 0.20}\%$
Fashion-MNIST (MLP/LeNet)	CC	$87.90 \pm 0.27\%$ / $88.96 \pm 0.14\%$
	RC	$88.40 \pm 0.13\%$ / $89.51 \pm 0.11\%$
	LW	$88.16 \pm 0.12\%$ / $88.28 \pm 0.33\%$
	CAVL	$\mathbf{88.73 \pm 0.21}\%$ / $\mathbf{89.79 \pm 0.10}\%$
CIFAR-10 (ResNet/DenseNet)	CC	$75.74 \pm 0.19\%$ / $76.78 \pm 0.33\%$
	RC	$\mathbf{77.98 \pm 0.46}\%$ / $78.56 \pm 0.37\%$
	LW	$76.82 \pm 0.21\%$ / $78.08 \pm 0.66\%$
	CAVL	$77.49 \pm 0.29\%$ / $\mathbf{79.20 \pm 0.30}\%$

Table 2: Test performance of CAVL and other methods on benchmark datasets using data generation by FPS. The best results among all methods with the same backbone are marked in **bold**.

Dataset (Backbones)	Method	q=0.3	q=0.5	q=0.7
MNIST (LeNet)	CC	$98.87 \pm 0.15\%$	$98.49 \pm 0.07\%$	$98.17 \pm 0.12\%$
	RC	$98.88 \pm 0.07\%$	$98.53 \pm 0.11\%$	$98.12 \pm 0.05\%$
	LW	$98.53 \pm 0.12\%$	$98.68 \pm 0.06\%$	$97.35 \pm 0.13\%$
	CAVL	$\mathbf{98.98 \pm 0.15\%}$	$\mathbf{98.75 \pm 0.06\%}$	$\mathbf{98.21 \pm 0.10\%}$
Kuzushiji-MNIST (LeNet)	CC	$93.11 \pm 0.08\%$	$90.87 \pm 0.06\%$	$89.98 \pm 0.14\%$
	RC	$93.21 \pm 0.17\%$	$91.19 \pm 0.22\%$	$90.15. \pm 0.04\%$
	LW	$92.65 \pm 0.18\%$	$91.28 \pm 0.16\%$	$\mathbf{90.55 \pm 0.17\%}$
	CAVL	$\mathbf{93.82 \pm 0.21\%}$	$\mathbf{91.55 \pm 0.13\%}$	$86.34 \pm 0.25\%$
Fashion-MNIST (LeNet)	CC	$89.41 \pm 0.17\%$	$88.72 \pm 0.06\%$	$85.87 \pm 0.25\%$
	RC	$89.53 \pm 0.07\%$	$88.84 \pm 0.14\%$	$85.41 \pm 0.18\%$
	LW	$89.19 \pm 0.08\%$	$87.19 \pm 0.23\%$	$85.92 \pm 0.13\%$
	CAVL	$\mathbf{89.86 \pm 0.08\%}$	$\mathbf{88.94 \pm 0.12\%}$	$\mathbf{86.15 \pm 0.12\%}$
CIFAR-10 (DenseNet)	CC	$77.32 \pm 0.14\%$	$76.42 \pm 0.13\%$	$66.17 \pm 0.25\%$
	RC	$78.14 \pm 0.12\%$	$77.42 \pm 0.16\%$	$70.21 \pm 0.15\%$
	LW	$80.95 \pm 0.17\%$	$78.72 \pm 0.17\%$	$\mathbf{71.26 \pm 0.16\%}$
	CAVL	$\mathbf{81.58 \pm 0.22\%}$	$\mathbf{79.48 \pm 0.15\%}$	$65.26 \pm 0.12\%$

4.1.2 REAL-WORLD DATASET COMPARISONS

Datasets and backbones. We select five real-world datasets including Lost (Cour et al., 2011), MSRCv2 (Liu & Dietterich, 2012), BirdSong (Briggs et al., 2012), Soccer Player (Zeng et al., 2013) and Yahoo!News (Guillaumin et al., 2010). Note that these real-world datasets have their candidate labels. As a common practice in (Feng et al., 2020; Lv et al., 2020; Wen et al., 2021), we select 1-layer linear model and 3-layer MLP as the backbones to validate the performance of our CAVL in these five datasets.

Compared methods and training settings. Apart from the three methods mentioned in Section 4.1.1, we add SURE (Feng & An, 2019b), CLPL (Cour et al., 2011), IPAL (Zhang & Yu, 2015), PLSVM (Elkan & Noto, 2008), PLECOC (Zhang et al., 2017) and PLKNN (Hüllermeier & Beringer, 2006) as extra methods for comparison, where the parameters are searched to maximize the accuracy on a validation set (10% of the training set). We repeatedly run all experiments 10 times, and report the average accuracy with the standard deviation for each method. Other settings are similar to Section 4.1.1. The comparison results using MLP is recorded in Appendix B.2.

Table 3: Test performance of CAVL and other methods uisng linear model on real-world datasets. The best and second best results among all methods are marked in **bold** and underline.

Method	Real-world datasets				
	Lost	MSRCv2	Birdsong	SoccerPlayer	YahooNews
IPAL	$71.16 \pm 2.56\%$	$\mathbf{50.64 \pm 3.85\%}$	$70.32 \pm 4.85\%$	$55.42 \pm 0.92\%$	$66.43 \pm 1.32\%$
CLPL	$75.01 \pm 4.39\%$	$36.72 \pm 4.61\%$	$64.35 \pm 1.28\%$	$37.01 \pm 1.02\%$	$45.21 \pm 0.82\%$
PLSVM	$48.91 \pm 3.33\%$	$35.95 \pm 3.96\%$	$48.99 \pm 1.98\%$	$45.90 \pm 0.98\%$	$57.02 \pm 1.02\%$
PLKNN	$37.73 \pm 2.85\%$	$41.28 \pm 2.25\%$	$64.32 \pm 1.05\%$	$48.21 \pm 1.21\%$	$40.67 \pm 1.58\%$
PLECOC	$50.95 \pm 7.81\%$	$43.25 \pm 3.61\%$	$70.51 \pm 4.31\%$	$55.29 \pm 1.95\%$	$61.23 \pm 1.52\%$
SURE	$75.56 \pm 5.62\%$	$46.72 \pm 4.21\%$	$55.42 \pm 1.52\%$	$48.61 \pm 0.84\%$	$55.17 \pm 1.05\%$
LW	$79.74 \pm 3.81\%$	$45.65 \pm 3.12\%$	$72.01 \pm 2.31\%$	$\underline{57.12 \pm 3.25\%}$	$67.94 \pm 1.64\%$
RC	$\underline{80.45 \pm 3.85\%}$	$46.85 \pm 2.52\%$	$\underline{72.15 \pm 2.14\%}$	$57.05 \pm 2.15\%$	$\underline{68.12 \pm 0.67\%}$
CC	$73.78 \pm 4.34\%$	$45.13 \pm 2.67\%$	$71.86 \pm 1.34\%$	$56.54 \pm 0.74\%$	$67.00 \pm 0.35\%$
CAVL	$\mathbf{81.78 \pm 3.28\%}$	$\underline{48.29 \pm 3.15\%}$	$\mathbf{72.26 \pm 0.66\%}$	$\mathbf{57.68 \pm 1.89\%}$	$\mathbf{68.41 \pm 0.61\%}$

Figure 2: Study of CAV attributes on various backbones and datasets. Note that here CAM could only been obtained in deep CNN architectures, namely ResNet and DenseNet.

Experiment results. In Table 3, our proposed CAVL shows the best performance in nearly all five real datasets. Besides, CAM is unable to be extracted with the word embedding input such as BirdSong, lacking spatial information. Therefore, the achievement of CAVL on these real datasets shows the generalization and superiority of our CAVL to shallow model, where CAV could serve as the CAM to lead the classifier to learn the true label.

4.2 CAV ATTRIBUTES

Recall that there are two attributes for CAV, i.e., `power` and `dynamic`, which are the key elements for the success of our CAVL (see in Section 2.2). In this part, we conduct several experiments to present how these attributes can guide the learning process to the true labels. We implement CAVL with four backbones including linear, MLP, ResNet and DenseNet on four benchmark datasets, whose candidate label sets are generated by using USS. The training settings are similar to the ones in Section 4.1.1. Figure 2 illustrates the averaging performance of CAV and CAM (for deep networks) during the 5-time training process.

Power. As shown in Figure 2, it is clear that CAV has more tendency to recognize the ground truth of candidate label sets than the basic output. With the help of CAV, the classifier learns to approximate the better data distribution so the accuracy keeps increasing for all benchmarks with various backbones. Particularly, a more powerful backbone shows more capability of obtaining the knowledge by CAV. For instance, CAVL with MLP forces the basic outputs to match the CAV to a higher degree than the linear model and even achieves extremely similar performance in three MNIST-

based datasets. Beisdes, the CAV shows similar `power` attribute with CAM (see the CIFAR-10 results in Figure 2) in deep models, further validating our effectiveness and generalization of CAV.

Dynamic. The change of performance gap in Figure 2 between CAV and basic outputs also verifies the `dynamic` attributes of our CAV. For all methods with different backbones, the accuracy trend recognized by CAV is consistent with the basic outputs. For deep models including ResNet and DenseNet, our CAV also achieves comparable `dynamic` capacity with the CAM, which is critical for successful guidance towards the true label for the classifier.

5 RELATED WORK

In this section, we give a brief introduction to the two mainstream strategies for *partial-label learning* (PLL), i.e., the *averaged-based strategy* (ABS) and the *identification-based strategy* (IBS).

ABS treats all candidate labels in an equal manner and then averages the model outputs of all candidate labels for prediction. Some non-parametric methods (Hüllermeier & Beringer, 2006; Gong et al., 2017) concentrated on predicting the label by leveraging the outputs of its neighbors. Furthermore, some methods (Cour et al., 2009; Zhang et al., 2016; Yao et al., 2020) aimed to subtly leverage the labels outside the candidate set so as to discriminate the potential true label. Yao et al. (2020) designed an entropy-based regularizer to minimize the entropy of each label to maximize the margin between the potential true label and the unlikely labels. A recent study (Feng et al., 2020; Lv et al., 2020; Wen et al., 2021; Lv et al., 2021) focused on the data generation process and proposed a classifier-consistent method based on a transition matrix. Although ABS is unable to alleviate the negative effect of the false positive labels in the candidate label set, the loss functions have been proved to be promising in the sense of robustness under some PLL cases (Lv et al., 2021).

IBS aims to constantly identify the most possible true label from the candidate label set to eliminate the label ambiguity. Early works treated the potential truth label as a latent variable and optimized the objective function by the maximum likelihood criterion (Jin & Ghahramani, 2002; Liu & Dietterich, 2014) or the maximum margin criterion (Nguyen & Caruana, 2008; Yu & Zhang, 2016). Later, taking advantage of topological information of feature space to generate the score of each candidate label (Zhang & Yu, 2015; Zhang et al., 2016; Feng & An, 2018; Wang et al., 2019) attracted much attention from researchers. These methods commonly aimed to iteratively update the confidence of each candidate label based on the widely used assumption that similar instance are supposed to possess the same label. Xu et al. (2019b) proposed to model the generalized label distribution by leveraging the topological information of the feature space. Feng & An (2019a) focused on balancing the maximum infinity norm of the outputs and the minimum loss to distinguish the true label from the candidate label set. It is worth noting that IBS is commonly susceptible to the false positive labels that co-occur with the true label in the candidate label set.

6 CONCLUSION

In this paper, we exploited the learned intrinsic representation of the model for *partial-label learning* (PLL). We made two key contributions. Firstly, we found that *class activation map* (CAM), a simple technique for discriminating the learning patterns of each class in an image, is surprisingly better at differentiating the true label from candidate labels than the model itself. Unfortunately, we are yet unable to directly use CAM for PLL, as CAM is subject to image inputs with convolutional neural networks. Thus, our second contribution is to propose *class activation value* (CAV), which not only owns similar properties of CAM but also is versatile in various types of inputs and models. Based on CAV, we proposed a simple yet effective PLL method that selects the true label by the class with the maximum CAV for model training. Comprehensive experimental results on various datasets demonstrated that our CAVL achieved state-of-the-art performance.

REFERENCES

Forrest Briggs, Xiaoli Z Fern, and Raviv Raich. Rank-loss support instance machines for miml instance annotation. In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pp. 534–542, 2012.

Aditya Chattopadhay, Anirban Sarkar, Prantik Howlader, and Vineeth N Balasubramanian. Grad-cam++: Generalized gradient-based visual explanations for deep convolutional networks. In *2018 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 839–847. IEEE, 2018.

Tarin Clanuwat, Mikel Bober-Irizar, Asanobu Kitamoto, Alex Lamb, Kazuaki Yamamoto, and David Ha. Deep learning for classical japanese literature. *arXiv preprint arXiv:1812.01718*, 2018.

Timothee Cour, Benjamin Sapp, Chris Jordan, and Ben Taskar. Learning from ambiguously labeled images. In *2009 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 919–926. IEEE, 2009.

Timothee Cour, Ben Sapp, and Ben Taskar. Learning from partial labels. *The Journal of Machine Learning Research (JMLR)*, 12:1501–1536, 2011.

Charles Elkan and Keith Noto. Learning classifiers from only positive and unlabeled data. In *Proceedings of the 14th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pp. 213–220, 2008.

Lei Feng and Bo An. Leveraging latent label distributions for partial label learning. In *International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 2107–2113, 2018.

Lei Feng and Bo An. Partial label learning by semantic difference maximization. In *International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 2294–2300, 2019a.

Lei Feng and Bo An. Partial label learning with self-guided retraining. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, pp. 3542–3549, 2019b.

Lei Feng, Jiaqi Lv, Bo Han, Miao Xu, Gang Niu, Xin Geng, Bo An, and Masashi Sugiyama. Provably consistent partial-label learning. In *Advances in Neural Information Processing Systems (NIPS)*, 2020.

Chen Gong, Tongliang Liu, Yuanyan Tang, Jian Yang, Jie Yang, and Dacheng Tao. A regularization approach for instance-based superset label learning. *IEEE Transactions on Cybernetics*, 48(3): 967–978, 2017.

Matthieu Guillaumin, Jakob Verbeek, and Cordelia Schmid. Multiple instance metric learning from automatically labeled bags of faces. In *European Conference on Computer Vision (ECCV)*, pp. 634–647. Springer, 2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4700–4708, 2017.

Eyke Hüllermeier and Jürgen Beringer. Learning from ambiguously labeled examples. *Intelligent Data Analysis*, 10(5):419–439, 2006.

Rong Jin and Zoubin Ghahramani. Learning with multiple labels. In *Advances in Neural Information Processing Systems (NIPS)*, volume 2, pp. 897–904. Citeseer, 2002.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations (ICLR)*, 2015.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Liping Liu and Thomas Dietterich. Learnability of the superset label learning problem. In *International Conference on Machine Learning (ICML)*, pp. 1629–1637. PMLR, 2014.

Liping Liu and Thomas G Dietterich. A conditional multinomial mixture model for superset label learning. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 548–556. Citeseer, 2012.

Tongliang Liu and Dacheng Tao. Classification with noisy labels by importance reweighting. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 38(3):447–461, 2015.

Michal Lukasik, Srinadh Bhojanapalli, Aditya Menon, and Sanjiv Kumar. Does label smoothing mitigate label noise? In *International Conference on Machine Learning (ICML)*, pp. 6448–6458. PMLR, 2020.

Jie Luo and Francesco Orabona. Learning from candidate labeling sets. In *Advances in Neural Information Processing Systems (NIPS)*, 2010.

Yucen Luo, Jun Zhu, Mengxi Li, Yong Ren, and Bo Zhang. Smooth neighbors on teacher graphs for semi-supervised learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8896–8905, 2018.

Jiaqi Lv, Miao Xu, Lei Feng, Gang Niu, Xin Geng, and Masashi Sugiyama. Progressive identification of true labels for partial-label learning. In *International Conference on Machine Learning (ICML)*, pp. 6500–6510. PMLR, 2020.

Jiaqi Lv, Lei Feng, Miao Xu, Bo An, Gang Niu, Xin Geng, and Masashi Sugiyama. On the robustness of average losses for partial-label learning. *arXiv preprint arXiv:2106.06152*, 2021.

Takeru Miyato, Shin-ichi Maeda, Masanori Koyama, and Shin Ishii. Virtual adversarial training: a regularization method for supervised and semi-supervised learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 41(8):1979–1993, 2018.

Nagarajan Natarajan, Inderjit S Dhillon, Pradeep K Ravikumar, and Ambuj Tewari. Learning with noisy labels. *Advances in Neural Information Processing Systems (NIPS)*, 26:1196–1204, 2013.

Nam Nguyen and Rich Caruana. Classification with partial labels. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining (KDD)*, pp. 551–559, 2008.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE International Conference on Computer Vision (CVPR)*, pp. 618–626, 2017.

Deng-Bao Wang, Li Li, and Min-Ling Zhang. Adaptive graph guided disambiguation for partial label learning. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD)*, pp. 83–91, 2019.

Yunchao Wei, Xiaodan Liang, Yunpeng Chen, Xiaohui Shen, Ming-Ming Cheng, Jiashi Feng, Yao Zhao, and Shuicheng Yan. Stc: A simple to complex framework for weakly-supervised semantic segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 39(11): 2314–2320, 2016.

Hongwei Wen, Jingyi Cui, Hanyuan Hang, Jiabin Liu, Yisen Wang, and Zhouchen Lin. Leveraged weighted loss for partial label learning. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning (ICML)*, volume 139, pp. 11091–11100. PMLR, 2021.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Kaidi Xu, Sijia Liu, Pu Zhao, Pin-Yu Chen, Huan Zhang, Quanfu Fan, Deniz Erdogmus, Yanzhi Wang, and Xue Lin. Structured adversarial attack: Towards general implementation and better interpretability. In *International Conference on Learning Representations (ICLR)*, 2019a.

Ning Xu, Jiaqi Lv, and Xin Geng. Partial label learning via label enhancement. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 33, pp. 5557–5564, 2019b.

Yan Yan and Yuhong Guo. Partial label learning with batch label correction. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pp. 6575–6582, 2020.

Yan Yan and Yuhong Guo. Multi-level generative models for partial label learning with non-random label noise. In *Proceedings of the International Joint Conference on Artificial Intelligence (IJ-CAI)*, pp. 3264–3270, 2021.

Yao Yao, Jiehui Deng, Xiuhua Chen, Chen Gong, Jianxin Wu, and Jian Yang. Deep discriminative cnn with temporal ensembling for ambiguously-labeled image classification. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pp. 12669–12676, 2020.

Fei Yu and Min-Ling Zhang. Maximum margin partial label learning. In *Asian Conference on Machine Learning (ACML)*, pp. 96–111. PMLR, 2016.

Zinan Zeng, Shijie Xiao, Kui Jia, Tsung-Han Chan, Shenghua Gao, Dong Xu, and Yi Ma. Learning by associating ambiguously labeled images. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 708–715, 2013.

Min-Ling Zhang and Fei Yu. Solving the partial label learning problem: An instance-based approach. In *Twenty-fourth International Joint Conference on Artificial Intelligence (IJCAI)*, 2015.

Min-Ling Zhang, Bin-Bin Zhou, and Xu-Ying Liu. Partial label learning via feature-aware disambiguation. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pp. 1335–1344, 2016.

Min-Ling Zhang, Fei Yu, and Cai-Zhi Tang. Disambiguation-free partial label learning. *IEEE Transactions on Knowledge and Data Engineering (TKDE)*, 29(10):2155–2167, 2017.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2921–2929, 2016.

Zhi-Hua Zhou. A brief introduction to weakly supervised learning. *National Science Review*, 5(1): 44–53, 08 2017.

Zhi-Hua Zhou, Min-Ling Zhang, Sheng-Jun Huang, and Yu-Feng Li. Multi-instance multi-label learning. *Artificial Intelligence*, 176(1):2291–2320, 2012.

Xiaojin Zhu and Andrew B Goldberg. Introduction to semi-supervised learning. *Synthesis lectures on Artificial Intelligence and Machine Learning*, 3(1):1–130, 2009.

A DERIVATION PROCESS OF EQUATION. (4)

The *SoftMax* function is $\psi^j(x) = \exp(x_j)/\sum_{j=1}^{k}\exp(x_j)$, where $x \in \mathbb{R}^d$ refers to an input vector. Then we can obtain the derivation of $-log(\psi^j(x))$ with respect to the x_j by

$$
\begin{aligned}
\frac{\partial(-\log(\psi^j(x)))}{\partial x_j} &= \frac{\partial(-\log(\psi^j(x)))}{\partial \psi^j(x)}\frac{\partial \psi^j(x)}{\partial x_j} \\
&= -\frac{1}{\psi^j(x)}\frac{\partial \psi^j(x)}{\partial x_j} \\
&= -\frac{1}{\psi^j(x)}\frac{\sum_{i=1}^{d} e^{x_j}e^{x_i} - (e^{x_i})^2}{\sum_{i=1}^{d}(e^{x_i})^2} \\
&= -\frac{1}{\psi^j(x)}(\frac{e^{x_j}}{\sum_{i=1}^{d}(e^{x_i})^2})(1 - \frac{e^{x_j}}{\sum_{i=1}^{d}(e^{x_i})^2}) \\
&= -\frac{1}{\psi^j(x)}\psi^j(x)(1 - \psi^j(x)) \\
&= \psi^j(x) - 1.
\end{aligned}
\tag{9}
$$

According to Eq. (9), we could easily obtain the v_j in Eq. (4) from Equation (3).

B DETAILED SUPPLEMENTARY FOR EXPERIMENTS

B.1 BENCHMARK DATASETS

In Section 4.1.1, we use four widely-used benchmark datasets, i.e. MNIST (LeCun et al., 1998), Fashion-MNIST (Xiao et al., 2017), Kuzushiji-MNIST (Clanuwat et al., 2018) and CIFAR-10 (Krizhevsky et al., 2009). Table 4 lists the characteristics of these datasets. We respectively describe these datasets as follows.

- MNIST: It is a 10-class dataset of handwritten digits. Each data is a 28 × 28 grayscale image.
- Fashion-MNIST: It is also a 10-class dataset. Each instance is a fashion item from one of the 10 classes, which are T-shirt/top, trouser, pullover, dress, sandal, coat, shirt, sneaker, bag, and ankle boot. Moreover, each image is a 28 × 28 grayscale image.
- Kuzushiji-MNIST: Each instance is a 28 × 28 grayscale image associated with one label of 10-class cursive Japanese ("Kuzushiji") characters.
- CIFAR-10: Each instance is a 32 × 32 × 3 colored image in RGB format. It is a ten-class dataset of objects including airplane, bird, automobile, cat, deer, frog, dog, horse, ship, and truck.

B.2 REAL DATASETS

In Section 4.1.2, We select five real-world datasets including Lost (Cour et al., 2011), MSRCv2 (Liu & Dietterich, 2012), BirdSong (Briggs et al., 2012), Soccer Player (Zeng et al., 2013) and Yahoo!News (Guillaumin et al., 2010). Here we make a comprehensive descriptions about them shown as follows.

- Lost, Soccer Player and Yahoo! News: They crop faces in images or video frames as instances, and the names appearing on the corresponding captions or subtitles are considered as candidate labels.
- MSRCv2: Each image segment is treated as a sample, and objects appearing in the same image are regarded as candidate labels.
- BirdSong: The singing syllables of birds are regarded as instances and bird species who are jointly singing during any ten seconds are represented as candidate labels

Table 4: Characteristics of benchmark datasets

Datasets	#Train	#Test	#Features	#Classes
MNIST	60,000	10,000	784	10
Fashion-MNIST	60,000	10,000	784	10
Kuzushiji-MNIST	60,000	10,000	784	10
CIFAR-10	50,000	10,000	3072	10

Table 5: Characteristics of real-world datasets

Datasets	Application Domain	#Examples	#Features	#Classes	Avg #CLs
Lost	Automatic face naming	1,122	108	16	2.23
MSRCv2	Object classification	1,758	48	23	3.16
BirdSong	Bird song classification	4,998	38	13	2.18
Soccer Player	Automatic face naming	17,472	279	171	2.09
Yahoo! News	Automatic face naming	22,991	163	219	1.91

Table 6: Test performance of the CAVL and other methods uisng MLP on real-world datasets. The best and second best results among all methods are marked in **bold** and underline.

Method	Real-world datasets				
	Lost	MSRCv2	Birdsong	SoccerPlayer	YahooNews
LW	$67.53 \pm 3.21\%$	$50.54 \pm 3.23\%$	$\mathbf{71.74 \pm 1.35\%}$	$53.29 \pm 1.95\%$	$65.94 \pm 0.92\%$
RC	$\mathbf{75.89 \pm 5.10\%}$	$\underline{51.13 \pm 2.67\%}$	$70.14 \pm 1.54\%$	$53.98 \pm 0.85\%$	$\underline{67.56 \pm 2.53\%}$
CC	$70.10 \pm 5.20\%$	$50.57 \pm 3.47\%$	$\underline{70.51 \pm 1.41\%}$	$\mathbf{54.87 \pm 0.25\%}$	$\mathbf{67.75 \pm 1.12\%}$
CAVL	$\underline{70.90 \pm 3.78\%}$	$\mathbf{52.15 \pm 3.51\%}$	$69.26 \pm 2.48\%$	$\underline{54.45 \pm 0.65\%}$	$64.15 \pm 0.38\%$

Table 5 shows the average number of candidate labels (Avg. # CLs) per instance. Table 6 presents the performance comparison between other methods and our CAVL method based on MLP model, the results of which also validate the effectiveness our CAVL.

B.3 GENERATION OF CANDIDATE LABELS

In Section 4.1.1 we introduce two different generation ways for the candidate label sets, i.e, USS, Uniformly sampling a label set from all the partial label space $\mathbb{C}$ for each instance. FPS, Setting a flipping probability q to any irrelevant label which could possibly become one item in the candidate label set with probability q.

For USS, each partially labeled example $(\boldsymbol{x}, S)$ is independently drawn from a probability distribution with the following density:

$$\widetilde{P}(\boldsymbol{x}, S) = \sum_{i=1}^{k} P(S|y=i)P(\boldsymbol{x}, y=i), P(S|y=i) = \begin{cases} \frac{1}{2^{k-1}-1} & i \in S, \\ 0 & i \notin S. \end{cases} \quad (10)$$

The generation process assumes that the candidate label set S is independent of the instance $\boldsymbol{x}$. There are totally $2^k - 1$ possible candidate label sets that contain the specific true label y. Therefore, Eq. (10) illustrates the candidate label set for each instance is uniformly sampled.

For FPS, we set a flipping probability q to any irrelevant label that possibly entries the candidate label set. Here we introduce the class transition matrix (denoted by T) for partially labeled data, where T_{ij} refers to the probability of the label j being a candidate label given the true label i for each instance. Note that $T_{ii} = 1$ always holds since the true label always belongs to the candidate

label. $T_{ij} = q, i \neq j$ holds for other elements. The matrix representation of T is expressed as:

$$
\begin{bmatrix}
1 & q & q & q & q & q & q & q & q & q \\
q & 1 & q & q & q & q & q & q & q & q \\
q & q & 1 & q & q & q & q & q & q & q \\
q & q & q & 1 & q & q & q & q & q & q \\
q & q & q & q & 1 & q & q & q & q & q \\
q & q & q & q & q & 1 & q & q & q & q \\
q & q & q & q & q & q & 1 & q & q & q \\
q & q & q & q & q & q & q & 1 & q & q \\
q & q & q & q & q & q & q & q & 1 & q \\
q & q & q & q & q & q & q & q & q & 1
\end{bmatrix}
$$

B.4 COMPARED METHODS

The compared PLL methods are listed as follows.

- SURE (Feng & An, 2019b): It iteratively enlarges the confidence of the candidate label with the highest probability to be the correct label.
- CLPL (Cour et al., 2011): It uses a convex formulation by using the one-versus-all strategy in the multi class loss function.
- IPAL (Zhang & Yu, 2015): It is a non-parametric method that applies the label propagation strategy to iteratively update the confidence of each candidate label.
- PLSVM (Elkan & Noto, 2008): It is a maximum margin-based method that differentiates candidate labels from non-candidate labels by maximizing the margin between them.
- PLECOC (Zhang et al., 2017): It adapts the Error-Correcting Output Codes method to deal with partially labeled examples in a disambiguation-free manner.
- PLKNN (Hüllermeier & Beringer, 2006): It adapts the widely-used *k-nearest neighbors* method to make predictions for partially labeled examples.
- CC & RC (Feng et al., 2020): The former method is a novel risk-consistent partial label learning method and the latter one is classifier-consistent based on the generation model.
- LW (Wen et al., 2021): The method proposes a family of loss function for the first time, where introduces the leverage parameter β to consider the trade-off between losses on partial labels and non-partial labels.

For all the above methods, their parameters are specified or searched according to the suggested parameter settings by respective papers to maximize the accuracy performance on a validation set, which is made by the 10% of the training set.

B.5 DETAILS OF THE BACKBONES

In Section 4 we select five network architectures as the backbones for modelling our classifier, which are linear, 3-layer MLP, 5-layer LeNet, 34-layer ResNet (He et al., 2016) and 22-layer DenseNet (Huang et al., 2017). The linear model is a linear-in-input model:$d - k$. MLP refers to a 3-layer fully connected networks with ReLU as the activation function, and the architecture is $d - 500 - k$. LeNet is comprised of 2 Convolution Layer and 3 fully connected layer. 34-layer ResNet and 22-layer DenseNet strictly follow the implementation by He et al. (2016) and Huang et al. (2017).