OPTIMAL TRANSPORT FOR CAUSAL DISCOVERY

ABSTRACT

Approaches based on Functional Causal Models (FCMs) have been proposed to determine causal direction between two variables, by properly restricting model classes; however, their performance is sensitive to the model assumptions, which makes it difficult for practitioners to use. In this paper, we provide a novel dynamical-system view of FCMs and propose a new framework for identifying causal direction in the bivariate case. We first show the connection between FCMs and optimal transport, and then study optimal transport under the constraints of FCMs. Furthermore, by exploiting the dynamical interpretation of optimal transport under the FCM constraints, we determine the corresponding underlying dynamical process of the static cause-effect pair data under the least action principle. It provides a new dimension for describing static causal discovery tasks, while enjoying more freedom for modeling the quantitative causal influences. In particular, we show that Additive Noise Models (ANMs) correspond to volume-preserving pressureless flows. Consequently, based on their velocity field divergence, we introduce a criterion to determine causal direction. With this criterion, we propose a novel optimal transport-based algorithm for ANMs which is robust to the choice of models and extend it to post-noninear models. Our method demonstrated state-of-the-art results on both synthetic and causal discovery benchmark datasets.

1 INTRODUCTION

Determining causal direction between two variables is a fundamental and challenging causal discovery task (Janzing et al., 2012). Conventional constraint-based and score-based causal discovery methods identify causal structures only up to Markov equivalent classes (Spirtes et al., 2001), in which some causal directions are undetermined. To address this challenge, properly constrained functional causal models (FCMs) have been proposed. FCMs represent the effect as a function of its cause and independent noise, and can help identify the causal direction between two variables by imposing substantial structural constraints on model classes, such as additive noise models (ANMs) (Shimizu et al., 2006; Hoyer et al., 2008) and post-nonlinear models (PNLs) (Zhang and Hyvärinen, 2009b). While some of the models, such as PNLs, are highly flexible, the constraints are still restrictive and difficult to interpret and relax. Inevitably, the performance of these methods is sensitive to model assumptions and optimization algorithms, especially in real-world applications.

To handle the mentioned issues, we consider FCMs from a dynamical-system view. By augmenting a time dimension for the static causal discovery task, we interpret FCMs with dynamical causal processes under the least action principle (Arnol'd, 2013). The new interpretation connects FCMs with a large class of models in dynamical systems. It then provides more freedom to model causal influences, possibilities to derive new causal discovery criteria, and a potential direction to generalize causal models with identifiable causal direction.

In particular, we exploit the above idea by leveraging the intrinsic connection between FCMs and optimal transport. Optimal transport has been receiving increasing interest in machine learning, especially in generative modeling (Arjovsky et al., 2017; Kolouri et al., 2018; Genevay et al., 2018). Monge (1781) originally introduced the optimal transport problem as *a mass transfer problem*, of which the modern form was initiated by Kantorovich (1948). Thereafter, Benamou and Brenier (2000) introduced its dynamical formulation by augmenting a time dimension for the original problem. We find that in the context of the Jacobian problem (Benamou and Brenier, 2000), FCMs can be connected with optimal transport. Furthermore, with the dynamical interpretation of optimal transport, one can naturally understand FCMs from a dynamical-system view, which makes it possible

to derive new criteria to identify causal direction. Moreover, it also enables us to develop practical algorithms with optimal transport for static causal discovery tasks in the bivariate case without learning a regression model. Accordingly, our main contributions are:

1. *Dynamical interpretation of FCMs in the bivariate case.* We provide dynamical interpretations of optimal transport under the constraints of FCMs. Furthermore, we introduce a time variable, determine the underlying dynamical process under the least action principle (Arnol'd, 2013) for the static bivariate causal discovery task, and characterize properties of the corresponding dynamical systems (Sec. 3.1 and Sec. 3.2).

2. *A criterion of determining causal direction between two variables for ANMs.* We study the corresponding dynamical systems of FCMs, and prove that ANMs correspond to volume-preserving pressureless flows. Moreover, based on the divergence of their velocity fields, we propose a criterion to determine causal direction, and show that under the identifiability conditions of ANMs, it is a valid criterion for ANMs, which can be extended to PNLs directly (Sec. 3.2).

3. *An optimal transport based approach (DIVOT) for distinguishing cause from effect between two variables.* DIVOT inherits the advantages of one-dimensional optimal transport. It can be computed efficiently, and does not require independence tests, learning a regression model, or deriving likelihood functions for complicated distributions. Experimental results show that our method is robust to the choice of models, and has a promising performance compared with the state-of-the-art methods on both synthetic and real cause-effect pair datasets (Sec. 4 and Sec. 6).

2 PRELIMINARIES

2.1 OPTIMAL TRANSPORT

In this work we mainly use the L^2 Wasserstein distance and we introduce its framework following the notations and definitions of (Benamou and Brenier, 2000) in this section.

The underdetermined Jacobian problem. Suppose that two probability density functions, $p_0(\mathbf{x})$ (the source density) and $p_T(\mathbf{x})$ (the target density), where $\mathbf{x} \in \mathbb{R}^d$, are non-negative and bounded with total mass one. Moreover, the transfer of samples from $p_0(\mathbf{x})$ to $p_T(\mathbf{x})$ is a smooth one-to-one map $M : \mathbb{R}^d \to \mathbb{R}^d$. Given p_0 and p_T, *the Jacobian problem* aims at finding M that satisfies *the Jacobian equation*:

$$p_0(\mathbf{x}_0) = p_T(M(\mathbf{x}_0))|\det(\nabla M(\mathbf{x}_0))|, \quad \mathbf{x}_T = M(\mathbf{x}_0), \tag{1}$$

where $\det(\cdot)$ denotes determinant. This is an underdetermined problem as many maps can be the solutions. Thus, a natural way is to choose the optimal one in the sense of lowest cost depending on applications. A common cost function is the L^p Wasserstein distance (Kantorovich, 1948).

L^p **Wasserstein distance and its one-dimensional closed-form solution.** The L^p Wasserstein distance between p_0 and p_T, denoted by $W_p(p_0, p_T)$, is defined by $W_p(p_0, p_T)^p = \inf_M \int |M(\mathbf{x}_0) - \mathbf{x}_0|^p p_0(\mathbf{x}_0) d\mathbf{x}_0$, where $p \geq 1$. We say that the optimal transport M^* achieving the infimum solves *the optimal transport (or L^p Monge-Kantorovich) problem*. In this work, we mainly use the square of the L^2 Wasserstein distance, denoted by W_2^2. Moreover, following the approach of Kantorovich (1948), the one-dimensional (1D) L^p Wasserstein distance has a closed-form solution, e.g., the 1D optimal solution of W_2^2 is

$$M^* = P_T^{-1} \circ P_0, \tag{2}$$

where P_0 and P_T are the cumulative distribution functions for p_0 and p_T, and "$\circ$" represents the function composition. In practice, the 1D optimal solution in Eqn. (2) can be computed with the average square distance between the sorted samples from p_0 and p_T (Kolouri et al., 2019).

2.2 FUNCTIONAL CAUSAL MODELS

A FCM represents the effect Y as a function $f(\cdot)$ of the direct cause X and independent noise E_y, where function f describes the causal influence of X on Y, and E_y is the exogenous variable/noise. Without any additional assumption on the functional classes, the causal direction is not

(a) Pressureless potential flow under FCM constraints

(b) Volume-preserving pressureless potential flow under ANM constraints

Figure 1: Panel (a) illustrates the trajectories in the pressureless potential flow corresponding to the L^2 Wasserstein distance under the constraints of FCMs , while panel (b) shows the trajectories in the volume-preserving pressureless potential flow corresponding to the one under the constraints of ANMs. They have zero velocities on the E_x or X axis and move along straight lines. In panel (b), the straight lines with the same values of X are parallel to each other.

identifiable (Hyvärinen and Pajunen, 1999; Zhang et al., 2015a). Roughly speaking, this is because given variable pair (X, Y), one can always construct $Y = f(X, E_y)$ and another different FCM, $X = \widetilde{f}(Y, E_x)$, such that both of them are consistent with the data distribution and have independent "noise" (Hyvärinen and Pajunen, 1999; Zhang et al., 2015a). Several works further introduce proper assumptions on the functional form of the FCMs and the distributions of the involved variables, and then identify causal direction in the bivariate case, i.e., the independence of cause and noise only holds in the causal direction. Examples include the ANM and PNL models:

$$\text{ANM:} \quad Y \;=\; g(X) + E_y; \qquad (3) \qquad \text{PNL:} \quad Y \;=\; h(g(X) + E_y), \qquad (4)$$

where g and h are nonlinear functions and h is invertible.

3 DYNAMICAL INTERPRETATION OF FUNCTIONAL CAUSAL MODELS

We first show the connection between FCMs and optimal transport in Sec. 3.1. In Sec. 3.2, we further elaborate the analogy between the optimal transport problem and the causal direction determination problem. We then study the optimal transport under the constraints of FCMs, show the corresponding dynamical systems of FCMs, and characterize the properties of such systems.

3.1 CAUSALITY AND OPTIMALITY OF THE MAPS IN THE JACOBIAN PROBLEM

As introduced in Sec. 2.2, FCMs are used to approximate the true data generation process. Given the FCM, $Y = f(X, E_y)$, we rewrite it in a Jacobian equation way,

$$\mathbf{x}_T = \begin{bmatrix} X \\ Y \end{bmatrix} = \begin{bmatrix} E_x \\ f(X, E_y) \end{bmatrix} = M\Big(\begin{bmatrix} E_x \\ E_y \end{bmatrix} \Big) = M(\mathbf{x}_0), \qquad (5)$$

where $\mathbf{x}_0, \mathbf{x}_T \in \mathbb{R}^2$, their probability densities p_0, $p_T \geq 0$, and $M : \mathbb{R}^2 \to \mathbb{R}^2$. As an analogy to the mass transfer scenario (Monge, 1781), we consider the samples of independent noise E_x and E_y as the particles of materials in the mass transfer problem and regard the map M in Eqn. (5) as a special transformation of the independent noise samples. As shown in Fig. 1, one can consider the data points are transferred from the original positions (which are unmeasured) in the plane E_x–E_y at time 0 to the observed positions in the plane X–Y at time T. Such transformation considers the transfer as a causal process which moves the unmeasured independent noise $\mathbf{x}_0 = [E_x, E_y]'$ [1] and consequently leads to the observations $\mathbf{x}_T = [X, Y]'$. The sense of causality is enforced in the transformation through the constraints of FCMs; the transformation in Jacobian equation (1) is regularized with the *FCM constraints*:

---

[1] "'" denotes the transpose of vectors or matrices.

(i) *The map constraint:* the values of X are determined by the values of its corresponding noise, i.e., $X = E_x$, while the values of the effect depend on cause X and noise E_y;

(ii) *The independence constraint:* the noise terms are independent, i.e, E_x is independent of E_y.

How is causality defined with the FCM constraints connected with the optimality of maps in optimal transport? The optimal transport M^* with the minimal L^p Wasserstein distance is not necessary to be the causal one given by Eqn. (5), because it has no information about the FCM constraints or the true data generation process. Therefore, optimality in terms of minimal transformation cost and causality in terms of the FCM constraints are two different selection criteria for the maps in the Jacobian problem.

3.2 DYNAMICAL INTERPRETATION OF FCMs: OPTIMAL TRANSPORT UNDER THE FCM CONSTRAINTS

In this section we jointly consider causality and optimality of the maps in the Jacobian problem. It provides both a causal sense of the transformation and a dynamical view of FCMs. We first recap the dynamical formulation of the L^2 Wasserstein distance, and then study such dynamical systems under the FCM constraints. Furthermore, we show their properties under the FCM and ANM constraints.

Dynamical interpretation of the L^2 Wasserstein distance. Benamou and Brenier (2000) formulate the L^2 Monge-Kantorovich problem as a convex space-time minimization problem in a continuum mechanics framework. Fixing a time interval $[0, T]$, they introduce the concepts of smooth time-dependent density $\rho(t, \mathbf{x}_t) \geq 0$ and velocity fields $\mathbf{v}(t, \mathbf{x}_t)$. When they are clear from context, we denote them by ρ and $\mathbf{v}$. Because we are considering the bivariate case, $\mathbf{x}_t \in \mathbb{R}^2$ and $\mathbf{v} \in \mathbb{R}^2$. Then, they give the dynamical formulation of W_2^2:

$$W_2^2(p_0, p_T) \quad = \quad \inf_{\rho, \mathbf{v}} T \int_{\mathbb{R}^2} \int_0^T \rho(t, \mathbf{x}_t) |\mathbf{v}(t, \mathbf{x}_t)|^2 d\mathbf{x}_t dt, \tag{6}$$

$$\text{s.t.} \quad \begin{cases} \text{initial and final conditions: } \rho(0, \cdot) = p_0, \rho(T, \cdot) = p_T \\ \text{the continuity equation: } \partial_t \rho + \nabla \cdot (\rho \mathbf{v}) = 0 \end{cases}.$$

They prove that the solutions of (6) are pressureless potential flows, which are also the trajectories of free particles with some initial velocities under the least action principle (Arnol'd, 2013). Suppose that M^* is the solution given by W_2^2. The corresponding flows follow *time evolution equation*,

$$\mathbf{x}_t = \mathbf{x}_0 + \frac{t}{T} \mathbf{v}(t, \mathbf{x}_t), \text{ where } \mathbf{v}(t, \mathbf{x}_t) = \mathbf{v}(0, \mathbf{x}_0) = M^*(\mathbf{x}_0) - \mathbf{x}_0 \text{ and } t \in [0, T]. \tag{7}$$

The time evolution equation shows that $\mathbf{x}_t$ is just a convex combination of $\mathbf{x}_0$ and $M^*(\mathbf{x}_0)$.

As an analogy between the optimal transport problem and causal direction determination, the density ρ and the velocity $\mathbf{v}$ of moving particles can be considered as the probability density and the velocity of changing values of data points. Moreover, the dynamical interpretation of the L^2 Wasserstein distance introduces a time variable and provides a natural time interpolation $\rho(t, \mathbf{x}_t)$ of ρ_0 and ρ_T together with the velocity field $\mathbf{v}(t, \mathbf{x}_t)$ under the least action principle. Similarly, we can also have the natural time interpolation $p(t, \mathbf{x}_t)$ between p_0 and p_T as well as the velocity field $\mathbf{v}(t, \mathbf{x}_t)$ under the least action principle, which is the dynamical interpretation of FCMs.

Dynamical L^2 Wasserstein distance under the FCMs constraints. First, we introduce FCM constraints in the context of the dynamical L^2 Wasserstein distance. According to time evolution equation (7), we know that the velocity is fully determined by the initial and final values of $\mathbf{x}_t$. We first consider FCM constraint (i). For the initial and final values of the cause, the value of its observation X is equal to its noise value E_x in Eqn. (5). Consequently, denoting $\mathbf{v} = [v_x, v_y]'$, where v_x and v_y represent the velocities along the E_x/X-axis and E_y/Y-axis respectively as shown in Fi.g 1, we know that $\forall t \in [0, T]$, $x_t \in \mathbb{R}$, $v_x(t, x_t) = 0$. As for FCM constraint (ii), it implies that the initial noise of cause and effect, corresponding to E_x and E_y at the time 0, are independent. Therefore, we have the FCM constraints for the dynamical L^2 Wasserstein distance,

(I) *The map constraints*: $\mathbf{v}(t, \mathbf{x}_t) = [v_x(t, x_t), v_y(t, y_t)]', \forall x_t, y_t \in \mathbb{R}, t \in [0, T], v_x(t, x_t) = 0$;

(II) *The independence constraint*: Two random variables (cause and effect) at the initial time have the joint probability density function $p_0(\mathbf{x}_0)$ and they are independent.

Second, we characterize the properties of the dynamical optimal transport (L^2 Wasserstein distance) under constraints (I) and (II). According to Eqn. (5), the form of M^* is determined as

$$M^*(\mathbf{x}_0) = \begin{bmatrix} E_x \\ f(E_x, E_y) \end{bmatrix} ; \tag{8}$$

otherwise, the FCM constraints will be violated. Moreover, the two-dimensional W_2^2 under the FCM constraints can be computed with the one-dimensional W_2^2 as shown in Prop. 1 (the derivation is in App. A),

Proposition 1. *Under constraints* (I) *and* (II) *the square of the L^2 Wasserstein distance between p_0 and p_T is*

$$W_2^2(p_0, p_T) = \mathbb{E}_{E_x} \left[W_2^2 \left(p(E_y), p(Y|E_x) \right) \right] . \tag{9}$$

Furthermore, we consider the constraints of ANMs and characterize the corresponding dynamical systems for now, which can be directly extended to PNLs as mentioned in Sec. 4.2. Based on constraints (I) and (II), we further introduce the *ANM constraint*,

(III) the effect is the sum of noise and a nonlinear function of cause as defined in Eqn. (3).

Theorem 1 (Zero divergence of the velocity field). *Under constraints* (I) *and* (II)*, the dynamical systems given by the L^2 Wasserstein distance are pressureless flows. Further under ANM constraint* (III)*, they become volume-preserving pressureless flows, of which the divergence of the velocity field, $\mathbf{v}(t, \mathbf{x}_t) = [v_x(t, x_t), v_y(t, y_t)]'$, satisfies*

$$div\ \mathbf{v}(t, \mathbf{x}_t) = \frac{\partial v_x(t, x_t)}{\partial x_t} + \frac{\partial v_y(t, y_t)}{\partial y_t} = 0, \forall t \in [0, T],\ x_t, y_t \in \mathbb{R},$$

where div is the divergence operator in vector calculus.

Thm. 1 determines the corresponding dynamical systems of FCMs and ANMs by analyzing their densities and velocity fields (the details of the proof are in App. A), and shows a property of the corresponding dynamical systems of ANMs. Importantly, the property indicates a potential criterion for causal direction determination, that in the causal direction the divergence of the velocity field is zero everywhere, while in the reverse direction it may not always hold. Next, we will verify the criterion rigorously, propose an algorithm based on it, and show the extension for the PNL cases.

4 CAUSAL DIRECTION DETERMINATION WITH OPTIMAL TRANSPORT

In this section we define a divergence measure as a criterion of determining causal direction between two variables for ANMs. Based on the criterion, we then provide an algorithm to identify the causal direction, named by the divergence measure with optimal transport (DIVOT).

4.1 DIVERGENCE MEASURE AS A CRITERION OF DETERMINING CAUSAL RELATION BETWEEN TWO VARIABLES

We first define the divergence measure and then show that it is a valid criterion for identifying the causal direction in the bivariate case under the identifiability conditions of ANMs, as shown in Prop. 2 (the proof is in App. A).

Proposition 2 (Divergence measure as a causal discovery criterion)**.** *Define the divergence measure,*

$$D(\mathbf{v}) = \int_{\mathbb{R}^2} |div\ \mathbf{v}|^2 p_0(\mathbf{x}_0) d\mathbf{x}_0 = \mathbb{E}_{\mathbf{x}_0} [\,|div\ \mathbf{v}|^2], \tag{10}$$

where $\mathbf{v} = M^*(\mathbf{x}_0) - \mathbf{x}_0$. Suppose that constraints (I)*,* (II)*,* (III)*, and the identifiability conditions of ANMs (Hoyer et al., 2008) are satisfied. The divergence measure of the corresponding dynamical system satisfies $D(\mathbf{v}) = 0$ if and only if X is the direct cause of Y.*

Nevertheless, there are some challenges to compute the divergence measure. For example, we need to solve a two-dimensional optimal transport problem and compute the derivative of a velocity field for all samples. Another challenge with computing M^* is that we in general have no information about $\mathbf{x}_0$. Such issues are all solved with DIVOT.

4.2 Proposed method: DIVOT

We first provide an overview of the algorithm, DIVOT, for determining the causal direction between two variables, and then introduce the four steps to compute the divergence measure.

Overview of DIVOT. Alg. 1 is based on the divergence-measure criterion of causal direction determination (Prop. 2) and determines causal direction between two variables. Given data of X and Y, we want to infer whether X causes Y ($X \rightarrow Y$) or Y causes X ($Y \rightarrow X$). We compute the divergence measure of both directions. And the one with the smaller value of its divergence measure is the causal direction.

Algorithm 1: DIVOT: Causal direction determination using the divergence measure with optimal transport

---

Input: data $\{(x_i, y_i)\}$ and noise distribution $p(E; \theta_0)$
Output: $X \rightarrow Y$ or $Y \rightarrow X$.

1 **Def** DIVOT ($\{(x_i, y_i)\}, p(E; \theta_0)$):
2   data, $\theta = \{(x_i, y_i)\}, \theta_0$
3     $\mathcal{L}_{X \rightarrow Y} = \text{Div}(\text{data}, p(E; \theta))$
4   data, $\theta = \{(y_i, x_i)\}, \theta_0$
5     $\mathcal{L}_{Y \rightarrow X} = \text{Div}(\text{data}, p(E; \theta))$

6 **if** $\mathcal{L}_{Y \rightarrow X} < \mathcal{L}_{X \rightarrow Y}$ **then**
7   **return** $Y \rightarrow X$
8 **else**
9   **return** $X \rightarrow Y$
10 **Def** Div (*data*, $p(E; \theta)$):
11   noise = Sampling($p(E; \theta)$)
12     $\text{data}^s, \text{noise}^s = \text{OT}(\text{data}, \text{noise})$
13   loss = VarDiv($\text{data}^s, \text{noise}^s$)
14   **return** $\min_\theta$ loss

Noise data generation: The first step of computing the divergence measure: To compute the divergence measure, we need to know the velocity field $\mathbf{v}$ as defined in time evolution equation (7). It requires the couplings of the data of $\mathbf{x}_0 = [E_x, E_y]'$ and $\mathbf{x}_T$. But in the bivariate causal discovery task, only the data of $\mathbf{x}_T = [X, Y]'$ are given. Therefore, as shown in Line 11 of Alg. 1, we first deal with the issue due to the lack of the noise data of $\mathbf{x}_0$, denoted by $\{(e_x^i, e_y^i)\}$. To obtain the noise data, we want to assume a multivariate probability distribution of $\mathbf{x}_0$ with the density $p_0(E_x, E_y)$, and then sample the data from it, represented by $(e_x^i, e_y^i) \sim p_0(E_x, E_y)$. Furthermore, due to the FCM constraints, we know that $p_0(E_x, E_y) = p_0(X, E_y) = p(X)p(E_y)$. So we only need to assume the probability distribution of E_y and parameterize it with θ, denoted by $p(E_y; \theta)$. Suppose that the dataset of $\mathbf{x}_T$ with N samples is given, denoted by $\{(x_i, y_i)\}_N$. We first sample a data set of E_y with the sample size N, denoted by $\{e_y^i\}_N$, e.g., in the experiments of this work, we use the simplified reparameterization trick,

$$e_y^i = f_\theta^{\text{noise}}(e_y^{\text{source}}) = \theta \times e_y^{\text{source}} \text{ and } e_y^{\text{source}} \sim \mathcal{N}(0, 1)/\mathcal{U}(0, 1), \tag{11}$$

where f_θ^{noise} is a monotonic function, and e_y^{source} is sampled from a standard normal distribution or a uniform distribution. As the monotonic f_θ^{noise} can be very flexible, we can represent flexible noise distributions with monotonic neural networks as in (Huang et al., 2018). Next, we randomly match the data of X, denoted by $\{x_i\}_N$, with $\{e_y^i\}_N$, which gives the $\{(x_i, e_y^i)\}_N$ as the data of $\mathbf{x}_0$.

Optimal transport: Find couplings of the observation and the generated noise. Computing the divergence measure requires the couplings of the data of $\mathbf{x}_0$ and $\mathbf{x}_T$, because we need $\mathbf{v} = M^*(\mathbf{x}_0) - \mathbf{x}_0$; in other words, given the data of $\mathbf{x}_0$ and $\mathbf{x}_T$, we need to solve a two-dimensional optimal transport problem, which gives M^* as in Line 12 of Alg. 1. According to Prop. 1, solving the two-dimensional optimal transport problem under the FCM constraints is equivalent to solving one-dimensional optimal transport problems. More specifically, the expectation in Eqn. (9) of Prop. 1 is computed by using N samples of E_x, denoted by $\{e_x^i\}_N$, and then the two-dimensional W_2^2 in Eqn. (9) is computed with N one-dimensional W_2^2, i.e., $W_2^2(p_0, p_T) = \frac{1}{N}\sum_i W_2^2(p(E_y), p(Y|E_x = e_x^i))$. Importantly, solving the one-dimensional optimal transport problem or computing the one-dimensional W_2^2 can be implemented with a sorting operation as in (Kolouri et al., 2019). Therefore, the couplings are found by which given each value of E_x we find the corresponding values of E_y and Y from $\{(e_x^i, e_y^i)\}_N$ and $\{(x_i, y_i)\}_N$, and then match such sorted values of E_y and Y .

Variance-based divergence measure. Suppose that the previous step has found the couplings, i.e., given any sample (e_x^i, e_y^i) we have its corresponding (x_i, y_i). Then, we will compute the divergence

of a velocity field as in Line 13 of Alg. 1. According to the definition, $|\text{div } \mathbf{v}|^2 = (\frac{dv_y}{dy})^2$. Since all the e_y^i are matched with y_i, we have $v_y^i = y_i - e_y^i$. A straightforward way to approximate the derivative is using its nearest neighbour pair (e_{xb}^i, e_{yb}^i) and (xb_i, yb_i) and then approximate it with $\frac{d}{dy}(v_y)|_{y=y_i} = \frac{(y_i - e_y^i) - (yb_i - e_{yb}^i)}{y_i - yb_i}$; however, it suffers the following issues (especially in the few-sample scenario) : (a) the denominator is in general a small number and the distance to the nearest neighbour can be large in the few sample case, which makes the computation unstable and inaccurate; (b) the deviation on the X-axis makes the approximation a biased estimate especially when the gradient of $g(X) + E_y$ at $X = x$ is large. Therefore, we propose the variance-based divergence measure working better in practice. It is straightforward to see that under constraints (I) and (II), the value of the divergence measure of an ANM is zero if and only if the value of the *variance-based divergence measure* is zero, which is defined as

$$D_{\text{var}}(\mathbf{v}) = \mathbb{E}_X[\mathbb{V}[V_{y|X}|X]], \tag{12}$$

where $\mathbb{V}[V_{y|X}|X]$ represents a conditional variance of the velocity field V_y (a random variable) at position X at the initial time. For example, $\mathbb{V}[V_{y|x}|X = x]$ represents the variance of all the velocities v_y at the positions where $X = x$ at the initial time. Let $\{(x_i, y_i)\}_N$ denote the cause-effect pair dataset with the sample size N, and $\{v_{y|x}^i\}_{N_x}$ denote all the velocities v_y^i at position $X = x$ at the initial time, the sample size is N_x, and their mean value is $\overline{v}_{y|x}$. Then, $\mathbb{V}[Vy|x|X = x] = \sum_{i=1}^{N_x}(v_{y|x}^i - \overline{v}_{y|x})^2/(N_x - 1)$, and

$$D_{\text{var}}(\mathbf{v}) \approx \frac{1}{N} \sum_{x \in \{x_i\}_N} \frac{\left\|\text{sort}(\overrightarrow{y_x}) - \text{sort}(\overrightarrow{e_y}) - \text{ave}(\overrightarrow{y_x} - \overrightarrow{e_y})\right\|_2^2}{N_x - 1}, \tag{13}$$

where $\{x_i\}_N$ represents the set of all the values of X and its sample size is N; $\overrightarrow{y_x}$ is the vector of the Y samples where $X = x$; $\overrightarrow{e_y}$ is the vector of the E_y samples where $E_x = x$; $\text{sort}(\cdot)$ sorts a vector; $\text{ave}(\cdot)$ computes the vector mean; and $\|\cdot\|_2^2$ is the square of a ℓ_2 norm.

Extension to PNLs. The measure (13) can be directly extended to the PNL cases. Since h in PNL (4) is an invertible function, by considering $h^{-1}(Y)$ as a new random variable, $h^{-1}(Y) = g(X) + E_y$ is an ANM. Thus, for PNLs, under the identifiabililty conditions of PNLs (Zhang and Hyvärinen, 2009b), Prop. 2 still holds; and we only need replace $\overrightarrow{y_x}$ in (13) with $\overrightarrow{\widetilde{y}_x} = f_\omega^{\text{PNL}}(\overrightarrow{y_x})$, where f_ω^{PNL} is an invertible function, e.g., it can be the simplified version of (Zhang et al., 2015a),

$$\overrightarrow{\widetilde{y}_x} = f_\omega^{\text{PNL}}(\overrightarrow{y_x}) = \overrightarrow{y_x} + \omega_a \cdot \tanh(\omega_b \cdot \overrightarrow{y_x} + \omega_c), \tag{14}$$

where ω_a, ω_b, and ω_c are positive scalars. Moreover, f_ω^{PNL} can also be the monotonic neural networks, such as (Huang et al., 2018).

Minimization w.r.t θ. Given the data $\{(x_i, y_i)\}_N$ and the density $p(E_y; \theta)$, we can compute the divergence measure with the variance-based method. Note that we only initialize θ with some random value, and $p(E_y; \theta)$ is not necessary to be the true distribution or even significantly different from the true one, which can lead to the wrong result of the divergence measure. Therefore, as shown in Line 14 of Alg. 1, we minimize the divergence measure w.r.t. θ. For the minimization, one can derive the gradient w.r.t θ in a simple parameterization case as (11), while in the complex case one can use auto-differentiation. According to Prop. 2, in the causal direction the divergence measure is zero if and only if $p(E_y; \theta^*)$ with the optimal parameter θ^* is the true noise distribution a.e., implied by the identifiability of ANMs. In this work, we used `autograd` and `RMSProp` (gradient descent) of JAX for the minimization.

5 RELATED WORK

There are mainly two types of causal discovery methods for static causal direction determination between two variables. The first one introduces model assumptions of FCMs to achieve the identifiability of causal direction. Most of such methods are based on LiNGAM (Shimizu et al., 2006), ANMs (Hoyer et al., 2008; Mooij et al., 2009) and some of them are based on the more general models, PNLs useing MLP for representing nonlinear functions (PNL-MLP) (Zhang and Hyvärinen,

(a) Accuracy on different ANM datasets. (b) Robustness to prior misspecification.

Figure 2: Performance on synthetic data generated from different ANMs with different sample sizes. f_{piece} is a discontinuous function: $f_{\text{piece}}(x) = 0.5x^3 - x, x \leq 0$; $f_{\text{piece}}(x) = 1 - 0.5x^3 + x, x > 0$. In panel (a), each result represents the percentage of correct results on datasets with a sample size generated from an ANM. Panel (b) shows the results of applying DIVOT using different types of distributions, $p(E_y; \theta)$, to the datasets with uniform distribution noise $E_y \sim \mathcal{U}(0, 1)$.

2009b), PNLs using warped Gaussian process and mixture of Gaussian noise (PNL-WGP-MoG) (Zhang et al., 2015a). Recently, Khemakhem et al. (2021) propose an autoregressive flow based model (CAREFL), of which the assumption is more general than ANMs and stricter than PNLs. They commonly apply (non)linear regression to learn the function g in (3) (or together with h in (4)), and then test the independence between the independent noise E_y in (3) (the residual) and the cause X. And the independence test is commonly Hilbert-Schmidt independence criterion (HSIC) (Gretton et al., 2005); however, as argued by Yamada and Sugiyama (2010), the kernel width limits its practical use and its common heuristic value limits the flexibility of the function approximation. Moreover, there are other criteria proposed in the first type of methods, such as the likelihood ratio (LLR) (Hyvärinen and Smith, 2013), maximum likelihood based criterion (MML), regression error based causal inference (RECI) (Blöbaum et al., 2018) and mutual information (Zhang and Hyvärinen, 2009a; Yamada and Sugiyama, 2010). Nevertheless, the common issue of the first type of methods is that they restrict the model classes and their performance depends on model assumptions. The second type of methods achieve idenifiability by proposing other principles instead of restricting model classes, such as exogeneity (Zhang et al., 2015b), randomness of exogeneous variables (Entropic) (Compton et al., 2021), and independent causal mechanisms, e.g., GPI (Stegle et al., 2010) and IGCI (Janzing et al., 2012).

6 EXPERIMENTS

We demonstrate and evaluate our method on the synthetic and real-world cause-effect pair data (Mooij et al., 2016). The details of implementation and experiments are in App. B.

6.1 SYNTHETIC DATA

We evaluate DIVOT with Gaussian noise as in (11) on the datasets with different (non)linear functions and samples sizes. We generate synthetic data with the ANMs: 1) $Y = X + E_y$; 2) $Y = 0.1(2.5X)^3 - 0.1X + E_y$; 3) $Y = \sin(4X) + E_y$; 4) if $x < 0, Y = 0.5X^3 - X + E_y$ and if $x \geq 0, Y = 1 - 0.5X^3 + X + E_y$, where $X \sim \mathcal{U}(-1, 1)$ and $E_y \sim \mathcal{U}(0, 1)$ are uniform distribution. For each ANM, we generate datasets with the sample sizes 10, 25, 50, 100, 200, and 500. With each sample size, 100 different datasets are generated for computing the accuracy.

Fig. 2a shows that DIVOT consistently recovers the causal direction for all the cases. Since DIVOT has no smoothness constraint of functions, it can deal with the case 4) which is a discontinuous function. We compared DIVOT with the results of CAREFL (Khemakhem et al., 2021), RECI (Blöbaum et al., 2018), and other benchmark methods in Appendix. As shown in Fig. 7 of App. B, our method performs better than the others. Moreover, we also show the robustness of DIVOT to

Table 1: Accuracy (%) of recovering the true causal direction on the Tübingen cause-effect pair dataset (Mooij et al., 2016) compared with the reported results of (Stegle et al., 2010) in the upper table and (Zhang et al., 2015a) in the lower table.

Ours (PNL)	Ours (ANM)	LiNGAM	ANM-Gauss	ANM-MML	ANM-HSIC	PNL	GPI-HSIC	GPI-MML	IGCI
78.9±3.9	71±4	62±3	45±3	68±1	68±3	67±4	62±4	72±2	76±1

Ours (PNL)	Ours (ANM)	ANM	WGP-Gauss	WGP-MoG	PNL-MLP	GPI	IGCI
76.6±4.5	67±3	63	67	73	70	72	73

the prior misspecification as the experiments in CAREFL (Khemakhem et al., 2021). The synthetic data are generated with uniform distribution noise $E_y \sim \mathcal{U}(0,1)$, where the $p(E_y; \theta)$ of DIVOT is either uniform distribution $\mathcal{U}(0,1)$, beta distribution $\mathcal{B}(a = 0.5, b = 0.5)$, or standard normal distribution $\mathcal{N}(0,1)$. As shown in Fig. 2b, DIVOT with the misspecified noise distributions has similar performance with the one using the correct class of distributions.

6.2 TÜBINGEN CAUSE-EFFECT PAIR DATASET

We apply DIVOT to the Tübingen cause-effect pair dataset (Mooij et al., 2016). This is a collection of real-world cause-effect pairs. We use the variance-based divergence measure (13) and parameterize $p(E_y; \theta)$ as in (11). As for the PNL extension, we implement (14) without the positivity constraint (in practice imposing no constraint on ω also performs well in this simple formulation). Moreover, we found that given a value of X or Y of the datasets, there are often few samples. Thus we consider a range of values of X, which may introduce bias of the divergence measure; hence we also use a linear debiasing function for reducing the bias. Then, we minimize the variance-based divergence measure over parameters with `autograd` of JAX. More details about the debiasing function and optimization can be found in App. B. To compare with the results reported in other works, we use the maximum number of the sample size $N = 500$ as (Stegle et al., 2010; Zhang et al., 2015a) and run all the experiments with 3 random seeds as (Stegle et al., 2010), though DIVOT is efficient enough for datasets with larger sample sizes as shown in Appendix. In addition, we normalize data and select the ones within 2 standard deviation, because DIVOT is sensitive to the outliers as optimal transport. As shown in Tab. 1, our proposed DIVOT, especially the extension for PNLs, outperforms than the other methods. The reported results in Tab. 1 are taken from (Stegle et al., 2010) and (Zhang et al., 2015a). And our results are based on the same datasets as them, i.e., with 68 and 77 cause-effect pairs respectively. Moreover, the entropic causal inference (Compton et al., 2021) is reported with 64.21% accuracy; CAREFL (Khemakhem et al., 2021) is reported with 73% accuracy on 108 pairs; RECI (Blöbaum et al., 2018) is reported with 76% weighted accuracy on the 100 pairs. From Tab. 1, we can also see that the other ANM/PNL-based methods are more sensitive to the choice of noise distributions. As shown in Tab. 1, the ANM/PNL with Gaussian noise performs worse than the one with a more complex distribution (mixture of Gaussian) or the one combined with a more stable measure, such as HSIC independence test. In contrast, the PNL extension of DIVOT with the Gaussian noise has a state-of-the-art result.

7 CONCLUSION

In this paper, we provide a new dynamical-system perspective of FCMs in the context of identifying causal relationships in the bivariate case. We first demonstrate the connection between FCMs and optimal transport, and study the dynamical systems of the optimal transport under constraints of FCMs. We then show that FCMs correspond to pressureless potential flows and that ANMs as a special case corresponding to the pressureless potential flows with the velocity field divergence equal to zero. Based on such findings, we propose a divergence measure-based criterion for causal discovery and provide an efficient optimal transport-based algorithm, DIVOT, for identifying causal direction between two variables. The experimental results on both synthetic and real datasets show that compared with the state-of-the-art methods, DIVOT has state-of-the-art results and promising properties for flexibility, efficiency, and prior misspecification robustness. We hope that the connection between FCMs and optimal transport has the potential of helping understand general FCMs from the dynamical perspective and inspiring more generic causal discovery methods.

REFERENCES

M. Arjovsky, S. Chintala, and L. Bottou. Wasserstein generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 214–223. PMLR, 06–11 Aug 2017.

V. I. Arnol'd. *Mathematical methods of classical mechanics*, volume 60. Springer Science & Business Media, 2013.

J.-D. Benamou and Y. Brenier. A computational fluid mechanics solution to the monge-kantorovich mass transfer problem. *Numerische Mathematik*, 84(3):375–393, 2000.

P. Blöbaum, D. Janzing, T. Washio, S. Shimizu, and B. Schölkopf. Cause-effect inference by comparing regression errors. In *International Conference on Artificial Intelligence and Statistics*, pages 900–909. PMLR, 2018.

J. Bradbury, R. Frostig, P. Hawkins, M. J. Johnson, C. Leary, D. Maclaurin, G. Necula, A. Paszke, J. VanderPlas, S. Wanderman-Milne, and Q. Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

R. T. Chen, Y. Rubanova, J. Bettencourt, and D. Duvenaud. Neural ordinary differential equations. *arXiv preprint arXiv:1806.07366*, 2018.

S. Compton, M. Kocaoglu, K. Greenewald, and D. Katz. Entropic causal inference: Identifiability and finite sample results. *arXiv preprint arXiv:2101.03501*, 2021.

A. Genevay, G. Peyré, and M. Cuturi. Learning generative models with sinkhorn divergences. In *International Conference on Artificial Intelligence and Statistics*, pages 1608–1617. PMLR, 2018.

A. Gretton, O. Bousquet, A. Smola, and B. Schölkopf. Measuring statistical dependence with hilbert-schmidt norms. In *International conference on algorithmic learning theory*, pages 63–77. Springer, 2005.

P. Hoyer, D. Janzing, J. M. Mooij, J. Peters, and B. Schölkopf. Nonlinear causal discovery with additive noise models. *Advances in neural information processing systems*, 21:689–696, 2008.

C.-W. Huang, D. Krueger, A. Lacoste, and A. Courville. Neural autoregressive flows. In *International Conference on Machine Learning*, pages 2078–2087. PMLR, 2018.

A. Hyvärinen and P. Pajunen. Nonlinear independent component analysis: Existence and uniqueness results. *Neural networks*, 12(3):429–439, 1999.

A. Hyvärinen and S. M. Smith. Pairwise likelihood ratios for estimation of non-gaussian structural equation models. *Journal of Machine Learning Research*, 14(Jan):111–152, 2013.

D. Janzing, J. Mooij, K. Zhang, J. Lemeire, J. Zscheischler, P. Daniušis, B. Steudel, and B. Schölkopf. Information-geometric approach to inferring causal directions. *Artificial Intelligence*, 182:1–31, 2012.

L. V. Kantorovich. On a problem of monge. *Uspekhi Mat. Nauk.*, 1948.

I. Khemakhem, R. Monti, R. Leech, and A. Hyvarinen. Causal autoregressive flows. In *International Conference on Artificial Intelligence and Statistics*, pages 3520–3528. PMLR, 2021.

S. Kolouri, G. K. Rohde, and H. Hoffmann. Sliced wasserstein distance for learning gaussian mixture models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3427–3436, 2018.

S. Kolouri, K. Nadjahi, U. Simsekli, R. Badeau, and G. Rohde. Generalized sliced wasserstein distances. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

G. Monge. Mémoire sur la théorie des déblais et des remblais. *Histoire de l'Académie Royale des Sciences de Paris*, 1781.

J. Mooij, D. Janzing, J. Peters, and B. Schölkopf. Regression by dependence minimization and its application to causal inference in additive noise models. In *Proceedings of the 26th annual international conference on machine learning*, pages 745–752, 2009.

J. M. Mooij, J. Peters, D. Janzing, J. Zscheischler, and B. Schölkopf. Distinguishing cause from effect using observational data: methods and benchmarks. *The Journal of Machine Learning Research*, 17(1):1103–1204, 2016.

S. Shimizu, P. O. Hoyer, A. Hyvärinen, A. Kerminen, and M. Jordan. A linear non-gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7(10), 2006.

L. N. Smith. Cyclical learning rates for training neural networks. In *2017 IEEE winter conference on applications of computer vision (WACV)*, pages 464–472. IEEE, 2017.

P. Spirtes, C. Glymour, and R. Scheines. Causation, prediction, and search, 2nd edn., vol. 1, 2001.

O. Stegle, D. Janzing, K. Zhang, J. M. Mooij, and B. Schölkopf. Probabilistic latent variable models for distinguishing between cause and effect. *Advances in neural information processing systems*, 23:1687–1695, 2010.

T. Tao. Matrix identities as derivatives of determinant identities, 2013. URL https://terrytao.wordpress.com/2013/01/13/matrix-identities-as-derivatives-of-determinant-identities/.

M. Yamada and M. Sugiyama. Dependence minimizing regression with model selection for non-linear causal inference under non-gaussian noise. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 24, 2010.

K. Zhang and A. Hyvärinen. Causality discovery with additive disturbances: An information-theoretical perspective. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 570–585. Springer, 2009a.

K. Zhang and A. Hyvärinen. On the identifiability of the post-nonlinear causal model. In *Proceedings of the Twenty-Fifth Conference on Uncertainty in Artificial Intelligence*, pages 647–655, 2009b.

K. Zhang, Z. Wang, J. Zhang, and B. Schölkopf. On estimation of functional causal models: general results and application to the post-nonlinear causal model. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 7(2):1–22, 2015a.

K. Zhang, J. Zhang, and B. Schölkopf. Distinguishing cause from effect based on exogeneity. *arXiv preprint arXiv:1504.05651*, 2015b.

APPENDIX

In App. A, we provide the proofs of Prop. 1, Prop. 2, and Thm. 1. In App. B, we introduce the details of the DIVOT implementation and the experiments:

- App. B.1: introduce the concept, position, for computing the divergence measure (13);
- App. B.2: show a potential problem of computing the variance-based divergence measure in the finite/limited-sample case, and introduce batches of data to deal with the problem;
- App. B.3: show that using batches can introduce bias and lead to wrong causal relationships, especially in the few-sample case, and then introduce debiasing functions to reduce the bias, which is used for the experiments in Sec. 6.2;
- App. B.4: introduce the optimization methods used in the experiments in Sec. 6.1 and Sec. 6.2, and show the convexity of the objective function, the divergence measure (13), under the construction in Sec. 6.1 and Sec. 6.2;
- App. B.5: show the robustness of DIVOT to prior misspecification;
- App. B.6: compare DIVOT with other benchmark methods;
- App. B.7: show the efficiency of DIVOT with its running time.

A PROOFS AND DERIVATION

A.1 DERIVATION OF PROP. 1

Under constraints (I) and (II),

$$
\begin{aligned}
&W_2^2(p_0, p_T) \\
&= \int |M^*(\mathbf{x}_0) - \mathbf{x}_0|^2 p_0(\mathbf{x}_0) d\mathbf{x}_0 &&\text{definition of } W_2^2 \\
&= \iint (f(E_x, E_y) - E_y)^2 p(E_y) dE_y p(E_x) dE_x &&\text{Eqn. (8), and the independence of } E_x \text{ and } E_y \\
&= \mathbb{E}_{E_x}[W_2^2(p(E_y), p(Y|E_x))]
\end{aligned}
$$

A.2 PROOF OF THM. 1

Part I. We first derive the time interpolation $p(t, \mathbf{x}_t)$ of p_0 and p_T under dynamical FCM constraints. Suppose that the FCMs are $Y = f(X, E_y)$. As for the dynamical formulation of the L^2 Wasserstein distance under constraints (I) and (II), according to the Jacobian equation, $p(t, \mathbf{x}_t) = p_0(\mathbf{x}_0)/|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})|$, $t \in (0, T)$, where $\mathbf{x}_t, \mathbf{x}_0 \in \mathbb{R}^2$ and $J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}}$ is the Jacobian matrix w.r.t $\mathbf{x}_0$. Moreover, $\frac{\partial \log p(t, \mathbf{x}_t)}{\partial t} = -\frac{\frac{\partial}{\partial t}|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})|}{|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})|}$, where $J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}} = \begin{bmatrix} 1 + \frac{t}{T}, & 0 \\ \frac{t}{T}\frac{\partial f}{\partial X}, & \frac{t}{T}(\frac{\partial f}{\partial E_y} - 1) + 1 \end{bmatrix}$.

According to Jacobi's formula and (Tao, 2013),

$$
\begin{aligned}
&\frac{d}{dt}|\det(A(t))| \\
&= \pm \det(A(t))\mathrm{tr}\left(A(t)^{-1}\frac{d}{dt}A(t) \right) \\
&= \pm \det(A(t))\mathrm{tr}\left(\det(A(t))^{-1}\mathrm{adj}(A(t))\frac{d}{dt}A(t) \right) \\
&= \pm \sum_{ij}\left(\mathrm{adj(A(t))}' \odot \frac{d}{dt}A(t) \right).
\end{aligned}
$$

where $\odot$ is element wise multiplication and $\mathrm{adj}(A)$ is adjugate matrix of A and the sign takes the same sign as $\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})$. Furthermore, since we know that under the structural constraints (I) and

(II), M^* is Eqn. (8). Thus, we replace $A(t)$ with $J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}} = I + \frac{t}{T}(\nabla M^* - I)$, and then we have

$$
J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}} = \begin{bmatrix} 1 + \frac{t}{T}, & 0 \\ \frac{t}{T}\frac{\partial f}{\partial X}, & \frac{t}{T}(\frac{\partial f}{\partial E_y} - 1) + 1 \end{bmatrix};
$$

$$
\mathrm{adj}(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})' = \begin{bmatrix} \frac{t}{T}(\frac{\partial f}{\partial E_y} - 1) + 1, & \frac{t}{T}\frac{\partial f}{\partial X} \\ 0, & 1 + \frac{t}{T} \end{bmatrix};
$$

$$
\frac{d}{dt}J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}} = \frac{1}{T}(\nabla M^* - I) = \begin{bmatrix} 0, & 0 \\ \frac{1}{T}\frac{\partial f}{\partial X}, & \frac{1}{T}(\frac{\partial f}{\partial E_y} - 1) \end{bmatrix}.
$$

Therefore,

$$
\frac{d}{dt}|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})| = \pm\frac{1}{T}(\frac{\partial f}{\partial E_y} - 1)(1 + \frac{t}{T}),
$$

which takes the same sign as $\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})$.

Part II. We then proof the property of the corresponding dynamical systems of ANMs in Thm. 1.

Because $\frac{\partial \log p(t, \mathbf{x}_t)}{\partial t} = -\frac{\frac{\partial}{\partial t}|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})|}{|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})|}$, under the conditions in Thm. 1, $\frac{\partial f}{\partial E_y} = 1$ and it is obvious that $\frac{d}{dt}|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})| = 0$ and $|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})| \neq 0$, $\forall t \in [0, T]$. Furthermore, according to the theorem of instantaneous change of variables (Chen et al., 2018), which is a variant of Fokker-Plank equation, we know that

$$
\frac{\partial \log p(\mathbf{x}(t))}{\partial t} = -\mathrm{tr}(\nabla \mathbf{v}) = -\mathrm{div}\,\mathbf{v}.
$$

Therefore, div $\mathbf{v} = 0$.

A.3 PROOF OF PROP. 2

Necessary direction. We prove the necessary direction by showing that given X is the direct cause of Y in an ANM, $D(\mathbf{v}) = 0$. In the causal direction, because of the time evolution equation (7), we know that it is sufficient to check the divergence of the velocity field at time 0, and that the divergence taking zero value everywhere at time 0 implies the divergence taking zero value everywhere for $t \in [0, T]$. Because of Thm. 1, we know the div $\mathbf{v} = 0$ at time 0. Therefore, $D(\mathbf{v}) = 0$.

Sufficient direction. We prove the sufficient direction by showing the contradiction with the identifiability of ANMs. Given that $D(\mathbf{v}) = 0$ under the constraints (I), (II), (III), and the identifiability conditions of ANMs, it tells us that there is an ANM in the form of Eqn. (3) which is consistent with the data distribution and has independent noise. Because of the identifiability of ANMs shown by (Hoyer et al., 2008), there is no ANM with $Y \rightarrow X$ which is consistent with the data distribution and has independent noise at the same time. Therefore, it can only be the case the X is the cause of Y.

Moreover, there is a concern that it may happen that in the direction which is not the causal direction, the model is not an ANM and its divergence measure is equal to zero. This may be problematic if the divergence measure is applied to applications. However, we will show that in general, this will not happen by proving that under weak assumptions $D(\mathbf{v}) = 0$ implies the model is an ANM. First, $D(\mathbf{v}) = 0$ implies div $\mathbf{v} = 0$ for all $\mathbf{x}_0$ with positive probability densities $p(\mathbf{x}_0) > 0$. In the following we say div $\mathbf{v} = 0$ in short. Second, div $\mathbf{v} = 0$ implies $\frac{\partial p(t, \mathbf{x}_t)}{\partial t} = 0$ a.e. according to Thm. 1. Consequently, $\frac{d|\det(J_{\frac{\partial \mathbf{x}_t}{\partial \mathbf{x}_0}})|}{dt} = 0$, which leads to $\frac{\partial f}{\partial E_y} = 1$ where $Y = f(X, E_y)$ a.e. according to the proof of Thm. 1. Therefore, under the assumptions: 1) $p(E_y)$ is positive in a continuous range of E_y; 2) in the range, $\frac{\partial f}{\partial E_y} = 1$ a.e. implies that it holds everywhere, we have $Y = E_y + C$, where C is a quantity which doesn't change with E_y, e.g., it can be a function of X or a constant. Therefore, $D(\mathbf{v}) = 0$ implies $Y = E_y + g(X)$ further under assumptions 1) and 2).

B   EXPERIMENTS AND DETAILS OF DIVOT

For the experiments in Sec. 6.1, we visualized the generated data with the sample size 500 in Fig. 3. For determining causal direction, we used the variance-based divergence measure in Eqn. (13).

Figure 3: Synthetic data generated from ANMs with different (non)linear functions. From left to right, they are (1) $Y = X + E_y$; (2) $Y = 0.1(2.5X)^3 - 0.1X + E_y$; (3) $Y = \sin(4X) + E_y$; (4) $Y = 0.5X^3 - X + E_y$ if $x < 0$, and $Y = 1 - 0.5X^3 + X + E_y$, otherwise, where $X \sim \mathcal{U}(-1, 1)$ and $E_y \sim \mathcal{U}(0, 1)$ are uniform distributions.

The experiment setup is the same for experiments with different ANMs. For each ANM, we run experiments with different sample sizes, 10, 25, 50, 100, 200, and 500. With each sample size, 100 different datasets are generated for testing the accuracy of DIVOT. For all the experiments in Sec. 6.1, we use batches for computing Eqn. (13) without using debiasing functions. In the following, we introduce positions (App. B.1), batches (App. B.2), debiasing functions (App. B.3), and optimization details (App. B.4) of DIVOT; as well as show its robustness to prior misspecification (App. B.5), more comparison with other benchmark methods (App. B.6), and its efficiency (App. B.7).

B.1   NUMBER OF POSITIONS FOR COMPUTING THE VARIANCE-BASED DIVERGENCE MEASURE

Suppose a dataset $\{(x_i, y_i)\}_N$ with sample size N. For computing the divergence measure, we call $x \in \{x_i\}_N$ as a position and for each $x \in \{x_i\}_N$ we need to specify the corresponding vector $\overrightarrow{y_x}$ of which the number of elements is N_x and generated samples of $\overrightarrow{e_y}$. In practice, it is not necessary to use all the N positions for computing Eqn. (13). For the experiments in Sec. 6.1, when $N > 50$, we choose 50 positions out of N; otherwise, we choose all the N positions. To select a position (when $N > 50$), we first find the maximal and minimal values of $\{x_i\}_N$, compute the interval length, $\left(\max(\{x_i\}_N) - \min(\{x_i\}_N)\right)/50$, and then choose a position every such length (or its nearest position available in the data). We can then compute Eqn. (13) for causal direction determination.

B.2   BATCHES FOR THE FINITE (OR LIMITED) SAMPLE SCENARIO

In the finite sample scenario, it can be the case that there is no other data at a position x. Therefore, we use the neighbors of x as a batch of data for computing Eqn. (13). We consider all the data in a batch as having the same value x. We represent the batch size with the percentage of the total number N of samples. For the experiments in Sec. 6.1, we use the batch size 0.4 for the datasets with sample size 10; 0.2 for the datasets with sample sizes 25 and 50; 0.15 for the datasets with sample sizes 100 and 200; and 0.05 for the datasets with sample size 500.

Note that for the experiments in Sec. 6.1, the batch size is not larger than 0.2 except the extremely small datasets with 10 samples. Because using larger batch sizes introduces bias by concatenating data at different positions in a batch. For the experiments in Fig. 4a, we generate a synthetic dataset with sample size 100 and use all the 100 positions for computing Eqn. (13). We can see that choosing a proper batch size can increase the accuracy of DIVOT by increasing the number of samples in a position; however, if further increasing the batch size such that it is larger than 0.2, the accuracy is decreased because concatenating data at different positions leads to a different corresponding noise distribution compared with the ground-true $p(E_y)$. Thus, as shown in Fig. 4b, the estimation of the noise distribution becomes worse and worse with increasing the batch size. Such bias can be problematic especially in the few-sample case where we have to choose a larger batch size for computing the divergence measure. Therefore, we use a debiasing function such that we can use a larger sample size for the few-sample case without sacrificing the performance of DIVOT.

(a) The influence of batch sizes on determining causal direction and the improvement with a linear debiasing function.

(b) The influence of batch sizes on estimating $p(E_y; \theta)$ and the improvement with a linear debiasing function. The ground-truth θ is 1.

Figure 4: The influence of the batch size and the debiasing function on causal direction determination in panel (a) and density estimation in panel (b). The synthetic data (of which the sample size is 100) are generated from the linear ANM, $Y = X + E_y$, where $X \sim \mathcal{U}(-1, 1)$ and $E_y \sim \mathcal{U}(0, 1)$ are uniform distributions. In panels (a) and (b), the batch size is represented as the ratio of the sample size, e.g., 0.1 represents that the batch size is 0.1×100; the red triangular represents the experiments with only using the variance-based divergence measure; the blue star represents using the the variance-based divergence measure and a linear debiasing function. The error bar in panel (b) represents standard deviation.

B.3   DEBIASING FUNCTIONS FOR THE FEW-SAMPLE SCENARIO

Because the mentioned bias is introduced by omitting the position information, we introduce it back with a debiasing function $g_d(x)$ to reduce the bias by modifying Eqn. (13) as

$$D_{\mathrm{var}}(\mathbf{v}) \approx \frac{1}{N} \sum_{x \in \{x_i\}_N} \frac{\left\| \mathrm{sort}(\overrightarrow{y_x^{\mathtt{debais}}}) - \mathrm{sort}(\overrightarrow{e_y}) - \mathrm{ave}(\overrightarrow{y_x^{\mathtt{debais}}} - \overrightarrow{e_y}) \right\|_2^2}{N_x - 1}, \quad e_y^i \sim p(E_y; \theta),$$

$$\overrightarrow{y_x^{\mathtt{debais}}} = \overrightarrow{y_x} - g_d(x; w), \tag{15}$$

where $g_d(x; w)$ is a (non)linear function parameterized with ω, e.g., in our experiments the linear debiasing function is $g_d(x) = w \times x$. As shown in Fig. 4, using the linear debiasing function guarantees not only the accuracy while using a larger batch size than 0.2, but also the correctness of the density estimation.

For a more complicated scenario, e.g., the ANM uses a nonlinear function, one can apply a neural network to the debiasing function. We found that as a by-product, a sufficient flexible debiasing function can be used for estimating $g(x)$ of ANMs in Eqn. (3). As shown in Fig. 5, we generate synthetic 500 data of an ANM with the nonlinear function $Y = g(X) + E_y = 0.1(2.5X)^3 - 0.1X + E_y$, where $X \sim \mathcal{U}(-1, 1)$ and $E_y \sim \mathcal{U}(-0.5, 0.5)$ satisfy uniform distribution. The $g_d(x)$ is close to the ground-truth $g(x)$. Because this is not the main focus of the work, we would like to refer the readers to the Jupyter notebook in supplementary materials for the details of the implementation.

Nevertheless, the purpose of using debiasing functions is not to estimate the $g(x)$ accurately but to reduce the bias introduced by using a large batch size. This means that when we use a restrictive class of $g_d(x)$, it can lead to a noticeable difference of $g_d(x)$ and $g(x)$. But for the purpose of causal direction determination, the divergence measure does not require to specify the nonlinear functional form of ANMs. Moreover, DIVOT based on optimal transport does not require to estimate $g(x)$ either. Therefore, DIVOT can still determine causal direction correctly in such case.

(a) The debiasing function and $g(x)$ in the ANM.

(b) The samples of $(x_i, y_i^{\texttt{debias}})$.

Figure 5: As a by-product, debiasing functions can be used for estimating the nonlinear function of an ANM in Eqn (3). We optimize the parameters of a neural network representing a nonlinear debiasing function and the parameter of a uniform distribution representing the hypothesized noise distribution. As for panel (a), the ground-true noise distribution is corresponding to $\theta = 1$ and the estimated parameter $\widehat{\theta}$ is 1.066. As for panel (b), given a dataset $\{(x_i, y_i)\}$, $y_i^{\texttt{debias}} = y_i - g_d(x_i)$.

B.4 OPTIMIZATION METHODS AND THE CONVEXITY OF THE OBJECTIVE FUNCTIONS OF DIVOT

In this section, we introduce the optimization method of the experiments in Sec. 6.1 and the convexity of the objective function. Next, we introduce the optimization method of DIVOT in Sec. 6.2 of which the divergence measure uses a linear debiasing function and standard Gaussian noise.

As for the experiments in Sec. 6.1, we minimize the variance-based divergence measure in Eqn. (13) as an objective function of which the parameter is θ. Because when $\theta > 0$, the linear function $f_\theta^{\texttt{noise}}(e_y^{\texttt{source}})$ does not change the order of sorting results of $\overrightarrow{e_y^{\texttt{source}}}$, we have

$$
\begin{aligned}
&D_{\text{var}}(\mathbf{v}) \\
&\approx \frac{1}{N} \sum_{x \in \{x_i\}_N} \frac{\left\| \text{sort}(\overrightarrow{y_x}) - f_\theta^{\texttt{noise}}(\text{sort}(\overrightarrow{e_y^{\texttt{source}}})) - \text{ave}(\overrightarrow{y_x} - f_\theta^{\texttt{noise}}(\overrightarrow{e_y^{\texttt{source}}})) \right\|_2^2}{N_x - 1}, \\
&= \frac{1}{N} \sum_{x \in \{x_i\}_N} \frac{\left\| \text{sort}(\overrightarrow{y_x}) - \theta \times \text{sort}(\overrightarrow{e_y^{\texttt{source}}}) - \text{ave}(\overrightarrow{y_x} - \theta \times \overrightarrow{e_y^{\texttt{source}}}) \right\|_2^2}{N_x - 1}, \\
&f_\theta^{\texttt{noise}}(\overrightarrow{e_y^{\texttt{source}}}) = \theta \times \overrightarrow{e_y^{\texttt{source}}}, \quad \theta > 0, \quad e_y^{\texttt{source}} \sim \mathcal{U}(0,1).
\end{aligned}
\tag{16}
$$

It is obvious that the divergence measure in Eqn. (16) is convex on $\theta > 0$. The convexity is achieved by parameterizing the noise distribution with a linear function $f_{\texttt{noise}}$, and there are many exited toolboxes for solving the minimization problem.

For the experiments in Sec. 6.1, we used gradient descend for finding the optimal θ^*. The gradient `jax.grad`(loss) is computed with the `autograd` in JAX (Bradbury et al., 2018). We update θ by specifying a step size `sz` and $\theta := \theta - $ `jax.grad`(loss) $\times$ `sz`. If after the update $\theta < 0$ (which has never happened), we set the value of θ as a positive number close to zero. We used `sz` $= 1$ for all the experiments in Sec. 6.1. Moreover, because of the convexity, one can also use an one-step update method to directly get the best parameter θ^* by finding the root of the gradient function of Eqn. (16). We simply give a range of θ and find θ^* by a binary search method such that the gradient at θ^* is equal to zero. The experiments of DIVOT for ANMs in Sec. 6.2 also used the one-step update for updating θ and the range θ is specified as $[0, 100]$. In addition, we need to optimize over the parameter w of the linear debiasing function. We use gradient descent to find the best parameter, w^*. We update θ every 10 updates of w. For the PNL extension of DIVOT, we used the cyclic learning rate (Smith, 2017) with gradient descent. We update θ every 10 updates of w and

Figure 6: Robustness to prior misspecification: The performance of DIVOT with different hypothesized distributions of $p(E_y; \theta)$ on the datasets with uniform distribution noise $E_y \sim \mathcal{U}(0, 1)$.

ω in (14). The program of DIVOT is terminated when the divergence measure converges. If a more complicated scenario requires $f_\theta^{\mathtt{noise}}$ to be a nonlinear function, one may need to use the gradient descend method instead of the one-step update. We find that it is sufficient to use the standard Gaussian distribution with the linear $f_\theta^{\mathtt{noise}}$ for DIVOT to have promising results in the experiments on the Tübingen datasets, which indicates that DIVOT is robust to the choice of models. We then investigate the robustness of DIVOT to prior misspecification.

B.5   ROBUSTNESS TO PRIOR MISSPECIFICATION

We use different hypothesized noise distributions in DIVOT to test the robustness to the misspecification of noise distribution. The synthetic data are generated as in Sec. 6.1 with uniform distrbution noise $E_y \sim \mathcal{U}(0, 1)$. In DIVOT, we use one of the three hypothesized distributions: uniform distribution $\mathcal{U}(0, 1)$, beta distribution $\mathcal{B}(a = 0.5, b = 0.5)$, and standard normal distribution $\mathcal{N}(0, 1)$. As shown in Fig. 6, DIVOT with the misspecified noise distributions has similar performance with the one using the correct class of distributions, which shows the robustness of DIVOT.

B.6   COMPARISON WITH RESULTS OF BENCHMARK METHODS

We compare DIVOT with other benchmark methods, such as ANM (Hoyer et al., 2008), CAREFL (Khemakhem et al., 2021), RECI (Blöbaum et al., 2018), and LLR (Hyvärinen and Smith, 2013). As in (Khemakhem et al., 2021), the synthetic data are generated with the Laplace distribution as the noise distribution. DIVOT uses batches without debiasing functions. And the data preprocessing is the same as in Sec. 6.2. We run experiments on each dataset for 100 times. As shown in Fig. 7, for the sample size larger than 100 the accuracy of DIVOT is 100% which shows that DIVOT has promising results and performs better compared the other methods, especially in the linear case.

B.7   EFFICIENCY OF DIVOT

For common causal discovery tasks in the bivariate case, the sample size 10000 is a large and challengeable one. Causal discovery methods need to consider the efficiency of algorithms especially in the large sample size scenario. We apply DIVOT with batches and no debiasing functions to the synthetic data of which the sample size is 10000 generated with $Y = 0.1((2.5X)^3 - X) + E_y$ and $E_y \sim \mathcal{U}(0, 1)$. As shown in Table 2, we test the running time of DIVOT to determine causal direction with different number of positions and different batch sizes. The experiments are based on MacBook Pro (15-inch, 2018) with 2.9 GHz 6-Core Intel Core i9. Our implementation is based on JAX (Bradbury et al., 2018) which uses Apache License and the running time is measured with the command %timeit in JAX.

Figure 7: Comparison of the results of DIVOT (the first row) with the reported results in (Khemakhem et al., 2021) (the second row). The figures in the second row are taken from the screenshot of (Khemakhem et al., 2021). The noise (Z_2 and E_y) distribution of the synthetic data is a Laplace distribution. CAREFL represents the causal autoregressive model (Khemakhem et al., 2021); CAREFL-NS represents the causal autoregressive model without scaling; RECI represents the method, regression error causal inference (Blöbaum et al., 2018); ANM (Hoyer et al., 2008) uses Gaussian process while ANM-NN uses a neural network; linear LR is the linear likelihood ratio method (Hyvärinen and Smith, 2013).

Table 2: Running time of DIVOT on synthetic data of which the sample size is 10000. The DIVOT with batches and no debiasing function is tested with different number of positions and batch sizes.

batch size	50 positions	100 positions
0.001	240 ms ± 3.48 ms	431 ms ± 4.33 ms
0.01	7.71 s ± 475 ms	14.3 s ± 262 ms
0.1	1min 7s ± 1.81 s	2min 19s ± 2.11 s