Simple and Optimal Greedy Online Contention Resolution Schemes

Abstract

Real-world problems such as ad allocation and matching have been extensively studied under the lens of combinatorial optimization. In several applications, uncertainty in the input appears naturally and this has led to the study of online stochastic optimization models for such problems. For the offline case, these constrained combinatorial optimization problems have been extensively studied, and Contention Resolution Schemes (CRSs), introduced by Chekuri, Vondrák, and Zenklusen, have emerged in recent years as a general framework to obtaining a solution. The idea behind a CRS is to first obtain a fractional solution to a (continuous) relaxation of the objective and then round the fractional solution to an integral one. When the order of rounding is controlled by an adversary, Online Contention Resolution Schemes (OCRSs) can be used instead, and have been successfully applied in settings such as prophet inequalities and stochastic probing.

In this work, we focus on *greedy* OCRSs, which provide guarantees against the strongest possible adversary, an *almighty* adversary. Intuitively, a greedy OCRS has to make all its decisions before the online process starts. We present simple $1/e$ - selectable greedy OCRSs for the single-item setting, partition matroids and transversal matroids, which improve upon the previous state-of-the-art greedy OCRSs of [FSZ16] for these constraints. We also show that our greedy OCRSs are optimal, even for the simple single-item case.

1 Introduction

In recent years, problems in Bayesian and stochastic online optimization have attracted significant interest, especially in the field of machine learning. In this setting, we are usually asked to make decisions in an online manner, based on the information available to us so far, and our objective is to minimize our "regret", which is captured by a loss function and describes how much better we could have done if we had all the information available a priori.

In several applications, in which our decision relies also on hidden information, such as deciding whether a user will click an ad they are presented with [AAD+20, XSC+19, BSSX20, BGMS21] or whether a kidney donor is a good match for another patient [BFT13, DS15], our online decision problem naturally becomes stochastic. The inherent uncertainty of such applications makes the study of stochastic optimization all the more significant, and demonstrating algorithms with reasonable competitive ratios when one has knowledge of the underlying distributions illustrates the importance of learning distributions in AI.

One can consider a simpler setting in which our decision at each time step is a binary choice. In one such formulation, elements arrive in an online manner and we have to select a subset of them, subject to certain combinatorial constraints. For example, we might be given a matroid and want to select an independent set, or be given a graph in which the elements correspond to edges and we might want to

select a feasible matching, or each element might be associated with a size and we need to select a feasible set subject to a knapsack constraint. Famous examples of such settings are prophet inequality problems [KS77, KW12, EFGT20] and secretary problems [Dyn63], which have found application in the design of posted-price mechanisms and auctions, among others.

One approach that has seen plenty of success for these problems is to use the known distributional information to obtain a continuous relaxation of the objective. One can then solve this relaxation and get an optimal fractional solution x^*, which corresponds to the marginals of the elements under the optimal distribution. Thus, the optimal value of the relaxation constitutes an upper bound to the performance of any online (or even offline) algorithm. Afterwards, x^* is used to devise an online algorithm in order to maximize the value of the subset of elements selected. It is easy to see that this algorithm essentially corresponds to an online rounding procedure for x^*.

In this paper, we contribute provably optimal algorithms for the problem of rounding an optimal solution to a linear program in an online manner, for a range of fundamental constraints. The online nature of our rounding is well-motivated in the field of AI due to the fact that we are not able to control the arrival order of the agents. Our algorithms apply for the single-item setting, for partition matroids, as well as transversal matroids which have been used extensively to model matching markets [DRS09, CFMP, BIK07].

1.1 Online Contention Resolution Schemes

Such rounding algorithms have recently been used to obtain several optimal and interesting results [CVZ11, FSZ16, AW18, EFGT20, BZ20, RS17, CL21], and have more applications in online mechanism design and posted pricing mechanisms [CHMS10, HKS07]. General rounding algorithms for offline problems are called *Contention Resolution Schemes (CRSs)* and were introduced by Chekuri, Vondrák and Zenklusen [CVZ11] with the purpose of maximizing a submodular function. A CRS is defined with respect to a constraint family, and [CVZ11] gave the first CRSs for several interesting constraint families, including matroids, matchoids and knapsack constraints among others. For a given fractional point x^*, the main idea behind CRSs is to first obtain a random set R, drawn from the product distribution with marginals x^*, hence called the *active elements*. Since R may be infeasible with respect to the constraints, the CRS proceeds to "drop" specific elements from R and obtain a new, feasible, set $R' \subseteq R$.

While the general applicability of the CRS approach is remarkable, they are unfortunately not useful for Bayesian and stochastic online optimization problems. In particular, one can utilize CRSs when they have the ability to choose the order in which they obtain information about the underlying ground set of elements, as CRSs round a fractional point x^* in a particular order to obtain a feasible solution.

To overcome the inherently offline nature of CRSs, Feldman, Svensson and Zenklusen [FSZ16] introduced the notion of *Online Contention Resolution Schemes (OCRSs)*, applicable in a variety of online settings in Bayesian and stochastic online optimization, such as prophet inequalities [LS18, RS17, CL21], stochastic probing [ASW16, GN13, GNS16, GNS17], and posted pricing mechanisms [HKS07]. Surprisingly, OCRSs yield constant-factor competitive ratios for several interesting feasibility constraints.

All of the results presented in [FSZ16] are based on a special subclass of OCRSs called *greedy OCRSs*. Intuitively, a greedy OCRS fixes a downward-closed subfamily of feasible sets $\mathcal{F}$ before the online process starts. During the online process, the greedy OCRS maintains a subset S of the elements which is feasible in $\mathcal{F}$, and then greedily accepts any active element i if $S \cup \{i\}$ is also feasible in $\mathcal{F}$, i.e. if i does not violate feasibility, with respect to $\mathcal{F}$, of the set maintained by the greedy OCRS. One can easily see that the final set at the end of the online process is feasible by construction.

Even though most OCRSs defined in past literature have been greedy, their best-known performance guarantees are suboptimal with respect to (non-greedy) OCRSs. We analyze the performance of greedy OCRSs and provide the first provably optimal greedy OCRS for the single-item setting, partition matroids and transversal matroids.

1.2 Our contributions

We have four main contributions:

- We design a $1/e$-selectable greedy OCRS for the single-item setting (Theorem 1.1).
- We show that our greedy OCRS extends naturally to partition matroids[1] (Corollary 1.2).
- We proceed to show that no greedy OCRS can be $(1/e + \varepsilon)$-selectable, for any $\varepsilon > 0$, even for the single item setting. This, combined with our first contribution, shows that our $1/e$-selectable greedy OCRS is the best possible (Theorem 1.3).
- We extend our greedy OCRS to transversal matroids[2] as well, and show that the selectability can be increased to $1 - 1/e$ for special cases of transversal matroids (Theorem 1.4).

Our results improve upon the $1/4$-selectable OCRSs of [FSZ16] for all the constraints discussed here.

As a corollary, our work presents the first instance of a dichotomy between the best possible guarantees by greedy OCRSs and (non-greedy) OCRSs, since a $1/2$ (non-greedy) OCRS is known for the single-item setting [Ala14].

We proceed with our four main results. The proof of the following theorem is found in Section 3.

Theorem 1.1. *There exists a $1/e$-selectable (randomized) greedy OCRS for the single-item setting.*

Next, we extend the single-item greedy OCRS to a partition matroid constraint, by decomposing the partition matroid into single-item instances, running the greedy OCRS above and accepting an active element if and only if it is independent in the corresponding single-item instance of the decomposition.

Corollary 1.2. *There exists a $1/e$-selectable (randomized) greedy OCRS for partition matroids.*

We complement the results above by also showing that it is tight. The proof of the following theorem can be found in Section 4.

Theorem 1.3. *For every $\varepsilon > 0$, there exists no greedy OCRS for the single-item setting that selects an active element i with probability at least $1/e + \varepsilon$ for all $i \in \mathcal{N}$.*

Finally, we extend Theorem 1.1 to a more general class of matroids, transversal matroids, and strengthen it for the special case in which every element's neighborhood has size at least 3. The proof of the following theorem is found in Section 5.

Theorem 1.4. *Let $\mathcal{M} = (U, \mathcal{I})$ be a transversal matroid represented by a bipartite graph $G = (U \cup V, E)$. Then, there exists a $1/e$-selectable (randomized) greedy OCRS π for $\mathcal{M}$. Furthermore, if for every element $u \in U$ we have $|N(u)| \geq 3$, where $N(u)$ is the set of neighbours of u in G, then π is a $(1 - 1/e)$-selectable (randomized) greedy OCRS for $\mathcal{M}$.*

1.3 Related work

Since their introduction [CVZ11], Contention Resolution Schemes (CRSs) have found several applications. Applications of CRSs in Bayesian mechanism design and posted price mechanisms [CHMS10] can be found in [CVZ11]. Later, Yan [Yan11] connected mechanism design with the notion of correlation gap [ADSY12]. OCRSs were developed [FSZ16] with applications to Bayesian mechanism design as one of the main motivations as they directly translate to competitive ratios for the prophet inequality problem [FSZ16, Rub16, RS17, CL21]. In fact, Alaei's work on uniform matroids [Ala14] precedes [FSZ16] and can be seen as an OCRS, even though it is formulated differently. Random order CRSs (ROCRSs) were introduced in [AW18] and yield improved bounds when the arrival order is random.

As stated previously, Feldman, Svensson and Zenklusen [FSZ16] gave the first greedy OCRS for matroids, which is $1/4$-selectable. Lee and Singla [LS18] showed a reverse connection between OCRSs and prophet inequalities, obtaining a $1/2$-selectable (non-greedy) OCRS for matroids and a $(1 - 1/e)$-selectable ROCRS for the single item setting. Adamczyk and Wlodarczyk [AW18] obtained several results, including a $1/k+1$-selectable ROCRS for the intersection of k matroids. For matchings, Ezra et al [EFGT20] designed a 0.337-selectable OCRS for bipartite graphs, while Bruggmann and Zenklusen [BZ20] developed optimal monotone CRSs via a novel polyhedral approach.

---

[1]A partition matroid consists of a partition of the elements into disjoint sets $A_1, \ldots, A_k$ such that a subset of the elements S is independent if and only if $|S \cap A_j| \leq 1$ for every $1 \leq j \leq k$.

[2]A transversal matroid consists of a bipartite graph $G = (A \cup B, E)$, in which the set of elements is A and a set $S \subseteq A$ is independent if and only if there exists a matching in G that covers S.

This work is connected to stochastic optimization, online algorithms, mechanism design and sub-modular optimization, all of which have extensive literature. There have been several surveys on the topic [Gup17, Luc17, CFH+19, Din13, HK92], as well as a survey on random-order models in general [GS20]. Singla's thesis [Sin18] has connections to several of the topics discussed here. On the application side, prophet inequality and secretary problems have received significant attention in the last years, due to their connections with Bayesian mechanism design and posted price mechanisms [GM66, HK82, Ker86, Dyn63, KS77, KW12, ACK17, CFH+17, CSZ20, AEE+17, EHLM15, HKS07, EHKS18, FZ18], while ROCRSs have found several applications to *stochastic probing* [ASW16, GN13, GNS16, GNS17, BSZ19, AN16]. Recently, Dughmi [Dug20, Dug21] showed the equivalence between the existence of constant-factor *universal* OCRSs and a constant-factor approximation to the famous matroid secretary problem [BIKK18].

Independently, [FLT+21] study the problem of designing an *oblivious* OCRS [3] for the same setting and obtain a similar result, showing that there exists a $1/e$-selectable oblivious OCRS and no oblivious OCRS can be $(1/e + \varepsilon)$-selectable for any $\varepsilon > 0$. We note that the two results (and schemes) are very different. In fact, their OCRS is not greedy, while ours is not oblivious. Whether one can achieve similar guarantees with greedy and oblivious OCRSs for more general settings is an interesting open problem.

1.4 Roadmap

We begin in Section 2 with some background. Then, in Section 3, we present our first main result, the $1/e$-selectable greedy OCRS for the single-item setting and partition matroids. Then, in Section 4, we show that our greedy OCRS is optimal. We proceed with our greedy OCRS for transversal matroids in Section 5, which also achieves the optimal $1/e$ selectability and show it performs even better under mild assumptions on the structure of the transversal matroid. Finally, we present our experimental results in Section 6, demonstrating how our schemes outperform the best previously known schemes for randomly generated as well as specific worst-case instances. All omitted proofs can be found in the Appendix which, along the code used for the experiments, is provided in the supplementary material.

2 Preliminaries

Before we proceed, we present the formal definitions of CRSs, OCRSs and greedy OCRSs and briefly describe a $1/4$-selectable single item OCRS by [FSZ16].

Let $\mathcal{N}$ be a finite ground set. A constraint family over $\mathcal{N}$ is a subset $\mathcal{I} \subseteq 2^{\mathcal{N}}$; a set $S \in \mathcal{I}$ is called feasible, while a set $S \notin \mathcal{I}$ is called infeasible. We say $\mathcal{P} \subseteq [0,1]^{\mathcal{N}}$ is a polyhedral relaxation of $(\mathcal{N}, \mathcal{I})$ if $\mathcal{P}$ is a polyhedron and $\mathbb{1}_S \in \mathcal{P}$ for all $S \in \mathcal{I}$ (here $\mathbb{1}_S$ is the characteristic vector of S).

Given a polyhedral relaxation $\mathcal{P}$ of a constraint $(\mathcal{N}, \mathcal{I})$ and a point $x \in \mathcal{P}$, a natural question is whether we can round x in order to obtain a feasible set $S \in \mathcal{I}$. One way to achieve this is via Contention Resolution Schemes, which we define below.

Definition 2.1 (Contention Resolution Scheme [CVZ11])**.** Let $b, c \in [0,1]$. A (b,c)-balanced *Contention Resolution Scheme* π for $\mathcal{P}_{\mathcal{I}}$ is a procedure that for every $x \in b \cdot \mathcal{P}_{\mathcal{I}}$ and $A \subseteq \mathcal{N}$, returns a random set $\pi_x(A) \subseteq A \cap \text{support}(x)$ and satisfies the following properties:

    1. $\pi_x(A) \in \mathcal{I}$ with probability 1, $\quad \forall A \subseteq \mathcal{N}, x \in b \cdot \mathcal{P}_{\mathcal{I}}$, and

    2. for all $i \in \text{support}(x)$, $\Pr\left[i \in \pi_x(R(x)) \mid i \in R(x)\right] \geq c, \quad \forall x \in b \cdot \mathcal{P}_{\mathcal{I}}$.

The scheme is said to be *monotone* if $\Pr\left[i \in \pi_x(A_1)\right] \geq \Pr\left[i \in \pi_x(A_2)\right]$ whenever $i \in A_1 \subseteq A_2$.

CRSs are offline rounding schemes. In the case where the arrival order of the elements is selected by an adversary, we can use the following notion of *Online Contention Resolution Schemes (OCRS)* to round x.

---

[3]An CRS (or OCRS) is called oblivious if and only if it does not make use of the fractional point x, i.e. if for every $S \subseteq \mathcal{N}$, the distribution of $\pi_x(S)$ and the distribution of $\pi_y(S)$ are identical for any two fractional points $x, y \in \mathcal{P}_{\mathcal{F}}$.

Definition 2.2 (Online Contention Resolution Scheme (OCRS) [FSZ16]). For an online selection setting where a point $x \in \mathcal{P}$ is given, we draw a random subset of the elements $R(x)$, which we call the *active* elements. Afterwards, we observe whether the element $e \in \mathcal{N}$ are active ($e \in R(x)$), one by one, and have to immediately and irrevocably decide whether to select an element or not before the next element is revealed. An *Online Contention Resolution Scheme* for $\mathcal{P}$ is an online algorithm which selects a subset $I \subseteq R(x)$ such that $\mathbb{1}_I \in \mathcal{P}$.

A scheme is called a *Random Order Contention Resolution Schemes (ROCRS)* if, instead of being chosen by an adversary, the arrival order of the elements is chosen uniformly at random. Adamczyk and Wlodarczyk present several interesting results on ROCRSs in [AW18]. In the case of adversarial arrival order, however, one can distinguish between three different adversaries in terms of the information they have at their disposal. An *offline adversary*, which is the weakest of the three, has to fix an ordering of the elements before any of the elements are revealed. An *almighty adversary*, the most powerful one, has access to the realizations of all random events; both the set of active elements and any potential random bits the algorithm may use. Therefore, an almighty adversary can predict the algorithm's behaviour and choose a truly worst-case ordering of the elements for the particular algorithm. In between the two extremes is the *online adversary*. An online adversary's choices can only depend on the realizations of the elements that have appeared so far. In other words, the adversary has, at any step, exactly the same information as the algorithm, and their decision as to which element to reveal at step i can only depend on the realizations of the elements revealed in steps 1 through $i - 1$.

We also define the notion of a *greedy* OCRS, which provide guarantees with respect to an almighty adversary.

Definition 2.3 (Greedy OCRS [FSZ16]). Let $\mathcal{P} \subseteq [0, 1]^n$ be a relaxation of the feasible sets $\mathcal{F} \subseteq 2^{\mathcal{N}}$. An OCRS π for $\mathcal{P}$ is called a *greedy OCRS* if, for any $x \in \mathcal{P}$, π defines a down-closed subfamily of feasible sets $\mathcal{F}_{\pi,x} \subseteq \mathcal{F}$, and it selects an active element e when it arrives if, together with the set of elements already selected, the resulting set is in $\mathcal{F}_{\pi,x}$. We say that π is a randomized greedy OCRS if, given x, the choice of $\mathcal{F}_{\pi,x}$ is randomized. Otherwise, we say that π is a deterministic greedy OCRS.

Intuitively, we say a greedy OCRS is c-selectable if and only if an active element $e \in R(x)$ can be included in the currently selected elements $I \subseteq R(x)$ and maintain feasibility with probability at least c.

Definition 2.4 (c-selectability). Let $c \in [0, 1]$. A greedy OCRS for $\mathcal{P}$ is c-selectable if and only if for any $x \in P$ we have

$$\Pr\left[I \cup \{e\} \in \mathcal{F}_x \forall I \subseteq R(x), I \in \mathcal{F}_x\right] \geq c \qquad \forall e \in \mathcal{N}.$$

Notice that a c-selectable greedy OCRS guarantees that each active element e is selected with probability at least c, even against the almighty adversary. We should note that the randomness in the above definition is with respect to both the randomness of $R(x)$ and also any potential randomness the greedy OCRS might use to decide upon $\mathcal{F}_x$.

Next, we briefly describe the $1/4$-selectable single item greedy OCRS by [FSZ16]. Given a fractional point x such that $\sum_{i=1}^n x_i \leq 1$, the greedy OCRS will, at step i, observe whether element i is active or not. If it is active, the greedy OCRS will choose to select with probability $1/2$ or discard it and move on to the next element. Since each element is active with probability x_i and is selected with probability $x_i/2$, the expected number of selected elements is at most half, and thus, by Markov's inequality, the probability the greedy OCRS selects no elements is at least $1/2$. Therefore, for every element i, we reach i without having selected an element with probability at least $1/2$ and we select i, given that it is active, with probability $1/2$, for an overall selectability of $1/4$.

We should note that for the single item setting there exists a $1/2$-selectable OCRS [Ala14] but, crucially, it is not greedy. In fact, we show in the Section 4 that there is no $1/2$-selectable greedy OCRS for the single item setting.

3 An $1/e$-selectable greedy OCRS for the single-item setting

This section is dedicated to proving Theorem 1.1. Before we begin, we need the following lemma.

Lemma 3.1. *Let $a_1, \ldots, a_k \in [0, 1]$. Then*

$$\ln\left(1 - \frac{a_k}{2}\right) + \sum_{j=1}^{k-1} \ln\left(1 - a_j + \frac{a_j^2}{2}\right) \geq -a_k - \sum_{j=1}^{k-1} a_j$$

Next, consider a ground set $\mathcal{N} = \{e_1, e_2, \ldots, e_n\}$, and let $\mathcal{M} = (\mathcal{N}, \mathcal{I})$ be the uniform matroid of rank 1 with respect to $\mathcal{N}$, i.e. $\mathcal{I} = \{\{e_i\} \mid e_i \in \mathcal{N}\}$. Let $\mathcal{P}$ be the following polyhedral relaxation of $\mathcal{M}$:

$$\mathcal{P} = \left\{ x \in [0, 1]^n \;\middle|\; \sum_{i=1}^{n} x_i \leq 1 \right\}$$

For a given $x \in \mathcal{P}$, let $\pi = \pi_x$ denote the OCRS we will create. π will draw a random set R where each element e_i appears in R independently with some probability q_i. The family of feasible subsets is

$$\mathcal{F}_{\pi,x} = \{\{e_i\} \mid e_i \in R\}.$$

We set $q_i = 1 - x_i/2$ for all $e_i \in \mathcal{N}$. Afterwards, π selects the first element e_i that is active and that $\{e_i\} \in \mathcal{F}$.

Lemma 3.2. *π is a randomized greedy OCRS.*

Next, we quantify the probability that each element is selected by π, given that it is active.

Lemma 3.3. *π selects every element $e_i \in \mathcal{N}$, given that it is active, with probability at least $1/e$.*

Proof. We relabel the elements of $\mathcal{N}$ so that each e_i arrives in the i-th step. Consider an element $e_i \in \mathcal{N}$. Given that e_i is active, since π is a greedy OCRS, π will select e_i if and only if it has not selected any elements before e_i and also $\{e_i\} \in \mathcal{F}_{\pi,x}$. Recall that we have $\{e_i\} \in \mathcal{F}_{\pi,x}$ with probability exactly $q_i = 1 - x_i/2$. Furthermore, for every element e_j where $j < i$, it needs to be the case that we avoid having both $\{e_j\} \in \mathcal{F}_{\pi,x}$ and also e_j coming up active. This happens with probability $1 - x_j \cdot (1 - x_i/2) = 1 - x_j + x_j^2/2$ for every e_j where $j < i$. Overall, if we denote by r_i the probability that e_i is selected by π, given that it is active, we have

$$\ln r_i = \ln\left(\left(1 - \frac{x_i}{2}\right) \cdot \prod_{j=1}^{i-1}\left(1 - x_j + \frac{x_j^2}{2}\right)\right) = \ln\left(1 - \frac{x_i}{2}\right) + \sum_{j=1}^{i-1} \ln\left(1 - x_j + \frac{x_j^2}{2}\right)$$

$$\geq -x_i - \sum_{j=1}^{i-1} x_j \geq -1,$$

where the first inequality follows from Lemma 3.1 and the second inequality follows from $\sum_i x_i \leq 1$. Therefore $r_i \geq 1/e$, for all $i \in \mathcal{N}$. $\qquad\square$

From Lemmas 3.2 and 3.3, it follows that π is a $1/e$-selectable (randomized) greedy OCRS for $\mathcal{P}$.

Remark 3.4. In a personal communication, Jan Vondrák devised an alternate scheme for the problem, after we notified him of our scheme. With his consent [Von], we have included this alternate scheme in the Appendix, which can be found in the supplementary material.

4 $1/e$ **is tight**

In this section, we present the proof of Theorem 1.3. Consider the instance where $x_i = 1/n$ for all $e_i \in \mathcal{N}$, where $n = |\mathcal{N}|$, and let A denote the set of active elements. Any greedy OCRS π will select a subset S of $\mathcal{F} = \{e_i \mid e_i \in \mathcal{N}\}$ with some probability α_S, and then accept the first element in S that comes up active. What is the worst-case probability that an element from S will be selected? This is minimized for the element in S which is last in the arrival order, which has a probability of being selected exactly equal to $(1 - 1/n)^{|S|-1}$, because the OCRS is greedy, and it would select an element from S which arrived earlier, if it came up active. Therefore, no greedy OCRS cannot

guarantee, for any $S \subseteq \mathcal{F}$, that an element $e \in \mathcal{N}$ will be selected, when $e \in A$, with probability greater than $(1 - 1/n)^{|S|-1}$. Thus, for any $e \in \mathcal{N}$ and any greedy OCRS π, we have

$$\Pr\left[e \in \pi(A) \mid e \in A\right] \leq \sum_{\substack{S \subseteq \mathcal{N} \\ e \in S}} \alpha_S \left(1 - \frac{1}{n}\right)^{|S|-1}$$

$$= \sum_{k=1}^{n} \left(1 - \frac{1}{n}\right)^{k-1} \sum_{\substack{S \subseteq \mathcal{N} \,:\, |S|=k \\ e \in S}} \alpha_S. \tag{1}$$

Next, for a greedy OCRS π to be c-selectable, it needs to guarantee that

$\min_{e \in \mathcal{N}} \Pr\left[e \in \pi(A) \mid e \in A\right] \geq c$. Therefore, if we show that

$$\min_{e \in \mathcal{N}} \left\{ \sum_{k=1}^{n} \left(1 - \frac{1}{n}\right)^{k-1} \sum_{\substack{S \subseteq \mathcal{N} \,:\, |S|=k \\ e \in S}} \alpha_S \right\} \leq c,$$

by (1) it follows that π cannot be $(c + \varepsilon)$-selectable for any $\varepsilon > 0$.

Lemma 4.1.

$$\min_{e \in \mathcal{N}} \left\{ \sum_{k=1}^{n} \left(1 - \frac{1}{n}\right)^{k-1} \sum_{\substack{S \subseteq \mathcal{N} \,:\, |S|=k \\ e \in S}} \alpha_S \right\} \leq \left(1 - \frac{1}{n}\right)^{n-1}.$$

By Lemma 4.1, since $\lim_{n \to \infty} (1 - 1/n)^{n-1} = 1/e$, it follows that there exists no greedy OCRS for $\mathcal{P}$ that selects an element e, when active, with probability at least $1/e + \varepsilon$ for all $e \in \mathcal{N}$.

5 Extension to Transversal Matroids

In this section, we prove Theorem 1.4. Let $\mathcal{M} = (U, \mathcal{I})$ be a transversal matroid and $G = (U \cup V, E)$ denote the underlying bipartite graph, where $|U| = n$. We know that a subset $S \subseteq U$ is independent if and only if there exists a matching in G that covers S. Let $\mathcal{P}$ be the natural polyhedral relaxation of $\mathcal{M}$. For a given $x \in \mathcal{P}$, let $\pi = \pi_x$ be the greedy OCRS we will create. For each $v \in V$, π will draw a random set R_v, in which each element $u \in U$ appears with probability q_u. For every $u \in U$, let $N(u)$ denote the set of neighbors of u in G. Then, we set

$$q_u = 1 - \left(1 - \frac{1 - e^{-x_u}}{x_u}\right)^{\frac{1}{|N(u)|}}.$$

It is easy to see that $q_u \in [0, 1]$ for every $|N(u)| \geq 1$, and thus q_u is well-defined.

Next, we create a down-closed subfamily of feasible sets by taking all possible combinations of sets created by taking at most one element from each R_v and then taking the union of all such elements. Specifically,

$$\mathcal{F}_{\pi,x} = \left\{ S = \{u_1, \ldots, u_k\} \subseteq U \,\big|\, \exists T = \{v_1, \ldots, v_k\} \subseteq V \text{ s.t. } u_j \in R_{v_j}, \ \forall j \in \{1, \ldots, k\} \right\}.$$

Any set S in $\mathcal{F}$ is clearly an independent set of $\mathcal{M}$, as the constraints guarantee that there always exists a matching in G that covers S. During the online process, π starts with a set of selected elements $S = \emptyset$, and greedily selects an active element u if $S + u \in \mathcal{F}$.

The proof of the following lemma is identical to the proof of Lemma 3.2 and follows from the discussion above.

Lemma 5.1. π is a randomized greedy OCRS.

Next, we again lower bound the selection probability of an active element.

Lemma 5.2. π *selects every element* $u \in U$, *given that it is active, with probability at least* $1/e$. *Furthermore, if* $|N(u)| \geq 3$ *for all* $u \in U$, π *selects every element* $u \in U$, *given that it is active, with probability at least* $1 - 1/e$.

We conclude that π is a $1/e$-selectable greedy OCRS for $\mathcal{M}$ and that if $|N(u)| \geq 3$ for every $u \in U$, π is a $(1 - 1/e)$-selectable greedy OCRS for $\mathcal{M}$.

6 Experimental Results

In this section, we present our experimental results which give a quantitative view into how our greedy OCRSs outperform the former state-of-the-art greedy OCRSs by [FSZ16]. For the constraint system, we consider both the single-item setting as well as randomly-generated transversal matroid constraints. The code used to run these experiments can be found in the supplementary material.

For our experiments, we have the following parameters:

- N: The number of elements. For the single item setting, this varies from 10 to 100. For the transversal matroid constraint, this is set to 50.

- ITERATIONS: For a fixed x, the number of times we simulate the realization of the elements. This is used to approximate the selectability of each element within a reasonable estimate and is set to $200,000$.

- REPETITIONS: The number of times we run the entire experiment from scratch. This has no effect on the uniform instance of the single-item setting or the transversal matroid constraint, but affects the random vector x in the randomly-generated instance of the single-item setting, and is set to 10.

We focus on two metrics: the *minimum selectability* and the *average selectability* of each element. For a fixed x, the minimum (resp. average) selectability records the minimum (resp. average) over all elements of the fraction of the times an element was selected by our greedy OCRS over the number of times it was active. While the average gives an idea of what selectability to expect for most elements, the minimum selectability provides a worst-case estimate.

For both types of constraints, we can see that our greedy OCRSs outperform the $1/4$-selectable single-item greedy OCRS by [FSZ16] in the minimum selectability metric and performs substantially better in the average selectability metric.

6.1 Single-Item Setting

We consider two different types of instances for the single-item setting: the *uniform instance*, where $x_i = 1/n$ for every element $i \in N$, as well as a *randomly-generated instance*, in which x is a random vector of length n with the constraint that $\sum_i x_i = 1$.

Figure 1: N = 5 to 100, ITERATIONS = $10,000$, REPETITIONS = 10

6.2 Transversal Matroid

For the transversal matroid constraint, we again consider two different types of instances: a transversal matroid with $|V| = 2$, $|N(u)| = 2$ and $x_u = 2/n$ for all vertices $u \in U$ as well as a transversal matroid with $|V| = 3$, $|N(u)| = 3$ and $x_u = 3/n$ for all vertices $u \in U$.

While there are many options for the choice of what transversal matroid to pick, we selected these "uniform" instances of transversal matroids to illustrate how the selectability changes as $|N(u)|$ increases. Since a transversal matroid with $|V| = 1$, $|N(u)| = 1$ and $x_u = 1/n$ for all vertices $u \in U$ is equivalent to a uniform instance of the single-item setting, we do not consider it explicitly, but we plot it together with the previous two instances.

Figure 2: N = 50, ITERATIONS = 200, 000

References

[AAD+20] Saba Ahmadi, Faez Ahmed, John P. Dickerson, Mark Fuge, and Samir Khuller. An algorithm for multi-attribute diverse matching. In Christian Bessiere, editor, *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20*, pages 3–9. International Joint Conferences on Artificial Intelligence Organization, 7 2020. Main track.

[ACK17] Yossi Azar, Ashish Chiplunkar, and Haim Kaplan. Prophet secretary: Surpassing the 1-1/e barrier. *CoRR*, abs/1711.01834, 2017.

[ADSY12] Shipra Agrawal, Yichuan Ding, Amin Saberi, and Yinyu Ye. Price of correlations in stochastic optimization. *Operations Research*, 60(1):150–162, 2012. Preliminary version in Proc. of ACM-SIAM SODA 2010.

[AEE+17] Melika Abolhassani, Soheil Ehsani, Hossein Esfandiari, MohammadTaghi Hajiaghayi, Robert Kleinberg, and Brendan Lucier. Beating 1-1/e for ordered prophets. *CoRR*, abs/1704.05836, 2017.

[Ala14] Saeed Alaei. Bayesian combinatorial auctions: Expanding single buyer mechanisms to many buyers. *SIAM Journal on Computing*, 43(2):930–972, 2014.

[AN16] Arash Asadpour and Hamid Nazerzadeh. Maximizing stochastic monotone submodular functions. *Management Science*, 62(8):2374–2391, 2016.

[ASW16] Marek Adamczyk, Maxim Sviridenko, and Justin Ward. Submodular stochastic probing on matroids. *Mathematics of Operations Research*, 41(3):1022–1038, 2016.

[AW18] Marek Adamczyk and Michal Wlodarczyk. Random order contention resolution schemes. In *59th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2018, Paris, France, October 7-9, 2018*, pages 790–801, 2018.

[BFT13] Dimitris Bertsimas, Vivek F. Farias, and Nikolaos Trichakis. Fairness, efficiency, and flexibility in organ allocation for kidney transplantation. *Operations Research*, 61(1):73–87, 2013.

[BGMS21] Brian Brubach, Nathaniel Grammel, Will Ma, and Aravind Srinivasan. Improved guarantees for offline stochastic matching via new ordered contention resolution schemes. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[BIK07] Moshe Babaioff, Nicole Immorlica, and Robert Kleinberg. Matroids, secretary problems, and online mechanisms. In *Proceedings of the Eighteenth Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '07, page 434–443, USA, 2007. Society for Industrial and Applied Mathematics.

[BIKK18] Moshe Babaioff, Nicole Immorlica, David Kempe, and Robert Kleinberg. Matroid secretary problems. *J. ACM*, 65(6), nov 2018.

[BSSX20] Brian Brubach, Karthik A. Sankararaman, Aravind Srinivasan, and Pan Xu. Attenuate locally, win globally: Attenuation-based frameworks for online stochastic matching with timeouts. *Algorithmica*, 82(1):64–87, Jan 2020.

[BSZ19] Domagoj Bradac, Sahil Singla, and Goran Zuzic. (Near) Optimal Adaptivity Gaps for Stochastic Multi-Value Probing. In Dimitris Achlioptas and László A. Végh, editors, *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques (APPROX/RANDOM 2019)*, volume 145 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 49:1–49:21, Dagstuhl, Germany, 2019. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.

[BZ20] Simon Bruggmann and Rico Zenklusen. An optimal monotone contention resolution scheme for bipartite matchings via a polyhedral viewpoint. *Mathematical Programming*, Oct 2020.

[CFH+17] José Correa, Patricio Foncea, Ruben Hoeksma, Tim Oosterwijk, and Tjark Vredeveld. Posted price mechanisms for a random stream of customers. In *Proceedings of the 2017 ACM Conference on Economics and Computation*, EC '17, pages 169–186, New York, NY, USA, 2017. ACM.

[CFH+19] José Correa, Patricio Foncea, Ruben Hoeksma, Tim Oosterwijk, and Tjark Vredeveld. Recent developments in prophet inequalities. *ACM SIGecom Exchanges*, 17(1):61–70, 2019.

[CFMP] Florin Constantin, Jon Feldman, S. Muthukrishnan, and Martin Pál. *An Online Mechanism for Ad Slot Reservations with Cancellations*, pages 1265–1274.

[CHMS10] Shuchi Chawla, Jason D Hartline, David L Malec, and Balasubramanian Sivan. Multi-parameter mechanism design and sequential posted pricing. In *Proceedings of the forty-second ACM symposium on Theory of computing*, pages 311–320, 2010.

[CL21] Chandra Chekuri and Vasilis Livanos. On submodular prophet inequalities and correlation gap. In Ioannis Caragiannis and Kristoffer Arnsfelt Hansen, editors, *Algorithmic Game Theory - 14th International Symposium, SAGT 2021, Aarhus, Denmark, September 21-24, 2021, Proceedings*, volume 12885 of *Lecture Notes in Computer Science*, page 410. Springer, 2021.

[CSZ20] Jose Correa, Raimundo Saona, and Bruno Ziliotto. Prophet secretary through blind strategies. *Mathematical Programming*, 08 2020.

[CVZ11] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Submodular function maximization via the multilinear relaxation and contention resolution schemes. In *Proceedings of the Forty-third Annual ACM Symposium on Theory of Computing*, STOC '11, pages 783–792, New York, NY, USA, 2011. ACM.

[Din13] Michael Dinitz. Recent advances on the matroid secretary problem. *ACM SIGACT News*, 44(2):126–142, 2013.

[DRS09] Shaddin Dughmi, Tim Roughgarden, and Mukund Sundararajan. Revenue submodularity. In *Proceedings of the 10th ACM Conference on Electronic Commerce*, EC '09, page 243–252, New York, NY, USA, 2009. Association for Computing Machinery.

[DS15] John Dickerson and Tuomas Sandholm. Futurematch: Combining human value judgments and machine learning to match in dynamic environments. *Proceedings of the AAAI Conference on Artificial Intelligence*, 29(1), Feb. 2015.

[Dug20] Shaddin Dughmi. The outer limits of contention resolution on matroids and connections to the secretary problem. In Artur Czumaj, Anuj Dawar, and Emanuela Merelli, editors, *47th International Colloquium on Automata, Languages, and Programming, ICALP 2020, July 8-11, 2020, Saarbrücken, Germany (Virtual Conference)*, volume 168 of *LIPIcs*, pages 42:1–42:18. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020.

[Dug21] Shaddin Dughmi. Matroid secretary is equivalent to contention resolution. *CoRR*, abs/2103.04205, 2021.

[Dyn63] E. B. Dynkin. The optimum choice of the instant for stopping a Markov process. *Soviet Math. Dokl*, 4, 1963.

[EFGT20] Tomer Ezra, Michal Feldman, Nick Gravin, and Zhihao Gavin Tang. Online stochastic max-weight matching: Prophet inequality for vertex and edge arrival models. In *Proceedings of the 21st ACM Conference on Economics and Computation*, EC '20, page 769–787, New York, NY, USA, 2020. Association for Computing Machinery.

[EHKS18] Soheil Ehsani, MohammadTaghi Hajiaghayi, Thomas Kesselheim, and Sahil Singla. Prophet secretary for combinatorial auctions and matroids. In *Proceedings of the Twenty-Ninth Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '18, page 700–714, USA, 2018. Society for Industrial and Applied Mathematics.

[EHLM15] Hossein Esfandiari, MohammadTaghi Hajiaghayi, Vahid Liaghat, and Morteza Monemizadeh. Prophet secretary. *CoRR*, abs/1507.01155, 2015.

[FLT+21] Hu Fu, Pinyan Lu, Zhihao Gavin Tang, Abner Turkieltaub, Hongxun Wu, Jinzhao Wu, and Qianfan Zhang. Oblivious online contention resolution schemes, 2021.

[FSZ16] Moran Feldman, Ola Svensson, and Rico Zenklusen. Online contention resolution schemes. In *Proceedings of the Twenty-seventh Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '16, pages 1014–1033, Philadelphia, PA, USA, 2016. Society for Industrial and Applied Mathematics.

[FZ18] Moran Feldman and Rico Zenklusen. The submodular secretary problem goes linear. *SIAM Journal on Computing*, 47(2):330–366, 2018.

[GM66] John P. Gilbert and Frederick Mosteller. Recognizing the maximum of a sequence. *Journal of the American Statistical Association*, 61(313):35–73, 1966.

[GN13] Anupam Gupta and Viswanath Nagarajan. A stochastic probing problem with applications. In Michel Goemans and José Correa, editors, *Integer Programming and Combinatorial Optimization*, pages 205–216, Berlin, Heidelberg, 2013. Springer Berlin Heidelberg.

[GNS16] Anupam Gupta, Viswanath Nagarajan, and Sahil Singla. Algorithms and adaptivity gaps for stochastic probing. In Robert Krauthgamer, editor, *Proceedings of the Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2016, Arlington, VA, USA, January 10-12, 2016*, pages 1731–1747. SIAM, 2016.

[GNS17] Anupam Gupta, Viswanath Nagarajan, and Sahil Singla. Adaptivity gaps for stochastic probing: Submodular and XOS functions. In Philip N. Klein, editor, *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2017, Barcelona, Spain, Hotel Porta Fira, January 16-19*, pages 1688–1702. SIAM, 2017.

[GS20] Anupam Gupta and Sahil Singla. Random-order models, 2020. `https://arxiv.org/abs/2002.12159`.

[Gup17] Anupam Gupta. Prophets and secretaries, June 2017.

[HK82] T. P. Hill and Robert P. Kertz. Comparisons of stop rule and supremum expectations of i.i.d. random variables. *Ann. Probab.*, 10(2):336–345, 05 1982.

[HK92] Theodore P Hill and Robert P Kertz. A survey of prophet inequalities in optimal stopping theory. *Contemp. Math*, 125:191–207, 1992.

[HKS07] Mohammad Taghi Hajiaghayi, Robert Kleinberg, and Tuomas Sandholm. Automated online mechanism design and prophet inequalities. In *Proceedings of the 22Nd National Conference on Artificial Intelligence - Volume 1*, AAAI'07, pages 58–65. AAAI Press, 2007.

[Ker86] Robert P Kertz. Stop rule and supremum expectations of i.i.d. random variables: A complete comparison by conjugate duality. *Journal of Multivariate Analysis*, 19(1):88 – 112, 1986.

[KS77] Ulrich Krengel and Louis Sucheston. Semiamarts and finite values. *Bull. Amer. Math. Soc.*, 83(4):745–747, 07 1977.

[KW12] Robert Kleinberg and Seth Matthew Weinberg. Matroid prophet inequalities. In *Proceedings of the forty-fourth annual ACM symposium on Theory of computing*, pages 123–136, 2012.

[LS18] Euiwoong Lee and Sahil Singla. Optimal online contention resolution schemes via ex-ante prophet inequalities. In Hannah Bast, Grzegorz Herman, and Yossi Azar, editors, *26th European Symposium on Algorithms, ESA 2018*, Leibniz International Proceedings in Informatics, LIPIcs, Germany, August 2018. Schloss Dagstuhl- Leibniz-Zentrum fur Informatik GmbH, Dagstuhl Publishing.

[Luc17] Brendan Lucier. An economic view of prophet inequalities. *SIGecom Exch.*, 16(1):24–47, September 2017.

[RS17] Aviad Rubinstein and Sahil Singla. Combinatorial prophet inequalities. In *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1671–1687. SIAM, 2017. Longer ArXiv version is at `http://arxiv.org/abs/1611.00665`.

[Rub16] Aviad Rubinstein. *Beyond Matroids: Secretary Problem and Prophet Inequality with General Constraints*, page 324–332. Association for Computing Machinery, New York, NY, USA, 2016.

[Sin18] Sahil Singla. *Combinatorial Optimization Under Uncertainty: Probing and Stopping-Time Algorithms*. PhD thesis, CMU, 2018. `http://reports-archive.adm.cs.cmu.edu/anon/2018/CMU-CS-18-111.pdf`.

[Von] Jan Vondrák. personal communication.

[XSC+19] Pan Xu, Yexuan Shi, Hao Cheng, John Dickerson, Karthik Abinav Sankararaman, Aravind Srinivasan, Yongxin Tong, and Leonidas Tsepenekas. A unified approach to online matching with conflict-aware constraints. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):2221–2228, Jul. 2019.

[Yan11] Qiqi Yan. Mechanism design via correlation gap. In Dana Randall, editor, *Proceedings of the Twenty-Second Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2011, San Francisco, California, USA, January 23-25, 2011*, pages 710–719. SIAM, 2011.