On Provable Benefits of Depth in Training Graph Convolutional Networks

Abstract

Graph Convolutional Networks (GCNs) are known to suffer from performance degradation as the number of layers increases, which is usually attributed to over-smoothing. Despite the apparent consensus, we observe that there exists a discrepancy between the theoretical understanding of over-smoothing and the practical capabilities of GCNs. Specifically, we argue that over-smoothing not necessarily happen in practice, a deeper model is provable expressive, can converge to global optimal with linear convergence rate, and achieve very high training accuracy as long as properly trained. Despite being capable of achieving high training accuracy, empirical results shows that the deeper models generalize poorly on the testing set and existing theoretical understanding of such behavior remains elusive. To achieve better understanding, we carefully analyzing the *generalization capability* of GCNs, we show that the training strategies to achieve high training accuracy significantly deteriorate the *generalization capability* of GCNs. Motivated by these findings, we propose a decoupled structure for GCNs that detaches weight matrices from feature propagation to preserve the expressive power and ensure good generalization performance. We conduct empirical evaluations on various synthetic and real-world datasets to validate the correctness of our theory.

1 Introduction

In recent years, Graph Convolutional Networks (GCNs) have achieved state-of-the-art performance in dealing with graph-structured applications, including social networks [28, 21, 49, 11, 43], traffic prediction [9, 44, 33, 30], knowledge graphs [50, 51, 42], drug reaction [13, 15] and recommendation system [2, 58]. Despite the success of GCNs, applying a shallow GCN model that only uses the information of a very limited neighborhood on a large sparse graph has shown to be not effective [23, 6, 19, 8, 45]. As a result, a deeper GCN model would be desirable to reach and aggregate information from farther neighbors. The inefficiency of shallow GCNs is exacerbated even further when the labeled nodes compared to graph size is negligible, as a shallow GCN cannot sufficiently propagate the label information to the entire graph with only a few available labels [34].

Although a deeper GCN is preferred to perceive more graph structure information, unlike traditional deep neural networks, it has been pointed out that deeper GCNs potentially suffer from over-smoothing [34, 40, 26, 4, 56], vanishing/exploding gradients [32], over-squashing [1], and training difficulties [60, 37], which significantly affect the performance of GCNs as the depth increases. Among these, the most widely accepted reason is "over-smoothing", which is referred to as a phenomenon due to applying multiple graph convolutions such that all node embeddings converge to a single subspace (or vector) and leads to indistinguishable node representations.

The conventional wisdom is that adding to the number of layers cause over-smoothing, which impairs the *expressiveness power* of GCNs and consequently leads to a poor *training accu-*

racy. However, we observe that there exists a discrepancy between theoretical understanding of their inherent capabilities and practical performances. According to the definition of over-smoothing that the node representation becomes indistinguishable as GCNs goes deeper, the classifier has difficulty assigning the correct label for each node if over-smoothing happens. As a result, the training accuracy is expected to be decreasing as the number of layers increases.

However, as shown in Figure 1, GCNs are capable of achieving high *training accuracy* regardless of the number of layers. However, deeper GCNs require more training iterations to reach a high training accuracy, and its *generalization performance* on evaluation set decreases as the number of layers increases. This observation suggests that the performance degradation is likely due to inappropriate training rather than the low expressive power caused by over-smoothing. Otherwise, a low expressiveness model cannot achieve almost perfect training accuracy simply by property training alone. Indeed, recent years have witnessed significant advances on tweaking the model architecture to overcome training difficulties and achieve good generalization performance [37, 6, 32, 60].

Figure 1: Comparison of F1-score of GCN with different depth on *Cora* dataset, where deeper model can achieve high training accuracy, but complicate the training by requiring more iterations to converge and suffer from poor generalization.

Contributions. Motivated by this, i.e., still achieving high training accuracy when trained properly but poor generalization performance, we aim at answering two fundamental questions in this paper:

Q1: Does increasing depth really impair the expressiveness power of GCNs? In Section 4, we argue that over-smoothing is not the key factor that leads to the performance degradation in deeper GCNs. In particular, we mathematically show that over-smoothing [40, 26, 34, 4] is mainly an artifact of theoretical analysis and simplifications made in analysis. Indeed, by characterizing the representational capacity of GCNs via Weisfeiler-Lehman (WL) graph isomorphism test [38, 53], we show that deeper GCN model is at least as expressive as the shallow GCN model as long as the GCNs are properly trained. Besides, we theoretically show that a deeper model requires more training iterations to achieve the same training error as the shallow one, which further suggests the poor training error in deep GCN training is most likely due to inappropriate training.

Q2: If expressive, why then deep GCNs generalize poorly? In Section 5, to understand the performance degradation phenomenon in deep GCNs during evaluation, we give a novel generalization analysis on GCNs and its variants (e.g., ResGCN, APPNP, and GCNII) under the semi-supervised setting for the node classification task. We show that the generalization gap of GCNs is governed by the number of training iterations, largest node degree, the largest singular value of weight matrices, and the number of layers. In particular, our result suggests that a deeper GCN model requires more iterations of training and optimization tricks to converge (e.g., adding skip-connections), which leads to a poor generalization. More interestingly, our generalization analysis shows that most of the so-called methods to solve over-smoothing [46, 59, 6, 29] can greatly improve the generalization ability of the model, therefore results in a deeper model.

The aforementioned findings naturally lead to the algorithmic contribution of this paper. In Section 6, we present a novel framework, *Decoupled GCN*, that is capable of training deeper GCNs and can significantly improve the generalization performance. The main idea is to isolate the expressive power from generalization ability by decoupling the weight parameters from feature propagation. In Section 7, we conduct experiments on the synthetic and real-world datasets to validate the correctness of the theoretical analysis and the advantages of DGCN over baseline methods.

2   Related works

Expressivity of GCNs. Existing results expressive power are mixed, [38, 36, 7, 5] argue that deeper model has higher expressive power but [40, 26, 25] has the completely contradict result. On the one hand, [38] shows a deeper GCN is as least as powerful as the shallow one in terms of distinguishing non-isomorphic graphs. [36] shows that deep and wide GCNs is Turing universal, however, GCNs lose power when their depth and width are restricted. [7] and [5] measures the expressive power of

GCNs via its subgraph counting capability and attribute work, and both show the expressive power of GCNs grows exponentially with the GCN depth. On the other hand, [25] studies the infinity wide GCNs and show that the covariance matrix of its outputs converges to a constant matrix at an exponential rate. [40, 26] characterize the expressive power using the distance between node embeddings to a node feature agnostic subspace and show the distance is decreasing as the number of layers increases. Details are deferred to Section 4 and Appendix B.

Generalization analysis of GCNs. In recent years, many papers are working on the generalization of GCNs using uniform stability [48, 61], Neural Tangent Kernel [14], VC-dimension [47], Rademacher complexity [17, 41], algorithm alignment [54, 55] and PAC-Bayesian [35]. Existing works only focus on a specific GCN structure, which cannot be used to understand the impact of GCN structures on its generalization ability. The most closely related to ours is [48], where they analyzes the stability of the single-layer GCN model, and show that the stability of GCN depends on the largest absolute eigenvalue of its Laplacian matrix. However, their result is under inductive learning setting and extending the results to multi-layer GCNs with different structures is non-trivial.

Literature with similar observations. [60] argues that the main factors to performance degradation are vanishing gradient, training instability, and over-fitting, rather than over-smoothing, and proposes a node embedding normalization heuristic to alleviate the issues. [37] argues that the performance degradation is mainly due to the training difficulty, and propose a different graph Laplacian formulation, weight parameter initialization, and skip-connections to improve the training difficulty. [57] argues that deep GCNs can learn to overcome the over-smoothing issue during training, and the key factor of performance degradation is over-fitting, and proposes a node embedding normalization method to help deep GCNs overcome the over-smoothing issue. All aforementioned literature only gives heuristic explanations based on the empirical results, and do not provide theoretical arguments.

3 Preliminaries

Notations and setup. We consider the semi-supervised node classification problem, where a self-connected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ with $N = |\mathcal{V}|$ nodes is given in which each node $i \in \mathcal{V}$ is associated with a feature vector $\mathbf{x}_i \in \mathbb{R}^{d_0}$, and only a subset of nodes $\mathcal{V}_{\text{train}} \subset \mathcal{V}$ are labeled, i.e., $y_i \in \{1, \ldots, |\mathcal{C}|\}$ for each $i \in \mathcal{V}_{\text{train}}$ and $\mathcal{C}$ is the set of all candidate classes. Let $\mathbf{A} \in \mathbb{R}^{N \times N}$ denotes the adjacency matrix and $\mathbf{D} \in \mathbb{R}^{N \times N}$ denotes the corresponding degree matrix with $D_{i,i} = \deg(i)$ and $D_{i,j} = 0$ if $i \neq j$. Then, the normalized Laplacian matrix is computed as $\mathbf{L} = \mathbf{D}^{-1/2} \mathbf{A} \mathbf{D}^{-1/2}$. Our goal is to learn a GCN model using the node features for all nodes $\{\mathbf{x}_i\}_{i \in \mathcal{V}}$ and node labels for the training set nodes $\{y_i\}_{i \in \mathcal{V}_{\text{train}}}$, and expect it generalizes well on the unlabeled node set $\mathcal{V}_{\text{test}} = \mathcal{V} \setminus \mathcal{V}_{\text{train}}$.

GCN architectures. In this paper, we consider the following architectures for training GCNs:

- *Vanilla GCN* [28] computes node embeddings by $\mathbf{H}^{(\ell)} = \sigma(\mathbf{L} \mathbf{H}^{(\ell-1)} \mathbf{W}^{(\ell)})$ where $\mathbf{H}^{(\ell)} = \{\mathbf{h}_i^{(\ell)}\}_{i=1}^N$ is the ℓth layer node embedding matrix, $\mathbf{h}_i^{(\ell)} \in \mathbb{R}^{d_\ell}$ is the embedding of ith node, $\mathbf{W}^{(\ell)} \in \mathbb{R}^{d_\ell \times d_{\ell-1}}$ is the ℓth layer weight matrix, and $\sigma(\cdot)$ is the ReLU activation.
- *ResGCN* [32] solve the vanishing gradient issue by adding skip-connections between adjacency layers. More specifically, ResGCN compute node embeddings by $\mathbf{H}^{(\ell)} = \sigma(\mathbf{L} \mathbf{H}^{(\ell-1)} \mathbf{W}^{(\ell)}) + \mathbf{H}^{(\ell-1)}$, where node embeddings of the previous layer is added to the output of current layer to facilitate the training of deeper GCN model.
- *APPNP* [29] adds skip-connections from the input layer to each hidden layer to preserve the feature information. APPNP computes node embeddings by $\mathbf{H}^{(\ell)} = \alpha_\ell \mathbf{L} \mathbf{H}^{(\ell-1)} + (1 - \alpha_\ell) \mathbf{H}^{(0)} \mathbf{W}$, where $\alpha_\ell \in [0, 1]$ balances the amount of information preserved at each layer. By decoupling feature transformation and propagation, APPNP can aggregation information from multi-hop neighbors without significantly increasing the computation complexity.
- *GCNII* [6] improves the capacity of APPNP by adding non-linearty and weight matrix at each individual layer. GCNII computes node embeddings by $\mathbf{H}^{(\ell)} = \sigma\big((\alpha_\ell \mathbf{L} \mathbf{H}^{(\ell-1)} + (1 - \alpha_\ell) \mathbf{H}^{(0)}) \bar{\mathbf{W}}^{(\ell)}\big)$, where $\bar{\mathbf{W}}^{(\ell)} = \beta_\ell \mathbf{W}^{(\ell)} + (1 - \beta_\ell) \mathbf{I}$ and constant α_ℓ the same as APPNP, and constant $\beta_\ell \in [0, 1]$ restricts the power of ℓth layer parameters.

4 On true expressiveness and optimization landscape of deep GCNs

Empirical validate on over-smoothing. In this section, we aim at answering the following central question: *"Does over-smoothing really cause the performance degradation in deeper GCNs?"*. As first defined in [34], *over-smoothing* is referred to as a phenomenon where all node embeddings converge to a single vector after applying multiple graph convolution operations to the node features. However, [34] only considers the graph convolution operation *without* non-linearity and the per-layer weight matrices. To verify whether over-smoothing exists in normal GCNs, we measure the pairwise distance between the normalized node embeddings with varying the model depth.

As shown in Figure 2, without the weight matrices and non-linearity, the pairwise distance between node embeddings indeed decreases as the number of layer increases. However, if considering the weight matrices and non-linearity, the pairwise distance is actually increasing after a certain depth which *contradicts* the definition of over-smoothing that node embeddings become indistinguishable when model becomes deeper. That is, graph convolution makes adjacent node embeddings getting closer, then non-linearity and weight matrices help node embeddings preserves distinguish-ability after convolution.

Figure 2: Comparison of intra- and inter-class normalized node embeddings $\mathbf{H}^{(\ell)}/\|\mathbf{H}^{(\ell)}\|_F$ pairwise distance on *Cora* dataset. See Appendix A for more evidences.

Most recently, [40, 26] generalize the idea of over-smoothing by taking both the non-linearity and weight matrices into considerations. More specifically, the expressive power of the ℓth layer node embeddings $\mathbf{H}^{(\ell)}$ is measured using $d_{\mathcal{M}}(\mathbf{H}^{(\ell)})$, which is defined as the distance of node embeddings to a subspace $\mathcal{M}$ that only has node degree information. Let denote λ_L as the second largest eigenvalue of graph Laplacian and λ_W as the largest singular value of weight matrices, they show that the expressive power $d_{\mathcal{M}}(\mathbf{H}^{(\ell)})$ is bounded by $d_{\mathcal{M}}(\mathbf{H}^{(\ell)}) \leq (\lambda_W \lambda_L)^\ell \cdot d_{\mathcal{M}}(\mathbf{X})$, i.e., the expressive power of node embeddings will exponentially decrease or increasing as the number of layers increases, depending on whether $\lambda_W \lambda_L < 1$ or $\lambda_W \lambda_L > 1$. They conclude that *"deeper GCN exponentially loss expressive power"* by assuming $\lambda_W \lambda_L < 1$. However, we argue that this assumption not always hold. To see this, let suppose $\mathbf{W}^{(\ell)} \in \mathbb{R}^{d_{\ell-1} \times d_\ell}$ is initialized by uniform distribution $\mathcal{N}(0, \sqrt{1/d_{\ell-1}})$. By the Gordon's theorem for Gaussian matrices [10], we know its expected largest singular value is bounded by $\mathbb{E}[\lambda_W] \leq 1 + \sqrt{d_\ell/d_{\ell-1}}$, which is strictly greater than 1 and d_W usually increases during training. The above discussion also hold for other commonly used initialization [18, 22].

Furthermore, since most real world graphs are sparse with λ_L close to 1, e.g., Cora has $\lambda_L = 0.9964$, Citeseer has $\lambda_L = 0.9987$, and Pubmed has $\lambda_L = 0.9905$, making assumption on $\lambda_W \lambda_L < 1$ is not realistic. As shown in Figure 3, when increasing the number of layers, we observe that the distance $d_{\mathcal{M}}(\mathbf{H}^{(\ell)})$ is decreasing on *untrained*-GCN models, however, the distance $d_{\mathcal{M}}(\mathbf{H}^{(\ell)})$ is increasing on *trained*-GCN models, which contradicts the conclusion in [40]. Due to the space limit, we defer the more empirical evidences to Appendix B. Through these

Figure 3: Compare $d_{\mathcal{M}}(\mathbf{H}^{(\ell)})$ and $\lambda_W(\mathbf{W}^{(\ell)})$ on both *trained*- (using 500 gradient update) and *untrained*-GCN models on *Cora* dataset.

findings, we cast doubt on the power of over-smoothing based analysis to provide a complete picture of why deep GCNs perform badly.

Definition 1. *Let $\mathcal{T}_i^L$ denote the L-layer computation tree of node i, which represents the structured L-hop neighbors of node i, where the children of any node j in the tree are the nodes in $\mathcal{N}(i)$.*

Exponentially growing expressiesness without strong assumptions. Indeed, we argue that *deeper GCNs have stronger expressive power than the shallow GCNs*. To prove this, we employ the connection between WL test[1] [31] and GCNs. Recently, [38] shows that GCNs have the same expressiveness

---
[1] WL test is a recursive algorithm where the label of a node depends on its own label and neighbors from the previous iterations, i.e., $c_i^{(\ell)} = \text{Hash}(c_i^{(\ell-1)}, \{c_j^{(\ell-1)} | j \in \mathcal{N}(i)\})$, where Hash$(\cdot)$ bijectively maps the a set of

as the WL-test for graph isomorphism if they are appropriately trained, i.e., a properly trained L-layer GCN computes different node representations for two nodes if their L-layer *computation tree* (Definition 1) have different structure or different features on the corresponding nodes. Since L-GCN can encode any different computation tree into different representations, it is natural to characterize the expressiveness of L-GCN by the number of computation graph it can encode.

Theorem 1. *Suppose $\mathcal{T}^L$ is a computation tree with binary node features and node degree at least d. Then the richness of the output of L-GCN defined on $\mathcal{T}^L$ is at least $|L\text{-}GCN(\mathcal{T}^L)| \geq 2(d-1)^{L-1}$.*

The proof is defered to Appendix E. The above theorem implies that the richness of L-GCN grows at least exponentially with respect to the number of layers.

Comparison of expressiveness metric. Although distance-based expressiveness metric [40, 26] is strong than WL-based metric in the sense that node embeddings can be *distinct* but *close to each other*, the distance-based metric requires explicit assumptions on the GCN structure, weight matrices, and graph structures comparing to the WL-based metric, which has been shown that are not likely hold. On the other hand, WL-based metric has been widely used in characterizing the expressive power of GCNs in graph-level task [38, 36, 7, 5]. More details are deferred to related works (Section 2).

Although expressive, it is still unclear why the deeper GCN requires more training iterations to achieve small training error and reach the properly trained status. To understand this, we show in Theorem 2 that under assumptions on the width of the final layer, the deeper GCN can converge to its global optimal with linear convergence rate. Besides, more training iterations are required for a deeper model to achieve the same training error than the shallow model.

Theorem 2. *Let $\boldsymbol{\theta}_t = \{\mathbf{W}_t^{(\ell)} \in \mathbb{R}^{d_{\ell-1} \times d_\ell}\}_{\ell=1}^{L+1}$ be the model parameter at the t-th iteration and using square loss $\mathcal{L}(\boldsymbol{\theta}) = \frac{1}{2}\|\mathbf{H}^{(L)}\mathbf{W}^{(L+1)} - \mathbf{Y}\|_{\mathrm{F}}^2$, $\mathbf{H}^{(\ell)} = \sigma(\mathbf{L}\mathbf{H}^{(\ell-1)}\mathbf{W}^{(\ell)})$ as objective function. Then, under the condition that $d_L \geq N$ we can obtain $\mathcal{L}(\boldsymbol{\theta}_T) \leq \epsilon$ if $T \geq C(L)\log(\mathcal{L}(\boldsymbol{\theta}_0)/\epsilon)$, where ϵ is the desired error and $C(L)$ is a function of GCN depth L that grows as GCN becomes deeper.*

A formal statement of Theorem 2 and its proof are deferred to Appendix C. Besides, gradient stability also provides an alternative way of empirically understanding why deeper GCN requires more iterations: Deeper neural networks are prone to exploding/vanishing gradient, which results in a very noisy gradient and requires small learning rate to stabilize the training. This issue can be significantly alleviated by adding skip-connections (Appendix D.5). When training with adaptive learning rate algorithm, such as Adam [27][2], noisy gradient will result in a much smaller update on current model comparing to a stabilized gradient, therefore more training iterations.

5   A different view from generalization

In the previous section, we provided evidences that a well-trained deep GCN is at least as powerful as a shallow one. However, it is still unclear why a deeper GCNs has worse performance than a shallow GCN during the evaluation phase. To answer this question, we provide a different view by analyzing the impact of GCN structures on the generalization.

Transductive uniform stability. In the following, we study the generalization ability of GCNs via *transductive uniform stability* [16], where the generalization gap is defined as the difference between the training and testing errors for the random partition of a full dataset into training and testing sets. Transductive uniform stability is defined under the notation that the output of a classifier does not change much if the input is perturbed a bit, which is an extension of uniform stability [3] from the inductive to the transductive setting. The previous analysis on the uniform stability of GCNs [48] only shows the result of GCN with one graph convolutional layer under inductive learning setting, which cannot explain the effect of depth, model structure, and training data size on the generalization, and its extension to multi-layer GCNs and other GCN structures are non-trivial.

Problem setup. Let $m = |\mathcal{V}_{\text{train}}|$ and $u = |\mathcal{V}_{\text{test}}|$ denote the training and test dataset sizes, respectively. Under the transductive learning setting, we start with a fixed set of points $X_{m+u} = \{x_1, \ldots, x_{m+u}\}$.

---

values to a unique value that has not been used in the previous iterations. After L-iterations, the WL test will assign two nodes with a different label if the L-hop neighborhood of two nodes are non-isomorphic.

[2]In the Adam optimizer, the contribution of bias correction of moments varies exponentially over epochs completed. Although the learning rate hyper-parameter is a constant, the contribution of gradients to updated weight varies over epochs, hence adaptive. Please refer to the Chapter 8.5 of [20] for more details.

For notation convenience, we assume X_m are the first m data points and X_u are the last u data points of X_{m+u}. We randomly select a subset $X_m \subset X_{m+u}$ uniformly at random and reveal the labels Y_m for the selected subset for training, but the labels for the remaining u data points $Y_u = Y_{m+u} \setminus Y_m$ are not available during the training phase. Let $S_m = ((x_1, y_1), \ldots, (x_m, y_m))$ denotes the labeled set and $X_u = (x_{m+1}, \ldots, x_{m+u})$ denotes the unlabeled set. Our goal is to learn a model to label the remaining unlabeled set as accurately as possible.

For the analysis purpose, we assume a binary classifier is applied to the final layer node representation $f(\mathbf{h}_i^{(L)}) = \tilde{\sigma}(\mathbf{v}^\top \mathbf{h}_i^{(L)})$ with $\tilde{\sigma}(\cdot)$ denotes the sigmoid function. We predict $\hat{y}_i = 1$ if $f(\mathbf{h}_i^{(L)}) > 1/2$ and $\hat{y}_i = 0$ otherwise, with ground truth label $y_i \in \{0, 1\}$. Let denote the perturbed dataset as $S_m^{ij} \triangleq (S_m \setminus \{(x_i, y_i)\}) \cup \{(x_j, y_j)\}$ and $X_u^{ij} \triangleq (X_u \setminus \{x_j\}) \cup \{x_i\}$, which is obtained by replacing the ith example in training set S_m with the jth example from the testing set X_u. Let $\boldsymbol{\theta}$ and $\boldsymbol{\theta}^{ij}$ denote the weight parameters trained on the original dataset (S_m, X_u) and the perturbed dataset (S_m^{ij}, X_u^{ij}), respectively. Then, we say transductive learner f is ϵ-uniformly stable if the outputs change less than ϵ when we exchange two examples from the training set and testing set, i.e., for any $S_m \subset S_{m+u}$ and any $i, j \in [m + u]$ it holds that $\sup_{i \in [m+u]} |f(\mathbf{h}_i^{(L)}) - \tilde{f}(\tilde{\mathbf{h}}_i^{(L)})| \leq \epsilon$, where $f(\mathbf{h}_i^{(L)})$ and $\tilde{f}(\tilde{\mathbf{h}}_i^{(L)})$ denote the prediction of node i using parameters $\boldsymbol{\theta}$ and $\boldsymbol{\theta}^{ij}$ respectively.

To define testing error and training error in our setting, let us introduce the difference in probability between the correct and the incorrect label as $p(z, y) \triangleq y(2z - 1) + (1 - y)(1 - 2z)$ with $p(z, y) \leq 0$ if there exists a classification error. Let denote the γ-margin loss as $\Phi_\gamma(x) = \min(1, \max(0, 1 - x/\gamma))$. Then, the testing error is defined as $\mathcal{R}_u(f) = \frac{1}{u} \sum_{i=m+1}^{m+u} \mathbf{1}\{p(f(\mathbf{h}_i^{(L)}), y_i) \leq 0\}$ and the training loss is defined as $\mathcal{R}_m^\gamma(f) = \frac{1}{m} \sum_{i=1}^m \Phi_\gamma(-p(f(\mathbf{h}_i^{(L)}), y_i))$. [3]

Theorem 3 (Transductive uniform stability bound [16]). *Let f be a ϵ-uniformly stable transductive learner and $\gamma, \delta > 0$, and define $Q = mu/(m + u)$. Then, with probability at least $1 - \delta$ over all training and testing partitions, we have $\mathcal{R}_u(f) \leq \mathcal{R}_m^\gamma(f) + \frac{2}{\gamma} \mathcal{O}\left(\epsilon \sqrt{Q \ln(\delta^{-1})}\right) + \mathcal{O}\left(\frac{\ln(\delta^{-1})}{\sqrt{Q}}\right).$*

Recall that as we discussed in Section 4, deeper GCN is provable more expressive and can achieve very low training error $\mathcal{R}_m^\gamma(f)$ if properly training. Then, if the dataset size is sufficiently large, the testing error $\mathcal{R}_u(f)$ will be dominated by the generalization gap, which is mainly controlled by uniformly stable constant ϵ. In the following, we explore the impact of GCN structures on ϵ. Our key idea is to decompose the ϵ into three terms: the Lipschitz continuous constant ρ_f, upper bound on gradient G_f, and the smoothness constant L_f of GCNs. Please refer to Lemma 1 for details.

Lemma 1. *Suppose function $f(\mathbf{h}^{(L)})$ is ρ_f-Lipschitz continuous, L_f-smoothness, and the gradient of loss w.r.t. the parameter is bounded by G_f. After T-steps of full-batch gradient descent, we have $\epsilon = \frac{2\eta \rho_f G_f}{m} \sum_{t=1}^T (1 + \eta L_f)^{t-1}$.*

The proof is deferred to Appendix K. By using Lemma 1, we can derive constant ϵ of different model structures by comparing the Lipschitz continuity, smoothness, and gradient scale. Before proceeding to our result, we make the following standard assumption on the node feature vectors and weight matrices, which are previously used in generalization analysis of GCNs [17, 35].

Assumption 1. *We assume the norm of node feature vectors, weight parameters are bounded, i.e., $\|\mathbf{x}_i\|_2 \leq B_x$, $\|\mathbf{W}^{(\ell)}\|_2 \leq B_w$, and $\|\mathbf{v}\|_2 \leq 1$.*

In Theorem 4, we show that the generalization bounds of GCN and its variants are dominated by the following terms: maximum node degree d, model depth L, training/validation set size (m, u), training iterations T, and spectral norm of the weight matrices B_w. The larger the aforementioned variables are, the larger the generalization gap is. We defer the formal statements and proofs to Appendices F, G, H, I.

---

[3]Notice that a different loss function is used in convergence analysis (i.e., $\mathcal{L}(\boldsymbol{\theta})$ in Theorem 7) and generalization analysis ($\mathcal{R}_m^\gamma(f)$ in Theorem 4). We do this because current understanding on the convergence of deep neural network is still mostly limited to the square loss, but the margin loss is more suitable and widely accepted loss function for generalization analysis.

Table 1: Comparison of uniform stability constant ϵ of GCN variants, where $\mathcal{O}(\cdot)$ is used to hide constants that shared between all bounds.

	ρ_f and G_f	L_f	C_1 and C_2
ϵ_{GCN}	$\mathcal{O}(C_1^L C_2)$	$\mathcal{O}\big(C_1^L C_2((L+2)C_1^L C_2+2)\big)$	$C_1=\max\{1,\sqrt{d}B_w\}$, $C_2=\sqrt{d}(1+B_x)$
ϵ_{ResGCN}	$\mathcal{O}(C_1^L C_2)$	$\mathcal{O}\big(C_1^L C_2((L+2)C_1^L C_2+2)\big)$	$C_1=1+\sqrt{d}B_w$, $C_2=\sqrt{d}(1+B_x)$
ϵ_{APPNP}	$\mathcal{O}(C_1)$	$\mathcal{O}\big(C_1(C_1 C_2)+1\big)$	$C_1=B_d^\alpha B_x$, $C_2=\max\{1,B_w\}$
ϵ_{GCNII}	$\mathcal{O}(\beta C_1^L C_2)$	$\mathcal{O}\big(\alpha\beta C_1^L C_2((\alpha\beta L+2)C_1^L C_2+2\beta)\big)$	$C_1=\max\{1,\alpha\sqrt{d}B_w^\beta\}$, $C_2=\sqrt{d}+B_{\ell,d}^{\alpha,\beta}B_x$
ϵ_{DGCN}	$\mathcal{O}(C_1)$	$\mathcal{O}(C_1(C_1 C_2)+1)$	$C_1=(\sqrt{d})^L B_x$, $C_2=\max\{1,B_w\}$

Theorem 4 (Informal). *We say model is ϵ-uniformly stable with $\epsilon = \frac{2\eta\rho_f G_f}{m}\sum_{t=1}^{T}(1+\eta L_f)^{t-1}$ where the result of ρ_f, G_f, L_f are summarized in Table 1, and other related constants as*

$$B_d^\alpha = (1-\alpha)\sum_{\ell=1}^{L}(\alpha\sqrt{d})^{\ell-1} + (\alpha\sqrt{d})^L, \ B_w^\beta = \beta B_w + (1-\beta),$$
$$B_{\ell,d}^{\alpha,\beta} = \max\big\{\beta\big((1-\alpha)L + \alpha\sqrt{d}\big), (1-\alpha)LB_w^\beta + 1\big\}. \tag{1}$$

In the following, we provide intuitions and discussions on the generalization bound of each algorithm:

- Deep **GCN** requires iterations T to achieve small training error. Since the generalization bound increases with T, more iterations significantly hurt its generalization power. Notice that our results considers both $B_w \leq 1$ and $B_w > 1$, where increasing model depth will not hurt the generalization if $B_w \leq 1$, and the generalization gap becomes sensitive to the model depth if $B_w > 1$. Notice that $B_w > 1$ is more likely happens during training as we discussed in Section 4.
- **ResGCN** resolves the training difficulties by adds skip-connections between hidden layers. Although it requires less training iterations T, adding skip-connections enlarge the dependency on the number of layers L and the spectral norm of weight matrices B_w, therefore results in a larger generalization gap and a poor generalization performance..
- **APPNP** alleviates the aforementioned dependency by decoupling the weight parameters and feature propagation. As a result, its generalization gap does not significantly changes as L and B_w increase. The optimal α that minimize the generalization gap can be obtained by finding the α that minimize the term B_d^α. Although APPNP can significantly reduce the generalization gap, because a single weight matrix is shared between all layers, its expressive power is not enough for large-scale challenging graph datasets [24].
- To gain expressiveness, **GCNII** proposes to add the weight matrices back and add another hyper-parameter that explicitly control the dependency on B_w. Although GCNII achieves the state-of-the-art performances on several graph datasets, the selection of hyper-parameter is non-trivial comparing to APPNP because α, β are coupled with L, B_w, and d. In practice, [6] builds a very deep GCNII by choosing β dynamically decreases as the number of layers and different α values for different datasets.
- By property chosen hyper-parameters, we have the following order on the generalization gap given the same training iteration T: APPNP $\leq$ GCNII $\leq$ GCN $\leq$ ResGCN, which exactly match our empirical evaluation on the generalization gap in Section 7 and Appendix D.

Remark 1. *In the following, we provide an alternative view of DropEdge [46] and PairNorm [59] from its generalization power. To improve the generalization power of GCN, DropEdge randomly drops edges in training phase, which leads to a smaller maximum node degree $d_s < d$. PairNorm applies normalization on intermediate node embeddings to ensure that the total pairwise feature distances remains a constant across layers, which leads to less dependency on d and B_w. However, since deep GCN requires significant more iterations to achieve low training error than shallow one, the performance of applying DropEdge and PairNorm on GCNs is still degrading as the number of layers increases. Most importantly, our empirical results in Appendix D.3 and D.4 suggest that applying Dropout and PairNorm is hurting the training accuracy (i.e., not alleviating over-smoothing) but reducing the generalization gap.*

6   Decoupled GCN

We propose to decouple the expressive power from generalization ability with **D**ecoupled **GCN** (DGCN). The DGCN model can be mathematically formulated as $\mathbf{Z} = \sum_{\ell=1}^{L}\alpha_\ell f^{(\ell)}(\mathbf{X})$ and

$f^{(\ell)}(\mathbf{X}) = \mathbf{L}^\ell \mathbf{X}\big(\beta_\ell \mathbf{W}^{(\ell)} + (1-\beta_\ell)\mathbf{I}\big)$, where $\mathbf{W}^{(\ell)}$, α_ℓ and β_ℓ are the learnable weights for ℓth layer function $f^{(\ell)}(\mathbf{X})$. The design of DGCN has the following key ingredients:

- (Decoupling) The generalization gap in GCN grows exponentially with the number of layers. To overcome this issue, we propose to decouple the weight matrices from propagation by assigning weight $\mathbf{W}^{(\ell)}$ to each individual layerwise function $f^{(\ell)}(\mathbf{X})$. DGCN can be thought of as an ensemble of multiple SGCs [52] with depth from 1 to L. By doing so, the generalization gap has less dependency on the number of weight matrices, and deep model with large receptive field can incorporate information of the global graph structure. Please refer to Theorem 5 for the details.
- (Learnable α_ℓ) After decoupling the weight matrices from feature propagation, the layerwise function $f^{(\ell)}(\mathbf{X})$ with more propagation steps can suffer from less expressive power. Therefore, we propose to assign a learnable weight α_ℓ for each step of feature propagation. Intuitively, DGCN assigns smaller weight α_ℓ to each layerwise function $f^{(\ell)}(\mathbf{X})$ with more propagation steps at the beginning of training. Throughout the training, DGCN gradually adjusts the weight to leverage more useful large receptive field information.
- (Learnable β_ℓ) A learnable weight $\beta_\ell \in [0,1]$ is assigned to each weight matrix to balance the expressiveness with model complexity, which guarantees a better generalization ability.

Theorem 5. *Let suppose α_ℓ and β_ℓ are pre-selected and fixed during training. We say DGCN is ϵ_{DGCN}-uniformly stable with $\epsilon_{DGCN} = \frac{2\eta\rho_f G_f}{m}\sum_{t=1}^{T}(1+\eta L_f)^{t-1}$ where*

$$\rho_f = G_f = \mathcal{O}\Big((\sqrt{d})^L B_x\Big), \quad L_f = \mathcal{O}\Big((\sqrt{d})^L B_x\big((\sqrt{d})^L B_x \max\{1, B_w\} + 1\big)\Big). \quad (2)$$

The details are deferred to Appendix J, and comparison of bound to other GCN variants are summarized in Table 1. Depending on the automatic selection of α_ℓ, β_ℓ, the generalization bound of DGCN is between APPNP and GCN. In the following, we make connection to many GCN structures:

- **Connections to APPNP:** APPNP can be think of as a variant of DGCN. More specifically, the layerwise weight in APPNP is computed as $\alpha_\ell = \alpha(1-\alpha)^\ell$ for $\ell < L$ and $\alpha_\ell = (1-\alpha)^\ell$ for $\ell = L$ given some constant $\alpha \in (0,1)$, and the weight matrix is shared between all layers. Although DGCN has L weight matrices, its generalization is independent on the number of weight matrices, and thus enjoys a low generalization error with high expressiveness.
- **Connections to GCNII:** GCNII can be regarded as a variant of DGCN. Comparing to GCNII, the decoupled propagation of DGCN significantly reduces the dependency of generalization error to the weight matrices. Besides, the learnable weights α_ℓ and β_ℓ allow DGCN to automatically adapt to challenging large-scale datasets without time-consuming hyper-parameter selection.
- **Connections to ResGCN:** By expanding the forward computation of ResGCN, we know that ResGCN can be think of as training an assemble of GCNs from 1 to L layer, i.e., $\mathbf{H}^{(L)} = \sum_{\ell=1}^{L} \alpha_\ell \sigma(\mathbf{L}\mathbf{H}^{(\ell-1)}\mathbf{W}^{(\ell)})$ with $\alpha_\ell = 1$. Therefore, ResGCN is a special case of DGCN with equal weights α_ℓ on each layerwise function.

7 Experiments

Synthetic dataset. We empirically compare the generalization error of different GCN structures on the synthetic dataset. In particular, we create the synthetic dataset by contextual stochastic block model (CSBM) [12] with two equal-size classes. CSBM is a graph generation algorithm that adds Gaussian random vectors as node features on top of classical SBM. CSBM allows for smooth control over the information ratio between node features and graph topology by a pair of hyper-parameter (μ, λ), where μ controls the diversity of the Gaussian distribution and λ controls the number of edges between intra- and inter-class nodes. We generate random graphs with 1000 nodes, average node degree as 5, and each nodes has a Gaussian random vectors of dimension 1000 as node features. We chose 75% nodes are training set, 15% of nodes as validation set, and the remaining nodes as testing set. We conduct experiment 20 times by randomly selecting (μ, λ) such that both node feature and graph topology are equally informative. As shown in Figure 4, we have the following order on the generalization gap given the same training iteration T: APPNP $\leq$ GCNII $\leq$ GCN $\leq$ ResGCN, which exactly match the theoretical result in Theorem 4. More specifically, ResGCN has the largest generalization gap due to the skip-connections, APPNP has the smallest generalization gap by removing the weight matrices in each individual layers. GCNII achieves a good balance between GCN and APPNP by balancing the expressive and generalization power. Finally, DGCN enjoys a small generalization error by using the decoupled GCN structure.

Figure 4: Comparison of generalization error on synthetic dataset. The curve early stopped at the largest training accuracy iteration.

Open graph benchmark dataset. As pointed out by Hu et al. [24], the traditional commonly-used graph datasets are unable to provide a reliable evaluation due to various factors including dataset size, leakage of node features, no consensus on data splitting. To truly evaluate the expressive and the generalization power of existing methods, we evaluate on the open graph benchmark (OGB) dataset. Experiment setups are based on the default setting for GCN implementation on the leaderboard. We choose the hidden dimension as 128, learning rate as 0.01, dropout ratio as 0.5 for *Arxiv* dataset, and no dropout for *Products* and *Protein* datasets. We train $300/1000/500$ epochs for *Products*, *Proteins*, and *Arxiv* dataset respectively. Due to limited GPU memory, the number of layers is selected as the one with the best performance between 2 to 16 layers for *Arvix* dataset, 2 to 8 layers for *Protein* dataset, and 2 to 4 for *Products* dataset. We choose α_ℓ from $\{0.9, 0.8, 0.5\}$ for APPNP and GCNII, and use $\beta_\ell = 0.5/\ell$ for GCNII, and select the setup with the best testing accuracy for comparison.

As shown in Table 2, DGCN achieves a compatible performance to GCNII[4] without the need of manually tuning the hyper-parameters for all settings, and it significantly outperform APPNP and ResGCN. Due to the space limit, the detailed setups and more results can be found in Appendix D. Notice that generalization bounds are more valuable when comparing two models with same training accuracy (therefore we first show in Section 4 that deeper model can also achieve low training error before our discussion

Table 2: Comparison of F1-score on OGB dataset.

%	**Products**	**Proteins**	**Arvix**
GCN	75.39 ± 0.21	71.66 ± 0.48	71.56 ± 0.19
ResGCN	75.53 ± 0.12	74.50 ± 0.41	72.56 ± 0.31
APPNP	66.35 ± 0.10	71.78 ± 0.29	66.90 ± 0.82
GCNII	$71.93 \pm 0.35^\dagger$	75.60 ± 0.47	$72.08 \pm 0.39^\ddagger$
DGCN	76.09 ± 0.29	75.45 ± 0.24	72.63 ± 0.12

on generalization in Section 5). In Table 2, becasue ResGCN has no restriction on the weight matrices, its can achieve lower training error and its test performance is mainly restricted by its generalization error. However, because GCNII and APPNP have restriction on the weight matrices, their performance are mainly restricted by their training error. A model with small generalization error and no restriction on the weight (e.g., DGCN) is preferred as it has higher potential to reach a better test accuracy by reducing its training error.

8 Conclusion

In this work, we show that there exists a discrepancy between over-smoothing based theoretical results and the practical behavior of deep GCNs. Our theoretical result shows that a deeper GCN can be as expressive as a shallow GCN, if it is properly trained. To truly understand the performance decay issue of deep GCNs, we provide the first transductive uniform stability-based generalization analysis of GCNs and other GCN structures. To improve the optimization issue and benefit from depth, we propose DGCN that enjoys a provable high expressive power and generalization power. We conduct empirical evaluations on various synthetic and real-world datasets to validate the correctness of our theory and advantages over the baselines.

---

[4]† GCNII underfits with the default hyper-parameters. ‡ GCNII achieves 72.74 ± 0.16 by using hidden dimension as 256 and a different design of graph convolution layer. Refer here for details.

References

[1] Uri Alon and Eran Yahav. On the bottleneck of graph neural networks and its practical implications. *arXiv preprint arXiv:2006.05205*, 2020.

[2] Rianne van den Berg, Thomas N Kipf, and Max Welling. Graph convolutional matrix completion. *arXiv preprint arXiv:1706.02263*, 2017.

[3] Olivier Bousquet and André Elisseeff. Stability and generalization. *Journal of machine learning research*, 2(Mar):499–526, 2002.

[4] Chen Cai and Yusu Wang. A note on over-smoothing for graph neural networks. *arXiv preprint arXiv:2006.13318*, 2020.

[5] Lei Chen, Zhengdao Chen, and Joan Bruna. On graph neural networks versus graph-augmented mlps. *arXiv preprint arXiv:2010.15116*, 2020.

[6] Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. Simple and deep graph convolutional networks. *arXiv preprint arXiv:2007.02133*, 2020.

[7] Zhengdao Chen, Lei Chen, Soledad Villar, and Joan Bruna. Can graph neural networks count substructures? *arXiv preprint arXiv:2002.04025*, 2020.

[8] Weilin Cong, Rana Forsati, Mahmut Kandemir, and Mehrdad Mahdavi. Minimal variance sampling with provable guarantees for fast training of graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1393–1403, 2020.

[9] Zhiyong Cui, Kristian Henrickson, Ruimin Ke, and Yinhai Wang. Traffic graph convolutional recurrent neural network: A deep learning framework for network-scale traffic learning and forecasting. *IEEE Transactions on Intelligent Transportation Systems*, 2019.

[10] Kenneth R Davidson and Stanislaw J Szarek. Local operator theory, random matrices and banach spaces. *Handbook of the geometry of Banach spaces*, 1(317-366):131, 2001.

[11] Songgaojun Deng, Huzefa Rangwala, and Yue Ning. Learning dynamic context graphs for predicting social events. In *KDD*, pages 1007–1016, 2019.

[12] Yash Deshpande, Andrea Montanari, Elchanan Mossel, and Subhabrata Sen. Contextual stochastic block models. *arXiv preprint arXiv:1807.09596*, 2018.

[13] Kien Do, Truyen Tran, and Svetha Venkatesh. Graph transformation policy network for chemical reaction prediction. In *KDD*, pages 750–760, 2019.

[14] Simon S Du, Kangcheng Hou, Russ R Salakhutdinov, Barnabas Poczos, Ruosong Wang, and Keyulu Xu. Graph neural tangent kernel: Fusing graph neural networks with graph kernels. In *Advances in Neural Information Processing Systems*, pages 5723–5733, 2019.

[15] David K Duvenaud, Dougal Maclaurin, Jorge Iparraguirre, Rafael Bombarell, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P Adams. Convolutional networks on graphs for learning molecular fingerprints. In *NeurIPS*, pages 2224–2232, 2015.

[16] Ran El-Yaniv and Dmitry Pechyony. Stable transductive learning. In *International Conference on Computational Learning Theory*, pages 35–49. Springer, 2006.

[17] Vikas K Garg, Stefanie Jegelka, and Tommi Jaakkola. Generalization and representational limits of graph neural networks. *arXiv preprint arXiv:2002.06157*, 2020.

[18] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256. JMLR Workshop and Conference Proceedings, 2010.

[19] Shunwang Gong, Mehdi Bahri, Michael M Bronstein, and Stefanos Zafeiriou. Geometrically principled connections in graph neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11415–11424, 2020.

[20] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016. http://www.deeplearningbook.org.

[21] Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in neural information processing systems*, pages 1024–1034, 2017.

[22] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

[23] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[24] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

[25] Wei Huang, Yayong Li, Weitao Du, Richard Yi Da Xu, Jie Yin, and Ling Chen. Wide graph neural networks: Aggregation provably leads to exponentially trainability loss. *arXiv preprint arXiv:2103.03113*, 2021.

[26] Wenbing Huang, Yu Rong, Tingyang Xu, Fuchun Sun, and Junzhou Huang. Tackling over-smoothing for general graph convolutional networks. *arXiv e-prints*, pages arXiv–2008, 2020.

[27] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[28] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[29] Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Graph neural networks meet personalized pagerank. *arXiv preprint arXiv:1810.05997*, 2018.

[30] Srijan Kumar, Xikun Zhang, and Jure Leskovec. Predicting dynamic embedding trajectory in temporal interaction networks. In *KDD*, pages 1269–1278, 2019.

[31] AA Leman and B Weisfeiler. A reduction of a graph to a canonical form and an algebra arising during this reduction. *Nauchno-Technicheskaya Informatsiya*, 2(9):12–16, 1968.

[32] Guohao Li, Matthias Muller, Ali Thabet, and Bernard Ghanem. Deepgcns: Can gcns go as deep as cnns? In *Proceedings of the IEEE International Conference on Computer Vision*, pages 9267–9276, 2019.

[33] Jia Li, Zhichao Han, Hong Cheng, Jiao Su, Pengyun Wang, Jianfeng Zhang, and Lujia Pan. Predicting path failure in time-evolving graphs. In *KDD*, pages 1279–1289, 2019.

[34] Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. *arXiv preprint arXiv:1801.07606*, 2018.

[35] Renjie Liao, Raquel Urtasun, and Richard Zemel. A pac-bayesian approach to generalization bounds for graph neural networks. *arXiv preprint arXiv:2012.07690*, 2020.

[36] Andreas Loukas. What graph neural networks cannot learn: depth vs width. *arXiv preprint arXiv:1907.03199*, 2019.

[37] Sitao Luan, Mingde Zhao, Xiao-Wen Chang, and Doina Precup. Training matters: Unlocking potentials of deeper graph convolutional neural networks. *arXiv preprint arXiv:2008.08838*, 2020.

[38] Christopher Morris, Martin Ritzert, Matthias Fey, William L Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4602–4609, 2019.

[39] Quynh Nguyen. On the proof of global convergence of gradient descent for deep relu networks with linear widths. *arXiv preprint arXiv:2101.09612*, 2021.

[40] Kenta Oono and Taiji Suzuki. Graph neural networks exponentially lose expressive power for node classification. *arXiv preprint arXiv:1905.10947*, 2019.

[41] Kenta Oono and Taiji Suzuki. Optimization and generalization analysis of transduction through gradient boosting and application to multi-scale graph neural networks. *Advances in Neural Information Processing Systems*, 33, 2020.

[42] Namyong Park, Andrey Kan, Xin Luna Dong, Tong Zhao, and Christos Faloutsos. Estimating node importance in knowledge graphs using graph neural networks. In *KDD*, pages 596–606, 2019.

[43] Jiezhong Qiu, Jian Tang, Hao Ma, Yuxiao Dong, Kuansan Wang, and Jie Tang. Deepinf: Modeling influence locality in large social networks. In *KDD*, 2018.

[44] Afshin Rahimi, Trevor Cohn, and Timothy Baldwin. Semi-supervised user geolocation via graph convolutional networks. *arXiv preprint arXiv:1804.08049*, 2018.

[45] Morteza Ramezani, Weilin Cong, Mehrdad Mahdavi, Anand Sivasubramaniam, and Mahmut Kandemir. Gcn meets gpu: Decoupling "when to sample" from "how to sample". *Advances in Neural Information Processing Systems*, 33, 2020.

[46] Yu Rong, Wenbing Huang, Tingyang Xu, and Junzhou Huang. Dropedge: Towards deep graph convolutional networks on node classification. In *International Conference on Learning Representations*, 2019.

[47] Franco Scarselli, Ah Chung Tsoi, and Markus Hagenbuchner. The vapnik–chervonenkis dimension of graph and recursive neural networks. *Neural Networks*, 108:248–259, 2018.

[48] Saurabh Verma and Zhi-Li Zhang. Stability and generalization of graph convolutional neural networks. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1539–1548, 2019.

[49] Hao Wang, Tong Xu, Qi Liu, Defu Lian, Enhong Chen, Dongfang Du, Han Wu, and Wen Su. Mcne: An end-to-end framework for learning multiple conditional network representations of social network. In *KDD*, pages 1064–1072, 2019.

[50] Hongwei Wang, Fuzheng Zhang, Mengdi Zhang, Jure Leskovec, Miao Zhao, Wenjie Li, and Zhongyuan Wang. Knowledge-aware graph neural networks with label smoothness regularization for recommender systems. In *KDD*, pages 968–977, 2019.

[51] Xiang Wang, Xiangnan He, Yixin Cao, Meng Liu, and Tat-Seng Chua. Kgat: Knowledge graph attention network for recommendation. In *KDD*, pages 950–958, 2019.

[52] Felix Wu, Tianyi Zhang, Amauri Holanda de Souza Jr, Christopher Fifty, Tao Yu, and Kilian Q Weinberger. Simplifying graph convolutional networks. *arXiv preprint arXiv:1902.07153*, 2019.

[53] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

[54] Keyulu Xu, Jingling Li, Mozhi Zhang, Simon S Du, Ken-ichi Kawarabayashi, and Stefanie Jegelka. What can neural networks reason about? *arXiv preprint arXiv:1905.13211*, 2019.

[55] Keyulu Xu, Mozhi Zhang, Jingling Li, Simon Shaolei Du, Ken-Ichi Kawarabayashi, and Stefanie Jegelka. How neural networks extrapolate: From feedforward to graph neural networks. In *International Conference on Learning Representations*, 2021.

[56] Yujun Yan, Milad Hashemi, Kevin Swersky, Yaoqing Yang, and Danai Koutra. Two sides of the same coin: Heterophily and oversmoothing in graph convolutional neural networks. *arXiv preprint arXiv:2102.06462*, 2021.

[57] Chaoqi Yang, Ruijie Wang, Shuochao Yao, Shengzhong Liu, and Tarek Abdelzaher. Revisiting" over-smoothing" in deep gcns. *arXiv preprint arXiv:2003.13663*, 2020.

[58] Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton, and Jure Leskovec. Graph convolutional neural networks for web-scale recommender systems. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 974–983, 2018.

[59] Lingxiao Zhao and Leman Akoglu. Pairnorm: Tackling oversmoothing in gnns. *arXiv preprint arXiv:1909.12223*, 2019.

[60] Kuangqi Zhou, Yanfei Dong, Wee Sun Lee, Bryan Hooi, Huan Xu, and Jiashi Feng. Effective training strategies for deep graph neural networks. *arXiv preprint arXiv:2006.07107*, 2020.

[61] Xianchen Zhou and Hongxia Wang. The generalization error of graph convolutional networks may enlarge with more layers. *Neurocomputing*, 424:97–106, 2021.