Tackling Neural Architecture Search
With Quality Diversity Optimization

Lennart Schneider[1] **Florian Pfisterer**[1] **Paul Kent**[2] **Juergen Branke**[3] **Bernd Bischl**[1]
Janek Thomas[1]

[1]Department of Statistics, LMU Munich, Germany
[2]Mathematics of Real World Systems, University of Warwick, UK
[3]Warwick Business School, University of Warwick, UK

Abstract Neural architecture search (NAS) has been studied extensively and has grown to become a research field with substantial impact. While classical single-objective NAS searches for the architecture with the best performance, multi-objective NAS considers multiple objectives that should be optimized simultaneously, e.g., minimizing resource usage along the validation error. Although considerable progress has been made in the field of multi-objective NAS, we argue that there is some discrepancy between the actual optimization problem of practical interest and the optimization problem that multi-objective NAS tries to solve. We resolve this discrepancy by formulating the multi-objective NAS problem as a quality diversity optimization (QDO) problem and introduce three quality diversity NAS optimizers (two of them belonging to the group of multifidelity optimizers), which search for high-performing yet diverse architectures that are optimal for application-specific niches, e.g., hardware constraints. By comparing these optimizers to their multi-objective counterparts, we demonstrate that quality diversity NAS in general outperforms multi-objective NAS with respect to quality of solutions and efficiency. We further show how applications and future NAS research can thrive on QDO.

1 Introduction

The goal of neural architecture search (NAS) is to automate the manual process of designing optimal neural network architectures. Traditionally, NAS is formulated as a single-objective optimization problem with the goal of finding an architecture that has minimal validation error [13, 35, 45, 47, 46, 63]. Considerations for additional objectives such as efficiency have led to the formulation of constraint NAS methods that enforce efficiency thresholds [1] as well as multi-objective NAS methods [10, 12, 37, 53, 36] that yield a Pareto optimal set of architectures. However,

Figure 1: Optimizing neural network architectures for a discrete set of devices. We are interested in the best solution (green) within the constraints of the respective device (dashed vertical lines). Multi-objective optimization, in contrast, approximates the full Pareto front (black).

in most practical applications, we are not interested in the complete Pareto optimal set. Instead, we would like to obtain solutions for a discrete set of scenarios (e.g., end-user devices), which we henceforth refer to as *niches* in this paper. This is illustrated in Figure 1. A concrete example is finding neural architectures for microcontrollers [32] and other edge devices [38], e.g., in μNAS [32] architectures for "mid-tier" IoT devices are searched. To evaluate the benefits for larger devices, the search would need to be restarted with adapted constraints, thus wasting computational resources. Formulating the search as a multi-objective problem would also waste resources; once an architecture satisfies the constraints of a device, we are not interested in additional trade-offs, and we select only based on the validation error.

We therefore argue that the multi-objective NAS problem *can* and usually *should* be formulated as a *quality diversity optimization* (QDO) problem, which directly corresponds to the actual optimization problem of interest. The main contributions of this paper are: We (1) formulate multi-objective NAS as a QDO problem; (2) show how to adapt black-box optimization algorithms for the QDO setting; (3) modify existing QDO algorithms for the NAS setting; (4) propose novel multifidelity QDO algorithms for NAS; and (5) illustrate that our approach can be used to extend a broad range of NAS methods from conventional to Once-for-All methods.

2 Theoretical Background and Related Work

Let $\mathcal{A}$ denote a search space of architectures and Λ the search space of additional hyperparameters controlling the training of an architecture A. Furthermore, let $f_{\mathrm{err}} : \mathcal{A} \times \Lambda \rightarrow \mathbb{R}$ denote the validation error obtained after training an architecture $A \in \mathcal{A}$ with a set of hyperparameters $\lambda \in \Lambda$ for a given number of epochs ($\lambda_{\mathrm{epoch}} \in \lambda$). Typically, we consider $\lambda \in \Lambda$ to be fixed, except for λ_{epoch} in multifidelity methods, and we therefore omit λ in the following. The goal of single-objective NAS is to find the architecture with the lowest validation error, $A^* := \arg\min_{A \in \mathcal{A}} f_{\mathrm{err}}(A)$.

NAS methods can be categorized along three dimensions: search space, search strategy, and performance estimation strategy [13]. For chain-structured neural networks (simply a connected sequence of layers), cell-based search spaces have gained popularity [46, 45]. In cell-based search spaces, different kinds of cells – typically, a normal cell preserving dimensionality of the input and a reduction cell reducing spatial dimension – are stacked in a predefined arrangement to form a final architecture. Regarding search strategy, popular methods utilize Bayesian optimization (BO) [3, 8, 39, 24, 57], evolutionary methods [41, 34, 47, 46, 12], reinforcement learning [63, 64], or gradient-based algorithms [35, 45]. For performance estimation, popular approaches leverage lower fidelity estimates [31, 14, 64] or make use of learning curve extrapolation [8, 27].

Multi-Objective Neural Architecture Search Contrary to the single-objective NAS formulation, multi-objective NAS does not solely aim for minimizing the validation error but simultaneously optimizes multiple objectives. These objectives typically take resource consumption – such as memory requirements, energy usage or latency – into account [10, 12, 37, 53, 36]. Denote by $f_1, \ldots, f_k$ the $k \geq 2$ objectives of interest, where typically $f_1 = f_{\mathrm{err}}$ and denote by $\mathbf{f}(A)$ the vector of objective function values obtained for architecture $A \in \mathcal{A}$, $\mathbf{f}(A) = (f_1(A), \ldots, f_k(A))'$. The optimization problem of multi-objective NAS is then formulated as $\min_{A \in \mathcal{A}} \mathbf{f}(A)$. There is no architecture that minimizes all objectives at the same time since these are typically in competition with each other. Rather, there are multiple Pareto optimal architectures reflecting different trade-offs in objectives approximating the true (unknown) Pareto front. An architecture A is said to dominate another architecture A' iff $\forall i \in \{1, \ldots, k\} : f_i(A) \leq f_i(A') \land \exists j \in \{1, \ldots, k\} : f_j(A) < f_j(A')$.

Constrained and Hardware-Aware Neural Architecture Search In contrast, *Constrained NAS* [62, 15, 55] solves the problem of finding an architecture that optimizes one objective (e.g., validation error) with constraints on secondary objectives (e.g., model size). Constraints can be naturally given by the target hardware that a model should be deployed on. *Hardware-Aware NAS* in turn searches for an architecture that trades off primary objectives [60] against secondary, hardware-specific

metrics. In Once-for-All [5], a large supernet is trained which can be efficiently searched for subnets that, e.g., meet latency constraints of target devices. For a recent survey, we refer to [1].

Quality Diversity Optimization The goal of a QDO algorithm is to find a set of high-performing, yet behaviorally diverse, solutions. Similarly to multi-objective optimization, there is no single best solution. However, whereas multi-objective optimization aims for the simultaneous minimization of multiple objectives, QDO minimizes a single-objective function with respect to diversity defined on one or more *feature functions*. A feature function measures a quality of interest and a combination of feature values points to a niche, i.e., a region in *feature space*. QDO could be considered a *set* of constrained optimisation problems over the same input domain where the niche boundaries are constraints in feature space. The key difference is that constrained optimisation seeks a single optimal configuration given some constraints, while QDO attempts to identify the optimal configuration for each of a set of constrained regions simultaneously. In this sense, QDO could be framed as a so-called multi-task optimization problem [43] where each task is to find the best solution belonging to a particular niche.

QDO algorithms maintain an archive of niche-optimal observations, i.e., a best-performing observed solution for each niche. Observations with similar feature values compete to be selected for the archive, and the solution set gradually improves during the optimization process. Once the optimization budget has been spent, QDO algorithms typically return this archive as their solution. QDO is motivated by applications where a group of diverse solutions is beneficial, such as the training of robot movement where a repertoire of behaviours must be learned [7], developing game playing agents with diverse strategies [44], and in automatic design where QDO can be used by human designers to search a large dimensional search space for diverse solutions before the optimization is finished by hand. Work on automatic design tasks have been varied and include air-foil design [18], computer game level design [16], and architectural design [9]. Recently, QDO algorithms were used for illuminating the interpretability and resource usage of machine learning models while minimizing their generalization error [52].

In the earliest examples, Novelty Search (NS; [29]) asks whether diversity alone can produce a good set of solutions. Despite not actively pursuing objective performance, NS performed surprisingly well in some settings and was followed by Novelty Search with Local Competition [30], the first true quality diversity (QD) algorithm. MAP-Elites [42], a standard evolutionary QDO algorithm, partitions the feature space a-priori into niches and attempts to identify the optimal solution in each of these niches. QDO has seen much work in recent years and a variant based on BO, BOP-Elites, was proposed recently [25]. BOP-Elites models the objective and feature functions with surrogate models and implements an acquisition function over a structured archive to achieve high sample efficiency even in the case of black-box features.

3 Formulating Neural Architecture Search as a Quality Diversity Optimization Problem

In the example in Figure 1, a quality diversity NAS (subsequently abbreviated as qdNAS) problem is given by the validation error and three behavioral niches (corresponding to different devices) that are defined via resource usage measured by a single feature function. Let $f_1 : \mathcal{A} \to \mathbb{R}, A \mapsto f_1(A)$ denote the objective function of interest (in our context, f_{err}). Denote by $f_i : \mathcal{A} \to \mathbb{R}, A \mapsto f_i(A), i \in \{2, \ldots, k\}, k \geq 2$ the feature function(s) of interest (e.g., memory usage). Behavioral niches $N_j \subseteq \mathcal{A}, j \in \{1, \ldots, c\}, c \geq 1$ are sets of architectures characterized via niche-specific boundaries $\mathbf{b}_{ij} = [l_{ij}, u_{ij}) \subseteq \mathbb{R}$ on the images of the feature functions. An architecture A belongs to niche N_j if its values with respect to the feature functions lie between the respective boundaries, i.e.:

$$A \in N_j \iff \forall i \in \{2, \ldots, k\} : f_i(A) \in \mathbf{b}_{ij}.$$

The goal of a QDO algorithm is then to find for each behavioral niche N_j the architecture that minimizes the objective function f_1:

$$A_j^* := \underset{A \in N_j}{\arg\min} f_1(A).$$

In other words, the goal is to obtain a set of architectures $S := \{A_1^*, \ldots, A_c^*\}$ that are diverse with respect to the feature functions and yet high-performing.

A Remark about Niches In the classical QDO literature, niches are typically constructed to be pairwise disjoint, i.e., a configuration can only belong to a single niche (or none) [42, 25]. However, depending on the concrete application, relaxing this constraint and allowing for *overlap* can be beneficial. For example, in our context, an architecture that fits on a mid-tier device should also be considered for deployment on a higher-tier device, i.e., in Figure 1, the boundaries indicated by vertical dashed lines resemble the respective upper bound of a niche whereas the lower bound is unconstrained. This results in niches being nested within each other, i.e., $N_1 \subsetneq N_2 \subsetneq \ldots \subsetneq N_c \subseteq \mathcal{A}$, with N_1 being the most restrictive niche, followed by N_2. In Supplement A, we further discuss different ways of constructing niches in the context of NAS.

3.1 Quality Diversity Optimizers for Neural Architecture Search

As the majority of NAS optimizers are iterative, we first demonstrate how any iterative optimizer can in principle be turned into a QD optimizer. Based on this correspondence, we introduce three novel QD optimizers for NAS: BOP-Elites*, qdHB and BOP-ElitesHB. Let $f_1 : \mathcal{A} \to \mathbb{R}, A \mapsto f_1(x)$ denote the objective function that should be minimized. In each iteration, an iterative optimizer proposes a new configuration (e.g., architecture) for evaluation, evaluates this configuration, potentially updates the incumbent (best configuration evaluated so far) if better performance has been observed, and updates its archive. For generic pseudo code, see Supplement B.

Moving to a QDO problem, there are now feature functions $f_i : \mathcal{A} \to \mathbb{R}, A \mapsto f_i(A), i \in \{2, \ldots, k\}, k \geq 2$, and niches $N_j, j \in \{1, \ldots, c\}, c \geq 1$, defined via their niche-specific boundaries $\mathbf{b}_{ij} = [l_{ij}, u_{ij}) \subseteq \mathbb{R}$ on the images of the feature functions. Any iterative single-objective optimizer must then keep track of the best incumbent per niche (often referred to as an *elite* in the QDO literature) and essentially becomes a QD optimizer (see Algorithm 1). The challenge

---

Algorithm 1: Generic pseudo code for an iterative quality diversity optimizer.

Input : $f_1, f_i, i \in \{2, \ldots, k\}, k \geq 2, N_j, j \in \{1, \ldots, c\}, c \geq 1, \mathcal{D}_{\text{design}}, n_{\text{total}}$
Result: $S = \{A_1^*, \ldots, A_c^*\}$

1 $\mathcal{D} \leftarrow \mathcal{D}_{\text{design}}$
2 **for** $j \leftarrow 1$ **to** c **do**
3 $\quad$ $A_j^* \leftarrow \arg\min_{A \in \mathcal{D}_{|N_j}} f_1(A)$ # initial incumbent of niche N_j based on archive
4 **end**
5 **for** $n \leftarrow 1$ **to** n_{total} **do**
6 $\quad$ Propose a new candidate $A^\star$ # subroutine
7 $\quad$ Evaluate $y \leftarrow f_1(A^\star), \forall i \in \{2, \ldots, k\} : z_i \leftarrow f_i(A^\star)$
8 $\quad$ **if** $A^\star \in N_j \wedge y < f_1(A_j^*)$ **then**
9 $\quad\quad$ $A_j^* \leftarrow A^\star$ # update incumbent of niche N_j
10 $\quad$ **end**
11 $\quad$ $\mathcal{D} \leftarrow \mathcal{D} \cup \{(A^\star, y, z_2, \ldots, z_k)\}$
12 **end**

---

in designing an efficient and well-performing QD optimizer now mostly lies in proposing a new candidate for evaluation that considers improvement over all niches.

Bayesian Optimization A recently proposed model-based QD optimizer, BOP-Elites [25], extends BO [54, 17] to QDO. BOP-Elites relies on Gaussian process surrogate models for the objective function and all feature functions. New candidates for evaluation are selected by a novel acquisition function – the expected joint improvement of elites (EJIE), which measures the expected improvement to the ensemble problem of identifying the best solution in every niche:

$$\alpha_{\text{EJIE}}(A) := \sum_{j=1}^{c} \mathcal{P}(A \in N_j | \mathcal{D}) \mathbb{E}_y \left[\mathbb{I}_{|N_j}(A) \right]. \tag{1}$$

Here, $\mathcal{P}(A \in N_j | \mathcal{D})$ is the posterior probability of A belonging to niche N_j, and $\mathbb{E}_y \left[\mathbb{I}_{|N_j}(A) \right]$ is the expected improvement (EI; [23]) with respect to niche N_j:

$$\mathbb{E}_y \left[\mathbb{I}_{|N_j}(A) \right] = \mathbb{E}_y \left[\max \left(f_{\min_{N_j}} - y, 0 \right) \right],$$

where $f_{\min_{N_j}}$ is the best observed objective function value in niche N_j so far, and y is the surrogate model prediction for A. A new candidate is then proposed by maximizing the EJIE, i.e., Line 6 in Algorithm 1 looks like the following: $A^\star \leftarrow \arg\max_{A \in \mathcal{A}} \alpha_{\text{EJIE}}(A)$.

BOP-Elites* In order to adapt BOP-Elites for NAS, we introduce several modifications. First, we employ truncated (one-hot) path encoding [56, 57]. In path encoding, architectures are transformed into a set of binary features indicating presence for each path of the directed acyclic graph from the input to the output. By then truncating the least-likely paths, the encoding scales linearly in the size of the cell [57] allowing for an efficient representation of architectures. Second, we substitute the Gaussian process surrogate models used in BOP-Elites with random forests [4] allowing us to model non-continuous hyperparameter spaces. Random forests have been successfully used as surrogates in BO [21, 33], often performing on a par with ensembles of neural networks [57] in the context of NAS [51, 59]. Third, we introduce a local mutation scheme similarly to the one used by the BANANAS algorithm [57] for optimizing the infill criterion EJIE: Since our aim is to find high quality solutions across all niches, we maintain an archive of the incumbent architecture in each niche and perform local mutations on each incumbent. We refer to our adjusted version as BOP-Elites* in the remainder of the paper to emphasize the difference from the original algorithm. For the initial design, we sample architectures based on adjacency matrix encoding [56].

Multifidelity Optimizers For NAS, performance estimation is the computationally most expensive component [13], and almost all NAS optimizers can be made more efficient by allowing access to cheaper, lower fidelity estimates [13, 31, 14, 64]. By evaluating most architectures at lower fidelity and only promoting promising architectures to higher fidelity, many more architectures can be explored given the same total computational budget. The fidelity parameter is typically the number of epochs over which an architecture is trained.

qdHB One of the most prominent multifidelity optimizers is Hyperband (HB; [31]), a multi-armed bandit strategy that uses repeated Successive Halving (SH; [22]) as a subroutine to identify the best configuration (e.g., architecture) among a set of randomly sampled ones. Given an initial and maximum fidelity, a scaling parameter η, and a set of configurations of size n, SH evaluates all configurations on the initial smallest fidelity, then sorts the configurations by performance and only keeps the best $1/\eta$ configurations. These configurations are then trained with fidelity increased by a factor of η. This process is repeated until the maximum fidelity for a single configuration is reached. HB repeatedly runs SH with different sized sets of initial configurations called brackets. Only two inputs are required: R, the maximum fidelity and η, the scaling parameter that controls the proportion of configurations discarded in each round of SH. Based on these inputs, the number $s_{\max}$ and size n_i of different brackets is determined. To adapt HB to the QD setting, we must track the incumbent architecture in each niche and promote configurations based on their performance within the respective niche (see Supplement B): To achieve this, we choose the top $\lfloor n_i/\eta \rfloor$ configurations

to be promoted uniformly over the c niches (done in the $\text{top}_{\text{k\_qdo}}$ function), i.e., we iteratively select one of the niches uniformly at random and choose the best configuration observed so far that has yet not been selected for promotion until $\lfloor n_i/\eta \rfloor$ configurations have been selected. Note that during this procedure, it may happen that not enough configurations belonging to a specific niche have been observed yet. In this case, we choose any configuration uniformly at random over the set of all configurations that have yet to be promoted. With those modifications, we propose qdHB, as a multifidelity QD optimizer.

BOP-ElitesHB While HB typically shows strong anytime performance [31], it only samples configurations at random and is typically outperformed by BO methods with respect to final performance if optimizer runtime is sufficiently large [14]. BOHB [14] combines the strengths of HB and BO in a single optimizer, resulting in strong anytime performance and fast convergence. This approach employs a fidelity schedule similar to HB to determine how many configurations to evaluate at which fidelity but replaces the random selection of configurations in each HB iteration by a model-based proposal. In BOHB, a Tree Parzen Estimator [2] is used to model densities $l(A) = p(y < \alpha | A, \mathcal{D})$ and $g(A) = p(y > \alpha | A, \mathcal{D})$, and candidates are proposed that maximize the ratio $l(A)/g(A)$, which is equivalent to maximizing EI [2]. Based on BOP-Elites* and qdHB, we can now derive the QD Bayesian optimization Hyperband optimizer (BOP-ElitesHB): Instead of selecting configurations at random at the beginning of each qdHB iteration, we propose candidates that maximize the EJIE criterion. This sampling procedure is described in Supplement B.

4 Main Benchmark Experiments and Results

We are interested in answering the following research questions: (**RQ1**) *Does qdNAS outperform multi-objective NAS if the optimization goal is to find high-performing architectures in pre-defined niches?* (**RQ2**) *Do multifidelity qdNAS optimizers improve over full-fidelity qdNAS optimizers?* To answer these questions, we benchmark our three qdNAS optimizers – BOP-Elites*, qdHB, and BOP-ElitesHB– on the well-known NAS-Bench-101 [61] and NAS-Bench-201 [11] and compare them to three multi-objective optimizers adapted for NAS: ParEGO*, moHB*, and ParEGOHB as well as a simple Random Search[1].

Experimental Setup It is important to compare optimizers using analogous implementation details. We therefore use truncated path encoding and random forest surrogates throughout our experiments for all model-based optimizers. Furthermore, we use local mutations as described in [57] in order to optimize acquisition functions in BOP-Elites*, BOP-ElitesHB, ParEGO*, and ParEGOHB. To control for differences in implementation, we re-implement all optimizers and take great care in matching the original implementations.

We provide full details regarding implementation in Supplement B and only briefly introduce conceptual differences: ParEGO* is a multi-objective optimizer based on ParEGO [28] and only deviates from BOP-Elites* in that it considers a differently scalarized objective in each iteration, which is optimized using local mutations similar to the acquisition function optimization of BOP-Elites*. moHB* is an extension of HB to the multi-objective setting (promoting configurations based on non-dominated sorting with hypervolume contribution for tie breaking, for similar approaches see, e.g., [48, 49, 50, 19]). ParEGOHB is a model-based extension of moHB* that relies on the ParEGO scalarization [28] and on the same acquisition function optimization as ParEGO*.

All optimizers were evaluated on NAS-Bench-101 (Cifar-10, validation error as the first objective and the number of trainable parameters as the feature function/second objective) and NAS-Bench-201 (Cifar-10, Cifar-100, ImageNet16-120, validation error as the first objective and latency as the feature function/second objective). For multifidelity, we train architectures for 4, 12, 36, 108 epochs on NAS-Bench-101 and for 2, 7, 22, 67, 200 epochs on NAS-Bench-201 (reflecting $\eta = 3$ in the HB variants). As the optimization budget, we consider 200 full architecture evaluations (resulting in

---

[1]using adjacency matrix encoding [56]

a total budget of 21600 epochs for NAS-Bench-101 and 40000 epochs for NAS-Bench-201). For each of these four settings, we construct three different scenarios by considering different niches of interest with respect to the feature function, resulting in a total of 12 benchmark problems. In the *small/medium/large* settings, two, five and ten niches are considered, respectively. Niches are constructed to be overlapping, and boundaries are defined based on percentiles of the feature function. For the *small* setting, the boundary is given by the 50% percentile ($q_{50\%}$), effectively resulting in two niches with boundaries $[0, q_{50\%})$ and $[0, \infty)$. For the *medium* and *large* settings, percentiles indicating progressively larger niches were used, ranging from: 1% to 30% and 70% respectively. More details on the niches can be found in Supplement C. All runs were replicated 100 times.

Results As an anytime performance measure, we are interested in the validation error obtained for each niche, which we aggregate in a single performance measure as $\sum_{j=1}^{c} f_{\mathrm{err}}(A_j^*)$, i.e., we consider the sum of validation errors over the best-performing architecture per niche. If a niche is empty, we assign a validation error of 100 as a penalty (this is common practice in QDO, i.e., if no solution has been found for a niche, this niche is assigned the worst possible objective function value [25]). For the final performance, we also consider the analogous test error. Figure 2 shows the anytime performance of optimizers. We observe that model-based optimizers (BOP-Elites* and ParEGO*) in general strongly outperform Random Search, and BO HB optimizers (BOP-ElitesHB and ParEGOHB) generally outperform their full-fidelity counterparts, although this effect diminishes with increasing optimization budget. In general, HB variants that do not rely on a surrogate model (qdHB and moHB*) show poor performance compared to the model-based optimizers. Moreover, especially in the *small* number of niches setting, QD strongly outperforms multi-objective optimization. Mean ranks of optimizers with respect to final validation and test performance are given in Table 1. For completeness, we also report critical differences plots of these ranks in Supplement C.

We also conducted two four-way ANOVAs on the average performance after half and all of the optimization budget is used, with the factors problem (benchmark problem), multifidelity (whether an optimizer uses multifidelity), QDO (whether an optimizer is a QD optimizer) and model-based (whether the optimizer relies on a surrogate model)[2]. For half the budget used, results indicate significant main effects of the factors multifidelity ($F(1) = 19.13, p = 0.0001$), QDO ($F(1) = 11.08, p = 0.0017$) and model-based ($F(1) = 21.13, p < 0.0001$). For all of the budget used, the significance of multifidelity diminishes, whereas the main effects of QDO ($F(1) = 18.31, p = 0.0001$) and model-based ($F(43.44), p < 0.0001$) are still significant. We can conclude that QDO in general outperforms competitors when the goal is to find high-performing architectures in pre-defined niches. Multi-fidelity optimizers improve over full-fidelity optimizers but this effect diminishes with increasing budget. Detailed results are reported in Supplement C.

Regarding efficiency, we analyzed the expected running time (ERT) of the QD optimizers given the average performance of the respective multi-objective optimizers after half of the optimization budget: For each benchmark problem, we computed the mean validation performance of each multi-objective optimizer after having spent half of its optimization budget and investigated the ERT of the analogous[3] QD optimizer. For each benchmark problem, we then computed the ratio of ERTs between multi-objective and QD optimizers and averaged them over the benchmark problems. For BOP-ElitesHB, we observe an average ERT ratio of 2.41, i.e., in expectation, BOP-ElitesHB is a factor of 2.41 faster than ParEGOHB in reaching the average performance of ParEGOHB (after half the optimization budget). For qdHB and BOP-Elites*, the average ERT ratios are 1.14 and 1.44. We conclude that all QD optimizers are more efficient than their multi-objective counterparts. More details can be found in Supplement C.

---

[2]For this analysis, we excluded qdHB and moHB* due to their lackluster performance.

[3]BOP-ElitesHB for ParEGOHB, qdHB for moHB*, and BOP-Elites* for ParEGO*

Figure 2: Anytime performance of optimizers. Ribbons represent standard errors over 100 replications. x-axis starts after 10 full-fidelity evaluations.

Table 1: Ranks of optimizers with respect to final performance, averaged over benchmark problems.

Mean Rank (SE)	BOP-ElitesHB	qdHB	BOP-Elites*	ParEGOHB	moHB*	ParEGO*	Random
Validation	2.08 (0.29)	5.92 (0.26)	1.83 (0.21)	4.25 (0.48)	6.42 (0.15)	2.58 (0.31)	4.92 (0.34)
Test	1.42 (0.19)	5.00 (0.17)	2.08 (0.23)	4.33 (0.50)	6.50 (0.19)	3.25 (0.35)	5.42 (0.42)

5 Additional Experiments and Applications

In this section, we illustrate how qdNAS can be used beyond the scenarios investigated so far and present results of additional experiments ranging from a comparison of qdNAS to multi-objective NAS on the MobileNetV3 search space to an example on how to incorporate QDO in existing frameworks such as Once-for-All [5] or how to use qdNAS for model compression.

Benchmarks on the MobileNetV3 Search Space We further investigated how qdNAS compares to multi-objective NAS on a search space that is frequently used in practice [20]. We consider CNNs divided into a sequence of units with feature map size gradually being reduced and channel numbers being increased. Each unit consists of a sequence of layers where only the first layer has stride 2 if the feature map size decreases and all other layers in the units have stride 1. Units can use an arbitrary number of layers (elastic depth chosen from $\{2, 3, 4\}$) and for each layer, an arbitrary number of channels (elastic width chosen from $\{3, 4, 6\}$) and kernel sizes (elastic kernel size chosen from $\{3, 5, 7\}$) can be used. Additionally, the input image size can be varied (elastic resolution ranging from 128 to 224 with a stride 4). For more details on the search space, see [5]. To allow for reasonable runtimes we use accuracy predictors (based on architectures trained and evaluated on ImageNet as described in [5]) and resource usage look-up tables of the Once-for-All module [5, 6] and construct a surrogate benchmark. As an objective function we select the validation error and as a feature function/second objective the latency (in ms) when deployed on a Samsung Note 10 (batch size of 1), or the number of FLOPS (M) used by the model. So far, we have only investigated qdNAS in the context of $k = 2$, i.e., considering one objective and one feature function. Here, we additionally consider a setting of $k = 3$, by incorporating both latency and the size of the model (in MB) as feature functions/second and third objective. We compare BOP-Elites* to ParEGO* and a

Random Search due to the accuracy predictors not supporting evaluations at multiple fidelities. We again construct three scenarios by considering different niches of interest with respect to the feature functions taking inspiration from latency and FLOPS constraints as used in [5] (details are given in Table 4 in Supplement C). Optimizers are given a total budget of 100 architecture evaluations. Figure 3 shows the anytime performance of optimizers with respect to the validation error summed over niches (averaged over 100 replications). BOP-Elites* strongly outperforms the competitors on all benchmark problems. More details are provided in Supplement D.

Figure 3: `MobileNetV3` search space. Anytime performance of optimizers. Ribbons represent standard errors over 100 replications. x-axis starts after 10 evaluations.

Making Once-for-All Even More Efficient In Once-for-All [5], an already trained supernet is searched via regularized evolution [46] for a well performing subnet that meets hardware requirements of a target device relying on an accuracy predictor and resource usage look-up tables. This is sensible if only a single solution is required, however, if various subnets meeting different constraints on the same device are desired, repeated regularized evolution is not efficient. Moreover, look-up tables do not generalize to new target devices in which case using as few as possible architecture evaluations suddenly becomes relevant again. We notice that the search for multiple architectures within Once-for-All can again be formulated as a QDO problem and therefore compare MAP-Elites [42] to regularized evolution when performing a joint search for architectures meeting different latency constraints on a Samsung Note 10. Results are given in Table 2 with MAP-Elites consistently outperforming regularized evolution, making this novel variant of Once-for-All even more efficient. More details are provided in Supplement E.

Table 2: MAP-Elites vs. regularized evolution within Once-for-All.

Method	Best Validation Error for Different Latency Constraints						
	$[0, 15)$	$[0, 18)$	$[0, 21)$	$[0, 24)$	$[0, 27)$	$[0, 30)$	$[0, 33)$
Reg. Evo.	**21.57** (0.01)	20.34 (0.02)	19.29 (0.01)	18.48 (0.02)	17.81 (0.02)	17.40 (0.02)	17.06 (0.02)
MAP-Elites	21.60 (0.01)	**20.28** (0.01)	**19.21** (0.01)	**18.39** (0.01)	**17.70** (0.01)	**17.25** (0.01)	**16.90** (0.01)

Average over 100 replications based on the accuracy predictor of Once-for-All [5, 6]. Standard errors in parentheses. Reg. Evo. = regularized evolution.

Applying qdNAS to Model Compression We are interested in deploying a `MobileNetV2` across different devices that are mainly constrained by memory. For each device, we can therefore only consider models up to a fixed amount of parameters, similarly as depicted in Figure 1. Given that we have a pretrained model that achieves high performance, we want to *compress* this model exploiting redundancies in model parameters. In our application, we use the Stanford Dogs dataset [26] and

rely on the neural network intelligence (NNI; [40]) toolkit for model compression. Pruning consists of several (iterative) steps as well as re-training of the pruned architectures. Choices for the pruner itself, pruner hyperparameters, and hyperparameters controlling retraining are available and must be carefully selected to obtain optimal models (see Supplement F). We consider the number of model parameters as a proxy measure for memory requirement, yielding three overlapping niches for different devices. The pre-trained `MobileNetV2` achieves a validation error of 20.25 using around 2.34 million model parameters. We define niches with boundaries corresponding to compression rates (number of parameters after pruning) of 40% to 50%, 40% to 60%, and 40% to 70%. As the QD optimizer, we use BOP-ElitesHB and specify the number of fine-tuning epochs a pruner can use as a fidelity parameter, since fine-tuning after pruning is costly but also strongly influences final performance. After evaluating only 69 configurations (a single BOP-ElitesHB run with $\eta = 3$), we obtain high-performing pruner configurations for each niche, resulting in the performance vs. memory requirement (number of parameters) trade-offs shown in Table 3.

Table 3: Results of using BOP-ElitesHB for model compression of `MobileNetV2` on Stanford Dogs.

Niche	Validation Error	# Params (in millions; rounded)	% (# Params$_{\text{Baseline}}$)
Niche 1 [0.94, 1.17)	31.20	1.13	48.10%
Niche 2 [0.94, 1.41)	29.07	1.29	54.99%
Niche 3 [0.94, 1.64)	27.76	1.62	68.97%
Baseline	20.25	2.34	100.00%

6 Conclusion

We demonstrated how multi-objective NAS can be formulated as a QDO problem that, contrary to multi-objective NAS, directly corresponds to the actual optimization problem of interest, i.e., finding high-performing architectures in different niches. We have shown how any iterative black box optimization algorithm can be adapted to the QDO setting and proposed three QDO algorithms for NAS, with two of which making use of multifidelity evaluations. In benchmark experiments, we have shown that qdNAS outperforms multi-objective NAS while simultaneously being more efficient. We furthermore illustrated how qdNAS can be used for model compression and how future NAS research can thrive on QDO. QDO is orthogonal to the NAS strategy of an algorithm and can be similarly used to extend, e.g., one-shot NAS methods.

Limitations The framework we describe relies on pre-defined niches, e.g., memory requirements of different devices. If niches are mis-specified or cannot be specified a priori, multi-objective NAS may outperform qdNAS. However, an initial study (see Supplement H) how qdNAS performs in a true multi-objective setting, which would correspond to unknown niches, shows little to no performance degradation depending on the choice of niches. Moreover, we only investigated the performance of qdNAS in the deterministic setting. Additionally, our multifidelity optimizers require niche membership to be unaffected by the multifidelity parameter. Finally, we mainly focused on model-based NAS algorithms that we have extended to the QDO setting.

Broader Impact Our work extends previous research on NAS and therefore inherits its implications on society and individuals such as potential discrimination in resulting models. Moreover, evaluating a large number of architectures is computationally costly and can introduce serious environmental issues. We have shown that qdNAS allows for finding better solutions, while simultaneously being more efficient than multi-objective NAS. As performance estimation is extremely costly in NAS, we believe that this is an important contribution towards reducing resource usage and the CO_2 footprint of NAS.

References

[1] H. Benmeziane, K. El Maghraoui, H. Ouarnoughi, S. Niar, M. Wistuba, and N. Wang. Hardware-aware neural architecture search: Survey and taxonomy. In Z.-H. Zhou, editor, *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI-21*, pages 4322–4329, 2021.

[2] J. Bergstra, R. Bardenet, Y. Bengio, and B. Kégl. Algorithms for hyper-parameter optimization. In *Advances in Neural Information Processing Systems*, volume 24, 2011.

[3] J. Bergstra, D. Yamins, and D. Cox. Making a science of model search: Hyperparameter optimization in hundreds of dimensions for vision architectures. In *Proceedings of the 30th International Conference on Machine Learning*, pages 115–123, 2013.

[4] L. Breiman. Random forests. *Machine Learning*, 45(1):5–32, 2001.

[5] H. Cai, C. Gan, T. Wang, Z. Zhang, and S. Han. Once-for-All: Train one network and specialize it for efficient deployment. In *International Conference on Learning Representations*, 2020.

[6] H. Cai, C. Gan, T. Wang, Z. Zhang, and S. Han. Once-for-All: Train one network and specialize it for efficient deployment. `https://github.com/mit-han-lab/once-for-all`, 2020.

[7] A. Cully and J.-B. Mouret. Evolving a behavioral repertoire for a walking robot. *Evolutionary Computation*, 24(1):59–88, 2016.

[8] T. Domhan, J. T. Springenberg, and F. Hutter. Speeding up automatic hyperparameter optimization of deep neural networks by extrapolation of learning curves. In *Proceedings of the 24th International Conference on Artificial Intelligence*, pages 3460–3468, 2015.

[9] S. Doncieux, N. Bredeche, L. L. Goff, B. Girard, A. Coninx, O. Sigaud, M. Khamassi, N. Díaz-Rodríguez, D. Filliat, T. Hospedales, A. Eiben, and R. Duro. Dream architecture: A developmental approach to open-ended learning in robotics. *arXiv:2005.06223 [cs.AI]*, 2020.

[10] J.-D. Dong, A.-C. Cheng, D.-C. Juan, W. Wei, and M. Sun. Dpp-net: Device-aware progressive search for pareto-optimal neural architectures. In *European Conference on Computer Vision*, 2018.

[11] X. Dong and Y. Yang. NAS-Bench-201: Extending the scope of reproducible neural architecture search. In *International Conference on Learning Representations*, 2020.

[12] T. Elsken, J. H. Metzen, and F. Hutter. Efficient multi-objective neural architecture search via Lamarckian evolution. In *Proceedings of the International Conference on Learning Representations*, 2019.

[13] T. Elsken, J. H. Metzen, and F. Hutter. Neural architecture search: A survey. *Journal of Machine Learning Research*, 20(55):1–21, 2019.

[14] S. Falkner, A. Klein, and F. Hutter. BOHB: Robust and efficient hyperparameter optimization at scale. In *Proceedings of the 35th International Conference on Machine Learning*, 2018.

[15] I. Fedorov, R. P. Adams, M. Mattina, and P. Whatmough. Sparse: Sparse architecture search for CNNs on resource-constrained microcontrollers. *Advances in Neural Information Processing Systems*, 32, 2019.

[16] M. C. Fontaine, R. Liu, J. Togelius, A. K. Hoover, and S. Nikolaidis. Illuminating mario scenes in the latent space of a generative adversarial network. In *AAAI Conference on Artificial Intelligence*, 2021.

[17] P. I. Frazier. A tutorial on Bayesian optimization. *arXiv:1807.02811 [stat.ML]*, 2018.

[18] A. Gaier, A. Asteroth, and J.-B. Mouret. Aerodynamic design exploration through surrogate-assisted illumination. In *18th AIAA/ISSMO Multidisciplinary Analysis and Optimization Conference*, 2017.

[19] J. Guerrero-Viu, S. Hauns, S. Izquierdo, G. Miotto, S. Schrodi, A. Biedenkapp, T. Elsken, D. Deng, M. Lindauer, and F. Hutter. Bag of baselines for multi-objective joint neural architecture search and hyperparameter optimization. In *8th ICML Workshop on Automated Machine Learning*, 2021.

[20] A. Howard, M. Sandler, G. Chu, L.-C. Chen, B. Chen, M. Tan, W. Wang, Y. Zhu, R. Pang, V. Vasudevan, Q. V. Le, and H. Adam. Searching for MobileNetV3. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1314–1324, 2019.

[21] F. Hutter, H. H. Hoos, and K. Leyton-Brown. Sequential model-based optimization for general algorithm configuration. In *International Conference on Learning and Intelligent Optimization*, pages 507–523, 2011.

[22] K. Jamieson and A. Talwalkar. Non-stochastic best arm identification and hyperparameter optimization. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2015.

[23] D. R. Jones, M. Schonlau, and W. J. Welch. Efficient global optimization of expensive black-box functions. *Journal of Global Optimization*, 13(4):455–492, 1998.

[24] K. Kandasamy, W. Neiswanger, J. Schneider, B. Poczos, and E. Xing. Neural architecture search with Bayesian optimisation and optimal transport. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, 2018.

[25] P. Kent and J. Branke. BOP-Elites, a Bayesian optimisation algorithm for quality-diversity search. *arXiv:2005.04320 [math.OC]*, 2020.

[26] A. Khosla, N. Jayadevaprakash, B. Yao, and L. Fei-Fei. Novel dataset for fine-grained image categorization. In *First Workshop on Fine-Grained Visual Categorization (FGVC), IEEE Conference on Computer Vision and Pattern Recognition*, 2011.

[27] A. Klein, S. Falkner, J. T. Springenberg, and F. Hutter. Learning curve prediction with Bayesian neural networks. In *International Conference on Learning Representations*, 2017.

[28] J. Knowles. ParEGO: A hybrid algorithm with on-line landscape approximation for expensive multiobjective optimization problems. *IEEE Transactions on Evolutionary Computation*, 10(1):50–66, 2006.

[29] J. Lehman and K. O. Stanley. Abandoning objectives: Evolution through the search for novelty alone. *Evolutionary Computation*, 19(2):189–223, 2011.

[30] J. Lehman and K. O. Stanley. Evolving a diversity of virtual creatures through novelty search and local competition. In *Proceedings of the 13th Annual Conference on Genetic and Evolutionary Computation*, pages 211–218, 2011.

[31] L. Li, K. Jamieson, G. DeSalvo, A. Rostamizadeh, and A. Talwalkar. Hyperband: Bandit-based configuration evaluation for hyperparameter optimization. In *International Conference on Learning Representations*, 2017.

[32] E. Liberis, Ł. Dudziak, and N. D. Lane. μnas: Constrained neural architecture search for microcontrollers. In *Proceedings of the 1st Workshop on Machine Learning and Systems*, pages 70–79, 2021.

[33] M. Lindauer, K. Eggensperger, M. Feurer, A. Biedenkapp, D. Deng, C. Benjamins, T. Ruhopf, R. Sass, and F. Hutter. SMAC3: A versatile Bayesian optimization package for hyperparameter optimization. *Journal of Machine Learning Research*, 23(54):1–9, 2022.

[34] H. Liu, K. Simonyan, O. Vinyals, C. Fernando, and K. Kavukcuoglu. Hierarchical representations for efficient architecture search. In *Proceedings of the International Conference on Learning Representations*, 2017.

[35] H. Liu, K. Simonyan, and Y. Yang. DARTS: Differentiable architecture search. In *Proceedings of the International Conference on Learning Representations*, 2019.

[36] Z. Lu, K. Deb, E. Goodman, W. Banzhaf, and V. N. Boddeti. NSGANetV2: Evolutionary multi-objective surrogate-assisted neural architecture search. In A. Vedaldi, H. Bischof, T. Brox, and J.-M. Frahm, editors, *European Conference on Computer Vision*, pages 35–51, 2020.

[37] Z. Lu, I. Whalen, V. Boddeti, Y. Dhebar, K. Deb, E. Goodman, and W. Banzhaf. NSGA-Net: A multi-objective genetic algorithm for neural architecture search. In *Proceedings of the Genetic and Evolutionary Computation Conference*, pages 419–427, 2019.

[38] B. Lyu, H. Yuan, L. Lu, and Y. Zhang. Resource-constrained neural architecture search on edge devices. *IEEE Transactions on Network Science and Engineering*, 9(1):134–142, 2021.

[39] H. Mendoza, A. Klein, M. Feurer, J. T. Springenberg, and F. Hutter. Towards automatically-tuned neural networks. In *ICML Workshop on Automatic Machine Learning*, 2016.

[40] Microsoft. Neural Network Intelligence. `https://github.com/microsoft/nni`, 2021.

[41] G. F. Miller, P. M. Todd, and S. U. Hegde. Designing neural networks using genetic algorithms. In *Proceedings of the Third International Conference on Genetic Algorithms*, pages 379–384, 1989.

[42] J.-B. Mouret and Jeff. Clune. Illuminating search spaces by mapping elites. *arXiv:1504.04909 [cs.AI]*, 2015.

[43] M. Pearce and J. Branke. Continuous multi-task Bayesian optimisation with correlation. *European Journal of Operational Research*, 270(3):1074–1085, 2018.

[44] D. Perez-Liebana, C. Guerrero-Romero, A. Dockhorn, D. Jeurissen, and L. Xu. Generating diverse and competitive play-styles for strategy games. In *2021 IEEE Conference on Games (CoG)*, pages 1–8, 2021.

[45] H. Pham, M. Guan, B. Zoph, Q. V. Le, and J. Dean. Efficient neural architecture search via parameter sharing. In *Proceedings of the 35th International Conference on Machine Learning*, pages 4095–4104, 2018.

[46] E. Real, A. Aggarwal, Y. Huang, and Q. V. Le. Regularized evolution for image classifier architecture search. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 4780–4789, 2019.

[47] E. Real, S. Moore, A. Selle, S. Saxena, Y. L. Suematsu, J. Tan, Q. V. Le, and A. Kurakin. Large-scale evolution of image classifiers. In *Proceedings of the 34th International Conference on Machine Learning*, pages 2902–2911, 2017.

[48] D. Salinas, V. Perrone, O. Cruchant, and C. Archambeau. A multi-objective perspective on jointly tuning hardware and hyperparameters. In *2nd Workshop on Neural Architecture Search at ICLR 2021*, 2021.

[49] R. Schmucker, M. Donini, V. Perrone, M. B. Zafar, and C. Archambeau. Multi-objective multi-fidelity hyperparameter optimization with application to fairness. In *NeurIPS Workshop on Meta-Learning*, 2020.

[50] R. Schmucker, M. Donini, M. B. Zafar, D. Salinas, and C. Archambeau. Multi-objective asynchronous successive halving. *arXiv:2106.12639 [stat.ML]*, 2021.

[51] L. Schneider, F. Pfisterer, M. Binder, and B. Bischl. Mutation is all you need. In *8th ICML Workshop on Automated Machine Learning*, 2021.

[52] L. Schneider, F. Pfisterer, J. Thomas, and B. Bischl. A collection of quality diversity optimization problems derived from hyperparameter optimization of machine learning models. *arXiv:2204.14061 [cs.LG]*, 2022.

[53] C. Schorn, T. Elsken, S. Vogel, A. Runge, A. Guntoro, and G. Ascheid. Automated design of error-resilient and hardware-efficient deep neural networks. *Neural Computing and Applications*, 32:18327–18345, 2020.

[54] J. Snoek, H. Larochelle, and R. P. Adams. Practical Bayesian optimization of machine learning algorithms. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 25, 2012.

[55] D. Stamoulis, R. Ding, D. Wang, D. Lymberopoulos, B. Priyantha, J. Liu, and D. Marculescu. Single-Path NAS: Designing hardware-efficient ConvNets in less than 4 hours. In U. Brefeld, E. Fromont, A. Hotho, A. Knobbe, M. Maathuis, and C. Robardet, editors, *Machine Learning and Knowledge Discovery in Databases*, pages 481–497, 2020.

[56] C. White, W. Neiswanger, S. Nolen, and Y. Savani. A study on encodings for neural architecture search. In *Advances in Neural Information Processing Systems*, 2020.

[57] C. White, W. Neiswanger, and Y. Savani. BANANAS: Bayesian optimization with neural architectures for neural architecture search. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

[58] C. White, S. Nolen, and Y. Savani. Exploring the loss landscape in neural architecture search. In *Uncertainty in Artificial Intelligence*, pages 654–664, 2021.

[59] C. White, A. Zela, B. Ru, Y. Liu, and F. Hutter. How powerful are performance predictors in neural architecture search? In *Proceedings of the 35th International Conference on Neural Information Processing Systems*, 2021.

[60] B. Wu, X. Dai, P. Zhang, Y. Wang, F. Sun, Y. Wu, Y. Tian, P. Vajda, Y. Jia, and K. Keutzer. Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10734–10742, 2019.

[61] C. Ying, A. Klein, E. Christiansen, E. Real, K. Murphy, and F. Hutter. NAS-Bench-101: Towards reproducible neural architecture search. In *Proceedings of the 36th International Conference on Machine Learning*, pages 7105–7114, 2019.

[62] Y. Zhou, S. Ebrahimi, S. Ö. Arık, H. Yu, H. Liu, and G. Diamos. Resource-efficient neural architect. *arXiv:1806.07912 [cs.NE]*, 2018.

[63] B. Zoph and Q. V. Le. Neural architecture search with reinforcement learning. In *Proceedings of the International Conference on Learning Representations*, 2017.

[64] B. Zoph, V. Vasudevan, J. Shlens, and Q. V. Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 8697–8710, 2018.